



RADIO TEST REPORT

Applicant	:	RAKOIT TECHNOLOGY(SZ) CO., LTD.
Address of Applicant	:	Floor 13th, Building 2 Block B, Baiwang R&D Building, Baimang Community, Xili Street, Nanshan District, Shenzhen, Guangdong Province 518000, P.R.China
Manufacturer	:	RAKOIT TECHNOLOGY(SZ) CO., LTD.
Address of Manufacturer	:	Floor 13th, Building 2 Block B, Baiwang R&D Building, Baimang Community, Xili Street, Nanshan District, Shenzhen, Guangdong Province 518000, P.R.China
Equipment under Test	:	Wireless Music Streamer
Model No.	:	LP20
FCC ID	:	2BCJV-LP20
IC	:	30908-LP20
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10-2020, RSS-247 Issue 4 July 24, 2025, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021), ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024
Report No.	:	DDT-RE25081404-3E01
Issue Date	:	2026/01/14
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information.....	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	9
2.3.	Block diagram of EUT configuration for test.....	9
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	10
2.6.	Test environment conditions	10
2.7.	Test laboratory	11
2.8.	Measurement uncertainty	11
3.	Equipment Used During Conductive Test	12
4.	20 dB Bandwidth	13
4.1.	Block diagram of test setup	13
4.2.	Limits	13
4.3.	Test procedure	13
4.4.	Test result.....	14
4.5.	Test graphs	15
5.	99% Bandwidth	18
5.1.	Block diagram of test setup	18
5.2.	Limits	18
5.3.	Test procedure	18
5.4.	Test result.....	19
5.5.	Test graphs	20
6.	Maximum Peak Output Power.....	23
6.1.	Block diagram of test setup	23
6.2.	Limits	23
6.3.	Test procedure	23
6.4.	Test result.....	24
6.5.	Test graphs	25
7.	Carrier Frequency Separation	28
7.1.	Block diagram of test setup	28
7.2.	Limits	28
7.3.	Test procedure	28
7.4.	Test result.....	29
7.5.	Test graphs	30
8.	Dwell Time.....	31

8.1.	Block diagram of test setup	31
8.2.	Limits	31
8.3.	Test procedure	31
8.4.	Test result.....	32
8.5.	Test graphs	33
9.	Number of Hopping Channel.....	39
9.1.	Block diagram of test setup	39
9.2.	Limits	39
9.3.	Test procedure	39
9.4.	Test result.....	40
9.5.	Test graphs	41
10.	Band Edge Compliance (Conducted Method).....	42
10.1.	Block diagram of test setup	42
10.2.	Limit.....	42
10.3.	Test procedure	42
10.4.	Test result.....	43
10.5.	Test graphs	44
11.	RF Conducted Spurious Emissions.....	48
11.1.	Block diagram of test setup	48
11.2.	Limits	48
11.3.	Test procedure	48
11.4.	Test result.....	48
11.5.	Test graphs	50
12.	Duty cycle.....	59
12.1.	Block diagram of test setup	59
12.2.	Limit.....	59
12.3.	Test procedure	59
12.4.	Test result.....	60
12.5.	Test graphs	61
13.	Antenna Requirements.....	64
13.1.	Limit.....	64
13.2.	Result	64
14.	Radiated Emission	65
14.1.	Test equipment.....	65
14.2.	Block diagram of test setup	66
14.3.	Limits	67
14.4.	Assistant equipment used for test	69
14.5.	Test procedure	69

14.6.	Test result.....	70
14.7.	Test data	71
15.	Band Edge Compliance.....	79
15.1.	Test equipment.....	79
15.2.	Block diagram of test setup	80
15.3.	Limits	80
15.4.	Assistant equipment used for test	80
15.5.	Test procedure	80
15.6.	Test result.....	80
15.7.	Test data	81
16.	Power Line Conducted Emissions.....	93
16.1.	Test equipment.....	93
16.2.	Block diagram of test setup	93
16.3.	Limits	93
16.4.	Assistant equipment used for test	93
16.5.	Test procedure	93
16.6.	Test result.....	94
16.7.	Test data	95
17.	Test Setup Photograph	97
18.	Photos of the EUT	99

Test Report Declare

Applicant	:	RAKOIT TECHNOLOGY(SZ) CO., LTD.
Address of Applicant	:	Floor 13th, Building 2 Block B, Baiwang R&D Building, Baimang Community, Xili Street, Nanshan District, Shenzhen, Guangdong Province 518000, P.R.China
Equipment under Test	:	Wireless Music Streamer
Model No.	:	LP20
Manufacturer	:	RAKOIT TECHNOLOGY(SZ) CO., LTD.
Address of Manufacturer	:	Floor 13th, Building 2 Block B, Baiwang R&D Building, Baimang Community, Xili Street, Nanshan District, Shenzhen, Guangdong Province 518000, P.R.China

Test Standard Used:
FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10-2020,
RSS-247 Issue 4 July 24, 2025,
RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021),
ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024

We Declare:
The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE25081404-3E01		
Date of Receipt:	2025/11/11	Date of Test:	2025/08/26 - 2026/01/05

Created: Johnson Huang	Reviewed: Tiger Mo	Approved: Damon Hu
		
2026/01/05	2026/01/14	2026/01/14

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2026/01/14	Damon Hu

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	Maximum Peak Output Power	47 CFR Part 15 15.247(b)(1), RSS-247 clause 6.2.3.2(a)	/	Pass
2	20 dB Bandwidth	47 CFR Part 15 15.247(a)(1), RSS-247 clause 6.2.3.1(a)	/	Pass
3	99% Bandwidth	RSS-Gen clause 6.7	/	Pass
4	Carrier Frequency Separation	47 CFR Part 15 15.247(a)(1), RSS-247 clause 6.2.3.1(a)	/	Pass
5	Number of Hopping Channel	47 CFR Part 15 15.247(a)(1)(iii), RSS-247 clause 6.2.3.1(b)	/	Pass
6	Dwell Time	47 CFR Part 15 15.247(a)(1)(iii), RSS-247 clause 6.2.3.1(b)	/	Pass
7	RF Conducted Spurious Emissions	47 CFR Part 15 15.247(d), RSS-247 clause 6.6	/	Pass
8	Radiated Emission	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
9	Band Edge Compliance	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
10	Antenna Requirement	47 CFR Part 15 15.203, RSS-Gen clause 6.8	/	Pass
11	Power Line Conducted Emissions	47 CFR Part 15 15.207(a), RSS-Gen clause 8.8	/	Pass
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	: Wireless Music Streamer
Model Number	: LP20
Difference of model number	: /
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 5V/2A powered by an external AC adapter
Antenna Type	: FPC
Max Antenna Gain(dBi)	: -3.5dBi

Radio Specification	: Bluetooth BR/EDR
Operation Frequency	: 2402 MHz to 2480 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK

Bluetooth BR/EDR Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477

22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454	/	
26	2428	53	2455	/	


Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☒” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: SecureCRT

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5 dB (According to the manufacturer's claims)

Tested mode, Tx Power Setting, Channel, and Frequency			
Tested mode	Tx Power Setting	Channel	Frequency (MHz)
GFSK hopping on Tx mode	Default	CH0 to CH78	2402 to 2480
$\pi/4$ -DQPSK hopping on Tx mode	Default	CH0 to CH78	2402 to 2480
8DPSK hopping on Tx mode	Default	CH0 to CH78	2402 to 2480
GFSK hopping off Tx mode	Default	CH0	2402
	Default	CH39	2441
	Default	CH78	2480
$\pi/4$ -DQPSK hopping off Tx mode	Default	CH0	2402
	Default	CH39	2441
	Default	CH78	2480
8DPSK hopping off Tx mode	Default	CH0	2402
	Default	CH39	2441
	Default	CH78	2480
Note: According exploratory test, EUT will have maximum output power in those data rate, worst-case data rates were: GFSK mode: DH5, $\pi/4$ -DQPSK mode: 2DH5, 8DPSK mode: 3DH5			

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to 106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.9%
Peak Output Power (Conducted) (Spectrum analyzer)	0.98 dB
Peak Output Power (Conducted) (Power Sensor)	1.18 dB
Power Spectral Density (Base EIRP)	1.51 dB
Power Spectral Density (Spectrum analyzer)	0.98 dB
Frequencies Stability	1.9 kHz
Conducted spurious emissions	1.21 dB ($9 \text{ kHz} \leq f < 7 \text{ GHz}$);
	3.31 dB ($7 \text{ GHz} \leq f < 40 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	5.5×10^{-8}
Time	0.11%
Temperature	0.3 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.28 dB (Antenna Polarize: V)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.14 dB (Antenna Polarize: H)
	4.22 dB (1 - 6 GHz)
	4.52 dB (6 GHz - 18 GHz)
Uncertainty for Power line conduction emission test	4.58 dB (18 GHz - 40 GHz)
	3.32dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☑RF Connected Test (RF Measurement System 4#)				
Signal &Spectrum Analyzer	R&S	FSV3044	101173	2026/03/28
Wideband Radio Communication Tester	R&S	CMW500	168801	2026/03/28
MXG Vector Signal Generator	Agilent	N5182A	MY48180737	2026/03/28
PSG Vector Signal Generator	Agilent	E8267D	US49060192	2026/08/10
RF Control Unit	Tonscend	JS0806-2	21I8060485	2026/03/28
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2026/03/28
Test Software	Tonscend	JS1120-3	V3.6.21	N/A

4. 20 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.3. Test procedure

- (1) The test according to ANSI C63.10 clause 6.9.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 20 dB bandwidth measurement:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 2 times and 5 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold

- (5) Measure and record the results in the report.


4.4. Test result


Test Engineer:	Tyang	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6℃,49.8%RH	Test Date:	2025.12.6-2025.12.31
Test Power Supply:	AC 120V/60Hz	Sample Number:	S25081404-004

Test Mode	Antenna	Frequency [MHz]	20dB EBW[MHz]
DH5	Ant1	2402	0.96
		2441	0.98
		2480	0.99
2DH5	Ant1	2402	1.34
		2441	1.35
		2480	1.35
3DH5	Ant1	2402	1.31
		2441	1.30
		2480	1.33

4.5. Test graphs








3DH5_Ant1_2441



3DH5_Ant1_2480



5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% bandwidth measurement:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Measure and record the results in the report.


5.4. Test result

Test Engineer:	Tyang	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6℃,49.8%RH	Test Date:	2025.12.6-2025.12.31
Test Power Supply:	AC 120V/60Hz	Sample Number:	S25081404-004


Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL[MHz]	FH[MHz]
DH5	Ant1	2402	0.87429	2401.5735	2402.4478
		2441	0.87412	2440.5718	2441.4459
		2480	0.87053	2479.5780	2480.4486
2DH5	Ant1	2402	1.1951	2401.4146	2402.6097
		2441	1.1927	2440.4167	2441.6094
		2480	1.1981	2479.4148	2480.6129
3DH5	Ant1	2402	1.1932	2401.4153	2402.6085
		2441	1.1910	2440.4176	2441.6085
		2480	1.1824	2479.4196	2480.6020

5.5. Test graphs







2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441




3DH5_Ant1_2480



6. Maximum Peak Output Power

6.1. Block diagram of test setup



6.2. Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

6.3. Test procedure

- (1) The test according to ANSI C63.10 clause 7.8.5.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	> 20 dB bandwidth of the emission being measured.
VBW:	VBW $\geq$ RBW.
Span:	Approximately five times the 20 dB bandwidth, centered on a hopping channel.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Use the marker-to-peak function to set the marker to the peak of the emission and record the results in the report.


6.4. Test result

Test Engineer:	Tyang	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6℃,49.8%RH	Test Date:	2025.12.6-2025.12.31
Test Power Supply:	AC 120V/60Hz	Sample Number:	S25081404-004


Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
DH5	Ant1	2402	7.29	≤20.97	3.79	≤36	PASS
		2441	7.05	≤20.97	3.55	≤36	PASS
		2480	6.96	≤20.97	3.46	≤36	PASS
2DH5	Ant1	2402	7.96	≤20.97	4.46	≤36	PASS
		2441	7.93	≤20.97	4.43	≤36	PASS
		2480	7.61	≤20.97	4.11	≤36	PASS
3DH5	Ant1	2402	8.54	≤20.97	5.04	≤36	PASS
		2441	8.28	≤20.97	4.78	≤36	PASS
		2480	8.21	≤20.97	4.71	≤36	PASS

6.5. Test graphs







2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441




3DH5_Ant1_2480



7. Carrier Frequency Separation

7.1. Block diagram of test setup



7.2. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

7.3. Test procedure

- (1) The test according to ANSI C63.10 clause 7.8.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	approximately 30% of the channel spacing
VBW:	$VBW \geq RBW$.
Span:	Wide enough to capture the peaks of two adjacent channels.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Use the marker-delta function to determine the separation between the peaks of the adjacent channels and record the results in the report.

7.4. Test result

Test Engineer:	Tyang	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6℃,49.8%RH	Test Date:	2025.12.6-2025.12.31
Test Power Supply:	AC 120V/60Hz	Sample Number:	S25081404-004


Test Mode	Antenna	Frequency [MHz]	Result [MHz]	Limit [MHz]	Verdict
DH5	Ant1	Hop	0.994	≥0.990	PASS
2DH5	Ant1	Hop	1.01	≥0.900	PASS
3DH5	Ant1	Hop	1.01	≥0.887	PASS

7.5. Test graphs



8. Dwell Time

8.1. Block diagram of test setup



8.2. Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

8.3. Test procedure

- (1) The test according to ANSI C63.10 clause 7.8.4.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	≤ channel spacing and where possible RBW should be set $\gg 1 / T$
VBW:	$VBW \geq RBW$.
Span:	Zero span, centered on a hopping channel.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Clear Write.
- (5) The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
- (6) Measure the hopping number and on time of each pulse with spectrum analyzer in zero span set, and calculate dwell time with formula Dwell time = total hops * pulse's on time.
- (7) Measure and record the results in the report.


8.4. Test result

Test Engineer:	Tyang	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6℃,49.8%RH	Test Date:	2025.12.6-2025.12.31
Test Power Supply:	AC 120V/60Hz	Sample Number:	S25081404-004



Test Mode	Antenna	Frequency [MHz]	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.380	319	0.121	≤0.4	PASS
DH3	Ant1	Hop	1.640	151	0.248	≤0.4	PASS
DH5	Ant1	Hop	2.880	112	0.323	≤0.4	PASS
2DH1	Ant1	Hop	0.370	319	0.118	≤0.4	PASS
2DH3	Ant1	Hop	1.620	152	0.246	≤0.4	PASS
2DH5	Ant1	Hop	2.880	110	0.317	≤0.4	PASS
3DH1	Ant1	Hop	0.370	320	0.118	≤0.4	PASS
3DH3	Ant1	Hop	1.620	164	0.266	≤0.4	PASS
3DH5	Ant1	Hop	2.870	109	0.313	≤0.4	PASS

8.5. Test graphs







DH5_Ant1_Hop





2DH1_Ant1_Hop







2DH5_Ant1_Hop




3DH1_Ant1_Hop





9. Number of Hopping Channel

9.1. Block diagram of test setup



9.2. Limits

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

9.3. Test procedure

- (1) The test according to ANSI C63.10 clause 7.8.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW:	VBW $\geq$ RBW.
Span:	The frequency band of operation
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Measure the hopping number and record the results in the report.
- (6) Measure and record the results in the report.

9.4. Test result

Test Engineer:	Tyang	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6℃,49.8%RH	Test Date:	2025.12.6-2025.12.31
Test Power Supply:	AC 120V/60Hz	Sample Number:	S25081404-004


Test Mode	Antenna	Frequency [MHz]	Result [Num]	Limit [Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS
3DH5	Ant1	Hop	79	≥15	PASS

9.5. Test graphs



10. Band Edge Compliance (Conducted Method)

10.1. Block diagram of test setup



10.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

10.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:


RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.


10.4. Test result

Test Engineer:	Tyang	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6℃,49.8%RH	Test Date:	2025.12.6-2025.12.31
Test Power Supply:	AC 120V/60Hz	Sample Number:	S25081404-004


Mode	Freq. (MHz)	Verdict
GFSK	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass
$\pi/4$ -DQPSK	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass
8DPSK	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass

10.5. Test graphs







2DH5_Ant1_Low_2402




2DH5_Ant1_High_2480




2DH5_Ant1_Low_Hop_2402




2DH5_Ant1_High_Hop_2480




3DH5_Ant1_Low_2402




3DH5_Ant1_High_2480



3DH5_Ant1_Low_Hop_2402




3DH5_Ant1_High_Hop_2480



11. RF Conducted Spurious Emissions

11.1. Block diagram of test setup



11.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

11.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

Center frequency

Test frequency

RBW:

100 kHz

VBW:

300 kHz

Span

Wide enough to capture the peak level of the in-band emission

Detector Mode:

Peak

Sweep time:

Auto

Trace mode

Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Set the spectrum analyzer as follows:

RBW:

100 kHz

VBW:

300 kHz

Span

Encompass frequency range to be measured

Number of measurement points

≥Span/RBW

Detector Mode:

Peak

Sweep time:

Auto

Trace mode

Max hold

Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

11.4. Test result

Test Engineer:	Tyang	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6℃,49.8%RH	Test Date:	2025.12.6-2025.12.31
Test Power	AC 120V/60Hz	Sample Number:	S25081404-004