



FCC TEST REPORT

FCC ID:2BCK8-C312

Applicant: Shenzhen Hongkang Shengda Technology Co., LTD
Address: 303, Building A, No.7, Lanqing 1st Road, Luhua Community, Guanhu Street, Longhua District, Shenzhen, Guangdong Province China

Manufacturer: Shenzhen Hongkang Shengda Technology Co., LTD
Address: 303, Building A, No.7, Lanqing 1st Road, Luhua Community, Guanhu Street, Longhua District, Shenzhen, Guangdong Province China

EUT: CAR DVR DASH CAM

Trade Mark: N/A

Model Number: C312

Date of Receipt: Apr. 22, 2025

Test Date: Apr. 22, 2025 to Apr. 29, 2025

Date of Report: Apr. 29, 2025

Prepared By: Shenzhen DL Testing Technology Co., Ltd.
Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China

Applicable Standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013

Test Result: Pass

Report Number: DLE-250506007R

Prepared (Test Engineer): Dimon Tan

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents

	Page
1. VERSION	4
2. SUMMARY OF TEST RESULTS	5
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
4. EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 TEST RESULT	14
4.2 RADIATED EMISSION MEASUREMENT	16
4.2.1 RADIATED EMISSION LIMITS	16
4.2.2 TEST PROCEDURE	16
4.2.3 DEVIATION FROM TEST STANDARD	17
4.2.4 TEST SETUP	17
4.2.5 EUT OPERATING CONDITIONS	18
4.2.6 TEST RESULTS	18
5. RADIATED BAND EMISSIONMEASUREMENT	29
5.1 TEST REQUIREMENT	29
5.2 TEST PROCEDURE	29
5.3 DEVIATION FROM TEST STANDARD	29
5.4 TEST SETUP	30
5.5 EUT OPERATING CONDITIONS	30
5.6 TEST RESULT	31
6.1 APPLIED PROCEDURES / LIMIT	33
6.2 TEST PROCEDURE	33
6.3 DEVIATION FROM STANDARD	33
6.4 TEST SETUP	33
6.5 EUT OPERATION CONDITIONS	33
6.6 TEST RESULT	34



7. 6DB OCCUPIED BANDWIDTH	39
7.1 APPLIED PROCEDURES / LIMIT	39
7.2 TEST PROCEDURE	39
7.3 DEVIATION FROM STANDARD	39
7.4 TEST SETUP	39
7.5 EUT OPERATION CONDITIONS	39
7.6 TEST RESULT	40
8. PEAK OUTPUT POWER TEST	45
8.1 APPLIED PROCEDURES/LIMIT	45
8.2 TEST PROCEDURE	45
8.3 DEVIATION FROM STANDARD	45
8.4 TEST SETUP	45
8.5 EUT OPERATION CONDITIONS	45
8.6 TEST RESULT	46
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	47
9.1 APPLICABLE STANDARD	47
9.2 TEST PROCEDURE	47
9.3 DEVIATION FROM STANDARD	47
9.4 TEST SETUP	47
9.5 EUT OPERATION CONDITIONS	47
9.6 TEST RESULTS	47
10. DUTY CYCLE	56
10.1 APPLIED PROCEDURES / LIMIT	56
10.2 DEVIATION FROM STANDARD	56
10.3 TEST SETUP	56
10.4 EUT OPERATION CONDITIONS	56
10.5 TEST RESULTS	57
11. ANTENNA REQUIREMENT	60
12. TEST SETUP PHOTO	61
13. EUT CONSTRUCTIONAL DETAILS	61



1. VERSION

Report No.	Version	Description	Approved
DLE-250506007R	Rev.01	Initial issue of report	Apr. 29, 2025



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (c)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	6dB Occupied Bandwidth	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	
ANSI C63.10:2013	Duty cycle	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Shenzhen DL Testing Technology Co., Ltd.

Add. : 101-201, Building C, Shuanghuan, No.8, Baoqing Roa Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB identifier: CN0118

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	3m camber Radiated spurious emission(9KHz-30MHz)	U=4.5dB
2	3m camber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	U=4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	U=5.0dB
5	Conducted disturbance	U=3.2dB
6	RF Band Edge	U=1.68dB
7	RF power conducted	U=1.86dB
8	RF conducted Spurious Emission	U=2.2dB
9	RF Occupied Bandwidth	U=1.8MHz
10	RF Power Spectral Density	U=1.75dB
11	humidity uncertainty	U=5.3%
12	Temperature uncertainty	U=0.59°C



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	CAR DVR DASH CAM
Model No.:	C312
Serial No.:	N/A
Model Different.:	N/A
Hardware Version:	V1.0
Software Version:	V1.1
Sample(s) Status:	Engineer sample
Frequency Range:	2412-2462MHz for 802.11 b/g/n20 2422-2452MHz for 802.11 n40
Channel Numbers:	802.11b/g/n (20M): 11 Channels 802.11n (40M): 7 Channels
Channel Separation:	5MHz
Modulation Technology:	802.11b: Direct Sequence Spread Spectrum(DSSS) 802.11g/n: Orthogonal Frequency Division Multiplexing(OFDM)
Data Rate:	802.11b: 1/2/5.5/11Mbit/s 802.11g: 6/9/12/24/18/36/48/54Mbit/s 802.11n: MCS0-MCS7
Antenna Type:	PCB Antenna
Antenna Gain:	2.58dBi
Power Supply:	Input: 5V $\overline{\text{---}}$ 1A
Battery:	DC 3.7V, 150mAh, 0.555Wh



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/g/n (20M)	802.11n (40M)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data. For battery operated equipment, the equipment tests shall be performed using a new battery.	


We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:				
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.				
Mode	802.11b	802.11g	802.11n20	802.11n40
Data rate	1Mbps	6Mbps	MCS0(HT0)	MCS0(HT0)

Test Software	REALTEK
Power level setup	Default



3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


Conducted Emission



Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	CAR DVR DASH CAM	N/A	C312	N/A	EUT
E-2	AC/DC Adapter	N/A	HW-200200CP1	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conduction Emissions Test

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	N/A	Sep. 30, 2024	Sep. 29, 2025
2	LISN	CYBERTEK	EM5040A	E1850400149	N/A	Sep. 30, 2024	Sep. 29, 2025
3	Test Cable	N/A	C-01	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
4	EMI Test Receiver	R&S	ESCI3	101393	4.42 SP3	Sep. 29, 2024	Sep. 28, 2025
5	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	N/A	\	\

Radiation Emissions & Radiation Spurious Emissions Test

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	N9020A	MY55370835	A.17.05	Sep. 29, 2024	Sep. 28, 2025
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Sep. 30, 2024	Sep. 29, 2025
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	100969	4.32	Sep. 29, 2024	Sep. 28, 2025
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	00877	N/A	Sep. 30, 2024	Sep. 29, 2025
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	N/A	Sep. 30, 2024	Sep. 29, 2025
6	Horn Antenna (15GHz-40GHz)	A.H.System	SAS-574	588	N/A	Sep. 30, 2024	Sep. 29, 2025
7	Loop Antenna	TESEQ	HLA6121	58357	N/A	Oct. 11, 2024	Oct. 10, 2025
8	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	60747	N/A	Sep. 29, 2024	Sep. 28, 2025
9	Amplifier (1GHz-26.5GHz)	HuiPu	8449B	3008A00315	N/A	Sep. 29, 2024	Sep. 28, 2025
10	Amplifier (500MHz-40GHz)	QuanJuDa	DLE-161	097	N/A	Sep. 30, 2024	Sep. 29, 2025
11	Test Cable	N/A	R-01	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
12	Test Cable	N/A	R-02	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
13	Test Cable	N/A	R-03	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
14	D.C. Power Supply	LongWei	TPR-6405D	GQ7516	N/A	Sep. 29, 2024	Sep. 28, 2025
15	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	N/A	\	\
16	Turntable	MF	MF-7802BS	N/A	N/A	\	\
17	Antenna tower	MF	MF-7802BS	N/A	N/A	\	\



RF Conducted Test

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	N9020A	MY55370835	A.17.05	Sep. 29, 2024	Sep. 28, 2025
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Sep. 30, 2024	Sep. 29, 2025
3	Test Cable	N/A	RF-01	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
4	Test Cable	N/A	RF-02	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
5	Test Cable	N/A	RF-03	N/A	N/A	Sep. 30, 2024	Sep. 29, 2025
6	ESG Signal Generator	Agilent	E4421B	GB40051203	B.03.84	Sep. 29, 2024	Sep. 28, 2025
7	Signal Generator	Agilent	N5182A	MY47420215	A.01.87	Sep. 29, 2024	Sep. 28, 2025
8	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	N/A	Sep. 29, 2024	Sep. 28, 2025
9	Van der Hoofden measuring head	Schwarzbeck Mess-elektronik	VDHH 9502	9502-039	N/A	Sep. 30, 2024	Sep. 29, 2025
10	Wideband Radio Communication Test	R&S	CMW500	106504	V 3.7.22	Sep. 30, 2024	Sep. 29, 2025
11	MWRF Power Meter Test system	MW	MW100-RF CB	10371	N/A	Sep. 29, 2024	Sep. 28, 2025
12	Power Meter	KEYSIGHT	N1912AP	926431	A.05.00	Sep. 29, 2024	Sep. 28, 2025
13	D.C. Power Supply	LongWei	TPR-6405D	GQ7516	N/A	Sep. 29, 2024	Sep. 28, 2025
14	RF Software	MW	MTS8310	V2.0.0.0	N/A	\	\



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS

FREQUENCY (MHz)	Limit (dBUV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation



4.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 TEST RESULT

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	L
Test Voltage:	AC 120V/60Hz	Test Mode:	TX 802.11n20 - 2412MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2310	20.01	20.37	40.38	62.41	-22.03	QP	P	
2	0.2310	10.27	20.37	30.64	52.41	-21.77	AVG	P	
3	0.4740	25.75	20.31	46.06	56.44	-10.38	QP	P	
4	0.4740	14.05	20.31	34.36	46.44	-12.08	AVG	P	
5	1.7159	5.53	20.30	25.83	46.00	-20.17	AVG	P	
6	1.7249	20.00	20.30	40.30	56.00	-15.70	QP	P	
7	3.5880	16.91	20.34	37.25	56.00	-18.75	QP	P	
8	3.6195	3.95	20.34	24.29	46.00	-21.71	AVG	P	
9	15.5040	17.27	20.49	37.76	60.00	-22.24	QP	P	
10	15.5040	3.07	20.49	23.56	50.00	-26.44	AVG	P	
11	23.8560	20.11	20.60	40.71	60.00	-19.29	QP	P	
12	24.3330	7.57	20.62	28.19	50.00	-21.81	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi - Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Reading level + Correct Factor.
4. Correct Factor = Loss factor + Cable loss factor + limiter factor.
5. Margin = Measurement Level - Limit.
6. The test data shows only the worst case TX 802.11n20 - 2412MHz.



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	N
Test Voltage:	AC 120V/60Hz	Test Mode:	TX 802.11n20 - 2412MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1725	21.92	20.26	42.18	64.84	-22.66	QP	P	
2	0.1730	5.27	20.26	25.53	54.82	-29.29	AVG	P	
3	0.4711	16.29	20.31	36.60	46.49	-9.89	AVG	P	
4	0.4785	25.40	20.31	45.71	56.37	-10.66	QP	P	
5	1.6979	7.16	20.30	27.46	46.00	-18.54	AVG	P	
6	1.7294	20.30	20.30	40.60	56.00	-15.40	QP	P	
7	4.1190	17.33	20.34	37.67	56.00	-18.33	QP	P	
8	4.1685	2.50	20.34	22.84	46.00	-23.16	AVG	P	
9	7.1520	3.66	20.40	24.06	50.00	-25.94	AVG	P	
10	7.2150	15.38	20.40	35.78	60.00	-24.22	QP	P	
11	23.5049	18.92	20.62	39.54	60.00	-20.46	QP	P	
12	23.7119	4.60	20.63	25.23	50.00	-24.77	AVG	P	

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi - Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Final Level = Reading level + Correct Factor.
- 4.Correct Factor = Lisn factor+ Cable loss factor + limiter factor.
- 5.Margin = Measurement Level-Limit.
- 6.The test data shows only the worst case TX 802.11n20 - 2412MHz.



4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	9kHz to 25GHz					
Test site:	Measurement Distance: 3m					
Receiver setup:	Frequency	Detector	RBW	VBW	Value	
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak	
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak	
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak	
	Above 1GHz	Peak	1MHz	3MHz	Peak	
		Peak	1MHz	10Hz	Average	

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.



- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS


Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.



Between 30MHz – 1GHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 3.7V	Test Mode :	TX 802.11n20 - 2412MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.6374	30.36	-14.21	16.15	40.00	-23.85	QP
2	85.2980	47.65	-19.73	27.92	40.00	-12.08	QP
3	185.7880	48.76	-17.85	30.91	43.50	-12.59	QP
4	252.0627	52.14	-15.48	36.66	46.00	-9.34	QP
5	755.3872	31.62	-6.56	25.06	46.00	-20.94	QP
6	1000.0000	29.81	-4.56	25.25	54.00	-28.75	QP

Remarks:

- 1.An initial pre-scan was performed on the peak detector.
- 2.Quasi - Peak measurement were performed at the frequencies with maximized peak emission.
- 3.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 4.Final Level = Reading level + Correct Factor.
- 5.Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
- 6.Margin = Measurement Level-Limit.
- 7.The test data shows only the worst case TX 802.11n20 - 2412MHz.



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 3.7V	Test Mode :	TX 802.11n20 - 2412MHz

**Remarks:**

1. An initial pre-scan was performed on the peak detector.
2. Quasi - Peak measurement were performed at the frequencies with maximized peak emission.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Final Level = Reading level + Correct Factor.
5. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
6. Margin = Measurement Level-Limit.
7. The test data shows only the worst case TX 802.11n20 - 2412MHz.



1GHz~25GHz

802.11b

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	50.39	30.55	5.77	24.66	50.27	74.00	-23.73	PK
V	4824.00	43.90	30.55	5.77	24.66	43.78	54.00	-10.22	AV
V	7236.00	54.66	30.33	6.32	24.55	55.20	74.00	-18.80	PK
V	7236.00	43.76	30.33	6.32	24.55	44.30	54.00	-9.70	AV
V	9648.00	51.98	30.85	7.45	24.69	53.27	74.00	-20.73	PK
V	9648.00	43.68	30.85	7.45	24.69	44.97	54.00	-9.03	AV
V	12060.00	53.48	31.02	8.99	25.57	57.02	74.00	-16.98	PK
V	12060.00	43.27	31.02	8.99	25.57	46.81	54.00	-7.19	AV
H	4824.00	54.99	30.55	5.77	24.66	54.87	74.00	-19.13	PK
H	4824.00	43.26	30.55	5.77	24.66	43.14	54.00	-10.86	AV
H	7236.00	50.79	30.33	6.32	24.55	51.33	74.00	-22.67	PK
H	7236.00	43.40	30.33	6.32	24.55	43.94	54.00	-10.06	AV
H	9648.00	54.11	30.85	7.45	24.69	55.40	74.00	-18.60	PK
H	9648.00	43.04	30.85	7.45	24.69	44.33	54.00	-9.67	AV
H	12060.00	51.15	31.02	8.99	25.57	54.69	74.00	-19.31	PK
H	12060.00	43.62	31.02	8.99	25.57	47.16	54.00	-6.84	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	52.06	30.55	5.77	24.66	51.94	74.00	-22.06	PK
V	4874.00	43.14	30.55	5.77	24.66	43.02	54.00	-10.98	AV
V	7311.00	53.77	30.33	6.32	24.55	54.31	74.00	-19.69	PK
V	7311.00	43.10	30.33	6.32	24.55	43.64	54.00	-10.36	AV
V	9748.00	53.82	30.85	7.45	24.69	55.11	74.00	-18.89	PK
V	9748.00	43.14	30.85	7.45	24.69	44.43	54.00	-9.57	AV
V	12185.00	50.63	31.02	8.99	25.57	54.17	74.00	-19.83	PK
V	12185.00	43.89	31.02	8.99	25.57	47.43	54.00	-6.57	AV
H	4874.00	51.00	30.55	5.77	24.66	50.88	74.00	-23.12	PK
H	4874.00	43.74	30.55	5.77	24.66	43.62	54.00	-10.38	AV
H	7311.00	54.43	30.33	6.32	24.55	54.97	74.00	-19.03	PK
H	7311.00	43.17	30.33	6.32	24.55	43.71	54.00	-10.29	AV
H	9748.00	50.33	30.85	7.45	24.69	51.62	74.00	-22.38	PK
H	9748.00	43.23	30.85	7.45	24.69	44.52	54.00	-9.48	AV
H	12185.00	53.70	31.02	8.99	25.57	57.24	74.00	-16.76	PK
H	12185.00	43.08	31.02	8.99	25.57	46.62	54.00	-7.38	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924.00	51.35	30.55	5.77	24.66	51.23	74.00	-22.77	PK
V	4924.00	43.05	30.55	5.77	24.66	42.93	54.00	-11.07	AV
V	7386.00	54.20	30.33	6.32	24.55	54.74	74.00	-19.26	PK
V	7386.00	43.20	30.33	6.32	24.55	43.74	54.00	-10.26	AV
V	9848.00	52.54	30.85	7.45	24.69	53.83	74.00	-20.17	PK
V	9848.00	43.19	30.85	7.45	24.69	44.48	54.00	-9.52	AV
V	12310.00	53.71	31.02	8.99	25.57	57.25	74.00	-16.75	PK
V	12310.00	43.97	31.02	8.99	25.57	47.51	54.00	-6.49	AV
H	4924.00	54.49	30.55	5.77	24.66	54.37	74.00	-19.63	PK
H	4924.00	43.66	30.55	5.77	24.66	43.54	54.00	-10.46	AV
H	7386.00	54.72	30.33	6.32	24.55	55.26	74.00	-18.74	PK
H	7386.00	43.36	30.33	6.32	24.55	43.90	54.00	-10.10	AV
H	9848.00	53.49	30.85	7.45	24.69	54.78	74.00	-19.22	PK
H	9848.00	43.40	30.85	7.45	24.69	44.69	54.00	-9.31	AV
H	12310.00	51.19	31.02	8.99	25.57	54.73	74.00	-19.27	PK
H	12310.00	43.92	31.02	8.99	25.57	47.46	54.00	-6.54	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11g

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	52.28	30.55	5.77	24.66	52.16	74.00	-21.84	PK
V	4824.00	43.44	30.55	5.77	24.66	43.32	54.00	-10.68	AV
V	7236.00	52.49	30.33	6.32	24.55	53.03	74.00	-20.97	PK
V	7236.00	43.25	30.33	6.32	24.55	43.79	54.00	-10.21	AV
V	9648.00	51.25	30.85	7.45	24.69	52.54	74.00	-21.46	PK
V	9648.00	43.01	30.85	7.45	24.69	44.30	54.00	-9.70	AV
V	12060.00	53.32	31.02	8.99	25.57	56.86	74.00	-17.14	PK
V	12060.00	43.06	31.02	8.99	25.57	46.60	54.00	-7.40	AV
H	4824.00	53.53	30.55	5.77	24.66	53.41	74.00	-20.59	PK
H	4824.00	43.37	30.55	5.77	24.66	43.25	54.00	-10.75	AV
H	7236.00	50.53	30.33	6.32	24.55	51.07	74.00	-22.93	PK
H	7236.00	43.70	30.33	6.32	24.55	44.24	54.00	-9.76	AV
H	9648.00	54.41	30.85	7.45	24.69	55.70	74.00	-18.30	PK
H	9648.00	43.27	30.85	7.45	24.69	44.56	54.00	-9.44	AV
H	12060.00	52.32	31.02	8.99	25.57	55.86	74.00	-18.14	PK
H	12060.00	43.44	31.02	8.99	25.57	46.98	54.00	-7.02	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	52.39	30.55	5.77	24.66	52.27	74.00	-21.73	PK
V	4874.00	43.74	30.55	5.77	24.66	43.62	54.00	-10.38	AV
V	7311.00	51.96	30.33	6.32	24.55	52.50	74.00	-21.50	PK
V	7311.00	43.53	30.33	6.32	24.55	44.07	54.00	-9.93	AV
V	9748.00	53.32	30.85	7.45	24.69	54.61	74.00	-19.39	PK
V	9748.00	43.15	30.85	7.45	24.69	44.44	54.00	-9.56	AV
V	12185.00	53.04	31.02	8.99	25.57	56.58	74.00	-17.42	PK
V	12185.00	43.16	31.02	8.99	25.57	46.70	54.00	-7.30	AV
H	4874.00	50.86	30.55	5.77	24.66	50.74	74.00	-23.26	PK
H	4874.00	43.55	30.55	5.77	24.66	43.43	54.00	-10.57	AV
H	7311.00	50.13	30.33	6.32	24.55	50.67	74.00	-23.33	PK
H	7311.00	43.45	30.33	6.32	24.55	43.99	54.00	-10.01	AV
H	9748.00	51.18	30.85	7.45	24.69	52.47	74.00	-21.53	PK
H	9748.00	43.46	30.85	7.45	24.69	44.75	54.00	-9.25	AV
H	12185.00	53.66	31.02	8.99	25.57	57.20	74.00	-16.80	PK
H	12185.00	43.50	31.02	8.99	25.57	47.04	54.00	-6.96	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924.00	52.55	30.55	5.77	24.66	52.43	74.00	-21.57	PK
V	4924.00	43.06	30.55	5.77	24.66	42.94	54.00	-11.06	AV
V	7386.00	53.72	30.33	6.32	24.55	54.26	74.00	-19.74	PK
V	7386.00	43.83	30.33	6.32	24.55	44.37	54.00	-9.63	AV
V	9848.00	52.24	30.85	7.45	24.69	53.53	74.00	-20.47	PK
V	9848.00	43.71	30.85	7.45	24.69	45.00	54.00	-9.00	AV
V	12310.00	53.92	31.02	8.99	25.57	57.46	74.00	-16.54	PK
V	12310.00	43.27	31.02	8.99	25.57	46.81	54.00	-7.19	AV
H	4924.00	52.38	30.55	5.77	24.66	52.26	74.00	-21.74	PK
H	4924.00	43.46	30.55	5.77	24.66	43.34	54.00	-10.66	AV
H	7386.00	51.59	30.33	6.32	24.55	52.13	74.00	-21.87	PK
H	7386.00	43.68	30.33	6.32	24.55	44.22	54.00	-9.78	AV
H	9848.00	53.44	30.85	7.45	24.69	54.73	74.00	-19.27	PK
H	9848.00	43.96	30.85	7.45	24.69	45.25	54.00	-8.75	AV
H	12310.00	53.91	31.02	8.99	25.57	57.45	74.00	-16.55	PK
H	12310.00	43.94	31.02	8.99	25.57	47.48	54.00	-6.52	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n20

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824.00	54.58	30.55	5.77	24.66	54.46	74.00	-19.54	PK
V	4824.00	43.68	30.55	5.77	24.66	43.56	54.00	-10.44	AV
V	7236.00	51.56	30.33	6.32	24.55	52.10	74.00	-21.90	PK
V	7236.00	43.68	30.33	6.32	24.55	44.22	54.00	-9.78	AV
V	9648.00	50.16	30.85	7.45	24.69	51.45	74.00	-22.55	PK
V	9648.00	43.24	30.85	7.45	24.69	44.53	54.00	-9.47	AV
V	12060.00	51.92	31.02	8.99	25.57	55.46	74.00	-18.54	PK
V	12060.00	43.33	31.02	8.99	25.57	46.87	54.00	-7.13	AV
H	4824.00	50.33	30.55	5.77	24.66	50.21	74.00	-23.79	PK
H	4824.00	43.30	30.55	5.77	24.66	43.18	54.00	-10.82	AV
H	7236.00	54.06	30.33	6.32	24.55	54.60	74.00	-19.40	PK
H	7236.00	43.21	30.33	6.32	24.55	43.75	54.00	-10.25	AV
H	9648.00	53.08	30.85	7.45	24.69	54.37	74.00	-19.63	PK
H	9648.00	43.68	30.85	7.45	24.69	44.97	54.00	-9.03	AV
H	12060.00	53.62	31.02	8.99	25.57	57.16	74.00	-16.84	PK
H	12060.00	43.96	31.02	8.99	25.57	47.50	54.00	-6.50	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	53.12	30.55	5.77	24.66	53.00	74.00	-21.00	PK
V	4874.00	43.62	30.55	5.77	24.66	43.50	54.00	-10.50	AV
V	7311.00	50.20	30.33	6.32	24.55	50.74	74.00	-23.26	PK
V	7311.00	43.63	30.33	6.32	24.55	44.17	54.00	-9.83	AV
V	9748.00	51.77	30.85	7.45	24.69	53.06	74.00	-20.94	PK
V	9748.00	43.17	30.85	7.45	24.69	44.46	54.00	-9.54	AV
V	12185.00	52.66	31.02	8.99	25.57	56.20	74.00	-17.80	PK
V	12185.00	43.66	31.02	8.99	25.57	47.20	54.00	-6.80	AV
H	4874.00	50.72	30.55	5.77	24.66	50.60	74.00	-23.40	PK
H	4874.00	43.36	30.55	5.77	24.66	43.24	54.00	-10.76	AV
H	7311.00	52.66	30.33	6.32	24.55	53.20	74.00	-20.80	PK
H	7311.00	43.83	30.33	6.32	24.55	44.37	54.00	-9.63	AV
H	9748.00	54.35	30.85	7.45	24.69	55.64	74.00	-18.36	PK
H	9748.00	43.44	30.85	7.45	24.69	44.73	54.00	-9.27	AV
H	12185.00	54.61	31.02	8.99	25.57	58.15	74.00	-15.85	PK
H	12185.00	43.13	31.02	8.99	25.57	46.67	54.00	-7.33	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924.00	50.39	30.55	5.77	24.66	50.27	74.00	-23.73	PK
V	4924.00	43.49	30.55	5.77	24.66	43.37	54.00	-10.63	AV
V	7386.00	54.91	30.33	6.32	24.55	55.45	74.00	-18.55	PK
V	7386.00	43.27	30.33	6.32	24.55	43.81	54.00	-10.19	AV
V	9848.00	50.66	30.85	7.45	24.69	51.95	74.00	-22.05	PK
V	9848.00	43.62	30.85	7.45	24.69	44.91	54.00	-9.09	AV
V	12310.00	54.89	31.02	8.99	25.57	58.43	74.00	-15.57	PK
V	12310.00	43.47	31.02	8.99	25.57	47.01	54.00	-6.99	AV
H	4924.00	54.59	30.55	5.77	24.66	54.47	74.00	-19.53	PK
H	4924.00	43.88	30.55	5.77	24.66	43.76	54.00	-10.24	AV
H	7386.00	51.52	30.33	6.32	24.55	52.06	74.00	-21.94	PK
H	7386.00	43.69	30.33	6.32	24.55	44.23	54.00	-9.77	AV
H	9848.00	52.50	30.85	7.45	24.69	53.79	74.00	-20.21	PK
H	9848.00	43.34	30.85	7.45	24.69	44.63	54.00	-9.37	AV
H	12310.00	53.39	31.02	8.99	25.57	56.93	74.00	-17.07	PK
H	12310.00	43.54	31.02	8.99	25.57	47.08	54.00	-6.92	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n40

Polar (H/V)	Frequenc y	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2422MHz									
V	4844.00	53.70	30.55	5.77	24.66	53.58	74.00	-20.42	PK
V	4844.00	43.28	30.55	5.77	24.66	43.16	54.00	-10.84	AV
V	7266.00	53.37	30.33	6.32	24.55	53.91	74.00	-20.09	PK
V	7266.00	43.80	30.33	6.32	24.55	44.34	54.00	-9.66	AV
V	9688.00	53.97	30.85	7.45	24.69	55.26	74.00	-18.74	PK
V	9688.00	43.80	30.85	7.45	24.69	45.09	54.00	-8.91	AV
V	12110.00	53.98	31.02	8.99	25.57	57.52	74.00	-16.48	PK
V	12110.00	43.59	31.02	8.99	25.57	47.13	54.00	-6.87	AV
H	4844.00	54.77	30.55	5.77	24.66	54.65	74.00	-19.35	PK
H	4844.00	43.79	30.55	5.77	24.66	43.67	54.00	-10.33	AV
H	7266.00	53.82	30.33	6.32	24.55	54.36	74.00	-19.64	PK
H	7266.00	43.37	30.33	6.32	24.55	43.91	54.00	-10.09	AV
H	9688.00	54.49	30.85	7.45	24.69	55.78	74.00	-18.22	PK
H	9688.00	43.18	30.85	7.45	24.69	44.47	54.00	-9.53	AV
H	12110.00	52.83	31.02	8.99	25.57	56.37	74.00	-17.63	PK
H	12110.00	43.28	31.02	8.99	25.57	46.82	54.00	-7.18	AV

Polar (H/V)	Frequenc y	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	52.80	30.55	5.77	24.66	52.68	74.00	-21.32	PK
V	4874.00	43.07	30.55	5.77	24.66	42.95	54.00	-11.05	AV
V	7311.00	53.05	30.33	6.32	24.55	53.59	74.00	-20.41	PK
V	7311.00	43.05	30.33	6.32	24.55	43.59	54.00	-10.41	AV
V	9748.00	53.67	30.85	7.45	24.69	54.96	74.00	-19.04	PK
V	9748.00	43.30	30.85	7.45	24.69	44.59	54.00	-9.41	AV
V	12185.00	52.37	31.02	8.99	25.57	55.91	74.00	-18.09	PK
V	12185.00	43.30	31.02	8.99	25.57	46.84	54.00	-7.16	AV
H	4874.00	51.31	30.55	5.77	24.66	51.19	74.00	-22.81	PK
H	4874.00	43.24	30.55	5.77	24.66	43.12	54.00	-10.88	AV
H	7311.00	50.97	30.33	6.32	24.55	51.51	74.00	-22.49	PK
H	7311.00	43.63	30.33	6.32	24.55	44.17	54.00	-9.83	AV
H	9748.00	51.77	30.85	7.45	24.69	53.06	74.00	-20.94	PK
H	9748.00	43.24	30.85	7.45	24.69	44.53	54.00	-9.47	AV
H	12185.00	50.35	31.02	8.99	25.57	53.89	74.00	-20.11	PK
H	12185.00	43.38	31.02	8.99	25.57	46.92	54.00	-7.08	AV



Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2452MHz									
V	4904.00	54.53	30.55	5.77	24.66	54.41	74.00	-19.59	PK
V	4904.00	43.10	30.55	5.77	24.66	42.98	54.00	-11.02	AV
V	7356.00	50.44	30.33	6.32	24.55	50.98	74.00	-23.02	PK
V	7356.00	43.66	30.33	6.32	24.55	44.20	54.00	-9.80	AV
V	9808.00	50.96	30.85	7.45	24.69	52.25	74.00	-21.75	PK
V	9808.00	43.15	30.85	7.45	24.69	44.44	54.00	-9.56	AV
V	12260.00	54.80	31.02	8.99	25.57	58.34	74.00	-15.66	PK
V	12260.00	43.91	31.02	8.99	25.57	47.45	54.00	-6.55	AV
H	4904.00	52.59	30.55	5.77	24.66	52.47	74.00	-21.53	PK
H	4904.00	43.35	30.55	5.77	24.66	43.23	54.00	-10.77	AV
H	7356.00	52.00	30.33	6.32	24.55	52.54	74.00	-21.46	PK
H	7356.00	43.38	30.33	6.32	24.55	43.92	54.00	-10.08	AV
H	9808.00	52.04	30.85	7.45	24.69	53.33	74.00	-20.67	PK
H	9808.00	43.79	30.85	7.45	24.69	45.08	54.00	-8.92	AV
H	12260.00	50.43	31.02	8.99	25.57	53.97	74.00	-20.03	PK
H	12260.00	43.03	31.02	8.99	25.57	46.57	54.00	-7.43	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



5. RADIATED BAND EMISSION MEASUREMENT

5.1 TEST REQUIREMENT

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2390MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above	Peak	1MHz	3MHz	Peak
	1GHz	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


5.3 DEVIATION FROM TEST STANDARD

No deviation



5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBu V/m)	Margin (dB)	Dete ctor Type	Result
802.11b	LowChannel 2412MHz										
	H	2390.00	54.59	30.22	4.85	23.98	53.20	74.00	-20.80	PK	PASS
	H	2390.00	44.12	30.22	4.85	23.98	42.73	54.00	-11.27	AV	PASS
	H	2400.00	54.65	30.22	4.85	23.98	53.26	74.00	-20.74	PK	PASS
	H	2400.00	44.79	30.22	4.85	23.98	43.40	54.00	-10.60	AV	PASS
	V	2390.00	54.29	30.22	4.85	23.98	52.90	74.00	-21.10	PK	PASS
	V	2390.00	44.32	30.22	4.85	23.98	42.93	54.00	-11.07	AV	PASS
	V	2400.00	53.72	30.22	4.85	23.98	52.33	74.00	-21.67	PK	PASS
	V	2400.00	44.72	30.22	4.85	23.98	43.33	54.00	-10.67	AV	PASS
	HighChannel 2462MHz										
	H	2483.50	54.89	30.22	4.85	23.98	53.50	74.00	-20.50	PK	PASS
	H	2483.50	44.46	30.22	4.85	23.98	43.07	54.00	-10.93	AV	PASS
	H	2500.00	54.04	30.22	4.85	23.98	52.65	74.00	-21.35	PK	PASS
	H	2500.00	44.96	30.22	4.85	23.98	43.57	54.00	-10.43	AV	PASS
	V	2483.50	53.13	30.22	4.85	23.98	51.74	74.00	-22.26	PK	PASS
	V	2483.50	44.55	30.22	4.85	23.98	43.16	54.00	-10.84	AV	PASS
	V	2500.00	54.74	30.22	4.85	23.98	53.35	74.00	-20.65	PK	PASS
	V	2500.00	44.01	30.22	4.85	23.98	42.62	54.00	-11.38	AV	PASS
802.11g	LowChannel 2412MHz										
	H	2390.00	54.63	30.22	4.85	23.98	53.24	74.00	-20.76	PK	PASS
	H	2390.00	44.57	30.22	4.85	23.98	43.18	54.00	-10.82	AV	PASS
	H	2400.00	54.48	30.22	4.85	23.98	53.09	74.00	-20.91	PK	PASS
	H	2400.00	44.20	30.22	4.85	23.98	42.81	54.00	-11.19	AV	PASS
	V	2390.00	54.98	30.22	4.85	23.98	53.59	74.00	-20.41	PK	PASS
	V	2390.00	44.92	30.22	4.85	23.98	43.53	54.00	-10.47	AV	PASS
	V	2400.00	53.44	30.22	4.85	23.98	52.05	74.00	-21.95	PK	PASS
	V	2400.00	44.82	30.22	4.85	23.98	43.43	54.00	-10.57	AV	PASS
	High Channel 2462MHz										
	H	2483.50	53.35	30.22	4.85	23.98	51.96	74.00	-22.04	PK	PASS
	H	2483.50	44.78	30.22	4.85	23.98	43.39	54.00	-10.61	AV	PASS
	H	2500.00	54.15	30.22	4.85	23.98	52.76	74.00	-21.24	PK	PASS
	H	2500.00	44.22	30.22	4.85	23.98	42.83	54.00	-11.17	AV	PASS
	V	2483.50	53.22	30.22	4.85	23.98	51.83	74.00	-22.17	PK	PASS
	V	2483.50	44.37	30.22	4.85	23.98	42.98	54.00	-11.02	AV	PASS
	V	2500.00	54.96	30.22	4.85	23.98	53.57	74.00	-20.43	PK	PASS
	V	2500.00	44.89	30.22	4.85	23.98	43.50	54.00	-10.50	AV	PASS
Remark: Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit											


$$\text{Emission Level} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Pre-amplifier, Margin} = \text{Emission Level} - \text{Limit}$$



6. POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.




6.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 3.7V


Test Mode	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
802.11b	2412	-18.912	8	PASS
	2437	-18.911	8	PASS
	2462	-19.762	8	PASS
802.11g	2412	-22.516	8	PASS
	2437	-22.718	8	PASS
	2462	-22.726	8	PASS
802.11n20	2412	-21.360	8	PASS
	2437	-21.614	8	PASS
	2462	-21.730	8	PASS
802.11n40	2422	-23.640	8	PASS
	2437	-24.285	8	PASS
	2452	-24.519	8	PASS




802.11b - CH01



802.11b - CH06




802.11b - CH11







802.11g - CH01



802.11g - CH06




802.11g - CH11







802.11n20 - CH01



802.11n20 - CH06




802.11n20 - CH11







802.11n40 - CH03



802.11n40 - CH06



802.11n40 - CH09





7. 6DB OCCUPIED BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB Occupied Bandwidth)	2400-2483.5	PASS


7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.




7.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 3.7V
Test Mode :	TX		


Test Mode	Test Channel (MHz)	6dB Occupied Bandwidth (MHz)	Limit (kHz)	Result
802.11b	2412	9.581	>500	Pass
	2437	10.02		
	2462	8.813		
802.11g	2412	16.31	>500	Pass
	2437	16.28		
	2462	16.07		
802.11n20	2412	16.31	>500	Pass
	2437	16.33		
	2462	16.56		
802.11n40	2422	32.51	>500	Pass
	2437	33.41		
	2452	35.06		




802.11b - CH01



802.11b - CH06




802.11b - CH11







802.11g - CH01



802.11g - CH06




802.11g - CH11







802.11n20 - CH01



802.11n20 - CH06




802.11n20 - CH11







802.11n40 - CH03



802.11n40 - CH06



802.11n40 - CH09





8. PEAK OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.



8.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 3.7V

Test Mode	Test Channel (MHz)	Peak Output Power (dBm)	Limit (dBm)	Result
802.11b	2412	7.155	30.00	Pass
	2437	7.597		
	2462	7.433		
802.11g	2412	6.995	30.00	Pass
	2437	6.807		
	2462	6.811		
802.11n20	2412	7.128	30.00	Pass
	2437	7.053		
	2462	6.981		
802.11n40	2422	6.979	30.00	Pass
	2437	6.986		
	2452	6.847		



9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE


Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.



9.6 TEST RESULTS




Band edge test plot as follows:

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 3.7V

802.11b - Lowest channel



802.11b - Highest channel





Keysight Spectrum Analyzer - Swept SA

Center Freq 2.412000000 GHz

Ref Offset 2.37 dB
Ref 20.00 dBm

Span 30.00 MHz
Sweep 5.333 ms (40001 pts)

#Res BW 100 kHz
#VBW 300 kHz

Mkr1 2.408 234 25 GHz
-9.248 dBm

10 dB/div
Log

PRM: Fast
IF Gain: Low

Trig: Free Run
#Atten: 30 dB


#Avg Type: RMS
Avg/Hold: 100/100

11:43:37 AM Apr 29, 2025

TRACE 1 2 1 4 1
TYPE: M W W W W W W
DEF: M N N N N N

STATUS

The image shows a Keysight Spectrum Analyzer display. The main plot area shows a signal spectrum with a peak marker labeled '1' at 2.408 GHz and -9.248 dBm. The y-axis is labeled '10 dB/div' and 'Log'. The x-axis is labeled 'Center Freq 2.412000000 GHz'. The plot area has a grid. The top of the screen shows various settings: 'PRM: Fast', 'IF Gain: Low', 'Trig: Free Run', '#Atten: 30 dB', '#Avg Type: RMS', and 'Avg/Hold: 100/100'. The bottom of the screen shows 'Span 30.00 MHz', 'Sweep 5.333 ms (40001 pts)', '#Res BW 100 kHz', and '#VBW 300 kHz'. The top right corner shows the date and time: '11:43:37 AM Apr 29, 2025'. The bottom right corner has a 'STATUS' button. The top left corner has the text 'Keysight Spectrum Analyzer - Swept SA'. The top center has the text 'Center Freq 2.412000000 GHz'. The top right has the text 'Ref Offset 2.37 dB' and 'Ref 20.00 dBm'. The bottom right has the text 'Mkr1 2.408 234 25 GHz' and '-9.248 dBm'. The bottom left has the text '10 dB/div' and 'Log'. The bottom center has the text 'PRM: Fast' and 'IF Gain: Low'. The bottom right has the text 'Trig: Free Run' and '#Atten: 30 dB'. The bottom left has the text '#Avg Type: RMS' and 'Avg/Hold: 100/100'. The bottom right has the text '11:43:37 AM Apr 29, 2025'. The bottom center has the text 'TRACE 1 2 1 4 1' and 'TYPE: M W W W W W W' and 'DEF: M N N N N N'. The bottom right has a 'STATUS' button.



Keysight Spectrum Analyzer - Sweet SA

7.1 100.000000 GHz 10.000000 MHz

Center Freq 2.462000000 GHz

PMO: Fast IF Gain: Low

SENSE: PULSE

Trig: Free Run

#Ave Type: RMS

Avg/Hold: 100/100

11:50:30 AM Apr 25, 2025

TRACE 1

TYPE: MNRW

DEF: MNRW

Ref Offset 2.35 dB

Ref 20.00 dBm

Mkr1 2.466 973 25 GHz

-8.994 dBm

10 dB/div

Log

Center 2.46200 GHz

#Res BW 100 kHz

#VBW 300 kHz


Span 30.00 MHz





Sweep 5.333 ms (40001 pts)

MSA

(STATUS)

The image shows a Keysight Spectrum Analyzer interface. The main display is a frequency spectrum plot with a grid. The horizontal axis represents frequency, and the vertical axis represents power in dBm. A signal is visible as a yellow trace, with a specific peak marked by a green arrow and labeled '1'. The peak is at 2.466 973 25 GHz with a power level of -8.994 dBm. The plot is centered at 2.46200 GHz with a span of 30.00 MHz. The resolution bandwidth (Res BW) is 100 kHz, and the video bandwidth (VBW) is 300 kHz. The sweep time is 5.333 ms. The reference level is 20.00 dBm, and the reference offset is 2.35 dB. The display also shows various settings like PMO: Fast, IF Gain: Low, SENSE: PULSE, Trig: Free Run, and #Ave Type: RMS. The average/hold time is 100/100. The date and time are 11:50:30 AM Apr 25, 2025. The trace is labeled 'TRACE 1' and the type is 'MNRW'. The definition is 'DEF: MNRW'. The vertical axis is labeled '10 dB/div' and 'Log'. The horizontal axis is labeled 'Center 2.46200 GHz' and '#Res BW 100 kHz'. The bottom status bar shows 'MSA' and '(STATUS)'.







Keysight Spectrum Analyzer - Swept SA

01:57:16 PM Apr 29, 2025

Center Freq 2.422000000 GHz

SENSE: PULSE

ALIGN: AUTO

#Avg Type: RMS

Avg/Hold: 100/100

PRF: Fast

Trig: Free Run

#Att: 30 dB

IF Gain: Low

Ref Offset 2.36 dB

Ref 20.00 dBm

Mkr1 2.413 250.5 GHz

-10.794 dBm

10 dB/div

Log

Center 2.42200 GHz

#Res BW 100 kHz


#VBW 300 kHz

Span 60.00 MHz

Sweep 8.000 ms (40001 pts)

STATUS

The image shows a Keysight Spectrum Analyzer display. The main plot area shows a swept signal with a yellow trace. The signal is centered at 2.42200 GHz. The y-axis is labeled '10 dB/div' and 'Log'. The x-axis is labeled 'Center 2.42200 GHz'. The span is 60.00 MHz. The resolution bandwidth (Res BW) is 100 kHz. The video bandwidth (VBW) is 300 kHz. The sweep time is 8.000 ms (40001 pts). A marker is placed at 2.4132505 GHz with a level of -10.794 dBm. The signal level is approximately -10 dBm. The display also shows various settings like SENSE: PULSE, ALIGN: AUTO, #Avg Type: RMS, Avg/Hold: 100/100, PRF: Fast, Trig: Free Run, #Att: 30 dB, IF Gain: Low, Ref Offset 2.36 dB, and Ref 20.00 dBm. The date and time are 01:57:16 PM Apr 29, 2025.



Keysight Spectrum Analyzer - Swept SA

Center Freq 2.452000000 GHz

Ref Offset 2.38 dB
Ref 20.00 dBm

PMO: Fast
IF Gain: Low

Trig: Free Run
#Atten: 30 dB

#Avg Type: RMS
Avg/Hold: 100/100

02:32:25 PM Apr 25, 2019

Trace 1: 1.4.1
Type: MWWWWWW
Def: NNNNN

Mkr1 2.455714 0 GHz
-11.428 dBm

10 dB/div
Log


Center 2.45200 GHz
#Res BW 100 kHz

#VBW 300 kHz

Span 60.00 MHz
Sweep 8.000 ms (40001 pts)

MSA



(STATUS)







Spurious emission test plot as follows:


802.11b
Lowest channel



Middle channel





Highest channel





30MHz ~ 26.5GHz





802.11g
Lowest channel



Middle channel





Highest channel





30MHz ~ 26.5GHz





802.11n20 Lowest channel



Middle channel





Highest channel





30MHz ~ 26.5GHz





802.11n40 Lowest channel



Middle channel



Highest channel



30MHz ~ 26.5GHz



10. DUTY CYCLE

Test Method:	ANSI C63.10:2013
--------------	------------------

10.1 APPLIED PROCEDURES / LIMIT


Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
 - 1) Set the center frequency of the instrument to the center frequency of the transmission.
 - 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
 - 3) Set $VBW \geq RBW$. Set detector = peak or average.
 - 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

10.2 DEVIATION FROM STANDARD

No deviation.

10.3 TEST SETUP



10.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.



10.5 TEST RESULTS

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 3.7V


Test Mode	Test Frequency (MHz)	Duty Cycle (%)	Factor (dB)	Result
802.11b	2412	99.91	0.04	Pass
802.11g	2412	99.55	0.02	Pass
802.11n20	2412	99.51	0.02	Pass
802.11n40	2422	99.00	0.04	Pass

Note: Duty Cycle = Ton / Total * 100%;
Duty Cycle Correction Factor = 10log (1/Duty Cycle).




802.11b

2412MHz



802.11g


2412MHz






802.11n20

2412MHz



802.11n40

2422MHz



Note: All channel have been tested, and the report only reflects the worst case data.



11. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is PCB antenna, the best case gain of the antenna is 2.58dBi, reference to the appendix II for details.	



12. TEST SETUP PHOTO

Reference to the appendix I for details.

13. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

******* END OF REPORT *******