

FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2BCKD-DV8910

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Modes& Channel Freq. (MHz)	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW/ cm2)	Result
BLE	GFSK&L CH	0±1	1	1.2589	1.7498 (2.43dBi)	0.0004	1	Pass
EDR	8DPSK& MCH	6±1	7	5.0119	1.7498 (2.43dBi)	0.0017	1	Pass
2.4GWIFI ANT1	802.11b &2437	14±1	15	31.6228	1.4997 (1.76dBi)	0.0094	1	Pass
2.4GWIFI ANT2	802.11b &2412	14±1	15	31.6228	1.71 (2.33dBi)	0.0108	1	Pass
5.2GWIFI ANT1	802.11a &5240	13±1	14	25.1189	1.6406 (2.15dBi)	0.0082	1	Pass
5.2GWIFI ANT2	802.11n(HT40)& 5230	12±1	13	19.9526	3.4356 (5.36dBi)	0.0136	1	Pass
5.8GWIFI ANT1	802.11a c80&577 5	12±1	13	19.9526	1.8493 (2.67dBi)	0.0073	1	Pass
5.8GWIFI ANT2	802.11a c80&577 5	12±1	13	19.9526	3.0409 (4.83dBi)	0.01208	1	Pass

Tech nolo gy	Tune up Produce power(dBm)		Maximum Tune-up (dBm)		Antenna Gain(ANT 1/ANT 2) (numeric)	Power Density (S) (mW/ cm2)		MPE Limit (mW/ cm2)	Σ MPE Ratio	Σ MPE Ratio Limit	Result
	ANT 1	ANT 2	ANT 1	ANT 2		ANT 1	ANT 2				
2.4G WIFI MIM O	14 ±1	14 ±1	15	15	ANT1:1.4997 (1.76dBi) ANT2:1.71 (2.33dBi)	0.0094	0.0108	1	0.0202	1	Pass

Tech nolo gy	Tune up Produce power(dBm)		Maximum Tune-up (dBm)		Antenna Gain(ANT 1/ANT 2) (numeric)	Power Density (S) (mW/ cm2)		MPE Limit (mW/ cm2)	Σ MPE Ratio	Σ MPE Ratio Limit	Result
	ANT 1	ANT 2	ANT 1	ANT 2		ANT 1	ANT 2				
5G WIFI MIM O	13 ±1	12 ±1	14	13	ANT1:1.6406 (2.15dBi) ANT2:3.4356 (5.36dBi)	0.0082	0.0136	1	0.0218	1	Pass