TEST REPORT

Reference No.	:	WTF23F05111170W
FCC ID	:	2BCMJ-NCA30EFPRO
Applicant	:	Foshan Shunde BIG Climatic Manufacture Co., Ltd
Address	:	C area, 2nd Floor, 9A building, factory buildings 2 and 3, section no. 10-6, Fu An industrial area (First phase),Leliu Town, Shunde District, Foshan City, Guangdong, China
Manufacturer	:	Foshan Shunde BIG Climatic Manufacture Co.,Ltd Zhongshan Branch
Address	:	No.20,Nantou Avenue East, Nantou town, Zhongshan City ,Guangdong ,China ,528427
Product Name	:	Electric heater
Model No.	:	NCA1-3.0EF-PRO WHITE, NCA2-3.0EF-PRO WHITE
Test specification	:	FCC CFR47 Part 15 Subpart C (Section 15.247):2021
Date of Receipt sample	:	2023-06-21
Date of Test	:	2023-06-22 to 2023-07-26
Date of Issue	:	2023-09-07
Test Report Form No.	:	WEW-15247A-01A
Test Result		**Pass**

Remarks:
The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:
Waltek Testing Group (Foshan) Co., Ltd.
Address: No.13-19, 2/F., 2nd Building, Sunlink International Machinery City, Chencun, Shunde District, Foshan, Guangdong, China
Tel:+86-757-23811398 Fax:+86-757-23811381 E-mail:info@waltek.com.cn

Tested by: Roy Hong

Approved by: Danny Zhou

1 Revision History

Test Report No.	Date of Issue	Description	Status
WTF23F05111170W	2023-09-07	Original	Valid

2 Contents

Page

1 REVISION HISTORY 2

2 CONTENTS 3

3 GENERAL INFORMATION 4

3.1 GENERAL DESCRIPTION OF E.U.T 4
3.2 TECHNICAL CHARACTERISTICS OF EUT 4
3.3 STANDARDS APPLICABLE FOR TESTING 4
3.4 TEST FACILITY 5
3.5 SUBCONTRACTED 5
3.6 ABNORMALITIES FROM STANDARD CONDITIONS 5

4 EUT SETUP AND TEST MODE 6

5 EQUIPMENT USED DURING TEST 7

5.1 EQUIPMENT LIST 7
5.2 TEST SOFTWARE 8
5.3 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT 8
5.4 MEASUREMENT UNCERTAINTY 8

6 SUMMARY OF TEST RESULT 9

6.1 ANTENNA REQUIREMENT 10
6.2 RADIATED SPURIOUS EMISSIONS 11
6.3 POWER SPECTRAL DENSITY 21
6.4 DTS BANDWIDTH 25
6.5 RF OUTPUT POWER 29
6.6 OUT OF BAND EMISSIONS 34
6.7 CONDUCTED EMISSIONS 45

7 PHOTOGRAPHS TEST SETUP 49

7.1 PHOTOGRAPHS - RADIATED EMISSION TEST SETUP 49
7.2 PHOTOGRAPHS – CONDUCTED EMISSION TEST SETUP 50

8 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS 51

8.1 EUT - EXTERNAL PHOTOS 51
8.2 EUT - INTERNAL PHOTOS 54

3 General Information

3.1 General Description of E.U.T

Product Name ..... : Electric heater

Model No. ..... : NCA1-3.0EF-PRO WHITE, NCA2-3.0EF-PRO WHITE

Model Description ..... : Two models are the same circuit diagram except for their appearance. Therefore the full tests were performed on model NCA1-3.0EF-PRO WHITE.

Rated Voltage..... : AC 120V, 60Hz, 1500W

Battery Capacity ..... : ---

Power Adapter ..... : ---

3.2 Technical Characteristics of EUT

Support Standards ..... : 802.11b, 802.11g, 802.11n

Frequency Range ..... : 2412-2462MHz for 802.11b/g/n(HT20)

RF Output Power ..... : 16.09dBm (Conducted)

Modulation ..... : 802.11b: DSSS(DBPSK/DQPSK/CCK)
802.11g/n: OFDM (BPSK/QPSK/16QAM/64QAM)

Data Rate..... : 1Mbps for 802.11b; 54Mbps for 802.11g; MCS7 for 802.11n

Quantity of Channels ..... : 11 for 802.11b/g/n(HT20)

Channel Separation..... : 5MHz

Type of Antenna ..... : PCB Printed Antenna

Antenna Gain ..... : 2.54dBi

3.3 Standards Applicable for Testing

The tests were performed according to following standards:

FCC Rules Part 15.247	Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
558074 D01 15.247 Meas Guidance v05r02	Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The FCC Rules
662911 D01 Multiple Transmitter Output v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

3.4 Test Facility

The test facility has a test site registered with the following organizations:

- **ISED – Registration No.: 21895**

Waltek Testing Group (Foshan) Co., Ltd. has been registered and fully described in a report filed with the Innovation, Science an Economic Development Canada(ISED). The acceptance letter from the ISED is maintained in our files. Registration ISED number:21895, March 12, 2019

- **FCC – Registration No.: 820106**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 820106, August 16, 2018

- **FCC – Designation No.: CN5034**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation No. CN5034.

- **NVLAP – Lab Code: 600191-0**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 600191-0.
This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

3.5 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test items: ---

Lab information: ---

3.6 Abnormalities from Standard Conditions

None.

4 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List

Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz, High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz, High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz, High:2462MHz

Test Conditions

Temperature:	22~25℃
Relative Humidity:	50~55%
Atmospheric pressure:	101.8kPa

5 Equipment Used during Test

5.1 Equipment List

☒Conducted Emissions 1#						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal Date**	**Cal Due Date**
1.	EMI Test Receiver	R&S	ESR3	102423	2023-01-05	2024-01-04
2.	LISN	R&S	ENV216	101343	2023-01-05	2024-01-04
3.	Cable	HUBER+SUHNER	CBL2-NN-6M	223NN624	2023-01-05	2024-01-04
4.	Switch	CD	RSU-A4 18G	RSUA4008	2023-01-05	2024-01-04
☐Conducted Emissions 2#						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal Date**	**Cal Due Date**
1.	EMI Test Receiver	R&S	ESCI	101178	2023-01-05	2024-01-04
2.	LISN	R&S	ENV216	101215	2023-01-05	2024-01-04
3.	Cable	HUBER+SUHNER	CBL2-NN-6M	6102701	2023-01-05	2024-01-04
4.	Switch	ESE	RSU/M2	---	2023-01-05	2024-01-04
☐Conducted Emissions 3#						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal Date**	**Cal Due Date**
1.	EMI Test Receiver	R&S	ESR3	102842	2023-01-05	2024-01-04
2.	LISN	R&S	ENV216	101542	2023-01-05	2024-01-04
3.	Cable	YIHENG	LMR195UF-NMNM-2.5	---	2023-01-05	2024-01-04
4.	Manual RF Switch	YIHENG	SW-2	RSU0402	2023-01-05	2024-01-04
☒Radiation Emissions						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Calibration Date**	**Calibration Due Date**
1.	3m Semi-anechoic Chamber	CHANGCHUANG	9m×6m×6m	-	2021-01-11	2024-01-10
2.	EMI Test Receiver	RS	ESR7	101566	2023-01-05	2024-01-04
3.	EMC Analyzer	Agilent	N9020A	MY48011796	2023-05-15	2024-05-14
4.	Active Loop Antenna	SCHWARZBECK	FMZB1519B	00004	2023-01-05	2024-01-04
5.	Trilog Broadband Antenna	SCHWARZBECK	VULB 9162	9162-117	2023-03-10	2024-03-09
6.	Coaxial Cable (below 1GHz)	H+S	CBL3-NN-12+3 m	214NN320	2023-01-06	2024-01-05
7.	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	01561	2023-01-06	2024-01-05
8.	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	01119	2023-01-06	2024-01-05
9.	Coaxial Cable (above 1GHz)	Times-Micorwave	CBL5-NN	-	2023-01-05	2024-01-04
10.	Amplifier	Lunar E M	LNA1G18-40	20160501002	2023-01-05	2024-01-04

☒RF Conducted Testing						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Calibration Date**	**Calibration Due Date**
1.	Spectrum Analyzer	Agilent	N9020A	MY48011796	2023-05-15	2024-05-14
2.	Analog Signal Generator	Agilent	N5181A	MY48180720	2023-01-05	2024-01-04
3.	RF Control Unit	CHANGCHUANG	JS0806-2	-	2023-01-06	2024-01-05

☐: ***Not Used***

☒: ***Used***

5.2 Test Software

Description	Manufacturer	Model	Version
EMI Test Software (Conducted Emission 1#)	FARATRONIC	EZ-EMC	EMEC-3A1
EMI Test Software (Conducted Emission 2#)	FARATRONIC	EZ-EMC	CON-03A1
EMI Test Software (Conducted Emission 3#)	FARATRONIC	EZ-EMC	COM 3A1.1
EMI Test Software (Radiated Emission)	FARATRONIC	EZ-EMC	RA-03A1-1
RF Conducted Test Software	TONSCEND	JS1120-2	V2.6

5.3 Special Accessories and Auxiliary Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.
1.	/	/	/	/

5.4 Measurement Uncertainty

Parameter	Uncertainty
RF Output Power	±2.2dB
Occupied Bandwidth	±1.5%
Conducted Emission	±2.6dB
Transmitter Spurious Emission	±3.8dB (for 25MHz-1GHz)
	±5.0dB (for 1GHz-18GHz)

6 Summary of Test Result

Test Items	FCC Rules	Result
Antenna Requirement	§15.203; §15.247(b)(4)(i)	Compliant
Restricted Band of Operation	§15.205	Compliant
Conducted Emissions	§15.207(a)	Compliant
Radiated Spurious Emissions	§15.209(a)	Compliant
Power Spectral Density	§15.247(e)	Compliant
DTS Bandwidth	§ 15.247(a)(2)	Compliant
RF Output Power	§15.247(b)(3)	Compliant
Band edge (Out of Band Emissions)	§15.247(d)	Compliant

Remark:

Pass Test item meets the requirement

Fail Test item does not meet the requirement

N/A Test case does not apply to the test object

6.1 Antenna Requirement

6.1.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

6.1.2 Evaluation Information

The EUT has an PCB Printed Antenna, the gain is 2.54dBi, fulfil the requirement of this section.



6.2 Radiated Spurious Emissions

6.2.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

6.2.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.
The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.
The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



6.2.3 Spectrum Analyzer Setup

9KHz-30MHz	30MHz-1GHz	Above 1GHz
RBW=10kHz	RBW=120kHz	RBW=1MHz
VBW=30kHz	VBW=300kHz	VBW=3MHz(Peak), 10MHz(AV)
Sweep time=Auto	Sweep time=Auto	Sweep time=Auto
Trace=Max hold	Trace=Max hold	Trace=Max hold
Detector function=peak	Detector function=peak, QP	Detector function=peak, AV

6.2.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Corr. Factor

Corr.Factor=Antenna Factor + Cable Factor - Amplifier Gain

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – Limit

6.2.5 Test Results

Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.

Test Frequency: Below 1GHz

Test Mode: 802.11b (worst case)

Test Channel Low Channel **Polarization** Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	31.5316	0.14	11.69	11.83	40.00	-28.17	QP	
2	48.0275	-1.02	13.89	12.87	40.00	-27.13	QP	
3	72.0083	3.05	10.79	13.84	40.00	-26.16	QP	
4	112.4848	0.91	12.46	13.37	43.50	-30.13	QP	
5	181.1562	1.09	14.16	15.25	43.50	-28.25	QP	
6	361.9675	0.71	18.65	19.36	46.00	-26.64	QP	

Test Channel Low Channel **Polarization** Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	32.7486	-0.33	13.59	13.26	40.00	-26.74	QP	
2	42.8847	-3.68	15.56	11.88	40.00	-28.12	QP	
3	71.9830	1.95	10.67	12.62	40.00	-27.38	QP	
4	166.4761	2.44	11.42	13.86	43.50	-29.64	QP	
5	300.1566	0.44	16.37	16.81	46.00	-29.19	QP	
6	580.7024	2.27	22.21	24.48	46.00	-21.52	QP	

Test Channel Middle Channel **Polarization** Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	36.6116	-0.71	14.44	13.73	40.00	-26.27	QP	
2	52.8896	-1.01	14.92	13.91	40.00	-26.09	QP	
3	100.7570	-0.47	14.38	13.91	43.50	-29.59	QP	
4	150.0107	1.60	10.87	12.47	43.50	-31.03	QP	
5	315.1490	-0.15	16.95	16.80	46.00	-29.20	QP	
6	549.2119	0.63	21.75	22.38	46.00	-23.62	QP	

Test Channel Middle Channel **Polarization** Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	43.9812	-1.77	15.74	13.97	40.00	-26.03	QP	
2	56.8913	-0.86	14.36	13.50	40.00	-26.50	QP	
3	111.6204	-0.80	13.64	12.84	43.50	-30.66	QP	
4	196.0968	1.03	13.31	14.34	43.50	-29.16	QP	
5	340.9010	0.00	18.24	18.24	46.00	-27.76	QP	
6	586.0211	0.57	22.44	23.01	46.00	-22.99	QP	

Test Channel High Channel **Polarization** Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	40.3038	-1.90	13.24	11.34	40.00	-28.66	QP	
2	72.0083	3.54	10.79	14.33	40.00	-25.67	QP	
3	103.7326	-0.43	11.65	11.22	43.50	-32.28	QP	
4	189.0079	-0.69	14.68	13.99	43.50	-29.51	QP	
5	378.9827	0.54	19.01	19.55	46.00	-26.45	QP	
6	569.6104	1.14	23.62	24.76	46.00	-21.24	QP	

Test Channel High Channel **Polarization** Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	47.3918	-1.65	15.58	13.93	40.00	-26.07	QP	
2	93.2111	-0.89	13.58	12.69	43.50	-30.81	QP	
3	140.1451	2.40	10.99	13.39	43.50	-30.11	QP	
4	235.4028	-0.22	14.73	14.51	46.00	-31.49	QP	
5	441.4327	0.77	19.93	20.70	46.00	-25.30	QP	
6	671.1947	0.34	24.24	24.58	46.00	-21.42	QP	

Test Frequency: Above 1GHz

Test Mode: 802.11b (worst case)

Frequency (MHz)	Reading (dBμV/m)	Detector	Polar (H/V)	Corrected Factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel							
4824	41.15	Peak	H	-3.82	37.33	74	-36.67
4824	32.97	AVG	H	-3.82	29.15	54	-24.85
7236	42.62	Peak	H	2.08	44.7	74	-29.3
7236	33.59	AVG	H	2.08	35.67	54	-18.33
4824	41.49	Peak	V	-3.41	38.08	74	-35.92
4824	31.06	AVG	V	-3.41	27.65	54	-26.35
7236	44.9	Peak	V	2.04	46.94	74	-27.06
7236	34.71	AVG	V	2.04	36.75	54	-17.25
Middle Channel							
4874	40.62	Peak	H	-3.68	36.94	74	-37.06
4874	31.34	AVG	H	-3.68	27.66	54	-26.34
7311	46.01	Peak	H	2.22	48.23	74	-25.77
7311	37.9	AVG	H	2.22	40.12	54	-13.88
4874	51.48	Peak	V	-3.3	48.18	74	-25.82
4874	41.83	AVG	V	-3.3	38.53	54	-15.47
7311	45.26	Peak	V	2.14	47.4	74	-26.6
7311	36.11	AVG	V	2.14	38.25	54	-15.75
High Channel							
4924	41.58	Peak	H	38.05	74	74	-35.95
4924	32.25	AVG	H	28.72	54	54	-25.28
7386	46.73	Peak	H	49.1	74	74	-24.9
7386	36.39	AVG	H	38.76	54	54	-15.24
4924	42.31	Peak	V	39.13	74	74	-34.87
4924	33.28	AVG	V	30.1	54	54	-23.9
7386	46.05	Peak	V	48.29	74	74	-25.71
7386	37.11	AVG	V	39.35	54	54	-14.65

Note: Testing is carried out with frequency range 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

6.3 Power Spectral Density

6.3.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.3.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

a) Set instrument center frequency to DTS channel center frequency.
b) Set span to at least 1.5 times the OBW.
c) Set RBW to: 3 kHz ⩽ RBW ⩽ 100 kHz. .
d) Set VBW ⩾3 x RBW.
e) Detector = power averaging (RMS) or sample detector (when RMS not available).
f) Ensure that the number of measurement points in the sweep ⩾ 2 x span/RBW.
g) Sweep time = auto couple.
h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
i) Use the peak marker function to determine the maximum amplitude level.
j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

6.3.3 Test Result

Test Mode	Test Channel(MHz)	Test Result (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-7.14	8
	2437	-6.78	8
	2462	-6.5	8
802.11g	2412	-15.1	8
	2437	-14.17	8
	2462	-14.01	8
802.11n (HT20)	2412	-12.43	8
	2437	-14.94	8
	2462	-14.38	8

Test plots:

802.11b_Low Channel



802.11b_Middle Channel



802.11b_High Channel



802.11g_Low Channel



802.11g_Middle Channel



802.11g_High Channel



802.11n(HT20)_Low Channel



802.11n(HT20)_Middle Channel



802.11n(HT20)_High Channel



6.4 DTS Bandwidth

6.4.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.4.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

a) Set RBW = 100 kHz.

b) Set the video bandwidth (VBW) ≥ 3 × RBW.

c) Detector = Peak.

d) Trace mode = max hold.

e) Sweep = auto couple.

f) Allow the trace to stabilize.

g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4.3 Test Result

Test Mode	Test Channel (MHz)	Test Result (MHz)	Limit (kHz)
802.11b	2412	8.520	≥ 500
	2437	8.000	≥ 500
	2462	7.960	≥ 500
802.11g	2412	16.600	≥ 500
	2437	16.560	≥ 500
	2462	16.560	≥ 500
802.11n (HT20)	2412	17.880	≥ 500
	2437	17.840	≥ 500
	2462	17.840	≥ 500

Test plots:

802.11b_Low Channel



802.11b_Middle Channel



802.11b_High Channel



802.11g_Low Channel



802.11g_Middle Channel



802.11g_High Channel



802.11n(HT20)_Low Channel



802.11n(HT20)_Middle Channel



802.11n(HT20)_High Channel



6.5 RF Output Power

6.5.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

6.5.2 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

a) Set span to at least 1.5 times the OBW.
b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
c) Set VBW ≥ 3 x RBW.
d) Number of points in sweep ≥ 2 × span / RBW. (This gives bin-to-bin spacing ≥RBW/2, so that narrowband signals are not lost between frequency bins.)
e) Sweep time = auto.
f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

6.5.3 Test Result

Modulation	Test Channel (MHz)	Reading (dBm)	Output Power (mW)	Limit (mW)
802.11b	2412	15.53	35.72	1000
	2437	15.92	39.08	1000
	2462	16.09	40.64	1000
802.11g	2412	12.39	17.34	1000
	2437	12.63	18.32	1000
	2462	12.94	19.68	1000
802.11n (HT20)	2412	15.15	19.68	1000
	2437	12.71	18.66	1000
	2462	12.89	19.45	1000

Test plots:

802.11b_Low Channel



802.11b_Middle Channel



802.11b_High Channel

802.11g_Low Channel



802.11g_Middle Channel



802.11g_High Channel



802.11n(HT20)_Low Channel



802.11n(HT20)_Middle Channel



802.11n(HT20)_High Channel



6.6 Out of Band Emissions

6.6.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

6.6.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

a) Set the center frequency and span to encompass frequency range to be measured.
b) Set the RBW = 100 kHz.
c) Set the VBW ≥ [3 × RBW].
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:
Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge,
as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz
for low bandedge, 2460MHz to 2500MHz for the high bandedge)
RBW = 1MHz, VBW = 1MHz for peak value measured
RBW = 1MHz, VBW = 10Hz for average value measured
Sweep = auto; Detector function = peak/average; Trace = max hold
All the trace to stabilize, set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emissions must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205.

Note that the method of measurement KDB publication number: 913591 may be used for the radiated band edge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

a) RBW = as specified in Table 9/

b) VBW ≥ [3 × RBW].

c) Detector = peak.

d) Sweep time = auto.

e) Trace mode = max hold.

f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1.

6.6.3 Test Result

Radiated Test

802.11b

Test Channel Low Channel **Polarization** Horizontal (worst case)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2310.000	14.90	31.96	46.86	74.00	-27.14	peak	
2	2310.000	-1.91	31.96	30.05	54.00	-23.95	AVG	
3	2390.000	14.44	32.32	46.76	74.00	-27.24	peak	
4	2390.000	-1.76	32.32	30.56	54.00	-23.44	AVG	
5	2400.000	15.23	32.36	47.59	74.00	-26.41	peak	
6	2400.000	-1.53	32.36	30.83	54.00	-23.17	AVG	
7	2412.000	51.70	32.41	84.11	74.00	10.11	peak	

Test Channel High Channel **Polarization** Horizontal (worst case)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2462.000	51.14	32.63	83.77	74.00	9.77	peak	
2	2483.500	15.74	32.73	48.47	74.00	-25.53	peak	
3	2483.500	-1.74	32.73	30.99	54.00	-23.01	AVG	
4	2500.000	15.33	32.80	48.13	74.00	-25.87	peak	
5	2500.000	-1.57	32.80	31.23	54.00	-22.77	AVG	

802.11g

Test Channel Low Channel **Polarization** Horizontal (worst case)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2310.000	14.64	31.96	46.60	74.00	-27.40	peak	
2	2310.000	-1.91	31.96	30.05	54.00	-23.95	AVG	
3	2390.000	15.87	32.32	48.19	74.00	-25.81	peak	
4	2390.000	-1.73	32.32	30.59	54.00	-23.41	AVG	
5	2400.000	27.19	32.36	59.55	74.00	-14.45	peak	
6	2400.000	0.87	32.36	33.23	54.00	-20.77	AVG	
7	2412.000	50.11	32.41	82.52	74.00	8.52	peak	

Test Channel High Channel **Polarization** Horizontal (worst case)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2462.000	53.14	32.63	85.77	74.00	11.77	peak	
2	2483.500	14.93	32.73	47.66	74.00	-26.34	peak	
3	2483.500	-1.67	32.73	31.06	54.00	-22.94	AVG	
4	2500.000	15.30	32.80	48.10	74.00	-25.90	peak	
5	2500.000	-1.53	32.80	31.27	54.00	-22.73	AVG	

802.11n(HT20)

Test Channel Low Channel **Polarization** Horizontal (worst case)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2310.000	15.29	31.96	47.25	74.00	-26.75	peak	
2	2310.000	-1.93	31.96	30.03	54.00	-23.97	AVG	
3	2390.000	15.98	32.32	48.30	74.00	-25.70	peak	
4	2390.000	-1.71	32.32	30.61	54.00	-23.39	AVG	
5	2400.000	27.99	32.36	60.35	74.00	-13.65	peak	
6	2400.000	1.99	32.36	34.35	54.00	-19.65	AVG	
7	2412.000	52.08	32.41	84.49	74.00	10.49	peak	

Test Channel High Channel **Polarization** Horizontal (worst case)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2462.000	53.68	32.63	86.31	74.00	12.31	peak	
2	2483.500	15.43	32.73	48.16	74.00	-25.84	peak	
3	2483.500	-1.67	32.73	31.06	54.00	-22.94	AVG	
4	2500.000	14.53	32.80	47.33	74.00	-26.67	peak	
5	2500.000	-1.53	32.80	31.27	54.00	-22.73	AVG	

Conducted Test

Test Mode	Channel (MHz)	Ref Level (dBm)	Result (dBm)	Limit (dBm)	Verdict
802.11b	2412	6.70	-41.71	<=-23.3	Pass
	2462	7.21	-47.56	<=-22.8	Pass
802.11g	2412	-0.11	-32.88	<=-30.11	Pass
	2462	0.46	-48.81	<=-29.54	Pass
802.11n (HT20)	2412	2.05	-31.78	<=-27.95	Pass
	2462	-0.17	-48.17	<=-30.17	Pass

Test Plots:

802.11b_Low Channel



802.11b_High Channel



802.11g_Low Channel



802.11g_High Channel



802.11n (HT20)_Low Channel



802.11n (HT20)_High Channel



6.7 Conducted Emissions

6.7.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013measurement procedure. The specification used was with the FCC Part 15.207Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in themiddle. The spacing between the peripherals was 10 cm.

6.7.2 Basic Test Setup Block Diagram



6.7.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....150 kHz

Stop Frequency.....30 MHz

Sweep Speed.....Auto

IF Bandwidth.....10 kHz

Quasi-Peak Adapter Bandwidth.....9 kHz

Quasi-Peak Adapter Mode.....Normal

6.7.4 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

6.7.5 Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF(Voltage Division Facotr), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Measurement=Reading Level+Correct Factor

Correct Facotor=LISN VDF+Cable Loss

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin= Measurement-Limit

6.7.6 Test Result

Test Mode Communication mode(AC 120V/60Hz) **Polarity** Line



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1580	37.01	9.57	46.58	65.56	-18.98	QP	
2	0.1580	13.63	9.57	23.20	55.56	-32.36	AVG	
3	0.2380	25.67	9.59	35.26	62.16	-26.90	QP	
4	0.2380	8.63	9.59	18.22	52.16	-33.94	AVG	
5	0.4380	20.38	9.62	30.00	57.10	-27.10	QP	
6	0.4380	7.37	9.62	16.99	47.10	-30.11	AVG	
7	0.8300	18.95	9.64	28.59	56.00	-27.41	QP	
8	0.8300	5.60	9.64	15.24	46.00	-30.76	AVG	
9	3.1820	20.26	9.74	30.00	56.00	-26.00	QP	
10	3.1820	2.28	9.74	12.02	46.00	-33.98	AVG	
11	17.5540	15.46	10.23	25.69	60.00	-34.31	QP	
12	17.5540	8.93	10.23	19.16	50.00	-30.84	AVG	

Test Mode Communication mode(AC 120V/60Hz) **Polarity** Neutral



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1500	34.27	9.73	44.00	65.99	-21.99	QP	
2	0.1500	12.29	9.73	22.02	55.99	-33.97	AVG	
3	0.2140	29.90	9.73	39.63	63.04	-23.41	QP	
4	0.2140	7.92	9.73	17.65	53.04	-35.39	AVG	
5	0.4260	20.38	9.62	30.00	57.33	-27.33	QP	
6	0.4260	6.56	9.62	16.18	47.33	-31.15	AVG	
7	0.8980	15.61	9.65	25.26	56.00	-30.74	QP	
8	0.8980	4.36	9.65	14.01	46.00	-31.99	AVG	
9	2.1220	20.17	9.83	30.00	56.00	-26.00	QP	
10	2.1220	2.91	9.83	12.74	46.00	-33.26	AVG	
11	23.2500	21.55	10.70	32.25	60.00	-27.75	QP	
12	23.2500	13.08	10.70	23.78	50.00	-26.22	AVG	

7 Photographs Test Setup

7.1 Photographs - Radiated Emission Test Setup

30MHz-1GHz

Above 1GHz

7.2 Photographs – Conducted Emission Test Setup

8 Photographs - Constructional Details

8.1 EUT - External Photos



8.2 EUT - Internal Photos






ACN
IR
DANGER!
LOW
DANGER!
RoHS
INVERTER 3.2 POWER V1.42
MCU BOARD




JH-6168
E524507


Model:WBR3
P/N:2.01.99.00006
S/N: 10000938600011
CE
RoHS
WBR3
ANT





======End of Report======