



TEST REPORT

Product Name: Smart Watch
FCC ID: 2BCNP-BS-SWMC
Trademark: BLACK SHARK
Model Number: BS-W2403, BS-W2401, BS-W2402, BS-W2404, BS-W2405, BS-W2406, BS-W2407, BS-W2408, BS-W2409, BS-W2410, BS-W2411, BS-W2412, BS-W2413, BS-W2414, BS-W2415, BS-W2416, BS-W2417, BS-W2418, BS-W2419, BS-W2420, BS-W2421, BS-W2422, BS-W2423, BS-W2424, BS-W2425, BS-W2426, BS-W2427, BS-W2428, BS-W2429, BS-W2430
Prepared For: Blackshark Technologies (Nanchang) Co., Ltd
Address: R1001, F10 of Floor 3-23, R201 of Building 8 and 9, No.528, Shuanggang West Street, Nanchang City, Jiangxi Province, China
Manufacturer: Blackshark Technologies (Nanchang) Co., Ltd
Address: R1001, F10 of Floor 3-23, R201 of Building 8 and 9, No.528, Shuanggang West Street, Nanchang City, Jiangxi Province, China
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.
Address: 1&2/F., Building A, No.26, Xinxhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: May. 13, 2024
Sample tested Date: May. 13, 2024 to May. 25, 2024
Issue Date: May. 25, 2024
Report No.: CTB240530032RF
Test Standards: FCC Part 22H & 24E
Test Results: PASS
Remark: This is GSM radio test report.

Compiled by:

Reviewed by:

Approved by:

Zhou kui

Arron Liu



Zhou Kui

Arron Liu

Bin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.

TABLE OF CONTENT

Test Report Declaration	Page
1. VERSION	4
2. TEST SUMMARY	5
3. MEASUREMENT UNCERTAINTY	6
4. PRODUCT INFORMATION AND TEST SETUP	7
4.1 Product Information	7
4.2 Test Setup Configuration	8
4.3 Support Equipment	8
4.4 Channel List	9
4.5 Test Mode	9
4.6 Test Environment	10
5. TEST FACILITY AND TEST INSTRUMENT USED	11
5.1 Test Facility	11
5.2 Test Instrument Used	11
6. RF OUTPUT POWER	13
6.1 Standard Applicable	13
6.2 Test Procedure	13
6.3 Environmental Conditions	13
6.4 Summary of Test Results/Plots	14
7. PEAK-TO-AVERAGE RATIO(PAR) OF TRANSMITTER	22
7.1 Standard Applicable	22
7.2 Test Procedure	22
7.3 Environmental Conditions	22
7.4 Summary of Test Results	23
8. EMISSION BANDWIDTH	25
8.1 Standard Applicable	25
8.2 Test Procedure	25
8.3 Environmental Conditions	25
8.4 Summary of Test Results/Plots	26
9. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL	40
9.1 Standard Applicable	40
9.2 Test Procedure	40
9.3 Environmental Conditions	40
9.4 Summary of Test Results/Plots	41
10. SPURIOUS RADIATED EMISSIONS	65
10.1 Standard Applicable	65
10.2 Test Procedure	65
10.3 Environmental Conditions	65
10.4 Summary of Test Results/Plots	66
11. FREQUENCY STABILITY	70
11.1 Standard Applicable	70
11.2 Test Procedure	70



11.3	Environmental Conditions	70
11.4	Summary of Test Results/Plots	71
12.	EUT TEST PHOTO	82

(Note: N/A means not applicable)



1. **VERSION**

Report No.	Issue Date	Description	Approved
CTB240530032RF	May. 25, 2024	Original	Valid

2. TEST SUMMARY

The Product has been tested according to the following specifications:

FCC Rules	Description of Test Item	Result
§1.1307, §2.1091	RF Exposure	Compliant
§22.913 (a), §24.232 (c)	RF Output Power	Compliant
§24.51	Peak-to-average Ratio(PAR) of Transmitter	Compliant
§22.917 (b), §24.238 (b)	Emission Bandwidth	Compliant
§22.917 (a), §24.238 (a)	Spurious Emissions at Antenna Terminal	Compliant
§22.917 (a), §24.238 (a)	Spurious Radiation Emissions	Compliant
§22.917 (a), §24.238 (a)	Out of Band Emissions	Compliant
§22.355, §24.235	Frequency Stability	Compliant

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Item	Uncertainty
Occupancy bandwidth	54.3kHz
Conducted output power Above 1G	0.9dB
Conducted output power below 1G	0.9dB
Power Spectral Density , Conduction	0.9dB
Conduction spurious emissions	2.0dB
Out of band emission	2.0dB
3m chamber Radiated spurious emission(30MHz-1GHz)	4.6dB
3m chamber Radiated spurious emission(1GHz-18GHz)	5.1dB
3m chamber Radiated spurious emission(18GHz-40GHz)	3.4dB
Receiver Reference Sensitivity level	1.9dB
humidity uncertainty	5.5%
Temperature uncertainty	0.63°C
frequency	1×10 ⁻⁷

4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Model(s):	BS-W2403, BS-W2401, BS-W2402, BS-W2404, BS-W2405, BS-W2406, BS-W2407, BS-W2408, BS-W2409, BS-W2410, BS-W2411, BS-W2412, BS-W2413, BS-W2414, BS-W2415, BS-W2416, BS-W2417, BS-W2418, BS-W2419, BS-W2420, BS-W2421, BS-W2422, BS-W2423, BS-W2424, BS-W2425, BS-W2426, BS-W2427, BS-W2428, BS-W2429, BS-W2430
Model Description:	All the model are the same circuit and RF module, only for model name. Test sample model: BS-W2403
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE 1900: 1850~1910MHz WCDMA Band 2: 1850~1910MHz WCDMA Band 5: 824~849MHz
Max. RF output power:	GSM850: 30.97dBm GSM1900: 28.53dBm WCDMA Band 2: 21.66dBm WCDMA Band 5: 22.37dBm
Type of Modulation:	GMSK, BPSK
Antenna installation:	Internal antenna
Antenna Gain:	GSM850: -2.45dBi, GSM1900: 1.36dBi WCDMA Band 2: 1.36dBi WCDMA Band 5: -2.45dBi
Ratings:	DC 5V charging from adapter DC 3.7V by Battery

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 Support Equipment

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Adapter	JYIN	JY-05100C	/	/

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EDGE	824.2 MHz	128
		836.6 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EDGE	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
WCDMA Band 5	WCDMA/HSDPA/HSUPA	826.4 MHz	4132
		836.6 MHz	4183
		846.6 MHz	4233
WCDMA Band 2	WCDMA/HSDPA/HSUPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538
Note: the transmitter has been tested on the communications mode of GSM, GPRS, EDGE, WCDMA, HSDPA, HSUPA compliance test and record the worst case.			

4.5 Test Mode

Test Mode List		
Test Mode	Description	Remark
TM1	GSM 850	Low, Middle, High Channels
TM2	GPRS 850	Low, Middle, High Channels
TM3	EDGE 850	Low, Middle, High Channels
TM4	GSM 1900	Low, Middle, High Channels
TM5	GPRS 1900	Low, Middle, High Channels
TM6	EDGE 1900	Low, Middle, High Channels
TM7	WCDMA Band 5	Low, Middle, High Channels
TM8	HSDPA Band 5	Low, Middle, High Channels
TM9	HSUPA Band 5	Low, Middle, High Channels
TM10	WCDMA Band 2	Low, Middle, High Channels
TM11	HSDPA Band 2	Low, Middle, High Channels
TM12	HSUPA Band 2	Low, Middle, High Channels



4.6 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(DC):	3.7V
Normal Temperature(°C)	23
Low Temperature(°C)	0
High Temperature(°C)	40

5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at 1&2F., Building A, No. 26, Xinghe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

5.2 Test Instrument Used

No.	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	A.14.16	2024.07.05
2	Power Sensor	Agilent	U2021XA	MY56120032	/	2024.07.05
3	Power Sensor	Agilent	U2021XA	MY56120034	/	2024.07.05
4	Communication test set	R&S	CMW500	108058	V3.5.80	2024.07.05
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2024.07.05
6	Signal Generator	Agilent	N5181A	MY50140365	A.01.60	2024.07.05
7	Vector signal generator	Agilent	N5182A	MY47420195	A.01.87	2024.07.05
8	Communication test set	Agilent	E5515C	MY50102567	B.19.07 (E1962B)	2024.07.06
9	2.4 GHz Filter	Shenxiang	MSF2400-24 83.5MS-1154	20181015001	/	2024.07.05
10	5 GHz Filter	Shenxiang	MSF5150-58 50MS-1155	20181015001	/	2024.07.06
11	Filter	Xingbo	XBLBQ-DZA 120	190821-1-1	/	2024.07.06
12	BT&WI-FI Automatic test software	Microwave	MTS8000	Ver. 2.0.0.0	/	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	/	2024.10.30
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	/	2024.07.05
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/	/
16	966 chamber	C.R.T.	966	/	/	2024.08.11
17	Receiver	R&S	ESPI	100362	RF_ATTEN_7 (104489/003)	2024.07.05
18	Amplifier	HP	8447E	2945A02747	/	2024.07.05
19	Amplifier	Agilent	8449B	3008A01838	/	2024.07.05
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2024.07.08



21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	/	2024.07.08
22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2024.07.08
24	loop antenna	ZHINAN	ZN30900A	GTS534	/	/
25	40G Horn antenna	A/H/System	SAS-574	588	/	2024.10.30
26	Amplifier	AEROFLEX	Aeroflex	097	/	2024.07.05

6. RF OUTPUT POWER


6.1 Standard Applicable

According to §22.913(a)(2), The ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

6.2 Test Procedure

Conducted output power test method:



Radiated power test method:

- 1.The setup of EUT is according with per ANSI/TIA Standard 603D and ANSI C63.4-2014 measurement procedure.
- 2.The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
- 3.The frequency range up to tenth harmonic of the fundamental frequency was investigated.
- 4.Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

6.3 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	54%
ATM Pressure:	1010 mbar

6.4 Summary of Test Results/Plots

Max. Radiated Power

ERP For GSM Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	30.01	1.5	0	H	1.5	-2.45	26.06	38.45
824.2	30.69	1.5	0	V	1.5	-2.45	26.74	38.45
Middle Channel								
836.6	30.38	1.5	0	H	1.5	-2.45	26.43	38.45
836.6	30.31	1.5	0	V	1.5	-2.45	26.36	38.45
High Channel								
848.8	30.53	1.5	0	H	1.5	-2.45	26.58	38.45
848.8	30.54	1.5	0	V	1.5	-2.45	26.59	38.45

EIRP For GSM Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
1850.2	27.62	1.5	0	H	1.9	1.36	27.08	33
1850.2	28.03	1.5	0	V	1.9	1.36	27.49	33
Middle Channel								
1880	27.44	1.5	0	H	1.9	1.36	26.90	33
1880	27.31	1.5	0	V	1.9	1.36	26.77	33
High Channel								
1909.8	27.75	1.5	0	H	1.9	1.36	27.21	33
1909.8	27.10	1.5	0	V	1.9	1.36	26.56	33



ERP For GPRS Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	30.12	1.5	0	H	1.5	-2.45	26.17	38.45
824.2	30.26	1.5	0	V	1.5	-2.45	26.31	38.45
Middle Channel								
836.6	30.25	1.5	0	H	1.5	-2.45	26.30	38.45
836.6	30.76	1.5	0	V	1.5	-2.45	26.81	38.45
High Channel								
848.8	30.27	1.5	0	H	1.5	-2.45	26.32	38.45
848.8	30.03	1.5	0	V	1.5	-2.45	26.08	38.45

EIRP For GPRS Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
1850.2	28.32	1.5	0	H	1.9	1.36	27.78	33
1850.2	27.66	1.5	0	V	1.9	1.36	27.12	33
Middle Channel								
1880	27.93	1.5	0	H	1.9	1.36	27.39	33
1880	27.37	1.5	0	V	1.9	1.36	26.83	33
High Channel								
1909.8	27.77	1.5	0	H	1.9	1.36	27.23	33
1909.8	26.90	1.5	0	V	1.9	1.36	26.36	33



ERP For EDGE Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	30.81	1.5	0	H	1.5	-2.45	26.86	38.45
824.2	30.79	1.5	0	V	1.5	-2.45	26.84	38.45
Middle Channel								
836.6	30.74	1.5	0	H	1.5	-2.45	26.79	38.45
836.6	30.61	1.5	0	V	1.5	-2.45	26.66	38.45
High Channel								
848.8	30.85	1.5	0	H	1.5	-2.45	26.90	38.45
848.8	30.03	1.5	0	V	1.5	-2.45	26.08	38.45

EIRP For EDGE Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
1850.2	27.73	1.5	0	H	1.9	1.36	27.19	33
1850.2	27.61	1.5	0	V	1.9	1.36	27.07	33
Middle Channel								
1880	27.61	1.5	0	H	1.9	1.36	27.07	33
1880	27.40	1.5	0	V	1.9	1.36	26.86	33
High Channel								
1909.8	27.08	1.5	0	H	1.9	1.36	26.54	33
1909.8	27.32	1.5	0	V	1.9	1.36	26.78	33



ERP For WCDMA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	21.51	1.5	0	H	1.5	-2.45	17.56	38.45
826.4	21.77	1.5	0	V	1.5	-2.45	17.82	38.45
Middle Channel								
836.6	21.77	1.5	0	H	1.5	-2.45	17.82	38.45
836.6	21.67	1.5	0	V	1.5	-2.45	17.72	38.45
High Channel								
846.6	22.06	1.5	0	H	1.5	-2.45	18.11	38.45
846.6	21.80	1.5	0	V	1.5	-2.45	17.85	38.45

ERP For HSDPA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	21.59	1.5	0	H	1.5	-2.45	17.64	38.45
826.4	21.45	1.5	0	V	1.5	-2.45	17.50	38.45
Middle Channel								
836.6	21.53	1.5	0	H	1.5	-2.45	17.58	38.45
836.6	20.94	1.5	0	V	1.5	-2.45	16.99	38.45
High Channel								
846.6	20.63	1.5	0	H	1.5	-2.45	16.68	38.45
846.6	20.97	1.5	0	V	1.5	-2.45	17.02	38.45

ERP For HSUPA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	21.65	1.5	0	H	1.5	-2.45	17.70	38.45
826.4	21.74	1.5	0	V	1.5	-2.45	17.79	38.45
Middle Channel								
836.6	21.08	1.5	0	H	1.5	-2.45	17.13	38.45
836.6	21.21	1.5	0	V	1.5	-2.45	17.26	38.45
High Channel								
846.6	21.17	1.5	0	H	1.5	-2.45	17.22	38.45
846.6	20.44	1.5	0	V	1.5	-2.45	16.49	38.45

EIRP For WCDMA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
1852.4	19.91	1.5	0	H	1.9	1.36	19.37	33
1852.4	20.01	1.5	0	V	1.9	1.36	19.47	33
Middle Channel								
1880	19.50	1.5	0	H	1.9	1.36	18.96	33
1880	19.03	1.5	0	V	1.9	1.36	18.49	33
High Channel								
1907.6	20.89	1.5	0	H	1.9	1.36	20.35	33
1907.6	19.16	1.5	0	V	1.9	1.36	18.62	33

EIRP For HSDPA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
1852.4	22.08	1.5	0	H	1.9	1.36	21.54	33
1852.4	21.57	1.5	0	V	1.9	1.36	21.03	33
Middle Channel								
1880	21.34	1.5	0	H	1.9	1.36	20.80	33
1880	22.54	1.5	0	V	1.9	1.36	22.00	33
High Channel								
1907.6	21.23	1.5	0	H	1.9	1.36	20.69	33
1907.6	20.64	1.5	0	V	1.9	1.36	20.10	33



EIRP For HSUPA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
1852.4	21.94	1.5	0	H	1.9	1.36	21.40	33
1852.4	21.19	1.5	0	V	1.9	1.36	20.65	33
Middle Channel								
1880	22.05	1.5	0	H	1.9	1.36	21.51	33
1880	22.47	1.5	0	V	1.9	1.36	21.93	33
High Channel								
1907.6	20.43	1.5	0	H	1.9	1.36	19.89	33
1907.6	21.30	1.5	0	V	1.9	1.36	20.76	33

Note: Result = Substitute - Cable loss + Antenna Gain

**Max. Conducted Output Power**

For Cellular Band (GSM850)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
GSM	Low Channel	824.2	30.97	38.45
	Middle Channel	836.6	30.82	38.45
	High Channel	848.8	30.81	38.45
GPRS(1 Slot)	Low Channel	824.2	30.96	38.45
	Middle Channel	836.6	30.80	38.45
	High Channel	848.8	30.80	38.45
EDGE(1 Slot)	Low Channel	824.2	30.97	38.45
	Middle Channel	836.6	30.83	38.45
	High Channel	848.8	30.85	38.45

For PCS Band (GSM1900)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
GSM	Low Channel	1850.2	28.46	33.0
	Middle Channel	1880.0	28.20	33.0
	High Channel	1909.8	27.80	33.0
GPRS(1 Slot)	Low Channel	1850.2	28.44	33.0
	Middle Channel	1880.0	28.23	33.0
	High Channel	1909.8	27.83	33.0
EDGE(1 Slot)	Low Channel	1850.2	28.53	33.0
	Middle Channel	1880.0	28.30	33.0
	High Channel	1909.8	27.89	33.0

For WCDMA Band 5

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
WCDMA	Low Channel	826.4	22.06	38.45
	Middle Channel	836.6	22.18	38.45
	High Channel	846.6	22.37	38.45
HSDPA	Low Channel	826.4	21.99	38.45
	Middle Channel	836.6	21.78	38.45
	High Channel	846.6	21.61	38.45
HSUPA	Low Channel	826.4	21.81	38.45
	Middle Channel	836.6	21.57	38.45
	High Channel	846.6	21.31	38.45

For WCDMA Band 2

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
WCDMA	Low Channel	1852.4	21.65	33.00
	Middle Channel	1880.0	21.64	33.00
	High Channel	1907.6	21.45	33.00
HSDPA	Low Channel	1852.4	21.66	33.00
	Middle Channel	1880.0	21.58	33.00
	High Channel	1907.6	21.51	33.00
HSUPA	Low Channel	1852.4	21.49	33.00
	Middle Channel	1880.0	21.50	33.00
	High Channel	1907.6	21.36	33.00

7. PEAK-TO-AVERAGE RATIO(PAR) OF TRANSMITTER


7.1 Standard Applicable

According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

7.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded. Record the maximum PAPR level associated with a probability of 0.1%.

Test Configuration for the emission bandwidth testing:



7.3 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	54%
ATM Pressure:	1010 mbar

7.4 Summary of Test Results

Only the worst case was selected to record
For GSM850

Test Mode	Channel	Frequency (MHz)	PAR (dB)	Limit (dB)
GSM	190	836.6	2.81	13
GPRS(1 Slot)	190	836.6	2.83	13
EDGE(1 Slot)	190	836.6	2.83	13

For PCS 1900

Test Mode	Channel	Frequency (MHz)	PAR (dB)	Limit (dB)
GSM	512	1850.2	2.82	13
GPRS(1 Slot)	512	1850.2	2.86	13
EDGE(1 Slot)	512	1850.2	2.85	13

For WCDMA Band 5

Test Mode	Channel	Frequency (MHz)	PAR (dB)	Limit (dB)
WCDMA	4182	836.4	2.86	13
HSDPA	4182	836.4	4.42	13
HSUPA	4182	836.4	3.99	13

For WCDMA Band 2

Test Mode	Channel	Frequency (MHz)	PAR (dB)	Limit (dB)
WCDMA	9262	1880	3.01	13
HSDPA	9400	1880	4.48	13
HSUPA	9400	1880	4.04	13

GSM :



WCDMA:



8. EMISSION BANDWIDTH

8.1 Standard Applicable


According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

8.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 10kHz for GSM mode and 100kHz for WCDMA mode, VBW shall be at least 3 times the RBW, and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



8.3 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	54%
ATM Pressure:	1010 mbar

8.4 Summary of Test Results/Plots

For Cellular Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	128	824.2	248.152	321.098
	190	836.6	247.029	303.658
	251	848.8	249.860	317.377
GPRS	128	824.2	239.124	304.036
	190	836.6	242.367	322.020
	251	848.8	239.664	322.041
EDGE	128	824.2	240.749	318.211
	190	836.6	243.921	314.498
	251	848.8	245.743	326.318

For PCS Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	512	1850.2	241.483	297.914
	661	1880.0	246.389	317.326
	810	1909.8	247.478	319.208
GPRS	512	1850.2	248.255	311.572
	661	1880.0	227.387	311.420
	810	1909.8	251.950	318.934
EDGE	512	1850.2	244.340	317.489
	661	1880.0	249.247	321.077
	810	1909.8	251.639	319.581

For Band 5

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
WCDMA	4132	826.4	4148.701	4638.206
	4183	836.6	4159.215	4672.133
	4233	846.6	4153.296	4679.089
HSDPA	4132	826.4	4158.074	4659.264
	4183	836.6	4147.317	4664.471
	4233	846.6	4160.868	4650.901
HSUPA	4132	826.4	4158.269	4671.794
	4183	836.6	4159.228	4651.213
	4233	846.6	4149.142	4664.390

For Band 2


Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
WCDMA	9262	1852.4	4157.226	4652.647
	9400	1880.0	4163.276	4653.499
	9538	1907.6	4140.665	4678.794
HSDPA	9262	1852.4	4167.293	4667.309
	9400	1880.0	4183.760	4664.785
	9538	1907.6	4137.472	4648.842
HSUPA	9262	1852.4	4141.101	4686.406
	9400	1880.0	4160.187	4671.222
	9538	1907.6	4145.959	4668.403

For Cellular Band


GSM Low Channel



GSM Middle Channel




GSM High Channel




GPRS Low Channel



GPRS Middle Channel



GPRS High Channel




EDGE Low Channel



EDGE Middle Channel




EDGE High Channel




For PCS Band


GSM Low Channel




GSM Middle Channel



GSM High Channel



GPRS Low Channel




GPRS Middle Channel




GPRS High Channel



EDGE Low Channel




EDGE Middle Channel




EDGE High Channel




For Band V



HSDPA Low Channel




HSDPA Middle Channel




HSDPA High Channel




HSUPA Low Channel




HSUPA Middle Channel




HSUPA High Channel




For Band II




HSDPA Low Channel




HSDPA Middle Channel




HSDPA High Channel




HSUPA Low Channel



HSUPA Middle Channel



HSUPA High Channel



9. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL

9.1 Standard Applicable


According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

9.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10th harmonic.

Test Configuration for the out of band emissions testing:






9.3 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	54%
ATM Pressure:	1010 mbar


9.4 Summary of Test Results/Plots

Please refer to the following test plots


For Cellular Band




GSM Low Channel	
GSM Middle Channel	
GSM High Channel	

GSM
Low
Band
Emission




GSM
High
Band
Emission







GPRS Low Channel		
GPRS Middle Channel		
GPRS High Channel		

GPRS
Low
Band
Emission



GPRS
High
Band
Emission



EDGE Low Channel	 <table><tr><th>MKR</th><th>FREQ</th><th>POWER</th></tr><tr><td>1</td><td>824.86 MHz</td><td>31.726 dBm</td></tr><tr><td>2</td><td>2.51826 GHz</td><td>-30.117 dBm</td></tr></table>	MKR	FREQ	POWER	1	824.86 MHz	31.726 dBm	2	2.51826 GHz	-30.117 dBm
MKR	FREQ	POWER								
1	824.86 MHz	31.726 dBm								
2	2.51826 GHz	-30.117 dBm								
EDGE Middle Channel	 <table><tr><th>MKR</th><th>FREQ</th><th>POWER</th></tr><tr><td>1</td><td>837.32 MHz</td><td>31.502 dBm</td></tr><tr><td>2</td><td>7.84324 GHz</td><td>-29.979 dBm</td></tr></table>	MKR	FREQ	POWER	1	837.32 MHz	31.502 dBm	2	7.84324 GHz	-29.979 dBm
MKR	FREQ	POWER								
1	837.32 MHz	31.502 dBm								
2	7.84324 GHz	-29.979 dBm								
EDGE High Channel	 <table><tr><th>MKR</th><th>FREQ</th><th>POWER</th></tr><tr><td>1</td><td>849.28 MHz</td><td>31.710 dBm</td></tr><tr><td>2</td><td>5.92950 GHz</td><td>-30.266 dBm</td></tr></table>	MKR	FREQ	POWER	1	849.28 MHz	31.710 dBm	2	5.92950 GHz	-30.266 dBm
MKR	FREQ	POWER								
1	849.28 MHz	31.710 dBm								
2	5.92950 GHz	-30.266 dBm								




EDGE
Low
Band
Emission




EDGE
High
Band
Emission




For PCS Band




GSM Low Channel		
GSM Middle Channel		
GSM High Channel		

GSM
Low
Band
Emission






GSM
High
Band
Emission




GPRS Low Channel		
GPRS Middle Channel		
GPRS High Channel		


GPRS Low Band Emission		
GPRS High Band Emission		

EDGE Low Channel	 Agilent Spectrum Analyzer - Sweep SA Center Freq 10.01500000 GHz Ref Offset 7.71 dB Ref 30.00 dBm Mkr1 1.850 8 GHz 29.421 dBm Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20.000 GHz Sweep 50.67 ms (40001 pts) <table><tr><th>MNR</th><th>MODE</th><th>TYPE</th><th>SOL</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>1.850 8 GHz</td><td></td><td></td><td>29.421 dBm</td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>16.519 7 GHz</td><td></td><td></td><td>-22.268 dBm</td></tr></table>	MNR	MODE	TYPE	SOL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	1.850 8 GHz			29.421 dBm	2	N	1	f	16.519 7 GHz			-22.268 dBm	
MNR	MODE	TYPE	SOL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																			
1	N	1	f	1.850 8 GHz			29.421 dBm																			
2	N	1	f	16.519 7 GHz			-22.268 dBm																			
EDGE Middle Channel	 Agilent Spectrum Analyzer - Sweep SA Center Freq 10.01500000 GHz Ref Offset 7.52 dB Ref 30.00 dBm Mkr1 1.880 2 GHz 29.228 dBm Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20.000 GHz Sweep 50.67 ms (40001 pts) <table><tr><th>MNR</th><th>MODE</th><th>TYPE</th><th>SOL</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>1.880 2 GHz</td><td></td><td></td><td>29.228 dBm</td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>1.960 1 GHz</td><td></td><td></td><td>-21.861 dBm</td></tr></table>	MNR	MODE	TYPE	SOL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	1.880 2 GHz			29.228 dBm	2	N	1	f	1.960 1 GHz			-21.861 dBm	
MNR	MODE	TYPE	SOL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																			
1	N	1	f	1.880 2 GHz			29.228 dBm																			
2	N	1	f	1.960 1 GHz			-21.861 dBm																			
EDGE High Channel	 Agilent Spectrum Analyzer - Sweep SA Center Freq 10.01500000 GHz Ref Offset 7.42 dB Ref 30.00 dBm Mkr1 1.910 2 GHz 28.902 dBm Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20.000 GHz Sweep 50.67 ms (40001 pts) <table><tr><th>MNR</th><th>MODE</th><th>TYPE</th><th>SOL</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>1.910 2 GHz</td><td></td><td></td><td>28.902 dBm</td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>16.592 8 GHz</td><td></td><td></td><td>-23.406 dBm</td></tr></table>	MNR	MODE	TYPE	SOL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	1.910 2 GHz			28.902 dBm	2	N	1	f	16.592 8 GHz			-23.406 dBm	
MNR	MODE	TYPE	SOL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																			
1	N	1	f	1.910 2 GHz			28.902 dBm																			
2	N	1	f	16.592 8 GHz			-23.406 dBm																			




EDGE
Low
Band
Emission



EDGE
High
Band
Emission



For Band V




WCDMA Low Channel	 <table><tr><th>MNR</th><th>MODE</th><th>FREQ</th><th>SQL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>828.10 MHz</td><td>22.615 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>6.093.77 GHz</td><td>-29.985 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	FREQ	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	828.10 MHz	22.615 dBm				2	N	1	f	6.093.77 GHz	-29.985 dBm				
MNR	MODE	FREQ	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																					
1	N	1	f	828.10 MHz	22.615 dBm																								
2	N	1	f	6.093.77 GHz	-29.985 dBm																								
WCDMA Middle Channel	 <table><tr><th>MNR</th><th>MODE</th><th>FREQ</th><th>SQL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>836.32 MHz</td><td>22.882 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>7.338.01 GHz</td><td>-30.055 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	FREQ	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	836.32 MHz	22.882 dBm				2	N	1	f	7.338.01 GHz	-30.055 dBm				
MNR	MODE	FREQ	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																					
1	N	1	f	836.32 MHz	22.882 dBm																								
2	N	1	f	7.338.01 GHz	-30.055 dBm																								
WCDMA High Channel	 <table><tr><th>MNR</th><th>MODE</th><th>FREQ</th><th>SQL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>846.28 MHz</td><td>22.828 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>6.926.75 GHz</td><td>-30.072 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	FREQ	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	846.28 MHz	22.828 dBm				2	N	1	f	6.926.75 GHz	-30.072 dBm				
MNR	MODE	FREQ	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																					
1	N	1	f	846.28 MHz	22.828 dBm																								
2	N	1	f	6.926.75 GHz	-30.072 dBm																								

WCDMA
Low
Band
Spurious
Emission



WCDMA
High
Band
Spurious
Emission






HSDPA Low Channel		
HSDPA Middle Channel		
HSDPA High Channel		

HSDPA
Low
Band
Spurious
Emission



HSDPA
High
Band
Spurious
Emission



HSUPA Low Channel	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.015000000 GHz Ref Offset 6.52 dB Ref 30.00 dBm Mkr1 827.85 MHz 22.575 dBm Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 10.000 GHz Sweep 18.67 ms (40001 pts) <table><tr><th>MNR</th><th>MODE</th><th>TRF</th><th>SOL</th><th>F</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>827.85 MHz</td><td>22.575 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>3.091.64 GHz</td><td>-29.467 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRF	SOL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	827.85 MHz	22.575 dBm				2	N	1	f	3.091.64 GHz	-29.467 dBm			
MNR	MODE	TRF	SOL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																				
1	N	1	f	827.85 MHz	22.575 dBm																							
2	N	1	f	3.091.64 GHz	-29.467 dBm																							
HSUPA Middle Channel	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.015000000 GHz Ref Offset 6.52 dB Ref 30.00 dBm Mkr1 837.82 MHz 22.624 dBm Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 10.000 GHz Sweep 18.67 ms (40001 pts) <table><tr><th>MNR</th><th>MODE</th><th>TRF</th><th>SOL</th><th>F</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>837.82 MHz</td><td>22.624 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>5.651.68 GHz</td><td>-29.750 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRF	SOL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	837.82 MHz	22.624 dBm				2	N	1	f	5.651.68 GHz	-29.750 dBm			
MNR	MODE	TRF	SOL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																				
1	N	1	f	837.82 MHz	22.624 dBm																							
2	N	1	f	5.651.68 GHz	-29.750 dBm																							
HSUPA High Channel	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.015000000 GHz Ref Offset 6.52 dB Ref 30.00 dBm Mkr1 846.64 MHz 22.484 dBm Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 10.000 GHz Sweep 18.67 ms (40001 pts) <table><tr><th>MNR</th><th>MODE</th><th>TRF</th><th>SOL</th><th>F</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>846.64 MHz</td><td>22.484 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>6.146.84 GHz</td><td>-29.966 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRF	SOL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	846.64 MHz	22.484 dBm				2	N	1	f	6.146.84 GHz	-29.966 dBm			
MNR	MODE	TRF	SOL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																				
1	N	1	f	846.64 MHz	22.484 dBm																							
2	N	1	f	6.146.84 GHz	-29.966 dBm																							




HSUPA
Low
Band
Spurious
Emission



HSUPA
High
Band
Spurious
Emission



For Band II

WCDMA Low Channel	 Agilent Spectrum Analyzer - Sweep SA Center Freq 10.015000000 GHz Ref Offset 7.7 dB Ref 30.00 dBm Mkr1 1.8543 GHz 22.641 dBm Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20,000 GHz Sweep 50.67 ms (40001 pts) <table><tr><th>MNR</th><th>MODE</th><th>TRF</th><th>SQL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>1.8543 GHz</td><td>22.641 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>19.1458 GHz</td><td>-23.151 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRF	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	1.8543 GHz	22.641 dBm				2	N	1	f	19.1458 GHz	-23.151 dBm			
MNR	MODE	TRF	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																				
1	N	1	f	1.8543 GHz	22.641 dBm																							
2	N	1	f	19.1458 GHz	-23.151 dBm																							
WCDMA Middle Channel	 Agilent Spectrum Analyzer - Sweep SA Center Freq 10.015000000 GHz Ref Offset 7.52 dB Ref 30.00 dBm Mkr1 1.8817 GHz 22.825 dBm Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20,000 GHz Sweep 50.67 ms (40001 pts) <table><tr><th>MNR</th><th>MODE</th><th>TRF</th><th>SQL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>1.8817 GHz</td><td>22.825 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>16.5788 GHz</td><td>-22.773 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRF	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	1.8817 GHz	22.825 dBm				2	N	1	f	16.5788 GHz	-22.773 dBm			
MNR	MODE	TRF	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																				
1	N	1	f	1.8817 GHz	22.825 dBm																							
2	N	1	f	16.5788 GHz	-22.773 dBm																							
WCDMA High Channel	 Agilent Spectrum Analyzer - Sweep SA Center Freq 10.015000000 GHz Ref Offset 7.42 dB Ref 30.00 dBm Mkr1 1.9067 GHz 22.350 dBm Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20,000 GHz Sweep 50.67 ms (40001 pts) <table><tr><th>MNR</th><th>MODE</th><th>TRF</th><th>SQL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>1.9067 GHz</td><td>22.350 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>16.4628 GHz</td><td>-23.415 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRF	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	1.9067 GHz	22.350 dBm				2	N	1	f	16.4628 GHz	-23.415 dBm			
MNR	MODE	TRF	SQL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																				
1	N	1	f	1.9067 GHz	22.350 dBm																							
2	N	1	f	16.4628 GHz	-23.415 dBm																							


WCDMA
Low
Band
Spurious
Emission




WCDMA
High
Band
Spurious
Emission




HSDPA
Low
Channel



HSDPA
Middle
Channel



HSDPA
High
Channel




HSDPA
Low
Band
Spurious
Emission



HSDPA
High
Band
Spurious
Emission




HSUPA
Low
Channel



HSUPA
Middle
Channel



HSUPA
High
Channel



HSUPA
Low
Band
Spurious
Emission



HSUPA
High
Band
Spurious
Emission



10. SPURIOUS RADIATED EMISSIONS

10.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

10.2 Test Procedure

- 1.The setup of EUT is according with per ANSI/TIA Standard 603D and ANSI C63.4-2014 measurement procedure.
- 2.The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
- 3.The frequency range up to tenth harmonic of the fundamental frequency was investigated.
- 4.Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB = $43 + 10 \log_{10}(\text{power out in Watts})$

10.3 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	54%
ATM Pressure:	101 kPa
Test Voltage	DC6.4V

10.4 Summary of Test Results/Plots

According to the data below, the FCC Part22.917 and 24.238 standards, and had the worst margin of:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes are performed, but only the worst case is recorded in this report.

For Cellular Band GSM850 Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (824.2MHz)						
45.36	-73.14	3.9	-69.24	-13	-56.24	H
1647.91	-56.67	4.83	-51.84	-13	-38.84	H
2465.39	-53.85	8.08	-45.77	-13	-32.77	H
42.78	-75.00	4.02	-70.98	-13	-57.98	V
1646.51	-54.32	4.48	-49.84	-13	-36.84	V
2469.97	-48.01	8.2	-39.81	-13	-26.81	V
Middle Channel (836.6MHz)						
38.49	-72.31	3.84	-68.47	-13	-55.47	H
1670.82	-56.81	4.62	-52.19	-13	-39.19	H
2505.19	-54.84	8.25	-46.59	-13	-33.59	H
43.67	-73.32	4.25	-69.07	-13	-56.07	V
1666.21	-52.53	4.54	-47.99	-13	-34.99	V
2505.35	-50.34	8.35	-41.99	-13	-29.75	V
High Channel (848.8MHz)						
42.60	-66.69	4.22	-70.91	-13	-57.91	H
1697.51	-53.80	4.87	-58.67	-13	-45.67	H
2543.92	-57.30	8.38	-65.68	-13	-52.68	H
44.68	-70.49	4.02	-74.51	-13	-61.51	V
1688.84	-50.51	4.56	-55.07	-13	-42.07	V
2543.71	-56.12	8.41	-64.53	-13	-51.53	V

For PCS Band GSM1900 Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1850.2MHz)						
39.80	-69.68	4.34	-65.34	-13	-52.34	H
3694.85	-57.04	10.54	-46.50	-13	-33.50	H
5542.79	-58.07	13.37	-44.70	-13	-31.70	H
41.82	-71.31	4.34	-66.97	-13	-53.97	V
3696.01	-52.04	10.54	-41.50	-13	-28.50	V
5545.82	-54.81	13.37	-41.44	-13	-28.44	V
Middle Channel (1880MHz)						
42.37	-68.30	4.02	-64.28	-13	-51.28	H
3757.73	-58.59	10.71	-47.88	-13	-34.88	H
5634.59	-58.13	13.73	-44.40	-13	-31.40	H
43.78	-68.78	4.14	-64.64	-13	-51.64	V
3750.29	-51.38	10.22	-41.16	-13	-28.16	V
5639.37	-56.32	13.16	-43.16	-13	-30.16	V
High Channel (1909.8MHz)						
43.64	-72.58	4.02	-68.56	-13	-55.56	H
3818.92	-55.49	4.9	-50.59	-13	-37.59	H
5721.88	-45.19	8.09	-37.10	-13	-24.10	H
37.51	-56.47	4.25	-52.22	-13	-39.22	V
3818.97	-56.65	4.93	-51.72	-13	-38.72	V
5727.70	-59.92	8.43	-51.49	-13	-38.49	V

For Band 5 Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (826.4MHz)						
37.69	-71.19	3.91	-67.28	-13	-54.28	H
1647.37	-55.76	10.56	-45.20	-13	-32.20	H
2471.81	-56.04	13.5	-42.54	-13	-29.54	H
37.72	-74.39	3.93	-70.46	-13	-57.46	V
1649.78	-56.75	10.41	-46.34	-13	-33.34	V
2474.81	-53.54	13.16	-40.38	-13	-27.38	V
Middle Channel (836.6MHz)						
42.72	-70.33	4.02	-66.31	-13	-53.31	H
1667.28	-60.90	4.66	-56.24	-13	-43.24	H
2508.62	-41.82	8.34	-33.48	-13	-20.48	H
36.62	-54.80	4.17	-50.63	-13	-37.63	V
1663.85	-56.62	4.94	-51.68	-13	-38.68	V
2508.96	-59.81	8.19	-51.62	-13	-38.62	V
High Channel (846.6MHz)						
38.40	-74.27	3.87	-70.40	-13	-57.40	H
1684.84	-62.91	4.89	-58.02	-13	-45.02	H
2530.49	-42.77	8.42	-34.35	-13	-21.35	H
41.47	-59.15	3.95	-55.20	-13	-42.20	V
1691.66	-59.59	4.99	-54.60	-13	-41.60	V
2537.25	-65.05	8.12	-56.93	-13	-43.93	V

For Band 2 Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1852.4MHz)						
42.43	-69.71	3.91	-65.80	-13	-52.80	H
1645.46	-50.70	10.56	-40.14	-13	-27.14	H
2471.12	-56.08	13.5	-42.58	-13	-29.58	H
42.81	-71.34	3.93	-67.41	-13	-54.41	V
1652.78	-57.75	10.41	-47.34	-13	-34.34	V
2469.97	-53.48	13.16	-40.32	-13	-27.32	V
Middle Channel (1880MHz)						
40.19	-74.53	4.02	-70.51	-13	-57.51	H
1662.99	-60.25	4.66	-55.59	-13	-42.59	H
2503.73	-42.90	8.34	-34.56	-13	-21.56	H
40.12	-62.78	4.17	-58.61	-13	-45.61	V
1668.90	-56.77	4.94	-51.83	-13	-38.83	V
2508.31	-55.99	8.19	-47.80	-13	-34.80	V
High Channel (1907.6MHz)						
41.27	-66.02	4.02	-62.00	-13	-49.00	H
1689.38	-56.32	4.66	-51.66	-13	-38.66	H
2534.48	-43.47	8.34	-35.13	-13	-22.13	H
44.51	-58.56	4.17	-54.39	-13	-41.39	V
1690.73	-56.29	4.94	-51.35	-13	-38.35	V
2535.80	-56.02	8.19	-47.83	-13	-34.83	V

Note: Result=Reading+ Correct, Margin= Result- Limit

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

11. FREQUENCY STABILITY

11.1 Standard Applicable

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Cellular Band

Frequency range (MHz)	Base, fixed (ppm)	Mobile >3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	N/A	N/A
929 to 960	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

According to §27.54 The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

11.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

11.3 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	101kPa

11.4 Summary of Test Results/Plots

For Cellular Band GSM Mode

Reference Frequency(Middle Channel): 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	8.93	0.01067
40	NV	9.30	0.01112
30	NV	9.75	0.01165
20	NV	9.17	0.01096
10	NV	10.41	0.01244
0	NV	10.76	0.01286
-10	NV	10.16	0.01215
-20	NV	10.96	0.01310
-30	NV	10.99	0.01313

For PCS Band GSM Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	12.79	0.00680
40	NV	13.05	0.00694
30	NV	12.54	0.00667
20	NV	12.40	0.00660
10	NV	12.89	0.00686
0	NV	13.87	0.00738
-10	NV	13.60	0.00723
-20	NV	14.42	0.00767
-30	NV	14.90	0.00792

For Cellular Band GPRS Mode

Reference Frequency(Middle Channel): 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	8.76	0.01047
40	NV	9.41	0.01125
30	NV	9.87	0.01179
20	NV	9.84	0.01177
10	NV	10.10	0.01207
0	NV	10.07	0.01204
-10	NV	10.70	0.01279
-20	NV	11.10	0.01327
-30	NV	11.35	0.01357

For PCS Band GPRS Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	12.18	0.00648
40	NV	13.10	0.00697
30	NV	12.78	0.00680
20	NV	12.62	0.00671
10	NV	13.38	0.00712
0	NV	13.61	0.00724
-10	NV	14.21	0.00756
-20	NV	13.94	0.00741
-30	NV	14.22	0.00756

For Cellular Band EDGE Mode

Reference Frequency(Middle Channel): 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	11.12	0.01330
40	NV	11.50	0.01374
30	NV	11.78	0.01408
20	NV	11.75	0.01404
10	NV	12.06	0.01442
0	NV	11.90	0.01422
-10	NV	12.48	0.01491
-20	NV	12.63	0.01510
-30	NV	13.18	0.01576

For PCS Band EDGE Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	-10.39	-0.00553
40	NV	-9.73	-0.00518
30	NV	-10.02	-0.00533
20	NV	-9.30	-0.00495
10	NV	-9.14	-0.00486
0	NV	-9.24	-0.00491
-10	NV	-9.07	-0.00482
-20	NV	-8.58	-0.00456
-30	NV	-8.19	-0.00436

For WCDMA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	0.43	0.00052
40	NV	0.24	0.00028
30	NV	-0.07	-0.00009
20	NV	0.29	0.00035
10	NV	0.37	0.00045
0	NV	0.42	0.00050
-10	NV	0.78	0.00093
-20	NV	0.80	0.00095
-30	NV	1.58	0.00189

For WCDMA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	-0.48	-0.00057
40	NV	-0.32	-0.00038
30	NV	0.37	0.00044
20	NV	0.59	0.00070
10	NV	0.83	0.00099
0	NV	0.54	0.00065
-10	NV	1.35	0.00162
-20	NV	1.66	0.00198
-30	NV	1.49	0.00178

For HSDPA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	0.28	0.00034
40	NV	0.60	0.00072
30	NV	0.70	0.00084
20	NV	0.58	0.00069
10	NV	1.01	0.00121
0	NV	2.02	0.00241
-10	NV	2.04	0.00243
-20	NV	1.61	0.00193
-30	NV	2.47	0.00295

For HSDPA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	4.74	0.00252
40	NV	4.91	0.00261
30	NV	5.63	0.00299
20	NV	5.86	0.00312
10	NV	5.92	0.00315
0	NV	6.87	0.00365
-10	NV	6.88	0.00366
-20	NV	6.49	0.00345
-30	NV	6.51	0.00346

For HSUPA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	0.89	0.00047
40	NV	0.35	0.00018
30	NV	0.40	0.00021
20	NV	1.01	0.00054
10	NV	1.49	0.00079
0	NV	1.90	0.00101
-10	NV	1.96	0.00104
-20	NV	2.47	0.00131
-30	NV	2.88	0.00153

For HSUPA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	NV	6.37	0.00339
40	NV	6.86	0.00365
30	NV	7.40	0.00393
20	NV	7.63	0.00406
10	NV	7.11	0.00378
0	NV	8.48	0.00451
-10	NV	8.06	0.00429
-20	NV	8.72	0.00464
-30	NV	8.42	0.00448

So, Frequency Stability Versus Input Voltage is:

Reference Frequency(Middle Channel): GSM 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	11.36	0.01358
	NV	10.96	0.01310
	HV	11.83	0.01415
Reference Frequency(Middle Channel): GSM 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	14.54	0.00774
	NV	14.60	0.00777
	HV	14.78	0.00786

Reference Frequency(Middle Channel): GPRS 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	10.96	0.01310
	NV	11.78	0.01408
	HV	11.63	0.01390
Reference Frequency(Middle Channel): GPRS 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	14.48	0.00770
	NV	14.48	0.00770
	HV	14.37	0.00764

Reference Frequency(Middle Channel): EDGE 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	12.42	0.01485
	NV	12.70	0.01518
	HV	13.47	0.01611
Reference Frequency(Middle Channel): EDGE 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	-7.73	-0.00411
	NV	-7.76	-0.00413
	HV	-7.21	-0.00384
Reference Frequency(Middle Channel): WCDMA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	1.03	0.00123
	NV	1.48	0.00177
	HV	1.46	0.00175
Reference Frequency(Middle Channel): WCDMA 1732.4MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	1.60	0.00092
	NV	0.43	0.00025
	HV	1.20	0.00069
Reference Frequency(Middle Channel): WCDMA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	2.41	0.00128
	NV	2.06	0.00109
	HV	3.36	0.00179


Reference Frequency(Middle Channel): HSDPA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	2.06	0.00246
	NV	2.22	0.00265
	HV	2.40	0.00287
Reference Frequency(Middle Channel): HSDPA 1732.4MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	6.02	0.00347
	NV	5.83	0.00336
	HV	6.24	0.00360
Reference Frequency(Middle Channel): HSDPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	6.41	0.00341
	NV	6.83	0.00364
	HV	6.92	0.00368
Reference Frequency(Middle Channel): HSUPA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	2.26	0.00270
	NV	2.68	0.00321
	HV	2.83	0.00338
Reference Frequency(Middle Channel): HSUPA 1732.4MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	5.80	0.00335
	NV	5.61	0.00324
	HV	6.34	0.00366

Reference Frequency(Middle Channel): HSUPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	LV	8.52	0.00453
	NV	8.83	0.00470
	HV	9.40	0.00500


12. EUT TEST PHOTO

Radiated Emission

Below 1G



Above 1G



***** END OF REPORT *****