



TEST REPORT

Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-4904-0113 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR26-SRF0177-A Page (1) of (29)	KCTL
---	--	---

1. Client

- Name : NC& CO., LTD
- Address : 660, Daewangpangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, South Korea
- Date of Receipt : 2026-08-05

2. Use of Report : Certification

3. Name of Product / Model : H1 QHD Infinite / H10-Q1

4. Manufacturer / Country of Origin : NC& CO., LTD / Korea

5. FCC ID : 2BCO9-H10Q1

6. Date of Test : 2026-08-13 to 2026-09-15

7. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing
 (Address: 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)

8. Test method used : FCC Part 15 Subpart E, 15.407

9. Test Result : Refer to the test result in the test report

Affirmation	Tested by Name : Minjung Kim (Signature)	Technical Manager Name : Kwonse Kim (Signature)
-------------	---	--

2026-10-06

Eurofins KCTL Co.,Ltd.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by Eurofins KCTL Co.,Ltd.

Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-4904-0113 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR26-SRF0177-A Page (2) of (29)	
---	---	---

REPORT REVISION HISTORY

Date	Revision	Page No
2026-09-21	Originally issued	-
2026-10-06	Removal of the standard for ISED	All

This report shall not be reproduced except in full, without the written approval of Eurofins KCTL Co.,Ltd. This document may be altered or revised by Eurofins KCTL Co.,Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by Eurofins KCTL Co.,Ltd. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

Note. The report No. KR26-SRF0177 is superseded by the report No. KR26-SRF0177-A.

General remarks for test reports

Statement concerning the uncertainty of the measurement systems used for the tests

(may be required by the product standard or client)

☐ Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

Procedure number, issue date and title:

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

☒ Statement not required by the standard or client used for type testing

CONTENTS

1.	General information	4
2.	Device information	4
2.1.	Frequency/channel operations.....	5
2.2.	RF power setting in TEST SW	5
2.3.	Duty Cycle Factor	5
3.	Antenna requirement	6
4.	Summary of tests	7
5.	Measurement uncertainty	8
6.	Measurement results explanation example	9
7.	Test results	10
7.1.	Maximum conducted output power	10
7.2.	Maximum Power Spectral Density	12
7.3.	26 dB Bandwidth & 99% Bandwidth.....	15
7.4.	Frequency stability.....	18
7.5.	Spurious Emission, Band Edge and Restricted bands.....	20
8.	Measurement equipment.....	29

1. General information

Client : NC& CO., LTD

Address : 660, Daewangpangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, South Korea

Manufacturer : NC& CO., LTD

Address : 660, Daewangpangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, South Korea

Laboratory : Eurofins KCTL Co.,Ltd.

Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea

Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132
 VCCI Registration No. : R-20080, G-20078, C-20059, T-20056
 CAB Identifier: KR0040
 ISED Number: 8035A
 KOLAS No.: KT231

2. Device information

Equipment under test : H1 QHD Infinite

Model : H10-Q1

Modulation technique : WIFI(802.11ac) : DSSS, OFDM

Number of channels : UNII-1 : 4 ch (20 MHz)

Power source : DC 12 ~ 24 V

Antenna specification : Dielectric Chip Antenna

Antenna gain : 2.79 dBi

Frequency range : UNII-1 : 5 180 MHz ~ 5 240 MHz (802.11ac_VHT20)

Software version : V1.00

Hardware version : PRIME_MAIN_V03, PRIME_SUB_QHD_V03

Test device serial No. : H1Q19A0010

Operation temperature : -20 °C ~ 60 °C

2.1. Frequency/channel operations

This device contains the following capabilities:

WLAN 5 GHz(802.11ac_VHT20)

UNII-1

Ch.	Frequency (MHz)
36	5 180
40	5 200
48	5 240

Table 2.1.1. 802.11ac_VHT20

2.2. RF power setting in TEST SW


Test Program	Test Mode	Frequency	RF Power setting value
		[MHz]	
MPTool	802.11ac_VHT20	5 180	47
		5 200	46
		5 240	43

2.3. Duty Cycle Factor

Test mode	Period (ms)	T _{On} time (ms)	Duty cycle		Duty Cycle Factor (dB)
			(Linear)	(%)	
802.11ac_VHT20	2.277	1.272	0.558 6	55.86	2.53

Notes:

1. Duty cycle (Linear) = T_{On} time / Period
2. DCF(Duty cycle factor) = 10log(1/duty cycle)
3. DCF is not compensated to average result if the duty cycle is more than 98%



Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-4904-0113 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR26-SRF0177-A Page (6) of (29)	 KCTL
---	---	---

3. Antenna requirement

Requirement of FCC part section 15.203:

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The transmitter has permanently attached Dielectric Chip Antenna (Internal antenna) on board.
- The E.U.T Complies with the requirement of §15.203, §15.407.



4. Summary of tests

FCC Part section(s)	Parameter	Test Condition	Test results
15.407(a)	Maximum conducted output power	Conducted	Pass
15.407(a)	Maximum power spectral density		Pass
15.407(a)	26 dB Channel Bandwidth		Pass
15.407(e)	6 dB Channel Bandwidth		Pass
15.207(a)	AC Conducted Emissions		Pass
15.407(b), 15.205(a), 15.209(a)	Spurious emission	Radiated	Pass
	Band-edge, restricted band		Pass

Notes:

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst-case emissions.
- According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
- EUT was investigated in three orthogonal orientations X, Y and Z. it was determined that **X** orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in **X** orientation.
- The test procedure(s) in this report were performed in accordance as following.
 - ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024
 - KDB 789033 D02 v02r01
- Based on the baseline scan, the worst-case data rates were:
802.11ac VHT20 mode: MCS0

5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2020.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty ($\pm$)	
Conducted RF Power	0.9 dB	
Conducted spurious emission	1.7 dB	
Radiated Emissions	Below 30 MHz	2.4 dB
	30 MHz to 1 000 MHz	2.6 dB
	1 000 MHz to 18 000 MHz	4.7 dB
	Above 18 000 MHz	4.8 dB
Conducted Emissions	150 kHz to 30 MHz	2.8 dB

6. Measurement results explanation example

The offset level is set in the spectrum analyzer to compensate the RF cable loss factor between EUT conducted output port and spectrum analyzer.

With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Frequency (MHz)	Factor(dB)	Frequency (MHz)	Factor(dB)
30	9.89	9 000	11.74
50	9.41	10 000	11.53
100	9.35	11 000	10.71
200	9.81	12 000	11.56
300	9.90	13 000	11.89
400	9.95	14 000	11.67
500	10.03	15 000	11.98
600	10.22	16 000	12.03
700	10.25	17 000	11.42
800	10.36	18 000	12.09
900	10.36	19 000	12.20
1 000	10.09	20 000	12.34
2 000	10.53	21 000	12.35
3 000	10.79	22 000	11.94
4 000	10.90	23 000	12.59
5 000	11.00	24 000	12.66
6 000	11.02	25 000	12.53
7 000	11.04	26 000	12.92
8 000	11.47	26 500	12.70


Note:

Offset(dB) = RF cable loss(dB) + Attenuator(dB)

7. Test results

7.1. Maximum conducted output power

Test setup



Limit

According to §15.407(a),

Band	EUT category		Conducted output power limit
UNII-1		Outdoor access point	1 W (30 dBm)
		Indoor access point	
		Fixed point-to-point access point	
	√	Client device	250 mW (23.98 dBm)
UNII-2A		-	250 mW or 11 dBm + 10logB ¹⁾
UNII-2C		-	250 mW or 11 dBm + 10logB ¹⁾
UNII-3		-	1 W (30 dBm)

Note:

1) Limit B is the 26 dB emission bandwidth.

Test procedure

ANSI C63.10 - Section 12.4.2.4

KDB 789033 D02 v02r01 - Section E.2.d)

Test settings

Method SA-2 uses trace averaging across ON and OFF times of the EUT transmissions, followed by duty cycle correction. The procedure for this method is as follows:

- Measure the duty cycle D of the transmitter output signal as described in 12.2.
- Set span to encompass the entire 99% OBW of the signal.
- Set RBW = 1 MHz.
- Set VBW ≥ 3 MHz.
- Number of points in sweep ≥ $[2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing ≤ RBW / 2, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto.
- Detector = Power averaging (rms), if available. Otherwise, use sample detector mode.
- Do not use sweep triggering. Allow the sweep to “free run.”
- Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
- Compute power by integrating the spectrum across the 99% OBW of the signal using the instrument's band-power measurement function with band limits set equal to the EBW or OBW band-edges. If the instrument does not have a band-power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 99% OBW of the spectrum.
- Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add $[10 \log (1 / 0.25)] = 6$ dB if the duty cycle is 25%.


Test results

Test mode	Band	Frequency (MHz)	Measured output power			Limit (dBm)
			Reading (dBm)	DCF (dB)	Result (dBm)	
802.11ac VHT20	UNII 1	5 180	2.50	2.53	5.03	23.98
		5 200	2.74		5.27	
		5 240	2.70		5.23	


Note:

- Result (dBm) = Reading (dBm) + D.C.F (dB)


UNII 1 / 802.11ac VHT20 / Low ch.



UNII 1 / 802.11ac VHT20 / Mid ch.




UNII 3 / 802.11a / High ch.



Blank

7.2. Maximum Power Spectral Density

Test setup



Limit

According to §15.407(a),

Band	EUT category		Limit
UNII-1		Outdoor access point	17dBm/MHz
		Indoor access point	
		Fixed point-to-point access point	
	√	Client device	11 dBm /MHz
UNII-2A	-		11 dBm /MHz
UNII-2C	-		11 dBm /MHz
UNII-3	-		30 dBm /500 kHz

Note:

When using transmitting antennas with a directional gain exceeding 6 dBi, the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceed 6 dBi

Test procedure

ANSI C63.10 - Section 12.6, 12.4.2.4

KDB 789033 D02 v02r01 - Section E and F

Test settings (12.6)

Notwithstanding that some regulatory requirements refer to peak power spectral density (PPSD), in some cases the intent is to measure the maximum value of the time average of the power spectral density during a period of continuous transmission. The procedure for this method is as follows:

- Create an average power spectrum for the EUT operating mode being tested by following the instructions in 12.4.2 for measuring maximum conducted output power using a spectrum analyzer or EMI receiver; that is, select the appropriate test method (SA-1, SA-2, SA-3, or their respective alternatives) and apply it up to, but not including, the step labeled, "Compute power...." (This procedure is required even if the maximum conducted output power measurement was performed using the power meter method PM.)
- Use the peak search function on the instrument to find the peak of the spectrum.
- Make the following corrections to the peak value of the spectrum, if applicable:
 - If method SA-2 or SA-2A was used, then add $[10 \log (1 / D)]$, where D is the duty cycle, to the peak of the spectrum.
 - If method SA-3A was used and the linear mode was used in step h) of 12.4.2.7, add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- The result is the PPSD.
- The procedure in item a) through item c) requires the use of 1 MHz resolution bandwidth to satisfy the 1 MHz measurement bandwidth specified by some regulatory authorities.⁸⁵ This requirement also permits use of resolution bandwidths less than 1 MHz "provided that the measured power is integrated to show the total power over the measurement bandwidth" (i.e., 1 MHz). If measurements are performed using a reduced resolution bandwidth and integrated over 1 MHz bandwidth, the following adjustments to the procedures apply:
 - Set $RBW \geq 1 / T$, where T is defined in 12.2 a).
 - Set $VBW \geq [3 \times RBW]$.

- 3) Care shall be taken such that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Test settings (12.4.2.4)

Method SA-2 uses trace averaging across ON and OFF times of the EUT transmissions, followed by duty cycle correction. The procedure for this method is as follows:


- a) Measure the duty cycle D of the transmitter output signal as described in 12.2.
- b) Set span to encompass the entire 99% OBW of the signal.
- c) Set RBW = 1 MHz.
- d) Set VBW $\geq$ 3 MHz.
- e) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- f) Sweep time = auto.
- g) Detector = Power averaging (rms), if available. Otherwise, use sample detector mode.
- h) Do not use sweep triggering. Allow the sweep to “free run.”
- i) Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
- j) Compute power by integrating the spectrum across the 99% OBW of the signal using the instrument’s band-power measurement function with band limits set equal to the EBW or OBW band-edges. If the instrument does not have a band-power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 99% OBW of the spectrum.
- k) Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add $[10 \log (1 / 0.25)] = 6 \text{ dB}$ if the duty cycle is 25%.

Test results

Test mode	Band	Frequency (MHz)	Measured PSD (dBm/MHz)	DCF (dB)	Maximum PSD (dB m/MHz)	Limit (dBm/MHz)
802.11ac VHT20	UNII 1	5 180	-8.40	2.53	-5.87	11.00
		5 200	-8.45		-5.92	
		5 240	-8.95		-6.42	


Note:

1. Maximum PSD(dBm/MHz) = Measured PSD (dBm/MHz) + D.C.F(dB)



7.3. 26 dB Bandwidth & 99% Bandwidth

Test setup



Limit

N/A

Test procedure

ANSI C63.10 - Section 12.5.2, 6.9.3

KDB 789033 D02 v02r01 - Section C.1 (26dB bandwidth), Section D (99% bandwidth)

Test settings

Emission bandwidth for all other bands (or 26 dB Bandwidth)

- Set RBW = Shall be in the range of 1% to 5% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

Occupied bandwidth (or 99% Occupied Bandwidth)

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.


The following procedure shall be used for measuring 99% power bandwidth:

- The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.6.2.
- Step a) through step c) might require iteration to adjust within the specified range.
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used.
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- The occupied bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Test results


Test mode	Band	Frequency(MHz)	26 dB bandwidth (MHz)	99% bandwidth (MHz)
802.11ac VHT20	UNII 1	5 180	21.600	17.755
		5 200	21.500	17.749
		5 240	21.550	17.754

26 dB bandwidth




99% bandwidth


UNII 1 / 802.11ac VHT20 / Low ch.



UNII 1 / 802.11ac VHT20 / Mid ch.




UNII 1 / 802.11ac VHT20 / High ch.



Blank

7.4. Frequency stability

Test setup




Limit

According to §15.407(g),

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

Test procedure


ANSI C63.10 - Section 6.8



Test results

Test band : UNII-1
 Frequency (Hz) : 5 180 000 000


Voltage (%)	Power (V)	Temp. (°C)	Frequency (Hz)	Frequency error (Hz)	Deviation (%)	Limit (MHz)
					(%)	(MHz)
100	12.00	22(Ref.)	5 180 039 160	39 160.000	0.000 756	5 150 ≤ F ≤ 5 250
		-30	5 180 027 770	27 770.000	0.000 536	
		-20	5 180 012 990	12 990.000	0.000 251	
		-10	5 180 015 380	15 380.000	0.000 297	
		0	5 180 018 380	18 380.000	0.000 355	
		10	5 179 998 000	-2 000.000	-0.000 039	
		20	5 179 989 610	-10 390.000	-0.000 201	
		30	5 179 982 420	-17 580.000	-0.000 339	
		40	5 179 981 020	-18 980.000	-0.000 366	
		50	5 180 020 980	20 980.000	0.000 405	
85	10.20	22(Ref.)	5 180 046 950	46 950.000	0.000 906	5 150 ≤ F ≤ 5 250
115	13.80	22(Ref.)	5 180 054 350	54 350.000	0.001 049	




7.5. Spurious Emission, Band Edge and Restricted bands

Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



Limit

According to section 15.209(a),

except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength ($\mu\text{V}/\text{m}$)	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section 15.231 and 15.241.

According to section 15.205(a) and (b),

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 - 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 - 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 - 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525 25	2 483.5 - 2 500	17.7 - 21.4
8.376 25 - 8.386 75	25	2 690 - 2 900	22.01 - 23.12
8.414 25 - 8.414 75	156.7 - 156.9	3 260 - 3 267	23.6 - 24.0
12.29 - 12.293	162.012 5 - 167.17	3 332 - 3 339	31.2 - 31.8
12.519 75 - 12.520 25	167.72 - 173.2	3 345.8 - 3 358	36.43 - 36.5
12.576 75 - 12.577 25	240 - 285	3 600 - 4 400	Above 38.6
13.36 - 13.41	322 - 335.4		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in section 15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in section 15.35 apply to these measurements.

According to section 15.407(b),

undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Test procedure

ANSI C63.10-2020 Section 12.7.5, 12.7.6, 12.7.7.2
KDB 789033 D02 V02r01 – Section G

Test settings

Peak field strength measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in table
3. VBW $\geq$ [3 $\times$ RBW]
4. Detector = peak
5. Sweep time = No faster than coupled (auto) time
6. Trace mode = max hold
7. Allow sweeps to continue until the trace stabilizes

Table. RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

Average field strength measurements

Trace averaging with continuous EUT transmission at full power

If the EUT can be configured or modified to transmit continuously ($D \geq 98\%$), then the average emission levels shall be measured using the following method (with EUT transmitting continuously):

- a) RBW = 1 MHz (unless otherwise specified).
- b) VBW $\geq$ [3 $\times$ RBW].
- c) Detector = Power averaging (RMS), if [span / (# of points in sweep)] $\leq$ (RBW / 2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms):
- e) As an alternative, the detector and averaging type may be set for linear voltage averaging.
- f) Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.

Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-4904-0113 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR26-SRF0177-A Page (23) of (29)	
--	---	---

Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT ($D \geq 98\%$) cannot be achieved and the duty cycle is constant (duty cycle variations are less than $\pm 2\%$), then the following procedure shall be used:


- The EUT shall be configured to operate at the maximum achievable duty cycle.
- Measure the duty cycle D of the transmitter output signal as described in 11.6.
- $RBW = 1 \text{ MHz}$ (unless otherwise specified).
- $VBW \geq [3 \times RBW]$.
- Detector = Power averaging (RMS), if $[\text{span} / (\# \text{ of points in sweep})] \leq (RBW / 2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- Averaging type = power (i.e., rms):
- As an alternative, the detector and averaging type may be set for linear voltage averaging.
- Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
- Sweep time = auto.
- Perform a trace average of at least 100 traces.
- A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
 - If power averaging (rms) mode was used in step e), then the applicable correction factor is $[10 \log (1 / D)]$, where D is the duty cycle.
 - If linear voltage averaging mode was used in step e), then the applicable correction factor is $[20 \log (1 / D)]$, where D is the duty cycle.

Notes:

- $f < 30 \text{ MHz}$, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/D_s)$
 $f \geq 30 \text{ MHz}$, extrapolation factor of 20 dB/decade of distance. $F_d = 20 \log(D_m/D_s)$
Where:
 F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters
- Factors(dB) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or F_d (dB)
- The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
- Average test would be performed if the peak result were greater than the average limit.
- ¹⁾ means restricted band.
- Below 30 MHz frequency range, In order to search for the worst result, all orientations about parallel, perpendicular, and ground-parallel were investigated then reported. when the emission level was higher than 20 dB of the limit, then the following statement shall be made: "No spurious emissions were detected within 20 dB of the limit."
- Above 1 GHz the worst results between two antenna polarizations (H and V) were documented in the test report.
- For above 1 GHz pre-scan to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 kHz for peak measurements.
- According to ANSI C63.10 Section 6.6.4.3 Note.1, If the maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.


Test results (Below 30 MHz) – Worst case: 802.11ac VHT20 / UNII1_5 200 MHz

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Quasi peak data								
No spurious emissions were detected within 20 dB of the limit.								



Test results (Below 1 000 MHz) – Worst case: 802.11ac VHT20 / UNII1_5 200 MHz

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Quasi peak data								
99.96	H	44.10	16.59	-31.28	-	29.41	43.52	14.11
167.98 ¹⁾	H	51.70	15.50	-31.11	-	36.09	43.52	7.43
264.01 ¹⁾	H	45.20	19.60	-30.97	-	33.83	46.02	12.19
359.92	H	47.00	20.70	-30.35	-	37.35	46.02	8.67
407.94 ¹⁾	H	48.70	21.90	-30.17	-	40.43	46.02	5.59
539.98	V	39.90	23.90	-30.09	-	33.71	46.02	12.31



Test results (Above 1 000 MHz)

UNII 1

802.11ac_VHT20_Lowest Channel (5 180 MHz)

Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
1 331.10 ¹⁾	V	67.50	25.70	-46.22	-	46.98	74.00	27.02
5 149.94 ¹⁾	V	50.40	33.30	-27.30	-	56.40	74.00	17.60
10 362.08	V	54.80	38.78	-39.63	-	53.95	68.20	14.25
15 490.06 ¹⁾	H	53.50	38.82	-37.94	-	54.38	74.00	19.62
Average Data								
5 149.94 ¹⁾	V	34.60	33.30	-27.30	-	40.60	54.00	13.40
15 490.06 ¹⁾	H	42.56	38.82	-37.94	-	43.44	54.00	10.56

802.11ac_VHT20_Middle Channel (5 200 MHz)



Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
1 330.55 ¹⁾	V	70.70	25.70	-46.22	-	50.18	74.00	23.82
10 385.08	V	54.10	38.73	-39.62	-	53.21	68.20	14.99
15 554.63 ¹⁾	H	53.10	38.80	-37.69	-	54.21	74.00	19.79
Average Data								
15 554.63 ¹⁾	H	42.26	38.80	-37.69	-	43.37	54.00	10.63

802.11ac_VHT20_Highest Channel (5 240 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp.+Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
1 328.17 ¹⁾	V	67.70	25.62	-46.22	-	47.10	74.00	26.90
10 476.70	V	54.60	38.80	-39.57	-	53.83	68.20	14.37
15 691.50 ¹⁾	H	52.60	38.70	-37.14	-	54.16	74.00	19.84
Average Data								
15 691.50 ¹⁾	H	42.94	38.70	-37.14	-	44.50	54.00	9.50

802.11ac_VHT20_Lowest Channel (5 180 MHz)

Average data



Horizontal/Vertical for Band-edge




Plot of Harmonics and Spurious Emissions


In order to simplify the report, attached plots were only the lowest margin condition

UNII 1_802.11ac VHT20_Highest Channel (5 240 MHz)


Horizontal/Vertical for 1 GHz ~ 6.5 GHz



Horizontal/Vertical for 6.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 40 GHz



Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-4904-0113 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR26-SRF0177-A Page (29) of (29)	
---	--	---

8. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSVA3030	101129	27.02.02
DC Power Supply	AGILENT	E3632A	MY40000265	27.04.23
Signal Generator	R&S	SMB100A	176206	27.01.15
Attenuator	HUBER+SUHNER	6610_SK-50-1/199_NE	ATT02	27.07.06
Spectrum Analyzer	R&S	FSV40	100988	27.04.06
Amplifier	SONOMA INSTRUMENT	310N	421910	27.07.06
Bi-log Antenna	Teseq GmbH	CBL 6112D	61521	26.12.11
Loop Antenna	R&S	HFH2-Z2	100355	28.06.29
Vector Signal Generator	R&S	SMBV100A	257566	27.07.06
Broadband Pre-Amplifier	SCHWARZBECK	BBV9718D	53	27.07.06
Low Noise Amplifier	TESTEK	TK-PA18H	220123-L	27.07.06
Low Noise Amplifier	TESTEK	TK-PA1840H	220234-L	27.04.28
Horn Antenna	SCHWARZBECK	BBHA9120D	2764	27.06.30
Horn Antenna	SCHWARZBECK	BBHA9170	1266	27.04.29
High Pass Filter	Qotana	DBHF058004000A	23041800061	27.04.28
High Pass Filter	Wainwright Instruments GmbH	WHKX8-5655-6500-18000-40SS	SN7	27.06.29
Cable Assembly	HUBER+SUHNER	SUCOFLEX 104	RF-N type 40G-002	26.11.26
Cable Assembly	HUBER+SUHNER	SUCOFLEX 104	RF-2.92 /40G-003	26.11.26
Cable Assembly	Isolution	KMSTA-KMSAT-ICA40G-7m	RF-2.92 /40G-005	26.12.08
Controller	INNCO SYSTEMS	CO3000	1442/54370322/P	N/A
Antenna Mast	INNCO SYSTEMS	MA4640-XP-ET	AM002	N/A
Turn Device	INNCO SYSTEMS	DS1200-S-1t	0001	N/A

End of test report