

Prüfbericht-Nr.: Test report no.:	CN2413SD 001	Auftrags-Nr.: Order no.:	170395963	Seite 1 von 18 Page 1 of 18	
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2024-12-10		
Auftraggeber: Client:	ONWARD BRANDS LLC 767 5TH AVE FL 37TH NEW YORK, NY 10153, USA				
Prüfgegenstand: Test item:	Incase Sculpt Ergonomic Keyboard				
Bezeichnung / Typ-Nr.: Identification / Type no.:	OB1559				
Auftrags-Inhalt: Order content:	Test Report				
Prüfgrundlage: Test specification:	FCC CFR Title 47, Part 15, Subpart C, Section 15.249 RSS-210 Issue 11 June 2024 RSS-Gen Issue 5 March 2019				
Wareneingangsdatum: Date of sample receipt:	2025-02-26	Please refer to Photo Document			
Prüfmuster-Nr.: Test sample no.:	LP24070228C10-S107				
Prüfzeitraum: Testing period:	2025-03-06 - 2025-03-08				
Ort der Prüfung: Place of testing:	Refer to section 2.1				
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Guangdong) Co., Ltd.				
Prüfergebnis*: Test result*:	Pass				
geprüft von: tested by:			genehmigt von: authorized by:		
Datum: Date:	2025-04-08		Ausstellungsdatum: Issue date:	2025-04-08	
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / Other:	FCC ID: 2BCOY-OB1559 IC: 32736-OB1559 HVIN: OB1559				
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged				
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar	5 = mangelhaft N/T = nicht getestet
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable	5 = poor N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

Prüfbericht-Nr.: CN2413SD 001
Test report no.:

Page 2 of 18
Seite 2 von 18

Anmerkungen
Remarks

1	The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request. <i>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</i> <i>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</i>
2	As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. <i>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</i>
3	Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report. <i>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</i>
4	The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019. <i>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</i>

Prüfbericht - Nr.: CN2413SD 001
Test Report No.:

Seite 3 von 18
Page 3 of 18

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 FIELD STRENGTH OF FUNDAMENTAL AND HARMONICS

RESULT: Pass

5.1.3 20dB AND 99% BANDWIDTH

RESULT: Pass

5.1.4 BAND EDGE

RESULT: Pass

5.1.5 CONDUCTED EMISSION ON AC MAINS

RESULT: N/A

Table of Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	8
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	9
3.5	SUBMITTED DOCUMENTS.....	9
4	TEST SET-UP AND OPERATION MODES	10
4.1	PRINCIPLE OF CONFIGURATION SELECTION	10
4.2	TEST OPERATION AND TEST SOFTWARE.....	10
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	10
4.5	TEST SETUP DIAGRAM	11
5	TEST RESULTS	13
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	13
5.1.1	<i>Antenna Requirement</i>	<i>13</i>
5.1.2	<i>Field strength of fundamental and harmonics</i>	<i>14</i>
5.1.3	<i>20dB and 99% Bandwidth</i>	<i>15</i>
5.1.4	<i>Band Edge.....</i>	<i>16</i>
5.1.5	<i>Conducted Emission on AC Mains.....</i>	<i>17</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	18
7	LIST OF TABLES.....	18

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test Results

2 Test Sites

2.1 Test Facilities

Dongguan Lepont Testing Service Co., Ltd.

Room 102, Building 11, No.7, Houjie Science And Technology Avenue, Houjie, Dongguan, Guangdong, China

FCC Accreditation Designation No.: CN1351

ISED wireless device testing laboratory: 20133

TÜV Rheinland (Guangdong) Co., Ltd. subcontract all test to Dongguan Lepont Testing Service Co., Ltd. And all tests at this site have been conducted under the supervision of a TÜV Rheinland engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing				
Equipment	Manufacturer	Model	Serial No.	Cal. until
Spectrum analyzer	Agilent	N9020A	MY49100060	Jan. 06, 2026
Vector source	Agilent	N5182A	MY47420382	Jan. 06, 2026
Analog signal source	Agilent	N5171B	MY51350292	Jan. 06, 2026
All instrument	Rohde & Schwarz	CMW 500	1201.002K50	Jan. 06, 2026
High and low temperature chamber	Math-mart	MT-1202-40	LEP-E041	Jan. 06, 2026
control unit	Tonscend	JS0806-2	10165	Jan. 06, 2026
Testing software	Tonscend	JSTS1120-3	Ver 2.6.77.0518	Jan. 06, 2026
Unwanted Emission Testing				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EMI Test Receiver	Rohde & Schwarz	ESR 3	101849	Dec. 22, 2025
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	743	Nov. 19, 2025
Spectrum analyzer	Agilent	N9020A	MY49100060	Jan. 06, 2026
Horn antenna	Schwarzbeck	BBHA 9120D	01875	Nov. 19, 2025
Preamplifier	Schwarzbeck	BBN 9718B	00010	Nov. 16, 2025
Signal Amplifier	HP	8447D	1726A01222	Jan. 06, 2026
6dB Attenuator	RswTech	5W 6dB	LEP-E084	Jan. 06, 2026
966 Chamber 1	MR	MR-L02	LEP-E051	Nov. 16, 2025
Test software	EZ-EMC	Fala	EMEC-3A1	N/A

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally, all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Table 2: Measurement Uncertainty

Parameter	Uncertainty (k=2)
RF output power, conducted	$\pm 1.06\text{dB}$
Occupied Channel Bandwidth	± 1.42
RF power density, conducted	$\pm 1.06\text{dB}$
Unwanted Emissions, conducted	$\pm 2.51\text{dB}$
All emissions, radiated	$\pm 3.70\text{dB}$
Conducted Emission 150kHz to 30MHz	$\pm 2.44\text{dB}$

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Guangdong) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

Dongguan Lepont Testing Service Co., Ltd. Test facility located at Room 102, Building 11, No.7, Houjie Science And Technology Avenue, Houjie, Dongguan, Guangdong, China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a Wireless Keyboard, which supports 2.4GHz wireless technologies.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	Wireless Keyboard
Type Designation:	OB1559
Trademark:	Incase
FCC ID:	2BCOY-OB1559
IC:	32736-OB1559
HVIN:	OB1559
Operating Voltage:	DC 3V (Supplied by AAA battery*2)
Test Voltage:	DC 3V
Operating Temperature Range:	-20 °C ~ +40 °C
Technical Specification of 2.4GHz	
Frequency Range:	2403 MHz to 2480 MHz
Type of Modulation:	GFSK
Channel Number:	24 channels
Channel Separation:	See table 4
Antenna Type:	PCB Layout Antenna
Antenna Gain:	-2.08dBi

Table 4: RF Channel and Frequency of General 2.4GHz Wireless

CHANNEL	FREQ (MHz)	CHANNEL	FREQ (MHz)	CHANNEL	FREQ (MHz)	CHANNEL	FREQ. (MHz)
1	2403	2	2405	3	2417	4	2419
5	2421	6	2423	7	2425	8	2427
9	2429	10	2431	11	2444	12	2446
13	2448	14	2450	15	2452	16	2454
17	2456	18	2468	19	2470	20	2472
21	2474	22	2476	23	2478	24	2480

3.3 Independent Operation Modes

The basic operation modes are:

- A. 2.4GHz transmitting mode
 - 1. Low channel
 - 2. Middle channel
 - 3. High channel
- B. On, normal operation
- C. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- | | |
|----------------------------------|-------------------------|
| - Application Form | - Block Diagram |
| - FCC/IC Label and Location Info | - Operation Description |
| - Schematics | - User Manual |

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2013.

Table 5: Test environments

Environment Parameter	Values During Tests		
	Temperature	Voltage	Relative Humidity
NTNV	25°C±2°C	3.0 Vdc	Ambient

Table 6: Test channel and frequency of 2.4GHz

Mode	Test Channels (MHz)	Remark
Transmitting	L/M/H: 2403MHz, 2444MHz, 2480MHz	--

4.3 Special Accessories and Auxiliary Equipment

Table 7: Auxiliary Equipment Used during Test

Description	Manufacturer	Model	S/N	Rating
N/A	N/A	N/A	N/A	N/A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.203
RSS-Gen Section 6.8

According to the manufacturer declared, the EUT has a PCB antenna, the gain of antenna is -2.08dBi, which that permanent attachment and no consideration of replacement.

Therefore, the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

Prüfbericht - Nr.: **CN2413SD 001**
Test Report No.:Seite 14 von 18
Page 14 of 18

5.1.2 Field strength of fundamental and harmonics

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.249(a) (d) (e) RSS-210 Section B.10
Basic standard	: ANSI C63.10: 2013
Limits	: FCC Part 15.249(a) (d) (e) & 15.209(a) RSS-210 Section B.10 (a) & (b) RSS-Gen Section 8.9
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: 2025-03-07
Input voltage	: DC 3V (Supplied by AAA battery*2)
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: 101 kPa

Note: Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst-case spurious emissions configuration of each mode was reported.

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: CN2413SD 001
Test Report No.:

Seite 15 von 18
Page 15 of 18

5.1.3 20dB and 99% Bandwidth

RESULT:

Pass

Test Specification

Test standard	: RSS-Gen Section 6.7
Basic standard	: ANSI C63.10: 2013
Limits	: Within assigned band
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2025-03-06
Input voltage	: DC 3V (Supplied by AAA battery*2)
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 21.2 °C
Relative humidity	: 53 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: CN2413SD 001
Test Report No.:

Seite 16 von 18
Page 16 of 18

5.1.4 Band Edge

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.249(a) (d) (e) & 15.209 & 15.205 RSS-210 Section B.10 (a) & (b) RSS-Gen Section 8.9 & 8.10
Basic standard	: ANSI C63.10: 2013
Limits	: FCC Part 15.249(a) (d) (e) & 15.209 & 15.205 RSS-Gen Table 5 & 7
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: 2025-03-07
Input voltage	: DC 3V (Supplied by AAA battery*2)
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: CN2413SD 001
Test Report No.:

Seite 17 von 18
Page 17 of 18

5.1.5 Conducted Emission on AC Mains

RESULT:

N/A

Test Specification

Test standard	: FCC Part 15.207(a) RSS-Gen Section 8.8
Basic standard	: ANSI C63.10: 2013
Frequency range	: 0.15 – 30MHz
Limits	: FCC Part 15.207(a) RSS-Gen Table 4
Kind of test site	: Shielded Room

Note: The wireless keyboard is powered by an alkaline battery and is not connected to the PC USB port, nor to the AC end, so it should not be evaluated

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty	7
Table 3: Technical Specification of EUT	8
Table 4: RF Channel and Frequency of General 2.4GHz Wireless	8
Table 5: Test environments	10
Table 6: Test channel and frequency of 2.4GHz	10
Table 7: Auxiliary Equipment Used during Test	10

Appendix B: Test Results of General 2.4GHz

APPENDIX B: TEST RESULTS OF GENERAL 2.4GHZ	1
APPENDIX B.1: FUNDAMENTAL	2
APPENDIX B.2: 20dB AND 99% BANDWIDTH	8
APPENDIX B.3: HARMONICS RADIATED EMISSION	13
30MHz - 1GHz	13
1GHz - 18GHz	19
<i>Note: The highest waveform in the figure is 2.4GHz Fundamental.</i>	<i>19</i>
APPENDIX B.4: TEST RESULTS OF RADIATED EMISSIONS IN RESTRICTED BANDS	25
Low channel	25
High channel	27

Appendix B.1: Fundamental




Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:		Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard:	FCC 15C 3M Radiation Peak(Fundamental)	Test Engineer:	Kervin
EUT:	Incise Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.:	OB1559	Ant. Polarization:	Vertical
Test Mode:	TX		
Remark 1:	2403MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2403.000	-4.78	84.92	80.14	114.00	-33.86	peak		
2	2403.000	-4.78	83.26	78.48	94.00	-15.52	AVG	*	

Note: Level=Reading+Factor, Over=Level-Limit.
MK.:*:Maximum data x:Over limit !:Over margin

File: OB1559-Fundamental\Data :#6






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:		Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard:	FCC 15C 3M Radiation Peak(Fundamental)	Test Engineer:	Kervin
EUT:	Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.:	OB1559	Ant. Polarization:	Horizontal
Test Mode:	TX		
Remark 1:	2403MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2403.000	-4.78	80.54	75.76	114.00	-38.24	peak		
2	2403.000	-4.78	77.83	73.05	94.00	-20.95	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-Fundamental\Data :#5






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:		Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard:	FCC 15C 3M Radiation Peak(Fundamental)	Test Engineer:	Kervin
EUT:	Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.:	OB1559	Ant. Polarization:	Horizontal
Test Mode:	TX		
Remark 1:	2444MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2444.000	-4.62	74.84	70.22	114.00	-43.78	peak		
2	2444.000	-4.62	69.37	64.75	94.00	-29.25	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-Fundamental\Data :#4






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:		Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard:	FCC 15C 3M Radiation Peak(Fundamental)	Test Engineer:	Kervin
EUT:	Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.:	OB1559	Ant. Polarization:	Vertical
Test Mode:	TX		
Remark 1:	2444MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2444.000	-4.62	82.63	78.01	114.00	-35.99	peak		
2	2444.000	-4.62	80.25	75.63	94.00	-18.37	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-Fundamental\Data :#3






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:		Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard:	FCC 15C 3M Radiation Peak(Fundamental)	Test Engineer:	Kervin
EUT:	Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.:	OB1559	Ant. Polarization:	Vertical
Test Mode:	TX		
Remark 1:	2480MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2480.000	-4.48	74.80	70.32	114.00	-43.68	peak		
2	2480.000	-4.48	76.75	72.27	94.00	-21.73	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-Fundamental\Data :#2






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:		Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard:	FCC 15C 3M Radiation Peak(Fundamental)	Test Engineer:	Kervin
EUT:	Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.:	OB1559	Ant. Polarization:	Horizontal
Test Mode:	TX		
Remark 1:	2480MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2480.000	-4.48	72.00	67.52	114.00	-46.48	peak		
2	2480.000	-4.48	69.20	64.72	94.00	-29.28	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-Fundamental\\Data :#1




Appendix B.2: 20dB and 99% Bandwidth

Channel	Test Mode Test Channel (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)	Limit (MHz)
Low Channel	2403	2998	2849.8	Within the assigned frequency band 2400~2483.5MHz
Middle Channel	2444	2429	2350.8	
High Channel	2480	1977	1803.9	
Maximum Measured Value	Maximum Measured Value	2998	2849.8	

Test Plot of 20dB Bandwidth

Low CH



Middle CH




High CH



Test Plot of 99% Bandwidth

Low CH



Middle CH



High CH



Appendix B.3: Harmonics Radiated Emission

Note:

- 1) This testing was carried out on different modulations, but only the worst case was presented in this report.
- 2) Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 26.5GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported.

30MHz - 1GHz




Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/8

Job No.:	Temp:	24.2 (C) / 57 %RH/ 1013
Test Standard: FCC PART 15B 3M Radiation	Test Engineer:	Kervin
EUT: Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.: OB1559	Ant. Polarization:	Horizontal
Test Mode: TX		
Remark 1: 2480MHZ		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	44.2752	12.58	8.58	21.16	40.00	-18.84	QP	*	
2	54.0711	11.98	8.75	20.73	40.00	-19.27	QP		
3	89.2764	8.53	9.24	17.77	43.50	-25.73	QP		
4	106.3850	10.18	9.68	19.86	43.50	-23.64	QP		
5	203.5228	10.83	9.58	20.41	43.50	-23.09	QP		
6	250.3012	11.23	9.29	20.52	46.00	-25.48	QP		

Note: Level=Reading+Factor, Over=Level-Limit.
MK.: Maximum data x: Over limit !: Over margin

File: OB1559-30-1G\Data :#6






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/8

Job No.:	Temp:	24.2 (C) / 57 %RH/ 1013
Test Standard: FCC PART 15B 3M Radiation	Test Engineer:	Kervin
EUT: Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.: OB1559	Ant. Polarization:	Vertical
Test Mode: TX		
Remark 1: 2480MHZ		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	45.8553	12.71	7.34	20.05	40.00	-19.95	QP	*	
2	54.4516	11.95	8.06	20.01	40.00	-19.99	QP		
3	100.2286	10.58	7.61	18.19	43.50	-25.31	QP		
4	112.1305	9.81	7.97	17.78	43.50	-25.72	QP		
5	199.2855	10.69	8.52	19.21	43.50	-24.29	QP		
6	337.2155	14.01	9.33	23.34	46.00	-22.66	QP		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-30-1G\Data :#5





Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn


Radiation Emission

Site: 966 Chamber 1

2025/3/8

Job No.:
Test Standard: FCC PART 15B 3M Radiation
EUT: Incase Sculpt Ergonomic Keyboard
Model No.: OB1559
Test Mode: TX
Remark 1: 2444MHZ

Temp: 24.2 (C) / 57 %RH/ 1013
Test Engineer: Kervin
Power Rating: DC 3V
Ant. Polarization: **Vertical**



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	44.1202	12.54	9.02	21.56	40.00	-18.44	QP		
2	50.5860	12.34	10.07	22.41	40.00	-17.59	QP	*	
3	59.8588	11.40	8.76	20.16	40.00	-19.84	QP		
4	101.2885	10.52	7.65	18.17	43.50	-25.33	QP		
5	216.7828	10.94	9.70	20.64	46.00	-25.36	QP		
6	291.0360	12.21	9.73	21.94	46.00	-24.06	QP		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-30-1G\Data :#4





Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn


Radiation Emission

Site: 966 Chamber 1

2025/3/8

Job No.:
Test Standard: FCC PART 15B 3M Radiation
EUT: Incase Sculpt Ergonomic Keyboard
Model No.: OB1559
Test Mode: TX
Remark 1: 2444MHZ

Temp: 24.2 (C) / 57 %RH/ 1013
Test Engineer: Kervin
Power Rating: DC 3V
Ant. Polarization: Horizontal



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	43.9658	12.50	8.16	20.66	40.00	-19.34	QP		
2	57.3923	11.65	9.15	20.80	40.00	-19.20	QP	*	
3	98.8326	10.38	8.52	18.90	43.50	-24.60	QP		
4	108.2667	10.06	7.91	17.97	43.50	-25.53	QP		
5	196.5098	10.24	9.09	19.33	43.50	-24.17	QP		
6	227.6906	11.01	9.26	20.27	46.00	-25.73	QP		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin
File: OB1559-30-1G\Data :#3





Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn


Radiation Emission

Site: 966 Chamber 1

2025/3/8

Job No.:
Test Standard: FCC PART 15B 3M Radiation
EUT: Incase Sculpt Ergonomic Keyboard
Model No.: OB1559
Test Mode: TX
Remark 1: 2403MHZ

Temp: 24.2 (C) / 57 %RH/ 1013
Test Engineer: Kervin
Power Rating: DC 3V
Ant. Polarization: Horizontal



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	44.1202	12.54	11.00	23.54	40.00	-16.46	QP	*	
2	50.0566	12.39	10.17	22.56	40.00	-17.44	QP		
3	94.0979	9.49	9.95	19.44	43.50	-24.06	QP		
4	109.7960	9.96	10.43	20.39	43.50	-23.11	QP		
5	202.8104	10.82	9.40	20.22	43.50	-23.28	QP		
6	234.1684	11.01	10.41	21.42	46.00	-24.58	QP		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-30-1G\Data :#2





Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn


Radiation Emission

Site: 966 Chamber 1

2025/3/8

Job No.:
Test Standard: FCC PART 15B 3M Radiation
EUT: Incase Sculpt Ergonomic Keyboard
Model No.: OB1559
Test Mode: TX
Remark 1: 2403MHZ

Temp: 24.2 (C) / 57 %RH/ 1013
Test Engineer: Kervin
Power Rating: DC 3V
Ant. Polarization: Vertical



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	45.6948	12.72	9.20	21.92	40.00	-18.08	QP	*	
2	52.9453	12.10	8.94	21.04	40.00	-18.96	QP		
3	61.3463	11.05	9.53	20.58	40.00	-19.42	QP		
4	102.7192	10.42	8.18	18.60	43.50	-24.90	QP		
5	196.5098	10.24	8.08	18.32	43.50	-25.18	QP		
6	227.6906	11.03	9.32	20.35	46.00	-25.65	QP		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-30-1G\Data :#1



1GHz - 18GHz

Note: The highest waveform in the figure is 2.4GHz Fundamental.



Dongguan Lepont Testing Service Co., Ltd.


Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:	Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard: FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT: Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.: OB1559	Ant. Polarization:	Vertical
Test Mode: TX		
Remark 1: 2480MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4961.000	-1.00	51.91	50.91	74.00	-23.09	peak		
2	7137.000	5.71	42.06	47.77	74.00	-26.23	peak		
3	9347.000	7.42	40.66	48.08	74.00	-25.92	peak		
4	4978.000	-1.01	39.96	38.95	54.00	-15.05	AVG	*	
5	7103.000	5.72	29.95	35.67	54.00	-18.33	AVG		
6	9483.000	7.51	29.97	37.48	54.00	-16.52	AVG		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-RSE\Data :#6





Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn


Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:
Test Standard: FCC Class B 3M Radiation Peak(Above 1G)
EUT: Incase Sculpt Ergonomic Keyboard
Model No.: OB1559
Test Mode: TX
Remark 1: 2480MHz

Temp: 23.7 (C) / 57 %RH/ 983 hpa
Test Engineer: Kervin
Power Rating: DC 3V
Ant. Polarization: **Horizontal**



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4961.000	-1.00	48.23	47.23	74.00	-26.77	peak		
2	7120.000	5.72	40.87	46.59	74.00	-27.41	peak		
3	9466.000	7.49	40.69	48.18	74.00	-25.82	peak		
4	4978.000	-1.01	36.14	35.13	54.00	-18.87	AVG		
5	7103.000	5.72	30.10	35.82	54.00	-18.18	AVG		
6	9483.000	7.51	29.96	37.47	54.00	-16.53	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin
File: OB1559-RSEIData :#5






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:		Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard:	FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT:	Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.:	OB1559	Ant. Polarization:	Horizontal
Test Mode:	TX		
Remark 1:	2444MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4893.000	-1.00	52.04	51.04	74.00	-22.96	peak		
2	7103.000	5.72	40.63	46.35	74.00	-27.65	peak		
3	9364.000	7.43	41.46	48.89	74.00	-25.11	peak		
4	4910.000	-1.01	40.00	38.99	54.00	-15.01	AVG	*	
5	7103.000	5.72	30.18	35.90	54.00	-18.10	AVG		
6	9483.000	7.51	29.80	37.31	54.00	-16.69	AVG		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-RSEIData :#4






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:	Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard: FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT: Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.: OB1559	Ant. Polarization:	Vertical
Test Mode: TX		
Remark 1: 2444MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4893.000	-1.00	45.61	44.61	74.00	-29.39	peak		
2	7137.000	5.71	40.32	46.03	74.00	-27.97	peak		
3	9432.000	7.47	40.56	48.03	74.00	-25.97	peak		
4	4910.000	-1.01	33.89	32.88	54.00	-21.12	AVG		
5	7103.000	5.72	30.01	35.73	54.00	-18.27	AVG		
6	9483.000	7.51	29.98	37.49	54.00	-16.51	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-RSEIData :#3





Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn


Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:
Test Standard: FCC Class B 3M Radiation Peak(Above 1G)
EUT: Incase Sculpt Ergonomic Keyboard
Model No.: OB1559
Test Mode: TX
Remark 1: 2403MHz

Temp: 23.7 (C) / 57 %RH/ 983 hpa
Test Engineer: Kervin
Power Rating: DC 3V
Ant. Polarization: **Vertical**



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4808.000	-1.01	47.90	46.89	74.00	-27.11	peak		
2	7137.000	5.71	40.59	46.30	74.00	-27.70	peak		
3	9483.000	7.51	40.27	47.78	74.00	-26.22	peak		
4	4825.000	-1.02	35.25	34.23	54.00	-19.77	AVG		
5	7103.000	5.72	29.98	35.70	54.00	-18.30	AVG		
6	9483.000	7.51	29.79	37.30	54.00	-16.70	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin
File: OB1559-RSEIData :#2






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:	Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard: FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT: Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.: OB1559	Ant. Polarization:	Horizontal
Test Mode: TX		
Remark 1: 2403MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4808.000	-1.01	50.59	49.58	74.00	-24.42	peak		
2	7069.000	5.74	41.07	46.81	74.00	-27.19	peak		
3	9466.000	7.49	40.84	48.33	74.00	-25.67	peak		
4	4825.000	-1.02	38.58	37.56	54.00	-16.44	AVG	*	
5	7103.000	5.72	30.26	35.98	54.00	-18.02	AVG		
6	9483.000	7.51	29.97	37.48	54.00	-16.52	AVG		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin
File: OB1559-RSEIData :#1



Appendix B.4: Test Results of Radiated Emissions in Restricted Bands

Low channel



Dongguan Lepont Testing Service Co., Ltd.

Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn


Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:
Test Standard: FCC Class B 3M Radiation Peak(Above 1G)
EUT: Incase Sculpt Ergonomic Keyboard
Model No.: OB1559
Test Mode: TX
Remark 1: 2403MHz

Temp: 23.7 (C) / 57 %RH/ 983 hpa
Test Engineer: Kervin
Power Rating: DC 3V
Ant. Polarization: Vertical



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2390.000	-4.83	49.82	44.99	74.00	-29.01	peak		
2	2400.000	-4.79	62.04	57.25	74.00	-16.75	peak	*	
3	2400.100	-4.79	34.93	30.14	54.00	-23.86	AVG		
4	2390.090	-4.83	31.15	26.32	54.00	-27.68	AVG		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:Maximum data x:Over limit !:Over margin

File: OB1559-BAND\Data :#2






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:		Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard:	FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT:	Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.:	OB1559	Ant. Polarization:	Horizontal
Test Mode:	TX		
Remark 1:	2403MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2390.000	-4.83	41.08	36.25	74.00	-37.75	peak		
2	2400.000	-4.79	51.87	47.08	74.00	-26.92	peak	*	
3	2389.980	-4.83	30.46	25.63	54.00	-28.37	AVG		
4	2400.100	-4.79	31.09	26.30	54.00	-27.70	AVG		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB1559-BAND1Data :#1



High channel




Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:	Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard: FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT: Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.: OB1559	Ant. Polarization:	Horizontal
Test Mode: TX		
Remark 1: 2480MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2483.500	-4.46	46.65	42.19	74.00	-31.81	peak		
2	2485.000	-4.46	43.36	38.90	74.00	-35.10	peak		
3	2483.440	-4.46	29.70	25.24	54.00	-28.76	AVG	*	
4	2485.000	-4.46	29.63	25.17	54.00	-28.83	AVG		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*:Maximum data x:Over limit !:Over margin

File: OB1559-BAND1Data :#4






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2025/3/7

Job No.:		Temp:	23.7 (C) / 57 %RH/ 983 hpa
Test Standard:	FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT:	Incase Sculpt Ergonomic Keyboard	Power Rating:	DC 3V
Model No.:	OB1559	Ant. Polarization:	Vertical
Test Mode:	TX		
Remark 1:	2480MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2483.500	-4.46	54.91	50.45	74.00	-23.55	peak	*	
2	2485.000	-4.46	50.64	46.18	74.00	-27.82	peak		
3	2483.500	-4.46	31.01	26.55	54.00	-27.45	AVG		
4	2484.970	-4.46	29.79	25.33	54.00	-28.67	AVG		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:Maximum data x:Over limit !:Over margin

File: OB1559-BAND\Data :#3

