



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 1 of 69

Applicant : Atlas Aerospace SIA
Address of Applicant : Ulbrokas Street 19A, 1021 Riga, Latvia

Product Name : Atlas Radio Module
Brand Name : ATLAS
Model Name : ATR-200
Sample Acquisition Method : Sent by Client
Sample No. : E23100021-01#02

FCC ID : 2BCPM-ATLATR200

Standards : FCC CFR47 Part 15, Subpart C

Date of Receipt : 2023-10-11
Date of Test : 2023-10-11~ 2023-10-18
Date of Issue : 2023-10-24

Remark:

This report details the results of the testing carried out on one sample, the results contained in this report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

Prepared by:

Erik Yang

(Erik Yang)

Reviewed by:

Jennifer Zhou

(Jennifer Zhou)

Approved by:

Echo Mu

(Authorized signatory: Echo Mu)





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 2 of 69

Contents

1	GENERAL INFORMATION	3
1.1	TESTING LABORATORY	3
1.2	DETAILS OF APPLICATION	3
1.3	DETAILS OF EUT	3
1.4	TEST METHODOLOGY	4
1.5	TEST SUMMARY	5
2	TEST CONDITION	6
2.1	ENVIRONMENTAL CONDITIONS	6
2.2	EQUIPMENT LIST	6
2.3	MEASUREMENT UNCERTAINTY	6
3	TEST SET-UP AND OPERATION MODES	7
3.1	DETAILS OF TEST MODE	7
3.2	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	7
3.3	SUPPORT SOFTWARE	7
3.4	TEST SETUP DIAGRAM	8
4	TEST RESULTS	9
4.1	TRANSMITTER REQUIREMENT & TEST SUITES	9
4.1.1	<i>Antenna Requirement</i>	9
4.1.2	<i>Maximum peak conducted output power</i>	10
4.1.3	<i>6dB Bandwidth</i>	11
4.1.4	<i>Maximum conducted output power spectral density</i>	15
4.1.5	<i>Conducted Spurious Emission & Authorized-band band-edge</i>	19
4.1.6	<i>Radiated Emission</i>	31
4.1.7	<i>Band Edge (Restricted-band band-edge)</i>	58
5	APPENDIXES	66
5.1	PHOTOGRAPHS OF THE SAMPLE	66
5.2	SET-UP FOR CONDUCTED RF TEST AT ANTENNA PORT	67
5.3	SET-UP FOR SPURIOUS EMISSIONS BELOW 1GHZ	67
5.4	SET-UP FOR SPURIOUS EMISSIONS ABOVE 1GHZ	68



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 3 of 69

1 General Information

1.1 Testing Laboratory

Company Name	ICAS Testing Technology Service (Shanghai) Co., Ltd.
Address	No.1298 Pingan Road, Minhang District, Shanghai, China
Telephone	0086 21-51682999
Fax	0086 21-54711112
Homepage	www.icasiso.com

1.2 Details of Application

Applicant Company Name	Atlas Aerospace SIA
Address	Ulbrokas Street 19A, 1021 Riga, Latvia
Contact Person	Arturs Neitals
Telephone	+37129778900
Email	certification@atlasdynamics.eu
Manufacturer Company Name	Atlas Aerospace SIA
Address	Ulbrokas Street 19A, 1021 Riga, Latvia

1.3 Details of EUT

Product Name	Atlas Radio Module
Brand Name	ATLAS
Test Model Name	ATR-200
FCC ID	2BCPM-ATLATR200
Frequency Range	2405MHz ~ 2469MHz
Number of Channels	Bandwidth 5M:65(at intervals of 1 MHz); Bandwidth 20M:51(at intervals of 1 MHz)
Modulation Type	OFDM
RF Output Power	Bandwidth 5M: 20.67dBm Bandwidth 20M: 21.28dBm
Antenna Type	External Antenna
Antenna Gain	1.52dBi
Test Voltage	DC 10-18V
Hardware Version	ATR-200-04-FD2
Software Version	r0+13092-74da93979e
RF power setting in TEST SW	ATLAS Radio web interface-Utilities-Test mode_Power level setting_17dBm

Note:

- The above information was declared by the manufacture.
- For more details, please refer to the User's manual of the EUT.



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 4 of 69

Channel List

Bandwidth 5MHz		Bandwidth 20MHz	
Channel	Frequency	Channel	Frequency
1	2.405GHz	1	2.412GHz
2	2.406GHz	2	2.413GHz
3	2.407GHz	3	2.414GHz
...	...	...	...
32	2.436GHz	25	2.436GHz
33	2.437GHz	26	2.437GHz
34	2.438GHz	27	2.438GHz
...	...	...	...
63	2.467GHz	49	2.460GHz
64	2.468GHz	50	2.461GHz
65	2.469GHz	51	2.462GHz

Note: Channel interval is 1MHz.

1.4 Test Methodology

47 CFR Part 15, Subpart C	Telecommunication-Radio Frequency Devices-Intentional Radiators
KDB Publication 558074 D01 v05r02	15.247 Meas Guidance.
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Note(s):

All test items were verified and recorded according to the standards and without any addition/deviation/exclusion during the test.



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 5 of 69

1.5 Test Summary

Test Item	FCC Rules	Result
Antenna Requirement	FCC Part 15.247(b)(4), Part 15.203	PASS
Maximum peak conducted output power	FCC Part 15.247(b)(3)	PASS
6dB Bandwidth	FCC Part 15.247(a)(2)	PASS
Maximum conducted output power spectral density	FCC Part 15.247(e)	PASS
Conducted Spurious Emission & Authorized-band band-edge	FCC Part 15.247(d)	PASS
Radiated Emission	FCC Part 15.247(d), 15.205, 15.209	PASS
Band Edge (Restricted-band band-edge)	FCC Part 15.247(d), 15.205, 15.209	PASS
Conducted Emission on AC Mains	FCC Part 15.207(a)	N/A ^{note}

Note(s): The EUT is powered by DC 18V. Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 6 of 69

2 Test Condition

2.1 Environmental conditions

Temperature (°C)	18-25
Humidity (%RH)	40-65
Barometric Pressure (mbar)	960-1060

2.2 Equipment List

Name of Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	Keysight	N9020B	MY59260184	2023-07-27	2024-07-26
Spectrum Analyzer	Rohde & Schwarz	FSV40N	101450	2023-06-08	2024-06-07
Signal Generator	Rohde & Schwarz	SMR27	100184	2023-07-27	2024-07-26
EMI Test Receiver	Rohde & Schwarz	ESR 7	101911	2023-06-08	2024-06-07
Broadband Antenna	SCHWARZBECK	VULB9163	9163-1037	2023-03-22	2025-03-21
Horn Antenna-18G	SCHWARZBECK	BBHA9120D	9120D-1775	2023-06-13	2025-06-12
Horn Antenna-40G	YINGLIAN	LB-180400-KF	N/A	2023-06-18	2025-06-17
Loop Antenna	SCHWARZBECK	FMZB 1513	/	2023-06-09	2024-06-08
Broadband Preamplifier	SCHWARZBECK	BBV 9718	346	2023-06-08	2024-06-07
EMC chamber 9*6*6(L*W*H)	CHANGNING	966	N/A	2023-06-09	2025-06-08
Test Software	BL	BL410_E	Version:1.0.0.117	N/A	N/A
Test Software	BL	BL410_R	Version:2.1.1.409	N/A	N/A

2.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in measurement" (GUM) published by CISPR and ANSI. The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95.45%.

Parameter		Uncertainty
Antenna Port Conducted Emission	< 1GHz	± 1.5 dB
	> 1GHz	± 1.5 dB
Radiated Emission	9KHz – 30MHz	± 3.42 dB
	30 MHz – 1GHz	± 5.00 dB
	> 1GHz	± 4.88 dB
Occupied Channel Bandwidth		± 5 %



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 7 of 69

3 Test Set-up and Operation Modes

3.1 Details of Test Mode

Using test software was control EUT work in continuous transmitting mode. Select test channel as below:

Bandwidth 5MHz:

Channel	Frequency
The lowest channel(CH01)	2405MHz
The middle channel(CH33)	2437MHz
The Highest channel(CH65)	2469MHz

Bandwidth 20MHz:

Channel	Frequency
The lowest channel(CH01)	2412MHz
The middle channel(CH26)	2437MHz
The Highest channel(CH51)	2462MHz

The basic operation modes are:

- A. On
 - 1. Bandwidth 5MHz/20MHz mode
 - a. Transmitting
 - i. Low Channel
 - ii. Middle Channel
 - iii. High Channel
 - b. Receiving
 - 2. Normal working with transmitter on
- B. Standby
- C. Off

3.2 Special Accessories and Auxiliary Equipment

Description	Manufacturer	Model Name	Serial No.
Laptop	HP	HP ZHAN 66 Pro G1	N/A
Network Cable	N/A	N/A	1.00m Unshielded

3.3 Support Software

Description	Manufacturer	Software Name
Software	N/A	ATLAS Radio web interface-Utilities-Test mode



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 8 of 69


3.4 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Transmitter Test





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 9 of 69

4 Test Results

4.1 Transmitter Requirement & Test Suites

4.1.1 Antenna Requirement

RESULT:

PASS

Test standard : FCC Part 15.247(b)(4), Part 15.203

Requirement : An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. In addition, If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

According to the manufacturer declaration, an antenna with a directional gain of 1.52dBi. The antenna is External Antenna with no possibility of replacement with a non-approved antenna by the end-user.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Therefore, the EUT is considered to comply with this provision.



TEST REPORT

Report No.: SHE23100021-01AE Date: 2023-10-24 Page 10 of 69

4.1.2 Maximum peak conducted output power

RESULT:

PASS

Test standard : FCC Part 15.247(b)(3)
Requirement : ANSI C63.10-2013 clause 11.9.1,
KDB 558074 D01 v05r02, Clause 8.3.1
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 23.5°C
Relative humidity : 50%

Table 1: Maximum peak conducted output power

Test Mode	Test Channel (MHz)	Maximum peak conducted output power		Limit (W)
		(dBm)	(mW)	
Bandwidth 5MHz	2405	20.67	116.68	< 1
	2437	19.95	98.86	
	2469	19.57	90.57	
Bandwidth 20MHz	2412	20.55	113.50	
	2437	21.28	134.28	
	2462	20.69	117.22	



TEST REPORT

Report No.: SHE23100021-01AE Date: 2023-10-24 Page 11 of 69

4.1.3 6dB Bandwidth

RESULT: **PASS**

Test standard : FCC Part 15.247(a)(2)
Requirement : ANSI C63.10-2013 clause 11.8.1,
KDB 558074 D01 v05r02, Clause 8.2
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 23.5°C
Relative humidity : 50%

Table 2: 6dB Bandwidth

Test Mode	Test Channel (MHz)	6dB Bandwidth (MHz)	Limit
Bandwidth 5MHz	2405	4.26	≥0.5 MHz
	2437	4.11	
	2469	4.32	
Bandwidth 20MHz	2412	15.13	
	2437	12.31	
	2462	11.68	



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 12 of 69

Figure 1: 6dB Bandwidth, Bandwidth 5MHz, 2405MHz



Figure 2: 6dB Bandwidth, Bandwidth 5MHz, 2437MHz





TEST REPORT

Report No.: SHE23100021-01AE


Date: 2023-10-24

Page 13 of 69

Figure 3: 6dB Bandwidth, Bandwidth 5MHz, 2469MHz



Figure 4: 6dB Bandwidth, Bandwidth 20MHz, 2412MHz





TEST REPORT

Report No.: SHE23100021-01AE


Date: 2023-10-24

Page 14 of 69

Figure 5: 6dB Bandwidth, Bandwidth 20MHz, 2437MHz



Figure 6: 6dB Bandwidth, Bandwidth 20MHz, 2462MHz





TEST REPORT

Report No.: SHE23100021-01AE Date: 2023-10-24 Page 15 of 69

4.1.4 Maximum conducted output power spectral density

RESULT: **PASS**

Test standard : FCC Part 15.247(e)
Requirement : ANSI C63.10-2013 clause 11.10.2,
KDB 558074 D01 v05r02, Clause 8.4
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 23.5°C
Relative humidity : 50%

Table 3: Maximum conducted output power spectral density

Test Mode	Test Channel (MHz)	Measured Result (dBm/3kHz)	Limit (dBm/3kHz)
Bandwidth 5MHz	2405	-6.07	8
	2437	-8.16	
	2469	-7.35	
Bandwidth 20MHz	2412	-12.33	
	2437	-12.51	
	2462	-13.11	



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 16 of 69

Figure 7: Power Spectral Density, Bandwidth 5MHz, 2405MHz




Figure 8: Power Spectral Density, Bandwidth 5MHz, 2437MHz





TEST REPORT

Report No.: SHE23100021-01AE


Date: 2023-10-24

Page 17 of 69

Figure 9: Power Spectral Density, Bandwidth 5MHz, 2469MHz



Figure 10: Power Spectral Density, Bandwidth 20MHz, 2412MHz





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 18 of 69

Figure 11: Power Spectral Density, Bandwidth 20MHz, 2437MHz





Figure 12: Power Spectral Density, Bandwidth 20MHz, 2462MHz





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 19 of 69

4.1.5 Conducted Spurious Emission & Authorized-band band-edge

RESULT:

PASS

Test standard : FCC Part 15.247(d), 15.209
Requirement : ANSI C63.10-2013, Clause 11.11.1(a)
KDB 558074 D01 v05r02, Clause 8.5
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High for spurious, Low/High for Band Edge
Operation Mode : A.1.a
Ambient temperature : 23.5°C
Relative humidity : 50%

For details refer to following test plot.

Figure 13: Conducted Spurious Emission & Authorized-band band-edge, 2405MHz, Bandwidth 5MHz Carrier Level





TEST REPORT

Report No.: SHE23100021-01AE


Date: 2023-10-24

Page 20 of 69

Band Edge



Conducted spurious emissions 30MHz-25GHz





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 21 of 69






TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 22 of 69

Conducted spurious emissions 30MHz-25GHz





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 23 of 69

Figure 15: Conducted Spurious Emission & Authorized-band band-edge, 2469MHz, Bandwidth 5MHz
Carrier Level



Band Edge






TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 24 of 69

Conducted spurious emissions 30MHz-25GHz





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 25 of 69

Figure 16: Conducted Spurious Emission & Authorized-band band-edge, 2412MHz, Bandwidth 20MHz
Carrier Level



Band Edge





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 26 of 69

Conducted spurious emissions 30MHz-25GHz





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 27 of 69

Figure 17: Conducted Spurious Emission & Authorized-band band-edge, 2437MHz, Bandwidth 20MHz Carrier Level



Conducted spurious emissions 30MHz-25GHz



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 28 of 69



Figure 18: Conducted Spurious Emission & Authorized-band band-edge, 2462MHz, Bandwidth 20MHz Carrier Level





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 29 of 69

Band Edge



Conducted spurious emissions 30MHz-25GHz





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 30 of 69





TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 31 of 69

4.1.6 Radiated Emission

RESULT:

PASS

Test standard : FCC Part 15.247(d), 15.205, 15.209
Requirement : ANSI C63.10-2013 clause 11.12,
KDB 558074 D01 v05r02, Clause 8.6
Kind of test site : 3m Semi-Anechoic Chamber

Test setup

Test Channel : Low/Middle/High
Operation Mode : A
Ambient temperature : 25°C
Relative humidity : 51%

Notes

1. For 9 kHz ~ 30 MHz, the amplitude of spurious emissions that are attenuated by more than 20dB below the permissible. The value has no need to be reported.
2. The spurious above 18GHz is noise only and 20dB below the limit. The value has no need to be reported.
3. All test modes had been pre-tested, but only the Bandwidth 20MHz at Middle channel of below 1 GHz is the worst case and recorded in the report.
4. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement -X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.




TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 32 of 69

Figure 19: Radiated Emission_30MHz-1GHz, Bandwidth 20MHz, 2437MHz
Horizontal Polarization



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	40.667	31.13	-25.16	40.0	8.87	Peak	81.40	100	Horizontal	Pass
2	49.880	24.02	-23.98	40.0	15.98	Peak	360.00	200	Horizontal	Pass
3	99.580	21.00	-25.71	43.5	22.50	Peak	321.60	200	Horizontal	Pass
4	125.001	34.88	-28.09	43.5	8.62	Peak	116.70	165	Horizontal	Pass
4*	125.001	34.25	-28.09	43.5	9.25	QP	116.70	165	Horizontal	Pass
5	170.130	26.27	-28.21	43.5	17.23	Peak	105.00	100	Horizontal	Pass
6	249.893	24.86	-23.52	46.0	21.14	Peak	85.50	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 33 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	33.734	35.23	-27.48	40.0	4.77	Peak	260.30	101	Vertical	Pass
1*	33.734	29.85	-27.48	40.0	10.15	QP	260.30	101	Vertical	Pass
2	35.562	31.46	-26.99	40.0	8.54	Peak	98.30	108	Vertical	Pass
2*	35.562	25.52	-26.99	40.0	14.48	QP	98.30	108	Vertical	Pass
3	36.041	33.49	-26.78	40.0	6.51	Peak	98.30	107	Vertical	Pass
3*	36.041	28.08	-26.78	40.0	11.92	QP	98.30	107	Vertical	Pass
4	36.733	36.66	-26.63	40.0	3.34	Peak	345.00	100	Vertical	Pass
4*	36.733	30.42	-26.63	40.0	9.58	QP	345.00	100	Vertical	Pass
5	37.517	37.48	-26.29	40.0	2.52	Peak	360.00	115	Vertical	Pass
5*	37.517	30.04	-26.29	40.0	9.96	QP	360.00	115	Vertical	Pass
6	39.493	35.71	-25.49	40.0	4.29	Peak	2.10	108	Vertical	Pass
6*	39.493	27.89	-25.49	40.0	12.11	QP	2.10	108	Vertical	Pass
7	40.456	33.48	-25.23	40.0	6.52	Peak	101.00	101	Vertical	Pass
7*	40.456	26.51	-25.23	40.0	13.49	QP	101.00	101	Vertical	Pass



TEST REPORT

Report No.: SHE23100021-01AE


Date: 2023-10-24

Page 34 of 69

Figure 20: Radiated Emission_1GHz-7GHz, Bandwidth 5MHz, 2405MHz

Horizontal Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1257.500	41.63	-13.34	74.0	32.37	Peak	285.60	100	Horizontal	Pass
1**	1257.500	30.03	-13.34	54.0	23.97	AV	285.60	100	Horizontal	Pass
2	1438.750	41.56	-12.68	74.0	32.44	Peak	357.70	100	Horizontal	Pass
2**	1438.750	30.45	-12.68	54.0	23.55	AV	357.70	100	Horizontal	Pass
3	1794.000	44.49	-12.43	74.0	29.51	Peak	110.00	100	Horizontal	Pass
3**	1794.000	33.99	-12.43	54.0	20.01	AV	110.00	100	Horizontal	Pass
4	2362.250	54.38	-8.05	74.0	19.62	Peak	186.80	100	Horizontal	Pass
4**	2362.250	43.83	-8.05	54.0	10.17	AV	186.80	100	Horizontal	Pass
5	2937.750	48.36	-4.42	74.0	25.64	Peak	262.40	100	Horizontal	Pass
5**	2937.750	37.15	-4.42	54.0	16.85	AV	262.40	100	Horizontal	Pass
6	4908.500	50.53	-0.78	74.0	23.47	Peak	288.70	100	Horizontal	Pass
6**	4908.500	40.42	-0.78	54.0	13.58	AV	288.70	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 35 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1307.000	41.29	-12.78	74.0	32.71	Peak	296.20	100	Vertical	Pass
1**	1307.000	30.28	-12.78	54.0	23.72	AV	296.20	100	Vertical	Pass
2	1793.500	42.60	-12.42	74.0	31.40	Peak	76.60	100	Vertical	Pass
2**	1793.500	35.58	-12.42	54.0	18.42	AV	76.60	100	Vertical	Pass
3	2361.000	49.19	-8.07	74.0	24.81	Peak	54.60	100	Vertical	Pass
3**	2361.000	38.55	-8.07	54.0	15.45	AV	54.60	100	Vertical	Pass
4	3030.500	47.70	-1.31	74.0	26.30	Peak	8.30	100	Vertical	Pass
4**	3030.500	38.21	-1.31	54.0	15.79	AV	8.30	100	Vertical	Pass
5	4714.000	50.22	-0.86	74.0	23.78	Peak	289.00	100	Vertical	Pass
5**	4714.000	40.43	-0.86	54.0	13.57	AV	289.00	100	Vertical	Pass
6	6020.500	54.06	1.91	74.0	19.94	Peak	289.00	100	Vertical	Pass
6**	6020.500	43.67	1.91	54.0	10.33	AV	289.00	100	Vertical	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 36 of 69

Figure 21: Radiated Emission_7GHz-18GHz, Bandwidth 5MHz, 2405MHz

Horizontal Polarization



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	8595.000	36.81	3.44	74.0	37.19	Peak	210.70	100	Horizontal	Pass
1**	8595.000	25.61	3.44	54.0	28.39	AV	210.70	100	Horizontal	Pass
2	9351.250	39.33	6.56	74.0	34.67	Peak	59.00	100	Horizontal	Pass
2**	9351.250	28.53	6.56	54.0	25.47	AV	59.00	100	Horizontal	Pass
3	11169.000	44.55	10.14	74.0	29.45	Peak	360.00	100	Horizontal	Pass
3**	11169.000	33.71	10.14	54.0	20.29	AV	360.00	100	Horizontal	Pass
4	12370.750	45.38	11.62	74.0	28.62	Peak	160.00	100	Horizontal	Pass
4**	12370.750	34.68	11.62	54.0	19.32	AV	160.00	100	Horizontal	Pass
5	14188.500	50.73	18.65	74.0	23.27	Peak	327.90	100	Horizontal	Pass
5**	14188.500	41.64	18.65	54.0	12.36	AV	327.90	100	Horizontal	Pass
6	14763.250	51.50	17.97	74.0	22.50	Peak	59.00	100	Horizontal	Pass
6**	14763.250	41.09	17.97	54.0	12.91	AV	59.00	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 37 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247_7GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	8771.000	36.46	3.96	74.0	37.54	Peak	274.00	100	Vertical	Pass
1**	8771.000	25.93	3.96	54.0	28.07	AV	274.00	100	Vertical	Pass
2	10489.750	41.43	9.12	74.0	32.57	Peak	68.20	100	Vertical	Pass
2**	10489.750	31.71	9.12	54.0	22.29	AV	68.20	100	Vertical	Pass
3	12401.000	45.14	11.79	74.0	28.86	Peak	360.00	100	Vertical	Pass
3**	12401.000	35.07	11.79	54.0	18.93	AV	360.00	100	Vertical	Pass
4	14180.250	50.61	18.41	74.0	23.39	Peak	189.80	100	Vertical	Pass
4**	14180.250	40.77	18.41	54.0	13.23	AV	189.80	100	Vertical	Pass
5	14485.500	50.90	16.95	74.0	23.10	Peak	68.20	100	Vertical	Pass
5**	14485.500	40.99	16.95	54.0	13.01	AV	68.20	100	Vertical	Pass
6	17865.251	59.01	23.71	74.0	14.99	Peak	325.20	100	Vertical	Pass
6**	17865.251	48.98	23.71	54.0	5.02	AV	325.20	100	Vertical	Pass



TEST REPORT

Report No.: SHE23100021-01AE


Date: 2023-10-24

Page 38 of 69

Figure 22: Radiated Emission_1GHz-7GHz, Bandwidth 5MHz, 2437MHz

Horizontal Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1297.250	41.62	-13.03	74.0	32.38	Peak	308.80	100	Horizontal	Pass
1**	1297.250	30.31	-13.03	54.0	23.69	AV	308.80	100	Horizontal	Pass
2	1792.750	43.48	-12.41	74.0	30.52	Peak	339.50	100	Horizontal	Pass
2**	1792.750	37.55	-12.41	54.0	16.45	AV	339.50	100	Horizontal	Pass
3	2235.000	45.60	-8.19	74.0	28.40	Peak	0.00	100	Horizontal	Pass
3**	2235.000	35.95	-8.19	54.0	18.05	AV	0.00	100	Horizontal	Pass
4	2392.250	52.11	-4.45	74.0	21.89	Peak	182.80	100	Horizontal	Pass
4**	2392.250	45.79	-4.45	54.0	8.21	AV	182.80	100	Horizontal	Pass
5	2847.000	48.62	-4.28	74.0	25.38	Peak	258.50	100	Horizontal	Pass
5**	2847.000	37.64	-4.28	54.0	16.36	AV	258.50	100	Horizontal	Pass
6	5102.000	50.67	0.37	74.0	23.33	Peak	173.90	100	Horizontal	Pass
6**	5102.000	40.70	0.37	54.0	13.30	AV	173.90	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 39 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1285.250	40.86	-13.00	74.0	33.14	Peak	12.10	100	Vertical	Pass
1**	1285.250	30.96	-13.00	54.0	23.04	AV	12.10	100	Vertical	Pass
2	1683.500	41.94	-13.04	74.0	32.06	Peak	86.20	100	Vertical	Pass
2**	1683.500	31.20	-13.04	54.0	22.80	AV	86.20	100	Vertical	Pass
3	2438.000	48.33	-5.43	74.0	25.67	Peak	86.20	100	Vertical	Pass
3**	2438.000	38.84	-5.43	54.0	15.16	AV	86.20	100	Vertical	Pass
4	2930.250	47.99	-4.65	74.0	26.01	Peak	258.90	100	Vertical	Pass
4**	2930.250	37.23	-4.65	54.0	16.77	AV	258.90	100	Vertical	Pass
5	3798.000	48.45	-3.06	74.0	25.55	Peak	161.20	100	Vertical	Pass
5**	3798.000	37.45	-3.06	54.0	16.55	AV	161.20	100	Vertical	Pass
6	5084.000	51.30	0.28	74.0	22.70	Peak	0.00	100	Vertical	Pass
6**	5084.000	40.57	0.28	54.0	13.43	AV	0.00	100	Vertical	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 40 of 69

Figure 23: Radiated Emission_7GHz-18GHz, Bandwidth 5MHz, 2437MHz

Horizontal Polarization



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	7957.000	35.38	2.75	74.0	38.62	Peak	240.20	100	Horizontal	Pass
1**	7957.000	24.31	2.75	54.0	29.69	AV	240.20	100	Horizontal	Pass
2	9087.250	38.85	5.36	74.0	35.15	Peak	199.20	100	Horizontal	Pass
2**	9087.250	27.01	5.36	54.0	26.99	AV	199.20	100	Horizontal	Pass
3	9884.750	42.02	8.51	74.0	31.98	Peak	325.40	100	Horizontal	Pass
3**	9884.750	30.27	8.51	54.0	23.73	AV	325.40	100	Horizontal	Pass
4	11683.250	44.38	10.44	74.0	29.62	Peak	19.80	100	Horizontal	Pass
4**	11683.250	32.61	10.44	54.0	21.39	AV	19.80	100	Horizontal	Pass
5	13198.500	46.55	13.20	74.0	27.45	Peak	251.10	100	Horizontal	Pass
5**	13198.500	36.42	13.20	54.0	17.58	AV	251.10	100	Horizontal	Pass
6	14185.750	52.52	18.59	74.0	21.48	Peak	325.40	100	Horizontal	Pass
6**	14185.750	41.14	18.59	54.0	12.86	AV	325.40	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 41 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247_7GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	7937.750	34.50	2.56	74.0	39.50	Peak	26.90	100	Vertical	Pass
1**	7937.750	24.24	2.56	54.0	29.76	AV	26.90	100	Vertical	Pass
2	9191.750	38.77	5.99	74.0	35.23	Peak	26.90	100	Vertical	Pass
2**	9191.750	27.56	5.99	54.0	26.44	AV	26.90	100	Vertical	Pass
3	10473.250	41.61	8.96	74.0	32.39	Peak	214.90	100	Vertical	Pass
3**	10473.250	31.38	8.96	54.0	22.62	AV	214.90	100	Vertical	Pass
4	11171.750	44.28	10.17	74.0	29.72	Peak	214.90	100	Vertical	Pass
4**	11171.750	33.74	10.17	54.0	20.26	AV	214.90	100	Vertical	Pass
5	14169.250	50.34	18.05	74.0	23.66	Peak	67.40	100	Vertical	Pass
5**	14169.250	40.84	18.05	54.0	13.16	AV	67.40	100	Vertical	Pass
6	14499.250	50.76	16.82	74.0	23.24	Peak	326.70	100	Vertical	Pass
6**	14499.250	40.37	16.82	54.0	13.63	AV	326.70	100	Vertical	Pass



TEST REPORT

Report No.: SHE23100021-01AE


Date: 2023-10-24

Page 42 of 69

Figure 24: Radiated Emission_1GHz-7GHz, Bandwidth 5MHz, 2469MHz

Horizontal Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1392.250	41.12	-12.75	74.0	32.88	Peak	209.20	100	Horizontal	Pass
1**	1392.250	30.98	-12.75	54.0	23.02	AV	209.20	100	Horizontal	Pass
2	1792.500	43.40	-12.41	74.0	30.60	Peak	114.60	100	Horizontal	Pass
2**	1792.500	34.02	-12.41	54.0	19.98	AV	114.60	100	Horizontal	Pass
3	2513.500	55.14	-6.82	74.0	18.86	Peak	345.30	100	Horizontal	Pass
3**	2513.500	45.25	-6.82	54.0	8.75	AV	345.30	100	Horizontal	Pass
4	2912.000	48.55	-4.48	74.0	25.45	Peak	0.00	100	Horizontal	Pass
4**	2912.000	37.39	-4.48	54.0	16.61	AV	0.00	100	Horizontal	Pass
5	3624.000	48.86	-2.24	74.0	25.14	Peak	295.40	100	Horizontal	Pass
5**	3624.000	37.79	-2.24	54.0	16.21	AV	295.40	100	Horizontal	Pass
6	5411.500	51.79	-0.36	74.0	22.21	Peak	359.10	100	Horizontal	Pass
6**	5411.500	41.60	-0.36	54.0	12.40	AV	359.10	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 43 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1328.250	41.31	-12.95	74.0	32.69	Peak	67.50	100	Vertical	Pass
1**	1328.250	30.75	-12.95	54.0	23.25	AV	67.50	100	Vertical	Pass
2	1427.750	41.48	-12.59	74.0	32.52	Peak	67.50	100	Vertical	Pass
2**	1427.750	31.30	-12.59	54.0	22.70	AV	67.50	100	Vertical	Pass
3	2203.750	44.89	-8.06	74.0	29.11	Peak	359.60	100	Vertical	Pass
3**	2203.750	34.61	-8.06	54.0	19.39	AV	359.60	100	Vertical	Pass
4	2400.250	48.57	-4.67	74.0	25.43	Peak	118.40	100	Vertical	Pass
4**	2400.250	38.92	-4.67	54.0	15.08	AV	118.40	100	Vertical	Pass
5	3025.500	47.98	-2.26	74.0	26.02	Peak	4.10	100	Vertical	Pass
5**	3025.500	38.31	-2.26	54.0	15.69	AV	4.10	100	Vertical	Pass
6	4674.500	50.29	-0.92	74.0	23.71	Peak	210.40	100	Vertical	Pass
6**	4674.500	40.63	-0.92	54.0	13.37	AV	210.40	100	Vertical	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 44 of 69

Figure 25: Radiated Emission_7GHz-18GHz, Bandwidth 5MHz, 2469MHz

Horizontal Polarization



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	7990.000	35.06	3.03	74.0	38.94	Peak	33.80	100	Horizontal	Pass
1**	7990.000	24.69	3.03	54.0	29.31	AV	33.80	100	Horizontal	Pass
2	9150.500	37.55	6.32	74.0	36.45	Peak	200.00	100	Horizontal	Pass
2**	9150.500	27.96	6.32	54.0	26.04	AV	200.00	100	Horizontal	Pass
3	10522.750	41.22	9.43	74.0	32.78	Peak	251.90	100	Horizontal	Pass
3**	10522.750	31.26	9.43	54.0	22.74	AV	251.90	100	Horizontal	Pass
4	12455.999	45.08	11.90	74.0	28.92	Peak	115.10	100	Horizontal	Pass
4**	12455.999	35.87	11.90	54.0	18.13	AV	115.10	100	Horizontal	Pass
5	14188.500	51.55	18.65	74.0	22.45	Peak	64.40	100	Horizontal	Pass
5**	14188.500	41.75	18.65	54.0	12.25	AV	64.40	100	Horizontal	Pass
6	17441.749	55.50	20.75	74.0	18.50	Peak	262.30	100	Horizontal	Pass
6**	17441.749	44.81	20.75	54.0	9.19	AV	262.30	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 45 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247_7GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	8501.500	35.13	2.91	74.0	38.87	Peak	173.00	100	Vertical	Pass
1**	8501.500	24.97	2.91	54.0	29.03	AV	173.00	100	Vertical	Pass
2	9920.500	40.35	8.96	74.0	33.65	Peak	0.00	100	Vertical	Pass
2**	9920.500	31.17	8.96	54.0	22.83	AV	0.00	100	Vertical	Pass
3	11257.000	43.30	11.14	74.0	30.70	Peak	268.80	100	Vertical	Pass
3**	11257.000	34.03	11.14	54.0	19.97	AV	268.80	100	Vertical	Pass
4	13539.500	46.29	13.87	74.0	27.71	Peak	173.00	100	Vertical	Pass
4**	13539.500	35.40	13.87	54.0	18.60	AV	173.00	100	Vertical	Pass
5	14757.750	51.13	17.91	74.0	22.87	Peak	142.10	100	Vertical	Pass
5**	14757.750	41.24	17.91	54.0	12.76	AV	142.10	100	Vertical	Pass
6	17474.750	55.59	21.50	74.0	18.41	Peak	0.00	100	Vertical	Pass
6**	17474.750	45.14	21.50	54.0	8.86	AV	0.00	100	Vertical	Pass



TEST REPORT

Report No.: SHE23100021-01AE


Date: 2023-10-24

Page 46 of 69

Figure 26: Radiated Emission_1GHz-7GHz, Bandwidth 20MHz, 2412MHz

Horizontal Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1263.750	40.30	-13.25	74.0	33.70	Peak	32.80	100	Horizontal	Pass
1**	1263.750	30.41	-13.25	54.0	23.59	AV	32.80	100	Horizontal	Pass
2	1792.750	44.17	-12.41	74.0	29.83	Peak	109.20	100	Horizontal	Pass
2**	1792.750	38.01	-12.41	54.0	15.99	AV	109.20	100	Horizontal	Pass
3	2392.500	54.48	-4.46	74.0	19.52	Peak	282.10	100	Horizontal	Pass
3**	2392.500	46.50	-4.46	54.0	7.50	AV	282.10	100	Horizontal	Pass
4	3047.500	48.29	1.90	74.0	25.71	Peak	105.60	100	Horizontal	Pass
4**	3047.500	38.40	1.90	54.0	15.60	AV	105.60	100	Horizontal	Pass
5	3711.500	48.99	-2.72	74.0	25.01	Peak	258.30	100	Horizontal	Pass
5**	3711.500	37.89	-2.72	54.0	16.11	AV	258.30	100	Horizontal	Pass
6	5666.000	53.43	0.54	74.0	20.57	Peak	11.20	100	Horizontal	Pass
6**	5666.000	42.77	0.54	54.0	11.23	AV	11.20	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 47 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1367.500	41.61	-12.69	74.0	32.39	Peak	83.90	100	Vertical	Pass
1**	1367.500	31.18	-12.69	54.0	22.82	AV	83.90	100	Vertical	Pass
2	1811.250	41.87	-12.28	74.0	32.13	Peak	274.20	100	Vertical	Pass
2**	1811.250	31.64	-12.28	54.0	22.36	AV	274.20	100	Vertical	Pass
3	2262.500	45.75	-7.26	74.0	28.25	Peak	201.50	100	Vertical	Pass
3**	2262.500	35.26	-7.26	54.0	18.74	AV	201.50	100	Vertical	Pass
4	2456.250	48.15	-5.78	74.0	25.85	Peak	243.30	100	Vertical	Pass
4**	2456.250	37.63	-5.78	54.0	16.37	AV	243.30	100	Vertical	Pass
5	4061.500	49.10	-1.36	74.0	24.90	Peak	40.90	100	Vertical	Pass
5**	4061.500	39.34	-1.36	54.0	14.66	AV	40.90	100	Vertical	Pass
6	5089.000	51.47	0.30	74.0	22.53	Peak	352.00	100	Vertical	Pass
6**	5089.000	41.57	0.30	54.0	12.43	AV	352.00	100	Vertical	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 48 of 69

Figure 27: Radiated Emission_7GHz-18GHz, Bandwidth 20MHz, 2412MHz

Horizontal Polarization



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	8430.000	34.81	2.79	74.0	39.19	Peak	347.80	100	Horizontal	Pass
1**	8430.000	24.17	2.79	54.0	29.83	AV	347.80	100	Horizontal	Pass
2	9343.000	39.58	6.51	74.0	34.42	Peak	241.80	100	Horizontal	Pass
2**	9343.000	28.47	6.51	54.0	25.53	AV	241.80	100	Horizontal	Pass
3	10844.500	43.28	10.18	74.0	30.72	Peak	74.00	100	Horizontal	Pass
3**	10844.500	32.71	10.18	54.0	21.29	AV	74.00	100	Horizontal	Pass
4	12436.750	45.54	11.85	74.0	28.46	Peak	74.00	100	Horizontal	Pass
4**	12436.750	36.11	11.85	54.0	17.89	AV	74.00	100	Horizontal	Pass
5	14496.500	51.37	16.84	74.0	22.63	Peak	74.00	100	Horizontal	Pass
5**	14496.500	41.25	16.84	54.0	12.75	AV	74.00	100	Horizontal	Pass
6	17529.750	55.34	20.87	74.0	18.66	Peak	241.80	100	Horizontal	Pass
6**	17529.750	44.53	20.87	54.0	9.47	AV	241.80	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 49 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247_7GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	8501.500	35.21	2.91	74.0	38.79	Peak	171.40	100	Vertical	Pass
1**	8501.500	24.78	2.91	54.0	29.22	AV	171.40	100	Vertical	Pass
2	9884.750	41.07	8.51	74.0	32.93	Peak	343.70	100	Vertical	Pass
2**	9884.750	30.41	8.51	54.0	23.59	AV	343.70	100	Vertical	Pass
3	10778.500	42.13	9.36	74.0	31.87	Peak	310.50	100	Vertical	Pass
3**	10778.500	31.71	9.36	54.0	22.29	AV	310.50	100	Vertical	Pass
4	12442.250	45.40	11.86	74.0	28.60	Peak	77.00	100	Vertical	Pass
4**	12442.250	35.42	11.86	54.0	18.58	AV	77.00	100	Vertical	Pass
5	13814.500	47.82	14.00	74.0	26.18	Peak	257.20	100	Vertical	Pass
5**	13814.500	37.69	14.00	54.0	16.31	AV	257.20	100	Vertical	Pass
6	14746.750	51.38	17.78	74.0	22.62	Peak	343.70	100	Vertical	Pass
6**	14746.750	41.26	17.78	54.0	12.74	AV	343.70	100	Vertical	Pass



TEST REPORT

Report No.: SHE23100021-01AE


Date: 2023-10-24

Page 50 of 69

Figure 28: Radiated Emission_1GHz-7GHz, Bandwidth 20MHz, 2437MHz

Horizontal Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1285.500	41.04	-13.01	74.0	32.96	Peak	279.20	100	Horizontal	Pass
1**	1285.500	30.75	-13.01	54.0	23.25	AV	279.20	100	Horizontal	Pass
2	1793.000	43.72	-12.42	74.0	30.28	Peak	110.00	100	Horizontal	Pass
2**	1793.000	34.68	-12.42	54.0	19.32	AV	110.00	100	Horizontal	Pass
3	2391.250	54.09	-5.61	74.0	19.91	Peak	191.00	100	Horizontal	Pass
3**	2391.250	45.06	-5.61	54.0	8.94	AV	191.00	100	Horizontal	Pass
4	2828.750	48.29	-4.59	74.0	25.71	Peak	201.40	100	Horizontal	Pass
4**	2828.750	37.66	-4.59	54.0	16.34	AV	201.40	100	Horizontal	Pass
5	4035.500	48.73	-1.59	74.0	25.27	Peak	220.30	100	Horizontal	Pass
5**	4035.500	39.13	-1.59	54.0	14.87	AV	220.30	100	Horizontal	Pass
6	5461.500	51.61	-0.01	74.0	22.39	Peak	307.00	100	Horizontal	Pass
6**	5461.500	41.55	-0.01	54.0	12.45	AV	307.00	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 51 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1317.250	41.10	-12.93	74.0	32.90	Peak	179.60	100	Vertical	Pass
1**	1317.250	30.46	-12.93	54.0	23.54	AV	179.60	100	Vertical	Pass
2	1555.000	41.52	-13.10	74.0	32.48	Peak	333.50	100	Vertical	Pass
2**	1555.000	29.82	-13.10	54.0	24.18	AV	333.50	100	Vertical	Pass
3	2391.750	48.96	-4.84	74.0	25.04	Peak	210.20	100	Vertical	Pass
3**	2391.750	40.00	-4.84	54.0	14.00	AV	210.20	100	Vertical	Pass
4	3026.000	48.59	-2.17	74.0	25.41	Peak	360.00	100	Vertical	Pass
4**	3026.000	38.18	-2.17	54.0	15.82	AV	360.00	100	Vertical	Pass
5	4052.000	48.64	-1.47	74.0	25.36	Peak	121.70	100	Vertical	Pass
5**	4052.000	38.94	-1.47	54.0	15.06	AV	121.70	100	Vertical	Pass
6	5113.000	51.21	0.41	74.0	22.79	Peak	24.10	100	Vertical	Pass
6**	5113.000	42.29	0.41	54.0	11.71	AV	24.10	100	Vertical	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 52 of 69

Figure 29: Radiated Emission_7GHz-18GHz, Bandwidth 20MHz, 2437MHz

Horizontal Polarization



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	8592.250	34.98	3.41	74.0	39.02	Peak	34.50	100	Horizontal	Pass
1**	8592.250	24.92	3.41	54.0	29.08	AV	34.50	100	Horizontal	Pass
2	9923.250	41.40	8.94	74.0	32.60	Peak	193.90	100	Horizontal	Pass
2**	9923.250	31.07	8.94	54.0	22.93	AV	193.90	100	Horizontal	Pass
3	11248.750	43.84	11.03	74.0	30.16	Peak	78.00	100	Horizontal	Pass
3**	11248.750	33.49	11.03	54.0	20.51	AV	78.00	100	Horizontal	Pass
4	12442.250	44.93	11.86	74.0	29.07	Peak	34.50	100	Horizontal	Pass
4**	12442.250	35.02	11.86	54.0	18.98	AV	34.50	100	Horizontal	Pass
5	14834.750	51.35	17.00	74.0	22.65	Peak	238.60	100	Horizontal	Pass
5**	14834.750	40.04	17.00	54.0	13.96	AV	238.60	100	Horizontal	Pass
6	17485.750	55.46	21.73	74.0	18.54	Peak	313.90	100	Horizontal	Pass
6**	17485.750	45.59	21.73	54.0	8.41	AV	313.90	100	Horizontal	Pass



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 53 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247_7GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	8699.500	36.06	3.70	74.0	37.94	Peak	285.30	100	Vertical	Pass
1**	8699.500	24.29	3.70	54.0	29.71	AV	285.30	100	Vertical	Pass
2	9967.250	40.32	8.63	74.0	33.68	Peak	357.60	100	Vertical	Pass
2**	9967.250	30.55	8.63	54.0	23.45	AV	357.60	100	Vertical	Pass
3	11246.000	43.72	10.99	74.0	30.28	Peak	0.00	100	Vertical	Pass
3**	11246.000	33.37	10.99	54.0	20.63	AV	0.00	100	Vertical	Pass
4	12447.750	45.16	11.87	74.0	28.84	Peak	3.50	100	Vertical	Pass
4**	12447.750	35.79	11.87	54.0	18.21	AV	3.50	100	Vertical	Pass
5	14152.750	50.73	17.51	74.0	23.27	Peak	0.00	100	Vertical	Pass
5**	14152.750	40.27	17.51	54.0	13.73	AV	0.00	100	Vertical	Pass
6	17485.750	55.38	21.73	74.0	18.62	Peak	148.40	100	Vertical	Pass
6**	17485.750	45.51	21.73	54.0	8.49	AV	148.40	100	Vertical	Pass



TEST REPORT

Report No.: SHE23100021-01AE


Date: 2023-10-24

Page 54 of 69

Figure 30: Radiated Emission_1GHz-7GHz, Bandwidth 20MHz, 2462MHz

Horizontal Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1265.750	39.81	-13.23	74.0	34.19	Peak	344.40	100	Horizontal	Pass
1**	1265.750	29.88	-13.23	54.0	24.12	AV	344.40	100	Horizontal	Pass
2	1792.250	44.21	-12.41	74.0	29.79	Peak	118.60	100	Horizontal	Pass
2**	1792.250	39.37	-12.41	54.0	14.63	AV	118.60	100	Horizontal	Pass
3	2508.000	54.24	-6.73	74.0	19.76	Peak	344.40	100	Horizontal	Pass
3**	2508.000	44.05	-6.73	54.0	9.95	AV	344.40	100	Horizontal	Pass
4	2926.750	47.40	-4.66	74.0	26.60	Peak	259.10	100	Horizontal	Pass
4**	2926.750	37.66	-4.66	54.0	16.34	AV	259.10	100	Horizontal	Pass
5	4095.000	49.20	-1.42	74.0	24.80	Peak	219.30	100	Horizontal	Pass
5**	4095.000	39.22	-1.42	54.0	14.78	AV	219.30	100	Horizontal	Pass
6	6431.500	54.48	2.84	74.0	19.52	Peak	91.30	100	Horizontal	Pass
6**	6431.500	44.49	2.84	54.0	9.51	AV	91.30	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 55 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_1GHz-7GHz RSE



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1333.250	40.53	-12.92	74.0	33.47	Peak	53.10	100	Vertical	Pass
1**	1333.250	30.83	-12.92	54.0	23.17	AV	53.10	100	Vertical	Pass
2	1813.750	43.07	-12.24	74.0	30.93	Peak	274.60	100	Vertical	Pass
2**	1813.750	31.36	-12.24	54.0	22.64	AV	274.60	100	Vertical	Pass
3	2438.000	59.78	-5.43	74.0	14.22	Peak	74.00	100	Vertical	Pass
3**	2438.000	38.51	-5.43	54.0	15.49	AV	74.00	100	Vertical	Pass
4	3048.500	47.81	2.09	74.0	26.19	Peak	11.20	100	Vertical	Pass
4**	3048.500	37.67	2.09	54.0	16.33	AV	11.20	100	Vertical	Pass
5	4049.500	48.74	-1.50	74.0	25.26	Peak	295.90	100	Vertical	Pass
5**	4049.500	38.81	-1.50	54.0	15.19	AV	295.90	100	Vertical	Pass
6	5665.000	52.94	0.55	74.0	21.06	Peak	42.90	100	Vertical	Pass
6**	5665.000	42.14	0.55	54.0	11.86	AV	42.90	100	Vertical	Pass



TEST REPORT

Report No.: SHE23100021-01AE


Date: 2023-10-24

Page 56 of 69

Figure 31: Radiated Emission_7GHz-18GHz, Bandwidth 20MHz, 2462MHz

Horizontal Polarization

REmission Test case_FCC_Part 15C_FCC 15.247_7GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	8031.250	34.75	3.63	74.0	39.25	Peak	360.00	100	Horizontal	Pass
1**	8031.250	25.26	3.63	54.0	28.74	AV	360.00	100	Horizontal	Pass
2	10140.500	40.66	8.45	74.0	33.34	Peak	328.40	100	Horizontal	Pass
2**	10140.500	31.08	8.45	54.0	22.92	AV	328.40	100	Horizontal	Pass
3	11210.250	44.12	10.55	74.0	29.88	Peak	182.40	100	Horizontal	Pass
3**	11210.250	33.53	10.55	54.0	20.47	AV	182.40	100	Horizontal	Pass
4	13820.000	47.96	14.01	74.0	26.04	Peak	328.40	100	Horizontal	Pass
4**	13820.000	38.12	14.01	54.0	15.88	AV	328.40	100	Horizontal	Pass
5	14510.250	50.96	16.73	74.0	23.04	Peak	360.00	100	Horizontal	Pass
5**	14510.250	41.00	16.73	54.0	13.00	AV	360.00	100	Horizontal	Pass
6	17504.999	55.39	21.37	74.0	18.61	Peak	68.70	100	Horizontal	Pass
6**	17504.999	45.67	21.37	54.0	8.33	AV	68.70	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 57 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247_7GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	8020.250	34.89	3.45	74.0	39.11	Peak	246.10	100	Vertical	Pass
1**	8020.250	24.31	3.45	54.0	29.69	AV	246.10	100	Vertical	Pass
2	9494.250	38.63	6.99	74.0	35.37	Peak	360.00	100	Vertical	Pass
2**	9494.250	28.71	6.99	54.0	25.29	AV	360.00	100	Vertical	Pass
3	10841.750	41.97	10.15	74.0	32.03	Peak	360.00	100	Vertical	Pass
3**	10841.750	32.96	10.15	54.0	21.04	AV	360.00	100	Vertical	Pass
4	11262.500	44.15	11.22	74.0	29.85	Peak	329.10	100	Vertical	Pass
4**	11262.500	34.27	11.22	54.0	19.73	AV	329.10	100	Vertical	Pass
5	13803.500	47.50	13.98	74.0	26.50	Peak	205.00	100	Vertical	Pass
5**	13803.500	37.77	13.98	54.0	16.23	AV	205.00	100	Vertical	Pass
6	14733.000	51.30	17.62	74.0	22.70	Peak	14.00	100	Vertical	Pass
6**	14733.000	41.59	17.62	54.0	12.41	AV	14.00	100	Vertical	Pass



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 58 of 69

4.1.7 Band Edge (Restricted-band band-edge)

RESULT:

PASS


Test standard : FCC Part 15.247(d), 15.205, 15.209
Requirement : ANSI C63.10-2013 clause 11.13,
KDB 558074 D01 v05r02, Clause 8.7
Kind of test site : 3m Semi-Anechoic Chamber

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1
Ambient temperature : 24.5°C
Relative humidity : 53%

Figure 32: Band Edge(Restricted-band band-edge), Bandwidth 5MHz, 2405MHz

Horizontal Polarization



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2362.437	56.97	-10.54	74.0	17.03	Peak	0.20	100	Horizontal	Pass
1**	2362.437	47.31	-10.54	54.0	6.69	AV	0.20	100	Horizontal	Pass
2	2390.000	51.37	-10.27	74.0	22.63	Peak	62.15	100	Horizontal	Pass
2**	2390.000	43.02	-10.27	54.0	10.98	AV	62.15	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 59 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_bandedge 2400



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2363.045	56.51	-10.53	74.0	17.49	Peak	52.90	100	Vertical	Pass
1**	2363.045	45.46	-10.53	54.0	8.54	AV	52.90	100	Vertical	Pass
2	2390.000	50.92	-10.27	74.0	23.08	Peak	158.59	100	Vertical	Pass
2**	2390.000	42.95	-10.27	54.0	11.05	AV	158.59	100	Vertical	Pass




TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 60 of 69

Figure 33: Band Edge(Restricted-band band-edge), Bandwidth 5MHz, 2469MHz
Horizontal Polarization



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	51.45	-9.82	74.0	22.55	Peak	178.54	100	Horizontal	Pass
1**	2483.500	43.26	-9.82	54.0	10.74	AV	178.54	100	Horizontal	Pass
2	2485.625	54.79	-9.82	74.0	19.21	Peak	250.80	100	Horizontal	Pass
2**	2485.625	43.46	-9.82	54.0	10.54	AV	250.80	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 61 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_bandedge 2400



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	51.32	-9.82	74.0	22.68	Peak	303.64	100	Vertical	Pass
1**	2483.500	42.55	-9.82	54.0	11.45	AV	303.64	100	Vertical	Pass
2	2488.798	54.88	-9.82	74.0	19.12	Peak	252.50	100	Vertical	Pass
2**	2488.798	43.31	-9.82	54.0	10.69	AV	252.50	100	Vertical	Pass




TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 62 of 69

Figure 34: Band Edge(Restricted-band band-edge), Bandwidth 20MHz, 2412MHz
Horizontal Polarization



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2375.600	55.78	-10.47	74.0	18.22	Peak	79.40	100	Horizontal	Pass
1**	2375.600	45.50	-10.47	54.0	8.50	AV	79.40	100	Horizontal	Pass
2	2390.000	51.97	-10.27	74.0	22.03	Peak	202.65	100	Horizontal	Pass
2**	2390.000	43.97	-10.27	54.0	10.03	AV	202.65	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 63 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_bandedge 2400



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2376.748	56.91	-10.46	74.0	17.09	Peak	14.30	100	Vertical	Pass
1**	2376.748	46.03	-10.46	54.0	7.97	AV	14.30	100	Vertical	Pass
2	2390.000	52.76	-10.27	74.0	21.24	Peak	243.89	100	Vertical	Pass
2**	2390.000	44.65	-10.27	54.0	9.35	AV	243.89	100	Vertical	Pass




TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 64 of 69

Figure 35: Band Edge(Restricted-band band-edge), Bandwidth 20MHz, 2462MHz
Horizontal Polarization



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2478.605	59.25	-9.82	74.0	14.75	Peak	127.60	100	Horizontal	Pass
1**	2478.605	47.66	-9.82	54.0	6.34	AV	127.60	100	Horizontal	Pass
2	2483.500	52.08	-9.82	74.0	21.92	Peak	127.60	100	Horizontal	Pass
2**	2483.500	44.10	-9.82	54.0	9.90	AV	127.60	100	Horizontal	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 65 of 69

Vertical Polarization

REmission Test case_FCC_Part 15C_FCC 15.247(2.4G)_bandedge 2400



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
2	2483.500	51.54	-9.82	74.0	22.46	Peak	171.96	100	Vertical	Pass
2**	2483.500	43.11	-9.82	54.0	10.89	AV	171.96	100	Vertical	Pass
3	2492.577	54.54	-9.81	74.0	19.46	Peak	228.50	100	Vertical	Pass
3**	2492.577	43.24	-9.81	54.0	10.76	AV	228.50	100	Vertical	Pass



TEST REPORT


Report No.: SHE23100021-01AE

Date: 2023-10-24


Page 66 of 69

5 Appendixes

5.1 Photographs of the Sample



Front of the sample



Rear of the sample



TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 67 of 69

5.2 Set-up for Conducted RF test at Antenna Port



5.3 Set-up for Spurious Emissions below 1GHz






TEST REPORT

Report No.: SHE23100021-01AE

Date: 2023-10-24

Page 68 of 69

5.4 Set-up for Spurious Emissions above 1GHz



End of the report

声明 Terms & conditions

1. 英格尔检测技术服务（上海）有限公司（以下简称“本公司”）以保密的方法处理及签发有关报告予客户。在未得本公司的同意下，该报告不得作部分翻制，或作宣传或其它未经本公司许可的用途。当该客户从本公司收到有关报告后，可以展示或传送该报告或由本公司所制定该报告的核证版本予其顾客、供应商或其它直接有关人士。除非被有关政府机构、法律或法庭命令所要求，本公司在未经客户的同意前，将不会与其他方就报告的内容进行任何讨论、书信的往来或透露。

A report will be issued in confidence to the Clients and it will be strictly treated as such by ICAS Testing Technology Service (Shanghai) Co., Ltd. (hereinafter referred to as "ICAS"). It should not be reproduced in part and it should not be used for advertising or other unauthorized purposes without the written consent of ICAS. The Clients to whom the Report is issued, however, show or send it, or a certified copy thereof prepared by ICAS, to his customer, supplier or other persons directly concerned. ICAS will, without the consent of the Clients, neither enter into any discussion or correspondence with nor disclose to any other party concerning the contents of the report unless required by the relevant governmental authorities, laws or court orders.

2. 假若该客户准备利用本公司所签发的报告在司法或仲裁程序上，该客户于呈交样品予本公司作测试前必须明确阐述此用途。
If the client is prepared to use the report issued by ICAS in the judicial or arbitral, the client must specify this use before submitting the sample to ICAS for testing.
3. 除非本公司的确进行抽样测试及于有关报告内阐明此项事实，该报告只适用于已被测试的样品，而不适用于大量额度的有关货品。
Unless ICAS does carry out a sampling test and clarify this fact in the relevant report, the report applies only to the samples that have been tested and do not apply to a large amount of the relevant goods.
4. 假若该客户并未指定该测试所应用的测试方法或标准，本公司将会自行选择适当的方法或标准并在委托协议 / 合同中告知。
If the Clients do not specify the methods / standards to be applied, ICAS will choose the appropriate methods/standards and inform the client in the agreement/contract.
5. 本公司对由于利用本公司所签发的任何报告或通讯内的资料而造成的损失，概不会承担任何责任。
ICAS will not be liable or accept responsibility for any loss or damage arising from the use of in the reports issued by ICAS or communication information.
6. 假若该报告被不适当地运用，本公司将会保留权利撤回该报告，及采取任何适当的措施。
If the report is inappropriately used, ICAS will reserve the right to withdraw the report and take any appropriate action.
7. 该客户同意其委托本公司进行测试所得出之报告，并不能作为针对本公司法律行动的依据。
Samples submitted for testing are accepted on the understanding that the report issued cannot form the basis of, or be the instrument for, legal action against ICAS.
8. 假若该客户的要求令致有关该样品的测试须于该客户或任何第三方的实验室进行，则本公司只会代为传送有关该测试的结果，对其准确性概不负任何责任。如本公司只可证明该客户或任何第三方的实验室已进行有关测试，则本公司只可确认某正确的样品已经被测试，而毋须为该测试的准确性负任何责任。
If the Clients require the analysis of samples by the Client's or any third party's laboratory, ICAS will only convey the result of the analysis without responsibility for its accuracy. If ICAS is only able to witness an analysis by the Client's or any third party's laboratory ICAS will only confirm that the correct sample has been analyzed without responsibility for the accuracy of any analysis or results.
9. 本公司在提供测试服务期间所衍生的任何报告、证书或其它物资，其相关的所有法律产权（包括知识产权），皆由本公司所拥有。
Any legal property right (include intellectual property) in respect of any report, certificate or other materials derived from ICAS during the provision of the testing service are owned by ICAS.
10. 当本公司收到该客户的请求，本公司可以电子媒介传递有关测试服务的结果，但该客户应注意，电子媒介传递不能保证其所含资料不会流失、延误或被其他方截取。对于电子媒介传递导致其所含的任何资料出现泄露、差错或遗漏，本公司将不会负任何责任。
When ICAS receives the request from the Client, ICAS transmit the results of the test service in electronic media, but the Client should note that the Electronic Media Delivery does not guarantee that the information contained therein will not be lost, delayed or intercepted by third party. ICAS is not liable for any disclosure, error or omission in the content of such messages as a result of electronic transmission.
11. 本公司对其可控范围之外发生的样品质量或其它特征的变化不承担责任。本报告不具有对测试项目或样品推荐或认可的作用。
ICAS assumes no responsibility for variations in quality or other characteristics of items submitted under conditions over which ICAS has no control. This Report does not constitute a recommendation for, or endorsement of, the item or material tested.
12. 本公司经与客户协商一致出具纸质版或电子版形式的报告：报告涂改无效；无授权签字人签字无效；纸质版报告未加盖本公司“检验检测专用章”或“报告专用章”和骑缝章无效；电子版报告未加盖本公司“检验检测专用章”或“报告专用章”无效。
The company issues the report in paper or electronic form through consultation with the customer. The report is invalid if altered or without authorized signatory; The paper version of the report is invalid without the company's "special seal for inspection and testing" or "special seal for report" and the cross seal; The electronic version of the report is invalid without the company's "special seal for inspection and testing" or "special seal for report".
13. 对报告若有异议，有法律法规规定的，依照法律法规执行。其它委托类型报告应于收到报告之日起十五日内向本公司提出，逾期不予受理。
Any objection to the report should execute according to laws and regulations if exist, other entrusted report should be submitted to ICAS within 15 days from the date of receiving the report, and overdue will not be handled.
14. 样品及样品信息由客户提供及确认。本公司不负责证实样品的真伪性，不承担证实客户提供信息的准确性、适当性和（或）完整性责任。
The sample(s) and sample information should be provided and confirmed by the Client. ICAS is not responsible for verifying the authenticity of the sample and does not assume responsibility for the accuracy, appropriateness and/or completeness of the information provided by the Client.
15. 不包含 CMA 资质认定标志的报告，检测数据和结果不具有对社会的证明作用，仅供科研、教学、内部质量控制之用。中英文报告内容以中文为准。
The date and results shown in the report without CMA logo are not used as proof for society, only used for reference in study, teaching and internal quality control. The Chinese version of the report written in Chinese and English shall prevail.

备注：1. 报告中带“*”代表暂未在 CNAS 范围内，“§”代表暂未在本公司 CMA 资质认定许可技术能力。

Note: “*”in the report indicates that it is not included in the scope of CNAS, “§” indicates that it is not included in the CMA scope of ICAS.

2. “#”号代表数据来源于指定的签约实验室

“#” indicated that data comes from designated contracted lab:

CMA 资质认定证书编号 CMA Certificate No:

CNAS 注册号 CNAS Registration No:

ICAS 英格尔检测中心 ICAS Testing Center
Tel: 0086 21-51682918 E-mail: info@icas.org.cn
Add: 上海市闵行区瓶北路 155 号/瓶安路 1298 号/徐汇区中山西路 2368 号 18F
155 Pingbai Rd / 1298 Pingan Rd, Minhang District, Shanghai/18F, 2368W Zhongshan Rd, Xuhui District.

ICAS 英格尔认证中心 ICAS Certification Center
Tel: 0086 21-51114700 E-mail: info@icas.org.cn
Add: 上海市徐汇区中山西路 2368 号华鼎大厦 31F/25F
31/25F Huading Tower, 2368W Zhongshan Rd, Xuhui District, Shanghai

ICAS 全国各分支机构 温州 / 广州 / 深圳 / 福州 / 厦门 / 昆明 / 南宁 / 长沙 / 重庆 / 成都 / 南京 / 合肥 / 青岛 / 郑州 / 济南 / 江西 / 天津
ICAS National Branch Offices Wenzhou/Guangzhou/Shenzhen/Fuzhou/Xiamen/Kunming/Nanning/Changsha/Chongqing/Chengdu/Nanjing/Hefei/Qingdao/Zhengzhou/Jinan/Jiangxi/Tianjin