

Appendix IV RF Exposure evaluation

FCC ID: 2BCR5-N75V2

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$
$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison.

BLE:

Worse case output power is as below: [2480MHz: 1.27dBm]

Maximum output power is 1.27dBm (1.34 mW).

$$(1.34\text{mW} / 5\text{mm}) \cdot [\sqrt{2.480(\text{GHz})}] = 0.42 < 3.0 \text{ for 1-g SAR.}$$

2.4G:

Worse case output power is as below: [2440MHz: 1.80dBm]

Maximum output power is 1.80dBm (1.51 mW).

$$(1.51\text{mW} / 5\text{mm}) \cdot [\sqrt{2.440(\text{GHz})}] = 0.47 < 3.0 \text{ for 1-g SAR.}$$

Then SAR evaluation is not required.