



HUAKE TESTING

802.11n (HT40) Modulation


Lowest Channel

Band Edge




Highest Channel




Band Edge





Spurious Emission






Spurious Emission



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



Middle Channel Spurious Emission





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



802.11ax (HE20) Modulation



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




Middle Channel Spurious Emission





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.





802.11ax (HE40) Modulation



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




Middle Channel Spurious Emission





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

4.6 Radiated Spurious Emission Measurement

Test Specification

Test Requirement:	FCC Part15 C Section 15.209					
Test Method:	ANSI C63.10: 2020					
Frequency Range:	9 kHz to 26 GHz					
Measurement Distance:	3 m					
Antenna Polarization:	Horizontal & Vertical					
Operation Mode:	Transmitting mode with modulation					
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark	
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
		Peak	1MHz	10Hz	Average Value	
Limit:	Frequency		Field Strength (microvolts/meter)		Measurement Distance (meters)	
	0.009-0.490		2400/F(KHz)		300	
	0.490-1.705		24000/F(KHz)		30	
	1.705-30		30		30	
	30-88		100		3	
	88-216		150		3	
	216-960		200		3	
	Above 960		500		3	
	Frequency		Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector	
	Above 1GHz		500	3	Average	
			5000	3	Peak	
	Test Setup:	For radiated emissions below 30MHz				
						

	30MHz to 1GHz  Above 1GHz 
Test Procedure:	1. For the radiated emission test below 1GHz: The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level. 2. For the radiated emission test above 1GHz: Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal.

	The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. 3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level 4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. 5. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=120 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement. 6. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test Results:	PASS



Test Instruments

Radiated Emission Test Site (966)					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum analyzer	Agilent	N9020A	HKE-025	Feb. 19, 2025	Feb. 18, 2026
Spectrum analyzer	KEYSIGHT	N9020A	HKE-117	Feb. 19, 2025	Feb. 18, 2026
Spectrum analyzer	R&S	FSV3044	HKE-126	Feb. 19, 2025	Feb. 18, 2026
Preamplifier	Schwarzbeck	EMC051845S E	HKE-006	Feb. 19, 2025	Feb. 18, 2026
Preamplifier	Agilent	83051A	HKE-016	Feb. 19, 2025	Feb. 18, 2026
Preamplifier	QJD	QJD18-40-50	HKE-030	Feb. 19, 2025	Feb. 18, 2026
6dB Attenuator	Pasternack	6dB	HKE-152	Feb. 19, 2025	Feb. 18, 2026
EMI Test Receiver	R&S	ESR-7	HKE-010	Feb. 19, 2025	Feb. 18, 2026
Broadband Antenna	Schwarzbeck	VULB9168	HKE-167	Feb. 21, 2024	Feb. 20, 2026
Loop Antenna	COM-POWER	AL-130R	HKE-014	Feb. 21, 2024	Feb. 20, 2026
Horn Antenna	Schwarzbeck	9120D	HKE-013	Feb. 21, 2024	Feb. 20, 2026
Broadband Horn Antenna	A-INFO	LB-180400-KF	HKE-031	Feb. 21, 2024	Feb. 20, 2026
EMI Test Software	Tonscend	JS32-RE 5.0.0	HKE-082	/	/
RSE Test Software	Tonscend	JS36-RSE 5.0.0	HKE-184	/	/




Radiated Emission Test Site (966)					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum analyzer	Agilent	N9020A	HKE-025	Feb. 06, 2026	Feb. 05, 2027
Spectrum analyzer	KEYSIGHT	N9020A	HKE-117	Feb. 06, 2026	Feb. 05, 2027
Spectrum analyzer	R&S	FSV3044	HKE-126	Feb. 06, 2026	Feb. 05, 2027
Preamplifier	Schwarzbeck	EMC051845SE	HKE-006	Feb. 04, 2026	Feb. 03, 2027
Preamplifier	Agilent	83051A	HKE-016	Feb. 04, 2026	Feb. 03, 2027
Preamplifier	QJD	QJD18-40-50	HKE-030	Feb. 05, 2026	Feb. 04, 2027
6dB Attenuator	Pasternack	6dB	HKE-152	Feb. 06, 2026	Feb. 05, 2027
EMI Test Receiver	R&S	ESR-7	HKE-010	Feb. 06, 2026	Feb. 05, 2027
Broadband Antenna	Schwarzbeck	VULB9168	HKE-167	Feb. 06, 2026	Feb. 05, 2028
Loop Antenna	COM-POWER	AL-130R	HKE-014	Feb. 06, 2026	Feb. 05, 2028
Horn Antenna	Schwarzbeck	9120D	HKE-013	Feb. 06, 2026	Feb. 05, 2028
Broadband Horn Antenna	A-INFO	LB-180400-KF	HKE-031	Feb. 06, 2026	Feb. 05, 2028
EMI Test Software	Tonscend	JS32-RE 5.0.0	HKE-082	/	/
RSE Test Software	Tonscend	JS36-RSE 5.0.0	HKE-184	/	/

Test Data

Below 1GHz Test Results

All the test modes completed for test. Only the worst result was reported as below:


Antenna polarity: Horizontal



Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	64.955	-15.07	26.11	11.04	40.00	28.96	100	154	Horizontal
2	125.155	-17.32	37.80	20.48	43.50	23.02	100	318	Horizontal
3	223.223	-14.17	40.33	26.16	46.00	19.84	100	122	Horizontal
4	264.004	-12.71	44.63	31.92	46.00	14.08	100	51	Horizontal
5	376.637	-10.42	49.58	39.16	46.00	6.84	100	201	Horizontal
6	648.509	-4.79	30.50	25.71	46.00	20.29	100	197	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical



Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	71.752	-17.75	38.71	20.96	40.00	19.04	100	41	Vertical
2	124.184	-17.12	46.78	29.66	43.50	13.84	100	282	Vertical
3	220.310	-14.27	40.40	26.13	46.00	19.87	100	37	Vertical
4	264.004	-12.71	41.76	29.05	46.00	16.95	100	182	Vertical
5	383.433	-10.18	40.90	30.72	46.00	15.28	100	83	Vertical
6	594.134	-5.70	34.10	28.40	46.00	17.60	100	182	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Harmonics and Spurious Emissions

Frequency Range (9kHz-30MHz)

Frequency (MHz)	Level@3m (dBμV/m)	Limit@3m (dBμV/m)
--	--	--
--	--	--
--	--	--
--	--	--

Note: 1. Emission Level=Reading+ Cable loss-Antenna factor-Amp factor.


2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement.

Above 1GHz Test Results

All the test modes completed for test. Only the worst result was reported as below:

For 1GHz to 18GHz


Antenna polarity: Horizontal



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1671.467	54.35	35.81	-18.54	74.00	38.19	150	340	Horizontal
2	4396.640	52.13	41.17	-10.96	74.00	32.83	150	190	Horizontal
3	7717.972	51.10	48.38	-2.72	74.00	25.62	150	50	Horizontal
4	9344.134	50.27	49.55	-0.72	74.00	24.45	150	330	Horizontal
5	10802.280	49.64	51.35	1.71	74.00	22.65	150	110	Horizontal
6	14123.612	46.94	53.45	6.51	74.00	20.55	150	140	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical




Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1977.498	53.34	36.60	-16.74	74.00	37.40	150	150	Vertical
2	2924.792	53.35	39.93	-13.42	74.00	34.07	150	130	Vertical
3	4699.670	51.38	41.42	-9.96	74.00	32.58	150	130	Vertical
4	7848.485	50.67	48.18	-2.49	74.00	25.82	150	280	Vertical
5	9291.629	51.20	50.37	-0.83	74.00	23.63	150	120	Vertical
6	10910.291	49.40	51.39	1.99	74.00	22.61	150	50	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

For 18GHz to 26GHz


Antenna polarity: Horizontal



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	19182.518	40.02	45.92	5.90	74.00	28.08	150	10	Horizontal
2	20119.412	40.54	46.67	6.13	74.00	27.33	150	350	Horizontal
3	20732.273	40.67	46.41	5.74	74.00	27.59	150	200	Horizontal
4	21245.925	42.19	47.46	5.27	74.00	26.54	150	50	Horizontal
5	21987.599	42.30	48.03	5.73	74.00	25.97	150	90	Horizontal
6	22436.444	43.26	48.93	5.67	74.00	25.07	150	250	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	19147.315	39.44	45.30	5.86	74.00	28.70	150	70	Vertical
2	20024.202	40.12	46.31	6.19	74.00	27.69	150	160	Vertical
3	20648.265	40.56	46.38	5.82	74.00	27.62	150	30	Vertical
4	21353.135	41.67	46.95	5.28	74.00	27.05	150	150	Vertical
5	21882.788	42.37	48.01	5.64	74.00	25.99	150	90	Vertical
6	22330.033	42.76	48.47	5.71	74.00	25.53	150	260	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

4.7 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction


The antenna used in this product is a FPC Antenna, need professional installation, not easy to remove. It conforms to the standard requirements. The directional gains of antenna used for transmitting is 3.36dBi.

WIFI Antenna



5. Test Setup Photos of the EUT


Radiated Emission



AC Conducted Emission



RF Conducted Emission



6. Photos of the EUT

Reference to the report: ANNEX A of external photos and ANNEX B of internal photos.

-----End of test report-----