

Prüfbericht-Nr.: Test report no.:	CN24LUJJ 001	Auftrags-Nr.: Order no.:	168496151	Seite 1 von 22 Page 1 of 22
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2024-07-25	
Auftraggeber: Client:	OHM (Chongqing) Electronics Technology CO., LTD. Chongqing District International Students Busi. chongqing, China			
Prüfgegenstand: Test item:	Remote Control			
Bezeichnung / Typ-Nr.: Identification / Type no.:	TCT-E10Z			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	CFR Title 47 FCC Part 15: Subpart C Section 15.247			
Wareneingangsdatum: Date of sample receipt:	2026-03-11	Please refer to photo documents		
Prüfmuster-Nr.: Test sample no.:	A004222466-001~021			
Prüfzeitraum: Testing period:	2026-03-26 - 2026-03-28			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	<u>X Bell Hu</u>		genehmigt von: authorized by:	<u>X Jonathan Li</u>
Datum: Date:	2026-05-27	Ausstellungsdatum: Issue date:		2026-05-27
Signed by: Bell Hu		Signed by: Jonathan Li		
Stellung / Position:	Sachverständige(r)/Expert	Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / Other:	FCC ID: 2BCT6-0004			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:		Prüfmuster vollständig und unbeschädigt Test item complete and undamaged		
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN24LUJJ 001
Test report no.:

Seite 2 von 22
Page 2 of 22

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfbedingungen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

RESULT: Pass

5.1.3 99% BANDWIDTH

RESULT: Pass

5.1.4 20dB BANDWIDTH

RESULT: Pass

5.1.5 CARRIER FREQUENCY SEPARATION

RESULT: Pass

5.1.6 NUMBER OF HOPPING FREQUENCY

RESULT: Pass

5.1.7 TIME OF OCCUPANCY

RESULT: Pass

5.1.8 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH

RESULT: Pass

5.1.9 RADIATED SPURIOUS EMISSION

RESULT: Pass

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	8
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	9
3.5	SUBMITTED DOCUMENTS.....	9
4	TEST SET-UP AND OPERATION MODES	10
4.1	PRINCIPLE OF CONFIGURATION SELECTION	10
4.2	TEST OPERATION AND TEST SOFTWARE.....	10
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	10
4.5	TEST SETUP DIAGRAM	11
5	TEST RESULTS	13
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	13
5.1.1	<i>Antenna Requirement</i>	<i>13</i>
5.1.2	<i>Maximum Peak Conducted Output Power</i>	<i>14</i>
5.1.3	<i>99% Bandwidth</i>	<i>15</i>
5.1.4	<i>20dB Bandwidth</i>	<i>16</i>
5.1.5	<i>Carrier Frequency Separation.....</i>	<i>17</i>
5.1.6	<i>Number of Hopping Frequency</i>	<i>18</i>
5.1.7	<i>Time of Occupancy</i>	<i>19</i>
5.1.8	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth</i>	<i>20</i>
5.1.9	<i>Radiated Spurious Emission</i>	<i>21</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	22
7	LIST OF TABLES.....	22

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of 915MHz band SRD

Appendix B: Photographs of the Test Set-up

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China

FCC Accreditation Designation No.: 694916

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (TS8997)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
Signal Analyzer	R&S	FSV 40	101441	2025-09-23	2026-09-22
OSP	R&S	OSP 150	101017	2025-10-30	2026-10-29
Control PC	DELL	OptiPlex 7050	FTJZ9P2	N/A	N/A
Test Software	R&S	WMS32 (V11.00.00)	N/A	N/A	N/A
Power Meter	R&S	NRP2	107105	2025-10-30	2026-10-29
Wideband Power Sensor	R&S	NRP-Z81	105677	2025-09-23	2026-09-22
Shielding Room	Albatross	SR1	APC17151-SR1	2024-09-14	2027-09-13
Unwanted Emission Testing (TS9975)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	2025-09-22	2026-09-21
Signal Analyzer	R&S	FSV 40	101439	2025-09-22	2026-09-21
System Controller Interface	R&S	SCI-100	S10010038	N/A	N/A
Filterbank	R&S	Wlan	100759	2025-09-22	2026-09-21
OSP	R&S	OSP 120	102040	N/A	N/A
Pre-amplifier	R&S	SCU08F1	08320031	2025-09-22	2026-09-21
Amplifier	R&S	SCU-18F	180070	2025-09-22	2026-09-21
Amplifier	R&S	SCU40A	100475	2025-09-22	2026-09-21
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	2024-09-28	2026-09-27
Double-Ridged Antenna(1 -18 GHz)	ETS-LINDGREN	3117	00218717	2024-09-28	2026-09-27
Wideband Ridged Horn Antenna(18-40 GHz)	Steatite	QMS-00880	19067	2024-09-28	2026-09-27
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	2024-09-28	2026-09-27
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A	N/A

Prüfbericht - Nr.: CN24LUJJ 001
Test Report No.:Seite 7 von 22
Page 7 of 22

3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	2024-09-14	2027-09-13
--------------------------	-----------	--------	--------------	------------	------------

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Table 2: Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	± 4.17 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The product is a remote control, which supports 915MHz SRD function.

For details refer to the User Manual, Technical Description and Circuit Diagram.

This device is battery powered only, and do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines, thus § 15.207 is not required.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	Remote Control
Type Designation:	TCT-E10Z
FCC ID:	2BCT6-0004
Operating Voltage:	DC 7.4V by lithium battery
Testing Voltage:	DC 7.4V by lithium battery
Operating Temperature Range:	-25 °C ~ +70 °C
Technical Specification of 915MHz band SRD	
Operating Frequency:	903.6-922 MHz
Type of Modulation:	GFSK
Channel Number:	96
Channel Separation:	200kHz
Antenna Type:	Integral Antenna
Antenna Number:	1Tx
Antenna Gain:	-2.50 dBi (Provided by the Client)
Working mechanism:	FHSS

Note: The correctness of all data provided by customer in the test report is ensured and responsible of the customer. Any misjudgment of the test results caused by the use of incorrect data provided by customer shall be borne by the customer.

3.3 Independent Operation Modes

The basic operation modes are:

A. On, 915MHz band SRD transmitting mode

- 1) Low Channel
- 2) Middle Channel
- 3) High Channel

B. On, Transmitting on Hopping channel

C. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- User Manual
- Operation Description
- ID Label and Location Info

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10:2020.

According to clause 3.1, all tests were performed in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 4: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N
Laptop	Lenovo	T480	PF-16A6N8

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(b)(4) and Part 15.203

According to the manufacturer declared, the EUT has Integral Antenna, permanent attachment and no consideration of replacement, refer to section 3.2 for details.

Therefore, the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

Prüfbericht - Nr.: CN24LUJJ 001
Test Report No.:

Seite 14 von 22
Page 14 of 22

5.1.2 Maximum Peak Conducted Output Power

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(b)(2)
 Basic standard : ANSI C63.10:2020
 Limits : < 1.0 W for at least 50 hopping frequencies
 Kind of test site : Shielded Room

Test Setup

Date of testing : 2026-03-26
 Input voltage : DC 7.4V by lithium battery
 Operation mode : B
 Test channel : Low / Middle / High
 Ambient temperature : 24.3 °C
 Relative humidity : 54 %
 Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 5: Test Result of Maximum Peak Conducted Output Power

Test Mode	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
915MHz band SRD	903.6	4.69	0.0029	< 1.0
	912.6	4.92	0.0031	
	922	3.81	0.0024	
Maximum Measured Value		4.92	0.0031	

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G): -2.50 dBi

Prüfbericht - Nr.: CN24LUJJ 001
Test Report No.:

Seite 15 von 22
Page 15 of 22

5.1.3 99% Bandwidth

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(a)
Basic standard : ANSI C63.10:2020
Kind of test site : Shielded Room

Test Setup

Date of testing : 2026-03-26
Input voltage : DC 7.4V by lithium battery
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 24.3 °C
Relative humidity : 54 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN24LUJJ 001
Test Report No.:Seite 16 von 22
Page 16 of 22

5.1.4 20dB Bandwidth

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(a)(1) (i)
Basic standard	: ANSI C63.10:2020 Not more than 500kHz and
Limits	: < 250kHz for at least 50 hopping frequencies >=250kHz for at least 25 hopping frequencies
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-26
Input voltage	: DC 7.4V by lithium battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 24.3 °C
Relative humidity	: 54 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN24LUJJ 001
Test Report No.:

Seite 17 von 22
Page 17 of 22

5.1.5 Carrier Frequency Separation

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(a)(1)
Basic standard	: ANSI C63.10:2020
Limits	: $\geq 20\text{dB}$ bandwidth
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-26
Input voltage	: DC 7.4V by lithium battery
Operation mode	: B
Ambient temperature	: 24.3 °C
Relative humidity	: 54 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN24LUJJ 001
Test Report No.:

Seite 18 von 22
Page 18 of 22

5.1.6 Number of Hopping Frequency

RESULT:

Pass

Test Specification

Test standard	: FCC part 15.247(a)(1)(i)
Basic standard	: ANSI C63.10:2020
Limits	: ≥ 50 non-overlapping channels
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-26
Input voltage	: DC 7.4V by lithium battery
Operation mode	: B
Ambient temperature	: 24.3 °C
Relative humidity	: 54 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN24LUJJ 001
Test Report No.:

Seite 19 von 22
Page 19 of 22

5.1.7 Time of Occupancy

RESULT:

Pass

Test Specification

Test standard	: FCC part 15.247(a)(1)(i)
Basic standard	: ANSI C63.10:2020
Limits	: < 0.4s
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-26
Input voltage	: DC 7.4V by lithium battery
Operation mode	: B
Ambient temperature	: 24.3 °C
Relative humidity	: 54 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN24LUJJ 001
Test Report No.:Seite 20 von 22
Page 20 of 22

5.1.8 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(d)
Basic standard	: ANSI C63.10:2020
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-26
Input voltage	: DC 7.4V by lithium battery
Operation mode	: A, B
Test channel	: Low / Middle / High
Ambient temperature	: 24.3 °C
Relative humidity	: 54 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN24LUJJ 001
Test Report No.:Seite 21 von 22
Page 21 of 22

5.1.9 Radiated Spurious Emission

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(d) & FCC Part 15.205
Basic standard	: ANSI C63.10:2020
Limits	: Refer to 15.209(a) of FCC part 15.247(d)
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: 2026-03-27 to 2026-03-28
Input voltage	: DC 7.4V by lithium battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: 101 kPa

Remark:

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix A.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix B.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty.....	7
Table 3: Technical Specification of EUT	8
Table 4: List of Accessories and Auxiliary Equipment.....	10
Table 5: Test Result of Maximum Peak Conducted Output Power.....	14

Appendix A: Test Results of 915MHz Band SRD


APPENDIX A: TEST RESULTS OF 915MHZ BAND SRD	1
APPENDIX A.1: TEST RESULTS OF 20DB BANDWIDTH	2
Test Result	2
Test Graphs	3
APPENDIX A.2: TEST RESULTS OF 99% BANDWIDTH	5
Test Result	5
Test Graphs	6
APPENDIX A.3: TEST RESULTS OF CARRIER FREQUENCY SEPARATION	8
Test Result	8
Test Graphs	9
APPENDIX A.4: TEST RESULTS OF TIME OF OCCUPANCY	11
Test Result	11
Test Graphs	12
APPENDIX A.5: TEST RESULTS OF NUMBER OF HOPPING FREQUENCY	13
Test Result	13
Test Graphs	14
APPENDIX A.6: TEST RESULTS OF BAND EDGE MEASUREMENTS	15
Fixed mode	15
Hopping mode	16
APPENDIX A.7: TEST RESULTS OF CONDUCTED SPURIOUS EMISSION	17
Fixed mode	17
Hopping mode	20
APPENDIX A.8: TEST RESULTS OF RADIATED SPURIOUS EMISSIONS	21
30 MHz - 1GHz	21
Above 1GHz	27

Appendix A.1: Test Results of 20dB Bandwidth


Test Result

Test Mode	Channel Frequency (MHz)	20dB Bandwidth (kHz)	Result
915MHz band SRD	903.6	11.07	Pass
	912.6	11.29	
	922	11.29	


Test Graphs



Date: 26.MAR.2026 05:06:11



Date: 26.MAR.2026 05:11:05




Date: 26.MAR.2026 05:14:51

Appendix A.2: Test Results of 99% Bandwidth


Test Result

Test Mode	Channel Frequency (MHz)	99% Bandwidth (kHz)	Limit (MHz)	Result
915MHz band SRD	903.6	13.24	/	Pass
	912.6	13.02		
	922	12.81		


Test Graphs



Date: 26.MAR.2026 05:04:46



Date: 26.MAR.2026 05:11:33




Appendix A.3: Test Results of Carrier Frequency Separation

Test Result


Test Mode	Channel	Measured Channel Separation (kHz)	Limit (kHz)	Result
915MHz band SRD	Low Channel	200.58	25	Pass
	Adjacency Channel			
	Middle Channel	200.58		Pass
	Adjacency Channel			
	High Channel	200.58		Pass
	Adjacency Channel			

Note: The limit is MAX {25 kHz, BW 20dB}


Test Graphs



Date: 26.MAR.2026 05:44:42



Date: 26.MAR.2026 05:46:21




Date: 26.MAR.2026 05:49:49

Appendix A.4: Test Results of Time of Occupancy

Test Result

Test Mode	Period (s)	Channel Occupancy Time (ms)	Limit (ms)	Result
915MHz band SRD	20	347.8	400	Pass

Test Graphs




Date: 26.MAR.2026 05:57:51

Appendix A.5: Test Results of Number of Hopping Frequency

Test Result

Test Mode	Hopping Frequencies	Limit	Result
915MHz band SRD	96	>50	Pass

Test Graphs




Date: 26.MAR.2026 05:48:30


Appendix A.6: Test Results of Band Edge Measurements

Fixed mode

Low Channel




High Channel




Hopping mode

Low Channel





High Channel




Appendix A.7: Test Results of Conducted Spurious Emission

Fixed mode


Low Channel



Middle Channel




Date: 26.MAR.2026 05:09:33




Date: 26.MAR.2026 06:10:49

High Channel




Date: 26.MAR.2026 05:12:32




Date: 26.MAR.2026 05:22:16

Hopping mode



Date: 26.MAR.2026 05:34:54



Date: 26.MAR.2026 06:05:54

Appendix A.8: Test Results of Radiated Spurious Emissions


Note:

- 1) Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and above 10GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 10GHz were reported.
- 2) The highest waveform in the figure is 915MHz Band SRD Fundamental.

30 MHz - 1GHz

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	903.6MHz
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
47.998889	18.20	40.00	21.80	100.0	H	170.0	-18.5
143.975000	25.14	43.50	18.36	100.0	H	359.0	-22.4
240.058889	29.50	46.00	16.50	100.0	H	252.0	-17.7
336.035000	36.91	46.00	9.09	100.0	H	0.0	-15.1
432.011111	41.76	46.00	4.24	100.0	H	0.0	-13.1
528.041111	31.93	46.00	14.07	100.0	H	170.0	-11.3
815.861667	38.07	46.00	7.93	100.0	H	238.0	-5.9
903.646667	101.70	---	---	100.0	H	87.0	-4.8

Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	903.6MHz
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
57.968333	17.40	40.00	22.60	100.0	V	353.0	-18.9
144.028889	22.63	43.50	20.87	100.0	V	358.0	-22.4
240.058889	27.33	46.00	18.67	100.0	V	257.0	-17.7
335.981111	29.37	46.00	16.63	100.0	V	116.0	-15.1
432.011111	28.56	46.00	17.44	100.0	V	116.0	-13.1
624.017222	30.36	46.00	15.64	100.0	V	129.0	-9.2
903.646667	95.03	---	---	100.0	V	48.0	-4.8

Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	912.6MHz
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
45.735556	17.80	40.00	22.20	100.0	H	78.0	-18.8
144.028889	24.63	43.50	18.87	100.0	H	0.0	-22.4
240.058889	29.42	46.00	16.58	100.0	H	241.0	-17.7
336.035000	36.66	46.00	9.34	100.0	H	162.0	-15.1
432.065000	42.62	46.00	3.38	100.0	H	347.0	-13.1
527.987222	32.12	46.00	13.88	100.0	H	332.0	-11.3
815.969444	38.24	46.00	7.76	100.0	H	204.0	-5.9
912.646111	100.32	---	---	100.0	H	78.0	-4.7

Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	912.6MHz
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
57.914444	19.23	40.00	20.77	100.0	V	213.0	-18.9
143.975000	22.00	43.50	21.50	100.0	V	344.0	-22.4
240.005000	27.52	46.00	18.48	100.0	V	292.0	-17.7
335.981111	27.87	46.00	18.13	100.0	V	153.0	-15.1
431.957222	28.23	46.00	17.77	100.0	V	117.0	-13.1
624.071111	29.67	46.00	16.33	100.0	V	153.0	-9.2
816.077222	31.92	46.00	14.08	100.0	V	28.0	-5.9
912.646111	93.89	---	---	100.0	V	351.0	-4.7

Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	922MHz
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
47.998889	18.33	40.00	21.67	100.0	H	173.0	-18.5
144.028889	24.44	43.50	19.06	100.0	H	311.0	-22.4
240.005000	29.30	46.00	16.70	100.0	H	252.0	-17.7
335.981111	36.80	46.00	9.20	100.0	H	344.0	-15.1
432.011111	42.56	46.00	3.44	100.0	H	0.0	-13.1
527.987222	31.04	46.00	14.96	100.0	H	159.0	-11.3
816.023333	36.78	46.00	9.22	100.0	H	210.0	-5.9
922.022778	98.21	---	---	100.0	H	76.0	-4.6

Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	922MHz
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
47.998889	16.94	40.00	23.06	100.0	V	62.0	-18.5
105.282778	16.27	43.50	27.23	100.0	V	229.0	-18.9
143.975000	21.54	43.50	21.96	100.0	V	329.0	-22.4
240.005000	27.46	46.00	18.54	100.0	V	284.0	-17.7
336.035000	27.95	46.00	18.05	100.0	V	116.0	-15.1
432.065000	28.11	46.00	17.89	100.0	V	110.0	-13.1
600.036667	28.95	46.00	17.05	100.0	V	21.0	-9.7
719.993333	30.52	46.00	15.48	100.0	V	142.0	-7.6
922.022778	91.65	---	---	100.0	V	349.0	-4.6


Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

Above 1GHz

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	903.6MHZ
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1007.500000	52.33	---	74.00	21.67	150.0	H	23.0	0.4
1008.000000	---	47.92	54.00	6.08	150.0	H	27.0	0.4
1104.000000	---	43.41	54.00	10.59	150.0	H	88.0	0.6
1105.000000	48.62	---	74.00	25.38	150.0	H	74.0	0.6
1806.966667	49.45	---	74.00	24.55	150.0	H	212.0	6.3
1806.966667	---	46.17	54.00	7.83	150.0	H	212.0	6.3
2710.908333	51.05	---	74.00	22.95	150.0	H	73.0	9.1
2710.908333	---	46.83	54.00	7.17	150.0	H	73.0	9.1
4649.441667	52.67	---	74.00	21.33	150.0	H	244.0	13.5
4658.375000	---	42.38	54.00	11.62	150.0	H	244.0	13.5

Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
----	----	----	----	----	----		----	

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	903.6MHZ
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1200.000000	---	40.21	54.00	13.79	150.0	V	151.0	1.8
1200.500000	47.16	---	74.00	26.84	150.0	V	151.0	1.8
1806.966667	48.84	---	74.00	25.16	150.0	V	328.0	6.3
1806.966667	---	43.63	54.00	10.37	150.0	V	328.0	6.3
2710.350000	---	42.00	54.00	12.00	150.0	V	172.0	9.1
2710.350000	47.99	---	74.00	26.01	150.0	V	172.0	9.1
3405.475000	---	42.71	54.00	11.29	150.0	V	87.0	10.2
3413.291667	50.28	---	74.00	23.72	150.0	V	100.0	10.2
6088.266667	---	46.11	54.00	7.89	150.0	V	197.0	16.9
6159.733333	56.14	---	74.00	17.86	150.0	V	288.0	17.1

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	903.6MHz
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8473.300000	44.21	---	74.00	29.79	150.0	H	108.0	9.0
8479.200000	---	34.86	54.00	19.14	150.0	H	15.0	9.0
9539.600000	---	35.56	54.00	18.44	150.0	H	164.0	10.1
9550.700000	45.74	---	74.00	28.26	150.0	H	108.0	10.2

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
100.00	100.00	100.00	100.00	100.00	100.00		100.00	100.00

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	912.6MHz
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1007.000000	52.51	---	74.00	21.49	150.0	H	23.0	0.4
1008.000000	---	47.80	54.00	6.20	150.0	H	18.0	0.4
1104.000000	---	42.95	54.00	11.06	150.0	H	76.0	0.6
1104.500000	48.08	---	74.00	25.92	150.0	H	64.0	0.6
1824.833333	49.37	---	74.00	24.63	150.0	H	274.0	6.4
1824.833333	---	46.17	54.00	7.83	150.0	H	274.0	6.4
2737.708333	49.85	---	74.00	24.15	150.0	H	71.0	9.3
2737.708333	---	47.23	54.00	6.77	150.0	H	71.0	9.3
4659.491667	52.03	---	74.00	21.97	150.0	H	355.0	13.5
4705.275000	---	42.77	54.00	11.23	150.0	H	297.0	13.5

Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	912.6MHz
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1007.500000	---	39.84	54.00	14.16	150.0	V	113.0	0.4
1008.000000	46.58	---	74.00	27.42	150.0	V	122.0	0.4
1200.000000	---	38.85	54.00	15.15	150.0	V	113.0	1.8
1200.500000	46.68	---	74.00	27.32	150.0	V	144.0	1.8
1824.833333	---	42.09	54.00	11.91	150.0	V	90.0	6.4
1825.391667	45.83	---	74.00	28.17	150.0	V	323.0	6.4
2737.708333	46.67	---	74.00	27.33	150.0	V	170.0	9.3
2737.708333	---	40.91	54.00	13.09	150.0	V	170.0	9.3
4577.975000	52.11	---	74.00	21.89	150.0	V	103.0	13.5
4615.941667	---	42.34	54.00	11.66	150.0	V	123.0	13.5

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	922MHz
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1008.000000	53.71	---	74.00	20.29	150.0	H	24.0	0.4
1008.000000	---	48.74	54.00	5.26	150.0	H	24.0	0.4
1104.000000	48.71	---	74.00	25.29	150.0	H	73.0	0.6
1104.000000	---	43.57	54.00	10.43	150.0	H	73.0	0.6
1843.816667	45.98	---	74.00	28.02	150.0	H	291.0	6.4
1843.816667	---	41.89	54.00	12.11	150.0	H	291.0	6.4
2766.183333	---	41.27	54.00	12.73	150.0	H	205.0	9.4
2768.975000	47.20	---	74.00	26.80	150.0	H	291.0	9.4
4750.500000	52.06	---	74.00	21.94	150.0	H	258.0	13.3
4754.966667	---	42.81	54.00	11.19	150.0	H	291.0	13.3

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dBm)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Remote Control
Model:	TCT-E10Z
Test Mode:	922MHz
Order No/Sample No:	168496151/A004222466-001
Test Voltage:	Battery
Remark:	Temp 23 Humi:53%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1007.500000	46.25	---	74.00	27.75	150.0	V	123.0	0.4
1008.000000	---	39.77	54.00	14.23	150.0	V	123.0	0.4
1200.000000	---	39.23	54.00	14.77	150.0	V	146.0	1.8
1200.500000	47.18	---	74.00	26.82	150.0	V	137.0	1.8
1824.275000	45.49	---	74.00	28.51	150.0	V	153.0	6.4
1843.816667	---	38.07	54.00	15.93	150.0	V	314.0	6.4
2766.183333	48.14	---	74.00	25.86	150.0	V	356.0	9.4
2766.183333	---	39.30	54.00	14.70	150.0	V	356.0	9.4
4708.066667	52.63	---	74.00	21.37	150.0	V	202.0	13.5
4716.441667	---	42.68	54.00	11.32	150.0	V	221.0	13.4

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
100.0	100.0	100.0	100.0	100.0	100.0		100.0	