RF Test Data for Bluetooth LE (Conducted Measurements)

General Description of EUT	
Product Name:	music power station
Test Model:	SKA700T
Sample ID:	202306-0024-3-2#
Environmental Conditions	
Temperature:	25℃
Relative Humidity:	55%
Test Voltage:	DC 16V
Test Engineer:	Huang jian ping
Note: For a more detailed features description, please refer to the report TBR-C-202306-0024-91 The report only show the worst case data.	

Contents

1.Duty Cycle....3
2.Maximum Conducted Output Power....6
3.-6dB Bandwidth....9
4.Occupied Channel Bandwidth....12
5.Maximum Power Spectral Density Level....15
6.Band Edge....18
7.Conducted RF Spurious Emission....21
8.Restrict Band....25

1.Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1Mbps	2402	Ant1	85.2	0.7	0.47
NVNT	BLE 1Mbps	2440	Ant1	84.8	0.72	0.47
NVNT	BLE 1Mbps	2480	Ant1	84.8	0.72	0.47

Test Graphs

Duty Cycle NVNT BLE 1Mbps 2402MHz Ant1



Duty Cycle NVNT BLE 1Mbps 2440MHz Ant1



Duty Cycle NVNT BLE 1Mbps 2480MHz Ant1



2.Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	1.265	26	Pass
NVNT	BLE 1Mbps	2440	Ant1	1.217	26	Pass
NVNT	BLE 1Mbps	2480	Ant1	1.008	26	Pass

Test Graphs

Power NVNT BLE 1Mbps 2402MHz Ant1



Power NVNT BLE 1Mbps 2440MHz Ant1



Power NVNT BLE 1Mbps 2480MHz Ant1



3.-6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	0.65	0.5	Pass
NVNT	BLE 1Mbps	2440	Ant1	0.74	0.5	Pass
NVNT	BLE 1Mbps	2480	Ant1	0.68	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT BLE 1Mbps 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1Mbps 2440MHz Ant1



-6dB Bandwidth NVNT BLE 1Mbps 2480MHz Ant1



4.Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1Mbps	2402	Ant1	1.034
NVNT	BLE 1Mbps	2440	Ant1	1.035
NVNT	BLE 1Mbps	2480	Ant1	1.034

Test Graphs

OBW NVNT BLE 1Mbps 2402MHz Ant1



OBW NVNT BLE 1Mbps 2440MHz Ant1



OBW NVNT BLE 1Mbps 2480MHz Ant1



5.Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-14.859	4	Pass
NVNT	BLE 1Mbps	2440	Ant1	-14.439	4	Pass
NVNT	BLE 1Mbps	2480	Ant1	-14.342	4	Pass

Test Graphs

PSD NVNT BLE 1Mbps 2402MHz Ant1



PSD NVNT BLE 1Mbps 2440MHz Ant1



PSD NVNT BLE 1Mbps 2480MHz Ant1



6.Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-51.04	-20	Pass
NVNT	BLE 1Mbps	2480	Ant1	-50.67	-20	Pass

Test Graphs

Band Edge NVNT BLE 1Mbps 2402MHz Ant1 Ref



Band Edge NVNT BLE 1Mbps 2402MHz Ant1 Emission



Band Edge NVNT BLE 1Mbps 2480MHz Ant1 Ref



Band Edge NVNT BLE 1Mbps 2480MHz Ant1 Emission



7.Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-37.83	-20	Pass
NVNT	BLE 1Mbps	2440	Ant1	-37.46	-20	Pass
NVNT	BLE 1Mbps	2480	Ant1	-37.08	-20	Pass

Test Graphs

Tx. Spurious NVNT BLE 1Mbps 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 1Mbps 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1Mbps 2440MHz Ant1 Ref



Tx. Spurious NVNT BLE 1Mbps 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 1Mbps 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1Mbps 2480MHz Ant1 Emission



8.Restrict Band

Condition	Mode	Frequency (MHz)	Antenna	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	2310	-42.2	6	59.06	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2310	-51.98	6	49.28	Average	54	Pass
NVNT	BLE 1Mbps	2402	Ant1	2385.36	-39.57	6	61.69	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2364.72	-51.58	6	49.68	Average	54	Pass
NVNT	BLE 1Mbps	2402	Ant1	2390	-41.09	6	60.17	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2390	-51.85	6	49.41	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.5	-41.27	6	59.99	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.5	-51.76	6	49.5	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2486.416	-39.32	6	61.94	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2488.264	-51.09	6	50.17	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2500	-41.3	6	59.96	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2500	-51.82	6	49.44	Average	54	Pass

Test Graphs

Restrict Band NVNT BLE 1Mbps 2402MHz Ant1 Peak



Restrict Band NVNT BLE 1Mbps 2402MHz Ant1 Average



Restrict Band NVNT BLE 1Mbps 2480MHz Ant1 Peak



Restrict Band NVNT BLE 1Mbps 2480MHz Ant1 Average



-----END OF THE REPORT-----