



RF Test Report

Standard(s): FCC Part 15 Subpart 15.247
Unlicensed Intentional Radiators

Issued To: SafelyYou
36 Clyde Street
San Francisco, CA 94107
United States

Product Name: Halo™ Wall Button and Halo™ Pendant
Model(s): SYC-00046 and SYC-00047
FCC ID: 2BCWO-SYC-0001

Report No. ML302743C-RF00 LoRa DTS
Date of Issue: March 5, 2026

Report Prepared By:

A handwritten signature in black ink, appearing to read "Amir Emami".

Amir Emami, Project Engineer

Reviewed By:

A handwritten signature in black ink, appearing to read "M. Xie".

Min Xie, Sr. EMC/RF Project Engineer

Megalab Group Inc. – 150 Addison Hall Circle, Aurora, Ontario, L4G 3X8, Canada
www.megalabinc.com – (905) 752-1925

This report may not be reproduced, except in full, without prior written approval of Megalab Group Inc.
TRRF_FCC-ICES-247-DTS_v1

Table of Contents

1.	Revision History	3
2.	Summary of Test Results.....	4
2.1	Test Verdict.....	4
2.2	Test Standards	5
2.3	Test Facility	6
3.	General Information	9
3.1	Client Information	9
3.2	Device Under Test (DUT)	9
3.3	Test Setup of DUT	10
3.4	Modifications for Compliance	10
4.	Test Results	11
4.1	Emission Bandwidth	11
4.2	Peak Conducted Output Power	16
4.3	Spurious Out of Band Emissions (-20dBc)	20
4.4	Transmitter Spurious Radiated Emissions	24
4.5	Power Spectral Density.....	32

1. Revision History

Project No. & Revision	Report Date	Initials	Description
ML302743C-RF00	March 5, 2026	AE	Initial Release
-	-	-	-

NOTE:

- Latest reports marked as a revision replace any previous report and/or report revision issued under the same project number.

2. Summary of Test Results

2.1 Test Verdict

Unless otherwise stated, the test data and results in this test report relate only to the sample(s) tested.

Requirement	Test Type	Result	Remark
FCC			
15.203 15.247(b)(4)	Antenna Gain and Requirement	Pass	Custom PCB antenna with 1.52dBi Gain
15.247(a)(2)	Emission Bandwidth	Pass	6dB Bandwidth > 500kHz
15.247(b)(3)	Peak Conducted Output Power	Pass	< 1 Watt
15.247(d)	Spurious Out of Band Emissions	Pass	< 20dBc
15.247(d) 15.209	Transmitter Spurious Radiated Emissions	Pass	---
15.247(e)	Power Spectral Density	Pass	< 8 dBm in 3kHz BW
15.207	Power Line Conducted Emissions	N/A	DUT is DC powered from a coin cell battery and does not connect to any mains network

2.1.1 Test Verdict Notes and Justifications

The DUT was mounted in three orthogonal axes and worst-case results were obtained in the Y-axis. Worst case results are presented. See the Test Setup Photos for axis details.

Antenna details obtained from Client's Antenna Datasheet. As per FCC 15.203, the antenna is a custom PCB trace antenna and has less than 6dBi gain.

2.2 Test Standards

Standard	Description
47 CFR FCC Part 15 Subpart C	Code of Federal Regulations – Radio Frequency Devices, Intentional Radiators
FCC KDB 558074:2019	Digital Transmission Systems, measurements and procedures
ANSI C63.4:2014 + C63.4a-2017	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10-2020 + C63.10a-2024	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
ISO 17025:2017	General Requirements for the Competence of Testing and Calibration Laboratories

2.3 Test Facility

All tests were performed at Megalab Group Inc., located at 150 Addison Hall Circle, Aurora, ON, L4G 3X8, Canada.

The 10-meter semi-anechoic chamber for radiated emission and radiated immunity is designed to handle weights of up to 10,000lb and has power capability of over 100A. The turntable is capable of supporting test devices or systems either floor standing or table top of up to 4 meters wide and 3m tall. Conducted emissions, unless otherwise specified, are performed on a 2.44m x 2.48m ground plane and using a 2.44m x 2.48m vertical ground plane if applicable.

2.3.1 Accreditations

This report does not indicate any product endorsement by any government, accreditation agency, or Megalab Group Inc. Megalab Group Inc. shall have no liability for any deductions, interpretations or generalizations drawn by the client or others from the issued reports. If any opinions or interpretations are expressed in this report, they are outside Megalab Group Inc.'s scope of accreditation and do not necessarily reflect the opinions of Megalab Group Inc., unless otherwise specified.



A2LA (Certificate #5179.02)

Megalab Group Inc. is accredited to ISO/IEC 17025:2017 by the American Association for Laboratory Accreditation (A2LA) with Testing Certificate #5179.02. The laboratories current scope of accreditation can be found as listed on A2LA's website.



Innovation, Science and
Economic Development Canada

ISED

Megalab Group Inc. is registered with and recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.
Company Number: 28697, CAB Identifier Number: CA0102



FCC

Megalab Group Inc. is registered with and recognized by the Federal Communications Commission (FCC) as an accredited testing laboratory.
Registration No. 200040



VCCI

The Semi-anechoic chamber of Megalab Group Inc. is registered with the Regulations for Voluntary Control Council for Interference (VCCI). Registration No.: R-20173, G-20174, C-20132, T-20133.

2.3.2 Measurement Uncertainty

As per ISO/IEC 17025 requirements, an evaluation of the measurement uncertainties associated with the emission test results should be included in the test report.

Where relevant, the following measurement uncertainty levels have been estimated for the tests performed on the DUT as specified in CISPR 16-4-2. The measurement uncertainties given below are based on a coverage factor $k = 2$ which yields approximately a 95% level of confidence for the near-normal distribution typical of most measurement results.

Measurement	Frequency Range	Uncertainty
Conducted Emissions at AC Mains Power Port	150kHz to 30MHz	2.27 dB
Radiated Emissions	30MHz to 1GHz	5.22 dB
	1GHz to 18GHz	4.76 dB

2.3.3 Sample Calculations

Conducted Emissions

$$\begin{aligned}
 \text{Emission Level (dB}\mu\text{V)} &= \text{Read Level (dB}\mu\text{V)} + \text{LISN Factor (dB)} + \text{Attenuation Factor (dB)} + \text{Cable Loss (dB)} \\
 &= 34.8 + 0.1 + 10.0 + 0.2 \\
 &= 45.1
 \end{aligned}$$

$$\begin{aligned}
 \text{Margin (dB)} &= \text{Limit (dB}\mu\text{V)} - \text{Emission Level (dB}\mu\text{V)} \\
 &= 60.0 - 45.1 \\
 &= 14.9
 \end{aligned}$$

Radiated Emissions

$$\begin{aligned}
 \text{Emission Level (dB}\mu\text{V/m)} &= \text{Read Level (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Pre-Amp Gain (dB)} \\
 &= 52.4 + 9.4 + 1.3 - 29.2 \\
 &= 33.9
 \end{aligned}$$

$$\begin{aligned}
 \text{Margin (dB)} &= \text{Limit (dB}\mu\text{V/m)} - \text{Emission Level (dB}\mu\text{V/m)} \\
 &= 50.0 - 33.9 \\
 &= 16.1
 \end{aligned}$$

2.3.4 Terms, Definitions and Abbreviations

AE	Auxiliary Equipment
DUT	Device Under Test
DTS	Digital Transmission System
EMC	Electro-Magnetic Compatibility
FHSS	Frequency Hopping Spread Spectrum
ISM	Industrial, Scientific and Medical
LISN	Line Impedance Stabilization Network
N/A	Not Applicable
NCR	No Calibration Required
RF	Radio Frequency
RBW	Resolution Bandwidth
VBW	Video Bandwidth

Auxiliary Equipment/Support Equipment

Equipment needed to exercise and/or monitor the operation of the DUT.

Artificial Mains Network

Network that provides a defined impedance to the DUT at radio frequencies, couples the disturbance voltage to the measuring receiver and decouples the test circuit from the supply mains.

Class A Equipment

Equipment suitable for use in all locations other than those allocated in residential environments and those directly connected to a low voltage power supply network which supplies buildings used for domestic purposes.

Class B Equipment

Equipment suitable for use in all locations, including in residential environments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes.

Device Under Test

Device or system being evaluated for compliance with the requirements of the Test Standards listed in this report.

Electro-Magnetic Compatibility

Ability of equipment or system to function satisfactorily in its EM environment without introducing intolerable electromagnetic disturbances to anything in that environment.

Electromagnetic Disturbance

Any electromagnetic phenomenon which may degrade the performance of a device, equipment or system.

3. General Information

3.1 Client Information

Company	SafelyYou
Address	36 Clyde Street San Francisco, CA 94107 United States
Contact	Ryan Schaub
Email	rschaub@safely-you.com
Phone	415-579-3630

3.2 Device Under Test (DUT)

3.2.1 DUT Information

DUT Name	Halo™ Wall Button and Halo™ Pendant
DUT Model(s)	SYC-00046 and SYC-00047
Power Source (AC / DC / Battery)	Coin Cell Battery
Input Voltage (V) or Range	3.1VDC
Frequency (Hz) or Range	N/A
Mode(s) of Operation	Idle, Transmitting
Connectors Available on DUT	None
Transmitter Information	
FCC ID	2BCWO-SYC-0001
Technology Used	LoRa – DTS
Operating Frequency	903.0MHz to 927.0MHz
Modulation Type	LoRa
Number of Channels	16
Data Rate	SF8
Channel Separation	1600kHz
Occupied Bandwidth	500kHz
Antenna Manufacturer	Custom/SafelyYou
Antenna Model	SYC-00051-R00
Antenna Type	PCB Trace
Antenna Gain	1.52 dBi

Note: Above antenna information is provided by the client. The characteristics and gain are obtained from the Antenna's Data Sheet.

3.2.2 DUT Description

The SafelyYou Halo™ Wall Button (SYC-00046) and Halo™ Pendant (SYC-00047) are devices that are used by facility residents to request assistance from facility staff members. Users push and release the white area of the Wall Button or press and release the ribbed area of the clip on the Pendant to activate either device and transmit a request.

Electrically, the two models are identical and only the plastic enclosure is different. One is mounted on the wall and the other is worn as a pendant.

3.3 Test Setup of DUT

3.3.1 Configuration

Power was supplied to the DUT via an external power supply at 3.1VDC

The DUT was configured in a direct test mode with the following parameters

- For all the tests, the DUT was set to transmit continuously with 100% duty cycle
- Output Power: -5dBm
- Channels:
 - o 1 (903.0MHz),
 - o 4 (907.8MHz),
 - o 8 (914.2MHz),
 - o 12 (920.6MHz),
 - o 16 (927.0MHz)
- Data Rate: SF8
- Payload Length: 235 bytes

During all radiated emission measurements, the DUT was mounted in three orthogonal axes. See Test Setup Photos for axis details.

Description of I/O Cables			
Cable Function	Length of Cable (m)	Shielded (Y/N)	Outdoor Use (Y/N)
None	--	--	--

3.3.2 Support Equipment

Device	Manufacturer	Model	S/N
Laptop with CLI tool terminal	Dell	XPS	N/A

3.4 Modifications for Compliance

No modifications were made to the device under test to comply with the testing requirements.

4. Test Results

4.1 Emission Bandwidth

Test Date: February 5, 2026
Temperature (°C) 20.5
Relative Humidity (%) 11.3
Barometric Pressure (kPa) 98.1

Initials: AE

4.1.1 Limits

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

4.1.2 Test Procedure

Tested according to ANSI C63.10 Section 11.8 and 6.9.3.

For the 6dB (DTS) Bandwidth:

- Set RBW = 100kHz and VBW $\geq [3 \times \text{RBW}]$.
- Detector = Peak and Trace Mode = Max Hold.
- Sweep = Auto Couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

For the 99% Bandwidth:

- Set RBW in the range of 1% to 5% of the actual occupied bandwidth.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Span set to 1.5 to 5 times the occupied bandwidth.
- Use the 99% power bandwidth function of the instrument to measure bandwidth.

4.1.3 Test Results

6dB (DTS) Bandwidth				
Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Test Result
1	903.00	0.6334	> 0.50	Pass
4	907.80	0.6334	> 0.50	Pass
8	914.20	0.6334	> 0.50	Pass
12	920.60	0.6314	> 0.50	Pass
16	927.00	0.6294	> 0.50	Pass

99% Bandwidth			
Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Test Result
1	903.00	0.5028	Pass
4	907.80	0.5077	Pass
8	914.20	0.5080	Pass
12	920.60	0.5041	Pass
16	927.00	0.5053	Pass




Figure 1 – 6dB Bandwidth – Channel 1




Figure 2 – 6dB Bandwidth – Channel 4




Figure 3 – 6dB Bandwidth – Channel 8




Figure 4 – 6dB Bandwidth – Channel 12




Figure 5 – 6dB Bandwidth – Channel 16




Figure 6 – 99% Bandwidth – Channel 1




Figure 7 – 99% Bandwidth – Channel 4




Figure 8 – 99% Bandwidth – Channel 8




Figure 9 – 99% Bandwidth – Channel 12




Figure 10 – 99% Bandwidth – Channel 16

4.1.4 Test Equipment List

Equipment ID	Description	Manufacturer	Model	Calibration Date	Calibration Due
EQ_EMC_58	EMI Receiver	Rohde & Schwarz	ESW 44	Mar 1, 2024	Mar 1, 2026
EQ_EMC_115	10dB Attenuator	Fairview Microwave	SA18E-10	Dec 22, 2025	Dec 22, 2026

4.2 Peak Conducted Output Power

Test Date: February 5, 2026
Temperature (°C) 20.5
Relative Humidity (%) 11.3
Barometric Pressure (kPa) 98.1

Initials: AE

4.2.1 Limits

The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt (+30dBm) for systems using digital modulation in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands. The maximum conducted output power is the highest total transmit power occurring in any mode.

4.2.2 Test Procedure

Tested according to ANSI C63.10 Section 11.9.1.

The test was performed using a spectrum analyzer with a resolution bandwidth greater than the DTS bandwidth.

The RF output of the DUT was connected to the spectrum analyzer with sufficient attenuation in front and the total path loss was set as reference offset to correct the final reading.

4.2.3 Test Results

Channel	Frequency (MHz)	Peak Power		Limit (dBm)	Test Result
		(dBm)	(mW)		
1	903.00	-5.64	0.273	30	Pass
4	907.80	-5.71	0.269	30	Pass
8	914.20	-5.87	0.259	30	Pass
12	920.60	-6.05	0.248	30	Pass
16	927.00	-6.19	0.240	30	Pass




Figure 11 – Peak Power – Channel 1




Figure 12 – Peak Power – Channel 4




Figure 13 – Peak Power – Channel 8




Figure 14 – Peak Power – Channel 12




Figure 15 – Peak Power – Channel 16

4.2.4 Test Equipment List

Equipment ID	Description	Manufacturer	Model	Calibration Date	Calibration Due
EQ_EMC_58	EMI Receiver	Rohde & Schwarz	ESW 44	Mar 1, 2024	Mar 1, 2026
EQ_EMC_115	10dB Attenuator	Fairview Microwave	SA18E-10	Dec 22, 2025	Dec 22, 2026

4.3 Spurious Out of Band Emissions (-20dBc)

Test Date:	February 5, 2026
Temperature (°C)	20.5
Relative Humidity (%)	11.3
Barometric Pressure (kPa)	98.1

Initials: AE

4.3.1 Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30dB instead of 20dB.

4.3.2 Test Procedure

Tested according to ANSI C63.10 Section 11.11

For the reference level measurement:

- Set RBW = 100kHz and VBW $\geq [3 \times \text{RBW}]$.
- Detector = Peak and Trace Mode = Max Hold.
- Sweep = Auto Couple.
- Span set to $\geq 1.5 \times$ DTS bandwidth.
- Use the peak marker function to determine the maximum level.

For the out of band emission measurement

- Set the start and stop frequency to encompass the frequency range to be measured (10 times the operating frequency).
- Set RBW = 100kHz and VBW $\geq [3 \times \text{RBW}]$.
- Detector = Peak and Trace Mode = Max Hold.
- Sweep = Auto Couple.
- Use the peak marker function to determine the maximum level.

The RF output of the DUT was connected to the spectrum analyzer with sufficient attenuation in front and the total path loss was set as reference offset to correct the final reading.

4.3.3 Test Results

The DUT met the 20dB below carrier requirement for out of band emissions.




Figure 16 – -20dBc Reference Level – Channel 1




Figure 17 – -20dBc – Channel 1




Figure 18 – -20dBc Band Edge – Channel 1




Figure 19 – -20dBc Band Edge – Channel 16

4.3.4 Test Equipment List

Equipment ID	Description	Manufacturer	Model	Calibration Date	Calibration Due
EQ_EMC_58	EMI Receiver	Rohde & Schwarz	ESW 44	Mar 1, 2024	Mar 1, 2026
EQ_EMC_115	10dB Attenuator	Fairview Microwave	SA18E-10	Dec 22, 2025	Dec 22, 2026

4.4 Transmitter Spurious Radiated Emissions

Test Date: January 6, 2026
Temperature (°C) 21.1
Relative Humidity (%) 19.7
Barometric Pressure (kPa) 96.3

Initials: AE

4.4.1 Limits

Any radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a), must comply with the general radiated emission limits specified in FCC 15.209(a). Other emissions shall be at least 20dB below the highest level of the intentional transmitter.

Base Standard(s): FCC Subpart C 15.209.

Frequency Range (MHz)	Field Strength Limit		Field Strength at 3m (dBμV/m)	Detector Type / Measurement Bandwidth
	μV/m	Distance		
0.009 – 0.150	2400/F(kHz)	300	128.5 – 104.1	Quasi-Peak‡ / 200Hz
0.150 – 0.490	2400/F(kHz)	300	104.1 – 93.8	Quasi-Peak‡ / 9kHz
0.490 – 1.705	24000/F(kHz)	30	73.8 – 63.0	Quasi-Peak / 9kHz
1.705 – 30	30	30	69.5	Quasi-Peak / 9kHz
30 – 88	100	3	40.0	Quasi-Peak / 120kHz
88 – 216	150	3	43.5	Quasi-Peak / 120kHz
216 – 960	200	3	46.0	Quasi-Peak / 120kHz
960 – 1000	500	3	54.0	Quasi-Peak / 120kHz
Above 1000	500	3	54.0	Average / 1MHz
Above 1000	5000	3	74.0	Peak / 1MHz

‡The emission limits below 1GHz shown in the above table are based on measurements employing a CISPR Quasi-Peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

As per ANSI C63.4 Section 4.2, if the Peak detector measurements do not exceed the Quasi-Peak limits, or Average limits where defined, then the DUT is considered to have passed the requirements.

4.4.2 Test Procedure

Tested according to ANSI C63.10 Section 6.3.

The device under test was setup inside a semi-anechoic chamber with remotely controlled turntable and antenna positioner at a 3m test distance. The DUT was placed on top of a 0.8m high non-conductive table above the reference ground plane for frequencies below 1GHz and 1.5m high for frequencies above 1GHz.

To determine the emission characteristics of the DUT, exploratory radiated emission scans were made while rotating the turntable 0° to 360° and using a Quasi-Peak, Average or Peak detector as applicable. The results were recorded in graphical form.


For each suspected emission, final measurements of the DUT radiated emissions with the Quasi-Peak, Average or Peak detector, as defined in the limit tables above, were made with the turntable azimuth rotated 0° to 360° and antenna height varied from 1m to 4m. The antenna was positioned to receive emissions in the vertical and horizontal polarizations such that the maximum radiated emission levels were detected.

As per FCC Part 15.33(a), the DUT was scanned to the 10th harmonic of the highest fundamental frequency.

Peak output power for low, mid and high channels, each in three orthogonal axes, were verified. The worst case was used for the spurious emissions which was on the low channel and in the Y-axis.


4.4.3 Test Results

Range:	9kHz to 30MHz	Tx Frequency	903.0MHz
Test Voltage:	3.1VDC	Antenna Polarization	N/A




Remark: Quasi-Peak Emission Plot

Range:	30MHz to 1GHz	Tx Frequency	903.0MHz
Test Voltage:	3.1VDC	Antenna Polarization	Horizontal



Remark: - Quasi-Peak Emission Plot
- A Notch filter was used to filter out the fundamental

Range:	1GHz to 10GHz	Tx Frequency	903.0MHz
Test Voltage:	3.1VDC	Antenna Polarization	Horizontal




Remark: - Peak and Average Emission Plot

Horizontal Antenna Polarization							
Frequency (MHz)	Detector	Reading (dBμV)	Correction Factor (dB/m)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Test Result
95.70	QP	44.95	-13.15	31.80	43.50	11.70	Pass
143.65	QP	42.57	-12.27	30.30	43.50	13.20	Pass
180.45	QP	38.91	-10.09	28.82	43.50	14.68	Pass
383.05	QP	32.64	-3.51	29.13	46.00	16.87	Pass
192.40	QP	36.61	-10.30	26.31	43.50	17.19	Pass
324.75	QP	34.83	-6.13	28.70	46.00	17.30	Pass
9814.00	PEAK	56.31	8.54	64.85	74.00	9.15	Pass
8461.00	PEAK	56.41	7.86	64.27	74.00	9.73	Pass
5748.00	PEAK	61.47	2.40	63.87	74.00	10.13	Pass
7818.00	PEAK	55.85	5.68	61.53	74.00	12.47	Pass
5307.00	PEAK	59.19	1.62	60.81	74.00	13.19	Pass
5005.00	PEAK	58.54	0.94	59.48	74.00	14.52	Pass
10000.00	AVG	39.54	9.26	48.80	54.00	5.20	Pass
8542.00	AVG	39.89	7.79	47.68	54.00	6.32	Pass
7893.00	AVG	39.22	5.90	45.12	54.00	8.88	Pass
5808.00	AVG	41.76	2.67	44.43	54.00	9.57	Pass
5166.00	AVG	42.19	1.42	43.61	54.00	10.39	Pass
2709.00	AVG	43.77	-2.68	41.09	54.00	12.91	Pass


Worst case position: Angle: 330 Deg
Height: 150 cm

Range:	30MHz to 1GHz	Tx Frequency	903.0MHz
Test Voltage:	3.1VDC	Antenna Polarization	Vertical



Remark: - Quasi-Peak Emission Plot
- A Notch filter was used to filter out the fundamental

Range:	1GHz to 10GHz	Tx Frequency	903.0MHz
Test Voltage:	3.1VDC	Antenna Polarization	Vertical



Remark: - Peak and Average Emission Plot

Vertical Antenna Polarization							
Frequency (MHz)	Detector	Reading (dBμV)	Correction Factor (dB/m)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Test Result
96.25	QP	53.86	-13.07	40.79	43.50	2.71	Pass
179.45	QP	44.04	-10.09	33.95	43.50	9.55	Pass
143.50	QP	45.87	-12.28	33.59	43.50	9.91	Pass
35.90	QP	38.29	-8.54	29.75	40.00	10.25	Pass
84.15	QP	42.86	-13.96	28.90	40.00	11.10	Pass
191.40	QP	40.86	-10.31	30.55	43.50	12.95	Pass
9765.00	PEAK	56.97	8.44	65.41	74.00	8.59	Pass
8543.00	PEAK	56.77	7.80	64.57	74.00	9.43	Pass
5921.00	PEAK	58.66	2.90	61.56	74.00	12.44	Pass
7708.00	PEAK	55.95	5.58	61.53	74.00	12.47	Pass
5439.00	PEAK	58.92	1.85	60.77	74.00	13.23	Pass
6373.00	PEAK	56.18	3.29	59.47	74.00	14.53	Pass
9999.00	AVG	39.77	9.26	49.03	54.00	4.97	Pass
8542.00	AVG	40.10	7.79	47.89	54.00	6.11	Pass
7894.00	AVG	39.44	5.90	45.34	54.00	8.66	Pass
5824.00	AVG	41.83	2.70	44.53	54.00	9.47	Pass
5168.00	AVG	42.34	1.43	43.77	54.00	10.23	Pass
2709.00	AVG	46.11	-2.68	43.43	54.00	10.57	Pass

Worst case position: Angle: 211 Deg
Height: 100 cm

4.4.4 Test Equipment List

Equipment ID	Description	Manufacturer	Model	Calibration Date	Calibration Due
EQ_EMC_132	EMI Receiver	Gauss Instruments	TDEMI X40	Nov 29, 2023	May 29, 2026
EQ_EMC_48	Loop Antenna 9kHz – 30MHz	Com-Power	AL-130R	Apr 9, 2024	Apr 9, 2026
EQ_EMC_59	BiLog Antenna 30MHz – 1GHz	ETS Lindgren	3142E	Apr 19, 2024	Apr 19, 2026
EQ_EMC_68	6dB Attenuator	Fairview Microwave	SA3NS-06	Apr 19, 2024	Apr 19, 2026
EQ_EMC_60	Horn Antenna 1GHz – 18GHz	ETS Lindgren	3117	April 9, 2024	April 9, 2026
EQ_EMC_85	RF Cable <1GHz	Times Microwave	LMR-400	Apr 2, 2025	Apr 2, 2026
EQ_EMC_75	RF Cable >1GHz	MegaPhase	EMC2	Apr 2, 2025	Apr 2, 2026
EQ_EMC_196	Preamplifier 30MHz – 1GHz	HP	8447D	Feb 18, 2025	Feb 18, 2026
EQ_EMC_42	Preamplifier 1GHz – 18GHz	Com-Power	PAM-118A	Jan 17, 2024	Jan 17, 2026
EQ_EMC_107	902MHz- 928MHz Notch Filter	Micro-Tronics	BRC50722	Apr 4, 2025	Apr 4, 2026
EQ_EMC_110	1.2GHz-18GHz HPF Filter	Micro-Tronics	HPM50108	Apr 4, 2025	Apr 4, 2026
EQ_EMC_149	Emissions Software	Gauss Instruments	EMI64k v6.31.2	NCR	NCR

4.5 Power Spectral Density

Test Date: February 5, 2026
Temperature (°C) 20.5
Relative Humidity (%) 11.3
Barometric Pressure (kPa) 98.1

Initials: AE

4.5.1 Limits

For digitally modulated systems, the power spectral density (PSD) conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.5.2 Test Procedure

Tested according to ANSI C63.10 Section 11.10

- Set RBW = 3kHz and VBW $\geq [3 \times \text{RBW}]$.
- Set Span to 1.5 times the DTS Bandwidth.
- Detector = Peak and Trace Mode = Max Hold.
- Sweep = Auto Couple.
- Use the peak marker function to determine the maximum level.

The RF output of the DUT was connected to the spectrum analyzer with sufficient attenuation in front and the total path loss was set as reference offset to correct the final reading.

4.5.3 Test Results

Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Test Result
1	903.00	-15.56	8.00	Pass
4	907.80	-15.80	8.00	Pass
8	914.20	-16.11	8.00	Pass
12	920.60	-16.69	8.00	Pass
16	927.00	-16.16	8.00	Pass




Figure 20 – PSD – Channel 1




Figure 21 – PSD – Channel 4




Figure 22 – PSD – Channel 8




Figure 23 – PSD – Channel 12




Figure 24 – PSD – Channel 16

4.5.4 Test Equipment List

Equipment ID	Description	Manufacturer	Model	Calibration Date	Calibration Due
EQ_EMC_58	EMI Receiver	Rohde & Schwarz	ESW 44	Mar 1, 2024	Mar 1, 2026
EQ_EMC_115	10dB Attenuator	Fairview Microwave	SA18E-10	Dec 22, 2025	Dec 22, 2026

----- End of Test Report -----