



FCC Part 15E Test Report

FCC ID: 2BD22-LG6

Applicant: Foshan Nanhai feilan projection technology electronics factory

Address: No.1 East, 3rd Floor, Rear Building, Hongke Building, Xiadong Sanzhou Industrial Development New Area, Guicheng Street, Nanhai District, Foshan City

Manufacturer: Foshan Nanhai feilan projection technology electronics factory

Address: No.1 East, 3rd Floor, Rear Building, Hongke Building, Xiadong Sanzhou Industrial Development New Area, Guicheng Street, Nanhai District, Foshan City

EUT: Projector

Trade Mark: N/A

Model Number: LG-6
LG-1, LG-2, LG-5, LG-7, LG-8, LG-9, H1, H2, H3, H4, H5, H6, H7, H8, H9, Z1, Z2, Z3, Z4, Z5, Z6, Z7, Z8, K6, M6, M8, R3, K6pro, Q6, H8BE, H8BL, X3WH, M61, M62, M63, M64, M65, M66, M67, M68, M69, M610, HQ20, HM6, HQ10, P2, Q5, Q4, Q3, X3, X2, X1, K8, Q9, T7, X4, X5, T10, Y2, YT400, T4, T300, Q1, YG300

Date of Receipt: Dec. 11, 2023

Test Date: Dec. 11, 2023 – Dec. 23, 2023

Date of Report: Dec. 23, 2023

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 E 15.407
ANSI C63.10:2013

Test Result: Pass

Report Number: DL-20231223009E

Prepared (Test Engineer): Alisa Song

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	4
1.1 MEASUREMENT UNCERTAINTY	4
2 . GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	8
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	8
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3 . EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	10
3.1.2 TEST PROCEDURE	10
3.1.3 DEVIATION FROM TEST STANDARD	10
3.1.4 TEST SETUP	11
3.1.5 EUT OPERATING CONDITIONS	11
3.1.6 TEST RESULTS	11
3.2 RADIATED EMISSION MEASUREMENT	14
3.2.1 RADIATED EMISSION LIMITS	14
3.2.2 TEST PROCEDURE	14
3.2.3 DEVIATION FROM TEST STANDARD	15
3.2.4 TEST SETUP	15
3.2.5 EUT OPERATING CONDITIONS	16
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	17
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	18
3.2.8 TEST RESULTS (1GHZ~40GHZ)	20
3.3 RADIATED BAND EMISSION MEASUREMENT	37
3.3.1 TEST REQUIREMENT:	37
3.3.2 TEST PROCEDURE	37
3.3.3 DEVIATION FROM TEST STANDARD	37
3.3.4 TEST SETUP	37
3.3.5 EUT OPERATING CONDITIONS	37
4 . PEAK OUTPUT POWER	42
4.1 APPLIED PROCEDURES / LIMIT	42
4.1.1 TEST PROCEDURE	42
4.1.2 DEVIATION FROM STANDARD	42
4.1.3 TEST SETUP	42
4.1.4 EUT OPERATION CONDITIONS	42
4.1.5 TEST RESULTS	43



Table of Contents	Page
5 . POWER SPECTRAL DENSITY TEST	50
5.1 APPLIED PROCEDURES / LIMIT	50
5.1.1 TEST PROCEDURE	50
5.1.2 DEVIATION FROM STANDARD	50
5.1.3 TEST SETUP	50
5.1.4 EUT OPERATION CONDITIONS	50
5.1.5 TEST RESULTS	51
6 . 6DB&26DB&99% BANDWIDTH TEST	58
6.1 APPLIED PROCEDURES / LIMIT	58
6.1.1 TEST PROCEDURE	58
6.1.2 DEVIATION FROM STANDARD	58
6.1.3 TEST SETUP	58
6.1.4 EUT OPERATION CONDITIONS	59
6.1.5 TEST RESULTS	59
7 . DUTY CYCLE TEST SIGNAL	66
7.1 APPLIED PROCEDURES / LIMIT	66
7.1.1 TEST PROCEDURE	66
7.1.2 DEVIATION FROM STANDARD	66
7.1.3 TEST SETUP	66
7.1.4 EUT OPERATION CONDITIONS	66
7.1.5 TEST RESULTS	67
8 . FREQUENCY STABILITY	70
8.1 APPLIED PROCEDURES / LIMIT	70
8.1.1 TEST PROCEDURE	70
8.1.2 DEVIATION FROM STANDARD	70
8.1.3 TEST SETUP	70
8.1.4 EUT OPERATION CONDITIONS	70
8.1.5 TEST RESULTS	71
9 . TRANSMISSION IN THE ABSENCE OF DATA	74
9.1 STANDARD REQUIREMENT	74
9.2 TEST RESULT	74
10 . ANTENNA REQUIREMENT	74
10.1 STANDARD REQUIREMENT	74
10.2 EUT ANTENNA	74
11 . TEST SEUUP PHOTO	75
12 . EUT PHOTO	77



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.407(b), 15.209	Radiated Spurious Emission	PASS	
15.407 (b)	Band Edge Emission	PASS	
15.407 (a)	Peak Output Power	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.403(i) 15.407(e)	26dB bandwidth and 99%dB Bandwidth 6dB bandwidth and 99%dB Bandwidth	PASS	
15.407(g)	Frequency Stability	PASS	
15.407(c)	Transmission in case of Absence of Information	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

Test lab: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB ID.: CN0118

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$
8	Bandwidth	$\pm 0.2\text{MHz}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Projector
Trademark	N/A
Model No.:	LG-6 LG-1, LG-2, LG-5, LG-7, LG-8, LG-9, H1, H2, H3, H4, H5, H6, H7, H8, H9, Z1, Z2, Z3, Z4, Z5, Z6, Z7, Z8, K6, M6, M8, R3, K6pro, Q6, H8BE, H8BL, X3WH, M61, M62, M63, M64, M65, M66, M67, M68, M69, M610, HQ20, HM6, HQ10, P2, Q5, Q4, Q3, X3, X2, X1, K8, Q9, T7, X4, X5, T10, Y2, YT400, T4, T300, Q1, YG300
Model Difference	The product's different for model number, appearance color.
Operation Frequency:	5180-5240, 5745-5825MHz(802.11a/n/ac(HT20)) 5190-5230, 5755-5795MHz(802.11n/ac(HT40)) 5210MHz , 5775MHz (802.11ac(HT80))
Channel numbers:	See channel list
Channel separation:	20MHz/40MHz/80MHz
Modulation technology:	64QAM, 16QAM, QPSK, BPSK for OFDM
Rate of Transmitter	802.11a: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps 802.11n: Up to 300Mbps 802.11ac: up to 867Mbps
Antenna Type:	Internal Antenna
Antenna gain:	2.86dBi
Power supply:	100-240V~ 50/60Hz

Note:

- 1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.The EUT's all information provided by client.



2. Channel List

Channel List for 802.11a/n(HT20)/ac(HT20)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
40	5200	48	5240

Channel List for 802.11n(HT40)/ac(HT40)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	46	5230

Channel List for 802.11ac(HT80)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	/	/

Channel List for 802.11a/n(HT20)/ac(HT20)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	161	5805
153	5765	165	5825
157	5785		

Channel List for 802.11n(HT40)/ac(HT40)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795

Channel List for 802.11ac(HT80)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
155	5775	/	/



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Description			
Pretest Mode	Channel	Band 1	Band 4
Mode 1	802.11a/n/acHT20	CH36, CH44, CH48	CH149, CH157, CH165
Mode 2	802.11n/acHT40	CH38, CH46	CH151, CH159
Mode 3	802.11acHT80	CH42	CH155
Mode 4	Link Mode		


For Radiated Emission			
Pretest Mode	Channel	Band 1	Band 4
Mode 1	802.11a/n/acHT20	CH36, CH44, CH48	CH149, CH157, CH165
Mode 2	802.11n/acHT40	CH38, CH46	CH151, CH159
Mode 3	802.11acHT80	CH42	CH155
Mode 4	Link Mode		

Note: 1. The measurements are performed at the highest, middle, lowest available channels.
2. During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.




2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	Projector	LG-6	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Max output power Setting				
Test software Version	Test program: SecureCRTPortable			
Mode	802.11a	802.11n HT20	802.11n HT40	802.11ac HT20/HT40/HT80
Data Rate	6Mbps	MSC0	MSC0	MSC0
Power Setting of Softwave	60	60	66	66



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 04, 2023	Nov. 03, 2024
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 04, 2023	Nov. 03, 2024
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 04, 2023	Nov. 03, 2024
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 04, 2023	Nov. 03, 2024
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 04, 2023	Nov. 03, 2024
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 04, 2023	Nov. 03, 2024
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 04, 2023	Nov. 03, 2024
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 04, 2023	Nov. 03, 2024
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 04, 2023	Nov. 03, 2024
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 04, 2023	Nov. 03, 2024
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 04, 2023	Nov. 03, 2024
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 04, 2023	Nov. 03, 2024
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 04, 2023	Nov. 03, 2024
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 04, 2023	Nov. 03, 2024
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 04, 2023	Nov. 03, 2024
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 04, 2023	Nov. 03, 2024

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Sep. 20, 2022	Sep. 19, 2025
2	EMI Receiver	R&S	ESR	101421	Nov. 04, 2023	Nov. 03, 2024
3	LISN	R&S	ENV216	102417	Nov. 04, 2023	Nov. 03, 2024
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 04, 2023	Nov. 03, 2024

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.5 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

3.1.6 TEST RESULTS



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4




Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1770	44.42	9.99	54.41	64.63	-10.22	QP	P	
2	0.1770	37.44	9.99	47.43	54.63	-7.20	AVG	P	
3	0.2940	42.82	9.07	51.89	60.41	-8.52	QP	P	
4	0.2940	34.07	9.07	43.14	50.41	-7.27	AVG	P	
5	0.5370	37.91	9.30	47.21	56.00	-8.79	QP	P	
6	0.5370	30.82	9.30	40.12	46.00	-5.88	AVG	P	
7	1.1940	31.90	9.44	41.34	56.00	-14.66	QP	P	
8	1.1940	22.55	9.44	31.99	46.00	-14.01	AVG	P	
9	3.5835	29.76	9.79	39.55	56.00	-16.45	QP	P	
10	3.5835	25.92	9.79	35.71	46.00	-10.29	AVG	P	
11	29.5710	42.58	10.93	53.51	60.00	-6.49	QP	P	
12 *	29.5710	34.66	10.93	45.59	50.00	-4.41	AVG	P	



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4



Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1767	42.60	9.60	52.20	64.64	-12.44	QP	P	
2 *	0.1767	39.49	9.60	49.09	54.64	-5.55	AVG	P	
3	0.2940	40.85	9.06	49.91	60.41	-10.50	QP	P	
4	0.2940	34.67	9.06	43.73	50.41	-6.68	AVG	P	
5	0.5324	34.16	9.42	43.58	56.00	-12.42	QP	P	
6	0.5324	27.82	9.42	37.24	46.00	-8.76	AVG	P	
7	1.6440	23.06	9.76	32.82	56.00	-23.18	QP	P	
8	1.6440	20.19	9.76	29.95	46.00	-16.05	AVG	P	
9	3.5834	29.33	10.00	39.33	56.00	-16.67	QP	P	
10	3.5834	23.47	10.00	33.47	46.00	-12.53	AVG	P	
11	15.6840	28.92	10.39	39.31	60.00	-20.69	QP	P	
12	15.6840	22.37	10.39	32.76	50.00	-17.24	AVG	P	



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.



- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (Between 9KHz – 30 MHz)**

Temperature:	20℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 4	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

**3.2.7 TEST RESULTS (Between 30MHz – 1GHz)**

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 4		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Margin dB	Detector
1		37.9448	48.10	-14.28	33.82	40.00	-6.18	QP
2	!	73.6170	51.62	-16.18	35.44	40.00	-4.56	QP
3	!	135.0318	55.20	-17.17	38.03	43.50	-5.47	QP
4	!	239.9873	54.42	-13.13	41.29	46.00	-4.71	QP
5	!	390.7225	51.99	-9.93	42.06	46.00	-3.94	QP
6	*	625.0778	48.14	-5.55	42.59	46.00	-3.41	QP


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;



Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
test voltage :	AC 120V/60Hz		
Test Mode :	Mode 4		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	37.2854	50.67	-14.44	36.23	40.00	-3.77	QP
2	!	55.0274	47.62	-12.95	34.67	40.00	-5.33	QP
3	!	71.8320	50.92	-15.78	35.14	40.00	-4.86	QP
4	!	143.3260	56.58	-17.55	39.03	43.50	-4.47	QP
5	!	280.0237	52.08	-11.94	40.14	46.00	-5.86	QP
6	!	390.7225	51.65	-9.93	41.72	46.00	-4.28	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;

**3.2.8 TEST RESULTS (1ghz~40ghZ)**

802.11a band 1

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	10360	56.23	49.05	15.3	37.39	59.87	74	-14.13	PK
V	10360	41.78	49.05	15.3	37.39	45.42	54	-8.58	AV
V	15540	56.36	49.16	15.27	40.45	62.92	74	-11.08	PK
V	15540	39.17	49.16	15.27	40.45	45.73	54	-8.27	AV
H	10360	56.85	49.05	15.3	37.39	60.49	74	-13.51	PK
H	10360	40.42	49.05	15.3	37.39	44.06	54	-9.94	AV
H	15540	59.63	49.16	15.27	40.45	66.19	74	-7.81	PK
H	15540	38.27	49.16	15.27	40.45	44.83	54	-9.17	AV
operation frequency:5200									
V	10400	57.44	49.09	15.34	37.42	61.11	74	-12.89	PK
V	10400	39.36	49.09	15.34	37.42	43.03	54	-10.97	AV
V	15600	59.28	49.18	15.29	40.47	65.86	74	-8.14	PK
V	15600	38.41	49.18	15.29	40.47	44.99	54	-9.01	AV
H	10400	56.43	49.09	15.34	37.42	60.1	74	-13.90	PK
H	10400	39.75	49.09	15.34	37.42	43.42	54	-10.58	AV
H	15600	59.63	49.18	15.29	40.47	66.21	74	-7.79	PK
H	15600	38.41	49.18	15.29	40.47	44.99	54	-9.01	AV
operation frequency:5240									
V	10480	58.43	49.11	15.37	37.46	62.15	74	-11.85	PK
V	10480	39.79	49.11	15.37	37.46	43.51	54	-10.49	AV
V	15720	59.15	49.21	15.34	40.51	65.79	74	-8.21	PK
V	15720	38.36	49.21	15.34	40.51	45	54	-9.00	AV
H	10480	57.17	49.11	15.37	31.31	54.74	74	-19.26	PK
H	10480	45.55	49.11	15.37	31.31	43.12	54	-10.88	AV
H	15720	57.63	49.21	15.34	40.51	64.27	74	-9.73	PK
H	15720	37.85	49.21	15.34	40.51	44.49	54	-9.51	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	10360	56.24	49.05	15.3	37.39	59.88	74	-14.12	PK
V	10360	38.13	49.05	15.3	37.39	41.77	54	-12.23	AV
V	15540	56.48	49.16	15.27	40.45	63.04	74	-10.96	PK
V	15540	38.26	49.16	15.27	40.45	44.82	54	-9.18	AV
H	10360	56.98	49.05	15.3	37.39	60.62	74	-13.38	PK
H	10360	39.44	49.05	15.3	37.39	43.08	54	-10.92	AV
H	15540	54.33	49.16	15.27	40.45	60.89	74	-13.11	PK
H	15540	38.64	49.16	15.27	40.45	45.2	54	-8.80	AV
operation frequency:5200									
V	10400	56.63	49.09	15.34	37.42	60.3	74	-13.70	PK
V	10400	39.38	49.09	15.34	37.42	43.05	54	-10.95	AV
V	15600	55.14	49.18	15.29	40.47	61.72	74	-12.28	PK
V	15600	38.29	49.18	15.29	40.47	44.87	54	-9.13	AV
H	10400	55.57	49.09	15.34	37.42	59.24	74	-14.76	PK
H	10400	40.65	49.09	15.34	37.42	44.32	54	-9.68	AV
H	15600	55.36	49.18	15.29	40.47	61.94	74	-12.06	PK
H	15600	39.24	49.18	15.29	40.47	45.82	54	-8.18	AV
operation frequency:5240									
V	10480	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	10480	40.58	49.11	15.37	37.46	44.3	54	-9.70	AV
V	15720	54.24	49.21	15.34	40.51	60.88	74	-13.12	PK
V	15720	38.46	49.21	15.34	40.51	45.1	54	-8.90	AV
H	10480	57.17	49.11	15.37	31.31	54.74	74	-19.26	PK
H	10480	44.55	49.11	15.37	31.31	42.12	54	-11.88	AV
H	15720	55.63	49.21	15.34	40.51	62.27	74	-11.73	PK
H	15720	39.74	49.21	15.34	40.51	46.38	54	-7.62	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5190									
V	10380	56.73	49.07	15.33	37.41	60.4	74	-13.60	PK
V	10380	39.34	49.07	15.33	37.41	43.01	54	-10.99	AV
V	15570	56.67	49.17	15.28	40.46	63.24	74	-10.76	PK
V	15570	38.36	49.17	15.28	40.46	44.93	54	-9.07	AV
H	10380	56.28	49.07	15.33	37.41	59.95	74	-14.05	PK
H	10380	40.15	49.07	15.33	37.41	43.82	54	-10.18	AV
H	15570	54.66	49.17	15.28	40.46	61.23	74	-12.77	PK
H	15570	38.39	49.17	15.28	40.46	44.96	54	-9.04	AV
operation frequency:5230									
V	10460	57.52	49.11	15.37	37.46	61.24	74	-12.76	PK
V	10460	39.24	49.11	15.37	37.46	42.96	54	-11.04	AV
V	15690	54.32	49.21	15.34	40.51	60.96	74	-13.04	PK
V	15690	38.39	49.21	15.34	40.51	45.03	54	-8.97	AV
H	10460	57.44	49.11	15.37	31.31	55.01	74	-18.99	PK
H	10460	44.31	49.11	15.37	31.31	41.88	54	-12.12	AV
H	15690	55.49	49.21	15.34	40.51	62.13	74	-11.87	PK
H	15690	39.41	49.21	15.34	40.51	46.05	54	-7.95	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11ac HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	10360	56.63	49.05	15.3	37.39	60.27	74	-13.73	PK
V	10360	39.14	49.05	15.3	37.39	42.78	54	-11.22	AV
V	15540	56.88	49.16	15.27	40.45	63.44	74	-10.56	PK
V	15540	38.34	49.16	15.27	40.45	44.9	54	-9.10	AV
H	10360	56.76	49.05	15.3	37.39	60.4	74	-13.60	PK
H	10360	38.27	49.05	15.3	37.39	41.91	54	-12.09	AV
H	15540	54.94	49.16	15.27	40.45	61.5	74	-12.50	PK
H	15540	39.83	49.16	15.27	40.45	46.39	54	-7.61	AV
operation frequency:5200									
V	10400	56.18	49.09	15.34	37.42	59.85	74	-14.15	PK
V	10400	41.86	49.09	15.34	37.42	45.53	54	-8.47	AV
V	15600	55.58	49.18	15.29	40.47	62.16	74	-11.84	PK
V	15600	40.14	49.18	15.29	40.47	46.72	54	-7.28	AV
H	10400	55.63	49.09	15.34	37.42	59.3	74	-14.70	PK
H	10400	40.57	49.09	15.34	37.42	44.24	54	-9.76	AV
H	15600	55.41	49.18	15.29	40.47	61.99	74	-12.01	PK
H	15600	41.26	49.18	15.29	40.47	47.84	54	-6.16	AV
operation frequency:5240									
V	10480	57.68	49.11	15.37	37.46	61.4	74	-12.60	PK
V	10480	40.73	49.11	15.37	37.46	44.45	54	-9.55	AV
V	15720	54.52	49.21	15.34	40.51	61.16	74	-12.84	PK
V	15720	39.91	49.21	15.34	40.51	46.55	54	-7.45	AV
H	10480	57.39	49.11	15.37	31.31	54.96	74	-19.04	PK
H	10480	44.95	49.11	15.37	31.31	42.52	54	-11.48	AV
H	15720	55.82	49.21	15.34	40.51	62.46	74	-11.54	PK
H	15720	40.69	49.21	15.34	40.51	47.33	54	-6.67	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11ac 40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5190									
V	10380	56.52	49.07	15.33	37.41	60.19	74	-13.81	PK
V	10380	40.43	49.07	15.33	37.41	44.1	54	-9.90	AV
V	15570	56.64	49.17	15.28	40.46	63.21	74	-10.79	PK
V	15570	39.58	49.17	15.28	40.46	46.15	54	-7.85	AV
H	10380	56.46	49.07	15.33	37.41	60.13	74	-13.87	PK
H	10380	40.34	49.07	15.33	37.41	44.01	54	-9.99	AV
H	15570	54.25	49.17	15.28	40.46	60.82	74	-13.18	PK
H	15570	39.86	49.17	15.28	40.46	46.43	54	-7.57	AV
operation frequency:5230									
V	10460	57.41	49.11	15.37	37.46	61.13	74	-12.87	PK
V	10460	41.13	49.11	15.37	37.46	44.85	54	-9.15	AV
V	15690	54.28	49.21	15.34	40.51	60.92	74	-13.08	PK
V	15690	39.85	49.21	15.34	40.51	46.49	54	-7.51	AV
H	10460	57.86	49.11	15.37	31.31	55.43	74	-18.57	PK
H	10460	44.77	49.11	15.37	31.31	42.34	54	-11.66	AV
H	15690	55.35	49.21	15.34	40.51	61.99	74	-12.01	PK
H	15690	40.46	49.21	15.34	40.51	47.1	54	-6.90	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT80

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5210									
V	10420	56.34	49.07	15.33	37.41	60.01	74	-13.99	PK
V	10420	41.47	49.07	15.33	37.41	45.14	54	-8.86	AV
V	15630	56.26	49.17	15.28	40.46	62.83	74	-11.17	PK
V	15630	39.15	49.17	15.28	40.46	45.72	54	-8.28	AV
H	10420	56.83	49.07	15.33	37.41	60.5	74	-13.50	PK
H	10420	41.35	49.07	15.33	37.41	45.02	54	-8.98	AV
H	15630	54.94	49.17	15.28	40.46	61.51	74	-12.49	PK
H	15630	40.23	49.17	15.28	40.46	46.8	54	-7.20	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11a band 4

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5745									
V	11490	54.58	49.05	15.3	37.39	58.22	74	-15.78	PK
V	11490	41.04	49.05	15.3	37.39	44.68	54	-9.32	AV
V	17235	55.36	49.16	15.27	40.45	61.92	68.2	-6.28	PK
V	17235	40.85	49.16	15.27	40.45	47.41	54	-6.59	AV
H	11490	52.36	49.05	15.3	37.39	56	74	-18.00	PK
H	11490	42.48	49.05	15.3	37.39	46.12	54	-7.88	AV
H	17235	51.34	49.16	15.27	40.45	57.9	68.2	-10.30	PK
H	17235	40.86	49.16	15.27	40.45	47.42	54	-6.58	AV
operation frequency:5785									
V	11570	51.74	49.09	15.34	37.42	55.41	74	-18.59	PK
V	11570	41.16	49.09	15.34	37.42	44.83	54	-9.17	AV
V	17355	50.38	49.18	15.29	40.47	56.96	68.2	-11.24	PK
V	17355	40.41	49.18	15.29	40.47	46.99	54	-7.01	AV
H	11570	50.86	49.09	15.34	37.42	54.53	74	-19.47	PK
H	11570	42.08	49.09	15.34	37.42	45.75	54	-8.25	AV
H	17355	48.74	49.18	15.29	40.47	55.32	68.2	-12.88	PK
H	17355	40.19	49.18	15.29	40.47	46.77	54	-7.23	AV
operation frequency:5825									
V	11650	52.48	49.11	15.37	37.46	56.2	74	-17.80	PK
V	11650	41.34	49.11	15.37	37.46	45.06	54	-8.94	AV
V	17475	49.26	49.21	15.34	40.51	55.9	68.2	-12.30	PK
V	17475	40.85	49.21	15.34	40.51	47.49	54	-6.51	AV
H	11650	57.94	49.11	15.37	31.31	55.51	74	-18.49	PK
H	11650	48.08	49.11	15.37	31.31	45.65	54	-8.35	AV
H	17475	49.32	49.21	15.34	40.51	55.96	68.2	-12.24	PK
H	17475	40.89	49.21	15.34	40.51	47.53	54	-6.47	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5745									
V	11490	49.24	49.05	15.3	37.39	52.88	74	-21.12	PK
V	11490	42.89	49.05	15.3	37.39	46.53	54	-7.47	AV
V	17235	48.85	49.16	15.27	40.45	55.41	68.2	-12.79	PK
V	17235	40.24	49.16	15.27	40.45	46.8	54	-7.20	AV
H	11490	49.86	49.05	15.3	37.39	53.5	74	-20.50	PK
H	11490	41.17	49.05	15.3	37.39	44.81	54	-9.19	AV
H	17235	48.41	49.16	15.27	40.45	54.97	68.2	-13.23	PK
H	17235	40.49	49.16	15.27	40.45	47.05	54	-6.95	AV
operation frequency:5785									
V	11570	52.68	49.09	15.34	37.42	56.35	74	-17.65	PK
V	11570	42.25	49.09	15.34	37.42	45.92	54	-8.08	AV
V	17355	49.99	49.18	15.29	40.47	56.57	68.2	-11.63	PK
V	17355	40.54	49.18	15.29	40.47	47.12	54	-6.88	AV
H	11570	49.32	49.09	15.34	37.42	52.99	74	-21.01	PK
H	11570	43.69	49.09	15.34	37.42	47.36	54	-6.64	AV
H	17355	49.78	49.18	15.29	40.47	56.36	68.2	-11.84	PK
H	17355	40.74	49.18	15.29	40.47	47.32	54	-6.68	AV
operation frequency:5825									
V	11650	51.83	49.11	15.37	37.46	55.55	74	-18.45	PK
V	11650	41.48	49.11	15.37	37.46	45.2	54	-8.80	AV
V	17475	48.44	49.21	15.34	40.51	55.08	68.2	-13.12	PK
V	17475	40.69	49.21	15.34	40.51	47.33	54	-6.67	AV
H	11650	57.74	49.11	15.37	31.31	55.31	74	-18.69	PK
H	11650	44.33	49.11	15.37	31.31	41.9	54	-12.10	AV
H	17475	49.25	49.21	15.34	40.51	55.89	68.2	-12.31	PK
H	17475	40.61	49.21	15.34	40.51	47.25	54	-6.75	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5755									
V	11510	49.63	49.07	15.33	37.41	53.3	74	-20.70	PK
V	11510	41.57	49.07	15.33	37.41	45.24	54	-8.76	AV
V	17265	49.64	49.17	15.28	40.46	56.21	68.2	-11.99	PK
V	17265	40.26	49.17	15.28	40.46	46.83	54	-7.17	AV
H	11510	48.74	49.07	15.33	37.41	52.41	74	-21.59	PK
H	11510	41.13	49.07	15.33	37.41	44.8	54	-9.20	AV
H	17265	49.85	49.17	15.28	40.46	56.42	68.2	-11.78	PK
H	17265	40.49	49.17	15.28	40.46	47.06	54	-6.94	AV
operation frequency:5795									
V	11590	49.63	49.11	15.37	37.46	53.35	74	-20.65	PK
V	11590	41.27	49.11	15.37	37.46	44.99	54	-9.01	AV
V	17385	48.45	49.21	15.34	40.51	55.09	68.2	-13.11	PK
V	17385	40.23	49.21	15.34	40.51	46.87	54	-7.13	AV
H	11590	57.57	49.11	15.37	31.31	55.14	74	-18.86	PK
H	11590	44.36	49.11	15.37	31.31	41.93	54	-12.07	AV
H	17385	48.85	49.21	15.34	40.51	55.49	68.2	-12.71	PK
H	17385	40.94	49.21	15.34	40.51	47.58	54	-6.42	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11ac HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5745									
V	11490	49.26	49.05	15.3	37.39	52.9	74	-21.10	PK
V	11490	42.48	49.05	15.3	37.39	46.12	54	-7.88	AV
V	17235	48.64	49.16	15.27	40.45	55.2	68.2	-13.00	PK
V	17235	40.63	49.16	15.27	40.45	47.19	54	-6.81	AV
H	11490	48.25	49.05	15.3	37.39	51.89	74	-22.11	PK
H	11490	41.66	49.05	15.3	37.39	45.3	54	-8.70	AV
H	17235	48.24	49.16	15.27	40.45	54.8	68.2	-13.40	PK
H	17235	40.48	49.16	15.27	40.45	47.04	54	-6.96	AV
operation frequency:5785									
V	11570	48.46	49.09	15.34	37.42	52.13	74	-21.87	PK
V	11570	41.17	49.09	15.34	37.42	44.84	54	-9.16	AV
V	17355	49.25	49.18	15.29	40.47	55.83	68.2	-12.37	PK
V	17355	40.46	49.18	15.29	40.47	47.04	54	-6.96	AV
H	11570	49.87	49.09	15.34	37.42	53.54	74	-20.46	PK
H	11570	43.46	49.09	15.34	37.42	47.13	54	-6.87	AV
H	17355	49.38	49.18	15.29	40.47	55.96	68.2	-12.24	PK
H	17355	40.41	49.18	15.29	40.47	46.99	54	-7.01	AV
operation frequency:5825									
V	11650	49.16	49.11	15.37	37.46	52.88	74	-21.12	PK
V	11650	41.69	49.11	15.37	37.46	45.41	54	-8.59	AV
V	17475	48.15	49.21	15.34	40.51	54.79	68.2	-13.41	PK
V	17475	40.25	49.21	15.34	40.51	46.89	54	-7.11	AV
H	11650	57.26	49.11	15.37	31.31	54.83	74	-19.17	PK
H	11650	44.27	49.11	15.37	31.31	41.84	54	-12.16	AV
H	17475	48.35	49.21	15.34	40.51	54.99	68.2	-13.21	PK
H	17475	40.56	49.21	15.34	40.51	47.2	54	-6.80	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11ac HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5755									
V	11510	49.85	49.07	15.33	37.41	53.52	74	-20.48	PK
V	11510	42.84	49.07	15.33	37.41	46.51	54	-7.49	AV
V	17265	48.63	49.17	15.28	40.46	55.2	68.2	-13.00	PK
V	17265	41.48	49.17	15.28	40.46	48.05	54	-5.95	AV
H	11510	48.41	49.07	15.33	37.41	52.08	74	-21.92	PK
H	11510	42.73	49.07	15.33	37.41	46.4	54	-7.60	AV
H	17265	48.88	49.17	15.28	40.46	55.45	68.2	-12.75	PK
H	17265	40.26	49.17	15.28	40.46	46.83	54	-7.17	AV

operation frequency:5795

V	11590	49.45	49.11	15.37	37.46	53.17	74	-20.83	PK
V	11590	41.33	49.11	15.37	37.46	45.05	54	-8.95	AV
V	17385	48.17	49.21	15.34	40.51	54.81	68.2	-13.39	PK
V	17385	40.84	49.21	15.34	40.51	47.48	54	-6.52	AV
H	11590	57.26	49.11	15.37	31.31	54.83	74	-19.17	PK
H	11590	44.76	49.11	15.37	31.31	42.33	54	-11.67	AV
H	17385	48.41	49.21	15.34	40.51	55.05	68.2	-13.15	PK
H	17385	40.63	49.21	15.34	40.51	47.27	54	-6.73	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT80

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5775									
V	11550	48.37	49.07	15.33	37.41	52.04	74	-21.96	PK
V	11550	42.25	49.07	15.33	37.41	45.92	54	-8.08	AV
V	17325	49.66	49.17	15.28	40.46	56.23	68.2	-11.97	PK
V	17325	40.87	49.17	15.28	40.46	47.44	54	-6.56	AV
H	11550	48.34	49.07	15.33	37.41	52.01	74	-21.99	PK
H	11550	41.26	49.07	15.33	37.41	44.93	54	-9.07	AV
H	17325	48.96	49.17	15.28	40.46	55.53	68.2	-12.67	PK
H	17325	40.64	49.17	15.28	40.46	47.21	54	-6.79	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

RSS-247 Section 5.5

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	5000MHz
Stop Frequency	5420MHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



Radiated Emission Test-Up Frequency Above 1GHz

**3.3.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.3.6 TEST RESULT**

802.11a

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	5150	53.24	49.12	15.6	37.34	57.06	74	-16.94	PK
V	5150	39.39	49.12	15.6	37.34	43.21	54	-10.79	AV
V	5145	54.24	49.19	15.24	40.43	60.72	74	-13.28	PK
V	5145	36.98	49.19	15.24	40.43	43.46	54	-10.54	AV
H	5150	52.46	49.12	15.6	37.34	56.28	74	-17.72	PK
H	5150	37.64	49.12	15.6	37.34	41.46	54	-12.54	AV
H	5145	54.23	49.19	15.24	40.43	60.71	74	-13.29	PK
H	5145	33.47	49.19	15.24	40.43	39.95	54	-14.05	AV
operation frequency:5240									
V	5350	53.23	49.13	15.32	37.46	56.88	74	-17.12	PK
V	5350	35.18	49.13	15.32	37.46	38.83	54	-15.17	AV
V	5370	53.65	49.24	15.36	40.51	60.28	74	-13.72	PK
V	5370	32.26	49.24	15.36	40.51	38.89	54	-15.11	AV
H	5350	52.37	49.13	15.32	31.31	49.87	74	-24.13	PK
H	5350	40.15	49.13	15.32	31.31	37.65	54	-16.35	AV
H	5370	52.36	49.24	15.36	40.51	58.99	74	-15.01	PK
H	5370	32.79	49.24	15.36	40.51	39.42	54	-14.58	AV
Remark:									
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit									
2. If peak below the average limit, the average emission was no test.									
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	5150	51.38	49.12	15.6	37.34	55.2	74	-18.8	PK
V	5150	33.84	49.12	15.6	37.34	37.66	54	-16.34	AV
V	5145	51.26	49.19	15.24	40.43	57.74	74	-16.26	PK
V	5145	33.68	49.19	15.24	40.43	40.16	54	-13.84	AV
H	5150	51.26	49.12	15.6	37.34	55.08	74	-18.92	PK
H	5150	33.68	49.12	15.6	37.34	37.5	54	-16.5	AV
H	5145	50.84	49.19	15.24	40.43	57.32	74	-16.68	PK
H	5145	32.33	49.19	15.24	40.43	38.81	54	-15.19	AV
operation frequency:5240									
V	5350	53.18	49.13	15.32	37.46	56.83	74	-17.17	PK
V	5350	34.24	49.13	15.32	37.46	37.89	54	-16.11	AV
V	5370	50.66	49.24	15.36	40.51	57.29	74	-16.71	PK
V	5370	33.52	49.24	15.36	40.51	40.15	54	-13.85	AV
H	5350	54.27	49.13	15.32	31.31	51.77	74	-22.23	PK
H	5350	36.53	49.13	15.32	31.31	34.03	54	-19.97	AV
H	5370	51.29	49.24	15.36	40.51	57.92	74	-16.08	PK
H	5370	33.84	49.24	15.36	40.51	40.47	54	-13.53	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11ac HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	5150	52.26	49.12	15.33	37.41	55.88	74	-18.12	PK
V	5150	34.65	49.12	15.33	37.41	38.27	54	-15.73	AV
V	5145	51.24	49.19	15.28	40.46	57.79	74	-16.21	PK
V	5145	33.37	49.19	15.28	40.46	39.92	54	-14.08	AV
H	5150	52.33	49.12	15.33	37.41	55.95	74	-18.05	PK
H	5150	34.15	49.12	15.33	37.41	37.77	54	-16.23	AV
H	5145	50.46	49.19	15.28	40.46	57.01	74	-16.99	PK
H	5145	33.47	49.19	15.28	40.46	40.02	54	-13.98	AV
operation frequency:5240									
V	5350	53.23	49.13	15.32	37.46	56.88	74	-17.12	PK
V	5350	36.34	49.13	15.32	37.46	39.99	54	-14.01	AV
V	5370	50.88	49.24	15.36	40.51	57.51	74	-16.49	PK
V	5370	33.66	49.24	15.36	40.51	40.29	54	-13.71	AV
H	5350	53.68	49.13	15.32	31.31	51.18	74	-22.82	PK
H	5350	40.94	49.13	15.32	31.31	38.44	54	-15.56	AV
H	5370	51.36	49.24	15.36	40.51	57.99	74	-16.01	PK
H	5370	35.54	49.24	15.36	40.51	42.17	54	-11.83	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5190									
V	5150	52.36	49.12	15.6	37.39	56.23	74	-17.77	PK
V	5150	35.74	49.12	15.6	37.39	39.61	54	-14.39	AV
V	5145	51.16	49.19	15.24	40.45	57.66	74	-16.34	PK
V	5145	34.35	49.19	15.24	40.45	40.85	54	-13.15	AV
H	5150	52.64	49.12	15.6	37.39	56.51	74	-17.49	PK
H	5150	34.16	49.12	15.6	37.39	38.03	54	-15.97	AV
H	5145	50.78	49.19	15.24	40.45	57.28	74	-16.72	PK
H	5145	35.33	49.19	15.24	40.45	41.83	54	-12.17	AV
operation frequency:5230									
V	5350	53.15	49.13	15.34	37.46	56.82	74	-17.18	PK
V	5350	37.93	49.13	15.34	37.46	41.6	54	-12.4	AV
V	5370	50.27	49.24	15.35	40.51	56.89	74	-17.11	PK
V	5370	36.64	49.24	15.35	40.51	43.26	54	-10.74	AV
H	5350	54.26	49.13	15.34	31.31	51.78	74	-22.22	PK
H	5350	41.64	49.13	15.34	31.31	39.16	54	-14.84	AV
H	5370	52.66	49.24	15.35	40.51	59.28	74	-14.72	PK
H	5370	36.17	49.24	15.35	40.51	42.79	54	-11.21	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11ac HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5190									
V	5150	52.24	49.12	15.32	37.41	55.85	74	-18.15	PK
V	5150	37.66	49.12	15.32	37.41	41.27	54	-12.73	AV
V	5145	52.17	49.19	15.36	40.46	58.8	74	-15.2	PK
V	5145	36.66	49.19	15.36	40.46	43.29	54	-10.71	AV
H	5150	52.94	49.12	15.32	37.41	56.55	74	-17.45	PK
H	5150	37.67	49.12	15.32	37.41	41.28	54	-12.72	AV
H	5145	51.16	49.19	15.36	40.46	57.79	74	-16.21	PK
H	5145	36.57	49.19	15.36	40.46	43.2	54	-10.8	AV
operation frequency:5230									
V	5350	54.36	49.13	15.34	37.34	57.91	74	-16.09	PK
V	5350	36.45	49.13	15.34	37.34	40	54	-14	AV
V	5370	51.31	49.24	15.35	40.43	57.85	74	-16.15	PK
V	5370	36.57	49.24	15.35	40.43	43.11	54	-10.89	AV
H	5350	54.76	49.13	15.34	37.34	58.31	74	-15.69	PK
H	5350	41.43	49.13	15.34	37.34	44.98	54	-9.02	AV
H	5370	50.55	49.24	15.35	40.43	57.09	74	-16.91	PK
H	5370	35.76	49.24	15.35	40.43	42.3	54	-11.7	AV
Remark:									
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit									
2. If peak below the average limit, the average emission was no test.									
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									

802.11ac HT80

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5210									
V	5350	52.36	49.13	15.32	37.48	56.03	74	-17.97	PK
V	5350	35.84	49.13	15.32	37.48	39.51	54	-14.49	AV
V	5370	51.37	49.24	15.36	40.42	57.91	74	-16.09	PK
V	5370	35.66	49.24	15.36	40.42	42.2	54	-11.8	AV
H	5350	52.73	49.13	15.32	37.48	56.4	74	-17.6	PK
H	5350	36.28	49.13	15.32	37.48	39.95	54	-14.05	AV
H	5370	50.24	49.24	15.36	40.42	56.78	74	-17.22	PK
H	5370	35.89	49.24	15.36	40.42	42.43	54	-11.57	AV
Remark:									
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit									
2. If peak below the average limit, the average emission was no test.									
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



3.3 CONDUCTED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.407

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Spectrum Parameter	Setting	
Attenuation	Auto	
Start Frequency	5150MHz	5725MHz
Stop Frequency	5250MHz	5850MHz
RB / VB (emission in restricted band)	1 MHz / 3 MHz for Peak, 1 MHz / 10Hz for Average	


3.3.2 TEST PROCEDURE

Test method: FCC KDB 789033 G)& Parts 15.407(b)(4) & 15.209(a)

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



3.3.5 EUT OPERATING CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




3.3.6 TEST RESULT

The antenna gain is compensated in the test data.

802.11a




5180MHz



5240MHz

802.11n HT20




5180MHz




5240MHz

802.11n HT40




5190MHz




5230MHz



802.11ac HT20




5180MHz




5240MHz

802.11ac HT40




5190MHz



5230MHz


802.11ac HT80



5210MHz



802.11a



5745MHz




5825MHz

802.11n HT20




5745MHz



5825MHz

802.11n HT40




5755MHz



5795MHz



802.11ac HT20




5745MHz




5825MHz

802.11ac HT40



5755MHz



5795MHz

802.11ac HT80



5775MHz



4. AVERAGING OUTPUT POWER

4.1 APPLIED PROCEDURES / LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

4.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
VBW $\geq$ RBW
Sweep = auto
Detector function = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
Trace = max hold

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**4.1.5 TEST RESULTS**


Temperature:	25 °C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	AC 120V/60Hz

Band	Mode	Test Channel	Average Output Power (dBm)	Duty factor (dB)	Total Output Power(dB)	LIMIT (dBm)
Band 1	802.11a	Low	5.481	0.7	6.181	23.98
		Middle	5.491	0.7	6.191	23.98
		High	5.936	0.7	6.636	23.98
	802.11n HT20	Low	6.284	0.11	6.394	23.98
		Middle	5.709	0.11	5.819	23.98
		High	6.145	0.11	6.255	23.98
	802.11n HT40	Low	5.546	0.21	5.756	23.98
		High	5.659	0.21	5.869	23.98
	802.11ac HT20	Low	5.65	0.11	5.76	23.98
		Middle	5.637	0.11	5.747	23.98
		High	6.087	0.11	6.197	23.98
	802.11ac HT40	Low	5.652	0.21	5.862	23.98
		High	5.695	0.21	5.905	23.98
	802.11ac HT80	/	5.376	0.41	5.786	23.98


Band	Mode	Test Channel	Average Output Power (dBm)	Duty factor (dB)	Total Output Power(dB)	LIMIT (dBm)
Band 4	802.11a	Low	8.798	0.7	9.498	30
		Middle	8.479	0.7	9.179	30
		High	8.638	0.7	9.338	30
	802.11n HT20	Low	9.592	0.11	9.702	30
		Middle	9.419	0.11	9.529	30
		High	9.367	0.11	9.477	30
	802.11n HT40	Low	9.167	0.21	9.377	30
		High	9.542	0.21	9.752	30
	802.11ac HT20	Low	9.597	0.11	9.707	30
		Middle	9.396	0.11	9.506	30
		High	9.266	0.11	9.376	30
	802.11ac HT40	Low	9.112	0.21	9.322	30
		High	9.394	0.21	9.604	30
	802.11ac HT80	/	9.169	0.41	9.579	30



802.11a




802.11n HT20



5180MHz



5180MHz



5200MHz



5200MHz




5240MHz


5240MHz




802.11n HT40



802.11ac HT20



5190MHz



5180MHz





5230MHz



5200MHz


5240MHz




802.11ac HT40 	802.11ac HT80 
5190MHz 	5210MHz
5230MHz	



802.11a



802.11n HT20



5745MHz



5745MHz



5785MHz



5785MHz




5825MHz


5825MHz



802.11n HT40



802.11ac HT20



5755MHz



5745MHz



5795MHz


5785MHz




5825MHz




802.11ac HT40



802.11ac HT80



5755MHz



5775MHz

5795MHz



5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

In addition, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW $\geq$ 1MHz for band 1 RBW $\geq$ 510KHz for band 4
VB	VBW $\geq$ 3RBW
Detector	RMS (i.e., power averaging).
Trace	Max Hold
Sweep Time	Auto


5.1.1 TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. The testing follows FCC KDB 789033 D02.
3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to Spectrum.
4. For U-NII1, U-NII-2A, U-NII-2C Band:
Set RBW=1MHz, VBW=3MHz, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
For U-NII-3 Band:
Set RBW=510 kHz, VBW=3*RBW, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
5. Use the cursor on spectrum to peak search the highest level of trace
6. Record the max. reading and add 10 log(1/duty cycle).
we test all antennas, the antenna 1 was worst mode and the data recording in the report.
7. Duty factor Reference is made to the test results in Section 7.1.5.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.1.5 TEST RESULTS**

	Mode	Test Channel	Reading Level (dBm)	Duty factor (dB)	PSD (dBm/MHz)	Limit (dBm)	Result
Band1	802.11a	Low	-3.957	0.7	-3.257	11.00	PASS
		Middle	-3.907	0.7	-3.207	11.00	PASS
		High	-3.429	0.7	-2.729	11.00	PASS
	802.11n20	Low	-3.232	0.11	-3.122	11.00	PASS
		Middle	-4.077	0.11	-3.967	11.00	PASS
		High	-3.413	0.11	-3.303	11.00	PASS
	802.11n40	Low	-7.407	0.21	-7.197	11.00	PASS
		High	-7.199	0.21	-6.989	11.00	PASS
	802.11ac20	Low	-4.051	0.11	-3.941	11.00	PASS
		Middle	-4.065	0.11	-3.955	11.00	PASS
		High	-3.612	0.11	-3.502	11.00	PASS
	802.11ac40	Low	-7.22	0.21	-7.01	11.00	PASS
		High	-7.275	0.21	-7.065	11.00	PASS
	802.11ac80	/	-10.353	0.41	-9.943	11.00	PASS

	Mode	Test Channel	Reading Level (dBm)	Duty factor (dB)	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
Band4	802.11a	Low	-3.424	0.7	-2.724	30.00	PASS
		Middle	-3.833	0.7	-3.133	30.00	PASS
		High	-3.405	0.7	-2.705	30.00	PASS
	802.11n20	Low	-3.106	0.11	-2.996	30.00	PASS
		Middle	-3.195	0.11	-3.085	30.00	PASS
		High	-3.353	0.11	-3.243	30.00	PASS
	802.11n40	Low	-6.433	0.21	-6.223	30.00	PASS
		High	-6.151	0.21	-5.941	30.00	PASS
	802.11ac20	Low	-3.156	0.11	-3.046	30.00	PASS
		Middle	-3.439	0.11	-3.329	30.00	PASS
		High	-3.545	0.11	-3.435	30.00	PASS
	802.11ac40	Low	-6.445	0.21	-6.235	30.00	PASS
		High	-6.391	0.21	-6.181	30.00	PASS
	802.11ac80	/	-9.818	0.41	-9.408	30.00	PASS



802.11a




802.11n HT20



5180MHz



5180MHz



5200MHz



5200MHz



5240MHz

5240MHz



802.11n HT40




802.11ac HT20



5190MHz



5180MHz



5230MHz



5200MHz



5240MHz



802.11ac HT40



802.11ac HT80



5190MHz



5210MHz

5230MHz



802.11a



802.11n HT20



5745MHz



5745MHz



5785MHz



5785MHz



5825MHz

5825MHz



802.11n HT40



802.11ac HT20



5755MHz



5745MHz



5795MHz


5785MHz




5825MHz



802.11ac HT40



802.11ac HT80



5755MHz



5775MHz

5795MHz



6. 6DB&26DB&99% BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

The 26 dB bandwidth is used to determine the conducted power limits.

There is no limit bandwidth for U-NII-1, U-NII-2-A and U-NII-2-C.

The minimum of 6dB Bandwidth measurement is 0.5 MHz for U-NII-3

6.1.1 TEST PROCEDURE

6dB Bandwidth	
Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	30MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

26dB Bandwidth	
Spectrum Parameters	Setting
RBW	approximately 1% of the emission bandwidth
VBW	>RBW
Span	30MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

99% Occupied Bandwidth	
Spectrum Parameters	Setting
RBW	1% to 5% of the OBW
VBW	Approximately three times the RBW
Span	between 1.5 times and 5.0 times the OBW
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP





6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


6.1.5 TEST RESULTS

		Test Channel	26dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
Band 1	802.11a	Low	19.46	16.363	Pass
		Middle	19.68	16.389	Pass
		High	19.39	16.391	Pass
	802.11n HT20	Low	20.18	17.573	Pass
		Middle	20.12	17.566	Pass
		High	19.97	17.539	Pass
	802.11n HT40	Low	40.22	35.959	Pass
		High	40.70	36.030	Pass
	802.11ac HT20	Low	20.10	17.560	Pass
		Middle	20.17	17.559	Pass
		High	20.03	17.539	Pass
	802.11ac HT40	Low	40.38	35.937	Pass
		High	40.04	36.011	Pass
	802.11ac HT80	/	80.34	75.325	Pass


		Test Channel	6dB Bandwidth (MHz)	6dB Bandwidth Limit (MHz)	Result
Band 4	802.11a	Low	15.974	>0.5	Pass
		Middle	15.707	>0.5	Pass
		High	16.006	>0.5	Pass
	802.11n HT20	Low	14.994	>0.5	Pass
		Middle	15.059	>0.5	Pass
		High	17.067	>0.5	Pass
	802.11n HT40	Low	35.11	>0.5	Pass
		High	33.836	>0.5	Pass
	802.11ac HT20	Low	14.786	>0.5	Pass
		Middle	15.087	>0.5	Pass
		High	17.267	>0.5	Pass
	802.11ac HT40	Low	35.096	>0.5	Pass
		High	35.005	>0.5	Pass
	802.11ac HT80	/	75.046	>0.5	Pass



802.11a



802.11n HT20



5180MHz



5180MHz



5200MHz



5200MHz




5240MHz

5240MHz



802.11n HT40



802.11ac HT20



5190MHz



5180MHz



5230MHz



5200MHz


5240MHz



802.11ac HT40



802.11ac HT80



5190MHz



5210MHz



5230MHz





802.11a



802.11n HT20



5745MHz



5745MHz



5785MHz



5785MHz



5825MHz


5825MHz



802.11n HT40



802.11ac HT20



5755MHz



5745MHz



5795MHz



5785MHz



5825MHz




802.11ac HT40



802.11ac HT80



5755MHz



5775MHz

5795MHz



7. DUTY CYCLE TEST SIGNAL

7.1 APPLIED PROCEDURES / LIMIT

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle. All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.


7.1.1 TEST PROCEDURE

1. Set RBW = 1 MHz.
2. Set the video bandwidth (VBW) $\geq$ RBW.
3. Detector = Peak.
4. Sweep = auto couple.
5. Allow the trace to stabilize.
6. Span=0

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


**7.1.5 TEST RESULTS**

Operation Mode		Duty Cycle(%)	Duty Fator (dB) 10 * log (1/ Duty cycle)
Band 1	802.11a	85.03	0.7
	802.11n(HT20)	97.53	0.11
	802.11n(HT40)	95.22	0.21
	802.11ac(HT20)	97.58	0.11
	802.11ac(HT40)	95.23	0.21
	802.11ac(HT80)	91.02	0.41


Operation Mode		Duty Cycle(%)	Duty Fator (dB) 10 * log (1/ Duty cycle)
Band 4	802.11a	85.18	0.7
	802.11n(HT20)	97.54	0.11
	802.11n(HT40)	95.34	0.21
	802.11ac(HT20)	97.58	0.11
	802.11ac(HT40)	95.28	0.21
	802.11ac(HT80)	91.01	0.41




802.11a



802.11n HT20




802.11n HT40




802.11ac HT20



802.11ac HT40




802.11ac HT80







802.11a



802.11n HT20




802.11n HT40




802.11ac HT20



802.11ac HT40



802.11ac HT80





8. FREQUENCY STABILITY

8.1 APPLIED PROCEDURES / LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


8.1.1 TEST PROCEDURE

1. The EUT was placed inside temperature chamber and powered and powered by nominal DC voltage.
2. Set EUT as normal operation.
3. Turn the EUT on and couple its output to spectrum.
4. Turn the EUT off and set the chamber to the highest temperature specified.
5. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT and measure the operating frequency.
6. Repeat step with the temperature chamber set to the lowest temperature.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



8.1.5 TEST RESULTS

Test Voltage	Test Temp.	Measured Frequency	Spectrum Frequency (MHz)			Δ Frequency (MHz)		
		(MHz)	802.11a	802.11n HT20	802.11ac HT20	802.11a	802.11n HT20	802.11ac HT20
132V	-20℃	5180	5180.0353	5180.0355	5180.0364	-0.0353	-0.0355	-0.0364
		5220	5220.0321	5220.0364	5220.0365	-0.0321	-0.0364	-0.0365
		5240	5240.0234	5240.0215	5240.0214	-0.0234	-0.0215	-0.0214
		5745	5745.0367	5745.0328	5745.0326	-0.0367	-0.0328	-0.0326
		5785	5785.0384	5785.0335	5785.0354	-0.0384	-0.0335	-0.0354
		5825	5825.0335	5825.0333	5825.0361	-0.0335	-0.0333	-0.0361
108V		5180	5180.0256	5180.0245	5180.0254	-0.0256	-0.0245	-0.0254
		5220	5220.0312	5220.0336	5220.0358	-0.0312	-0.0336	-0.0358
		5240	5240.0244	5240.0248	5240.0225	-0.0244	-0.0248	-0.0225
		5745	5745.0268	5745.0264	5745.0291	-0.0268	-0.0264	-0.0291
		5785	5785.0325	5785.0376	5785.0354	-0.0325	-0.0376	-0.0354
		5825	5825.0416	5825.0455	5825.0413	-0.0416	-0.0455	-0.0413
120V	25℃	5180	5180.0528	5180.0514	5180.0535	-0.0528	-0.0514	-0.0535
		5220	5220.0264	5220.0247	5220.0246	-0.0264	-0.0247	-0.0246
		5240	5240.0324	5240.0315	5240.0367	-0.0324	-0.0315	-0.0367
		5745	5745.0356	5745.0326	5745.0344	-0.0356	-0.0326	-0.0344
		5785	5785.0434	5785.0418	5785.0464	-0.0434	-0.0418	-0.0464
		5825	5825.0214	5825.0274	5825.0228	-0.0214	-0.0274	-0.0228
132V	50℃	5180	5180.0318	5180.0365	5180.0364	-0.0318	-0.0365	-0.0364
		5220	5220.0234	5220.0246	5220.0276	-0.0234	-0.0246	-0.0276
		5240	5240.0356	5240.0358	5240.0358	-0.0356	-0.0358	-0.0358
		5745	5745.0668	5745.0654	5745.0665	-0.0668	-0.0654	-0.0665
		5785	5785.0424	5785.0425	5785.0446	-0.0424	-0.0425	-0.0446
		5825	5825.0646	5825.0622	5825.0665	-0.0646	-0.0622	-0.0665
108V	50℃	5180	5180.0387	5180.0323	5180.0348	-0.0387	-0.0323	-0.0348
		5220	5220.0255	5220.0266	5220.0255	-0.0255	-0.0266	-0.0255
		5240	5240.0317	5240.0358	5240.0326	-0.0317	-0.0358	-0.0326
		5745	5745.0465	5745.0434	5745.0468	-0.0465	-0.0434	-0.0468
		5785	5785.0256	5785.0254	5785.0244	-0.0256	-0.0254	-0.0244
		5825	5825.0728	5825.0739	5825.0762	-0.0728	-0.0739	-0.0762



Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)		Δ Frequency (MHz)	
			802.11n HT40	802.11ac HT40	802.11n HT40	802.11ac HT40
132V	-20℃	5190	5190.0246	5190.0256	-0.0246	-0.0256
		5230	5230.0388	5230.0384	-0.0388	-0.0384
		5755	5755.0575	5755.0543	-0.0575	-0.0543
		5795	5795.0656	5795.0665	-0.0656	-0.0665
108V		5190	5190.0268	5190.0257	-0.0268	-0.0257
		5230	5230.0345	5230.0344	-0.0345	-0.0344
		5755	5755.0234	5755.0665	-0.0234	-0.0665
		5795	5795.0455	5795.0445	-0.0455	-0.0445
120V	25℃	5190	5190.0267	5190.0264	-0.0267	-0.0264
		5230	5230.0673	5230.0652	-0.0673	-0.0652
		5755	5755.0254	5755.0234	-0.0254	-0.0234
		5795	5795.0564	5795.0538	-0.0564	-0.0538
132V	50℃	5190	5190.0665	5190.0654	-0.0665	-0.0654
		5230	5230.0566	5230.0563	-0.0566	-0.0563
		5755	5755.0465	5755.0485	-0.0465	-0.0485
		5795	5795.0324	5795.0356	-0.0324	-0.0356
108V	50℃	5190	5190.0588	5190.0564	-0.0588	-0.0564
		5230	5230.0356	5230.0344	-0.0356	-0.0344
		5755	5755.0354	5755.0364	-0.0354	-0.0364
		5795	5795.0464	5795.0486	-0.0464	-0.0486



Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)	Δ Frequency (MHz)
			802.11ac HT80	802.11ac HT80
132V	-20℃	5210	5210.0156	-0.0156
		5775	5775.0168	-0.0168
108V		5210	5210.0274	-0.0274
		5775	5775.0343	-0.0343
120V	25℃	5210	5210.0465	-0.0465
		5775	5775.0364	-0.0364
132V	50℃	5210	5210.0347	-0.0347
		5775	5775.0265	-0.0265
108V	50℃	5210	5210.0336	-0.0336
		5775	5775.0547	-0.0547



9. TRANSMISSION IN THE ABSENCE OF DATA

9.1 STANDARD REQUIREMENT

According to §15.407(c)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

9.2 TEST RESULT

No non-compliance noted:
Refer to the theory of operation.

10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is Internal Antenna, It comply with the standard requirement.




11. TEST SEUUP PHOTO

Radiated Measurement Photos





Conducted Measurement Photos








12. EUT PHOTO


























***** END OF REPORT *****