

SPECIFICATION

Shenzhen Guandetong Electronic Limited

3rd Floor, Building D, Maoyuan Industrial Park, Huanguan South Road, Guanhu Street,
Longhua District, Shenzhen, China



深圳市冠得通电子有限公司

Shenzhen Guandetong Electronic Co., Ltd.

Ultrasonic decorative antenna

Product Specification


connection		frequency range	//
Frequency band wire name		edition	A1
Customer part number		Guandetong part number	
Guandetong No			
R F design	肖彬	RF Manager	刘亮
Structural design	王栋	Structure Manager	王华
Technical Director	叶定坤	Date	2023-11-09

Customer confirmation:

Does the assembly meet your company's requirements: ☐OK ☐NG

Cover	1
catalogue.....	2
一、Product pictures	3
二、Product parameters	3
三、Structural drawings.....	4
四、Environmental performance test.....	4- 5

一、 Product pictures



二、 Product parameters

Product testing parameters			
Product name		(Model Type)	
(Electrical Specifications)			
(Frequency Range)	//	(Polarization)	//
(Impedance)	//	Radiation	//
(VSWR)	//	(Power)	//
(Gain)	//	(Bandwidth)	//
(Mechanical Specifications)			
(Dimensions)	104.99*11.95-+0.3mm	(Chassis Color)	//
(Connector)	//	(Cable Length)	//
(Chassis Material)	ABS		
(Working Temperature)	-40℃-+85℃	(Limit Temperature)	-40℃-+85℃


公司地址：深圳市龙华区观湖街道环观南茂源工业园 D 栋 3 楼 电话：0755-88298396 传真：0755-89733896

<http://www.szgdtrf.com>

保 密 要 求

本公司已拥有专有技术所提供的资料，这些专有资料应严加保密，在未经深圳冠得通电子有限公司事先书面同意的时不允许透露给任何人或公司。

三、Structural drawings



四、Environmental performance test

project	Project test conditions	Specifications
Storage environment	The test temperature, humidity and air pressure are as follows when there is no specific condition: 1. The temperature is - 30 °C~+80 °C 2. Relative humidity: 45% - 85% 3. The air pressure is 86kpa-106kpa	Normal electrical and mechanical performance

公司地址：深圳市龙华区观湖街道环观南茂源工业园 D 栋 3 楼 电话：0755-88298396 传真：0755-89733896

<http://www.szgdtrf.com>

深圳市冠得通电子有限公司

保 密 要 求

本公司已拥有专有技术所提供的资料，这些专有资料应严加保密，在未经深圳冠得通电子有限公司事先书面同意的时不允许透露给任何人或公司。


High and low temperature test	5 cycles between 70 ° C and 40 ° C, then under normal conditions1-2H, check the appearance quality.	The size shall meet the requirements and Mechanical and electrical performance
Constant damp heat resistance test	Relative humidity: 95 ± 3%, test temperature: 40 °C. After lasting for 2h, The electrical performance shall be measured within 5 minutes after the test object is taken out, and the test object shall be within the normal range Part 1-2H, check the appearance quality	The size shall meet the requirements and Mechanical and electrical performance
vibration test	Vibration frequency range: 10-55HZ, displacement amplitude: 0.35MM, acceleration amplitude: 50.0M/s, frequency sweep cycles: 30 times	Normal electrical and mechanical performance
Drop test	Free fall for 3 times in the direction of mutually perpendicular axes at a height of 1M	Normal electrical and mechanical performance

公司地址：深圳市龙华区观湖街道环观南茂源工业园 D 栋 3 楼 电话：0755-88298396 传真：0755-89733896


<http://www.szgdtrf.com>

五:3D pattern


2400.000MHz




2450.000MHz




2500.000MHz



5000.000MHz



5500.000MHz



6000.000MHz

