



Radio Test Report

Report No.: STS2601034W02

Issued for

Zhiyi (Zhongshan) Technology Co., Ltd

No. 39 Donghui Road, Cuiheng New District, Zhongshan,
Guangdong, PEOPLE'S REPUBLIC OF CHINA

Product Name: Robot vacuum cleaner

Brand Name: ILIFE, ZACO,
ZHIYI 智意, EASINE

Model Name: X321

Series Model(s): V5s Max

FCC ID: 2BD8J-X321

Test Standards: FCC Part15.247

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT**

Applicant's Name : Zhiyi (Zhongshan) Technology Co., Ltd
Address : No. 39 Donghui Road, Cuiheng New District, Zhongshan,
Guangdong, PEOPLE'S REPUBLIC OF CHINA
Manufacturer's Name : Zhiyi (Zhongshan) Technology Co., Ltd
Address : No. 39 Donghui Road, Cuiheng New District, Zhongshan,
Guangdong, PEOPLE'S REPUBLIC OF CHINA

Product Description

Product Name : Robot vacuum cleaner
Brand Name : ILIFE, ZACO, ZHIYI 智意, EASINE
Model Name : X321
Series Model(s) : V5s Max
Standards : FCC Part 15.247
Test Procedure : ANSI C63.10-2020

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test

Date of receipt of test item : 06 Jan. 2026
Date (s) of performance of tests : 06 Jan. 2026 ~ 31 Jan. 2026
Date of Issue : 31 Jan. 2026
Test Result : **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 TEST SOFTWARE AND POWER LEVEL	10
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	12
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3. EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.2 RADIATED EMISSION MEASUREMENT	18
4. DUTY CYCLE	35
4.1 TEST STANDARD	35
4.2 TEST PROCEDURE	35
4.3 DEVIATION FROM STANDARD	35
4.4 TEST SETUP	35
4.6 TEST RESULTS	35
5. CONDUCTED SPURIOUS & BAND EDGE EMISSION	36
5.1 LIMIT	36
5.2 TEST PROCEDURE	36
5.3 DEVIATION FROM STANDARD	36
5.4 TEST SETUP	36
5.5 EUT OPERATION CONDITIONS	36
5.6 TEST RESULTS	36
6. POWER SPECTRAL DENSITY TEST	37
6.1 LIMIT	37
6.2 TEST PROCEDURE	37
6.3 DEVIATION FROM STANDARD	37
6.4 TEST SETUP	37
6.5 EUT OPERATION CONDITIONS	37
6.6 TEST RESULTS	37



Table of Contents	Page
7. BANDWIDTH TEST	38
7.1 LIMIT	38
7.2 TEST PROCEDURE	38
7.3 DEVIATION FROM STANDARD	38
7.4 TEST SETUP	38
7.5 EUT OPERATION CONDITIONS	38
7.6 TEST RESULTS	38
8. PEAK OUTPUT POWER TEST	39
7.1 LIMIT	39
8.2 TEST PROCEDURE	39
8.3 DEVIATION FROM STANDARD	39
8.4 TEST SETUP	39
8.5 EUT OPERATION CONDITIONS	39
8.6 TEST RESULTS	39
9. ANTENNA REQUIREMENT	40
9.1 STANDARD REQUIREMENT	40
9.2 EUT ANTENNA	40
APPENDIX 1-TEST DATA	41
DUTY CYCLE	41
MAXIMUM PEAK CONDUCTED OUTPUT POWER	47
-6DB BANDWIDTH	48
MAXIMUM POWER SPECTRAL DENSITY LEVEL	54
BAND EDGE	60
CONDUCTED RF SPURIOUS EMISSION	67
APPENDIX 2-PHOTOS OF TEST SETUP	77

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	31 Jan. 2026	STS2601034W02	ALL	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted Band Edge Emission	PASS	--
Part 15.247(d)/ part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2020.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.751\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.888\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.48\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 2.52\text{dB}$
5	All emissions, radiated 1G-18GHz	$\pm 3.48\text{dB}$
6	All emissions, radiated >18GHz	$\pm 4.18\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.48\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.52\text{dB}$
9	Occupied Channel Bandwidth	$\pm 3.6\%$
10	Power Spectral Density, conducted	$\pm 1.214\text{dB}$
11	Duty Cycle	$\pm 3.2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Robot vacuum cleaner	
Brand Name	ILIFE, ZACO, ZHIYI 智意, EASINE	
Model Name	X321	
Series Model(s)	V5s Max	
Model Difference	The difference lies only in the Brand name and Model name of the different models.	
Product Description	The EUT is a Robot vacuum cleaner	
	Operation Frequency:	802.11b/g/n 20: 2412~2462 MHz
	Modulation Type:	802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM
	Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20MHz): 65/58.5/52/39/26/19.5/13/6.5Mbps
	Number of Channel:	802.11b/g/n20: 11CH
	Antenna Type:	PCB
	Antenna Gain (dBi):	2.54
Channel List	Please refer to the Note 3.	
Power Rating	N/A	
Adapter	Model: K12V190060U Brand: N/A Input: 100-240V~50/60Hz 0.35A Output:DC19V 0.6A	
Battery	Model: H18650CH-4S1P-AGX-8 Brand: N/A Rated Voltage:14.4V Charge Limit Voltage:16.6V Capacity: 2600mAh	
Hardware version number	N/A	
Software version number	N/A	
Connecting I/O Port(s)	Please refer to the Note 1.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna details in this report are based on the manufacturer provided antenna specification documents and apply only to the tested sample identified herein.
Any discrepancies in the antenna information may affect the accuracy of the test results, and the



customer assumes responsibility for any related issues..

3

Operation Frequency of channel 802.11b/g/n (20MHz)	
Channel	Frequency
01	2412
02	2417
03	2422
04	2427
05	2432
06	2437
07	2442
08	2447
09	2452
10	2457
11	2462

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

2.4GHz Test Frequency:

For 802.11b/g/n (HT20)	
Channel	Freq.(MHz)
01	2412
06	2437
11	2462



2.2 DESCRIPTION OF THE TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11b CH01	1 Mbps
Mode 2	TX IEEE 802.11b CH06	1 Mbps
Mode 3	TX IEEE 802.11 b CH11	1 Mbps
Mode 4	TX IEEE 802.11g CH01	6 Mbps
Mode 5	TX IEEE 802.11g CH06	6 Mbps
Mode 6	TX IEEE 802.11g CH11	6 Mbps
Mode 7	TX IEEE 802.11n HT20 CH01	MCS 0
Mode 8	TX IEEE 802.11n HT20 CH06	MCS 0
Mode 9	TX IEEE 802.11n HT20 CH11	MCS 0

Note:

- (1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
- (2) We have be tested for all available U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V /60Hz is shown in the report.

AC Conducted Emission

Test Case	
AC Conducted Emission	Mode10: Keeping TX + WLAN Link


2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.


RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(2.4G)	2.4G WIFI	802.11b	2.54	75	UI_mptool.1v3
		802.11g		85	
		802.11n(HT20)		90	

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


Radiated Spurious Emission Test



AC Conducted Emission Test



RF Conducted Test





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
E-1	Notebook	DELL	Inspiron 3501	N/A
E-2	Adapter	N/A	K12V190060U	N/A
C-1	Serial port board	XES	WTYZK	N/A
C-2	USB Cable	MI	RYEW3A	N/A
C-3	USB Cable	N/A	K12V190060U	N/A

Item	Equipment	Mfr/Brand	Length	Note
C-2	Shielded	NO	150cm	N/A
C-3	Shielded	NO	150cm	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

RF Radiation Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Pre-Amplifier(0.1M-3GHz)	EM	EM330	060665	2025.02.22	2026.02.21
Pre-Amplifier(1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2025.09.25	2026.09.24
Pre-Amplifier(18G-40GHz)	SKET	LNPA_1840-50	SK2018101801	2025.02.22	2026.02.21
Active loop Antenna	ZHINAN	ZN30900C	16035	2025.02.25	2027.02.24
Bilog Antenna	TESEQ	CBL6111D	34678	2025.09.27	2027.09.26
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2025.09.27	2027.09.26
Horn Antenna	A-INFOMW	LB-180400-KF	J211020657	2025.09.27	2027.09.26
Positioning Controller	MF	MF-7802	MF-780208587	N/A	N/A
Signal Analyzer	R&S	FSV 40-N	101823	2025.09.26	2026.09.25
Switch Control Box	N/A	N/A	N/A	N/A	N/A
Band 2.4G-2.5G Filter	HX MICROWAVE	HXLBQ-DZA61	N/A	2025.09.23	2026.09.22
Antenna Mast	MF	MFA-440H	N/A	N/A	N/A
Turn Table	MF	SC100_1	60531	N/A	N/A
AC Power Source	APC	KDF-11010G	F214050035	N/A	N/A
DC power supply	HONGSHENG FENG	DPS-305AF	17064939	2025.09.22	2026.09.21
Test SW	EZ-EMC	Ver.STSLAB-03A1 RE			
Conduction Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2025.09.25	2026.09.24
Limiter	CYBERTEK	EM5010	N/A	2025.09.25	2026.09.24
LISN	R&S	ENV216	101242	2025.09.25	2026.09.24
LISN	EMCO	3810/2NM	23625	2025.09.25	2026.09.24
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Test SW	EZ-EMC	Ver.STSLAB-03A1 CE			
RF Connected Test					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Analyzer	Agilent	N9020A	MY51510623	2025.02.22	2026.02.21
Pulse Power Sensor	Anritsu	MA2411B	917389	2025.09.23	2026.09.22
Power Meter	Anritsu	ML2480	1005127	2025.09.23	2026.09.22
Switch control box	MW	MW100-RFCB	N/A	N/A	N/A
Temperature& Humidity test chamber	Safety test	AG80L	171200018	2025.02.22	2026.02.21
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Test SW	MW	MTS 8310_2.0.0.0			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.1.5 TEST RESULT

Temperature:	25.1°C	Relative Humidity:	59%
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 10		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1940	21.84	19.39	41.23	63.86	-22.63	QP
2	0.1940	9.30	19.39	28.69	53.86	-25.17	AVG
3	0.2940	21.11	19.37	40.48	60.41	-19.93	QP
4	0.2940	8.44	19.37	27.81	50.41	-22.60	AVG
5	0.4500	19.87	19.39	39.26	56.88	-17.62	QP
6	0.4500	12.50	19.39	31.89	46.88	-14.99	AVG
7	0.5540	24.74	19.39	44.13	56.00	-11.87	QP
8	0.5540	18.96	19.39	38.35	46.00	-7.65	AVG
9	0.6220	19.41	19.38	38.79	56.00	-17.21	QP
10	0.6220	11.31	19.38	30.69	46.00	-15.31	AVG
11	0.7540	16.95	19.37	36.32	56.00	-19.68	QP
12	0.7540	7.90	19.37	27.27	46.00	-18.73	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor=LISN factor+Cable loss+Limiter (10dB)






Temperature:	25.1℃	Relative Humidity:	59%
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 10		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	21.88	19.42	41.30	66.00	-24.70	QP
2	0.1500	5.71	19.42	25.13	56.00	-30.87	AVG
3	0.3740	16.09	19.36	35.45	58.41	-22.96	QP
4	0.3740	8.59	19.36	27.95	48.41	-20.46	AVG
5	0.5620	21.57	19.36	40.93	56.00	-15.07	QP
6	0.5620	14.83	19.36	34.19	46.00	-11.81	AVG
7	1.1220	13.36	19.39	32.75	56.00	-23.25	QP
8	1.1220	5.27	19.39	24.66	46.00	-21.34	AVG
9	1.4980	15.47	19.39	34.86	56.00	-21.14	QP
10	1.4980	4.89	19.39	24.28	46.00	-21.72	AVG
11	1.7100	14.75	19.38	34.13	56.00	-21.87	QP
12	1.7100	4.30	19.38	23.68	46.00	-22.32	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			



For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2310 to 2430 MHz Upper Band Edge: 2445 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)



Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE


- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested with a band-stop filter and performed pretest to three orthogonal axis. The worst-case emissions were reported.

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

Please refer to section 3.1.4 of this report.



3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$




3.2.6 TEST RESULT

(Between 9KHz – 30 MHz)

Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 14.4V	Polarization:	--
Test Mode:	Mode 1/2/3/4/5/6/7/8/9 (Mode 9 worst mode)		

9K-150K


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0106	18.36	19.42	37.78	127.10	-89.32	peak
2	0.0182	18.28	19.97	38.25	122.40	-84.15	peak
3	0.0252	18.03	20.00	38.03	119.58	-81.55	peak
4	0.0434	18.11	19.63	37.74	114.85	-77.11	peak
5	0.0782	18.25	18.65	36.90	109.74	-72.84	peak
6	0.1107	20.39	17.58	37.97	106.72	-68.75	peak





150K-30M

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5210	9.63	20.21	29.84	73.27	-43.43	peak
2	1.3141	9.88	20.26	30.14	65.23	-35.09	peak
3	3.0253	11.46	20.11	31.57	69.50	-37.93	peak
4	6.3887	10.90	20.42	31.32	69.50	-38.18	peak
5	10.3886	11.88	20.29	32.17	69.50	-37.33	peak
6	16.1794	10.04	21.58	31.62	69.50	-37.88	peak



Note:

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.




(30MHz - 1000MHz)

Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 14.4V	Phase:	Horizontal
Test Mode:	Mode 1/2/3/4/5/6/7/8/9 (Mode 9 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	71.7100	59.13	-24.56	34.57	40.00	-5.43	peak
2	95.9600	59.78	-20.67	39.11	43.50	-4.39	peak
3	119.2400	54.94	-18.38	36.56	43.50	-6.94	peak
4	239.5200	55.19	-18.10	37.09	46.00	-8.91	peak
5	304.5100	47.18	-14.65	32.53	46.00	-13.47	peak
6	970.9000	34.10	2.06	36.16	54.00	-17.84	peak

Remark:

1. Margin = Result (Result = Reading + Factor) – Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) - Amplifier gain
3. All modes have been tested, only show the worst case.






Temperature:	23.4°C	Relative Humidity:	60%
Test Voltage:	DC 14.4V	Phase:	Vertical
Test Mode:	Mode 1/2/3/4/5/6/7/8/9 (Mode 9 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.9700	43.71	-13.35	30.36	40.00	-9.64	peak
2	71.7100	61.05	-24.56	36.49	40.00	-3.51	peak
3	94.9900	58.80	-20.78	38.02	43.50	-5.48	peak
4	119.2400	55.54	-18.38	37.16	43.50	-6.34	peak
5	240.4900	49.93	-17.93	32.00	46.00	-14.00	peak
6	980.6000	31.21	2.63	33.84	54.00	-20.16	peak

Remark:.

1. Margin = Result (Result =Reading + Factor)–Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.





(1000MHz-25GHz) Spurious emission Requirements


Low Channel (802.11n20/2412 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1495.50	48.59	-1.05	74	-25.41	Peak	148.7	Horizontal	Pass
1495.50	34.56	-1.05	54	-19.44	AV	148.7	Horizontal	Pass
2492.50	49.65	3.16	74	-24.35	Peak	94.1	Horizontal	Pass
2492.50	37.80	3.16	54	-16.20	AV	94.1	Horizontal	Pass
9494.25	52.16	1.51	74	-21.84	Peak	152.1	Horizontal	Pass
9494.25	41.36	1.51	54	-12.64	AV	152.1	Horizontal	Pass
12431.25	53.49	2.86	74	-20.51	Peak	8.4	Horizontal	Pass
12431.25	42.37	2.86	54	-11.63	AV	8.4	Horizontal	Pass
14400.25	56.70	6.99	74	-17.30	Peak	347.2	Horizontal	Pass
14400.25	46.36	6.99	54	-7.64	AV	347.2	Horizontal	Pass
17928.50	55.88	7.02	74	-18.12	Peak	0.2	Horizontal	Pass
17928.50	44.99	7.02	54	-9.01	AV	0.2	Horizontal	Pass
Middle Channel (802.11n20/2437 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1495.22	47.06	-1.12	74.00	-26.94	Peak	138.87	Horizontal	Pass
1495.22	33.59	-1.12	54.00	-20.41	AV	138.87	Horizontal	Pass
2492.25	49.00	3.14	74.00	-25.00	Peak	87.19	Horizontal	Pass
2492.25	36.70	3.14	54.00	-17.30	AV	87.19	Horizontal	Pass
9493.99	50.75	1.46	74.00	-23.25	Peak	148.51	Horizontal	Pass
9493.99	40.72	1.46	54.00	-13.28	AV	148.51	Horizontal	Pass
12430.95	52.96	2.83	74.00	-21.04	Peak	9.23	Horizontal	Pass
12430.95	41.59	2.83	54.00	-12.41	AV	9.23	Horizontal	Pass
14399.77	54.84	6.96	74.00	-19.16	Peak	343.47	Horizontal	Pass
14399.77	45.74	6.96	54.00	-8.26	AV	343.47	Horizontal	Pass
17928.09	55.26	6.98	74.00	-18.74	Peak	6.12	Horizontal	Pass
17928.09	44.18	6.98	54.00	-9.82	AV	6.12	Horizontal	Pass



High Channel (802.11n20/2462 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1495.00	45.95	-1.19	74.00	-28.05	Peak	137.25	Horizontal	Pass
1495.00	32.39	-1.19	54.00	-21.61	AV	137.25	Horizontal	Pass
2491.82	48.13	3.10	74.00	-25.87	Peak	86.20	Horizontal	Pass
2491.82	35.80	3.10	54.00	-18.20	AV	86.20	Horizontal	Pass
9493.63	49.19	1.42	74.00	-24.81	Peak	143.44	Horizontal	Pass
9493.63	40.13	1.42	54.00	-13.87	AV	143.44	Horizontal	Pass
12430.68	51.49	2.78	74.00	-22.51	Peak	7.73	Horizontal	Pass
12430.68	40.77	2.78	54.00	-13.23	AV	7.73	Horizontal	Pass
14399.31	53.09	6.94	74.00	-20.91	Peak	341.08	Horizontal	Pass
14399.31	44.82	6.94	54.00	-9.18	AV	341.08	Horizontal	Pass
17927.59	54.40	6.96	74.00	-19.60	Peak	5.83	Horizontal	Pass
17927.59	42.35	6.96	54.00	-11.65	AV	5.83	Horizontal	Pass


1GHz-18GHz-H-High Channel

RE_FCC Test Case_FCC 15C 1GHz-18GHz - 2.4G





18GHz-26GHz-H-High Channel



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19048.000	50.26	1.72	51.98	54.00	-2.02	peak
2	20184.000	50.31	1.96	52.27	54.00	-1.73	peak
3	21000.000	49.31	2.66	51.97	54.00	-2.03	peak
4	22032.000	49.06	3.45	52.51	54.00	-1.49	peak
5	23304.000	48.21	3.93	52.14	54.00	-1.86	peak
6	25144.000	46.78	5.41	52.19	54.00	-1.81	peak




Low Channel (802.11n20/2412 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1493.50	49.96	-1.06	74	-24.04	Peak	94.7	Vertical	Pass
1493.50	35.11	-1.06	54	-18.89	AV	94.7	Vertical	Pass
2882.50	47.81	4.93	74	-26.19	Peak	355.1	Vertical	Pass
2882.50	35.90	4.93	54	-18.10	AV	355.1	Vertical	Pass
9992.00	51.82	1.15	74	-22.18	Peak	330.6	Vertical	Pass
9992.00	41.42	1.15	54	-12.58	AV	330.6	Vertical	Pass
11435.75	53.52	1.96	74	-20.48	Peak	164.3	Vertical	Pass
11435.75	41.19	1.96	54	-12.81	AV	164.3	Vertical	Pass
13974.00	57.00	8.12	74	-17.00	Peak	42.3	Vertical	Pass
13974.00	45.80	8.12	54	-8.20	AV	42.3	Vertical	Pass
17774.50	55.30	6.27	74	-18.70	Peak	5.2	Vertical	Pass
17774.50	44.79	6.27	54	-9.21	AV	5.2	Vertical	Pass
Middle Channel (802.11n20/2437 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1493.16	49.03	-1.13	74.00	-24.97	Peak	92.43	Vertical	Pass
1493.16	33.43	-1.13	54.00	-20.57	AV	92.43	Vertical	Pass
2882.26	46.74	4.90	74.00	-27.26	Peak	348.98	Vertical	Pass
2882.26	34.27	4.90	54.00	-19.73	AV	348.98	Vertical	Pass
9991.64	50.37	1.12	74.00	-23.63	Peak	325.35	Vertical	Pass
9991.64	39.89	1.12	54.00	-14.11	AV	325.35	Vertical	Pass
11435.44	52.97	1.93	74.00	-21.03	Peak	156.46	Vertical	Pass
11435.44	40.47	1.93	54.00	-13.53	AV	156.46	Vertical	Pass
13973.53	55.70	8.08	74.00	-18.30	Peak	36.81	Vertical	Pass
13973.53	44.55	8.08	54.00	-9.45	AV	36.81	Vertical	Pass
17774.02	53.93	6.24	74.00	-20.07	Peak	6.38	Vertical	Pass
17774.02	43.79	6.24	54.00	-10.21	AV	6.38	Vertical	Pass



High Channel (802.11n20/2462 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1492.73	47.16	-1.21	74.00	-26.84	Peak	84.76	Vertical	Pass
1492.73	32.45	-1.21	54.00	-21.55	AV	84.76	Vertical	Pass
2881.91	45.98	4.88	74.00	-28.02	Peak	343.75	Vertical	Pass
2881.91	33.63	4.88	54.00	-20.37	AV	343.75	Vertical	Pass
9991.32	48.38	1.08	74.00	-25.62	Peak	317.45	Vertical	Pass
9991.32	38.00	1.08	54.00	-16.00	AV	317.45	Vertical	Pass
11435.02	51.72	1.91	74.00	-22.28	Peak	151.76	Vertical	Pass
11435.02	39.66	1.91	54.00	-14.34	AV	151.76	Vertical	Pass
13973.09	55.02	8.03	74.00	-18.98	Peak	34.95	Vertical	Pass
13973.09	42.74	8.03	54.00	-11.26	AV	34.95	Vertical	Pass
17773.72	53.03	6.21	74.00	-20.97	Peak	7.76	Vertical	Pass
17773.72	41.90	6.21	54.00	-12.10	AV	7.76	Vertical	Pass


1GHz-18GHz-V-High Channel

RE_FCC Test Case_FCC 15C 1GHz-18GHz - 2.4G





18GHz-26GHz-V-High Channel



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18936.000	50.78	1.81	52.59	54.00	-21.41	peak
2	20752.000	49.55	2.44	51.99	54.00	-22.01	peak
3	22056.000	48.34	3.47	51.81	54.00	-22.19	peak
4	23032.000	48.33	3.67	52.00	54.00	-22.00	peak
5	24280.000	47.22	4.68	51.90	54.00	-22.10	peak
6	25152.000	46.50	5.41	51.91	54.00	-22.09	peak

Remark:


- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- All modes have been measured, only worst mode was reported.
Emission Level = Reading + Factor
Margin = Emission Level-Limit
- The frequency above 18GHz emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



3.2.6 TEST RESULTS(Band edge Requirements)


802.11 n20-Low

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.200	58.01	0.80	58.81	74.00	-15.19	peak
2	2389.200	37.31	0.80	38.11	54.00	-15.89	AVG
3	2390.000	59.82	0.81	60.63	74.00	-13.37	peak
4	2390.000	38.19	0.81	39.00	54.00	-15.00	AVG

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.960	47.12	0.80	47.92	54.00	-6.08	peak
2	2390.000	50.66	0.81	51.47	54.00	-2.53	peak




802.11 n20-High

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	60.62	1.02	61.64	74.00	-12.36	peak
2	2483.500	40.56	1.02	41.58	54.00	-12.42	AVG
3	2484.900	58.94	1.03	59.97	74.00	-14.03	peak
4	2484.900	38.64	1.03	39.67	54.00	-14.33	AVG

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	55.82	1.02	56.84	74.00	-17.16	peak
2	2483.500	36.13	1.02	37.15	54.00	-16.85	AVG
3	2484.690	54.93	1.03	55.96	74.00	-18.04	peak
4	2484.690	34.90	1.03	35.93	54.00	-18.07	AVG

Note: All modes have been measured, only worst mode was reported.



4. DUTY CYCLE

4.1 TEST STANDARD

Please refer to ANSI C63.10-2020 Section 11.6

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Zero
RB	set RBW to the largest available value
VB	$VBW \geq RBW$.
Detector	Peak
Trace	Clear Write
Sweep Time	Auto

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



5. CONDUCTED SPURIOUS & BAND EDGE EMISSION

5.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

5.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

5.6 TEST RESULTS

Note:

1. The test data please refer to APPENDIX 1.



6. POWER SPECTRAL DENSITY TEST

6.1 LIMIT

FCC Part15.247 , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤ 8 dBm (RBW ≥ 3 KHz)	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the $100\text{ kHz} \geq \text{RBW} \geq 3\text{ kHz}$.
4. Set the $\text{VBW} \geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

6.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



7. BANDWIDTH TEST

7.1 LIMIT

FCC Part15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 1% to 5% of the OBW but not less than 100 kHz., VBW $\geq$ 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

7.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



8. PEAK OUTPUT POWER TEST

7.1 LIMIT

FCC Part15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE


PKPM1 Peak power meter method:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

8.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT


15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


9.2 EUT ANTENNA


The EUT antenna is PCB Antenna. It comply with the standard requirement.


**APPENDIX 1-TEST DATA****Duty Cycle**


Condition	Mode	Frequency (MHz)	On Time (ms)	Period (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	12.42	12.545	99	0.04	0.08
NVNT	b	2437	12.42	12.55	98.96	0.05	0.08
NVNT	b	2462	12.415	12.545	98.96	0.05	0.08
NVNT	g	2412	2.066	2.196	94.08	0.27	0.48
NVNT	g	2437	2.064	2.194	94.07	0.27	0.48
NVNT	g	2462	2.064	2.194	94.07	0.27	0.48
NVNT	n20	2412	1.922	2.05	93.76	0.28	0.52
NVNT	n20	2437	1.92	2.05	93.66	0.28	0.52
NVNT	n20	2462	1.92	2.05	93.66	0.28	0.52















Maximum Peak Conducted Output Power


Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	19.14	≤ 30	Pass
NVNT	b	2437	19.58	≤ 30	Pass
NVNT	b	2462	19.87	≤ 30	Pass
NVNT	g	2412	19.01	≤ 30	Pass
NVNT	g	2437	19.98	≤ 30	Pass
NVNT	g	2462	19.83	≤ 30	Pass
NVNT	n20	2412	20.73	≤ 30	Pass
NVNT	n20	2437	20.69	≤ 30	Pass
NVNT	n20	2462	20.95	≤ 30	Pass


**-6dB Bandwidth**


Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	9.118	≥ 0.5	Pass
NVNT	b	2437	9.118	≥ 0.5	Pass
NVNT	b	2462	9.117	≥ 0.5	Pass
NVNT	g	2412	16.4	≥ 0.5	Pass
NVNT	g	2437	16.35	≥ 0.5	Pass
NVNT	g	2462	16.37	≥ 0.5	Pass
NVNT	n20	2412	17.6	≥ 0.5	Pass
NVNT	n20	2437	17.57	≥ 0.5	Pass
NVNT	n20	2462	17.6	≥ 0.5	Pass

















Maximum Power Spectral Density Level


Condition	Mode	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	-8.59	<=8	Pass
NVNT	b	2437	-7.83	<=8	Pass
NVNT	b	2462	-7.77	<=8	Pass
NVNT	g	2412	-11.96	<=8	Pass
NVNT	g	2437	-10.92	<=8	Pass
NVNT	g	2462	-11.01	<=8	Pass
NVNT	n20	2412	-10.76	<=8	Pass
NVNT	n20	2437	-9.52	<=8	Pass
NVNT	n20	2462	-10.36	<=8	Pass

















Band Edge


Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	-51.61	≤ -20	Pass
NVNT	b	2462	-59.75	≤ -20	Pass
NVNT	g	2412	-34.52	≤ -20	Pass
NVNT	g	2462	-50.9	≤ -20	Pass
NVNT	n20	2412	-35.5	≤ -20	Pass
NVNT	n20	2462	-50.65	≤ -20	Pass




















Conducted RF Spurious Emission


Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	-44.95	<=-20	Pass
NVNT	b	2437	-46.09	<=-20	Pass
NVNT	b	2462	-46.35	<=-20	Pass
NVNT	g	2412	-40.57	<=-20	Pass
NVNT	g	2437	-41.85	<=-20	Pass
NVNT	g	2462	-42.25	<=-20	Pass
NVNT	n20	2412	-42.87	<=-20	Pass
NVNT	n20	2437	-43.21	<=-20	Pass
NVNT	n20	2462	-42.69	<=-20	Pass

























APPENDIX 2-PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※