

EUT Specification

FCC ID: 2BD9Y-2400

Characteristics	Description
Product Name	Portable Power Station
Model number	2400, 2000
Brand	
Power Supply	AC 120V/60Hz / DC 150V / Battery 51.2V
Operating Frequency Range	110-205KHz
Modulation Technique	FSK
Antenna Type	Coil Antenna
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others ____
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Applicable Standard:

FCC Part 1(1.1310) ,Part 2(2.1091) and KDB 680106 D01 RF Exposure
Wireless Charging Apps v03

Applicable Requirement:

Three different categories of transmitters are defined by the FCC in OET Bulletin 65.

These categories are fixed installation, mobile, and portable and are

defined as follows:

Fixed Installations: fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.

Mobile Devices: a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.

Portable Devices: a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure.

These two categories are defined as follows:

Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure. The phrase fully aware in the context of applying these exposure limits means that an exposed person has received written and/or verbal information fully explaining the potential for RF exposure resulting from his or her employment. With the exception of transient persons, this phrase also means that an exposed person has received appropriate training regarding work practices relating to controlling or mitigating his or her exposure. Such training is not required for transient persons, but they must receive written and/or verbal information and notification (for example, using signs) concerning their exposure potential and appropriate means available to mitigate their exposure. The phrase exercise control means that an exposed person is allowed to and knows how to reduce or avoid exposure by administrative or engineering controls and work practices, such as use of personal protective equipment or time averaging of exposure.


General population/uncontrolled exposure limits apply in situations in


which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Licensees and applicants are responsible for compliance with both the occupational/controlled exposure limits and the general population/uncontrolled exposure limits as they apply to transmitters under their jurisdiction. Licensees and applicants should be aware that the occupational/controlled exposure limits apply especially in situations where workers may have access to areas in very close proximity to antennas and access to the general public may be restricted.

In lieu of evaluation with the general population/uncontrolled exposure limits, amateur licensees authorized under part 97 of this chapter and members of his or her immediate household may be evaluated with respect to the occupational/controlled exposure limits in this section, provided appropriate training and information has been provided to the amateur licensee and members of his/her household. Other nearby persons who are not members of the amateur licensee's household must be evaluated with respect to the general population/uncontrolled exposure limits.

Test Setup Block





Test Procedure

1. Connect the EUT and equipment as above diagram of test configuration.
2. EUT was placed on a table, and the measure probe was placed at a measurement distance of 15cm from the EUT to the center of the probe.
3. Power on the measuring probe, the EUT was set at the maximum field strength emission state.
4. The EUT was put in different directions (Left, Right, Front, Rear, Top and Bottom) toward to the measure probe. The distance from the top of the EUT to the probe is 20CM, and the distance from other directions is 15cm. Measure the value of field strength.
5. Record the worst data of the different directions.

Measuring Device And Test Equipment

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
☒	E&H-Field Probe(9kHz-30M Hz)	Narda	EHP-200A	180ZX11012	2023/09/18	2024/09/17

Description of Support Device

Phone : Manufacturer: Apple Inc.
M/N: A2176
S/N: N/A

SAMSUNG S9 : Manufacturer: SAMSUNG
M/N: Galaxy Note 10
S/N: N/A

Xiaomi 9 : Manufacturer: Xiaomi
M/N: Xiaomi 10
S/N: N/A

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

Note: f denotes for frequency in MHz.

* denotes for plane-wave equivalent power density.

Measurement Result

We tested three modes (15W load, 10W load, 5W load) for EUT. test data see the following.

Magnetic Field (H-Field) strength at 15cm from the boundaries of EUT, and 20cm from the top.

Test Mode: Wireless Charging 15W						
		Measuring Distance(cm)	H-Field(A/m)	50% H-Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	15	0.0917	0.0459	1.63	0.815
Measurement Point 2	Back	15	0.0921	0.0461		
Measurement Point 3	Left	15	0.0928	0.0462		
Measurement Point 4	Right	15	0.0913	0.0457		
Measurement Point 5	Bottom	15	0.0927	0.0464		
Measurement Point 6	Top	20	0.0935	0.0468		

Test Mode: Wireless Charging 15W						
		Measuring Distance(cm)	E-Field(V/m)	50% E-Field(V/m)	Limit(V/m)	50% Limit(V/m)
Measurement Point 1	Front	15	2.3274	1.1638	614	307
Measurement Point 2	Back	15	2.2586	1.1292		
Measurement Point 3	Left	15	2.2721	1.1361		
Measurement Point 4	Right	15	2.2653	1.1327		
Measurement Point 5	Bottom	15	2.2925	1.1463		
Measurement Point 6	Top	20	2.3016	1.1505		

Test Mode: Wireless Charging 10W						
		Measuring Distance(cm)	H-Field(A/m)	50% H-Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	15	0.0842	0.0423	1.63	0.815
Measurement Point 2	Back	15	0.0831	0.0414		
Measurement Point 3	Left	15	0.0907	0.0456		
Measurement Point 4	Right	15	0.0817	0.0408		
Measurement Point 5	Bottom	15	0.0966	0.0482		
Measurement Point 6	Top	20	0.0928	0.0465		

Test Mode: Wireless Charging 10W						
		Measuring Distance(cm)	E-Field(V/m)	50% E-Field(V/m)	Limit(V/m)	50% Limit(V/m)
Measurement Point 1	Front	15	1.5052	0.7523	614	307
Measurement Point 2	Back	15	1.5261	0.7633		
Measurement Point 3	Left	15	1.3013	0.6505		
Measurement Point 4	Right	15	1.2912	0.6457		
Measurement Point 5	Bottom	15	1.5799	0.7901		
Measurement Point 6	Top	20	1.7836	0.8917		

Test Mode: Wireless Charging 5W						
		Measuring Distance(cm)	H-Field(A/m)	50% H-Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	15	0.0643	0.0321	1.63	0.815
Measurement Point 2	Back	15	0.0621	0.0312		
Measurement Point 3	Left	15	0.0702	0.0352		
Measurement Point 4	Right	15	0.0649	0.0326		
Measurement Point 5	Bottom	15	0.0791	0.0396		
Measurement Point 6	Top	20	0.0739	0.0371		

Test Mode: Wireless Charging 5W						
		Measuring Distance(cm)	E-Field(V/m)	50% E-Field(V/m)	Limit(V/m)	50% Limit(V/m)
Measurement Point 1	Front	15	1.1796	0.5897	614	307
Measurement Point 2	Back	15	1.3327	0.6665		
Measurement Point 3	Left	15	1.2708	0.6354		
Measurement Point 4	Right	15	1.3027	0.6515		
Measurement Point 5	Bottom	15	1.3964	0.6982		
Measurement Point 6	Top	20	1.4660	0.7329		

PHOTOGRAPHS OF TEST SETUP



Signature

Tiger Xu

Tiger Xu
Laboratory Supervisor

Date: 2024-04-23

