TCT 通测检测
TESTING CENTRE TECHNOLOGY

TEST REPORT

FCC ID.....:	2BDBH-VT018
Test Report No..... :	TCT231024E008
Date of issue..... :	Oct. 27, 2023
Testing laboratory ..... :	SHENZHEN TONGCE TESTING LAB
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
Applicant's name..... :	Shenzhen Bagus Technology Co., Ltd
Address..... :	207, Building 2, Baili Mingyuan, Juling New Village, Jutang Community, Fucheng Street, Longhua District, Shenzhen, 518100 China
Manufacturer's name ... :	Shenzhen Bagus Technology Co., Ltd
Address..... :	207, Building 2, Baili Mingyuan, Juling New Village, Jutang Community, Fucheng Street, Longhua District, Shenzhen, 518100 China
Standard(s) ..... :	FCC CFR Title 47 Part 1.1310 KDB 680106 D01 RF Exposure Wireless Charging App v03r01
Product Name..... :	Wireless charging
Trade Mark ..... :	WeeFancy
Model/Type reference..... :	VT018
Rating(s)..... :	Type-C Input: DC 5V, 1.0A Rechargeable Li-ion Battery DC 3.85V
Date of receipt of test item ..... :	Oct. 24, 2023
Date (s) of performance of test..... :	Oct. 24, 2023 ~ Oct. 27, 2023
Tested by (+signature) ... :	Rleo LIU
Check by (+signature).... :	Beryl ZHAO
Approved by (+signature):	Tomsin

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information 3
1.1. EUT description 3
1.2. Model(s) list 3
2. General Information 4
2.1. Test environment and mode 4
3. Facilities and Accreditations 5
3.1. Facilities 5
3.2. Location 5
4. Technical Requirements Specification 6
4.1. Requirements 6
4.2. Test Setup 7
4.3. Test Procedure 8
4.4. Test Instruments List 8
4.5. Test Result 9
4.6. Test Set-up Photo 13

1. General Product Information

1.1. EUT description

Product Name.....:	Wireless charging
Model/Type reference.....:	VT018
Sample Number.....:	TCT231024E007-0101
Operation Frequency .....:	323.60KHz
Output power……...:	2.5W
Modulation Technology .....:	Load modulation
Antenna Type.....:	Inductive loop coil Antenna
Rating(s).....:	Type-C Input: DC 5V, 1.0A Rechargeable Li-ion Battery DC 3.85V

1.2. Model(s) list

None.

2. General Information

2.1. Test environment and mode

Operating Environment:		
Condition	Conducted Emission	Radiated Emission
Temperature:	23.5 °C	24.4 °C
Humidity:	52 % RH	51 % RH
Atmospheric Pressure:	1010 mbar	1010 mbar
Test Mode:		
AC mode	AC/DC adapter + EUT + Watch (battery status>95%)	
	AC/DC adapter + EUT + Watch (battery status<50%)	
	AC/DC adapter + EUT + Watch (battery status<1%)	
Internal Battery Mode	EUT + Watch (battery status>95%)	
	EUT + Watch (battery status<50%)	
	EUT + Watch (battery status<1%)	
The sample was placed 0.8m for the measurement below 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case(Z axis) are shown in Test Results of the following pages.		

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098
  SHENZHEN TONGCE TESTING LAB
  Designation Number: CN1205
  The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.
- IC - Registration No.: 10668A-1
  SHENZHEN TONGCE TESTING LAB
  CAB identifier: CN0031
  The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

3.2. Location

SHENZHEN TONGCE TESTING LAB
Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
TEL: +86-755-27673339

4. Technical Requirements Specification

4.1. Requirements

According to the item 5 of KDB 680106 D01 RF Exposure Wireless Charging App v03r01:

(1) Power transfer frequency is less than 1 MHz.
Wireless power transfer operation frequency is 323.60K.

(2) Output power from each primary coil is less than or equal to 15 watts.
The output power is 2.5W

(3) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.
Device only capable of wireless power transfer between one sourse and one client at a time, only allow wireless power transfer to take place through a single pair of coils at any given time, and it use one overlapping smaller coil in a charging zone.

(4) Client device is placed directly in contact with the transmitter.
Direct contact

(5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
No

(6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
Yes

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm^2)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f^2)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f^2)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
*=Plane-wave equivalent power density
RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

4.2. Test Setup

A:



B:



4.3. Test Procedure

1) The RF exposure test was performed in an echoic chamber;

2) The measurement probe was placed at test distance (15 cm from edges, 20 cm and 15cm from top) Which is between the edge of the charger and the geometric center of probe, for test setup A;

3) In addition to what is described in KDB 680106 D01, please measure and provide magnetic and electrical field strength at a distance 0cm to 20cm at 2cm iteration, i.e. at a distance of 0cm, 2cm, 4cm, ……. 20cm. Which is between the edge of the charger and the edge of of probe, for test setup B;

4) The highest emission leve laws recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed;

5) The EUT was measured according to the dictates of KDB680106D01v03; And KDB Tracking Number 671578; TCB Workshop, October 2018, 5.2 RF Exposure Procedures

Remark: The EUT' s test position A, B, C, D and E is valid for the E and H field measurements.

4.4. Test Instruments List

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due
Electric and Magnetic Field Analyzer	Narda	EHP-200A	180ZX20511	Jul. 04, 2024
Adapter	jinhu	WC065A11JH	J121083BA1003016	/
Apple Watch	Apple	Apple Watch A1757	/	/

4.5. Test Result

Note: EUT mode: wireless output 2.5 W

Test Result for Test setup A:

Note： Internal battery power mode

E-Filed Strength at (15 cm from edges A, B, C, D, 20 cm and 15cm from top E) surrounding the EUT (V/m)

Charging Load Worse case	Test Position A (V/m)	Test Position B (V/m)	Test Position C (V/m)	Test Position D (V/m)	Test Position E (V/m)20cm	Test Position E (V/m)15cm	Limits (V/m)
<1%	1.53	1.68	1.72	1.80	1.59	1.68	614
50%	1.36	1.64	1.66	1.75	1.56	1.65	614
>95%	1.31	1.49	1.57	1.54	1.52	1.61	614

H-Filed Strength at (15 cm from edges A, B, C, D, 20 cm and 15cm from top E) surrounding the EUT (A/m)

Charging Load Worse case	Test Position A (A/m)	Test Position B (A/m)	Test Position C (A/m)	Test Position D (A/m)	Test Position E (A/m)20cm	Test Position E (A/m)15cm	Limits (A/m)
<1%	0.202	0.196	0.201	0.205	0.191	0.195	1.63
50%	0.195	0.194	0.198	0.197	0.188	0.186	1.63
>95%	0.191	0.188	0.192	0.191	0.182	0.183	1.63

Note: AC power in mode

E-Filed Strength at (15 cm from edges A, B, C, D, 20 cm and 15cm from top E) surrounding the EUT (V/m)

Charging Load Worse case	Test Position A (V/m)	Test Position B (V/m)	Test Position C (V/m)	Test Position D (V/m)	Test Position E (V/m)20cm	Test Position E (V/m)15cm	Limits (V/m)
<1%	1.51	1.68	1.62	1.78	1.51	1.70	614
50%	1.37	1.62	1.54	1.69	1.47	1.67	614
>95%	1.32	1.39	1.51	1.58	1.42	1.61	614

H-Filed Strength at (15 cm from edges A, B, C, D, 20 cm and 15cm from top E) surrounding the EUT (A/m)

Charging Load Worse case	Test Position A(A/m)	Test Position B(A/m)	Test Position C(A/m)	Test Position D(A/m)	Test Position E(A/m)20cm	Test Position E(A/m)15cm	Limits (A/m)
<1%	0.205	0.191	0.199	0.197	0.192	0.203	1.63
50%	0.198	0.185	0.196	0.194	0.187	0.194	1.63
>95%	0.192	0.176	0.192	0.190	0.185	0.191	1.63

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

Test Result for Test setup B:

Note: internal battery power mode is worse case， and only worse case is reported.

<1%, 50%, >95% load all have been tested, only worse case Max load (<1%) is reported.

E-Filed Strength at (distance 0cm to 20cm at 2cm iteration, i.e. at a distance of 20cm, 18cm, 16cm, ……. 0cm, Which is between the edge of the charger and the edge of of probe,) surrounding the EUT (V/m)

Test distance (cm)	Test Position A(V/m)	Test Position B(V/m)	Test Position C(V/m)	Test Position D(V/m)	Test Position E(V/m)	Limits (V/m)
0	2.51	2.59	2.58	2.65	2.38	614
2	2.47	2.56	2.47	2.61	2.33	614
4	2.25	2.37	2.35	2.35	2.28	614
6	2.18	2.35	2.28	2.30	2.22	614
8	2.12	2.33	2.24	2.22	2.17	614
10	2.04	2.16	2.08	2.19	2.05	614
12	1.99	2.14	2.05	2.16	1.98	614
14	1.96	2.10	2.02	2.11	1.95	614
16	1.95	2.02	1.96	2.08	1.91	614
18	1.91	1.98	1.88	2.04	1.87	614
20	1.89	1.95	1.84	2.01	1.85	614

H-Filed Strength at (distance 0cm to 20cm at 2cm iteration, i.e. at a distance of 20cm, 18cm, 16cm, ……. 0cm, Which is between the edge of the charger and the edge of of probe,) surrounding the EUT (A/m)

Test distance (cm)	Test Position A(A/m)	Test Position B(A/m)	Test Position C(A/m)	Test Position D(A/m)	Test Position E(A/m)	Limits (A/m)
0	0.378	0.357	0.345	0.348	0.356	1.63
2	0.371	0.354	0.343	0.341	0.350	1.63
4	0.342	0.317	0.319	0.308	0.307	1.63
6	0.305	0.293	0.295	0.287	0.281	1.63
8	0.283	0.262	0.266	0.255	0.265	1.63
10	0.266	0.241	0.251	0.244	0.243	1.63
12	0.257	0.235	0.247	0.238	0.238	1.63
14	0.249	0.229	0.236	0.227	0.224	1.63
16	0.224	0.218	0.228	0.216	0.221	1.63
18	0.218	0.217	0.212	0.211	0.218	1.63
20	0.212	0.213	0.210	0.209	0.215	1.63

4.6. Test Set-up Photo

AC in mode









Internal battery mode





Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com





********END OF REPORT********