

TEST REPORT

Reference No...... : WTX26X04115694W001
FCC ID..... : 2BDC6-PILL
Applicant..... : Shelly Europe Ltd.
Address..... : 51 Cherni Vrah Blvd., bldg.3,fl.2-3,Sofia 1407,Bulgaria
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : The Pill by Shelly
Model No...... : S3SN-0U53X
Standards..... : FCC Part 15.247
Date of Receipt sample..... : 2026-04-29
Date of Test..... : 2026-04-29 to 2026-05-11
Date of Issue..... : 2026-05-29
Test Report Form No...... : WTX_Part 15_247W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,

Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Approved by:

Tris Li

Silin Chen

Tris Li/Project Engineer

Silin Chen/Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	12
3. ANTENNA REQUIREMENT	13
3.1 STANDARD APPLICABLE	13
3.2 EVALUATION INFORMATION	13
4. POWER SPECTRAL DENSITY	14
4.1 STANDARD APPLICABLE	14
4.2 TEST SETUP BLOCK DIAGRAM	14
4.3 TEST PROCEDURE	14
4.4 SUMMARY OF TEST RESULTS/PLOTS	14
5. DTS BANDWIDTH	15
5.1 STANDARD APPLICABLE	15
5.2 TEST SETUP BLOCK DIAGRAM	15
5.3 TEST PROCEDURE	15
5.4 SUMMARY OF TEST RESULTS/PLOTS	15
6. RF OUTPUT POWER	16
6.1 STANDARD APPLICABLE	16
6.2 TEST SETUP BLOCK DIAGRAM	16
6.3 TEST PROCEDURE	16
6.4 SUMMARY OF TEST RESULTS/PLOTS	16
7. FIELD STRENGTH OF SPURIOUS EMISSIONS	17
7.1 STANDARD APPLICABLE	17
7.2 TEST PROCEDURE	17
7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	19
7.4 SUMMARY OF TEST RESULTS/PLOTS	19
8. OUT OF BAND EMISSIONS	28
8.1 STANDARD APPLICABLE	28
8.2 TEST PROCEDURE	28
8.3 SUMMARY OF TEST RESULTS/PLOTS	29
9. CONDUCTED EMISSIONS	38
9.1 TEST PROCEDURE	38
9.2 BASIC TEST SETUP BLOCK DIAGRAM	38
9.3 TEST RECEIVER SETUP	38
9.4 SUMMARY OF TEST RESULTS/PLOTS	38
APPENDIX SUMMARY	41
APPENDIX A	42
APPENDIX B	47
APPENDIX C	52
APPENDIX D	57
APPENDIX PHOTOGRAPHS	65

Report version

Version No.	Date of issue	Description
Rev.00	2026-05-29	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	The Pill by Shelly
Trade Name:	
Model No.:	S3SN-0U53X
Adding Model(s):	/
Rated Voltage:	DC 5V
Power Adapter Model:	/
<i>Note: The sample information is provided by the customer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power:	15.37dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation:	5MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	1.56dBi
<i>Note: 1: The Antenna Gain is provided by the customer and can affect the validity of results.</i>	
<i>2: The data provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the FCC rules.

ANSI C63.10-2020: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM4	802.11n-HT40	Low:2422MHz, Middle:2437MHz,High:2452MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~75 %
ATM Pressure:	1021 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Temperature sensing line	0.95	Unshielded	Without Ferrite
AUX splitter	0.45	Unshielded	Without Ferrite
micro Prot to AUX Prot Cable	0.23	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC Cable	1	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Adapter	XIAOMI	MDY-11-EX	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.57\text{dB}$
Occupied Bandwidth	Conducted	$\pm 0.015\text{MHz}$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emission 1#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Conducted Emission 2#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Transmitter Spurious Emissions chamber A	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.70\text{dB}$
		@1GHz to 6GHz: $\pm 5.88\text{dB}$
		@6GHz to 18GHz: $\pm 5.96\text{dB}$
		@18GHz to 40GHz: $\pm 6.12\text{dB}$
Transmitter Spurious Emissions chamber B	Radiated	@30MHz to 1GHz: $\pm 5.36\text{dB}$
Transmitter Spurious Emissions chamber C	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.28\text{dB}$
		@1GHz to 6GHz: $\pm 5.56\text{dB}$
		@6GHz to 18GHz: $\pm 5.72\text{dB}$
		@18GHz to 40GHz: $\pm 6.12\text{dB}$

1.7 Test Equipment List and Details

Internal No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1002	Communication Tester	Rohde & Schwarz	CMW500	1201.0002 k50-14865 0-FB	2026-03-25	2027-03-24
WTXE1005A 1005	MXA Signal Analyzer	Agilent	N9020A	US471401 02	2026-03-25	2027-03-24
WTXE1084A 1001	MXA Signal Analyzer	KEYSIGHT	N9020A	MY543205 48	2026-02-06	2027-02-05
WTXE1005A 1006	Spectrum Analyzer	Rohde & Schwarz	FSP40	1164.4391 K38Ser.10 0368	2026-04-29	2027-04-28
WTXW1105A 1136	RF ATTENUATOR	FEIYANG	N-JK	/	2026-02-06	2027-02-05
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2026-02-23	2027-02-22
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2026-02-05	2027-02-04
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2026-02-05	2027-02-04
WTXE1007A 1002	Amplifier	HP	8447F	2805A034 75	2026-02-05	2027-02-04
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2026-02-05	2027-02-04
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2026-03-11	2029-03-10
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
☐ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2026-02-05	2027-02-04
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2026-02-05	2027-02-04
WTXE1065A 1001	Amplifier	C&D	PAP-1.0G18	14918	2026-02-05	2027-02-04
WTXE1010A	Horn Antenna	ETS	3117	00086197	2026-02-05	2027-02-04

1005						
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2026-02-10	2027-02-09
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2026-02-05	2027-02-04
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2026-02-05	2027-02-04
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2026-02-05	2027-02-04
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2026-02-23	2027-02-22
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
☒ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2026-02-05	2027-02-04
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2026-02-05	2027-02-04
WTXE1007A 1003	Amplifier	HP	8447F	2944A038 69	2026-02-05	2027-02-04
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1034-2	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
☒ Chamber C: Above 1GHz						

WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2026-02-05	2027-02-04
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2025-06-13	2027-06-12
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2026-02-05	2027-02-04
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2026-02-10	2027-02-09
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2026-02-05	2027-02-04
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2025-11-25	2026-11-24
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2026-02-05	2027-02-04
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2026-02-05	2027-02-04
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2026-02-23	2027-02-22
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2026-02-05	2027-02-04
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2026-02-05	2027-02-04
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22

Software List			
Description	Manufacturer	Model	Version
EMI Test Software/EZ-EMC (Radiated Emission A)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission B)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission C)	Farad	RA-03A1-2	1.1.4.2
EMI Test Software/EZ-EMC (Conducted Emission Room 1#)	Farad	3A1*CE-RE	1.1.4.3
EMI Test Software/EZ-EMC (Conducted Emission Room 2#)	Farad	3A1*CE-RE	1.1.4.3

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information


This product has a PCB antenna, fulfill the requirement of this section.

4. Power Spectral Density

4.1 Standard Applicable

According to 15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

4.2 Test Setup Block Diagram



4.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

4.4 Summary of Test Results/Plots


Please refer to Appendix A

5. DTS Bandwidth

5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2020 Subclause 11.8.1, the test method of DTS Bandwidth as below:

Option 1:

The steps for the first option are as follows:

- Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Trace mode = max-hold.
- Sweep = No faster than coupled (auto) time.
- Allow the trace to stabilize.
- Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB downamplitude” value, then it shall be as close as possible to this value.

Option 2:

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in ANSI C63.10-2020 Subclause 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB

5.4 Summary of Test Results/Plots


Please refer to Appendix B

6. RF Output Power

6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands: 1 Watt.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to the KDB-558074 D01 v05r02 Sub clause 8.3.2.2 and ANSI C63.10-2020 Sub clause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth.

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This gives bin-to-bin spacing $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

6.4 Summary of Test Results/Plots

Please refer to Appendix C

7. Field Strength of Spurious Emissions

7.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

7.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10kHz,	RBW=120kHz,	RBW=1MHz,
VBW =30kHz	VBW=300kHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


7.4 Summary of Test Results/Plots

Note: 1.This EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes (different data rate and different modulation) are performed, but only the worst case(802.11b_11Mbps) is recorded in this report.


➤ Spurious Emissions Below 1GHz

802.11b_11Mbps(worst case)			
Test Channel	Low(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	40.0173	29.85	-8.86	20.99	40.00	-19.01	-	-	peak
2	59.7315	27.48	-8.84	18.64	40.00	-21.36	-	-	peak
3	159.7586	33.89	-8.29	25.60	43.50	-17.90	-	-	peak
4	198.6424	41.56	-11.64	29.92	43.50	-13.58	-	-	peak
5	240.1442	42.24	-10.36	31.88	46.00	-14.12	-	-	peak
6	749.6761	30.43	1.13	31.56	46.00	-14.44	-	-	peak


802.11b_11Mbps(worst case)			
Test Channel	Low(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	40.2995	28.55	-8.84	19.71	40.00	-20.29	-	-	peak
2	57.2654	28.26	-8.64	19.62	40.00	-20.38	-	-	peak
3	159.7586	29.76	-8.29	21.47	43.50	-22.03	-	-	peak
4	240.1442	31.51	-10.36	21.15	46.00	-24.85	-	-	peak
5	415.4486	28.50	-5.92	22.58	46.00	-23.42	-	-	peak
6	798.6205	31.45	1.70	33.15	46.00	-12.85	-	-	peak


- Spurious Emissions Above 1GHz
- Test Mode: 802.11b_11Mbps (worst case)

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4805.307	64.42	-12.11	52.31	74.00	-21.69	-	-	peak
2	7236.000	51.35	-6.41	44.94	74.00	-29.06	-	-	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4805.307	64.45	-12.11	52.34	74.00	-21.66	-	-	peak
2	7236.000	50.87	-6.41	44.46	74.00	-29.54	-	-	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4861.299	63.84	-11.72	52.12	74.00	-21.88	-	-	peak
2	7311.000	50.68	-4.97	45.71	74.00	-28.29	-	-	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4861.299	63.85	-11.72	52.13	74.00	-21.87	-	-	peak
2	7291.932	54.01	-5.17	48.84	74.00	-25.16	-	-	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4917.942	64.52	-12.24	52.28	74.00	-21.72	-	-	peak
2	7376.898	53.32	-5.82	47.50	74.00	-26.50	-	-	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4917.942	64.23	-12.24	51.99	74.00	-22.01	-	-	peak
2	7386.000	52.02	-6.00	46.02	74.00	-27.98	-	-	peak

Remark: '-' Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. Out of Band Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Test Procedure

According to the KDB 558074D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2020 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission

must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

8.3 Summary of Test Results/Plots


➤ Radiated test

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.86	1.26	45.12	54.00	-8.88	Average Detector
	2310.000	58.11	1.26	59.37	74.00	-14.63	Peak Detector
2	2390.000	44.85	1.32	46.17	54.00	-7.83	Average Detector
	2390.000	58.51	1.32	59.83	74.00	-14.17	Peak Detector
3	2400.000	48.70	1.28	49.98	Delta=49.42dBc		Average Detector
4	2411.242	98.03	1.37	99.40			Average Detector

802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.122	96.27	1.60	97.87	/	/	Average Detector
	2462.926	105.47	1.59	107.06	/	/	Peak Detector
2	2483.500	44.54	1.46	46.00	54.00	-8.00	Average Detector
	2483.500	57.62	1.46	59.08	74.00	-14.92	Peak Detector
3	2500.000	43.71	1.36	45.07	54.00	-8.93	Average Detector
	2500.000	56.66	1.36	58.02	74.00	-15.98	Peak Detector

802.11g_54Mbps			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.81	1.26	45.07	54.00	-8.93	Average Detector
	2310.000	56.30	1.26	57.56	74.00	-16.44	Peak Detector
2	2390.000	46.18	1.32	47.50	54.00	-6.50	Average Detector
	2390.000	60.24	1.32	61.56	74.00	-12.44	Peak Detector
3	2400.000	51.85	1.28	53.13	Delta=42.34dBc		Average Detector
4	2416.533	94.06	1.41	95.47			Average Detector

802.11g_54Mbps			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.327	92.06	1.59	93.65	/	/	Average Detector
	2462.826	103.78	1.59	105.37	/	/	Peak Detector
2	2483.500	46.16	1.46	47.62	54.00	-6.38	Average Detector
	2483.500	59.64	1.46	61.10	74.00	-12.90	Peak Detector
3	2500.000	43.79	1.36	45.15	54.00	-8.85	Average Detector
	2500.000	56.70	1.36	58.06	74.00	-15.94	Peak Detector

802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.76	1.26	45.02	54.00	-8.98	Average Detector
	2310.000	56.40	1.26	57.66	74.00	-16.34	Peak Detector
2	2390.000	45.89	1.32	47.21	54.00	-6.79	Average Detector
	2390.000	60.63	1.32	61.95	74.00	-12.05	Peak Detector
3	2400.000	51.40	1.28	52.68	Delta=41.28dBc		Average Detector
4	2416.774	92.55	1.41	93.96			Average Detector

802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.126	90.93	1.59	92.52	/	/	Average Detector
	2463.727	102.39	1.59	103.98	/	/	Peak Detector
2	2483.500	46.04	1.46	47.50	54.00	-6.50	Average Detector
	2483.500	59.36	1.46	60.82	74.00	-13.18	Peak Detector
3	2500.000	43.70	1.36	45.06	54.00	-8.94	Average Detector
	2500.000	56.18	1.36	57.54	74.00	-16.46	Peak Detector

802.11n-HT40_MCS7			
Test Channel	Low	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.72	1.26	44.98	54.00	-9.02	Average Detector
	2310.000	56.81	1.26	58.07	74.00	-15.93	Peak Detector
2	2390.000	46.39	1.32	47.71	54.00	-6.29	Average Detector
	2390.000	59.00	1.32	60.32	74.00	-13.68	Peak Detector
3	2400.000	50.05	1.28	51.33	Delta=39.54dBc		Average Detector
4	2419.419	89.43	1.44	90.87			Average Detector

802.11n-HT40_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2441.363	88.07	1.60	89.67	/	/	Average Detector
	2442.625	99.48	1.61	101.09	/	/	Peak Detector
2	2483.500	46.55	1.46	48.01	54.00	-5.99	Average Detector
	2483.500	60.11	1.46	61.57	74.00	-12.43	Peak Detector
3	2500.000	43.88	1.36	45.24	54.00	-8.76	Average Detector
	2500.000	57.17	1.36	58.53	74.00	-15.47	Peak Detector

➤ Conducted test
Please refer to Appendix D


9. Conducted Emissions

9.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

9.2 Basic Test Setup Block Diagram




9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150kHz
Stop Frequency.....	30MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth.....	9kHz
Quasi-Peak Adapter Mode.....	Normal


9.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2100	14.07	9.63	23.70	53.20	-29.50	AVG
2	0.2340	23.42	9.63	33.05	62.30	-29.25	QP
3	0.7180	11.79	9.74	21.53	46.00	-24.47	AVG
4*	0.7220	25.15	9.74	34.89	56.00	-21.11	QP
5	2.5260	6.98	9.38	16.36	46.00	-29.64	AVG
6	2.5460	20.85	9.38	30.23	56.00	-25.77	QP
7	6.8740	12.91	9.78	22.69	50.00	-27.31	AVG
8	7.0460	21.30	9.79	31.09	60.00	-28.91	QP
9	11.1980	20.74	9.74	30.48	60.00	-29.52	QP
10	12.5900	9.60	9.65	19.25	50.00	-30.75	AVG
11	19.6100	5.02	9.54	14.56	50.00	-35.44	AVG
12	20.7060	12.26	9.54	21.80	60.00	-38.20	QP

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2860	22.41	9.63	32.04	60.64	-28.60	QP
2	0.3020	13.74	9.63	23.37	50.19	-26.82	AVG
3*	0.7220	23.18	9.74	32.92	56.00	-23.08	QP
4	0.7780	11.53	9.75	21.28	46.00	-24.72	AVG
5	1.3020	13.02	9.64	22.66	46.00	-23.34	AVG
6	1.3980	23.00	9.60	32.60	56.00	-23.40	QP
7	2.0620	8.58	9.36	17.94	46.00	-28.06	AVG
8	2.4620	21.39	9.38	30.77	56.00	-25.23	QP
9	7.0300	13.17	9.79	22.96	50.00	-27.04	AVG
10	7.6620	21.56	9.79	31.35	60.00	-28.65	QP
11	12.0260	20.76	9.69	30.45	60.00	-29.55	QP
12	12.2180	10.31	9.68	19.99	50.00	-30.01	AVG




APPENDIX SUMMARY




Project No.	WTX26X04115694W001	Test Engineer	Baidi Zhong
Start date	2026/5/11	Finish date	2026/5/11
Temperature	22.6℃	Humidity	52%
RF specifications	WIFI-2.4G		

APPENDIX	Description of Test Item	Result
A	Power Spectral Density	Compliant
B	DTS Bandwidth	Compliant
C	RF Output Power	Compliant
D	Conducted Out of Band Emissions	Compliant

APPENDIX A

Power Spectral Density			
Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b_11Mbps	2412	-7.40	8
	2437	-6.24	8
	2462	-7.56	8
802.11g_54Mbps	2412	-9.32	8
	2437	-8.67	8
	2462	-9.00	8
802.11n-HT20_MCS7	2412	-10.07	8
	2437	-9.98	8
	2462	-10.78	8
802.11n-HT40_MCS7	2422	-12.18	8
	2437	-13.16	8
	2452	-12.90	8

802.11b-Low	 Ref: 20 dBm *Att: 30 dB *RBW: 30 kHz Marker 1 [T1] -7.40 dBm *VSW: 100 kHz 2.41160000 GHz SWT: 35 ms Center: 2.412 GHz 3 MHz/ Span: 30 MHz Date: 11.MAY.2026 10:39:43
802.11b-Middle	 Ref: 20 dBm *Att: 30 dB *RBW: 30 kHz Marker 1 [T1] -6.24 dBm *VSW: 100 kHz 2.436220000 GHz SWT: 35 ms Center: 2.437 GHz 3 MHz/ Span: 30 MHz Date: 11.MAY.2026 10:40:09
802.11b-High	 Ref: 20 dBm *Att: 30 dB *RBW: 30 kHz Marker 1 [T1] -7.56 dBm *VSW: 100 kHz 2.461460000 GHz SWT: 35 ms Center: 2.462 GHz 3 MHz/ Span: 30 MHz Date: 11.MAY.2026 10:40:34




802.11g-Low	 Date: 11.MAY.2026 10:39:17
802.11g-Middle	 Date: 11.MAY.2026 10:38:52
802.11g-High	 Date: 11.MAY.2026 10:38:24

Channel	Frequency (GHz)	Power (dBm)	Bandwidth (kHz)	Span (MHz)	Resolution (kHz)	Marker 1 [T1]
802.11n-HT20-Low	2.412	-10.07	100	30	30	2.416980000
802.11n-HT20-Middle	2.437	-9.98	100	30	30	2.436340000
802.11n-HT20-High	2.462	-10.78	100	30	30	2.463840000

The figure displays three spectral plots for 802.11n-HT20 channels, arranged vertically. Each plot shows a signal spectrum with a central peak and sidebands. The plots are labeled with their respective channel names and frequency values.




- 802.11n-HT20-Low:** The plot shows a signal centered at 2.412 GHz. The power level is -10.07 dBm. The bandwidth is 100 kHz. The span is 30 MHz. The resolution is 30 kHz. The marker 1 [T1] is at 2.416980000 GHz.
- 802.11n-HT20-Middle:** The plot shows a signal centered at 2.437 GHz. The power level is -9.98 dBm. The bandwidth is 100 kHz. The span is 30 MHz. The resolution is 30 kHz. The marker 1 [T1] is at 2.436340000 GHz.
- 802.11n-HT20-High:** The plot shows a signal centered at 2.462 GHz. The power level is -10.78 dBm. The bandwidth is 100 kHz. The span is 30 MHz. The resolution is 30 kHz. The marker 1 [T1] is at 2.463840000 GHz.




The plots are arranged in a 3x1 grid. The top plot is for the Low channel, the middle for the Middle channel, and the bottom for the High channel. Each plot has a title bar with the channel name and frequency. The y-axis represents power in dBm, ranging from -80 to 20. The x-axis represents frequency in GHz, ranging from 2.410 to 2.470. The plots show a signal with a peak at the center frequency, with sidebands and noise floor visible.


802.11n-HT40-Low	 Date: 11.MAY.2026 10:36:38
802.11n-HT40-Middle	 Date: 11.MAY.2026 10:33:19
802.11n-HT40-High	 Date: 11.MAY.2026 10:29:32




APPENDIX B

DTS Bandwidth			
Test Mode	Test Channel MHz	6 dB Bandwidth MHz	Limit kHz
802.11b_11Mbps	2412	8.82	≥500
	2437	8.46	≥500
	2462	8.46	≥500
802.11g_54Mbps	2412	16.64	≥500
	2437	16.64	≥500
	2462	16.64	≥500
802.11n-HT20_MCS7	2412	17.44	≥500
	2437	17.44	≥500
	2462	17.44	≥500
802.11n-HT40_MCS7	2422	35.52	≥500
	2437	35.52	≥500
	2452	35.68	≥500

802.11b-Low	 Ref: 20 dBm, Att: 30 dB, RBW: 300 kHz, VSW: 1 MHz, SWT: 2.5 ms, Marker 1 [T1]: 2.411520000 GHz, 3.37 dBm ndB [T1]: 6.00 dB, BW: 8.820000000 MHz, Temp: 1 [T1] dBm -2.96 dBm, 2.407800000 GHz, -2.62 dBm, 2.416620000 GHz Center: 2.412 GHz, 3 MHz/, Span: 30 MHz Date: 11.MAY.2026 10:58:15
802.11b-Middle	 Ref: 20 dBm, Att: 30 dB, RBW: 300 kHz, VSW: 1 MHz, SWT: 2.5 ms, Marker 1 [T1]: 2.436460000 GHz, 5.92 dBm ndB [T1]: 6.00 dB, BW: 8.460000000 MHz, Temp: 1 [T1] dBm -0.14 dBm, 2.432800000 GHz, -0.14 dBm, 2.441260000 GHz Center: 2.437 GHz, 3 MHz/, Span: 30 MHz Date: 11.MAY.2026 10:57:36
802.11b-High	 Ref: 20 dBm, Att: 30 dB, RBW: 300 kHz, VSW: 1 MHz, SWT: 2.5 ms, Marker 1 [T1]: 2.461520000 GHz, 5.47 dBm ndB [T1]: 6.00 dB, BW: 8.460000000 MHz, Temp: 1 [T1] dBm -1.05 dBm, 2.457800000 GHz, -0.72 dBm, 2.466260000 GHz Center: 2.462 GHz, 3 MHz/, Span: 30 MHz Date: 11.MAY.2026 10:41:25




802.11g-Low	 Ref 20 dBm Att 30 dB RBW 300 kHz VSW 1 MHz SWT 2.5 ms Marker 1 [T1] 2.41200000 GHz -5.16 dBm 2.420320000 GHz -6.42 dBm 2.403680000 MHz -4.00 dBm BW 16.64000000 MHz Temp 1 [T1] 0.00 dB Center 2.412 GHz 4 MHz/ Span 40 MHz Date: 11.MAY.2026 10:59:40
802.11g-Middle	 Ref 20 dBm Att 30 dB RBW 300 kHz VSW 1 MHz SWT 2.5 ms Marker 1 [T1] 2.441160000 GHz -4.38 dBm 2.428680000 GHz -1.99 dBm 2.445320000 GHz -4.00 dBm BW 16.64000000 MHz Temp 1 [T1] 0.00 dB Center 2.437 GHz 4 MHz/ Span 40 MHz Date: 11.MAY.2026 11:05:03
802.11g-High	 Ref 20 dBm Att 30 dB RBW 300 kHz VSW 1 MHz SWT 2.5 ms Marker 1 [T1] 2.466160000 GHz -2.96 dBm 2.453680000 GHz -2.44 dBm 2.470320000 GHz -4.00 dBm BW 16.64000000 MHz Temp 1 [T1] 0.00 dB Center 2.462 GHz 4 MHz/ Span 40 MHz Date: 11.MAY.2026 11:07:18









802.11n-HT40-Low	 Ref 20 dBm *Att 30 dB *VSW 3 MHz *RBW 1 MHz Marker 1 [T1] 2.425520000 GHz 2.63 dBm 20 Offset 1 dB 1 2.404400000 GHz -2.10 dBm 2.439920000 GHz -2.10 dBm Center 2.422 GHz 8 MHz/ Span 80 MHz Date: 11.MAY.2026 11:09:36
802.11n-HT40-Middle	 Ref 20 dBm *Att 30 dB *VSW 3 MHz *RBW 1 MHz Marker 1 [T1] 2.440200000 GHz 4.12 dBm 20 Offset 1 dB 1 2.419400000 GHz -1.62 dBm 2.454920000 GHz -1.97 dBm Center 2.437 GHz 8 MHz/ Span 80 MHz Date: 11.MAY.2026 11:10:57
802.11n-HT40-High	 Ref 20 dBm *Att 30 dB *VSW 3 MHz *RBW 1 MHz Marker 1 [T1] 2.455360000 GHz 5.45 dBm 20 Offset 1 dB 1 2.434240000 GHz -0.86 dBm 2.469920000 GHz -0.81 dBm Center 2.452 GHz 8 MHz/ Span 80 MHz Date: 11.MAY.2026 11:11:27




APPENDIX C

Test Mode	Frequency MHz	Reading dBm	Limit dBm
802.11b _ 11Mbps	2412	15.37	30.00
	2437	15.15	30.00
	2462	15.02	30.00
802.11g_54Mbps	2412	14.10	30.00
	2437	14.09	30.00
	2462	14.02	30.00
802.11n HT20_MCS7	2412	13.47	30.00
	2437	13.06	30.00
	2462	13.04	30.00
802.11n HT40_MCS7	2422	12.57	30.00
	2437	12.02	30.00
	2452	12.03	30.00

802.11b-Low	 Date: 11.MAY.2026 09:50:38
802.11b-Middle	 Date: 11.MAY.2026 09:51:25
802.11b-High	 Date: 11.MAY.2026 09:52:41




802.11g-Low	 Date: 11.MAY.2026 09:55:12
802.11g-Middle	 Date: 11.MAY.2026 09:54:25
802.11g-High	 Date: 11.MAY.2026 09:53:48




802.11n-HT20-Low	 Ref 20 dBm Offset 1 dB Att 30 dB RBW 300 kHz VBW 1 MHz SWT 2.5 ms Center 2.412 GHz 3 MHz/ Span 30 MHz Tx Channel Bandwidth 20 MHz Power 13.47 dBm Date: 11.MAY.2026 10:15:42
802.11n-HT20-Middle	 Ref 20 dBm Offset 1 dB Att 30 dB RBW 300 kHz VBW 1 MHz SWT 2.5 ms Center 2.437 GHz 3 MHz/ Span 30 MHz Tx Channel Bandwidth 20 MHz Power 13.06 dBm Date: 11.MAY.2026 10:16:41
802.11n-HT20-High	 Ref 20 dBm Offset 1 dB Att 30 dB RBW 300 kHz VBW 1 MHz SWT 2.5 ms Center 2.462 GHz 3 MHz/ Span 30 MHz Tx Channel Bandwidth 20 MHz Power 13.04 dBm Date: 11.MAY.2026 10:17:46

802.11n-HT40-Low	 Date: 11.MAY.2026 10:18:44
802.11n-HT40-Middle	 Date: 11.MAY.2026 10:19:20
802.11n-HT40-High	 Date: 11.MAY.2026 10:21:19



APPENDIX D

Conducted Out of Band Emissions


802.11b-Low	 Date: 11.MAY.2026 11:29:17
	 Date: 11.MAY.2026 11:29:35
802.11b-Middle	 Date: 11.MAY.2026 11:30:25




	 Date: 11.MAY.2026 11:30:49
802.11b-High	 Date: 11.MAY.2026 11:31:27
	 Date: 11.MAY.2026 11:31:46

802.11g-Low





802.11g-Middle





	
802.11g-High	
	

802.11n-HT20-Low




802.11n-HT20-Middle






Date: 11.MAY.2026 11:23:27




Date: 11.MAY.2026 11:23:58

802.11n-HT20-High





Date: 11.MAY.2026 11:24:18

802.11n-HT40-Low




802.11n-HT40-Middle






Date: 11.MAY.2026 11:19:39



Date: 11.MAY.2026 11:12:57

802.11n-HT40-High



Date: 11.MAY.2026 11:13:41

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****