

FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2BDC6-PRESENCE

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Modes& Channel Freq. (MHz)	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW / cm2)	Result
2.4G WIFI	802.11b&2 412M	13±1	14	25.1189	0.3819 (-4.18dBi)	0.0019	1	Pass
BLE 1M	GFSK &2440M	3±1	4	2.5119	0.4074 (-3.90dBi)	0.0002	1	Pass
BLE 2M	GFSK &2440M	2±1	3	1.9953	0.4074 (-3.90dBi)	0.0002	1	Pass
Zigbee	O-QPSK &2405M	8±1	9	7.9433	0.4074 (-3.90dBi)	0.0006	1	Pass
Radar	FMCW &62G	8±1	9	7.94	1.2589 (1dBi)	0.001989	1	Pass

BLE+WIFI+ Radar+Zigbee supported simultaneous transmission:

BLE+WIFI+ Radar+Zigbee: Σ MPE Ratio

=0.0002/1+0.0019/1+0.001989/1+0.0006/1=0.004689≤1,

So passed.