



MPE Report

Report No.: STS2601304H01

Issued for

Shelly Europe Ltd.

51 Cherni Vrah Blvd., bldg.3,fl.2-3 Sofia 1407 Bulgaria

Product Name: Smart Switch

Brand Name: Ogemray

Model Name: SW40

Series Model(s): N/A

FCC ID: 2BDC6-SW40

Test Standard: FCC 47CFR §2.1091

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the ShenZhen STS Test Services Co., Ltd.

**TEST REPORT****Applicant's Name**: Shelly Europe Ltd.

Address: 51 Cherni Vrah Blvd., bldg.3,fl.2-3 Sofia 1407 Bulgaria

Manufacturer's Name.....: Shenzhen Ogemray Technology Co., LtdAddress: 3/F-4/F, NO. 5 Bldg, Dongwu Industrial Park, Donghuan 1st Road,
Longhua Town, Shenzhen, China**Product Description**

Product Name.....: Smart Switch

Brand Name: Ogemray

Model Name: SW40

Series Model(s).....: N/A

Test Standards: FCC 47CFR §2.1091

447498 D01 Interim General RF Exposure Guidance v06

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the ShenZhen STS Test Services Co., Ltd.

Date of Test:

Date of receipt of test item.....: 18 Dec. 2025

Date (s) of performance of tests.....: 18 Dec. 2025 to 7 Jan. 2026

Date of Issue.....: 7 Jan. 2026

Test Result.....: **Pass**

Testing Engineer : _____

Aaron Bu

(Aaron Bu)

Technical Manager : _____

Skylar Li

(Skylar Li)

Authorized Signatory : _____

Bovey Yang

(Bovey Yang)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	5
2. FCC 47CFR §2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 TEST RESULT	7

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	7 Jan. 2026	STS2601304H01	ALL	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Smart Switch	
Brand Name	Ogemray	
Model Name	SW40	
Series Model(s)	N/A	
Model Difference	N/A	
Product Description	The EUT is a Smart Switch	
	Operation Frequency:	2402~2480 MHz 802.11b/g/n 20: 2412~2462 MHz 802.11n40:2422~2452MHz
	Modulation Type:	GFSK 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11b/g Support SISO 802.11n Support SISO
	Antenna gain:	1.55 dBi
	Antenna Designation:	Internal Antenna
Power Rating	Input: AC 120V/6Hz	
Adapter	N/A	
Battery	N/A	
Hardware Version	N/A	
Software Version	N/A	

1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
3.0-30	1842/f	4.89/f	*(900/f ²)
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1.34-30	824/f	2.19/f	*(180f ²)
1500 – 100000	--	--	1.0

F= Frequency in MHz

Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.



2.3 TEST RESULT

Tune up

Mode	Detector	Tune up Power
2.4G WIFI	AV	12±1dBm
BLE	AV	1±1dBm

Protocol	Fre. (GHz)	Separati on distance (cm)	Max Tune up power (dBm)	ANT Gain (dBi)	Max EIRP (dBm)	Max EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/ cm ²)	Ratio	Result
2.4G WIFI	2.437	20	13	1.55	14.55	28.51	0.0057	1	0.0057	Pass
BLE	2.48	20	2	1.55	3.55	2.265	0.0005	1	0.0005	Pass

Note: 1. The Maximum power is less than the limit, complies with the exemption requirements.

2. The Bluetooth and WLAN can't simultaneous transmission at the same time.

3. ERP = EIRP - 2.15

※※※※※END OF THE REPORT※※※※※