

RF Exposure Evaluation

For

Shenzhen Yunji New Energy Technology Co., Ltd

Portable power station

Test Model: P1500 PLUS

Prepared for : Shenzhen Yunji New Energy Technology Co., Ltd
Address : A2 3F BUILDING ENET NEW INDUSTRIAL PARK DAFU
INDUSTRIAL ZONE, GUANLAN, LONGHUA, Shenzhen,
Guangdong, 518000, China

Prepared by : Guangzhou LCS Compliance Testing Laboratory Ltd.
Address : No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou,
Guangdong, China

Tel : (+86) 020-39166689
Fax : (+86) 020-39166619
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : September 11, 2025
Number of tested samples : 2
Sample number : C250910008-1, C250910008-2
Serial number : Prototype
Date of Test : September 11, 2025 ~September 28, 2025
Date of Report : September 29, 2025


RF Exposure Evaluation

Report Reference No. : LCSC09105006EC
Date of Issue..... : September 29, 2025
Testing Laboratory Name..... : Guangzhou LCS Compliance Testing Laboratory Ltd.
Address..... : No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
Testing Location/ Procedure..... : Full application of Harmonised standards ■
 Partial application of Harmonised standards □
 Other standard testing method □


Applicant's Name..... : Shenzhen Yunji New Energy Technology Co., Ltd
Address..... : A2 3F BUILDING ENET NEW INDUSTRIAL PARK DAFU INDUSTRIAL ZONE, GUANLAN, LONGHUA, Shenzhen, Guangdong, 518000, China
Test Specification
Standard..... : FCC CFR 47 part1 1.1310
 FCC CFR 47 part2 2.1091

Test Report Form No..... : TRF-4-E-214 A/0
TRF Originator..... : Guangzhou LCS Compliance Testing Laboratory Ltd.
Master TRF..... : Dated 2011-03
Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved.


This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

EUT Description..... : Portable power station
Trade Mark..... : N/A
Test Model..... : P1500 PLUS
Ratings..... : Please Refer to Page 6
Result : PASS
Compiled by:


Lifeng Le/ Administrator

Supervised by:


Justin Zhu/ Technique principal

Approved by:


Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. : LCSC09105006EC	<u>September 29, 2025</u> Date of issue
---	--

Test Model.....	: P1500 PLUS
EUT.....	: Portable power station
Applicant.....	: Shenzhen Yunji New Energy Technology Co., Ltd
Address.....	: A2 3F BUILDING ENET NEW INDUSTRIAL PARK DAFU INDUSTRIAL ZONE, GUANLAN, LONGHUA, Shenzhen, Guangdong, 518000, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Shenzhen Yunji New Energy Technology Co., Ltd
Address.....	: A2 3F BUILDING ENET NEW INDUSTRIAL PARK DAFU INDUSTRIAL ZONE, GUANLAN, LONGHUA, Shenzhen, Guangdong, 518000, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Huizhou Yunji New Energy Technology Co., LTD
Address.....	: Floor 4, Building 7, Huiyang hengang technologyindustry park Yangnacun Area, Danshui Street, huiyang district, Huizhou City
Telephone.....	: /
Fax.....	: /

Test Result	PASS
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	September 29, 2025	Initial Issue	--

TABLE OF CONTENTS

Description	Page
1. PRODUCT INFORMATION	6
2. EVALUATION METHOD	7
3. LIMIT	7
4. MPE CALCULATION METHOD	8
5. ANTENNA INFORMATION	8
6. CONDUCTED POWER	8
7. MANUFACTURING TOLERANCE	9
8. MEASUREMENT RESULTS	10
9. CONCLUSION	10
10. DESCRIPTION OF TEST FACILITY	11
11. MEASUREMENT UNCERTAINTY	11

1. Product Information

EUT	: Portable power station
Test Model	: P1500 PLUS
Ratings	: AC Input: 100-120V~, 50/60Hz, 10A, 1200W Max PV Input: DC 12V~50V, 11A, 500W Max Input: DC 12V, 8A, DC 24V, 10A AC Output: 100-120Vac 1800W (USA:120V JP:100V), Rated power 1800W, Surge Power 3600W Max USB-A Output: 5V===3A, 9V===2A, 12V===1.5A, 18W Type C Output: 5V===3A, 9V===3A, 12V===1.5A, 15V===1A, 20V===1A, 20W Type C Output: 5V===3A, 9V===3A, 12V===3A, 15V===3A, 20V===5A, 100W DC output: 12V===3A, total 36W Output: 12V===10A, 120W Battery: 1536Wh 3.2V/480000mAh(51.2V/30000mAh)
Hardware Version	: /
Software Version	: /
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 40 channels for Bluetooth V5.2 (DTS)
Channel Spacing	: 2MHz for Bluetooth V5.2 (DTS)
Modulation Type	: GFSK for Bluetooth V5.2 (DTS)
Bluetooth Version	: V5.2
Antenna Description	: PCB Antenna, -1.0dBi(Max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz)
Channel Spacing	: 5MHz
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PCB Antenna, -1.0dBi(Max.)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device
Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.	

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3. 1 Refer Evaluation Method

[ANSI C95.1–2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3. 2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Internal/External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Internal Antenna	PCB Antenna	2400-2500 MHz	-1.0dBi	BT/ WIFI Antenna

6. Conducted Power

[BT LE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	0.34
	19	2440	0.34
	39	2480	-0.56

[2.4G WLAN]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
IEEE 802.11b	1	2412	14.93
	6	2437	15.04
	11	2462	15.3
IEEE 802.11g	1	2412	14.01
	6	2437	14.48
	11	2462	14.74
IEEE 802.11n HT20	1	2412	13.61
	6	2437	13.73
	11	2462	14.08

7. Manufacturing Tolerance

[BT LE]

BT LE(Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WLAN]

IEEE 802.11b(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	14.0	15.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n20(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	13.0	13.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

8. Measurement Results

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT LE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	1.0	1.2589	-1.0	0.7943	0.0002	1.0000

[2.4GWLAN]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	16.0	39.8107	-1.0	0.7943	0.0063	1.0000
IEEE 802.11g	15.0	31.6228	-1.0	0.7943	0.0050	1.0000
IEEE 802.11n HT20	15.0	31.6228	-1.0	0.7943	0.0050	1.0000

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

10. Description of Test Facility

CNAS Registration Number is L11555

A2LA Certificate Number: 5099.01

FCC Designation Number is CN1379

Test Firm Registration Number: 729882

11. Measurement Uncertainty

BLE/2.4GWIFI

Test Item		Frequency Range	Uncertainty	Note
Output power	:	1GHz-40GHz	$\pm 0.57\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

-----THE END OF REPORT-----