CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 ISSUE 2 (DSS)

TEST REPORT

For

Helmet TWS Bluetooth Headset

MODEL NUMBER: JYM 0021

REPORT NUMBER: E04A23080906F00401

ISSUE DATE: October 27, 2023

FCC ID:2BDD2-JYM0021

IC: 31454-JYM0021

Prepared for

Huizhou Jiuyunmu Technology Co.,Ltd
Room 03, 33rd Floor, Building 9, No. 8 and 9, Shuguang Road, Chenjiang Street, Zhongkai Hi-tech Zone, Huizhou, China

Prepared by

Guangdong Global Testing Technology Co., Ltd.

Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808

This report shall not be reproduced, except in full, without the written approval of Guangdong Global Testing Technology Co., Ltd.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	October 27, 2023	Initial Issue	Jok Yang

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c) RSS-Gen Issue 5, Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013 Clause 6.2	FCC Part 15.207 RSS-Gen Issue 5, Clause 8.8	Pass
Conducted Output Power	ANSI C63.10-2013 Clause 7.8.5	FCC Part 15.247 (b)(1) RSS-247 Issue 2, Clause 5.4(b)	Pass
20 dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013 Clause 6.9.2	FCC Part 15.247 (a)(1) RSS-247 Issue 2, Clause 5.1(a)	Pass
Carrier Hopping Channel Separation	ANSI C63.10-2013 Clause 7.8.2	FCC Part 15.247 (a)(1) RSS-247 Issue 2, Clause 5.1(b)	Pass
Number of Hopping Frequency	ANSI C63.10-2013 Clause 7.8.3	FCC Part 15.247 (b)(1) RSS-247 Issue 2, Clause 5.1(d)	Pass
Time of Occupancy (Dwell Time)	ANSI C63.10-2013 Clause 7.8.4	FCC Part 15.247 (a)(1) RSS-247 Issue 2, Clause 5.1(d)	Pass
Conducted Bandedge and Spurious Emission	ANSI C63.10-2013 Clause 6.10.4 & Clause 7.8.8	FCC Part 15.247(d) RSS-247 Issue 2, Clause 5.5	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013 Clause 6.3 & 6.5 & 6.6	FCC Part 15.205/15.209 RSS-Gen Issue 5, Clause 6.13/ 8.9/ 8.10	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.
*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 ISSUE 2 (DSS)> when <Accuracy Method> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS 5

2. TEST METHODOLOGY 6

3. FACILITIES AND ACCREDITATION 6

4. CALIBRATION AND UNCERTAINTY 7

4.1. MEASURING INSTRUMENT CALIBRATION 7

4.2. MEASUREMENT UNCERTAINTY 7

5. EQUIPMENT UNDER TEST 8

5.1. DESCRIPTION OF EUT 8

5.2. CHANNEL LIST 8

5.3. MAXIMUM AVERAGE EIRP 9

5.4. TEST CHANNEL CONFIGURATION 9

5.5. THE WORSE CASE POWER SETTING PARAMETER 9

5.6. DESCRIPTION OF AVAILABLE ANTENNAS 10

5.7. SUPPORT UNITS FOR SYSTEM TEST 10

5.8. SETUP DIAGRAM 10

6. MEASURING EQUIPMENT AND SOFTWARE USED 11

7. ANTENNA PORT TEST RESULTS 13

7.1. Conducted Output Power 13

7.2. 20 dB Bandwidth and 99% Occupied Bandwidth 15

7.3. Carrier Hopping Channel Separation 17

7.4. Number of Hopping Frequency 19

7.5. Time of Occupancy (Dwell Time) 21

7.6. Conducted Bandedge and Spurious Emission 23

8. Radiated Band edge and Spurious Emission 25

9. ANTENNA REQUIREMENT 32

10. AC POWER LINE CONDUCTED EMISSION 34

11. TEST DATA - Appendix A 36

APPENDIX: PHOTOGRAPHS OF TEST CONFIGURATION 92

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name:	Huizhou Jiuyunmu Technology Co.,Ltd
Address:	Room 03, 33rd Floor, Building 9, No. 8 and 9, Shuguang Road, Chenjiang Street, Zhongkai Hi-tech Zone, Huizhou, China

Manufacturer Information

Company Name:	Huizhou Jiuyunmu Technology Co.,Ltd
Address:	Room 03, 33rd Floor, Building 9, No. 8 and 9, Shuguang Road, Chenjiang Street, Zhongkai Hi-tech Zone, Huizhou, China

EUT Information

Product Description:	Helmet TWS Bluetooth Headset
Model:	JYM 0021
Brand:	/
Sample Received Date:	October 17, 2023
Sample Status:	Normal
Sample ID:	A23080906 001
Date of Tested:	October 20, 2023 to October 24, 2023

APPLICABLE STANDARDS	
STANDARD	**TEST RESULTS**
CFR 47 FCC PART 15 SUBPART C **ISED RSS-247 ISSUE 2 (DSS)**	**Pass**

Prepared By:

Jok Yang

Project Engineer

Checked By:

Alan He

Laboratory Leader

Approved By:

Shawn Wen

Laboratory Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C ISED RSS-247 ISSUE 2 (DSS)

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	**A2LA (Certificate No.: 6947.01)** Guangdong Global Testing Technology Co., Ltd. has been assessed and proved to be in compliance with A2LA. **FCC (FCC Designation No.: CN1343)** Guangdong Global Testing Technology Co., Ltd. has been recognized to perform compliance testing on equipment subject to Supplier's Declaration of Conformity (SDoC) and Certification rules **ISED (Company No.: 30714)** Guangdong Global Testing Technology Co., Ltd. has been registered and fully described in a report filed with ISED. The Company Number is 30714 and the test lab Conformity Assessment Body Identifier (CABID) is CN0148.

Note: All tests measurement facilities use to collect the measurement data are located at Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People’s Republic of China, 523808

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Items	k	Uncertainty
DTS Bandwidth	1.96	±9.2 PPM
20dB Emission Bandwidth	1.96	±9.2 PPM
Carrier Frequency Separation	1.96	±9.2 PPM
Time of Occupancy	1.96	±0.57%
Conducted Output Power	1.96	±1.5 dB
Power Spectral Density Level	1.96	±1.9 dB
Conducted Spurious Emission	1.96	9 kHz-30 MHz: ± 0.95 dB 30 MHz-1 GHz: ± 1.5 dB 1GHz-12.75GHz: ± 1.8 dB 12.75 GHz-26.5 GHz: ± 2.1dB
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.		

Test Item	Measurement Frequency Range	K	U(dB)
Conducted emissions from the AC mains power ports (AMN)	150 kHz ~ 30 MHz	2	3.37
Radiated emissions	9 kHz ~ 30 MHz	2	4.16
Radiated emissions	30 MHz ~ 1 GHz	2	3.79
Radiated emissions	1 GHz ~ 18 GHz	2	5.62
Radiated emissions	18 GHz ~ 40 GHz	2	5.54
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.			

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name		Helmet TWS Bluetooth Headset
Model		JYM 0021
EUT Classification		Class B
Hardware Version		1.0
Software Version		1.0
Ratings		Input:USB-C:5V / Battery 3.7V
Battery Ratings		XYT 402030 3.7V 200mAh 0.74Wh
Power Supply	DC	5V
	Battery	3.7V
Remark: The left and right ears of the EUT have the same RF module and antenna, PCB layout, schematics and component.		

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	5.3
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Type of Modulation:	GFSK, π/4DQPSK
Number of Channels:	79
Channel Separation:	1 MHz
Maximum Peak Power:	3.08 dBm
Antenna Type:	Internal Antenna
Antenna Gain:	0 dBi
EUT Test software:	FCC_assist_1.0.2.2

5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470
09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475

14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	/	/

5.3. MAXIMUM AVERAGE EIRP

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)	Maximum EIRP (dBm)
GFSK	2402 ~ 2480	0-78[79]	2.31	2.31
π /4-DQPSK	2402 ~ 2480	0-78[79]	3.08	3.08

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK	CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402 MHz, 2441 MHz, 2480 MHz
π /4-DQPSK	CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402 MHz, 2441 MHz, 2480 MHz

Note: The hop is hopping mode.

PACKET TYPE CONFIGURATION

Test Mode	Packet Type	Setting (Packet Length)
GFSK	DH1	27
	DH3	183
	DH5	339
π /4-DQPSK	2-DH1	54
	2-DH3	367
	2-DH5	679

5.5. THE WORSE CASE POWER SETTING PARAMETER

WORST-CASE CONFIGURATIONS

Bluetooth Mode	Modulation Technology	Modulation Type	Data Rate (Mbps)
BR	FHSS	GFSK	1Mbit/s
EDR	FHSS	π /4-DQPSK	2Mbit/s

Note: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		FCC_assist_1.0.2.2		
Modulation Type	Transmit Antenna Number	Test Software setting value		
		CH 00	CH 39	CH 78
GFSK	1	10	10	10
π /4-DQPSK	1	10	10	10

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	Internal Antenna	0

Test Mode	Transmit and Receive Mode	Description
GFSK	☒1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
π /4-DQPSK	☒1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

5.7. SUPPORT UNITS FOR SYSTEM TEST

Equipment	**Manufacturer**	**Model No.**
Adapter	Lulian	CD170
PC	Lenovo	T14
Test board	/	/

5.8. SETUP DIAGRAM

AC conducted emission :

Radiated Emission:



RF conducted:



6. MEASURING EQUIPMENT AND SOFTWARE USED

Test Equipment of Conducted RF					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Due Date**
Spectrum Analyzer	Rohde & Schwarz	FSV40	102257	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51285127	2023/09/18	2024/09/17
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61253075	2023/09/18	2024/09/17
Vector Signal Generator	Rohde & Schwarz	SMM100A	101899	2023/09/18	2024/09/17
RF Control box	MWRF-test	MW100-RFCB	MW220926GTG	2023/09/18	2024/09/17
Wideband Radio Communication Tester	Rohde & Schwarz	CMW270	102792	2023/09/18	2024/09/17
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	103235	2023/09/18	2024/09/17
temperature humidity chamber	Espec	SH-241	SH-241-2014	2023/09/18	2024/09/17
RF Test Software	MWRF-test	MTS8310E (Ver. V2/0)	N/A	N/A	N/A

Test Equipment of Radiated emissions below 1GHz					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Due Date**
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2146	2022/08/30	2025/08/29
EMI Test Receiver	Rohde & Schwarz	ESCI3	101409	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2023/09/18	2024/09/17
Pre-Amplifier	HzEMC	HPA-9K0130	HYPA21001	2023/09/18	2024/09/17
Biconilog Antenna	Schwarzbeck	VULB 9168	01315	2022/10/10	2025/10/09
Biconilog Antenna	ETS	3142E	00243646	2022/03/23	2025/03/22
Loop Antenna	ETS	6502	243668	2022/03/30	2025/03/29
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE)	N/A	N/A	N/A

Test Equipment of Radiated emissions above 1GHz					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Due Date**
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2149	2022/08/30	2025/08/29
Spectrum Analyzer	Rohde & Schwarz	FSV40	101413	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2023/09/18	2024/09/17
Pre-Amplifier	A-INFO	HPA-1G1850	HYPA21003	2023/09/18	2024/09/17
Horn antenna	A-INFO	3117	246069	2022/03/11	2025/03/10
Pre-Amplifier	ZKJC	HPA-184057	HYPA21004	2023/09/18	2024/09/17

Horn antenna	ZKJC	3116C	246265	2022/03/29	2025/03/28
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE+)	N/A	N/A	N/A

Test Equipment of Conducted emissions					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Due Date**
Shielded Room	CHENG YU	8m*5m*4m	N/A	2022/10/29	2025/10/28
EMI Test Receiver	Rohde & Schwarz	ESR3	102647	2023/09/18	2024/09/17
LISN/AMN	Rohde & Schwarz	ENV216	102843	2023/09/18	2024/09/17
NNLK 8129 RC	Schwarzbeck	NNLK 8129 RC	5046	2023/09/18	2024/09/17
Test Software	Farad	EZ-EMC (Ver. EMC-con-3A1 1+)	N/A	N/A	N/A

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	Peak Conduct Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.5.

Connect the EUT to the spectrum Analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	>20 dB bandwidth of the emission being measured
VBW	≥RBW
Span	Approximately five times the 20 dB bandwidth, centered on a hopping channel.
Trace	Max hold
Sweep time	Auto

Allow trace to stabilize.
Use the marker-to-peak function to set the marker to the peak of the emission.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4℃	Relative Humidity	45%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.2. 20 DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1) RSS-247 Clause 5.1 (a)	20 dB Bandwidth	None; for reporting purposes only.	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	None; for reporting purposes only.	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 6.9.2.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 20 dB Bandwidth: 1 % to 5 % of the 20 dB bandwidth For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 20 dB Bandwidth: approximately 3×RBW For 99 % Occupied Bandwidth: ≥ 3×RBW
Span	Approximately 2 to 3 times the 20dB bandwidth
Trace	Max hold
Sweep	Auto couple

a) Use the occupied bandwidth function of the instrument, allow the trace to stabilize and report the measured 99 % occupied bandwidth and 20 dB Bandwidth.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4℃	Relative Humidity	45%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.3. CARRIER HOPPING CHANNEL SEPARATION

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1) ISED RSS-247 Clause 5.1 (b)	Carrier Frequency Separation	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.2.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Span	wide enough to capture the peaks of two adjacent channels
Detector	Peak
RBW	Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
VBW	≥RBW
Trace	Max hold
Sweep time	Auto couple

Allow the trace to stabilize and use the marker-delta function to determine the separation between the peaks of the adjacent channels.
Compliance of an EUT with the appropriate regulatory limit shall be determined.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4℃	Relative Humidity	45%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.4. NUMBER OF HOPPING FREQUENCY

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 5.1 (d)	Number of Hopping Frequency	at least 15 hopping channels

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.3.

Connect the EUT to the spectrum Analyzer and use the following settings:

Detector	Peak
RBW	To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW	≥RBW
Span	The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
Trace	Max hold
Sweep time	Auto couple

Set EUT to transmit maximum output power and switch on frequency hopping function. then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer, count the quantity of peaks to get the number of hopping channels.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4℃	Relative Humidity	45%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.5. TIME OF OCCUPANCY (DWELL TIME)

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 5.1 (d)	Time of Occupancy (Dwell Time)	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.4.

Connect the EUT to the spectrum Analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1 MHz
VBW	≥RBW
Span	Zero span, centered on a hopping channel
Trace	Max hold
Sweep time	As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel

Use the marker-delta function to determine the transmit time per hop (Burst Width). If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

For FHSS Mode (79 Channel):
DH1/3DH1 Dwell Time: Burst Width * (1600/2) * 31.6 / (channel number)
DH3/3DH3 Dwell Time: Burst Width * (1600/4) * 31.6 / (channel number)
DH5/3DH5 Dwell Time: Burst Width * (1600/6) * 31.6 / (channel number)

For AFHSS Mode (20 Channel):
DH1/3DH1 Dwell Time: Burst Width * (1600/2) * 8 / (channel number)
DH3/3DH3 Dwell Time: Burst Width * (1600/4) * 8 / (channel number)
DH5/3DH5 Dwell Time: Burst Width * (1600/6) * 8 / (channel number)

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4℃	Relative Humidity	45%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.6. CONDUCTED BANDEDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Spurious Emission	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.6 and 7.8.8.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	≥3 × RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	≥3 × RBW
measurement points	≥span/RBW
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4℃	Relative Humidity	45%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

8. Radiated Band edge and Spurious Emission

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz-1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (µA/m)	Measurement distance (m)
9 - 490 kHz[Note 1]	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands[Note 1]		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 – 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 – 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 – 8500	
108 – 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

Note: [1]Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
[2]Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.

2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.

5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.

7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω. For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to Y-51.5 = Z dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz

The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 1.5 m above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.

6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

TEST SETUP







TEST ENVIRONMENT

Temperature	24.1℃	Relative Humidity	53%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A.

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC §15.203
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)
The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Standard	Requirement
RSS-Gen issue 5 6.8.	The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list. For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below). When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested. For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location: This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

	Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver is used to test the emissions from the AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013.Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4℃	Relative Humidity	45%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

11. TEST DATA - Appendix A

Radiated Band edge and Spurious Emission

Mode:	2DH5 2402
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	35.820	42.91	25.15	40.00	14.85	PK+	V	-17.76
2	66.860	40.20	15.77	40.00	24.23	PK+	V	-24.43
3	115.360	41.33	16.94	43.50	26.56	PK+	V	-24.39
4	255.040	39.58	21.04	46.00	24.96	PK+	V	-18.54
5	274.440	40.88	22.11	46.00	23.89	PK+	V	-18.77
6	959.260	30.97	28.19	46.00	17.81	PK+	V	-2.78

Mode:	2DH5 2402
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	71.710	47.38	22.59	40.00	17.41	PK+	H	-24.79
2	95.960	49.62	25.08	43.50	18.42	PK+	H	-24.54
3	150.280	38.34	16.32	43.50	27.18	PK+	H	-22.02
4	259.890	37.55	19.23	46.00	26.77	PK+	H	-18.32
5	318.090	38.99	21.31	46.00	24.69	PK+	H	-17.68
6	938.890	29.89	27.75	46.00	18.25	PK+	H	-2.14

Mode:	2DH5 2402
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	3364.500	56.36	41.87	74.00	32.13	PK+	H	-14.49
2	4804.500	55.19	43.85	74.00	30.15	PK+	H	-11.34
3	7206.000	57.61	49.61	74.00	24.39	PK+	H	-8
4	9607.500	58.99	51.93	74.00	22.07	PK+	H	-7.06
5	12213.000	48.78	44.31	74.00	29.69	PK+	H	-4.47
6	17682.000	47.01	47.29	74.00	26.71	PK+	H	0.28

Mode:	2DH5 2402
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	3756.000	55.15	41.68	74.00	32.32	PK+	V	-13.47
2	5113.500	53.03	42.66	74.00	31.34	PK+	V	-10.37
3	6949.500	50.95	42.99	74.00	31.01	PK+	V	-7.96
4	7564.500	50.79	42.85	74.00	31.15	PK+	V	-7.94
5	9607.500	54.76	47.70	74.00	26.30	PK+	V	-7.06
6	17713.500	47.77	47.66	74.00	26.34	PK+	V	-0.11

Mode:	2DH5 2441
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	3303.000	55.30	40.90	74.00	33.10	PK+	V	-14.4
2	4860.000	53.60	42.41	74.00	31.59	PK+	V	-11.19
3	6225.000	51.00	42.65	74.00	31.35	PK+	V	-8.35
4	8034.000	50.56	42.58	74.00	31.42	PK+	V	-7.98
5	9763.500	55.79	48.82	74.00	25.18	PK+	V	-6.97
6	16696.500	47.94	47.46	74.00	26.54	PK+	V	-0.48

Mode:	2DH5 2441
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	3703.500	55.58	42.00	74.00	32.00	PK+	H	-13.58
2	4882.500	56.57	45.42	74.00	28.58	PK+	H	-11.15
3	6337.500	51.45	43.43	74.00	30.57	PK+	H	-8.02
4	7323.000	55.57	47.62	74.00	26.38	PK+	H	-7.95
5	9765.000	60.65	53.68	74.00	20.32	PK+	H	-6.97
6	17673.000	46.78	47.08	74.00	26.92	PK+	H	0.3

Mode:	2DH5 2480
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	3613.500	54.02	40.45	74.00	33.55	PK+	H	-13.57
2	4959.000	57.90	46.55	74.00	27.45	PK+	H	-11.35
3	6327.000	50.18	42.27	74.00	31.73	PK+	H	-7.91
4	7438.500	54.92	46.97	74.00	27.03	PK+	H	-7.95
5	9919.500	58.44	52.09	74.00	21.91	PK+	H	-6.35
6	16000.500	48.31	46.23	74.00	27.77	PK+	H	-2.08

Mode:	2DH5 2480
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	3534.000	55.09	41.19	74.00	32.81	PK+	V	-13.9
2	4959.000	54.48	43.13	74.00	30.87	PK+	V	-11.35
3	7215.000	50.93	42.92	74.00	31.08	PK+	V	-8.01
4	9921.000	56.21	49.87	74.00	24.13	PK+	V	-6.34
5	12004.500	48.51	44.02	74.00	29.98	PK+	V	-4.49
6	17694.000	46.75	46.96	74.00	27.04	PK+	V	0.21

Mode:	2DH5 2402
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	2339.568	14.57	52.59	74.00	21.41	PK+	V	38.02
2	2390.080	12.51	50.29	74.00	23.71	PK+	V	37.78

Mode:	2DH5 2402
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	2371.600	14.46	52.28	74.00	21.72	PK+	H	37.82
2	2390.080	12.73	50.51	74.00	23.49	PK+	H	37.78

Mode:	2DH5 2480
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	2483.524	12.80	51.05	74.00	22.95	PK+	V	38.25
2	2483.672	14.27	52.52	74.00	21.48	PK+	V	38.25
3	2533.548	14.61	52.80	74.00	21.20	PK+	V	38.19

Mode:	2DH5 2480
Power:	DC 3.7V
TE:	Big
Date	2023/10/23
T/A/P	24.1℃/53%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)	Det.	Pol.	Corr. (dB)
1	2483.524	11.63	49.88	74.00	24.12	PK+	H	38.25
2	2491.960	13.67	51.91	74.00	22.09	PK+	H	38.24

Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	2.24	21	Pass
NVNT	1-DH5	2441	Ant1	2.31	21	Pass
NVNT	1-DH5	2480	Ant1	2.09	21	Pass
NVNT	2-DH5	2402	Ant1	3.02	21	Pass
NVNT	2-DH5	2441	Ant1	3.08	21	Pass
NVNT	2-DH5	2480	Ant1	2.84	21	Pass

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Antenna Gain （dBi）	E.i.r.p (dBm)	Limit (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	2.24	0	2.24	36.02	Pass
NVNT	1-DH5	2441	Ant1	2.31	0	2.31	36.02	Pass
NVNT	1-DH5	2480	Ant1	2.09	0	2.09	36.02	Pass
NVNT	2-DH5	2402	Ant1	3.02	0	3.02	36.02	Pass
NVNT	2-DH5	2441	Ant1	3.08	0	3.08	36.02	Pass
NVNT	2-DH5	2480	Ant1	2.84	0	2.84	36.02	Pass

Test Graphs

Power NVNT 1-DH5 2402MHz Ant1



Date: 21.OCT.2023 15:57:30

Power NVNT 1-DH5 2441MHz Ant1



Date: 21.OCT.2023 15:58:43

Power NVNT 1-DH5 2480MHz Ant1



Date: 21.OCT.2023 15:59:44

Power NVNT 2-DH5 2402MHz Ant1



Date: 21.OCT.2023 16:03:34

Power NVNT 2-DH5 2441MHz Ant1



Date: 21.OCT.2023 16:02:33

Power NVNT 2-DH5 2480MHz Ant1



Date: 21.OCT.2023 16:00:58

-20dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH5	2402	Ant1	1.007	0	Pass
NVNT	1-DH5	2441	Ant1	1.023	0	Pass
NVNT	1-DH5	2480	Ant1	1.027	0	Pass
NVNT	2-DH5	2402	Ant1	1.285	0	Pass
NVNT	2-DH5	2441	Ant1	1.314	0	Pass
NVNT	2-DH5	2480	Ant1	1.316	0	Pass

Test Graphs

-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2480MHz Ant1



Date: 21.OCT.2023 16:00:06

-20dB Bandwidth NVNT 2-DH5 2402MHz Ant1



Date: 21.OCT.2023 16:04:14

-20dB Bandwidth NVNT 2-DH5 2441MHz Ant1



Date: 21.OCT.2023 16:02:55

-20dB Bandwidth NVNT 2-DH5 2480MHz Ant1



Date: 21.OCT.2023 16:01:19

Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH5	2402	Ant1	0.888
NVNT	1-DH5	2441	Ant1	0.905
NVNT	1-DH5	2480	Ant1	0.913
NVNT	2-DH5	2402	Ant1	1.186
NVNT	2-DH5	2441	Ant1	1.198
NVNT	2-DH5	2480	Ant1	1.215

Test Graphs

OBW NVNT 1-DH5 2402MHz Ant1



OBW NVNT 1-DH5 2441MHz Ant1



OBW NVNT 1-DH5 2480MHz Ant1



Date: 21.OCT.2023 15:59:55

OBW NVNT 2-DH5 2402MHz Ant1



Date: 21.OCT.2023 16:04:05

OBW NVNT 2-DH5 2441MHz Ant1



Date: 21.OCT.2023 16:02:45

OBW NVNT 2-DH5 2480MHz Ant1



Date: 21.OCT.2023 16:01:09

Carrier Frequencies Separation

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	Ant1	2402.054	2403.052	0.998	0.671	Pass
NVNT	1-DH5	Ant1	2440.986	2441.998	1.012	0.682	Pass
NVNT	1-DH5	Ant1	2479.052	2480.012	0.96	0.685	Pass
NVNT	2-DH5	Ant1	2401.986	2402.996	1.01	0.857	Pass
NVNT	2-DH5	Ant1	2440.986	2441.996	1.01	0.876	Pass
NVNT	2-DH5	Ant1	2478.986	2479.984	0.998	0.877	Pass

Test Graphs

CFS NVNT 1-DH5 2402MHz Ant1



CFS NVNT 1-DH5 2441MHz Ant1



CFS NVNT 1-DH5 2480MHz Ant1



CFS NVNT 2-DH5 2402MHz Ant1



CFS NVNT 2-DH5 2441MHz Ant1



CFS NVNT 2-DH5 2480MHz Ant1



Number of Hopping Channel

Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH5	Ant1	79	15	Pass
NVNT	2-DH5	Ant1	79	15	Pass

Test Graphs

Hopping No. NVNT 1-DH5 2402MHz Ant1



Hopping No. NVNT 2-DH5 2402MHz Ant1



Dwell Time

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH5	2402	Ant1	2.888	311.904	108	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.887	314.683	109	31600	400	Pass
NVNT	1-DH5	2480	Ant1	2.887	306.022	106	31600	400	Pass
NVNT	2-DH5	2402	Ant1	2.893	289.3	100	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.893	303.765	105	31600	400	Pass
NVNT	2-DH5	2480	Ant1	2.892	277.632	96	31600	400	Pass

Test Graphs

Dwell NVNT 1-DH5 2402MHz Ant1 One Burst



Dwell NVNT 1-DH5 2402MHz Ant1 Accumulated



Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



Date: 21.OCT.2023 16:21:45

Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated



Date: 21.OCT.2023 16:22:19

Dwell NVNT 1-DH5 2480MHz Ant1 One Burst



Date: 21.OCT.2023 16:23:13

Dwell NVNT 1-DH5 2480MHz Ant1 Accumulated



Date: 21.OCT.2023 16:23:46

Dwell NVNT 2-DH5 2402MHz Ant1 One Burst



Date: 21.OCT.2023 16:08:16

Dwell NVNT 2-DH5 2402MHz Ant1 Accumulated



Date: 21.OCT.2023 16:08:50

Dwell NVNT 2-DH5 2441MHz Ant1 One Burst



Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated



Dwell NVNT 2-DH5 2480MHz Ant1 One Burst



Dwell NVNT 2-DH5 2480MHz Ant1 Accumulated



Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	No-Hopping	-53.84	-20	Pass
NVNT	1-DH5	2480	Ant1	No-Hopping	-54.76	-20	Pass
NVNT	2-DH5	2402	Ant1	No-Hopping	-51.56	-20	Pass
NVNT	2-DH5	2480	Ant1	No-Hopping	-54.55	-20	Pass

Test Graphs

Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref



Date: 21.OCT.2023 15:57:57

Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40195 GHz	1.74 dBm		
M2		1	2.4 GHz	-54.82 dBm		
M3		1	2.4 GHz	-54.82 dBm		
M4		1	2.3819 GHz	-52.35 dBm		

Date: 21.OCT.2023 15:58:00

Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47985 GHz	1.53 dBm		
M2		1	2.4835 GHz	-57.62 dBm		
M3		1	2.5 GHz	-53.70 dBm		
M4		1	2.4962 GHz	-53.06 dBm		

Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Ref



Date: 21.OCT.2023 16:04:20

Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40205 GHz	0.40 dBm		
M2		1	2.4 GHz	-56.18 dBm		
M3		1	2.4 GHz	-56.18 dBm		
M4		1	2.3832 GHz	-52.00 dBm		

Date: 21.OCT.2023 16:04:23

Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Ref



Date: 21.OCT.2023 16:01:24

Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47995 GHz	1.26 dBm		
M2		1	2.4835 GHz	-57.41 dBm		
M3		1	2.5 GHz	-54.28 dBm		
M4		1	2.4988 GHz	-52.80 dBm		

Date: 21.OCT.2023 16:01:27

Band Edge(Hopping)

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	Hopping	-53.22	-20	Pass
NVNT	1-DH5	2480	Ant1	Hopping	-52.82	-20	Pass
NVNT	2-DH5	2402	Ant1	Hopping	-53.74	-20	Pass
NVNT	2-DH5	2480	Ant1	Hopping	-52.92	-20	Pass

Test Graphs

Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Ref



Date: 21.OCT.2023 16:20:20

Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40595 GHz	1.91 dBm		
M2		1	2.4 GHz	-52.61 dBm		
M3		1	2.4 GHz	-52.61 dBm		
M4		1	2.3971 GHz	-51.29 dBm		

Date: 21.OCT.2023 16:20:44

Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Ref



Date: 21.OCT.2023 16:09:31

Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40215 GHz	1.64 dBm		
M2		1	2.4 GHz	-54.18 dBm		
M3		1	2.4 GHz	-54.18 dBm		
M4		1	2.3817 GHz	-51.75 dBm		

Date: 21.OCT.2023 16:09:56

Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Ref



Date: 21.OCT.2023 16:16:06

Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47605 GHz	0.24 dBm		
M2		1	2.4835 GHz	-53.85 dBm		
M3		1	2.5 GHz	-55.38 dBm		
M4		1	2.4952 GHz	-51.01 dBm		

Date: 21.OCT.2023 16:16:20

Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	-48.16	-20	Pass
NVNT	1-DH5	2441	Ant1	-46.33	-20	Pass
NVNT	1-DH5	2480	Ant1	-42.78	-20	Pass
NVNT	2-DH5	2402	Ant1	-47.03	-20	Pass
NVNT	2-DH5	2441	Ant1	-46.86	-20	Pass
NVNT	2-DH5	2480	Ant1	-41.21	-20	Pass

Test Graphs

Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Ref



Date: 21.OCT.2023 15:58:06

Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40207 GHz	1.49 dBm		
M2		1	7.206017 GHz	-46.42 dBm		
M3		1	4.803423 GHz	-47.75 dBm		
M4		1	7.206017 GHz	-46.42 dBm		
M5		1	9.607728 GHz	-48.58 dBm		

Date: 21.OCT.2023 15:58:22

Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4409 GHz	1.90 dBm		
M2		1	9.763901 GHz	-44.17 dBm		
M3		1	4.881069 GHz	-44.90 dBm		
M4		1	7.322485 GHz	-46.22 dBm		
M5		1	9.763901 GHz	-44.17 dBm		

Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47972 GHz	0.26 dBm		
M2		1	4.959596 GHz	-41.26 dBm		
M3		1	4.959596 GHz	-41.26 dBm		
M4		1	7.439835 GHz	-47.76 dBm		
M5		1	9.920074 GHz	-42.60 dBm		

Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40207 GHz	-3.61 dBm		
M2		1	7.206017 GHz	-45.05 dBm		
M3		1	4.803423 GHz	-48.60 dBm		
M4		1	7.206017 GHz	-45.05 dBm		
M5		1	9.607728 GHz	-47.54 dBm		

Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4409 GHz	-2.95 dBm		
M2		1	9.763901 GHz	-45.44 dBm		
M3		1	4.881951 GHz	-46.01 dBm		
M4		1	7.322485 GHz	-49.60 dBm		
M5		1	9.763901 GHz	-45.44 dBm		

Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Emission



AC Power Line Conducted Emission



Phase: L1	Mode: 2-DH5 2441MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2625	14.07	9.81	23.88	61.35	-37.47	QP
2	0.2625	1.47	9.81	11.28	51.35	-40.07	AVG
3	0.3885	11.61	9.85	21.46	58.10	-36.64	QP
4	0.3885	3.63	9.85	13.48	48.10	-34.62	AVG
5	0.8610	21.45	10.08	31.53	56.00	-24.47	QP
6	0.8610	13.32	10.08	23.40	46.00	-22.60	AVG
7	2.5889	7.33	10.09	17.42	56.00	-38.58	QP
8	2.5889	-3.62	10.09	6.47	46.00	-39.53	AVG
9	4.9335	10.87	10.24	21.11	56.00	-34.89	QP
10	4.9335	-0.03	10.24	10.21	46.00	-35.79	AVG
11	7.4444	14.88	10.63	25.51	60.00	-34.49	QP
12	7.4444	7.01	10.63	17.64	50.00	-32.36	AVG



Phase: N	Mode: 2-DH5 2441MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1590	18.59	9.97	28.56	65.52	-36.96	QP
2	0.1590	4.09	9.97	14.06	55.52	-41.46	AVG
3	0.3840	10.50	9.93	20.43	58.19	-37.76	QP
4	0.3840	0.17	9.93	10.10	48.19	-38.09	AVG
5	0.8430	21.94	10.04	31.98	56.00	-24.02	QP
6	0.8430	9.94	10.04	19.98	46.00	-26.02	AVG
7	2.1120	8.32	10.15	18.47	56.00	-37.53	QP
8	2.1120	-4.21	10.15	5.94	46.00	-40.06	AVG
9	3.5070	9.22	10.24	19.46	56.00	-36.54	QP
10	3.5070	-2.40	10.24	7.84	46.00	-38.16	AVG
11	7.5255	14.83	10.57	25.40	60.00	-34.60	QP
12	7.5255	6.37	10.57	16.94	50.00	-33.06	AVG

APPENDIX: PHOTOGRAPHS OF TEST CONFIGURATION

AC Power Line Conducted Emission



Radiated Band edge and Spurious Emission




Global Testing Group
3m法电波暗室

END OF REPORT