

TEST REPORT

Reference No...... : WTX25X01000784W
FCC ID..... : 2BDE5-G50
Applicant..... : GUANGZHOU GEOSURV INFORMATION TECHNOLOGY Co., Ltd
Address..... : Room C401 TOPS Beidou Base No 83 Kaiyuan Avenue, Guangzhou
510700, China
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : Laser GNSS Receiver
Model No...... : G50
Standards..... : **47 CFR FCC Part 15, Subpart B**
Date of Receipt sample..... : 2025-01-02
Date of Test..... : 2025-01-02 to 2025-01-20
Date of Issue..... : 2025-01-20
Test Report Form No...... : WTX_FCC PART15B_001
Test Result..... : **Pass**

Remarks:


The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Mike Shi/ Project Engineer

Approved by:



Jason Su/ Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND OPERATION MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	11
3. CONDUCTED EMISSIONS	12
3.1 TEST PROCEDURE	12
3.2 BASIC TEST SETUP BLOCK DIAGRAM	12
3.3 ENVIRONMENTAL CONDITIONS	12
3.4 SUMMARY OF TEST RESULTS	12
4. RADIATED EMISSION	15
4.1 TEST PROCEDURE	15
4.2 BLOCK DIAGRAM OF TEST SETUP	15
4.3 TEST RECEIVER SETUP	16
4.4 CORRECTED AMPLITUDE & MARGIN CALCULATION	16
4.5 ENVIRONMENTAL CONDITIONS	16
4.6 SUMMARY OF TEST RESULTS	16
APPENDIX PHOTOGRAPHS	23

Report version

Version No.	Date of issue	Description
Rev.00	2025-01-20	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Laser GNSS Receiver
Trade Name:	GINTEC
Model No.:	G50
Adding Model(s):	G40Pro, G40Ultra, F300, G60, G60Plus
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model G50, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Rated Voltage:	Battery:DC3.6V
Battery Capacity:	13200mAh
Rated Power:	/
Power Adapter Model:	MODEL:TYPE-C45IC Input: 100-240V~ 50/60Hz 1.3A Output: DC5.0V3.0A/9.0V3.0A/12.0V/3.0A/15.0V3.0A/20.0V2.25A MAX:45.0W
Lowest Internal Frequency:	24MHz
Highest Internal Frequency:	2480MHz
Classification of ITE:	Class B

1.2 Test Standards

The tests were performed according to following standards:

47 CFR FCC Part 15, Subpart B:Unintentional Radiators.

ANSI C63.4-2014:American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

ANSI C63.4a-2017:American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

Amendment 1:Test Site Validation

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List			
Test Mode	Description	Remark	Power Supply Mode
TM1	Charging And Normal working	Connect to the Adapter	AC120V 60Hz for adapter
TM2	Downloading	Connect to the Notebook	Battery:DC3.6V

EUT Cable List and Details				
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite	With / Without Chip
USB-C to USB-C Cable	1.5	Unshielded	Without Ferrite	Without Chip
USB-A to USB-C Cable	1.5	Unshielded	Without Ferrite	Without Chip

Special Cable List and Details				
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite	With / Without Chip
USB-A to USB-C Cable	1.0	Shielded	Without Ferrite	Without Chip

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Computer	Lenovo	L13 Yoga	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Radiated Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
☐ Chamber A:Below 1GHz					
Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2024-02-24	2025-02-23
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
Amplifier	HP	8447F	2805A03475	2024-02-24	2025-02-23
Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
Trilog Broadband Antenna	Schwarz beck	VULB9163	9163-333	2024-02-24	2025-02-23
Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
☐ Chamber A:Above 1GHz					
Amplifier	C&D	PAP-1G18	2002	2024-02-27	2025-02-26
Horn Antenna	ETS	3117	00086197	2024-02-26	2025-02-25
Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14
Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14
Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14
☐ Chamber B:Below 1GHz					
EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2024-02-24	2025-02-23
Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
Amplifier	Agilent	8447D	2944A10457	2024-02-24	2025-02-23
Coaxial Cable	/	1.5MRFC-LWB3	/	2024-07-03	2025-07-02
Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
☒ Chamber C:Below 1GHz					
EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
Amplifier	HP	8447F	2944A03869	2024-02-24	2025-02-23
Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
☒ Chamber C:Above 1GHz					

EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
Amplifier	Tonscend	TAP010180 50	AP22E80623 5	2024-02-27	2025-02-26
DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
Coaxial Cable	/	RC-18G-N- M	/	2024-07-03	2025-07-02
Coaxial Cable	/	RC-18G-N- M	/	2024-07-03	2025-07-02
Coaxial Cable	/	RC-18G-N- M	/	2024-07-03	2025-07-02
☐ Conducted Room 1#					
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2024-02-24	2025-02-23
EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2024-12-08	2025-12-07
AC LISN	Schwarz beck	NSLK8126	8126-279	2024-02-24	2025-02-23
Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
Coaxial Cable	/	6MRFC-DP	/	2024-07-03	2025-07-02
☒ Conducted Room 2#					
EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2024-02-24	2025-02-23
LISN	Rohde & Schwarz	ENV 216	100097	2024-02-24	2025-02-23
Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission A)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission B)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission C)	Farad	EZ-EMC	RA-03A1-2 (1.1.4.2)
EMI Test Software (Conducted Emission Room 1#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3
EMI Test Software (Conducted Emission Room 2#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

Description of Test	Result
§15.107(a) Conducted Emission	Compliant
§15.109(a) Radiated Emission	Compliant


N/A: not applicable

3. Conducted Emissions

3.1 Test Procedure

The test is conducted under the description of ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

3.2 Basic Test Setup Block Diagram




3.3 Environmental Conditions

Temperature:	23.5 °C
Relative Humidity:	54 %
ATM Pressure:	1014 mbar

3.4 Summary of Test Results


Please find the results below:

Test mode:	TM1	Polarity:	Line
------------	-----	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	39.99	9.76	49.75	65.99	-16.24	QP
2	0.1580	24.07	9.73	33.80	55.56	-21.76	AVG
3	0.3140	31.99	9.65	41.64	59.86	-18.22	QP
4*	0.3260	25.84	9.65	35.49	49.55	-14.06	AVG
5	1.0300	18.20	9.67	27.87	46.00	-18.13	AVG
6	1.3940	27.89	9.65	37.54	56.00	-18.46	QP
7	4.9260	24.20	9.71	33.91	56.00	-22.09	QP
8	5.0980	14.83	9.71	24.54	50.00	-25.46	AVG
9	13.7260	24.17	9.93	34.10	60.00	-25.90	QP
10	13.7260	14.11	9.93	24.04	50.00	-25.96	AVG
11	24.5740	26.98	10.09	37.07	60.00	-22.93	QP
12	24.5740	23.40	10.09	33.49	50.00	-16.51	AVG

Test mode:	TM1	Polarity:	Neutral
------------	-----	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1580	38.04	9.73	47.77	65.56	-17.79	QP
2	0.1860	24.79	9.62	34.41	54.21	-19.80	AVG
3	0.3740	18.70	9.68	28.38	48.41	-20.03	AVG
4	0.4420	25.12	9.71	34.83	57.02	-22.19	QP
5	1.4860	22.92	9.65	32.57	56.00	-23.43	QP
6	1.4860	16.24	9.65	25.89	46.00	-20.11	AVG
7	2.9700	11.63	9.62	21.25	46.00	-24.75	AVG
8	4.1180	20.87	9.67	30.54	56.00	-25.46	QP
9	8.7299	7.28	9.83	17.11	50.00	-32.89	AVG
10	13.5140	18.88	9.93	28.81	60.00	-31.19	QP
11	24.5780	26.63	10.09	36.72	60.00	-23.28	QP
12	24.5780	21.73	10.09	31.82	50.00	-18.18	AVG


4. RADIATED EMISSION

4.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

4.2 Block Diagram of Test Setup



4.3 Test Receiver Setup

Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10kHz,	RBW=120kHz,	RBW=1MHz,
VBW =30kHz	VBW=300kHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

4.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Correct} \\ \text{Correct} = \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit for a Class B device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15.109(a) Limit}$$

4.5 Environmental Conditions


Temperature:	22.5 °C
Relative Humidity:	52 %
ATM Pressure:	1011 mbar

4.6 Summary of Test Results

Please find the results below:


Below 1GHz

Test mode:	TM1	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	48.3780	28.39	-7.71	20.68	40.00	-19.32	-	-	QP
2	110.8581	33.59	-10.98	22.61	43.50	-20.89	-	-	QP
3	123.1815	35.12	-9.79	25.33	43.50	-18.17	-	-	QP
4	172.5976	35.60	-8.68	26.92	43.50	-16.58	-	-	QP
5	455.1888	32.20	-5.15	27.05	46.00	-18.95	-	-	QP
6	986.0440	31.26	3.44	34.70	54.00	-19.30	-	-	QP

Test mode:	TM1	Polarity:	Vertical
------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.7616	34.96	-8.85	26.11	40.00	-13.89	-	-	QP
2	49.7571	37.19	-7.59	29.60	40.00	-10.40	-	-	QP
3	123.1813	37.20	-9.79	27.41	43.50	-16.09	-	-	QP
4	172.5974	40.25	-8.68	31.57	43.50	-11.93	-	-	QP
5	464.8867	31.85	-5.06	26.79	46.00	-19.21	-	-	QP
6	893.6556	31.28	2.02	33.30	46.00	-12.70	-	-	QP

Test mode:	TM2	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	51.1756	41.51	-7.72	33.79	40.00	-6.21	-	-	QP
2	124.0501	45.24	-9.73	35.51	43.50	-7.99	-	-	QP
3	146.8391	40.50	-8.31	32.19	43.50	-11.31	-	-	QP
4	236.7926	51.23	-10.36	40.87	46.00	-5.13	-	-	QP
5	268.7212	50.12	-8.92	41.20	46.00	-4.80	-	-	QP
6	718.7246	37.58	-0.62	36.96	46.00	-9.04	-	-	QP


Test mode:	TM2	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	51.1756	42.40	-7.72	34.68	40.00	-5.32	-	-	QP
2	124.9249	42.42	-9.67	32.75	43.50	-10.75	-	-	QP
3	235.1346	48.76	-10.55	38.21	46.00	-7.79	-	-	QP
4	268.7212	44.27	-8.92	35.35	46.00	-10.65	-	-	QP
5	481.5112	40.63	-4.94	35.69	46.00	-10.31	-	-	QP
6	624.4897	39.05	-1.78	37.27	46.00	-8.73	-	-	QP


Above 1GHz

Test mode:	TM1(worst case)	Polarity:	Horizontal
------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	1477.946	55.21	-22.92	32.29	74.00	-41.71	-	-	peak
2	1516.423	44.15	-22.80	21.35	54.00	-32.65	-	-	AVG
3	1970.926	44.23	-20.50	23.73	54.00	-30.27	-	-	AVG
4	2509.521	54.24	-19.23	35.01	74.00	-38.99	-	-	peak
5	3469.198	43.51	-14.95	28.56	54.00	-25.44	-	-	AVG
6	3614.830	54.99	-14.90	40.09	74.00	-33.91	-	-	peak
7	6732.903	54.02	-7.97	46.05	74.00	-27.95	-	-	peak
8	7124.563	42.66	-7.11	35.55	54.00	-18.45	-	-	AVG
9	9212.464	54.86	-5.81	49.05	74.00	-24.95	-	-	peak
10	9599.191	42.37	-5.30	37.07	54.00	-16.93	-	-	AVG
11	11973.627	52.22	-2.47	49.75	74.00	-24.25	-	-	peak
12	12035.332	41.36	-2.55	38.81	54.00	-15.19	-	-	AVG

Test mode:	TM1(worst case)	Polarity:	Vertical
------------	-----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	1516.423	44.21	-22.80	21.41	54.00	-32.59	-	-	AVG
2	1539.989	54.66	-22.66	32.00	74.00	-42.00	-	-	peak
3	1991.293	44.14	-20.40	23.74	54.00	-30.26	-	-	AVG
4	2264.352	54.38	-19.78	34.60	74.00	-39.40	-	-	peak
5	3523.109	54.59	-14.78	39.81	74.00	-34.19	-	-	peak
6	3633.458	43.48	-14.93	28.55	54.00	-25.45	-	-	AVG
7	5830.376	54.67	-9.99	44.68	74.00	-29.32	-	-	peak
8	5860.422	43.02	-9.91	33.11	54.00	-20.89	-	-	AVG
9	7936.657	54.25	-6.77	47.48	74.00	-26.52	-	-	peak
10	7977.558	42.89	-6.63	36.26	54.00	-17.74	-	-	AVG
11	11912.238	41.51	-2.60	38.91	54.00	-15.09	-	-	AVG
12	11973.627	53.05	-2.47	50.58	74.00	-23.42	-	-	peak

Remark: '-' Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****