Shenzhen Huatongwei International Inspection Co.,Ltd.
Huatongwei 101, No.006, Keji south 12th Road, High-tech zone community, Yuehai Street,
Nanshan District, Shenzhen, Guangdong, China
Phone:86-755-26715499 E-mail: cs@szhtw.com.cn Website:http://www.szhtw.com.cn

TEST REPORT

For Bluetooth-EDR

Report Verification:

Report No. ..... :	**CHTEW24010015**
Project No.....:	**2BDG9-697083172PF27**
FCC ID ..... :	**Shenzhen Insighters Medical Technology Co.,Ltd**
Applicant's name ..... :	The 13th floor of Hengtemei Building, Ganli Road No.3,518000 Shenzhen, Guangdong, PEOPLE'S REPUBLIC OF CHINA
Address.....:	**Insight Workstation**
Product Name ..... :	insighters Trust in sight
Trade Mark .....:	iS-PF1
Model No. .....:	iS-PF2
Listed Model(s) .....:	**2BDG9-697083172PF27**
Standard ..... :	**FCC CFR Title 47 Part 15 Subpart C § 15.247**
Date of receipt of test sample.....:	Oct.24, 2023
Date of testing.....:	Oct.24, 2023- Jan.10, 2024
Date of issue.....:	Jan.11, 2024
Result..... .....:	**PASS**

Compiled by (Position+Printed name+Signature):	File administrators Kiki Kong	Kiki Kong
Supervised by (Position+Printed name+Signature):	Project Engineer Kiki Kong	Kiki Kong
Approved by (Position+Printed name+Signature):	RF Manager Xu yang	Xu. Yang

Testing Laboratory Name ..... :	**Shenzhen Huatongwei International Inspection Co., Ltd.**
Address.....:	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

1.	**TEST STANDARDS AND REPORT VERSION**	**3**
1.1.	**Test Standards**	**3**
1.2.	**Report version**	**3**
2.	**TEST DESCRIPTION**	**4**
3.	**SUMMARY**	**5**
3.1.	**Client Information**	**5**
3.2.	**Product Description**	**5**
3.3.	**Radio Specification Description**	**5**
3.4.	**Testing Laboratory Information**	**6**
4.	**TEST CONFIGURATION**	**7**
4.1.	**Test frequency list**	**7**
4.2.	**Descriptions of Test mode**	**7**
4.3.	**Test mode**	**7**
4.4.	**Test sample information**	**8**
4.5.	**Support unit used in test configuration and system**	**8**
4.6.	**Testing environmental condition**	**8**
4.7.	**Statement of the measurement uncertainty**	**9**
4.8.	**Equipment Used during the Test**	**10**
5.	**TEST CONDITIONS AND RESULTS**	**12**
5.1.	**Antenna Requirement**	**12**
5.2.	**AC Conducted Emission**	**13**
5.3.	**Peak Output Power**	**15**
5.4.	**20 dB Bandwidth**	**16**
5.5.	**99% Occupied Bandwidth**	**17**
5.6.	**Carrier Frequencies Separation**	**18**
5.7.	**Hopping Channel Number**	**19**
5.8.	**Dwell Time**	**20**
5.9.	**Duty Cycle Correction Factor (DCCF)**	**21**
5.10.	**Pseudorandom Frequency Hopping Sequence**	**22**
5.11.	**Conducted Band edge and Spurious Emission**	**23**
5.12.	**Radiated Band edge Emission**	**25**
5.13.	**Radiated Spurious Emission**	**27**
6.	**TEST SETUP PHOTOS**	**32**
7.	**EXTERNAL AND INTERNAL PHOTOS**	**34**
8.	**APPENDIX REPORT**	**34**

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

– FCC CFR Title 47 Part 15 Subpart C § 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

– ANSI C63.10:2020: American National Standard for Testing Unlicensed Wireless Devices

– KDB 558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2024-01-11	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result	Test Engineer
5.1	Antenna Requirement	15.203/15.247 (c)	PASS	Xiangyuwei
5.2	AC Conducted Emission	15.207	PASS	Junman Wang
5.3	Peak Output Power	15.247 (b)(1)	PASS	Xiangyuwei
5.4	20 dB Bandwidth	15.247 (a)(1)	PASS	Xiangyuwei
5.5	99% Occupied Bandwidth	-	PASS*1	Xiangyuwei
5.6	Carrier Frequency Separation	15.247 (a)(1)	PASS	Xiangyuwei
5.7	Hopping Channel Number	15.247 (a)(1)	PASS	Xiangyuwei
5.8	Dwell Time	15.247 (a)(1)	PASS	Xiangyuwei
5.9	Duty Cycle Correction Factor	-	PASS*1	Xiangyuwei
5.10	Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	PASS	Xiangyuwei
5.11	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS	Xiangyuwei
5.12	Radiated Band Edge Emission	15.205/15.209	PASS	Yifan Wang
5.13	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS	Yifan Wang

Note:

– The measurement uncertainty is not included in the test result.

– *1: No requirement on standard, only report these test data.

3. SUMMARY

3.1. Client Information

Applicant:	Shenzhen Insighters Medical Technology Co.,Ltd
Address:	The 13th floor of Hengtemei Building, Ganli Road No.3,518000 Shenzhen, Guangdong, PEOPLE'S REPUBLIC OF CHINA
Manufacturer:	Shenzhen Insighters Medical Technology Co.,Ltd
Address:	The 13th floor of Hengtemei Building, Ganli Road No.3,518000 Shenzhen, Guangdong, PEOPLE'S REPUBLIC OF CHINA

3.2. Product Description

Main unit information:	
Product Name:	Insight Workstation
Trade Mark:	insighters Trust in sight
Model No.:	iS-PF1
Listed Model(s):	iS-PF2
Power supply:	DC 7.4V from Battery
Hardware version:	1.0.82
Software version:	PF1V1.0.0.118
Accessory unit information:	
Battery information:	Model:18650-2S5P 7.4V 13000mAh 96.2Wh
Adapter information:	Model:PH50-112 Input:100-240V a.c., 50/60Hz 1.4-0.6A Output:12Vd.c., 4.0A

3.3. Radio Specification Description

Bluetooth version:	V5.0
Support function:	EDR
Modulation:	GFSK, π/4DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PCB Antenna
Antenna gain:	2.79dBi

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China	
Contact information:	Phone: 86-755-26715499 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn	
Qualifications	Type	Accreditation Number
	FCC Registration Number	762235
	FCC Designation Number	CN1181

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

Channel	Frequency (MHz)
00	**2402**
01	2403
⋮	⋮
39	**2441**
⋮	⋮
77	2479
78	**2480**

4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates and recorded the RF output power in the clause 5.3

Note:

1) The manufacturer declare that the maximum power value of the product is set as a default value in the enter test mode software.
2) All the test data for each data rate were verified, found 8DPSK Modulation which is worse case mode

4.3. Test mode

For RF test items:			
The engineering test program was provided and enabled to make EUT continuous transmitting.			
Test Item	Modulation / Data Rate		
	GFSK 1Mbps	π/4DQPSK 2Mbps	8DPSK 3Mbps
Conducted test item	✓	✓	✓
Radiated test item	-	-	✓
Remark: – For radiated test item, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests. – The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.			

4.4. Test sample information

Test item	HTW sample no.
RF Conducted test items	Refer to the description in the appendix report
RF Radiated test items	YPHT23070163005
EMI test items	YPHT23070163001

Note:

RF Conducted test items: Peak Output Power, 20 dB Bandwidth, 99% Occupied Bandwidth, Carrier Frequency Separation, Hopping Channel Number, Dwell Time, Duty Cycle Correction Factor, Pseudorandom Frequency Hopping Sequence, Conducted Band Edge and Spurious Emission

RF Radiated test items: Radiated Band Edge Emission, Radiated Spurious Emission

EMI test items: AC Conducted Emission

4.5. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?			
✓ No			
Item	Equipment	Trade Name	Model No.
1			
2			

4.6. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.7. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	AC Conducted Emission	3.21dB
2	Peak Output Power	1.07
3	Power Spectral Density	1.07
4	6dB Bandwidth	0.002%
5	99% Occupied Bandwidth	0.002%
6	Duty cycle	-
7	Conducted Band Edge and Spurious Emission	1.68dB
8	Radiated Band Edge Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz
9	Radiated Spurious Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.8. Equipment Used during the Test

● RF Conducted test item							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	HTWE0242	FSV40	100048	2023/08/22	2024/08/21
●	Signal & Spectrum Analyzer	R&S	HTWE0262	FSW26	103440	2023/08/22	2024/08/21
●	Vector signal generator	R&S	HTWE0244	SMBV100A	260790	2023/05/23	2024/05/22
●	Test software	Tonscend	N/A	JS1120	N/A	N/A	N/A

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2023/8/22	2024/8/21
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2023/8/18	2024/8/17
●	Protection Network	SCHWARZBECK	HTWE0567	VTSD9561FN	00899	2023/8/18	2024/8/17
●	ISN	FCC	HTWE0148	FCC-TLISN-T2-02	20371	2023/8/18	2024/8/17
●	ISN	FCC	HTWE0150	FCC-TLISN-T8-02	20375	2023/8/18	2024/8/17
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated Emission – 9kHz~30MHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/4/6	2026/4/5
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2023/8/22	2024/8/21
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2021/4/6	2024/4/5
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated Emission - 30MHz~1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/4/6	2026/4/5
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2023/8/22	2024/8/21
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2023/2/22	2026/2/21
●	Pre-Amplifer	SCHWARZBECK	HTWE0295	BBV 9742	/	2023/5/25	2024/5/24
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated emission-Above 1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11121	2023/4/17	2026/4/16
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2023/8/22	2024/8/21
●	Horn Antenna	SCHWARZBECK	HTWE0126	BBHA 9120D	1011	2023/2/14	2026/2/13
●	Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2023/2/20	2026/2/19
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2023/5/25	2024/5/24
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

REQUIREMENT

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

The antenna type is a PCB antenna, Refer to the below antenna photo.



5.2. AC Conducted Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

Test Line:	L



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.1715	57.03	---	64.89	7.86	L1	10.9
0.1780	56.71	---	64.58	7.87	L1	10.9
0.1795	---	50.86	54.51	3.65	L1	10.9
0.2315	---	31.19	52.40	21.21	L1	10.9
0.2955	---	37.23	50.37	13.14	L1	10.9
0.4155	---	36.37	47.54	11.17	L1	10.9
4.4075	---	29.85	46.00	16.15	L1	11.1
13.5115	35.09	---	60.00	24.91	L1	11.3
13.5195	37.38	---	60.00	22.62	L1	11.3
13.5365	---	23.59	50.00	26.41	L1	11.3
13.6195	32.67	---	60.00	27.33	L1	11.3
13.6475	29.73	---	60.00	30.27	L1	11.3

Test Line:	N



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.1715	---	51.76	54.89	3.13	N	10.7
0.1780	56.59	---	64.58	7.99	N	10.7
0.2195	40.62	---	62.84	22.22	N	10.7
0.2355	---	33.86	52.25	18.39	N	10.7
0.2995	---	29.61	50.26	20.65	N	10.7
0.3995	---	35.51	47.86	12.35	N	10.6
4.4395	---	29.08	46.00	16.92	N	10.8
13.3275	27.80	---	60.00	32.20	N	11.0
13.4715	28.77	---	60.00	31.23	N	11.0
13.4955	33.62	---	60.00	26.38	N	11.0
13.6315	32.56	---	60.00	27.44	N	11.0
13.6355	---	22.07	50.00	27.93	N	11.0

5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1):
For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the pathloss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
   Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
   RBW≥ the 20 dB bandwidth of the emission being measured, VBW≥RBW
   Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST DATA

Refer to the appendix report

5.4. 20 dB Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
   Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
   RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW
   Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST DATA

Refer to the appendix report

5.5. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output andthe spectrum analyzer).
   Center Frequency =channel center frequency
   Span≥1.5 x OBW
   RBW = 1%~5%OBW
   VBW ≥ 3 × RBW
   Sweep time= auto couple
   Detector = Peak
   Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST DATA

Refer to the appendix report

5.6. Carrier Frequencies Separation

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):
Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively,
Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
   Span = wide enough to capture the peaks of two adjacent channels
   RBW ≥ 1% of the span, VBW ≥ RBW
   Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE
Refer to the clause 4.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

TEST DATA
Refer to the appendix report

5.7. Hopping Channel Number

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):
Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
   Span = the frequency band of operation
   RBW ≥ 1% of the span, VBW ≥ RBW
   Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE
Refer to the clause 4.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

TEST DATA
Refer to the appendix report

5.8. Dwell Time

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):The average time of occupancy on any channel shall not be greater than 0.4 seconds within a pe-riod of 0.4 seconds multiplied by the number of hopping channels employed.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
   Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW ≥ RBW
   Sweep = as necessary to capture the entire dwell time per hopping channel,
   Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE

Refer to the clause 4.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

TEST DATA

Refer to the appendix report

5.9. Duty Cycle Correction Factor (DCCF)

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
   Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW ≥ RBW
   Sweep = as necessary to capture the entire dwell time per hopping channel,
   Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE

Refer to the clause 4.3

TEST DATA

Refer to the appendix report

5.10. Pseudorandom Frequency Hopping Sequence

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):Frequency hopping systems shall have hopping channel carrier fre-quencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Al-ternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier fre-quencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to chan-nel frequencies that are selected at the system hopping rate from a pseudo ran-domly ordered list of hopping fre-quencies. Each frequency must be used equally on the average by each trans-mitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their cor-responding transmitters and shall shift frequencies in synchronization with the transmitted signals.

TEST RESULTS

The pseudorandom frequency hopping sequence may be generated in a nice-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage.And the result is fed back to the input of the friststage.The sequence begins with the frist one of 9 consecutive ones,forexample:the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An explame of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.
The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

5.11. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Emission level measurement

   Set the center frequency and span to encompass frequency range to be measured

   RBW = 100 kHz, VBW ≥ 3 x RBW

   Detector = peak, Sweep time = auto couple, Trace mode = max hold

   Allow trace to fully stabilize

   Use the peak marker function to determine the maximum amplitude level.
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST DATA

Refer to the appendix report

5.12. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT waspositioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. Thisis repeated for both horizontal and vertical polarization of the antenna. In order to find themaximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
   a) Span shall wide enough to fully capture the emission being measured
   b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
   c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

      For average measurement: use duty cycle correction factor method (DCCF)

      Averager level = Peak level + DCCF

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

Note:

1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
2) Over Limit = Level– Limit
3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

Test channel:	CH00	Polarity	Horizontal

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	48.13	27.86	4.01	41.80	38.20	74.00	-35.80	Peak
2	2389.93	57.38	27.54	4.31	41.80	47.43	74.00	-26.57	Peak
3	2390.03	53.22	27.54	4.31	41.80	43.27	74.00	-30.73	Peak

Test channel:	CH00	Polarity	Vertical

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	49.09	27.86	4.01	41.80	39.16	74.00	-34.84	Peak
2	2389.83	63.45	27.54	4.31	41.80	53.50	74.00	-20.50	Peak
3	2390.03	61.22	27.54	4.31	41.80	51.27	74.00	-22.73	Peak

Test channel:	CH78	Polarity	Horizontal

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	55.50	27.33	4.18	41.80	45.21	74.00	-28.79	Peak
2	2500.00	55.92	27.30	4.19	41.80	45.61	74.00	-28.39	Peak

Test channel:	CH78	Polarity	Vertical

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	50.24	27.33	4.18	41.80	39.95	74.00	-34.05	Peak
2	2484.60	54.22	27.33	4.18	41.80	43.93	74.00	-30.07	Peak
3	2500.00	55.12	27.30	4.19	41.80	44.81	74.00	-29.19	Peak

5.13. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak

Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.

Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION

- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
   a) Span shall wide enough to fully capture the emission being measured;
   b) Below 1 GHz:

      RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

      If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
   c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

      For average measurement: use duty cycle correction factor method (DCCF)

      Averager level = Peak level + DCCF

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

Note:

1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
2) Over Limit = Level– Limit
3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

For 9 kHz ~ 30 MHz

The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

For 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH39 which it was worst case, so only show the worst case's data on this report.

Polarization:	Horizontal



Final_Result

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
349.9788	40.06	46.00	5.94	100.0	H	89.0	-5.4
399.9338	42.69	46.00	3.31	100.0	H	42.0	-4.5
450.0100	34.83	46.00	11.17	100.0	H	11.0	-3.4
474.9875	33.44	46.00	12.56	100.0	H	358.0	-3.0
945.3163	40.13	46.00	5.87	100.0	H	309.0	7.1
948.4688	42.06	46.00	3.94	300.0	H	0.0	7.1

Polarization:	Vertical



Final_Result

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
124.9388	36.85	43.50	6.65	100.0	V	133.0	-13.5
400.0550	42.91	46.00	3.09	100.0	V	176.0	-4.5
450.0100	33.80	46.00	12.20	100.0	V	184.0	-3.4
599.9963	38.31	46.00	7.69	100.0	V	184.0	1.1
945.1950	38.67	46.00	7.33	100.0	V	289.0	7.1
948.4688	43.60	46.00	2.40	100.0	V	270.0	7.1

For 1 GHz ~ 25 GHz

Test channel	CH00	Polarity	Horizontal

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1124.74	63.81	25.25	2.72	42.40	49.38	68.20	-18.82	Peak
2	1625.13	63.79	25.05	3.40	42.20	50.04	68.20	-18.16	Peak
3	4278.06	53.40	30.11	5.78	41.40	47.89	74.00	-26.11	Peak
4	5406.96	51.58	31.63	6.50	40.88	48.83	74.00	-25.17	Peak

Test channel	CH00	Polarity	Vertical

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1124.74	62.24	25.25	2.72	42.40	47.81	68.20	-20.39	Peak
2	1499.88	63.28	25.70	3.20	42.20	49.98	68.20	-18.22	Peak
3	3419.49	54.22	28.52	5.02	41.60	46.16	74.00	-27.84	Peak
4	6001.77	45.79	32.40	6.84	40.63	44.40	74.00	-29.60	Peak

Test channel	CH39	Polarity	Horizontal

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1124.74	63.81	25.25	2.72	42.40	49.38	68.20	-18.82	Peak
2	1625.13	63.79	25.05	3.40	42.20	50.04	68.20	-18.16	Peak
3	3428.21	54.77	28.57	4.98	41.60	46.72	74.00	-27.28	Peak
4	7319.96	46.10	36.14	7.74	40.98	49.00	74.00	-25.00	Peak

Test channel	CH39	Polarity	Vertical

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1124.74	62.24	25.25	2.72	42.40	47.81	68.20	-20.39	Peak
2	1499.88	63.28	25.70	3.20	42.20	49.98	68.20	-18.22	Peak
3	3419.49	54.51	28.52	5.02	41.60	46.45	74.00	-27.55	Peak
4	6379.86	45.38	33.32	7.15	40.60	45.25	74.00	-28.75	Peak

Test channel	CH78	Polarity	Horizontal

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1124.74	63.81	25.25	2.72	42.40	49.38	68.20	-18.82	Peak
2	1625.13	63.79	25.05	3.40	42.20	50.04	68.20	-18.16	Peak
3	2995.54	55.91	28.50	4.75	41.65	47.51	74.00	-26.49	Peak
4	4785.08	47.54	31.27	5.98	41.37	43.42	74.00	-30.58	Peak

Test channel	CH78	Polarity	Vertical

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1124.74	62.24	25.25	2.72	42.40	47.81	68.20	-20.39	Peak
2	1499.88	63.28	25.70	3.20	42.20	49.98	68.20	-18.22	Peak
3	3419.49	53.31	28.52	5.02	41.60	45.25	74.00	-28.75	Peak
4	6396.13	46.93	33.38	7.22	40.61	46.92	74.00	-27.08	Peak

6. TEST SETUP PHOTOS

Radiated Emission







AC Conducted Emission

7. EXTERNAL AND INTERNAL PHOTOS

Refer to the test report No. CHTEW24010014

8. APPENDIX REPORT

APPENDIX REPORT

Project No.	SHT2307016301EW	Radio Specification	Bluetooth EDR
Test sample No.	YPHT23070163003	Model No.	iS-PF1
Start test date	2023-11-03	Finish date	2023-11-06
Temperature	24.2℃	Humidity	48%
Test Engineer	Xiangyu Wei	Auditor	Xiaodong Zhao

Appendix clause	Test item	Result
A	Peak Output Power	PASS
B	20 dB Bandwidth	PASS
C	99% Occupied Bandwidth	PASS
D	Carrier Frequencies Separation	PASS
E	Hopping Channel Number	PASS
F	Dwell Time	PASS
G	Duty Cycle Correction Factor (DCCF)	PASS
H	Band edge and Spurious Emissions(coducted)	PASS

Appendix A：Peak Output Power

Modulation type	Channel	Peak Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
GFSK	00	5.11	5.05	≤ 30.00	Pass
	39	5.65	5.61		
	78	6.15	6.09		
π/4DQPSK	00	6.64	6.61	≤ 21.00	Pass
	39	8.01	7.95		
	78	8.49	8.44		
8DPSK	00	7.05	6.99	≤ 21.00	Pass
	39	8.33	8.29		
	78	8.90	8.84		

Modulation Type:	**GFSK**
CH00	 Date: 6.NOV.2023 10:94:52
CH39	 Date: 6.NOV.2023 10:98:17
CH78	 Date: 6.NOV.2023 10:99:44

Modulation Type:	**π/4DQPSK**
CH00	 Date: 6.NOV.2023 10:22:10
CH39	 Date: 3.NOV.2023 15:27:03
CH78	 Date: 3.NOV.2023 15:28:23

Modulation Type:	**8DPSK**
CH00	 Date: 6.NOV.2023 10:11:37
CH39	 Date: 3.NOV.2023 15:31:46
CH78	 Date: 3.NOV.2023 15:33:01

Appendix B : 20 dB Bandwidth

Modulation type	Channel	20 dB Bandwidth (kHz)	Limit (kHz)	Result
GFSK	00	925.00	-	Pass
	39	925.00		
	78	925.00		
π/4DQPSK	00	1358.00	-	Pass
	39	1358.00		
	78	1360.00		
8DPSK	00	1323.00	-	Pass
	39	1313.00		
	78	1323.00		

Modulation Type:	**GFSK**
CH00	
CH39	
CH78	

Modulation Type:	**π/4DQPSK**
CH00	
CH39	
CH78	

Modulation Type:	**8DPSK**
CH00	
CH39	
CH78	

Appendix C：99% Occupied Bandwidth

Modulation type	Channel	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
GFSK	00	0.90	-	Pass
	39	0.90		
	78	0.90		
π/4DQPSK	00	1.21	-	Pass
	39	1.21		
	78	1.21		
8DPSK	00	1.20	-	Pass
	39	1.20		
	78	1.20		

Modulation Type:	**GFSK**
CH00	 Date: 6.NOV.2023 10:94:44
CH39	 Date: 6.NOV.2023 10:98:99
CH78	 Date: 6.NOV.2023 10:99:36

Modulation Type:	**π/4DQPSK**
CH00	 Date: 3.NOV.2023 15:25:02
CH39	 Date: 3.NOV.2023 15:26:55
CH78	 Date: 3.NOV.2023 15:28:15

Modulation Type:	**8DPSK**
CH00	 Date: 3.NOV.2023 15:30:07
CH39	 Date: 3.NOV.2023 15:31:38
CH78	 Date: 3.NOV.2023 15:32:53

Appendix D：Carrier Frequencies Separation

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (kHz) *	Result
GFSK	39	1.00	≥925	Pass
π/4DQPSK	39	1.00	≥907	Pass
8DPSK	39	1.00	≥882	Pass

Note:

*: GFSK limit = The maximum 20 dB Bandwidth for GFSK modulation on the appendix B.

π/4DQPSK limit = 2/3 * The maximum 20 dB Bandwidth for π/4DQPSK modulation on the appendix B.

8DPSK limit = 2/3 * The maximum 20 dB Bandwidth for 8DPSK modulation on the appendix B

GFSK	 Date: 6.NOV.2023 10:07:09
π/4DQPSK	 Date: 3.NOV.2023 14:56:04
8DPSK	 Date: 3.NOV.2023 15:00:22

Appendix E：Hopping Channel Number

Modulation type	Channel number	Limit	Result
GFSK	79	≥15.00	Pass
π/4DQPSK	79		
8DPSK	79		

GFSK	 Date: 6.NOV.2023 10:13:19
π/4DQPSK	 Date: 3.NOV.2023 15:95:18
8DPSK	 Date: 3.NOV.2023 15:96:58

Appendix F：Dwell Time

Modulation type	Packet	Burst Width [ms]	Total Hops[hop*ch]	Dwell time (Second)	Limit (Second)	Result
GFSK	DH1	0.38	316.00	0.12	≤ 0.40	Pass
	DH3	0.66	152.00	0.10		
	DH5	2.89	106.00	0.31		
π/4DQPSK	2DH1	0.39	315.00	0.12	≤ 0.40	Pass
	2DH3	1.64	146.00	0.24		
	2DH5	1.69	114.00	0.19		
8DPSK	3DH1	0.39	316.00	0.12	≤ 0.40	Pass
	3DH3	1.64	172.00	0.28		
	3DH5	2.89	112.00	0.32		

Modulation Type:	**GFSK**
DH1 Burst width	
DH1 Burst number	
DH3 Burst width	

DH3 Burst number	 Date: 3.NOV.2023 15:10:01
DH5 Burst width	 Date: 6.NOV.2023 10:13:56
DH5 Burst number	 Date: 6.NOV.2023 10:14:29

Modulation Type:	**π/4DQPSK**
2DH1 Burst width	 Date: 3.NOV.2023 15:11:56
2DH1 Burst number	 Date: 3.NOV.2023 15:12:29
2DH3 Burst width	 Date: 3.NOV.2023 15:13:04

2DH3 Burst number	 Date: 3.NOV.2023 15:13:37
2DH5 Burst width	 Date: 3.NOV.2023 15:14:11
2DH5 Burst number	 Date: 3.NOV.2023 15:14:44

Modulation Type:	**8DPSK**
3DH1 Burst width	
3DH1 Burst number	
3DH3 Burst width	

3DH3 Burst number	 Date: 3 NOV 2023 15:16:55
3DH5 Burst width	 Date: 3 NOV 2023 15:17:21
3DH5 Burst number	 Date: 3 NOV 2023 15:17:54

Appendix G：Duty Cycle Correction Factor (DCCF)

DCCF Calculate Formula					
DCCF=20 * Log(duty cycle) = 20 * Log($T_{on\ time}$ / T_{period})					
Modulation type	Test Frequency（MHz）	$T_{on\ time}$ for single burst [ms]	T_{period} [ms]	Burst Quantity	DCCF [dB]
GFSK	2441	2.87	100	1.00	-30.84
π /4 DQPSK	2441	1.68	100	1.00	-35.49
8DPSK	2441	2.88	100	2.00	-30.81

GFSK	
	
$T_{on\ time}$ for single burst	Burst Quantity
π /4 DQPSK	
	
$T_{on\ time}$ for single burst	Burst Quantity
8DPSK	
	
$T_{on\ time}$ for single burst	Burst Quantity

Appendix H：Band edge and Spurious Emissions (conducted)

Test Item:	Band edge	Modulation type:	GFSK
CH00 No hopping mode			
CH00 Hopping mode			
CH78 No hopping mode			

CH78 Hopping mode	

Test Item:	Band edge	Modulation type:	π/4DQPSK
CH00 No hopping mode			
CH00 Hopping mode			
CH78 No hopping mode			

CH78 Hopping mode	

Test Item:	Band edge	Modulation type:	8DPSK
CH00 No hopping mode			
CH00 Hopping mode			
CH78 No hopping mode			

CH78 Hoppig mode	

Test Item:	Spurious Emission	Modulation type:	GFSK
CH00 Reference level			
CH00 30MHz~1000MHz			
CH00 1GHz~26GHz			

CH39 Reference level	 Date: 6.NOV.2023 10:08:22
CH39 30MHz~1000MHz	 Date: 6.NOV.2023 10:08:37
CH39 1GHz~26GHz	 Date: 6.NOV.2023 10:08:52

CH78 Reference level	 Date: 6.NOV.2023 10:10:02
CH78 30MHz~1000MHz	 Date: 6.NOV.2023 10:10:17
CH78 1GHz~26GHz	 Date: 6.NOV.2023 10:10:33

Test Item:	Spurious Emission	Modulation type:	π/4DQPSK
CH00 Reference level	 Date: 3.NOV.2023 15:25:29		
CH00 30MHz~1000MHz	 Date: 3.NOV.2023 15:25:44		
CH00 1GHz~26GHz	 Date: 3.NOV.2023 15:25:59		

CH39 Reference level	 Date: 3.NOV.2023 15:27:08
CH39 30MHz~1000MHz	 Date: 3.NOV.2023 15:27:23
CH39 1GHz~26GHz	 Date: 3.NOV.2023 15:27:38

CH78 Reference level	 Date: 3.NOV.2023 15:28:41
CH78 30MHz~1000MHz	 Date: 3.NOV.2023 15:28:56
CH78 1GHz~26GHz	 Date: 3.NOV.2023 15:29:11

Test Item:	Spurious Emission	Modulation type:	8DPSK
CH00 Reference level	 Date: 3.NOV.2023 15:30:34		
CH00 30MHz~1000MHz	 Date: 3.NOV.2023 15:30:49		
CH00 1GHz~26GHz	 Date: 3.NOV.2023 15:31:04		

CH39 Reference level	 Date: 3.NOV.2023 15:31:52
CH39 30MHz~1000MHz	 Date: 3.NOV.2023 15:32:07
CH39 1GHz~26GHz	 Date: 3.NOV.2023 15:32:22

CH78 Reference level	 Date: 3.NOV.2023 15:33:20
CH78 30MHz~1000MHz	 Date: 3.NOV.2023 15:33:35
CH78 1GHz~26GHz	 Date: 3.NOV.2023 15:33:50

--------End of Report--------