

**FCC Test Report**

Report Reference No.: HK2412187831-6E

FCC ID: 2BDI3-S

Compiled by

(position+printed name+signature) : Testing Engineer Len Liao

Len Liao

Supervised by

(position+printed name+signature) : Technical Manager Sliver Wan

Sliver Wan

Approved by

(position+printed name+signature) : Authorized Signatory Jason Zhou

Jason Zhou

Date of issue : Feb. 17, 2025

Testing Laboratory Name : Shenzhen HUAKE Testing Technology Co., Ltd.Address : 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park,
Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China**Applicant's name : Shenzhen Haimeilan Technology Co., LTD.**Address : 9V777, East 9th Floor, Building 2, SEG Science Park, Huaqiang North
Street, Futian District, Shenzhen, 518000 China**Test specification..... :**Standard : **FCC Part 22: PUBLIC MOBILE SERVICES****FCC Part 24: PERSONAL COMMUNICATIONS SERVICES****Shenzhen HUAKE Testing Technology Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description..... : Smart Phone

Trade Mark..... : N/A

Model/Type reference : S25 Ultra

Series Models : S24 Ultra, S23 Ultra, C25 Ultra, C24 Ultra, C23 Ultra, X23 Ultra, X24
Ultra, X25 Ultra, Z23 Ultra, Z24 Ultra, Z25 Ultra, C10 Plus, C30 Plus,
G50 Plus, G60 Plus, C73, C7 Ultra, Polaris7 Pro, C3 Luxury, G37
Ultra, M13 Pro, Polaris7, Rise77 Luxury, Opus33 Luxury, Acro77
Luxury, Sirius40 Ultra, H50 Ultra, G3 Luxury, Rise30 Ultra, G7 Ultra,
E-on33 Ultra, Vista16 Ultra, I24 Ultra, I25 Ultra, X24, S01, C25, S10,
S11, S08, S25 MAX, I15 Ultra, S24 Pro Max

Ratings..... : DC 5V From Type-C or DC 3.85V From Battery

Modulation : GMSK/8PSK

GPRS..... : Supported

Hardware version..... : V1.0

Software version : V1.0

Frequency : GSM 850MHz; PCS 1900MHz;

Result..... : **PASS**



TEST REPORT

Test Report No. :	HK2412187831-6E	Feb. 17, 2025
		Date of issue

Equipment under Test : Smart Phone

Model /Type : S25 Ultra

Series Models : S24 Ultra, S23 Ultra, C25 Ultra, C24 Ultra, C23 Ultra, X23 Ultra, X24 Ultra, X25 Ultra, Z23 Ultra, Z24 Ultra, Z25 Ultra, C10 Plus, C30 Plus, G50 Plus, G60 Plus, C73, C7 Ultra, Polaris7 Pro, C3 Luxury, G37 Ultra, M13 Pro, Polaris7, Rise77 Luxury, Opus33 Luxury, Acro77 Luxury, Sirius40 Ultra, H50 Ultra, G3 Luxury, Rise30 Ultra, G7 Ultra, E-on33 Ultra, Vista16 Ultra, I24 Ultra, I25 Ultra, X24, S01, C25, S10, S11, S08, S25 MAX, I15 Ultra, S24 Pro Max

Applicant : Shenzhen Haimeilan Technology Co., LTD.

Address : 9V777, East 9th Floor, Building 2, SEG Science Park, Huaqiang North Street, Futian District, Shenzhen, 518000 China

Manufacturer : Shenzhen Yinma Intelligent Technology Co., Ltd

Address : 2nd Floor, Building 2, Donglongxing Science and Technology Park, Dalang Street, Longhua District, Shenzhen, 518000 China

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Contents

1	Test Standards	5
2	Summary	6
2.1	General Remarks	6
2.2	Product Description	6
2.3	Equipment Under Test	7
2.4	Short Description of The Equipment Under Test (EUT)	8
2.5	EUT Configuration	8
2.6	Related Submittal(s) / Grant (s)	8
2.7	Modifications	8
2.8	General Test Conditions/Configurations	8
2.9	Modifications	8
3	Test Environment	9
3.1	Information of The Test Laboratory	9
3.2	Environmental Conditions	9
3.3	Test Description	9
3.4	Equipments Used During The Test	11
4	Test Conditions and Results	12
4.1	Output Power	12
4.2	Radiated Spurious Emission	17
4.3	Occupied Bandwidth and Emission Bandwidth	29
4.4	Band Edge Compliance	34
4.5	Spurious Emission on Antenna Port	39
4.6	Frequency Stability Test	48
4.7	Peak-to-Average Ratio (PAR)	52
5	Test Setup Photos of the EUT	54
6	Photos of the EUT	61



**** Modified History ****

Revision	Description	Issued Data	Remark
Revision 1.0	Initial Test Report Release	Feb. 17, 2025	Jason Zhou



1 Test Standards

The tests were performed according to following standards:

[FCC Part 2:](#) Frequency Allocation And Radio Treaty Matters; General Rules And Regulations.

[FCC Part 22 Subpart H:](#) Private Land Mobile Radio Services.

[FCC Part 24 Subpart E:](#) Public Mobile Services.

[ANSI/TIA-603-E-2016:](#) Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[ANSI C63.26-2015:](#) IEEE/ANSI Standard for Compliance Testing of Transmitters Used in Licensed Radio Services.

[KDB971168 D01:v03r01](#) Measurement Guidance For Certification Of Licensed Digital Transmitters.



2 Summary

2.1 General Remarks

Date of receipt of test sample	:	Dec. 18, 2024
Testing commenced on	:	Dec. 18, 2024
Testing concluded on	:	Feb. 17, 2025

2.2 Product Description

Product Name:	Smart Phone
Model/Type reference:	S25 Ultra
Series Models:	S24 Ultra, S23 Ultra, C25 Ultra, C24 Ultra, C23 Ultra, X23 Ultra, X24 Ultra, X25 Ultra, Z23 Ultra, Z24 Ultra, Z25 Ultra, C10 Plus, C30 Plus, G50 Plus, G60 Plus, C73, C7 Ultra, Polaris7 Pro, C3 Luxury, G37 Ultra, M13 Pro, Polaris7, Rise77 Luxury, Opus33 Luxury, Acro77 Luxury, Sirius40 Ultra, H50 Ultra, G3 Luxury, Rise30 Ultra, G7 Ultra, E-on33 Ultra, Vista16 Ultra, I24 Ultra, I25 Ultra, X24, S01, C25, S10, S11, S08, S25 MAX, I15 Ultra, S24 Pro Max
Model Difference:	All model's the function, software and electric circuit are the same, only with a product appearance, color and model named different. Test sample mode: S25 Ultra.
Power supply:	DC 5V From Type-C or DC 3.85V From Battery
Adapter Information:	DC 5V From Type-C or DC 3.85V From Battery
Modulation Type:	GMSK/8PSK
Antenna Type:	FPC Antenna
Antenna Gain	0.56dBi
GSM/EDGE/GPRS:	Supported EGPRS/GPRS/GSM
GSM/GPRS Power Class:	GSM850:Power Class 4/ PCS1900:Power Class 1
GSM/GPRS Operation Frequency:	GSM850:824.2MHz-848.8MHz/PCS1900:1850.2MHz-1909.8MHz
GPRS Operation Frequency Band:	GPRS850/GPRS1900
GPRS/EDGE Multislot Class:	EGPRS/GPRS: Multi-slot Class 12
EGPRS Multislot Class:	/
Extreme temp. Tolerance:	-30°C to +50°C
GPRS operation mode:	Class B
Note: 1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2. Antenna gain Refer to the antenna specifications. 3. The cable loss data is obtained from the supplier. 4. The test results in the report only apply to the tested sample.	



2.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐	120V / 60 Hz	☐	230V / 50Hz
		☐	12 V DC	☐	24 V DC
		☒	Other (specified in blank below)		

DC 5V From Type-C or DC 3.85V From Battery

Test frequency list

Test Mode	TX/RX	RF Channel		
		Low(L)	Middle (M)	High (H)
GSM850	TX	Channel 128	Channel 190	Channel 251
		824.2 MHz	836.6 MHz	848.8 MHz
	RX	Channel 128	Channel 190	Channel 251
		869.2 MHz	881.6 MHz	893.8 MHz
Test Mode	TX/RX	RF Channel		
		Low(L)	Middle (M)	High (H)
GSM1900	TX	Channel 512	Channel 661	Channel 810
		1850.2 MHz	1880.0 MHz	1909.8 MHz
	RX	Channel 512	Channel 661	Channel 810
		1930.2 MHz	1960.0 MHz	1989.8 MHz



2.4 Short Description of The Equipment Under Test (EUT)

This is a Smart Phone.

For more details, refer to the user's manual of the EUT.

2.5 EUT Configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○ /	M/N : /
	Manufacturer: /

2.6 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2BDI3-S** filing to comply with FCC Part 22 and Part 24 Rules.

2.7 Modifications

No modifications were implemented to meet testing criteria.

2.8 General Test Conditions/Configurations

2.8.1 Test Modes

NOTE: The test mode(s) are selected according to relevant radio technology specifications.

Test Mode 1	GPRS
Test Mode 2	GSM
Test Mode 3	EGPRS

2.8.2 Test Environment

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	4.25V
	VN	5.0V
	VH	5.75V

NOTE: VL=lower extreme test voltage VN=nominal voltage
VH=upper extreme test voltage TN=normal temperature

2.9 Modifications

No modifications were implemented to meet testing criteria.



3 Test Environment

3.1 Information of The Test Laboratory

Shenzhen HUAKE Testing Technology Co., Ltd.
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping,
Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Testing Laboratory Authorization:

A2LA Accreditation Code is 4781.01.
FCC Designation Number is CN1229.
Canada IC CAB identifier is CN0045.
CNAS Registration Number is L9589.

3.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.3 Test Description

3.3.1 Cellular Band (824-849MHz paired with 869-894MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §22.913	FCC: ERP ≤ 7W.	Pass
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §22.917	≤-13dBm/1%*EBW, in 1MHz bands immediately outside and adjacent to The frequency block.	Pass
Spurious Emission at Antenna Terminals	§2.1051, §22.917	FCC: ≤ -13dBm/100kHz, from 9kHz to 10th harmonics but outside authorized operating frequency ranges.	Pass
Field Strength of Spurious Radiation	§2.1053, §22.917	FCC: ≤ -13dBm/100kHz.	Pass
Frequency Stability	§2.1055, §22.355	≤ ±2.5ppm.	Pass

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" de notes "not tested".

**3.3.2 PCS Band (1850-1915MHz paired with 1930-1995MHz)**

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §24.232	EIRP $\leq$ 2W	Pass
Peak-Average Ratio	§2.1046, §24.232	FCC:Limit $\leq$ 13dB	Pass
Modulation Characteristics	§2.1047	Digital modulation	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §24.238	$\leq$ -13dBm/1%*EBW, In 1MHz bands immediately outside and adjacent to The frequency block.	Pass
Spurious Emission at Antenna Terminals	§2.1051, §24.238	$\leq$ -13dBm/1MHz, from 9kHz to10th harmonics but outside authorized Operating frequency ranges.	Pass
Field Strength of Spurious Radiation	§2.1053, §24.238	$\leq$ -13dBm/1MHz.	Pass
Frequency Stability	§2.1055, §24.235	FCC: within authorized frequency block.	Pass
NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" de notes "not tested".			

Remark:

1. The measurement uncertainty is not included in the test result.



3.4 Equipments Used During The Test

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
1	L.I.S.N.	R&S	ENV216	HKE-002	2024/02/20	2025/02/19
2	L.I.S.N.	R&S	ENV216	HKE-059	2024/02/20	2025/02/19
3	EMI Test Receiver	R&S	ESR	HKE-005	2024/02/20	2025/02/19
4	Spectrum analyzer	Agilent	N9020A	HKE-117	2024/02/20	2025/02/19
5	Spectrum analyzer	R&S	FSV3044	HKE-126	2024/02/20	2025/02/19
6	Preamplifier	EMCI	EMC051845S	HKE-006	2024/02/20	2025/02/19
7	Preamplifier	Schwarzbeck	BBV 9743	HKE-016	2024/02/20	2025/02/19
8	Preamplifier	A.H. Systems	SAS-574	HKE-182	2024/02/20	2025/02/19
9	6d Attenuator	Pasternack	6db	HKE-184	2024/02/20	2025/02/19
10	EMI Test Receiver	Rohde & Schwarz	ESR-7	HKE-010	2024/02/20	2025/02/19
11	Broadband Antenna	Schwarzbeck	VULB9168	HKE-167	2024/02/21	2026/02/20
12	Loop Antenna	COM-POWER	AL-130R	HKE-014	2024/02/21	2026/02/20
13	Horn Antenna	Schwarzbeck	9120D	HKE-013	2024/02/21	2026/02/20
14	EMI Test Software	Tonscend	JS32-CE 2.5.0.6	HKE-081	/	/
15	EMI Test Software	Tonscend	JS32-RE 5.0.0	HKE-082	/	/
16	RF Automatic control unit	Tonscend	JS0806-1	HKE-096	2024/02/20	2025/02/19
17	High pass filter unit	Tonscend	JS0806-F	HKE-055	2024/02/20	2025/02/19
18	Wireless Communication Test Set	R&S	CMU200	HKE-026	2024/02/20	2025/02/19
19	Wireless Communication Test Set	R&S	CMW500	HKE-027	2024/02/20	2025/02/19
20	High-low temperature chamber	Guangke	HT-80L	HKE-118	2024/06/10	2025/06/09
21	Temperature and humidity meter	Boyang	HTC-1	HKE-075	2024/06/10	2025/06/09
22	RF Test Software	Tonscend	JS1120 Version 3.1.46	HKE-183	/	/
23	RSE Test Software	Tonscend	JS36-RSE 5.0.0	HKE-184	/	/

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



4 Test Conditions and Results


4.1 Output Power

TEST APPLICABLE

During the process of testing, the EUT was controlled via R&S Digital Radio Communication tester (CMW500) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

4.1.1 Conducted Output Power

TEST CONFIGURATION



TEST PROCEDURE

Conducted Power Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a CMW500 by an Att.
- EUT Communicate with CMW500 then selects a channel for testing.
- Add a correction factor to the display CMW500, and then test.

GSM850				
Function	Power step	Nominal output power (dBm)	Power & Multislot class	Operation class
GSM	5	33dBm(2W)	4	/
GPRS	3	33dBm(2W)	12	B
EDGE	8	27dBm(0.5W)	12	B

PCS1900				
Function	Power step	Nominal output power (dBm)	Power & Multislot class	Operation class
GSM	0	30dBm(1W)	1	/
GPRS	3	30dBm(1W)	12	B
EDGE	2	27dBm(0.5W)	12	B

**TEST RESULTS**

GSM 850		Burst Average Conducted power (dBm)		
		Channel/Frequency(MHz)		
		128/824.2	190/836.6	251/848.8
GSM		33.61	33.79	33.76
GPRS (GMSK)	33.70	33.54	33.61	33.62
	32.60	32.41	32.53	32.55
	30.40	30.14	30.30	30.35
	29.30	29.00	29.17	29.22
EGPRS (8PSK)	31.50	31.30	31.16	31.40
	30.50	30.33	30.31	30.47
	28.60	28.39	28.36	28.57
	27.60	27.34	27.30	27.51
GSM 1900		Burst Average Conducted power (dBm)		
		Channel/Frequency(MHz)		
		512/1850.2	661/1880.0	810/1909.8
GSM		32.02	31.48	31.24
GPRS (GMSK)	31.99	31.97	31.41	31.18
	31.30	31.22	30.73	30.51
	29.40	29.34	28.94	28.80
	28.30	28.22	27.88	27.74
EGPRS (8PSK)	31.20	31.14	30.60	30.44
	30.40	30.39	30.00	29.83
	28.80	28.77	28.50	28.40
	27.90	27.83	27.44	27.39

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China


4.1.2 Radiated Output Power

TEST DESCRIPTION

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(e) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

TEST CONFIGURATION



TEST PROCEDURE

1. EUT was placed on a 0.80 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 0.80m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).



4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} + G_a$$

We used SMF100A microwave signal generator which signal level can up to 33dBm, so we not used power Amplifier for substitution test; The measurement results are amend as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{cl} + G_a$$

6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

TEST LIMIT

Note: We test the H direction and V direction, V direction is worse.

According to 22.913(a) and 24.232(c), the ERP should be not exceed following table limits:

GSM850(GPRS850,EDGE850)		
Function	Power Step	Burst Peak ERP (dBm)
GSM	5	$\leq 38.45\text{dBm}$ (7W)
GPRS	3	$\leq 38.45\text{dBm}$ (7W)
EDGE	8	$\leq 38.45\text{dBm}$ (7W)

PCS1900(GPRS1900,EDGE1900)		
Function	Power Step	Burst Peak EIRP (dBm)
GSM	0	$\leq 33\text{dBm}$ (2W)
GPRS	3	$\leq 33\text{dBm}$ (2W)
EDGE	5	$\leq 33\text{dBm}$ (2W)

TEST RESULTS

Remark:

1. We were tested all Configuration refer 3GPP TS151 010.
2. $EIRP = P_{Mea}(\text{dBm}) - P_{cl}(\text{dB}) + P_{Ag}(\text{dB}) + G_a(\text{dBi})$
3. $ERP = EIRP - 2.15\text{dBi}$ as EIRP by subtracting the gain of the dipole.

Note: 1. We tested Horizontal and Vertical, and Recorded the worst data at the Vertical.



GSM 850

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.20	-15.97	2.42	8.45	2.15	36.82	24.73	38.45	13.72	V
836.60	-12.38	2.46	8.45	2.15	36.82	28.28	38.45	10.17	V
848.80	-13.58	2.53	8.36	2.15	36.82	26.92	38.45	11.53	V

GSM 1900

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.20	-13.52	3.41	10.24	33.6	14.52	33.01	18.49	V
1880.00	-12.11	3.49	10.24	33.6	15.85	33.01	17.16	V
1909.80	-12.03	3.55	10.23	33.6	15.87	33.01	17.14	V

GPRS 850

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.20	-16.14	2.42	8.45	2.15	36.82	24.56	38.45	13.89	V
836.60	-12.29	2.46	8.45	2.15	36.82	28.37	38.45	10.08	V
848.80	-12.75	2.53	8.36	2.15	36.82	27.75	38.45	10.7	V

GPRS 1900

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.20	-13.64	3.41	10.24	33.6	14.4	33.01	18.61	V
1880.00	-12.86	3.49	10.24	33.6	15.1	33.01	17.91	V
1909.80	-11.75	3.55	10.23	33.6	16.15	33.01	16.86	V

EGPRS 850

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.20	-14.16	2.42	8.45	2.15	36.82	26.54	38.45	11.91	V
836.60	-10.81	2.46	8.45	2.15	36.82	29.85	38.45	8.6	V
848.80	-14.24	2.53	8.36	2.15	36.82	26.26	38.45	12.19	V

EGPRS 1900


Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.20	-14.27	3.41	10.24	33.6	13.77	33.01	19.24	V
1880.00	-11.27	3.49	10.24	33.6	16.69	33.01	16.32	V
1909.80	-13.03	3.55	10.23	33.6	14.87	33.01	18.14	V

4.2 Radiated Spurious Emission

TEST APPLICABLE

According to the TIA/EIA 603D:2010 test method, The Receiver or Spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

TEST CONFIGURATION



TEST PROCEDURE

1. EUT was placed on a 0.80 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 0.80m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.



3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
The measurement results are obtained as described below:
 $Power(EIRP) = P_{Mea} - P_{Ag} - P_{cl} + G_a$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.
8. In order to make sure test results more clearly, we set frequency range and sweep time for difference frequency range as follows table:

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
GSM 850	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
PCS 1900	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

TEST LIMITS

According to 24.238 and 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Frequency	Channel	Frequency Range	Verdict
GSM 850	Low	9KHz-10GHz	PASS
	Middle	9KHz -10GHz	PASS
	High	9KHz -10GHz	PASS
PCS 1900	Low	9KHz -20GHz	PASS
	Middle	9KHz -20GHz	PASS
	High	9KHz -20GHz	PASS

**TEST RESULTS**

Remark:

1. We were tested all refer 3GPP TS151 010.
2. $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + G_a(dBi)$
3. We were not recorded other points as values lower than limits.
4. $Margin = Limit - EIRP$

Test Model No.: S25 Ultra

GSM 850 Low Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.4	-35.28	3.00	3.00	9.58	-28.7	-13.00	15.7	H
2472.6	-36.01	3.03	3.00	10.72	-28.32	-13.00	15.32	H
1648.4	-37.01	3.00	3.00	9.68	-30.33	-13.00	17.33	V
2472.6	-39.12	3.03	3.00	10.72	-31.43	-13.00	18.43	V

GSM 850 Middle Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.2	-36.36	3.00	3.00	9.58	-29.78	-13.00	16.78	H
2509.8	-30.31	3.03	3.00	10.72	-22.62	-13.00	9.62	H
1673.2	-32.28	3.00	3.00	9.68	-25.6	-13.00	12.6	V
2509.8	-36.84	3.03	3.00	10.72	-29.15	-13.00	16.15	V

GSM 850 High Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.6	-31.64	3.00	3.00	9.58	-25.06	-13.00	12.06	H
2546.4	-36.62	3.03	3.00	10.72	-28.93	-13.00	15.93	H
1697.6	-29.98	3.00	3.00	9.68	-23.3	-13.00	10.3	V
2546.4	-32.76	3.03	3.00	10.72	-25.07	-13.00	12.07	V

GSM 1900 Low Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.4	-40.63	4.39	3.00	12.34	-32.68	-13.00	19.68	H
5550.6	-39.61	5.31	3.00	13.52	-31.4	-13.00	18.4	H
3700.4	-40.54	4.39	3.00	12.34	-32.59	-13.00	19.59	V
5550.6	-42.87	5.31	3.00	13.52	-34.66	-13.00	21.66	V

GSM 1900 Middle Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-40.21	4.41	3.00	12.34	-32.28	-13.00	19.28	H
5640.0	-39.94	5.38	3.00	13.58	-31.74	-13.00	18.74	H
3760.0	-40.23	4.41	3.00	12.34	-32.3	-13.00	19.3	V
5640.0	-42.04	5.38	3.00	13.58	-33.84	-13.00	20.84	V

**GSM 1900 High Channel**

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.6	-40.51	4.45	3.00	12.45	-32.51	-13.00	19.51	H
5729.4	-39.61	5.47	3.00	13.66	-31.42	-13.00	18.42	H
3819.6	-40.71	4.45	3.00	12.45	-32.71	-13.00	19.71	V
5729.4	-44.22	5.48	3.00	13.66	-36.04	-13.00	23.04	V

GPRS 850 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.4	-35.04	3.00	3.00	9.58	-28.46	-13.00	15.46	H
2472.6	-37.15	3.03	3.00	10.72	-29.46	-13.00	16.46	H
1648.4	-37.11	3.00	3.00	9.68	-30.43	-13.00	17.43	V
2472.6	-39.39	3.03	3.00	10.72	-31.7	-13.00	18.7	V

GPRS 850 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.2	-36.55	3.00	3.00	9.58	-29.97	-13.00	16.97	H
2509.8	-30.99	3.03	3.00	10.72	-23.3	-13.00	10.3	H
1673.2	-31.73	3.00	3.00	9.68	-25.05	-13.00	12.05	V
2509.8	-38.06	3.03	3.00	10.72	-30.37	-13.00	17.37	V

GPRS 850 High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.6	-31.26	3.00	3.00	9.58	-24.68	-13.00	11.68	H
2546.4	-37.22	3.03	3.00	10.72	-29.53	-13.00	16.53	H
1697.6	-29.99	3.00	3.00	9.68	-23.31	-13.00	10.31	V
2546.4	-31.99	3.03	3.00	10.72	-24.3	-13.00	11.3	V

GPRS 1900 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.4	-41.52	4.39	3.00	12.34	-33.57	-13.00	20.57	H
5550.6	-39.73	5.31	3.00	13.52	-31.52	-13.00	18.52	H
3700.4	-41.22	4.39	3.00	12.34	-33.27	-13.00	20.27	V
5550.6	-42.39	5.31	3.00	13.52	-34.18	-13.00	21.18	V

GPRS 1900 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-40.03	4.41	3.00	12.34	-32.1	-13.00	19.1	H
5640.0	-40.09	5.38	3.00	13.58	-31.89	-13.00	18.89	H
3760.0	-41.02	4.41	3.00	12.34	-33.09	-13.00	20.09	V
5640.0	-42.36	5.38	3.00	13.58	-34.16	-13.00	21.16	V

*GPRS 1900_High Channel*

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.6	-40.82	4.45	3.00	12.45	-32.82	-13.00	19.82	H
5729.4	-40.29	5.47	3.00	13.66	-32.1	-13.00	19.1	H
3819.6	-41.03	4.45	3.00	12.45	-33.03	-13.00	20.03	V
5729.4	-43.24	5.48	3.00	13.66	-35.06	-13.00	22.06	V

EGPRS 850_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.4	-34.25	3.00	3.00	9.58	-27.67	-13.00	14.67	H
2472.6	-35.96	3.03	3.00	10.72	-28.27	-13.00	15.27	H
1648.4	-37.58	3.00	3.00	9.68	-30.9	-13.00	17.9	V
2472.6	-35.96	3.03	3.00	10.72	-28.27	-13.00	15.27	V

EGPRS 850_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.2	-35.98	3.00	3.00	9.58	-29.4	-13.00	16.4	H
2509.8	-30.11	3.03	3.00	10.72	-22.42	-13.00	9.42	H
1673.2	-31.66	3.00	3.00	9.68	-24.98	-13.00	11.98	V
2509.8	-36.82	3.03	3.00	10.72	-29.13	-13.00	16.13	V

EGPRS 850_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.6	-31.43	3.00	3.00	9.58	-24.85	-13.00	11.85	H
2546.4	-36.79	3.03	3.00	10.72	-29.1	-13.00	16.1	H
1697.6	-28.94	3.00	3.00	9.68	-22.26	-13.00	9.26	V
2546.4	-31.72	3.03	3.00	10.72	-24.03	-13.00	11.03	V

EGPRS 1900_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.4	-41.16	4.39	3.00	12.34	-33.21	-13.00	20.21	H
5550.6	-37.13	5.31	3.00	13.52	-28.92	-13.00	15.92	H
3700.4	-39.72	4.39	3.00	12.34	-31.77	-13.00	18.77	V
5550.6	-36.04	5.31	3.00	13.52	-27.83	-13.00	14.83	V

EGPRS 1900_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-40.31	4.41	3.00	12.34	-32.38	-13.00	19.38	H
5640.0	-37.81	5.38	3.00	13.58	-29.61	-13.00	16.61	H
3760.0	-39.21	4.41	3.00	12.34	-31.28	-13.00	18.28	V
5640.0	-37.78	5.38	3.00	13.58	-29.58	-13.00	16.58	V

*EGPRS 1900 High Channel*

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.6	-40.31	4.45	3.00	12.45	-32.31	-13.00	19.31	H
5729.4	-43.32	5.47	3.00	13.66	-35.13	-13.00	22.13	H
3819.6	-37.09	4.45	3.00	12.45	-29.09	-13.00	16.09	V
5729.4	-33.32	5.48	3.00	13.66	-25.14	-13.00	12.14	V

Note: We tested GSM/GPRS/EGPRS mode and recorded the worst case at the GPRS mode.

Series Model No.: X24 Ultra

GPRS 850 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.4	-35.3	3.00	3.00	9.58	-28.72	-13.00	15.72	H
2472.6	-37.24	3.03	3.00	10.72	-29.55	-13.00	16.55	H
1648.4	-37.56	3.00	3.00	9.68	-30.88	-13.00	17.88	V
2472.6	-39.59	3.03	3.00	10.72	-31.9	-13.00	18.9	V

GPRS 850 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.2	-36.17	3.00	3.00	9.58	-29.59	-13.00	16.59	H
2509.8	-30.76	3.03	3.00	10.72	-23.07	-13.00	10.07	H
1673.2	-31.71	3.00	3.00	9.68	-25.03	-13.00	12.03	V
2509.8	-38.17	3.03	3.00	10.72	-30.48	-13.00	17.48	V

GPRS 850 High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.6	-31.32	3.00	3.00	9.58	-24.74	-13.00	11.74	H
2546.4	-36.85	3.03	3.00	10.72	-29.16	-13.00	16.16	H
1697.6	-29.81	3.00	3.00	9.68	-23.13	-13.00	10.13	V
2546.4	-32.49	3.03	3.00	10.72	-24.8	-13.00	11.8	V

GPRS 1900 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.4	-41.71	4.39	3.00	12.34	-33.76	-13.00	20.76	H
5550.6	-39.99	5.31	3.00	13.52	-31.78	-13.00	18.78	H
3700.4	-40.83	4.39	3.00	12.34	-32.88	-13.00	19.88	V
5550.6	-42.52	5.31	3.00	13.52	-34.31	-13.00	21.31	V

GPRS 1900 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-40.29	4.41	3.00	12.34	-32.36	-13.00	19.36	H
5640.0	-40.1	5.38	3.00	13.58	-31.9	-13.00	18.9	H
3760.0	-40.76	4.41	3.00	12.34	-32.83	-13.00	19.83	V
5640.0	-42.02	5.38	3.00	13.58	-33.82	-13.00	20.82	V

*GPRS 1900 High Channel*

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.6	-40.34	4.45	3.00	12.45	-32.34	-13.00	19.34	H
5729.4	-40.54	5.47	3.00	13.66	-32.35	-13.00	19.35	H
3819.6	-40.86	4.45	3.00	12.45	-32.86	-13.00	19.86	V
5729.4	-43.03	5.48	3.00	13.66	-34.85	-13.00	21.85	V

Series Model No.: C24 Ultra

GPRS 850 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.4	-34.84	3.00	3.00	9.58	-28.26	-13.00	15.26	H
2472.6	-37.21	3.03	3.00	10.72	-29.52	-13.00	16.52	H
1648.4	-37.26	3.00	3.00	9.68	-30.58	-13.00	17.58	V
2472.6	-39.82	3.03	3.00	10.72	-32.13	-13.00	19.13	V

GPRS 850 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.2	-36.98	3.00	3.00	9.58	-30.4	-13.00	17.4	H
2509.8	-30.85	3.03	3.00	10.72	-23.16	-13.00	10.16	H
1673.2	-31.29	3.00	3.00	9.68	-24.61	-13.00	11.61	V
2509.8	-38.22	3.03	3.00	10.72	-30.53	-13.00	17.53	V

GPRS 850 High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.6	-31.61	3.00	3.00	9.58	-25.03	-13.00	12.03	H
2546.4	-37.06	3.03	3.00	10.72	-29.37	-13.00	16.37	H
1697.6	-30.15	3.00	3.00	9.68	-23.47	-13.00	10.47	V
2546.4	-31.69	3.03	3.00	10.72	-24	-13.00	11	V

GPRS 1900 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.4	-41.8	4.39	3.00	12.34	-33.85	-13.00	20.85	H
5550.6	-39.27	5.31	3.00	13.52	-31.06	-13.00	18.06	H
3700.4	-40.99	4.39	3.00	12.34	-33.04	-13.00	20.04	V
5550.6	-42.62	5.31	3.00	13.52	-34.41	-13.00	21.41	V

GPRS 1900 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-39.67	4.41	3.00	12.34	-31.74	-13.00	18.74	H
5640.0	-40.12	5.38	3.00	13.58	-31.92	-13.00	18.92	H
3760.0	-41.35	4.41	3.00	12.34	-33.42	-13.00	20.42	V
5640.0	-42.65	5.38	3.00	13.58	-34.45	-13.00	21.45	V

*GPRS 1900 High Channel*

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.6	-40.45	4.45	3.00	12.45	-32.45	-13.00	19.45	H
5729.4	-40.11	5.47	3.00	13.66	-31.92	-13.00	18.92	H
3819.6	-41.33	4.45	3.00	12.45	-33.33	-13.00	20.33	V
5729.4	-43.7	5.48	3.00	13.66	-35.52	-13.00	22.52	V

Series Model No.: C25

GPRS 850 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.4	-35.07	3.00	3.00	9.58	-28.49	-13.00	15.49	H
2472.6	-37.25	3.03	3.00	10.72	-29.56	-13.00	16.56	H
1648.4	-36.62	3.00	3.00	9.68	-29.94	-13.00	16.94	V
2472.6	-39.82	3.03	3.00	10.72	-32.13	-13.00	19.13	V

GPRS 850 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.2	-36.6	3.00	3.00	9.58	-30.02	-13.00	17.02	H
2509.8	-30.65	3.03	3.00	10.72	-22.96	-13.00	9.96	H
1673.2	-31.53	3.00	3.00	9.68	-24.85	-13.00	11.85	V
2509.8	-38.26	3.03	3.00	10.72	-30.57	-13.00	17.57	V

GPRS 850 High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.6	-31.58	3.00	3.00	9.58	-25	-13.00	12	H
2546.4	-36.73	3.03	3.00	10.72	-29.04	-13.00	16.04	H
1697.6	-30.48	3.00	3.00	9.68	-23.8	-13.00	10.8	V
2546.4	-31.68	3.03	3.00	10.72	-23.99	-13.00	10.99	V

GPRS 1900 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.4	-41.58	4.39	3.00	12.34	-33.63	-13.00	20.63	H
5550.6	-39.46	5.31	3.00	13.52	-31.25	-13.00	18.25	H
3700.4	-41.71	4.39	3.00	12.34	-33.76	-13.00	20.76	V
5550.6	-42.22	5.31	3.00	13.52	-34.01	-13.00	21.01	V

GPRS 1900 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-40.44	4.41	3.00	12.34	-32.51	-13.00	19.51	H
5640.0	-39.71	5.38	3.00	13.58	-31.51	-13.00	18.51	H
3760.0	-40.58	4.41	3.00	12.34	-32.65	-13.00	19.65	V
5640.0	-42.38	5.38	3.00	13.58	-34.18	-13.00	21.18	V

*GPRS 1900 High Channel*

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.6	-40.91	4.45	3.00	12.45	-32.91	-13.00	19.91	H
5729.4	-40.14	5.47	3.00	13.66	-31.95	-13.00	18.95	H
3819.6	-40.82	4.45	3.00	12.45	-32.82	-13.00	19.82	V
5729.4	-43.64	5.48	3.00	13.66	-35.46	-13.00	22.46	V

Series Model No.: I15 Ultra

GPRS 850 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.4	-35.36	3.00	3.00	9.58	-28.78	-13.00	15.78	H
2472.6	-36.8	3.03	3.00	10.72	-29.11	-13.00	16.11	H
1648.4	-36.74	3.00	3.00	9.68	-30.06	-13.00	17.06	V
2472.6	-39.44	3.03	3.00	10.72	-31.75	-13.00	18.75	V

GPRS 850 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.2	-36.43	3.00	3.00	9.58	-29.85	-13.00	16.85	H
2509.8	-30.82	3.03	3.00	10.72	-23.13	-13.00	10.13	H
1673.2	-31.93	3.00	3.00	9.68	-25.25	-13.00	12.25	V
2509.8	-38.26	3.03	3.00	10.72	-30.57	-13.00	17.57	V

GPRS 850 High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.6	-31.56	3.00	3.00	9.58	-24.98	-13.00	11.98	H
2546.4	-37.24	3.03	3.00	10.72	-29.55	-13.00	16.55	H
1697.6	-29.5	3.00	3.00	9.68	-22.82	-13.00	9.82	V
2546.4	-31.84	3.03	3.00	10.72	-24.15	-13.00	11.15	V

GPRS 1900 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.4	-41.54	4.39	3.00	12.34	-33.59	-13.00	20.59	H
5550.6	-39.95	5.31	3.00	13.52	-31.74	-13.00	18.74	H
3700.4	-40.77	4.39	3.00	12.34	-32.82	-13.00	19.82	V
5550.6	-42.69	5.31	3.00	13.52	-34.48	-13.00	21.48	V

GPRS 1900 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-39.67	4.41	3.00	12.34	-31.74	-13.00	18.74	H
5640.0	-40.44	5.38	3.00	13.58	-32.24	-13.00	19.24	H
3760.0	-40.64	4.41	3.00	12.34	-32.71	-13.00	19.71	V
5640.0	-42.8	5.38	3.00	13.58	-34.6	-13.00	21.6	V

*GPRS 1900 High Channel*

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.6	-40.36	4.45	3.00	12.45	-32.36	-13.00	19.36	H
5729.4	-40.6	5.47	3.00	13.66	-32.41	-13.00	19.41	H
3819.6	-41.38	4.45	3.00	12.45	-33.38	-13.00	20.38	V
5729.4	-43.38	5.48	3.00	13.66	-35.2	-13.00	22.2	V

Series Model No.: C7 Ultra

GPRS 850 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.4	-35.43	3.00	3.00	9.58	-28.85	-13.00	15.85	H
2472.6	-36.83	3.03	3.00	10.72	-29.14	-13.00	16.14	H
1648.4	-37.32	3.00	3.00	9.68	-30.64	-13.00	17.64	V
2472.6	-39.71	3.03	3.00	10.72	-32.02	-13.00	19.02	V

GPRS 850 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.2	-36.1	3.00	3.00	9.58	-29.52	-13.00	16.52	H
2509.8	-30.6	3.03	3.00	10.72	-22.91	-13.00	9.91	H
1673.2	-31.41	3.00	3.00	9.68	-24.73	-13.00	11.73	V
2509.8	-37.67	3.03	3.00	10.72	-29.98	-13.00	16.98	V

GPRS 850 High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.6	-30.85	3.00	3.00	9.58	-24.27	-13.00	11.27	H
2546.4	-36.73	3.03	3.00	10.72	-29.04	-13.00	16.04	H
1697.6	-30.42	3.00	3.00	9.68	-23.74	-13.00	10.74	V
2546.4	-31.68	3.03	3.00	10.72	-23.99	-13.00	10.99	V

GPRS 1900 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.4	-41.09	4.39	3.00	12.34	-33.14	-13.00	20.14	H
5550.6	-39.89	5.31	3.00	13.52	-31.68	-13.00	18.68	H
3700.4	-41.37	4.39	3.00	12.34	-33.42	-13.00	20.42	V
5550.6	-42.81	5.31	3.00	13.52	-34.6	-13.00	21.6	V

GPRS 1900 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-40.18	4.41	3.00	12.34	-32.25	-13.00	19.25	H
5640.0	-39.78	5.38	3.00	13.58	-31.58	-13.00	18.58	H
3760.0	-40.66	4.41	3.00	12.34	-32.73	-13.00	19.73	V
5640.0	-41.97	5.38	3.00	13.58	-33.77	-13.00	20.77	V

*GPRS 1900 High Channel*

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.6	-40.52	4.45	3.00	12.45	-32.52	-13.00	19.52	H
5729.4	-40.26	5.47	3.00	13.66	-32.07	-13.00	19.07	H
3819.6	-41.19	4.45	3.00	12.45	-33.19	-13.00	20.19	V
5729.4	-42.94	5.48	3.00	13.66	-34.76	-13.00	21.76	V

Series Model No.: S24 Ultra

GPRS 850 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.4	-34.83	3.00	3.00	9.58	-28.25	-13.00	15.25	H
2472.6	-37.28	3.03	3.00	10.72	-29.59	-13.00	16.59	H
1648.4	-36.79	3.00	3.00	9.68	-30.11	-13.00	17.11	V
2472.6	-39.32	3.03	3.00	10.72	-31.63	-13.00	18.63	V

GPRS 850 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.2	-36.99	3.00	3.00	9.58	-30.41	-13.00	17.41	H
2509.8	-30.96	3.03	3.00	10.72	-23.27	-13.00	10.27	H
1673.2	-31.51	3.00	3.00	9.68	-24.83	-13.00	11.83	V
2509.8	-38.46	3.03	3.00	10.72	-30.77	-13.00	17.77	V

GPRS 850 High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.6	-31.57	3.00	3.00	9.58	-24.99	-13.00	11.99	H
2546.4	-37.26	3.03	3.00	10.72	-29.57	-13.00	16.57	H
1697.6	-29.66	3.00	3.00	9.68	-22.98	-13.00	9.98	V
2546.4	-31.87	3.03	3.00	10.72	-24.18	-13.00	11.18	V

GPRS 1900 Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.4	-41.91	4.39	3.00	12.34	-33.96	-13.00	20.96	H
5550.6	-39.71	5.31	3.00	13.52	-31.5	-13.00	18.5	H
3700.4	-41.13	4.39	3.00	12.34	-33.18	-13.00	20.18	V
5550.6	-42.85	5.31	3.00	13.52	-34.64	-13.00	21.64	V

GPRS 1900 Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-40.21	4.41	3.00	12.34	-32.28	-13.00	19.28	H
5640.0	-39.72	5.38	3.00	13.58	-31.52	-13.00	18.52	H
3760.0	-41.27	4.41	3.00	12.34	-33.34	-13.00	20.34	V
5640.0	-42.32	5.38	3.00	13.58	-34.12	-13.00	21.12	V

**GPRS 1900 High Channel**

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.6	-41.05	4.45	3.00	12.45	-33.05	-13.00	20.05	H
5729.4	-40.55	5.47	3.00	13.66	-32.36	-13.00	19.36	H
3819.6	-40.98	4.45	3.00	12.45	-32.98	-13.00	19.98	V
5729.4	-43.38	5.48	3.00	13.66	-35.2	-13.00	22.2	V




4.3 Occupied Bandwidth and Emission Bandwidth

TEST APPLICABLE

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. The table below lists the measured 99% Bandwidth and -26dBc Bandwidth.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The Occupied bandwidth and Emission Bandwidth were measured with Aglient Spectrum Analyzer N9020A (peak);
3. Set RBW=5.1KHz,VBW=15KHz,Span=1MHz,SWT=100ms;
4. Set SPA Max hold and View, Set 99% Occupied Bandwidth/ Set -26dBc Occupied Bandwidth;
5. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (Low, middle and high of operational frequency range).

TEST RESULTS

GSM 850				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Emission Bandwidth (26 dBc BW) (kHz)	Verdict
128	824.20	245.63	312.2	PASS
190	836.60	247.89	311.7	PASS
251	848.80	244.90	316.6	PASS

GSM 1900				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Emission Bandwidth (26 dBc BW) (kHz)	Verdict
512	1850.20	244.60	308.8	PASS
661	1880.00	244.21	308.5	PASS
810	1909.80	245.88	316.2	PASS




GPRS 850				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Emission Bandwidth (26 dBc BW) (kHz)	Verdict
128	824.20	242.99	310.8	PASS
190	836.60	246.98	307.5	PASS
251	848.80	247.96	312.6	PASS

GPRS 1900				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Emission Bandwidth (26 dBc BW) (kHz)	Verdict
512	1850.20	278.73	314.5	PASS
661	1880.00	240.67	312.8	PASS
810	1909.80	246.64	318.6	PASS

EGPRS 850				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Emission Bandwidth (26 dBc BW) (kHz)	Verdict
128	824.20	256.68	322.7	PASS
190	836.60	255.87	322.5	PASS
251	848.80	260.85	326.2	PASS


EGPRS 1900				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Emission Bandwidth (26 dBc BW) (kHz)	Verdict
512	1850.20	267.11	350.9	PASS
661	1880.00	267.93	349.3	PASS
810	1909.80	266.85	348.5	PASS



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com


Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




EGPRS 850




EGPRS 1900



Channel 128




Channel 512



Channel 190



Channel 661



Channel 251

Channel 810




4.4 Band Edge Compliance

TEST APPLICABLE

During the process of testing, the EUT was controlled via Aglient Digital Radio Communication tester (CMW500) to ensure max power transmission and proper modulation.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The power was measured with Aglient Spectrum Analyzer N9020A;
3. Set RBW=5.1KHz,VBW=15KHz,Span=2MHz,SWT=100ms, Dector: RMS;
4. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20 MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (bottom, middle and top of operational frequency range).

TEST RESULTS

GSM 850					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
128	824.20	824.00	-25.00	-13.00	PASS
251	848.80	849.02	-21.69	-13.00	PASS

GSM 1900					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
512	1850.20	1849.98	-25.86	-13.00	PASS
810	1909.80	1910.02	-25.92	-13.00	PASS


GPRS 850					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
128	824.20	824.00	-24.88	-13.00	PASS
251	848.80	849.02	-25.01	-13.00	PASS





GPRS 1900					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
512	1850.20	1850.00	-25.58	-13.00	PASS
810	1909.80	1910.02	-28.05	-13.00	PASS

EGPRS 850					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
128	824.20	823.98	-28.02	-13.00	PASS
251	848.80	849.00	-26.59	-13.00	PASS

EGPRS 1900					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
512	1850.20	1849.99	-23.58	-13.00	PASS
810	1909.80	1910.01	-22.93	-13.00	PASS










4.5 Spurious Emission on Antenna Port

TEST APPLICABLE

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 9 KHz to 19.1 GHz, data taken from 9 KHz to 25 GHz. For GSM850, data taken from 9 KHz to 9 GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; if the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give an optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:
The trace mode is set to MaxHold to get the highest signal at each frequency;
Wait 25 seconds;
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The power was measured with Agilent Spectrum Analyzer N9020A (peak);
3. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20 MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (Low, middle and high of operational frequency range).

TEST LIMIT

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

TEST RESULTS

Note: We tested GSM/GPRS/EGPRS mode and recorded the worst case at the GPRS mode.


**4.5.1 For GPRS 850 Test Results****A. Test Verdict**

Test Mode/ Channel	Frequency (MHz)	Frequency Range	Limit (dBm)	Verdict
GPRS 850 /128	824.20	150KHz-30MHz	-13.00	PASS
		30MHz-1GHz	-13.00	PASS
		1GHz-3GHz	-13.00	PASS
		3GHz-10GHz	-13.00	PASS
GPRS 850 /190	836.60	150KHz-30MHz	-13.00	PASS
		30MHz-1GHz	-13.00	PASS
		1GHz-3GHz	-13.00	PASS
		3GHz-10GHz	-13.00	PASS
GPRS 850 /251	848.80	150KHz-30MHz	-13.00	PASS
		30MHz-1GHz	-13.00	PASS
		1GHz-3GHz	-13.00	PASS
		3GHz-10GHz	-13.00	PASS

Note:

1. In general, the worse case attenuation requirement shown above was applied.
2. “---” means that the emission level is too low to be measured or at least 20 dB down than the limit.


B. Test Plots



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




Test Mode: GPRS


Test channel : 251




0.15~30MHz



30MHz ~1GHz



1GHz ~3GHz



3GHz ~10GHz



4.5.2 For GPRS 1900 Test Results


A. Test Verdict

Test Mode/ Channel	Frequency (MHz)	Frequency Range	Limit (dBm)	Verdict
GPRS 1900 /512	1850.20	150KHz-30MHz	-13.00	PASS
		30MHz-1GHz	-13.00	PASS
		1GHz-3GHz	-13.00	PASS
		3GHz-10GHz	-13.00	PASS
GPRS 1900 /661	1880.00	150KHz-30MHz	-13.00	PASS
		30MHz-1GHz	-13.00	PASS
		1GHz-3GHz	-13.00	PASS
		3GHz-10GHz	-13.00	PASS
GPRS 1900 /810	1909.80	150KHz-30MHz	-13.00	PASS
		30MHz-1GHz	-13.00	PASS
		1GHz-3GHz	-13.00	PASS
		3GHz-10GHz	-13.00	PASS

Note:

1. In general, the worse case attenuation requirement shown above was applied.
2. “---” means that the emission level is too low to be measured or at least 20 dB down than the limit.

B. Test Plots



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China