# FCC Test Report

| | |
|---|---|
| **Report Reference No.....:** | HK2412187831-9E |
| **FCC ID.....:** | 2BDI3-S |
| Compiled by ( position+printed name+signature)..: | Testing Engineer Len Liao |
| Supervised by ( position+printed name+signature)..: | Technical Manager Sliver Wan |
| Approved by ( position+printed name+signature)..: | Authorized Signatory Jason Zhou |
| Date of issue.....: | Feb. 17, 2025 |
| **Testing Laboratory Name .....:** | **Shenzhen HUAK Testing Technology Co., Ltd.** |
| Address .....: | 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China |
| **Applicant's name.....:** | **Shenzhen Haimeilan Technology Co., LTD.** |
| Address .....: | 9V777, East 9th Floor, Building 2, SEG Science Park, Huaqiang North Street, Futian District, Shenzhen, 518000 China |
| **Test specification .....:** | |
| Standard .....: | **FCC CFR Title 47 Part 2, Part 27** |
| TRF Originator.....: | Shenzhen HUAK Testing Technology Co., Ltd. |

**Shenzhen HUAK Testing Technology Co., Ltd. All rights reserved.**
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd.takess no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

| | |
|---|---|
| **Test item description .....:** | Smart Phone |
| Trade Mark .....: | N/A |
| **Manufacturer.....:** | **Shenzhen Yinma Intelligent Technology Co., Ltd** |
| Model/Type reference.....: | S25 Ultra |
| Series Models .....: | S24 Ultra, S23 Ultra, C25 Ultra, C24 Ultra, C23 Ultra, X23 Ultra, X24 Ultra, X25 Ultra, Z23 Ultra, Z24 Ultra, Z25 Ultra, C10 Plus, C30 Plus, G50 Plus, G60 Plus, C73, C7 Ultra, Polaris7 Pro, C3 Luxury, G37 Ultra, M13 Pro, Polaris7, Rise77 Luxury, Opus33 Luxury, Acro77 Luxury, Sirius40 Ultra, H50 Ultra, G3 Luxury, Rise30 Ultra, G7 Ultra, E-on33 Ultra, Vista16 Ultra, I24 Ultra, I25 Ultra, X24, S01, C25, S10, S11, S08, S25 MAX, I15 Ultra, S24 Pro Max |
| Modulation Type .....: | QPSK, 16QAM |
| Rating .....: | DC 5V From Type-C or DC 3.85V From Battery |
| Hardware version .....: | V1.0 |
| Software version .....: | V1.0 |
| Result.....: | **PASS** |

# TEST REPORT

| Test Report No. : | HK2412187831-9E | Feb. 17, 2025<br>Date of issue |
|---|---|---|

| | | |
|---|---|---|
| Equipment under Test | : | Smart Phone |
| Model /Type | : | S25 Ultra |
| Series Models | : | S24 Ultra, S23 Ultra, C25 Ultra, C24 Ultra, C23 Ultra, X23 Ultra, X24 Ultra, X25 Ultra, Z23 Ultra, Z24 Ultra, Z25 Ultra, C10 Plus, C30 Plus, G50 Plus, G60 Plus, C73, C7 Ultra, Polaris7 Pro, C3 Luxury, G37 Ultra, M13 Pro, Polaris7, Rise77 Luxury, Opus33 Luxury, Acro77 Luxury, Sirius40 Ultra, H50 Ultra, G3 Luxury, Rise30 Ultra, G7 Ultra, E-on33 Ultra, Vista16 Ultra, I24 Ultra, I25 Ultra, X24, S01, C25, S10, S11, S08, S25 MAX, I15 Ultra, S24 Pro Max |
| **Applicant** | : | **Shenzhen Haimeilan Technology Co., LTD.** |
| Address | : | 9V777, East 9th Floor, Building 2, SEG Science Park, Huaqiang North Street, Futian District, Shenzhen, 518000 China |
| **Manufacturer** | : | **Shenzhen Yinma Intelligent Technology Co., Ltd** |
| Address | : | 2nd Floor, Building 2, Donglongxing Science and Technology Park, Dalang Street, Longhua District, Shenzhen, 518000 China |

| **Test result** | **Pass** |
|---|---|

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

# Contents


| | | |
|---|---|---|
| 1 | Summary | 5 |
| 1.1 | Test Standards | 5 |
| 1.2 | Test Description | 5 |
| 1.3 | Information of The Test Laboratory | 6 |
| 1.4 | Statement of The Measurement Uncertainty | 6 |
| 2 | General Information | 7 |
| 2.1 | Environmental Conditions | 7 |
| 2.2 | Description of Test Modes | 7 |
| 2.3 | Test frequency list | 7 |
| 2.4 | Equipments Used During The Test | 8 |
| 2.5 | Related Submittal(s) / Grant (s) | 9 |
| 2.6 | Modifications | 9 |
| 3 | Test Conditions and Results | 10 |
| 3.1 | Output Power | 10 |
| 3.2 | Peak-to-Average Ratio (PAR) | 15 |
| 3.3 | Occupied Bandwidth and Emission Bandwidth | 22 |
| 3.4 | Band Edge Compliance | 29 |
| 3.5 | Spurious Emission | 36 |
| 3.6 | Frequency Stability Under Temperature & Voltage Variations | 81 |
| 4 | Test Setup Photos of the EUT | 83 |
| 5 | Photos of the EUT | 90 |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com
Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

# ** Modified History **

| Revision | Description | Issued Data | Remark |
|---|---|---|---|
| Revision 1.0 | Initial Test Report Release | Feb. 17, 2025 | Jason Zhou |
| | | | |
| | | | |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com
Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

# 1 Summary

## 1.1 Test Standards

The tests were performed according to following standards:

FCC Part 27: Miscellaneous Wireless Communications Services.

TIA/EIA 603 D June 2010:Land Mobile FM or PM Communications Equipment Measurement and Performance Standards 47 CFR FCC Part 15 Subpart B: - Unintentional Radiators.

FCC Part 2: Frequency Alloca-Tions And Radio Treaty Mat-Ters; General Rules And Reg-Ulations.

KDB971168 D01:v03r01 Measurement Guidance For Certification Of Licensed Digital Transmitters.

## 1.2 Test Description

| Test Item | Section in CFR 47 | Result |
|---|---|---|
| RF Output Power | Part 2.1046<br>Part 27.50(d)(4) | Pass |
| Peak-to-Average Ratio | Part 27.50(d)(4) | Pass |
| 99% & -26 dB Occupied Bandwidth | Part 2.1049<br>Part 27.53(h) | Pass |
| Spurious Emissions at Antenna Terminal | Part 2.1051<br>Part 27.53(h) | Pass |
| Field Strength of Spurious Radiation | Part 2.1053<br>Part 27.53(h) | Pass |
| Out of band emission, Band Edge | Part 2.1051<br>Part 27.53(h) | Pass |
| Frequency stability | Part 2.1055<br>Part 27.54 | Pass |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## 1.3 Information of The Test Laboratory

Shenzhen HUAK Testing Technology Co., Ltd.
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Testing Laboratory Authorization：

A2LA Accreditation Code is 4781.01.
FCC Designation Number is CN1229.
Canada IC CAB identifier is CN0045.
CNAS Registration Number is L9589.

## 1.4 Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4:Uncertainty in EMC Measurements“ and is documented in the Shenzhen HUAK Testing Technology Co., Ltd.quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen HUAK Testing Technology Co., Ltd.is reported:

| Test | Range | Measurement Uncertainty | Notes |
|---|---|---|---|
| Radiated Emission | 30~1000MHz | 4.10dB | (1) |
| Radiated Emission | Above 1GHz | 4.32dB | (1) |
| Conducted Disturbance | 0.15~30MHz | 3.20dB | (1) |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

# 2 General Information

## 2.1 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|---|---|
| Normal Temperature: | 25°C |
| Relative Humidity: | 55 % |
| Air Pressure: | 101 kPa |

## 2.2 Description of Test Modes

The EUT has been tested under typical operating condition. The CMW500 used to control the EUT staying in continuous transmitting and receiving mode for testing. Regards to the frequency band operation: the lowest、middle and highest frequency of channel were selected to perform the test, then shown on this report.

Note:

1. For the ERP/EIRP and radiated emission test, every axis (X, Y, Z) was verified, and show the worst resulton this report.
2. Test method and refer to 3GPP TS136521.

## 2.3 Test frequency list

| TX Channel Bandwidth | Frequency (MHz) | channel |
|---|---|---|
| 1.4 MHz | 1710.7 | 19957 |
| | 1732.5 | 20175 |
| | 1754.3 | 20393 |
| 3 MHz | 1711.5 | 19965 |
| | 1732.5 | 20175 |
| | 1753.5 | 20385 |
| 5 MHz | 1712.5 | 19975 |
| | 1732.5 | 20175 |
| | 1752.5 | 20375 |
| 10 MHz | 1715.0 | 20000 |
| | 1732.5 | 20175 |
| | 1750.0 | 20350 |
| 15 MHz | 1717.5 | 20025 |
| | 1732.5 | 20175 |
| | 1747.5 | 20325 |
| 20 MHz | 1720.0 | 20050 |
| | 1732.5 | 20175 |
| | 1745.0 | 20300 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## 2.4 Equipments Used During The Test

| Item | Test Equipment | Manufacturer | Model No. | Serial No. | Calibration Date | Calibration Due Date |
|---|---|---|---|---|---|---|
| 1 | L.I.S.N. | R&S | ENV216 | HKE-002 | 2024/02/20 | 2025/02/19 |
| 2 | L.I.S.N. | R&S | ENV216 | HKE-059 | 2024/02/20 | 2025/02/19 |
| 3 | EMI Test Receiver | R&S | ESR | HKE-005 | 2024/02/20 | 2025/02/19 |
| 4 | Spectrum analyzer | Agilent | N9020A | HKE-117 | 2024/02/20 | 2025/02/19 |
| 5 | Spectrum analyzer | R&S | FSV3044 | HKE-126 | 2024/02/20 | 2025/02/19 |
| 6 | Preamplifier | EMCI | EMC051845S | HKE-006 | 2024/02/20 | 2025/02/19 |
| 7 | Preamplifier | Schwarzbeck | BBV 9743 | HKE-016 | 2024/02/20 | 2025/02/19 |
| 8 | Preamplifier | A.H. Systems | SAS-574 | HKE-182 | 2024/02/20 | 2025/02/19 |
| 9 | 6d Attenuator | Pasternack | 6db | HKE-184 | 2024/02/20 | 2025/02/19 |
| 10 | EMI Test Receiver | Rohde & Schwarz | ESR-7 | HKE-010 | 2024/02/20 | 2025/02/19 |
| 11 | Broadband Antenna | Schwarzbeck | VULB9168 | HKE-167 | 2024/02/21 | 2026/02/20 |
| 12 | Loop Antenna | COM-POWER | AL-130R | HKE-014 | 2024/02/21 | 2026/02/20 |
| 13 | Horn Antenna | Schwarzbeck | 9120D | HKE-013 | 2024/02/21 | 2026/02/20 |
| 14 | EMI Test Software | Tonscend | JS32-CE 2.5.0.6 | HKE-081 | / | / |
| 15 | EMI Test Software | Tonscend | JS32-RE 5.0.0 | HKE-082 | / | / |
| 16 | RF Automatic control unit | Tonscend | JS0806-1 | HKE-096 | 2024/02/20 | 2025/02/19 |
| 17 | High pass filter unit | Tonscend | JS0806-F | HKE-055 | 2024/02/20 | 2025/02/19 |
| 18 | Wireless Communication Test Set | R&S | CMU200 | HKE-026 | 2024/02/20 | 2025/02/19 |
| 19 | Wireless Communication Test Set | R&S | CMW500 | HKE-027 | 2024/02/20 | 2025/02/19 |
| 20 | High-low temperature chamber | Guangke | HT-80L | HKE-118 | 2024/06/10 | 2025/06/09 |
| 21 | Temperature and humidity meter | Boyang | HTC-1 | HKE-075 | 2024/06/10 | 2025/06/09 |
| 22 | RF Test Software | Tonscend | JS1120 Version 3.1.46 | HKE-183 | / | / |
| 23 | RSE Test Software | Tonscend | JS36-RSE 5.0.0 | HKE-184 | / | / |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## 2.5 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2BDI3-S filing to comply with of the FCC Part 27 Rules.

## 2.6 Modifications

No modifications were implemented to meet testing criteria.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

# 3 Test Conditions and Results

## 3.1 Output Power

**LIMIT**

According to §27.50 (d) (4): Fixed, mobile, and portable (hand- held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

**TEST CONFIGURATION**

Conducted Power Measurement




Radiated Power Measurement:




**TEST PROCEDURE**

The EUT was setup according to EIA/TIA 603D.

**Conducted Power Measurement:**

a) Place the EUT on a bench and set it in transmitting mode.
b) Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
c) EUT Communicate with CMW500, then select a channel for testing.
d) Add a correction factor to the display of spectrum, and then test.

**Radiated Power Measurement:**

a. The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
b. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to thefrequency of the transmitter.
c. The output of the test antenna shall be connected to the measuring receiver.
d. The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
e. The test antenna shall be raised and lowered through the specified range of height until a maximum signal

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

level is detected by the measuring receiver.

f. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
g. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
h. The maximum signal level detected by the measuring receiver shall be noted.
i. The transmitter shall be replaced by a substitution antenna.
j. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
k. The substitution antenna shall be connected to a calibrated signal generator.
l. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
m. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
n. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
o. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
p. The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
q. Test site anechoic chamber refer to ANSI C63.4.

## TEST RESULTS

**Conducted Measurement:**

| *LTE FDD Band 4* | | | | |
|---|---|---|---|---|
| TX Channel Bandwidth | Frequency (MHz) | RB Size/Offset | Average Power [dBm] | |
| | | | QPSK | 16QAM |
| 1.4 MHz | 1710.7 | 1 RB low | 25.69 | 24.46 |
| | | 1 RB high | 25.77 | 24.55 |
| | | 50% RB mid | 25.71 | 24.43 |
| | | 100% RB | 25.73 | 24.54 |
| | 1732.5 | 1 RB low | 25.95 | 24.64 |
| | | 1 RB high | 25.06 | 24.78 |
| | | 50% RB mid | 25.93 | 24.69 |
| | | 100% RB | 25.03 | 24.77 |
| | 1754.3 | 1 RB low | 25.65 | 24.46 |
| | | 1 RB high | 25.81 | 24.67 |
| | | 50% RB mid | 25.67 | 24.51 |
| | | 100% RB | 25.72 | 24.14 |
| 3 MHz | 1711.5 | 1 RB low | 25.12 | 24.19 |
| | | 1 RB high | 25.20 | 24.20 |
| | | 50% RB mid | 25.11 | 24.22 |
| | | 100% RB | 24.18 | 23.19 |
| | 1732.5 | 1 RB low | 25.57 | 24.35 |
| | | 1 RB high | 25.59 | 24.27 |
| | | 50% RB mid | 25.58 | 24.34 |
| | | 100% RB | 25.57 | 23.46 |
| | 1753.5 | 1 RB low | 25.22 | 23.90 |
| | | 1 RB high | 25.23 | 23.98 |
| | | 50% RB mid | 25.25 | 24.02 |
| | | 100% RB | 25.23 | 23.21 |
| 5 MHz | 1712. | 1 RB low | 25.14 | 24.13 |
| | | 1 RB high | 25.28 | 24.24 |
| | | 50% RB mid | 25.17 | 24.11 |
| | | 100% RB | 25.19 | 23.16 |
| | 1732.5 | 1 RB low | 25.43 | 24.46 |
| | | 1 RB high | 25.58 | 24.57 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

| | | | | |
|---|---|---|---|---|
| | | 50% RB mid | 25.43 | 24.45 |
| | | 100% RB | 25.54 | 23.46 |
| | 1752.5 | 1 RB low | 25.17 | 24.07 |
| | | 1 RB high | 25.30 | 24.22 |
| | | 50% RB mid | 25.22 | 24.05 |
| | | 100% RB | 24.19 | 23.19 |
| 10 MHz | 1715.0 | 1 RB low | 25.17 | 24.24 |
| | | 1 RB high | 25.50 | 24.34 |
| | | 50% RB mid | 25.30 | 24.34 |
| | | 100% RB | 25.29 | 23.26 |
| | 1732.5 | 1 RB low | 25.56 | 24.32 |
| | | 1 RB high | 25.81 | 24.48 |
| | | 50% RB mid | 25.58 | 24.26 |
| | | 100% RB | 25.56 | 23.60 |
| | 1750.0 | 1 RB low | 25.36 | 24.08 |
| | | 1 RB high | 25.40 | 24.09 |
| | | 50% RB mid | 25.30 | 24.03 |
| | | 100% RB | 25.38 | 23.40 |
| 15 MHz | 1717.5 | 1 RB low | 25.57 | 24.25 |
| | | 1 RB high | 25.32 | 24.38 |
| | | 50% RB mid | 25.30 | 24.35 |
| | | 100% RB | 25.41 | 24.45 |
| | 1732.5 | 1 RB low | 25.39 | 24.50 |
| | | 1 RB high | 25.56 | 24.63 |
| | | 50% RB mid | 25.31 | 24.44 |
| | | 100% RB | 25.64 | 24.60 |
| | 1747.5 | 1 RB low | 25.90 | 24.15 |
| | | 1 RB high | 25.48 | 24.14 |
| | | 50% RB mid | 25.36 | 23.99 |
| | | 100% RB | 25.50 | 24.51 |
| 20 MHz | 1720.0 | 1 RB low | 25.07 | 23.98 |
| | | 1 RB high | 25.53 | 24.45 |
| | | 50% RB mid | 25.34 | 24.20 |
| | | 100% RB | 25.23 | 23.23 |
| | 1732.5 | 1 RB low | 25.57 | 24.34 |
| | | 1 RB high | 25.78 | 24.82 |
| | | 50% RB mid | 25.31 | 24.32 |
| | | 100% RB | 25.51 | 23.57 |
| | 1745.0 | 1 RB low | 25.78 | 24.13 |
| | | 1 RB high | 25.50 | 24.32 |
| | | 50% RB mid | 25.07 | 23.86 |
| | | 100% RB | 25.46 | 23.54 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

Radiated Measurement

*Remark:*

1. *We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case for each Channel Bandwidth of LTE FDD Band 4.*
2. *EIRP=$P_{Mea}$(dBm)-$P_{cl}$(dB)+$P_{Ag}$(dB)+$G_a$(dBi)*

*LTE FDD Band 4_Channel Bandwidth 1.4MHz_QPSK*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1710.7 | -16.62 | 3.06 | 9.68 | 34.80 | 24.80 | 30.00 | 5.20 | V |
| 1732.5 | -17.14 | 3.17 | 9.68 | 34.80 | 24.17 | 30.00 | 5.83 | V |
| 1754.3 | -15.66 | 3.22 | 9.75 | 34.80 | 25.67 | 30.00 | 4.33 | V |

*LTE FDD Band 4_Channel Bandwidth 3MHz_QPSK*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1711.5 | -15.36 | 3.06 | 9.68 | 34.80 | 26.06 | 30.00 | 3.94 | V |
| 1732.5 | -14.19 | 3.17 | 9.68 | 34.80 | 27.12 | 30.00 | 2.88 | V |
| 1753.5 | -15.71 | 3.22 | 9.75 | 34.80 | 25.62 | 30.00 | 4.38 | V |

*LTE FDD Band 4_Channel Bandwidth 5MHz_QPSK*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1712.5 | -16.99 | 3.06 | 9.68 | 34.80 | 24.43 | 30.00 | 5.57 | V |
| 1732.5 | -15.77 | 3.17 | 9.68 | 34.80 | 25.54 | 30.00 | 4.46 | V |
| 1752.5 | -15.61 | 3.22 | 9.75 | 34.80 | 25.72 | 30.00 | 4.28 | V |

*LTE FDD Band 4_Channel Bandwidth 10MHz_QPSK*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1715.0 | -14.95 | 3.06 | 9.68 | 34.80 | 26.47 | 30.00 | 3.53 | V |
| 1732.5 | -15.45 | 3.17 | 9.68 | 34.80 | 25.86 | 30.00 | 4.14 | V |
| 1750.0 | -16.11 | 3.22 | 9.75 | 34.80 | 25.22 | 30.00 | 4.78 | V |

*LTE FDD Band 4_Channel Bandwidth 15MHz_QPSK*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1717.5 | -16.76 | 3.06 | 9.68 | 34.80 | 24.66 | 30.00 | 5.34 | V |
| 1732.5 | -15.56 | 3.17 | 9.68 | 34.80 | 25.75 | 30.00 | 4.25 | V |
| 1747.5 | -16.22 | 3.22 | 9.75 | 34.80 | 25.11 | 30.00 | 4.89 | V |

*LTE FDD Band 4_Channel Bandwidth 20MHz_QPSK*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1720.0 | -13.86 | 3.06 | 9.68 | 34.80 | 27.56 | 30.00 | 2.44 | V |
| 1732.5 | -14.71 | 3.17 | 9.68 | 34.80 | 26.60 | 30.00 | 3.40 | V |
| 1745.0 | -15.98 | 3.22 | 9.75 | 34.80 | 25.35 | 30.00 | 4.65 | V |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

*LTE FDD Band 4_Channel Bandwidth 1.4MHz_16QAM*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1710.7 | -16.81 | 3.06 | 9.68 | 34.80 | 24.61 | 30.00 | 5.39 | V |
| 1732.5 | -16.13 | 3.17 | 9.68 | 34.80 | 25.18 | 30.00 | 4.82 | V |
| 1754.3 | -14.88 | 3.22 | 9.75 | 34.80 | 26.45 | 30.00 | 3.55 | V |

*LTE FDD Band 4_Channel Bandwidth 3MHz_16QAM*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1711.5 | -15.74 | 3.06 | 9.68 | 34.80 | 25.68 | 30.00 | 4.32 | V |
| 1732.5 | -15.05 | 3.17 | 9.68 | 34.80 | 26.26 | 30.00 | 3.74 | V |
| 1753.5 | -16.6 | 3.22 | 9.75 | 34.80 | 24.73 | 30.00 | 5.27 | V |

*LTE FDD Band 4_Channel Bandwidth 5MHz_16QAM*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1712.5 | -16.13 | 3.06 | 9.68 | 34.80 | 25.29 | 30.00 | 4.71 | V |
| 1732.5 | -16.58 | 3.17 | 9.68 | 34.80 | 24.73 | 30.00 | 5.27 | V |
| 1752.5 | -16.13 | 3.22 | 9.75 | 34.80 | 25.20 | 30.00 | 4.80 | V |

*LTE FDD Band 4_Channel Bandwidth 10MHz_16QAM*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1715.0 | -15.28 | 3.06 | 9.68 | 34.80 | 26.14 | 30.00 | 3.86 | V |
| 1732.5 | -14.82 | 3.17 | 9.68 | 34.80 | 26.49 | 30.00 | 3.51 | V |
| 1750.0 | -17.05 | 3.22 | 9.75 | 34.80 | 24.28 | 30.00 | 5.72 | V |

*LTE FDD Band 4_Channel Bandwidth 15MHz_16QAM*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1717.5 | -16.11 | 3.06 | 9.68 | 34.80 | 25.31 | 30.00 | 4.69 | V |
| 1732.5 | -15.33 | 3.17 | 9.68 | 34.80 | 25.98 | 30.00 | 4.02 | V |
| 1747.5 | -15.26 | 3.22 | 9.75 | 34.80 | 26.07 | 30.00 | 3.93 | V |

*LTE FDD Band 4_Channel Bandwidth 20MHz_16QAM*

| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain(dB) | $P_{Ag}$ (dB) | EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|---|---|---|---|---|---|---|---|---|
| 1720.0 | -15.71 | 3.06 | 9.68 | 34.80 | 25.71 | 30.00 | 4.29 | V |
| 1732.5 | -13.91 | 3.17 | 9.68 | 34.80 | 27.40 | 30.00 | 2.60 | V |
| 1745.0 | -15.18 | 3.22 | 9.75 | 34.80 | 26.15 | 30.00 | 3.85 | V |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## 3.2 Peak-to-Average Ratio (PAR)

**LIMIT**

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

**TEST CONFIGURATION**




**TEST PROCEDURE**

1. Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
2. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
3. Set the number of counts to a value that stabilizes the measured CCDF curve;
4. Set the measurement interval as follows:
   1). for continuous transmissions, set to 1 ms;
   2). for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
5. Record the maximum PAPR level associated with a probability of 0.1%.

**TEST RESULTS**

*Remark:*

1. *We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case for each Channel Bandwidth of LTE FDD Band 4.*

| *LTE FDD Band 4* | | | | |
|---|---|---|---|---|
| TX Channel Bandwidth | Frequency (MHz) | RB Size/Offset | PAPR (dB) | |
| | | | QPSK | 16QAM |
| 1.4 MHz | 1710.7 | *1RB#0* | 4.11 | 5.25 |
| | 1732.5 | | 3.84 | 4.84 |
| | 1754.3 | | 3.97 | 5.15 |
| 3 MHz | 1711.5 | *1RB#0* | 4.12 | 5.29 |
| | 1732.5 | | 3.87 | 4.82 |
| | 1753.5 | | 3.95 | 4.91 |
| 5 MHz | 1712.5 | *1RB#0* | 4.21 | 5.01 |
| | 1732.5 | | 4.06 | 4.84 |
| | 1752.5 | | 4.11 | 4.90 |
| 10 MHz | 1715.0 | *1RB#0* | 4.21 | 5.37 |
| | 1732.5 | | 4.03 | 4.95 |
| | 1750.0 | | 3.97 | 4.97 |
| 15 MHz | 1717.5 | *1RB#0* | 4.27 | 5.45 |
| | 1732.5 | | 4.10 | 5.05 |
| | 1747.5 | | 3.67 | 4.70 |
| 20 MHz | 1720.0 | *1RB#0* | 4.42 | 5.53 |
| | 1732.5 | | 4.23 | 5.03 |
| | 1745.0 | | 4.12 | 5.12 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-1.4MHz Channel Bandwidth PAPR

### QPSK




1RB#0

### 16QAM




1RB#0

### Low Channel




1RB#0




1RB#0

### Middle Channel




1RB#0




1RB#0

### High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-3MHz Channel Bandwidth PAPR

| QPSK | 16QAM |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### Low Channel

| | |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### Middle Channel

| | |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-5MHz Channel Bandwidth PAPR

| QPSK | 16QAM |
|---|---|
|  | |
| 1RB#0 | 1RB#0 |





### Low Channel

| | |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### Middle Channel

| | |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-10MHz Channel Bandwidth PAPR

| QPSK | 16QAM |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### Low Channel

| | |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### Middle Channel

| | |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-15MHz Channel Bandwidth PAPR

| QPSK | 16QAM |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### Low Channel

| | |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### Middle Channel

| | |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-20MHz Channel Bandwidth PAPR

| QPSK | 16QAM |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### Low Channel

| | |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### Middle Channel

| | |
|---|---|
|  |  |
| 1RB#0 | 1RB#0 |





### High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## 3.3 Occupied Bandwidth and Emission Bandwidth

**LIMIT**

N/A

**TEST CONFIGURATION**




**TEST PROCEDURE**

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at low, middle and high channel in each band. The -26dBc Emission bandwidth was also measured and recorded. Set RBW was set to about 1% of emission BW, VBW≥3 times RBW.
-26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

**TEST RESULTS**

*Remark:*

1. *We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case for each Channel Bandwidth of LTE FDD Band 4.*

| *LTE FDD Band 4* | | | | | | |
|---|---|---|---|---|---|---|
| TX Channel Bandwidth | RB Size/Offset | Frequency (MHz) | -26dBc Emission bandwidth (MHz) | | 99% Occupied bandwidth (MHz) | |
| | | | QPSK | 16QAM | QPSK | 16QAM |
| 1.4 MHz | *6RB#0* | 1710.7 | 1.284 | 1.293 | 1.0971 | 1.0950 |
| | | 1732.5 | 1.296 | 1.276 | 1.0972 | 1.0880 |
| | | 1754.3 | 1.298 | 1.296 | 1.0945 | 1.0974 |
| 3 MHz | *15RB#0* | 1711.5 | 2.890 | 2.909 | 2.6874 | 2.6836 |
| | | 1732.5 | 2.893 | 2.936 | 2.6882 | 2.6842 |
| | | 1753.5 | 2.904 | 2.894 | 2.6889 | 2.6871 |
| 5 MHz | *25RB#0* | 1712.5 | 4.967 | 4.909 | 4.4967 | 4.4954 |
| | | 1732.5 | 4.919 | 4.963 | 4.4883 | 4.4968 |
| | | 1752.5 | 4.942 | 4.924 | 4.5056 | 4.5082 |
| 10 MHz | *50RB#0* | 1715.0 | 9.765 | 9.778 | 8.9894 | 8.9929 |
| | | 1732.5 | 9.757 | 9.816 | 8.9883 | 8.9906 |
| | | 1750.0 | 9.762 | 9.783 | 8.9764 | 8.9877 |
| 15 MHz | *75RB#0* | 1717.5 | 14.71 | 14.66 | 13.493 | 13.488 |
| | | 1732.5 | 19.85 | 16.83 | 13.488 | 13.525 |
| | | 1747.5 | 14.62 | 14.70 | 13.432 | 13.476 |
| 20 MHz | *100RB#0* | 1720.0 | 19.34 | 19.38 | 17.970 | 18.022 |
| | | 1732.5 | 19.58 | 19.30 | 17.947 | 17.964 |
| | | 1745.0 | 19.29 | 19.29 | 17.942 | 17.957 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-1.4MHz Channel Bandwidth

| QPSK | 16QAM |
|---|---|
|  |  |
| 6RB#0 | 6RB#0 |



### Low Channel

| | |
|---|---|
|  |  |
| 6RB#0 | 6RB#0 |



### Middle Channel

| | |
|---|---|
|  |  |
| 6RB#0 | 6RB#0 |



### High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-3MHz Channel Bandwidth

### QPSK




15RB#0

### 16QAM




15RB#0

## Low Channel




15RB#0




15RB#0

## Middle Channel




15RB#0




15RB#0

## High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-5MHz Channel Bandwidth

| QPSK | 16QAM |
|---|---|
|  |  |
| 25RB#0 | 25RB#0 |



### Low Channel

| | |
|---|---|
|  |  |
| 25RB#0 | 25RB#0 |



### Middle Channel

| | |
|---|---|
|  |  |
| 25RB#0 | 25RB#0 |



### High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-10MHz Channel Bandwidth

### QPSK




50RB#0

### 16QAM




50RB#0

### Low Channel




50RB#0




50RB#0

### Middle Channel




50RB#0




50RB#0

### High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-15MHz Channel Bandwidth

| QPSK | 16QAM |
|---|---|
|  |  |
| 75RB#0 | 75RB#0 |





### Low Channel

| | |
|---|---|
|  |  |
| 75RB#0 | 75RB#0 |





### Middle Channel

| | |
|---|---|
|  |  |
| 75RB#0 | 75RB#0 |





### High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## LTE FDD Band 4-20MHz Channel Bandwidth

### QPSK




100RB#0

### 16QAM




100RB#0

## Low Channel




100RB#0




100RB#0

## Middle Channel




100RB#0




100RB#0

## High Channel

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## 3.4 Band Edge Compliance

**LIMIT**

According to §27.53 (h): For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least 43 + 10 log10(P) dB.

**TEST CONFIGURATION**




**TEST PROCEDURE**

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest and highest channels for each band and different modulation.
5. Measure Band edge using RMS (Average) detector by spectrum.

**TEST RESULTS**

*Remark:*

1. *We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case for each Channel Bandwidth of LTE FDD Band 4.*

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

| LTE FDD Band 4-1.4MHz Channel Bandwidth Band Edge Compliance | |
|---|---|
| QPSK | 16QAM |
|  |  |
| 6RB#0 | 6RB#0 |
| Low Channel | |
|  |  |
| 6RB#0 | 6RB#0 |
| High Channel | |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

| LTE FDD Band 4-3MHz Channel Bandwidth Band Edge Compliance | |
|---|---|
| QPSK | 16QAM |
|  |  |
| 15RB#0 | 15RB#0 |
| Low Channel | |
|  |  |
| 15RB#0 | 15RB#0 |
| High Channel | |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

TEL：+86-755 2302 9901 FAX ：+86-755 2302 9901 E-mail：service@cer-mark.com
Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

## LTE FDD Band 4-5MHz Channel Bandwidth Band Edge Compliance

| QPSK | 16QAM |
|---|---|
|  |  |
| 25RB#0 | 25RB#0 |
| Low Channel | |
|  |  |
| 25RB#0 | 25RB#0 |
| High Channel | |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

TEL：+86-755 2302 9901 FAX ：+86-755 2302 9901 E-mail：service@cer-mark.com
Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

| LTE FDD Band 4-10MHz Channel Bandwidth Band Edge Compliance | |
|---|---|
| QPSK | 16QAM |
|  |  |
| 50RB#0 | 50RB#0 |
| Low Channel | |
|  |  |
| 50RB#0 | 50RB#0 |
| High Channel | |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

| LTE FDD Band 4-15MHz Channel Bandwidth Band Edge Compliance | |
|---|---|
| QPSK | 16QAM |
|  |  |
| 75RB#0 | 75RB#0 |
| Low Channel | |
|  |  |
| 75RB#0 | 75RB#0 |
| High Channel | |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

| LTE FDD Band 4-20MHz Channel Bandwidth Band Edge Compliance | |
|---|---|
| QPSK | 16QAM |
|  |  |
| 100RB#0 | 100RB#0 |
| Low Channel | |
|  |  |
| 100RB#0 | 100RB#0 |
| High Channel | |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

## 3.5 Spurious Emission

**LIMIT**

According to §27.53 (h): For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least 43 + 10 log10(P) dB.

**TEST CONFIGURATION**

Conducted Spurious Measurement:




Radiated Spurious Measurement:




**TEST PROCEDURE**

The EUT was setup according to EIA/TIA 603D.

**Conducted Spurious Measurement:**

a. Place the EUT on a bench and set it in transmitting mode.
b. Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
c. EUT Communicate with CMW500, then select a channel for testing.
d. Add a correction factor to the display of spectrum, and then test.
e. The resolution bandwidth of the spectrum analyzer was set sufficient scans were taken to show the out of band Emission if any up to10th harmonic.
f. Please refer to following tables for test antenna conducted emissions.

| Working Frequency | Sub range (GHz) | RBW | VBW | Sweep time (s) |
|---|---|---|---|---|
| LTE FDD Band 4 | 0.000015~0.03 | 10KHz | 30KHz | Auto |
| | 0.03~1 | 100KHz | 300KHz | Auto |
| | 1~20 | 1 MHz | 3 MHz | Auto |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

**Radiated Spurious Measurement:**

a. The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
b. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter.
c. The output of the test antenna shall be connected to the measuring receiver.
d. The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
e. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
f. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
g. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
h. The maximum signal level detected by the measuring receiver shall be noted.
i. The transmitter shall be replaced by a substitution antenna.
j. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
k. The substitution antenna shall be connected to a calibrated signal generator.
l. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
m. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
n. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
o. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
p. The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
q. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for Part 22 and 1MHz for Part 24. The frequency range was checked up to 10th harmonic.
r. Test site anechoic chamber refer to ANSI C63.

**TEST RESULTS**

*Remark:*

1. *We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case for each Channel Bandwidth of LTE FDD Band 4.*

**Conducted Measurement:**

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

| LTE FDD Band 4-1.4MHz Channel Bandwidth | |
|---|---|
| Low Channel | |
| QPSK | 16QAM |
|   |   |
| 0.15MHz~30MHz | 0.15MHz~30MHz |
|   |   |
| 30MHz~1GHz | 30MHz~1GHz |
|   |   |
| 1GHz~3GHz | 1GHz~3GHz |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

3GHz~20GHz

1RB#0

3GHz~20GHz

1RB#0

| *LTE FDD Band 4-1.4MHz Channel Bandwidth* | |
|---|---|
| *Middle Channel* | |
| *QPSK* | *16QAM* |




0.15MHz~30MHz




0.15MHz~30MHz




30MHz~1GHz




30MHz~1GHz

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

1GHz~3GHz




1GHz~3GHz




3GHz~20GHz




3GHz~20GHz

1RB#0 | 1RB#0

*LTE FDD Band 4-1.4MHz Channel Bandwidth*

*High Channel*

*QPSK* | *16QAM*




0.15MHz~30MHz




0.15MHz~30MHz

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.




30MHz~1GHz




30MHz~1GHz

1GHz~3GHz




1GHz~3GHz

3GHz~20GHz

1RB#0




3GHz~20GHz

1RB#0

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

| LTE FDD Band 4-3MHz Channel Bandwidth | |
|---|---|
| Low Channel | |
| QPSK | 16QAM |
|  |  |
| 0.15MHz~30MHz | 0.15MHz~30MHz |
|  |  |
| 30MHz~1GHz | 30MHz~1GHz |
|  |  |
| 1GHz~3GHz | 1GHz~3GHz |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.

3GHz~20GHz

1RB#0




3GHz~20GHz

1RB#0

*LTE FDD Band 4-3MHz Channel Bandwidth*

*Middle Channel*

*QPSK*




0.15MHz~30MHz

30MHz~1GHz

*16QAM*




0.15MHz~30MHz




30MHz~1GHz

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.




1GHz~3GHz




1GHz~3GHz




3GHz~20GHz




3GHz~20GHz

1RB#0 | 1RB#0

| *LTE FDD Band 4-3MHz Channel Bandwidth* | |
|---|---|
| *High Channel* | |
| *QPSK* | *16QAM* |




0.15MHz~30MHz




0.15MHz~30MHz

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.




30MHz~1GHz




30MHz~1GHz




1GHz~3GHz




1GHz~3GHz




3GHz~20GHz

1RB#0




3GHz~20GHz

1RB#0

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAK, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.cer-mark.com.