







The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Radiated Measurement:

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 12; recorded worst case for each Channel Bandwidth of LTE FDD Band 12.
2. $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + G_a(dBi)$
3. We were not recorded other points as values lower than limits.
4. Margin = Limit – EIRP

Test Model No.: I16 Pro max

LTE FDD Band 12_Channel Bandwidth 1.4MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1399.4	-46.41	2.86	3.00	7.25	-44.17	-13.00	31.17	H
2099.1	-48.19	2.94	3.00	9.53	-43.75	-13.00	30.75	H
1399.4	-47.52	2.86	3.00	7.25	-45.28	-13.00	32.28	V
2099.1	-52.6	2.94	3.00	9.53	-48.16	-13.00	35.16	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.0	-46.22	2.86	3.00	7.25	-43.98	-13.00	30.98	H
2122.5	-43.12	2.94	3.00	9.53	-38.68	-13.00	25.68	H
1415.0	-48.23	2.86	3.00	7.25	-45.99	-13.00	32.99	V
2122.5	-50.12	2.94	3.00	9.53	-45.68	-13.00	32.68	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-45.24	2.86	3.00	7.25	-43	-13.00	30	H
2145.9	-45.76	2.94	3.00	9.53	-41.32	-13.00	28.32	H
1430.6	-46.97	2.86	3.00	7.25	-44.73	-13.00	31.73	V
2145.9	-47.33	2.94	3.00	9.53	-42.89	-13.00	29.89	V

LTE FDD Band 12_Channel Bandwidth 3MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1401.0	-50.03	2.86	3.00	7.25	-47.79	-13.00	34.79	H
2101.5	-45.15	2.94	3.00	9.53	-40.71	-13.00	27.71	H
1401.0	-45.31	2.86	3.00	7.25	-43.07	-13.00	30.07	V
2101.5	-49.42	2.94	3.00	9.53	-44.98	-13.00	31.98	V

LTE FDD Band 12_Channel Bandwidth 3MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.0	-47.6	2.86	3.00	7.25	-45.36	-13.00	32.36	H
2122.5	-45.8	2.94	3.00	9.53	-41.36	-13.00	28.36	H
1415.0	-45.56	2.86	3.00	7.25	-43.32	-13.00	30.32	V
2122.5	-47.7	2.94	3.00	9.53	-43.26	-13.00	30.26	V

LTE FDD Band 12_Channel Bandwidth 3MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-46.33	2.86	3.00	7.25	-44.09	-13.00	31.09	H
2143.5	-46.81	2.94	3.00	9.53	-42.37	-13.00	29.37	H
1429.0	-47.05	2.86	3.00	7.25	-44.81	-13.00	31.81	V
2143.5	-49.28	2.94	3.00	9.53	-44.84	-13.00	31.84	V

LTE FDD Band 12_Channel Bandwidth 5MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1403.0	-46.94	2.86	3.00	7.25	-44.7	-13.00	31.7	H
2104.5	-47.32	2.94	3.00	9.53	-42.88	-13.00	29.88	H
1403.0	-48.29	2.86	3.00	7.25	-46.05	-13.00	33.05	V
2104.5	-50.15	2.94	3.00	9.53	-45.71	-13.00	32.71	V

LTE FDD Band 12_Channel Bandwidth 5MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.0	-45.13	2.86	3.00	7.25	-42.89	-13.00	29.89	H
2122.5	-43.27	2.94	3.00	9.53	-38.83	-13.00	25.83	H
1415.0	-48.23	2.86	3.00	7.25	-45.99	-13.00	32.99	V
2122.5	-50.75	2.94	3.00	9.53	-46.31	-13.00	33.31	V

LTE FDD Band 12_Channel Bandwidth 5MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-44.87	2.86	3.00	7.25	-42.63	-13.00	29.63	H
2140.5	-45.03	2.94	3.00	9.53	-40.59	-13.00	27.59	H
1427.0	-46.75	2.86	3.00	7.25	-44.51	-13.00	31.51	V
2140.5	-48.32	2.94	3.00	9.53	-43.88	-13.00	30.88	V

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1408.0	-48.19	2.86	3.00	7.25	-45.95	-13.00	32.95	H
2112.0	-46.82	2.94	3.00	9.53	-42.38	-13.00	29.38	H
1408.0	-48.35	2.86	3.00	7.25	-46.11	-13.00	33.11	V
2112.0	-47.84	2.94	3.00	9.53	-43.4	-13.00	30.4	V

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.0	-46.64	2.86	3.00	7.25	-44.4	-13.00	31.4	H
2122.5	-42.96	2.94	3.00	9.53	-38.52	-13.00	25.52	H
1415.0	-46.94	2.86	3.00	7.25	-44.7	-13.00	31.7	V
2122.5	-49.11	2.94	3.00	9.53	-44.67	-13.00	31.67	V

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-47.66	2.86	3.00	7.25	-45.42	-13.00	32.42	H
2133.0	-45.85	2.94	3.00	9.53	-41.41	-13.00	28.41	H
1422.0	-48.95	2.86	3.00	7.25	-46.71	-13.00	33.71	V
2133.0	-47.37	2.94	3.00	9.53	-42.93	-13.00	29.93	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1399.4	-45.86	2.86	3.00	7.25	-43.62	-13.00	30.62	H
2099.1	-45.93	2.94	3.00	9.53	-41.49	-13.00	28.49	H
1399.4	-45.9	2.86	3.00	7.25	-43.66	-13.00	30.66	V
2099.1	-49.02	2.94	3.00	9.53	-44.58	-13.00	31.58	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.0	-45.78	2.86	3.00	7.25	-43.54	-13.00	30.54	H
2122.5	-47.07	2.94	3.00	9.53	-42.63	-13.00	29.63	H
1415.0	-45.26	2.86	3.00	7.25	-43.02	-13.00	30.02	V
2122.5	-48.22	2.94	3.00	9.53	-43.78	-13.00	30.78	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-45.02	2.86	3.00	7.25	-42.78	-13.00	29.78	H
2145.9	-45.66	2.94	3.00	9.53	-41.22	-13.00	28.22	H
1430.6	-45.93	2.86	3.00	7.25	-43.69	-13.00	30.69	V
2145.9	-48.04	2.94	3.00	9.53	-43.6	-13.00	30.6	V

LTE FDD Band 12_Channel Bandwidth 3MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1401.0	-46.32	2.86	3.00	7.25	-44.08	-13.00	31.08	H
2101.5	-45.74	2.94	3.00	9.53	-41.3	-13.00	28.3	H
1401.0	-44.77	2.86	3.00	7.25	-42.53	-13.00	29.53	V
2101.5	-50.65	2.94	3.00	9.53	-46.21	-13.00	33.21	V

LTE FDD Band 12_Channel Bandwidth 3MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.0	-46.17	2.86	3.00	7.25	-43.93	-13.00	30.93	H
2122.5	-46.81	2.94	3.00	9.53	-42.37	-13.00	29.37	H
1415.0	-44.96	2.86	3.00	7.25	-42.72	-13.00	29.72	V
2122.5	-47.98	2.94	3.00	9.53	-43.54	-13.00	30.54	V

LTE FDD Band 12_Channel Bandwidth 3MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-46.6	2.86	3.00	7.25	-44.36	-13.00	31.36	H
2143.5	-43.88	2.94	3.00	9.53	-39.44	-13.00	26.44	H
1429.0	-44.88	2.86	3.00	7.25	-42.64	-13.00	29.64	V
2143.5	-51.09	2.94	3.00	9.53	-46.65	-13.00	33.65	V

LTE FDD Band 12_Channel Bandwidth 5MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1403.0	-47.7	2.86	3.00	7.25	-45.46	-13.00	32.46	H
2104.5	-43.64	2.94	3.00	9.53	-39.2	-13.00	26.2	H
1403.0	-49.85	2.86	3.00	7.25	-47.61	-13.00	34.61	V
2104.5	-48.71	2.94	3.00	9.53	-44.27	-13.00	31.27	V

LTE FDD Band 12_Channel Bandwidth 5MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.0	-48.14	2.86	3.00	7.25	-45.9	-13.00	32.9	H
2122.5	-44.35	2.94	3.00	9.53	-39.91	-13.00	26.91	H
1415.0	-45.03	2.86	3.00	7.25	-42.79	-13.00	29.79	V
2122.5	-49.53	2.94	3.00	9.53	-45.09	-13.00	32.09	V

LTE FDD Band 12_Channel Bandwidth 5MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-46.23	2.86	3.00	7.25	-43.99	-13.00	30.99	H
2140.5	-46.06	2.94	3.00	9.53	-41.62	-13.00	28.62	H
1427.0	-45.41	2.86	3.00	7.25	-43.17	-13.00	30.17	V
2140.5	-50.41	2.94	3.00	9.53	-45.97	-13.00	32.97	V

LTE FDD Band 12_Channel Bandwidth 10MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1408.0	-47.35	2.86	3.00	7.25	-45.11	-13.00	32.11	H
2112.0	-46.91	2.94	3.00	9.53	-42.47	-13.00	29.47	H
1408.0	-46.95	2.86	3.00	7.25	-44.71	-13.00	31.71	V
2112.0	-47.27	2.94	3.00	9.53	-42.83	-13.00	29.83	V

LTE FDD Band 12_Channel Bandwidth 10MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.0	-46.9	2.86	3.00	7.25	-44.66	-13.00	31.66	H
2122.5	-43.53	2.94	3.00	9.53	-39.09	-13.00	26.09	H
1415.0	-45.28	2.86	3.00	7.25	-43.04	-13.00	30.04	V
2122.5	-50.02	2.94	3.00	9.53	-45.58	-13.00	32.58	V

LTE FDD Band 12_Channel Bandwidth 10MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-43.92	2.86	3.00	7.25	-41.68	-13.00	28.68	H
2133.0	-44.43	2.94	3.00	9.53	-39.99	-13.00	26.99	H
1422.0	-45.6	2.86	3.00	7.25	-43.36	-13.00	30.36	V
2133.0	-46.97	2.94	3.00	9.53	-42.53	-13.00	29.53	V

All modes of operation were investigated and the worst-case emissions are reported.

Series Model No.: S26 Ultra

LTE FDD Band 12_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-45.09	2.86	3.00	7.25	-42.85	-13.00	29.85	H
2145.9	-45.51	2.94	3.00	9.53	-41.07	-13.00	28.07	H
1430.6	-48.02	2.86	3.00	7.25	-45.78	-13.00	32.78	V
2145.9	-49.14	2.94	3.00	9.53	-44.7	-13.00	31.7	V

LTE FDD Band 12_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-44.4	2.86	3.00	7.25	-42.16	-13.00	29.16	H
2143.5	-43.77	2.94	3.00	9.53	-39.33	-13.00	26.33	H
1429.0	-46.32	2.86	3.00	7.25	-44.08	-13.00	31.08	V
2143.5	-49.01	2.94	3.00	9.53	-44.57	-13.00	31.57	V

LTE FDD Band 12_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-45.66	2.86	3.00	7.25	-43.42	-13.00	30.42	H
2140.5	-44.45	2.94	3.00	9.53	-40.01	-13.00	27.01	H
1427.0	-44.91	2.86	3.00	7.25	-42.67	-13.00	29.67	V
2140.5	-47.74	2.94	3.00	9.53	-43.3	-13.00	30.3	V

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-46.81	2.86	3.00	7.25	-44.57	-13.00	31.57	H
2133.0	-44.17	2.94	3.00	9.53	-39.73	-13.00	26.73	H
1422.0	-45.33	2.86	3.00	7.25	-43.09	-13.00	30.09	V
2133.0	-46.99	2.94	3.00	9.53	-42.55	-13.00	29.55	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-44.66	2.86	3.00	7.25	-42.42	-13.00	29.42	H
2145.9	-44.73	2.94	3.00	9.53	-40.29	-13.00	27.29	H
1430.6	-47.15	2.86	3.00	7.25	-44.91	-13.00	31.91	V
2145.9	-49.17	2.94	3.00	9.53	-44.73	-13.00	31.73	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

LTE FDD Band 12_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-46.46	2.86	3.00	7.25	-44.22	-13.00	31.22	H
2143.5	-44.94	2.94	3.00	9.53	-40.5	-13.00	27.5	H
1429.0	-45.77	2.86	3.00	7.25	-43.53	-13.00	30.53	V
2143.5	-47.39	2.94	3.00	9.53	-42.95	-13.00	29.95	V

LTE FDD Band 12_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-45.12	2.86	3.00	7.25	-42.88	-13.00	29.88	H
2140.5	-46	2.94	3.00	9.53	-41.56	-13.00	28.56	H
1427.0	-46.82	2.86	3.00	7.25	-44.58	-13.00	31.58	V
2140.5	-47.22	2.94	3.00	9.53	-42.78	-13.00	29.78	V

LTE FDD Band 12_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-46.35	2.86	3.00	7.25	-44.11	-13.00	31.11	H
2133.0	-44.27	2.94	3.00	9.53	-39.83	-13.00	26.83	H
1422.0	-47.99	2.86	3.00	7.25	-45.75	-13.00	32.75	V
2133.0	-47.1	2.94	3.00	9.53	-42.66	-13.00	29.66	V

Series Model No.: Pixel 9

LTE FDD Band 12_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-45.44	2.86	3.00	7.25	-43.2	-13.00	30.2	H
2145.9	-44.37	2.94	3.00	9.53	-39.93	-13.00	26.93	H
1430.6	-46.64	2.86	3.00	7.25	-44.4	-13.00	31.4	V
2145.9	-47.51	2.94	3.00	9.53	-43.07	-13.00	30.07	V

LTE FDD Band 12_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-46.98	2.86	3.00	7.25	-44.74	-13.00	31.74	H
2143.5	-44.26	2.94	3.00	9.53	-39.82	-13.00	26.82	H
1429.0	-47.36	2.86	3.00	7.25	-45.12	-13.00	32.12	V
2143.5	-48.84	2.94	3.00	9.53	-44.4	-13.00	31.4	V

LTE FDD Band 12_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-45.75	2.86	3.00	7.25	-43.51	-13.00	30.51	H
2140.5	-45.2	2.94	3.00	9.53	-40.76	-13.00	27.76	H
1427.0	-46.68	2.86	3.00	7.25	-44.44	-13.00	31.44	V
2140.5	-49.57	2.94	3.00	9.53	-45.13	-13.00	32.13	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-45.13	2.86	3.00	7.25	-42.89	-13.00	29.89	H
2133.0	-43.64	2.94	3.00	9.53	-39.2	-13.00	26.2	H
1422.0	-46.81	2.86	3.00	7.25	-44.57	-13.00	31.57	V
2133.0	-48.39	2.94	3.00	9.53	-43.95	-13.00	30.95	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-47.1	2.86	3.00	7.25	-44.86	-13.00	31.86	H
2145.9	-45.68	2.94	3.00	9.53	-41.24	-13.00	28.24	H
1430.6	-48.32	2.86	3.00	7.25	-46.08	-13.00	33.08	V
2145.9	-49.71	2.94	3.00	9.53	-45.27	-13.00	32.27	V

LTE FDD Band 12_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-46.26	2.86	3.00	7.25	-44.02	-13.00	31.02	H
2143.5	-43.56	2.94	3.00	9.53	-39.12	-13.00	26.12	H
1429.0	-46.05	2.86	3.00	7.25	-43.81	-13.00	30.81	V
2143.5	-48.62	2.94	3.00	9.53	-44.18	-13.00	31.18	V

LTE FDD Band 12_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-44.75	2.86	3.00	7.25	-42.51	-13.00	29.51	H
2140.5	-45.09	2.94	3.00	9.53	-40.65	-13.00	27.65	H
1427.0	-45.01	2.86	3.00	7.25	-42.77	-13.00	29.77	V
2140.5	-49.06	2.94	3.00	9.53	-44.62	-13.00	31.62	V

LTE FDD Band 12_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-47.15	2.86	3.00	7.25	-44.91	-13.00	31.91	H
2133.0	-46.27	2.94	3.00	9.53	-41.83	-13.00	28.83	H
1422.0	-48.4	2.86	3.00	7.25	-46.16	-13.00	33.16	V
2133.0	-48.06	2.94	3.00	9.53	-43.62	-13.00	30.62	V

Series Model No.: SP30 Pro

LTE FDD Band 12_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-44.96	2.86	3.00	7.25	-42.72	-13.00	29.72	H
2145.9	-45.76	2.94	3.00	9.53	-41.32	-13.00	28.32	H
1430.6	-46.94	2.86	3.00	7.25	-44.7	-13.00	31.7	V
2145.9	-48.33	2.94	3.00	9.53	-43.89	-13.00	30.89	V

LTE FDD Band 12_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-44.88	2.86	3.00	7.25	-42.64	-13.00	29.64	H
2143.5	-45.05	2.94	3.00	9.53	-40.61	-13.00	27.61	H
1429.0	-45.76	2.86	3.00	7.25	-43.52	-13.00	30.52	V
2143.5	-48.29	2.94	3.00	9.53	-43.85	-13.00	30.85	V

LTE FDD Band 12_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-47.53	2.86	3.00	7.25	-45.29	-13.00	32.29	H
2140.5	-44.21	2.94	3.00	9.53	-39.77	-13.00	26.77	H
1427.0	-48.54	2.86	3.00	7.25	-46.3	-13.00	33.3	V
2140.5	-48.52	2.94	3.00	9.53	-44.08	-13.00	31.08	V

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-44.9	2.86	3.00	7.25	-42.66	-13.00	29.66	H
2133.0	-44.16	2.94	3.00	9.53	-39.72	-13.00	26.72	H
1422.0	-45.53	2.86	3.00	7.25	-43.29	-13.00	30.29	V
2133.0	-48.81	2.94	3.00	9.53	-44.37	-13.00	31.37	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-44.81	2.86	3.00	7.25	-42.57	-13.00	29.57	H
2145.9	-43.74	2.94	3.00	9.53	-39.3	-13.00	26.3	H
1430.6	-45.99	2.86	3.00	7.25	-43.75	-13.00	30.75	V
2145.9	-49.36	2.94	3.00	9.53	-44.92	-13.00	31.92	V

LTE FDD Band 12_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-44.62	2.86	3.00	7.25	-42.38	-13.00	29.38	H
2143.5	-45.93	2.94	3.00	9.53	-41.49	-13.00	28.49	H
1429.0	-46.29	2.86	3.00	7.25	-44.05	-13.00	31.05	V
2143.5	-49.87	2.94	3.00	9.53	-45.43	-13.00	32.43	V

LTE FDD Band 12_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-44.54	2.86	3.00	7.25	-42.3	-13.00	29.3	H
2140.5	-45.43	2.94	3.00	9.53	-40.99	-13.00	27.99	H
1427.0	-46.21	2.86	3.00	7.25	-43.97	-13.00	30.97	V
2140.5	-49.04	2.94	3.00	9.53	-44.6	-13.00	31.6	V

LTE FDD Band 12_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-45.62	2.86	3.00	7.25	-43.38	-13.00	30.38	H
2133.0	-45.29	2.94	3.00	9.53	-40.85	-13.00	27.85	H
1422.0	-45.32	2.86	3.00	7.25	-43.08	-13.00	30.08	V
2133.0	-47.07	2.94	3.00	9.53	-42.63	-13.00	29.63	V

Series Model No.: MT Ultimate

LTE FDD Band 12_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-45.3	2.86	3.00	7.25	-43.06	-13.00	30.06	H
2145.9	-45.07	2.94	3.00	9.53	-40.63	-13.00	27.63	H
1430.6	-47.46	2.86	3.00	7.25	-45.22	-13.00	32.22	V
2145.9	-50.11	2.94	3.00	9.53	-45.67	-13.00	32.67	V

LTE FDD Band 12_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-45.3	2.86	3.00	7.25	-43.06	-13.00	30.06	H
2143.5	-43.17	2.94	3.00	9.53	-38.73	-13.00	25.73	H
1429.0	-45.76	2.86	3.00	7.25	-43.52	-13.00	30.52	V
2143.5	-48.74	2.94	3.00	9.53	-44.3	-13.00	31.3	V

LTE FDD Band 12_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-47.93	2.86	3.00	7.25	-45.69	-13.00	32.69	H
2140.5	-45.89	2.94	3.00	9.53	-41.45	-13.00	28.45	H
1427.0	-47.64	2.86	3.00	7.25	-45.4	-13.00	32.4	V
2140.5	-47.83	2.94	3.00	9.53	-43.39	-13.00	30.39	V

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-44.55	2.86	3.00	7.25	-42.31	-13.00	29.31	H
2133.0	-45.85	2.94	3.00	9.53	-41.41	-13.00	28.41	H
1422.0	-46.9	2.86	3.00	7.25	-44.66	-13.00	31.66	V
2133.0	-48.61	2.94	3.00	9.53	-44.17	-13.00	31.17	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-46.03	2.86	3.00	7.25	-43.79	-13.00	30.79	H
2145.9	-45.6	2.94	3.00	9.53	-41.16	-13.00	28.16	H
1430.6	-47.16	2.86	3.00	7.25	-44.92	-13.00	31.92	V
2145.9	-49.29	2.94	3.00	9.53	-44.85	-13.00	31.85	V

LTE FDD Band 12 Channel Bandwidth 3MHz 16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-44.67	2.86	3.00	7.25	-42.43	-13.00	29.43	H
2143.5	-45.32	2.94	3.00	9.53	-40.88	-13.00	27.88	H
1429.0	-46.83	2.86	3.00	7.25	-44.59	-13.00	31.59	V
2143.5	-49.05	2.94	3.00	9.53	-44.61	-13.00	31.61	V

LTE FDD Band 12 Channel Bandwidth 5MHz 16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-44.6	2.86	3.00	7.25	-42.36	-13.00	29.36	H
2140.5	-45.54	2.94	3.00	9.53	-41.1	-13.00	28.1	H
1427.0	-47.75	2.86	3.00	7.25	-45.51	-13.00	32.51	V
2140.5	-48.1	2.94	3.00	9.53	-43.66	-13.00	30.66	V

LTE FDD Band 12 Channel Bandwidth 10MHz 16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-47.17	2.86	3.00	7.25	-44.93	-13.00	31.93	H
2133.0	-43.66	2.94	3.00	9.53	-39.22	-13.00	26.22	H
1422.0	-46.04	2.86	3.00	7.25	-43.8	-13.00	30.8	V
2133.0	-47.41	2.94	3.00	9.53	-42.97	-13.00	29.97	V

Series Model No.: M15 pro

LTE FDD Band 12 Channel Bandwidth 1.4MHz QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-46.68	2.86	3.00	7.25	-44.44	-13.00	31.44	H
2145.9	-44.29	2.94	3.00	9.53	-39.85	-13.00	26.85	H
1430.6	-47.85	2.86	3.00	7.25	-45.61	-13.00	32.61	V
2145.9	-48.49	2.94	3.00	9.53	-44.05	-13.00	31.05	V

LTE FDD Band 12 Channel Bandwidth 3MHz QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-44.95	2.86	3.00	7.25	-42.71	-13.00	29.71	H
2143.5	-44.3	2.94	3.00	9.53	-39.86	-13.00	26.86	H
1429.0	-48.01	2.86	3.00	7.25	-45.77	-13.00	32.77	V
2143.5	-49.2	2.94	3.00	9.53	-44.76	-13.00	31.76	V

LTE FDD Band 12 Channel Bandwidth 5MHz QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-46.02	2.86	3.00	7.25	-43.78	-13.00	30.78	H
2140.5	-43.19	2.94	3.00	9.53	-38.75	-13.00	25.75	H
1427.0	-47.94	2.86	3.00	7.25	-45.7	-13.00	32.7	V
2140.5	-48.32	2.94	3.00	9.53	-43.88	-13.00	30.88	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-46.89	2.86	3.00	7.25	-44.65	-13.00	31.65	H
2133.0	-46.49	2.94	3.00	9.53	-42.05	-13.00	29.05	H
1422.0	-47.46	2.86	3.00	7.25	-45.22	-13.00	32.22	V
2133.0	-49.39	2.94	3.00	9.53	-44.95	-13.00	31.95	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.6	-45.61	2.86	3.00	7.25	-43.37	-13.00	30.37	H
2145.9	-46.64	2.94	3.00	9.53	-42.2	-13.00	29.2	H
1430.6	-46.93	2.86	3.00	7.25	-44.69	-13.00	31.69	V
2145.9	-47.96	2.94	3.00	9.53	-43.52	-13.00	30.52	V

LTE FDD Band 12_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1429.0	-46.27	2.86	3.00	7.25	-44.03	-13.00	31.03	H
2143.5	-46.19	2.94	3.00	9.53	-41.75	-13.00	28.75	H
1429.0	-45.48	2.86	3.00	7.25	-43.24	-13.00	30.24	V
2143.5	-47.47	2.94	3.00	9.53	-43.03	-13.00	30.03	V

LTE FDD Band 12_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.0	-44.91	2.86	3.00	7.25	-42.67	-13.00	29.67	H
2140.5	-44.86	2.94	3.00	9.53	-40.42	-13.00	27.42	H
1427.0	-47.12	2.86	3.00	7.25	-44.88	-13.00	31.88	V
2140.5	-46.89	2.94	3.00	9.53	-42.45	-13.00	29.45	V

LTE FDD Band 12_Channel Bandwidth 10MHz_16QAM


Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-46.73	2.86	3.00	7.25	-44.49	-13.00	31.49	H
2133.0	-45.92	2.94	3.00	9.53	-41.48	-13.00	28.48	H
1422.0	-46.16	2.86	3.00	7.25	-43.92	-13.00	30.92	V
2133.0	-48.69	2.94	3.00	9.53	-44.25	-13.00	31.25	V

3.6 Frequency Stability Under Temperature & Voltage Variations

LIMIT

the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation and should not exceed 2.5ppm.

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D.

Frequency Stability Under Temperature Variations:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 12, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1V increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS

Remark:

1. We tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 12; recorded worst case.

LTE Band 12, 1.4MHz bandwidth (worst case of all bandwidths)

Frequency Error vs Voltage



Voltage (V)	Frequency error (Hz)		Frequency error (ppm)	
	QPSK	16QAM	QPSK	16QAM
4.25V	-6.58	-8.03	-0.009404	-0.011476
5.0V	-5.82	-5.38	-0.008318	-0.007689
5.75V	-8.43	-10.21	-0.012048	-0.014592

Frequency Error vs Temperature


Temperature (°C)	Frequency error (Hz)		Frequency error (ppm)	
	QPSK	16QAM	QPSK	16QAM
-30°	-7.34	-6.24	-0.010490	-0.008918
-20°	-8.07	-5.91	-0.011534	-0.008446
-10°	-8.83	-4.09	-0.012620	-0.005845
0°	-9.30	-6.51	-0.013291	-0.009304
10°	-6.51	-8.77	-0.009304	-0.012534
20°	-8.70	-6.67	-0.012434	-0.009533
30°	-10.34	-6.77	-0.014615	-0.009569
40°	-6.84	-8.75	-0.009668	-0.012367
50°	-10.41	-2.70	-0.014714	-0.003816

4 Test Setup Photos of the EUT



Test Model No.: I16 Pro max
Radiated Emissions



RF Conducted Emission




Series Model No.: S26 Ultra
Radiated Emissions



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



Series Model No.: Pixel 9
Radiated Emissions



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China


Series Model No.: SP30 Pro
Radiated Emissions



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



Series Model No.: MT Ultimate
Radiated Emissions



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Series Model No.: M15 pro
Radiated Emissions



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

5 Photos of the EUT

Reference to the report: ANNEX A of external photos and ANNEX B of internal photos.

.....**End of Report**.....