






1GHz~3GHz

1GHz~3GHz



3GHz~20GHz

1RB#0




3GHz~20GHz

1RB#0


LTE FDD Band 4-3MHz Channel Bandwidth High Channel

QPSK

16QAM




0.15MHz~30MHz




0.15MHz~30MHz



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.


Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
 Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



LTE FDD Band 4-10MHz Channel Bandwidth Middle Channel


QPSK

16QAM





30MHz~1GHz

30MHz~1GHz




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
 Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




1GHz~3GHz

1GHz~3GHz



3GHz~20GHz



3GHz~20GHz

1RB#0


1RB#0

LTE FDD Band 4-15MHz Channel Bandwidth


High Channel

QPSK

16QAM





0.15MHz~30MHz





0.15MHz~30MHz

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.






The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



1GHz~3GHz

1GHz~3GHz



3GHz~20GHz

3GHz~20GHz



1RB#0

1RB#0

LTE FDD Band 4-20MHz Channel Bandwidth High Channel

QPSK

16QAM




0.15MHz~30MHz

0.15MHz~30MHz

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Radiated Measurement:

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case for each Channel Bandwidth of LTE FDD Band 4.
2. $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + G_a(dBi)$
3. We were not recorded other points as values lower than limits.
4. $Margin = Limit - EIRP$

Test Model No.: I16 Pro max

LTE FDD Band 4 Channel Bandwidth 1.4MHz_QPSK_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3421.4	-45.56	4.02	3.00	12.5	-37.08	-13.00	24.08	H
5132.1	-49.04	5.11	3.00	13.38	-40.77	-13.00	27.77	H
3421.4	-53.15	4.02	3.00	12.5	-44.67	-13.00	31.67	V
5132.1	-48.83	5.11	3.00	13.38	-40.56	-13.00	27.56	V

LTE FDD Band 4 Channel Bandwidth 1.4MHz_QPSK_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-44.43	4.02	3.00	12.45	-36	-13.00	23	H
5197.5	-48.52	5.11	3.00	13.38	-40.25	-13.00	27.25	H
3465.0	-49.05	4.02	3.00	12.45	-40.62	-13.00	27.62	V
5197.5	-46.45	5.11	3.00	13.38	-38.18	-13.00	25.18	V

LTE FDD Band 4 Channel Bandwidth 1.4MHz_QPSK_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-44.34	4.02	3.00	12.21	-36.15	-13.00	23.15	H
5262.9	-47.15	5.11	3.00	13.26	-39	-13.00	26	H
3508.6	-47.97	4.02	3.00	12.21	-39.78	-13.00	26.78	V
5262.9	-48.19	5.11	3.00	13.26	-40.04	-13.00	27.04	V

LTE FDD Band 4 Channel Bandwidth 3MHz_QPSK_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3423.0	-49.27	4.02	3.00	12.5	-40.79	-13.00	27.79	H
5134.5	-54.1	5.11	3.00	13.38	-45.83	-13.00	32.83	H
3423.0	-54.04	4.02	3.00	12.5	-45.56	-13.00	32.56	V
5134.5	-50.45	5.11	3.00	13.38	-42.18	-13.00	29.18	V

LTE FDD Band 4 Channel Bandwidth 3MHz_QPSK_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-44.39	4.02	3.00	12.45	-35.96	-13.00	22.96	H
5197.5	-46.79	5.11	3.00	13.38	-38.52	-13.00	25.52	H
3465.0	-49.46	4.02	3.00	12.45	-41.03	-13.00	28.03	V
5197.5	-48.31	5.11	3.00	13.38	-40.04	-13.00	27.04	V

LTE FDD Band 4 Channel Bandwidth 3MHz QPSK High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-42.7	4.02	3.00	12.21	-34.51	-13.00	21.51	H
5260.5	-48.89	5.11	3.00	13.26	-40.74	-13.00	27.74	H
3507.0	-49.78	4.02	3.00	12.21	-41.59	-13.00	28.59	V
5260.5	-48.04	5.11	3.00	13.26	-39.89	-13.00	26.89	V

LTE FDD Band 4 Channel Bandwidth 5MHz QPSK Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3425.0	-48.01	4.02	3.00	12.5	-39.53	-13.00	26.53	H
5137.5	-51.77	5.11	3.00	13.38	-43.5	-13.00	30.5	H
3425.0	-53.95	4.02	3.00	12.5	-45.47	-13.00	32.47	V
5137.5	-53.62	5.11	3.00	13.38	-45.35	-13.00	32.35	V

LTE FDD Band 4 Channel Bandwidth 5MHz QPSK Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-44.52	4.02	3.00	12.45	-36.09	-13.00	23.09	H
5197.5	-47.7	5.11	3.00	13.38	-39.43	-13.00	26.43	H
3465.0	-50.18	4.02	3.00	12.45	-41.75	-13.00	28.75	V
5197.5	-47.58	5.11	3.00	13.38	-39.31	-13.00	26.31	V

LTE FDD Band 4 Channel Bandwidth 5MHz QPSK High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-41.88	4.02	3.00	12.21	-33.69	-13.00	20.69	H
5257.5	-47.56	5.11	3.00	13.26	-39.41	-13.00	26.41	H
3505.0	-49.04	4.02	3.00	12.21	-40.85	-13.00	27.85	V
5257.5	-47.57	5.11	3.00	13.26	-39.42	-13.00	26.42	V

LTE FDD Band 4 Channel Bandwidth 10MHz QPSK Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3430.0	-49.16	4.02	3.00	12.5	-40.68	-13.00	27.68	H
5145.0	-54.76	5.11	3.00	13.38	-46.49	-13.00	33.49	H
3430.0	-53.06	4.02	3.00	12.5	-44.58	-13.00	31.58	V
5145.0	-52.46	5.11	3.00	13.38	-44.19	-13.00	31.19	V

LTE FDD Band 4 Channel Bandwidth 10MHz QPSK Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-43.93	4.02	3.00	12.45	-35.5	-13.00	22.5	H
5197.5	-47.2	5.11	3.00	13.38	-38.93	-13.00	25.93	H
3465.0	-48.19	4.02	3.00	12.45	-39.76	-13.00	26.76	V
5197.5	-47.92	5.11	3.00	13.38	-39.65	-13.00	26.65	V

LTE FDD Band 4 Channel Bandwidth 10MHz QPSK High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-42.41	4.02	3.00	12.21	-34.22	-13.00	21.22	H
5250.0	-47.04	5.11	3.00	13.26	-38.89	-13.00	25.89	H
3500.0	-49.24	4.02	3.00	12.21	-41.05	-13.00	28.05	V
5250.0	-48.51	5.11	3.00	13.26	-40.36	-13.00	27.36	V

LTE FDD Band 4 Channel Bandwidth 15MHz QPSK Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3435.0	-50.63	4.02	3.00	12.5	-42.15	-13.00	29.15	H
5152.5	-53.44	5.11	3.00	13.38	-45.17	-13.00	32.17	H
3435.0	-53.26	4.02	3.00	12.5	-44.78	-13.00	31.78	V
5152.5	-55.55	5.11	3.00	13.38	-47.28	-13.00	34.28	V

LTE FDD Band 4 Channel Bandwidth 15MHz QPSK Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-44.72	4.02	3.00	12.45	-36.29	-13.00	23.29	H
5197.5	-47.72	5.11	3.00	13.38	-39.45	-13.00	26.45	H
3465.0	-51.09	4.02	3.00	12.45	-42.66	-13.00	29.66	V
5197.5	-48.14	5.11	3.00	13.38	-39.87	-13.00	26.87	V

LTE FDD Band 4 Channel Bandwidth 15MHz QPSK High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-42.9	4.02	3.00	12.21	-34.71	-13.00	21.71	H
5242.5	-46.79	5.11	3.00	13.26	-38.64	-13.00	25.64	H
3495.0	-49.76	4.02	3.00	12.21	-41.57	-13.00	28.57	V
5242.5	-47.73	5.11	3.00	13.26	-39.58	-13.00	26.58	V

LTE FDD Band 4 Channel Bandwidth 20MHz QPSK Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3440.0	-51.13	4.02	3.00	12.5	-42.65	-13.00	29.65	H
5160.0	-53.7	5.11	3.00	13.38	-45.43	-13.00	32.43	H
3440.0	-52.3	4.02	3.00	12.5	-43.82	-13.00	30.82	V
5160.0	-49.67	5.11	3.00	13.38	-41.4	-13.00	28.4	V

LTE FDD Band 4 Channel Bandwidth 20MHz QPSK Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-40.92	4.02	3.00	12.45	-32.49	-13.00	19.49	H
5197.5	-47.91	5.11	3.00	13.38	-39.64	-13.00	26.64	H
3465.0	-49.63	4.02	3.00	12.45	-41.2	-13.00	28.2	V
5197.5	-47.53	5.11	3.00	13.38	-39.26	-13.00	26.26	V

LTE FDD Band 4 Channel Bandwidth 20MHz QPSK High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-42.28	4.02	3.00	12.21	-34.09	-13.00	21.09	H
5235.0	-46.77	5.11	3.00	13.26	-38.62	-13.00	25.62	H
3490.0	-48.79	4.02	3.00	12.21	-40.6	-13.00	27.6	V
5235.0	-48.4	5.11	3.00	13.26	-40.25	-13.00	27.25	V

LTE FDD Band 4 Channel Bandwidth 1.4MHz 16QAM Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3421.4	-52.79	4.02	3.00	12.5	-44.31	-13.00	31.31	H
5132.1	-53.18	5.11	3.00	13.38	-44.91	-13.00	31.91	H
3421.4	-54.12	4.02	3.00	12.5	-45.64	-13.00	32.64	V
5132.1	-50.34	5.11	3.00	13.38	-42.07	-13.00	29.07	V

LTE FDD Band 4 Channel Bandwidth 1.4MHz 16QAM Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-44.44	4.02	3.00	12.45	-36.01	-13.00	23.01	H
5197.5	-48.16	5.11	3.00	13.38	-39.89	-13.00	26.89	H
3465.0	-49.84	4.02	3.00	12.45	-41.41	-13.00	28.41	V
5197.5	-46.62	5.11	3.00	13.38	-38.35	-13.00	25.35	V

LTE FDD Band 4 Channel Bandwidth 1.4MHz 16QAM High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-42.28	4.02	3.00	12.21	-34.09	-13.00	21.09	H
5262.9	-47.48	5.11	3.00	13.26	-39.33	-13.00	26.33	H
3508.6	-49.78	4.02	3.00	12.21	-41.59	-13.00	28.59	V
5262.9	-48.72	5.11	3.00	13.26	-40.57	-13.00	27.57	V

LTE FDD Band 4 Channel Bandwidth 3MHz 16QAM Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3423.0	-50.23	4.02	3.00	12.5	-41.75	-13.00	28.75	H
5134.5	-52	5.11	3.00	13.38	-43.73	-13.00	30.73	H
3423.0	-53.67	4.02	3.00	12.5	-45.19	-13.00	32.19	V
5134.5	-51.42	5.11	3.00	13.38	-43.15	-13.00	30.15	V

LTE FDD Band 4 Channel Bandwidth 3MHz 16QAM Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-44.28	4.02	3.00	12.45	-35.85	-13.00	22.85	H
5197.5	-47.96	5.11	3.00	13.38	-39.69	-13.00	26.69	H
3465.0	-50.34	4.02	3.00	12.45	-41.91	-13.00	28.91	V
5197.5	-46.92	5.11	3.00	13.38	-38.65	-13.00	25.65	V

LTE FDD Band 4 Channel Bandwidth 3MHz 16QAM High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-42.26	4.02	3.00	12.21	-34.07	-13.00	21.07	H
5260.5	-47.21	5.11	3.00	13.26	-39.06	-13.00	26.06	H
3507.0	-48.95	4.02	3.00	12.21	-40.76	-13.00	27.76	V
5260.5	-47.34	5.11	3.00	13.26	-39.19	-13.00	26.19	V

LTE FDD Band 4 Channel Bandwidth 5MHz 16QAM Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3425.0	-47.21	4.02	3.00	12.5	-38.73	-13.00	25.73	H
5137.5	-54.19	5.11	3.00	13.38	-45.92	-13.00	32.92	H
3425.0	-51.31	4.02	3.00	12.5	-42.83	-13.00	29.83	V
5137.5	-50.15	5.11	3.00	13.38	-41.88	-13.00	28.88	V

LTE FDD Band 4 Channel Bandwidth 5MHz 16QAM Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-43.17	4.02	3.00	12.45	-34.74	-13.00	21.74	H
5197.5	-47.93	5.11	3.00	13.38	-39.66	-13.00	26.66	H
3465.0	-48.55	4.02	3.00	12.45	-40.12	-13.00	27.12	V
5197.5	-46.85	5.11	3.00	13.38	-38.58	-13.00	25.58	V

LTE FDD Band 4 Channel Bandwidth 5MHz 16QAM High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-43.02	4.02	3.00	12.21	-34.83	-13.00	21.83	H
5257.5	-48.44	5.11	3.00	13.26	-40.29	-13.00	27.29	H
3505.0	-48.91	4.02	3.00	12.21	-40.72	-13.00	27.72	V
5257.5	-47.67	5.11	3.00	13.26	-39.52	-13.00	26.52	V

LTE FDD Band 4 Channel Bandwidth 10MHz 16QAM Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3430.0	-46.78	4.02	3.00	12.5	-38.3	-13.00	25.3	H
5145.0	-48.63	5.11	3.00	13.38	-40.36	-13.00	27.36	H
3430.0	-52.1	4.02	3.00	12.5	-43.62	-13.00	30.62	V
5145.0	-52.85	5.11	3.00	13.38	-44.58	-13.00	31.58	V

LTE FDD Band 4 Channel Bandwidth 10MHz 16QAM Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-44.16	4.02	3.00	12.45	-35.73	-13.00	22.73	H
5197.5	-48.45	5.11	3.00	13.38	-40.18	-13.00	27.18	H
3465.0	-49.94	4.02	3.00	12.45	-41.51	-13.00	28.51	V
5197.5	-46.82	5.11	3.00	13.38	-38.55	-13.00	25.55	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 4 Channel Bandwidth 10MHz 16QAM High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-42.17	4.02	3.00	12.21	-33.98	-13.00	20.98	H
5250.0	-47.39	5.11	3.00	13.26	-39.24	-13.00	26.24	H
3500.0	-49.36	4.02	3.00	12.21	-41.17	-13.00	28.17	V
5250.0	-48.3	5.11	3.00	13.26	-40.15	-13.00	27.15	V

LTE FDD Band 4 Channel Bandwidth 15MHz 16QAM Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3435.0	-48.18	4.02	3.00	12.5	-39.7	-13.00	26.7	H
5152.5	-51.36	5.11	3.00	13.38	-43.09	-13.00	30.09	H
3435.0	-54.83	4.02	3.00	12.5	-46.35	-13.00	33.35	V
5152.5	-53.61	5.11	3.00	13.38	-45.34	-13.00	32.34	V

LTE FDD Band 4 Channel Bandwidth 15MHz 16QAM Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-44.55	4.02	3.00	12.45	-36.12	-13.00	23.12	H
5197.5	-46.23	5.11	3.00	13.38	-37.96	-13.00	24.96	H
3465.0	-50.46	4.02	3.00	12.45	-42.03	-13.00	29.03	V
5197.5	-46.98	5.11	3.00	13.38	-38.71	-13.00	25.71	V

LTE FDD Band 4 Channel Bandwidth 15MHz 16QAM High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-42.86	4.02	3.00	12.21	-34.67	-13.00	21.67	H
5242.5	-47.57	5.11	3.00	13.26	-39.42	-13.00	26.42	H
3495.0	-48.79	4.02	3.00	12.21	-40.6	-13.00	27.6	V
5242.5	-49.1	5.11	3.00	13.26	-40.95	-13.00	27.95	V

LTE FDD Band 4 Channel Bandwidth 20MHz 16QAM Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3440.0	-49.09	4.02	3.00	12.5	-40.61	-13.00	27.61	H
5160.0	-52.3	5.11	3.00	13.38	-44.03	-13.00	31.03	H
3440.0	-51.02	4.02	3.00	12.5	-42.54	-13.00	29.54	V
5160.0	-53.96	5.11	3.00	13.38	-45.69	-13.00	32.69	V

LTE FDD Band 4 Channel Bandwidth 20MHz 16QAM Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-44.26	4.02	3.00	12.45	-35.83	-13.00	22.83	H
5197.5	-46.66	5.11	3.00	13.38	-38.39	-13.00	25.39	H
3465.0	-48.61	4.02	3.00	12.45	-40.18	-13.00	27.18	V
5197.5	-48.72	5.11	3.00	13.38	-40.45	-13.00	27.45	V

LTE FDD Band 4 Channel Bandwidth 20MHz 16QAM High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-41.33	4.02	3.00	12.21	-33.14	-13.00	20.14	H
5235.0	-46.88	5.11	3.00	13.26	-38.73	-13.00	25.73	H
3490.0	-48.34	4.02	3.00	12.21	-40.15	-13.00	27.15	V
5235.0	-49.15	5.11	3.00	13.26	-41	-13.00	28	V

All modes of operation were investigated and the worst-case emissions are reported.
Series Model No.: S26 Ultra

LTE FDD Band 4 Channel Bandwidth 1.4MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-42.8	4.02	3.00	12.21	-34.61	-13.00	21.61	H
5262.9	-46.45	5.11	3.00	13.26	-38.3	-13.00	25.3	H
3508.6	-48.96	4.02	3.00	12.21	-40.77	-13.00	27.77	V
5262.9	-48.15	5.11	3.00	13.26	-40	-13.00	27	V

LTE FDD Band 4 Channel Bandwidth 3MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-42.47	4.02	3.00	12.21	-34.28	-13.00	21.28	H
5260.5	-46.87	5.11	3.00	13.26	-38.72	-13.00	25.72	H
3507.0	-48.49	4.02	3.00	12.21	-40.3	-13.00	27.3	V
5260.5	-48.27	5.11	3.00	13.26	-40.12	-13.00	27.12	V

LTE FDD Band 4 Channel Bandwidth 5MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-42.42	4.02	3.00	12.21	-34.23	-13.00	21.23	H
5257.5	-46.36	5.11	3.00	13.26	-38.21	-13.00	25.21	H
3505.0	-49.27	4.02	3.00	12.21	-41.08	-13.00	28.08	V
5257.5	-48.6	5.11	3.00	13.26	-40.45	-13.00	27.45	V

LTE FDD Band 4 Channel Bandwidth 10MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-43.02	4.02	3.00	12.21	-34.83	-13.00	21.83	H
5250.0	-46.25	5.11	3.00	13.26	-38.1	-13.00	25.1	H
3500.0	-49.02	4.02	3.00	12.21	-40.83	-13.00	27.83	V
5250.0	-48.28	5.11	3.00	13.26	-40.13	-13.00	27.13	V

LTE FDD Band 4 Channel Bandwidth 15MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-43.01	4.02	3.00	12.21	-34.82	-13.00	21.82	H
5242.5	-46.32	5.11	3.00	13.26	-38.17	-13.00	25.17	H
3495.0	-49.36	4.02	3.00	12.21	-41.17	-13.00	28.17	V
5242.5	-48.34	5.11	3.00	13.26	-40.19	-13.00	27.19	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 4 Channel Bandwidth 20MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-43.42	4.02	3.00	12.21	-35.23	-13.00	22.23	H
5235.0	-46.81	5.11	3.00	13.26	-38.66	-13.00	25.66	H
3490.0	-48.9	4.02	3.00	12.21	-40.71	-13.00	27.71	V
5235.0	-48.73	5.11	3.00	13.26	-40.58	-13.00	27.58	V

LTE FDD Band 4 Channel Bandwidth 1.4MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-42.68	4.02	3.00	12.21	-34.49	-13.00	21.49	H
5262.9	-47.11	5.11	3.00	13.26	-38.96	-13.00	25.96	H
3508.6	-48.89	4.02	3.00	12.21	-40.7	-13.00	27.7	V
5262.9	-48.53	5.11	3.00	13.26	-40.38	-13.00	27.38	V

LTE FDD Band 4 Channel Bandwidth 3MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-42.72	4.02	3.00	12.21	-34.53	-13.00	21.53	H
5260.5	-46.46	5.11	3.00	13.26	-38.31	-13.00	25.31	H
3507.0	-48.79	4.02	3.00	12.21	-40.6	-13.00	27.6	V
5260.5	-48.86	5.11	3.00	13.26	-40.71	-13.00	27.71	V

LTE FDD Band 4 Channel Bandwidth 5MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-43.12	4.02	3.00	12.21	-34.93	-13.00	21.93	H
5257.5	-47.24	5.11	3.00	13.26	-39.09	-13.00	26.09	H
3505.0	-48.34	4.02	3.00	12.21	-40.15	-13.00	27.15	V
5257.5	-48.23	5.11	3.00	13.26	-40.08	-13.00	27.08	V

LTE FDD Band 4 Channel Bandwidth 10MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-43.24	4.02	3.00	12.21	-35.05	-13.00	22.05	H
5250.0	-47.09	5.11	3.00	13.26	-38.94	-13.00	25.94	H
3500.0	-49.18	4.02	3.00	12.21	-40.99	-13.00	27.99	V
5250.0	-48.74	5.11	3.00	13.26	-40.59	-13.00	27.59	V

LTE FDD Band 4 Channel Bandwidth 15MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-42.93	4.02	3.00	12.21	-34.74	-13.00	21.74	H
5242.5	-47.08	5.11	3.00	13.26	-38.93	-13.00	25.93	H
3495.0	-48.02	4.02	3.00	12.21	-39.83	-13.00	26.83	V
5242.5	-48.43	5.11	3.00	13.26	-40.28	-13.00	27.28	V

LTE FDD Band 4 Channel Bandwidth 20MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-43.54	4.02	3.00	12.21	-35.35	-13.00	22.35	H
5235.0	-46.66	5.11	3.00	13.26	-38.51	-13.00	25.51	H
3490.0	-48.56	4.02	3.00	12.21	-40.37	-13.00	27.37	V
5235.0	-47.96	5.11	3.00	13.26	-39.81	-13.00	26.81	V

Series Model No.: Pixel 9

LTE FDD Band 4 Channel Bandwidth 1.4MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-42.01	4.02	3.00	12.21	-33.82	-13.00	20.82	H
5262.9	-46.87	5.11	3.00	13.26	-38.72	-13.00	25.72	H
3508.6	-48.73	4.02	3.00	12.21	-40.54	-13.00	27.54	V
5262.9	-48.85	5.11	3.00	13.26	-40.7	-13.00	27.7	V

LTE FDD Band 4 Channel Bandwidth 3MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-42.75	4.02	3.00	12.21	-34.56	-13.00	21.56	H
5260.5	-46.47	5.11	3.00	13.26	-38.32	-13.00	25.32	H
3507.0	-49.21	4.02	3.00	12.21	-41.02	-13.00	28.02	V
5260.5	-48.62	5.11	3.00	13.26	-40.47	-13.00	27.47	V

LTE FDD Band 4 Channel Bandwidth 5MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-42.84	4.02	3.00	12.21	-34.65	-13.00	21.65	H
5257.5	-46.87	5.11	3.00	13.26	-38.72	-13.00	25.72	H
3505.0	-49.03	4.02	3.00	12.21	-40.84	-13.00	27.84	V
5257.5	-49	5.11	3.00	13.26	-40.85	-13.00	27.85	V

LTE FDD Band 4 Channel Bandwidth 10MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-43.28	4.02	3.00	12.21	-35.09	-13.00	22.09	H
5250.0	-46.23	5.11	3.00	13.26	-38.08	-13.00	25.08	H
3500.0	-48.83	4.02	3.00	12.21	-40.64	-13.00	27.64	V
5250.0	-47.8	5.11	3.00	13.26	-39.65	-13.00	26.65	V

LTE FDD Band 4 Channel Bandwidth 15MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-43	4.02	3.00	12.21	-34.81	-13.00	21.81	H
5242.5	-47.32	5.11	3.00	13.26	-39.17	-13.00	26.17	H
3495.0	-49.07	4.02	3.00	12.21	-40.88	-13.00	27.88	V
5242.5	-48.28	5.11	3.00	13.26	-40.13	-13.00	27.13	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 4 Channel Bandwidth 20MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-42.74	4.02	3.00	12.21	-34.55	-13.00	21.55	H
5235.0	-47.21	5.11	3.00	13.26	-39.06	-13.00	26.06	H
3490.0	-48.71	4.02	3.00	12.21	-40.52	-13.00	27.52	V
5235.0	-48.37	5.11	3.00	13.26	-40.22	-13.00	27.22	V

LTE FDD Band 4 Channel Bandwidth 1.4MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-42.89	4.02	3.00	12.21	-34.7	-13.00	21.7	H
5262.9	-46.85	5.11	3.00	13.26	-38.7	-13.00	25.7	H
3508.6	-49.53	4.02	3.00	12.21	-41.34	-13.00	28.34	V
5262.9	-48.52	5.11	3.00	13.26	-40.37	-13.00	27.37	V

LTE FDD Band 4 Channel Bandwidth 3MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-43.53	4.02	3.00	12.21	-35.34	-13.00	22.34	H
5260.5	-46.46	5.11	3.00	13.26	-38.31	-13.00	25.31	H
3507.0	-48.31	4.02	3.00	12.21	-40.12	-13.00	27.12	V
5260.5	-48.38	5.11	3.00	13.26	-40.23	-13.00	27.23	V

LTE FDD Band 4 Channel Bandwidth 5MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-43.27	4.02	3.00	12.21	-35.08	-13.00	22.08	H
5257.5	-46.74	5.11	3.00	13.26	-38.59	-13.00	25.59	H
3505.0	-48.42	4.02	3.00	12.21	-40.23	-13.00	27.23	V
5257.5	-47.85	5.11	3.00	13.26	-39.7	-13.00	26.7	V

LTE FDD Band 4 Channel Bandwidth 10MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-42.94	4.02	3.00	12.21	-34.75	-13.00	21.75	H
5250.0	-46.83	5.11	3.00	13.26	-38.68	-13.00	25.68	H
3500.0	-48	4.02	3.00	12.21	-39.81	-13.00	26.81	V
5250.0	-48.42	5.11	3.00	13.26	-40.27	-13.00	27.27	V

LTE FDD Band 4 Channel Bandwidth 15MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-42.75	4.02	3.00	12.21	-34.56	-13.00	21.56	H
5242.5	-47.1	5.11	3.00	13.26	-38.95	-13.00	25.95	H
3495.0	-48.73	4.02	3.00	12.21	-40.54	-13.00	27.54	V
5242.5	-48.05	5.11	3.00	13.26	-39.9	-13.00	26.9	V

LTE FDD Band 4 Channel Bandwidth 20MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-42.29	4.02	3.00	12.21	-34.1	-13.00	21.1	H
5235.0	-46.59	5.11	3.00	13.26	-38.44	-13.00	25.44	H
3490.0	-47.93	4.02	3.00	12.21	-39.74	-13.00	26.74	V
5235.0	-47.8	5.11	3.00	13.26	-39.65	-13.00	26.65	V

Series Model No.: SP30 Pro

LTE FDD Band 4 Channel Bandwidth 1.4MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-42.6	4.02	3.00	12.21	-34.41	-13.00	21.41	H
5262.9	-46.22	5.11	3.00	13.26	-38.07	-13.00	25.07	H
3508.6	-48.41	4.02	3.00	12.21	-40.22	-13.00	27.22	V
5262.9	-48.85	5.11	3.00	13.26	-40.7	-13.00	27.7	V

LTE FDD Band 4 Channel Bandwidth 3MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-43.04	4.02	3.00	12.21	-34.85	-13.00	21.85	H
5260.5	-46.53	5.11	3.00	13.26	-38.38	-13.00	25.38	H
3507.0	-48.71	4.02	3.00	12.21	-40.52	-13.00	27.52	V
5260.5	-48.59	5.11	3.00	13.26	-40.44	-13.00	27.44	V

LTE FDD Band 4 Channel Bandwidth 5MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-42.73	4.02	3.00	12.21	-34.54	-13.00	21.54	H
5257.5	-46.5	5.11	3.00	13.26	-38.35	-13.00	25.35	H
3505.0	-49.23	4.02	3.00	12.21	-41.04	-13.00	28.04	V
5257.5	-47.91	5.11	3.00	13.26	-39.76	-13.00	26.76	V

LTE FDD Band 4 Channel Bandwidth 10MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-43.08	4.02	3.00	12.21	-34.89	-13.00	21.89	H
5250.0	-47.08	5.11	3.00	13.26	-38.93	-13.00	25.93	H
3500.0	-48.94	4.02	3.00	12.21	-40.75	-13.00	27.75	V
5250.0	-48.34	5.11	3.00	13.26	-40.19	-13.00	27.19	V

LTE FDD Band 4 Channel Bandwidth 15MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-42.87	4.02	3.00	12.21	-34.68	-13.00	21.68	H
5242.5	-46.6	5.11	3.00	13.26	-38.45	-13.00	25.45	H
3495.0	-49.32	4.02	3.00	12.21	-41.13	-13.00	28.13	V
5242.5	-48.57	5.11	3.00	13.26	-40.42	-13.00	27.42	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 4 Channel Bandwidth 20MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-42.87	4.02	3.00	12.21	-34.68	-13.00	21.68	H
5235.0	-46.97	5.11	3.00	13.26	-38.82	-13.00	25.82	H
3490.0	-48.64	4.02	3.00	12.21	-40.45	-13.00	27.45	V
5235.0	-48.49	5.11	3.00	13.26	-40.34	-13.00	27.34	V

LTE FDD Band 4 Channel Bandwidth 1.4MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-42.57	4.02	3.00	12.21	-34.38	-13.00	21.38	H
5262.9	-46.86	5.11	3.00	13.26	-38.71	-13.00	25.71	H
3508.6	-48.6	4.02	3.00	12.21	-40.41	-13.00	27.41	V
5262.9	-48.94	5.11	3.00	13.26	-40.79	-13.00	27.79	V

LTE FDD Band 4 Channel Bandwidth 3MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-43.33	4.02	3.00	12.21	-35.14	-13.00	22.14	H
5260.5	-46.98	5.11	3.00	13.26	-38.83	-13.00	25.83	H
3507.0	-48.16	4.02	3.00	12.21	-39.97	-13.00	26.97	V
5260.5	-49.04	5.11	3.00	13.26	-40.89	-13.00	27.89	V

LTE FDD Band 4 Channel Bandwidth 5MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-42.82	4.02	3.00	12.21	-34.63	-13.00	21.63	H
5257.5	-46.95	5.11	3.00	13.26	-38.8	-13.00	25.8	H
3505.0	-48.56	4.02	3.00	12.21	-40.37	-13.00	27.37	V
5257.5	-49.09	5.11	3.00	13.26	-40.94	-13.00	27.94	V

LTE FDD Band 4 Channel Bandwidth 10MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-42.9	4.02	3.00	12.21	-34.71	-13.00	21.71	H
5250.0	-46.3	5.11	3.00	13.26	-38.15	-13.00	25.15	H
3500.0	-48.82	4.02	3.00	12.21	-40.63	-13.00	27.63	V
5250.0	-48.59	5.11	3.00	13.26	-40.44	-13.00	27.44	V

LTE FDD Band 4 Channel Bandwidth 15MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-43.19	4.02	3.00	12.21	-35	-13.00	22	H
5242.5	-46.85	5.11	3.00	13.26	-38.7	-13.00	25.7	H
3495.0	-48.58	4.02	3.00	12.21	-40.39	-13.00	27.39	V
5242.5	-48.74	5.11	3.00	13.26	-40.59	-13.00	27.59	V

LTE FDD Band 4 Channel Bandwidth 20MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-43.33	4.02	3.00	12.21	-35.14	-13.00	22.14	H
5235.0	-46.96	5.11	3.00	13.26	-38.81	-13.00	25.81	H
3490.0	-48.73	4.02	3.00	12.21	-40.54	-13.00	27.54	V
5235.0	-48.18	5.11	3.00	13.26	-40.03	-13.00	27.03	V

Series Model No.: MT Ultimate

LTE FDD Band 4 Channel Bandwidth 1.4MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-43.3	4.02	3.00	12.21	-35.11	-13.00	22.11	H
5262.9	-46.68	5.11	3.00	13.26	-38.53	-13.00	25.53	H
3508.6	-49.03	4.02	3.00	12.21	-40.84	-13.00	27.84	V
5262.9	-48.66	5.11	3.00	13.26	-40.51	-13.00	27.51	V

LTE FDD Band 4 Channel Bandwidth 3MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-43.1	4.02	3.00	12.21	-34.91	-13.00	21.91	H
5260.5	-46.42	5.11	3.00	13.26	-38.27	-13.00	25.27	H
3507.0	-48.89	4.02	3.00	12.21	-40.7	-13.00	27.7	V
5260.5	-48.15	5.11	3.00	13.26	-40	-13.00	27	V

LTE FDD Band 4 Channel Bandwidth 5MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-43.41	4.02	3.00	12.21	-35.22	-13.00	22.22	H
5257.5	-46.6	5.11	3.00	13.26	-38.45	-13.00	25.45	H
3505.0	-48.87	4.02	3.00	12.21	-40.68	-13.00	27.68	V
5257.5	-47.82	5.11	3.00	13.26	-39.67	-13.00	26.67	V

LTE FDD Band 4 Channel Bandwidth 10MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-42.98	4.02	3.00	12.21	-34.79	-13.00	21.79	H
5250.0	-46.14	5.11	3.00	13.26	-37.99	-13.00	24.99	H
3500.0	-48.31	4.02	3.00	12.21	-40.12	-13.00	27.12	V
5250.0	-47.88	5.11	3.00	13.26	-39.73	-13.00	26.73	V

LTE FDD Band 4 Channel Bandwidth 15MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-43.1	4.02	3.00	12.21	-34.91	-13.00	21.91	H
5242.5	-47.05	5.11	3.00	13.26	-38.9	-13.00	25.9	H
3495.0	-48.29	4.02	3.00	12.21	-40.1	-13.00	27.1	V
5242.5	-47.93	5.11	3.00	13.26	-39.78	-13.00	26.78	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 4 Channel Bandwidth 20MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-42.69	4.02	3.00	12.21	-34.5	-13.00	21.5	H
5235.0	-46.42	5.11	3.00	13.26	-38.27	-13.00	25.27	H
3490.0	-48.46	4.02	3.00	12.21	-40.27	-13.00	27.27	V
5235.0	-48.84	5.11	3.00	13.26	-40.69	-13.00	27.69	V

LTE FDD Band 4 Channel Bandwidth 1.4MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-42.62	4.02	3.00	12.21	-34.43	-13.00	21.43	H
5262.9	-47.41	5.11	3.00	13.26	-39.26	-13.00	26.26	H
3508.6	-48.92	4.02	3.00	12.21	-40.73	-13.00	27.73	V
5262.9	-48.82	5.11	3.00	13.26	-40.67	-13.00	27.67	V

LTE FDD Band 4 Channel Bandwidth 3MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-43.55	4.02	3.00	12.21	-35.36	-13.00	22.36	H
5260.5	-47.16	5.11	3.00	13.26	-39.01	-13.00	26.01	H
3507.0	-48.1	4.02	3.00	12.21	-39.91	-13.00	26.91	V
5260.5	-49.15	5.11	3.00	13.26	-41	-13.00	28	V

LTE FDD Band 4 Channel Bandwidth 5MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-43.11	4.02	3.00	12.21	-34.92	-13.00	21.92	H
5257.5	-46.12	5.11	3.00	13.26	-37.97	-13.00	24.97	H
3505.0	-49.16	4.02	3.00	12.21	-40.97	-13.00	27.97	V
5257.5	-48.42	5.11	3.00	13.26	-40.27	-13.00	27.27	V

LTE FDD Band 4 Channel Bandwidth 10MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-42.22	4.02	3.00	12.21	-34.03	-13.00	21.03	H
5250.0	-46.29	5.11	3.00	13.26	-38.14	-13.00	25.14	H
3500.0	-48.31	4.02	3.00	12.21	-40.12	-13.00	27.12	V
5250.0	-48.07	5.11	3.00	13.26	-39.92	-13.00	26.92	V

LTE FDD Band 4 Channel Bandwidth 15MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-42.52	4.02	3.00	12.21	-34.33	-13.00	21.33	H
5242.5	-46.78	5.11	3.00	13.26	-38.63	-13.00	25.63	H
3495.0	-48.51	4.02	3.00	12.21	-40.32	-13.00	27.32	V
5242.5	-48.49	5.11	3.00	13.26	-40.34	-13.00	27.34	V

LTE FDD Band 4 Channel Bandwidth 20MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-42.57	4.02	3.00	12.21	-34.38	-13.00	21.38	H
5235.0	-46.16	5.11	3.00	13.26	-38.01	-13.00	25.01	H
3490.0	-48.33	4.02	3.00	12.21	-40.14	-13.00	27.14	V
5235.0	-48.69	5.11	3.00	13.26	-40.54	-13.00	27.54	V

Series Model No.: M15 pro

LTE FDD Band 4 Channel Bandwidth 1.4MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-42.48	4.02	3.00	12.21	-34.29	-13.00	21.29	H
5262.9	-46.7	5.11	3.00	13.26	-38.55	-13.00	25.55	H
3508.6	-48.09	4.02	3.00	12.21	-39.9	-13.00	26.9	V
5262.9	-48.52	5.11	3.00	13.26	-40.37	-13.00	27.37	V

LTE FDD Band 4 Channel Bandwidth 3MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-43.05	4.02	3.00	12.21	-34.86	-13.00	21.86	H
5260.5	-46.05	5.11	3.00	13.26	-37.9	-13.00	24.9	H
3507.0	-49.63	4.02	3.00	12.21	-41.44	-13.00	28.44	V
5260.5	-48.34	5.11	3.00	13.26	-40.19	-13.00	27.19	V

LTE FDD Band 4 Channel Bandwidth 5MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-43.17	4.02	3.00	12.21	-34.98	-13.00	21.98	H
5257.5	-47.01	5.11	3.00	13.26	-38.86	-13.00	25.86	H
3505.0	-49.08	4.02	3.00	12.21	-40.89	-13.00	27.89	V
5257.5	-47.94	5.11	3.00	13.26	-39.79	-13.00	26.79	V

LTE FDD Band 4 Channel Bandwidth 10MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-43.35	4.02	3.00	12.21	-35.16	-13.00	22.16	H
5250.0	-47.54	5.11	3.00	13.26	-39.39	-13.00	26.39	H
3500.0	-48.42	4.02	3.00	12.21	-40.23	-13.00	27.23	V
5250.0	-47.88	5.11	3.00	13.26	-39.73	-13.00	26.73	V

LTE FDD Band 4 Channel Bandwidth 15MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-42.78	4.02	3.00	12.21	-34.59	-13.00	21.59	H
5242.5	-46.8	5.11	3.00	13.26	-38.65	-13.00	25.65	H
3495.0	-48.17	4.02	3.00	12.21	-39.98	-13.00	26.98	V
5242.5	-48.51	5.11	3.00	13.26	-40.36	-13.00	27.36	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 4 Channel Bandwidth 20MHz QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-43.42	4.02	3.00	12.21	-35.23	-13.00	22.23	H
5235.0	-46.81	5.11	3.00	13.26	-38.66	-13.00	25.66	H
3490.0	-49.28	4.02	3.00	12.21	-41.09	-13.00	28.09	V
5235.0	-49.12	5.11	3.00	13.26	-40.97	-13.00	27.97	V

LTE FDD Band 4 Channel Bandwidth 1.4MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-43.58	4.02	3.00	12.21	-35.39	-13.00	22.39	H
5262.9	-46.12	5.11	3.00	13.26	-37.97	-13.00	24.97	H
3508.6	-47.91	4.02	3.00	12.21	-39.72	-13.00	26.72	V
5262.9	-47.97	5.11	3.00	13.26	-39.82	-13.00	26.82	V

LTE FDD Band 4 Channel Bandwidth 3MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-42.97	4.02	3.00	12.21	-34.78	-13.00	21.78	H
5260.5	-47.06	5.11	3.00	13.26	-38.91	-13.00	25.91	H
3507.0	-47.89	4.02	3.00	12.21	-39.7	-13.00	26.7	V
5260.5	-48.34	5.11	3.00	13.26	-40.19	-13.00	27.19	V

LTE FDD Band 4 Channel Bandwidth 5MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-43.45	4.02	3.00	12.21	-35.26	-13.00	22.26	H
5257.5	-47.38	5.11	3.00	13.26	-39.23	-13.00	26.23	H
3505.0	-49.29	4.02	3.00	12.21	-41.1	-13.00	28.1	V
5257.5	-47.7	5.11	3.00	13.26	-39.55	-13.00	26.55	V

LTE FDD Band 4 Channel Bandwidth 10MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-42.96	4.02	3.00	12.21	-34.77	-13.00	21.77	H
5250.0	-46.46	5.11	3.00	13.26	-38.31	-13.00	25.31	H
3500.0	-49.38	4.02	3.00	12.21	-41.19	-13.00	28.19	V
5250.0	-49.03	5.11	3.00	13.26	-40.88	-13.00	27.88	V

LTE FDD Band 4 Channel Bandwidth 15MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-43.36	4.02	3.00	12.21	-35.17	-13.00	22.17	H
5242.5	-46.86	5.11	3.00	13.26	-38.71	-13.00	25.71	H
3495.0	-48.91	4.02	3.00	12.21	-40.72	-13.00	27.72	V
5242.5	-48	5.11	3.00	13.26	-39.85	-13.00	26.85	V

LTE FDD Band 4 Channel Bandwidth 20MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-42.93	4.02	3.00	12.21	-34.74	-13.00	21.74	H
5235.0	-46.65	5.11	3.00	13.26	-38.5	-13.00	25.5	H
3490.0	-49.18	4.02	3.00	12.21	-40.99	-13.00	27.99	V
5235.0	-47.73	5.11	3.00	13.26	-39.58	-13.00	26.58	V


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

3.6 Frequency Stability Under Temperature & Voltage Variations

LIMIT

According to §27.54, §2.1055 requirement, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation and should not exceed 2.5ppm.

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D.

Frequency Stability Under Temperature Variations:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 4, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS

Remark:

1. We tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 4; recorded worst case.

LTE Band 4, 1.4MHz bandwidth, QPSK (worst case of all bandwidths).

LTE FDD Band 4				
DC Power(V)	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Verdict
4.25	20	4.32	0.002525	PASS
5.0	20	-15.25	-0.008914	PASS
5.75	20	-12.20	-0.007132	PASS
5.0	-30	-8.00	-0.004676	PASS
5.0	-20	-11.04	-0.006453	PASS
5.0	-10	-6.90	-0.004033	PASS
5.0	0	-12.42	-0.007260	PASS
5.0	10	-9.64	-0.005635	PASS
5.0	20	-6.88	-0.004022	PASS
5.0	30	-7.05	-0.004069	PASS
5.0	40	-12.77	-0.007371	PASS
5.0	50	7.77	0.004485	PASS

LTE Band 4, 1.4MHz bandwidth , 16QAM (worst case of all bandwidths)

LTE FDD Band 4				
DC Power(V)	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Verdict
4.25	20	6.74	0.003940	PASS
5.0	20	9.14	0.005343	PASS
5.75	20	-3.75	-0.002192	PASS
5.0	-30	-12.06	-0.007050	PASS
5.0	-20	8.01	0.004682	PASS
5.0	-10	-8.43	-0.004928	PASS
5.0	0	-12.10	-0.007073	PASS
5.0	10	-8.55	-0.004998	PASS
5.0	20	3.13	0.001830	PASS
5.0	30	-5.65	-0.003261	PASS
5.0	40	-8.60	-0.004964	PASS
5.0	50	-12.10	-0.006984	PASS