







The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Radiated Measurement:

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 66; recorded worst case for each Channel Bandwidth of LTE FDD Band 66.
2. $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + G_a(dBi)$
3. We were not recorded other points as values lower than limits.
4. Margin = Limit – EIRP

Test Model No.: I16 Pro max

LTE FDD Band 66_Channel Bandwidth 1.4MHz_QPSK_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3421.4	-44.25	4.02	3.00	12.5	-35.77	-13.00	22.77	H
5132.1	-49.65	5.11	3.00	13.38	-41.38	-13.00	28.38	H
3421.4	-51.96	4.02	3.00	12.5	-43.48	-13.00	30.48	V
5132.1	-53.1	5.11	3.00	13.38	-44.83	-13.00	31.83	V

LTE FDD Band 66_Channel Bandwidth 1.4MHz_QPSK_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-44.29	4.02	3.00	12.45	-35.86	-13.00	22.86	H
5235	-46.93	5.11	3.00	13.38	-38.66	-13.00	25.66	H
3490	-49.53	4.02	3.00	12.45	-41.1	-13.00	28.1	V
5235	-48.48	5.11	3.00	13.38	-40.21	-13.00	27.21	V

LTE FDD Band 66_Channel Bandwidth 1.4MHz_QPSK_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-42.14	4.02	3.00	12.21	-33.95	-13.00	20.95	H
5337.9	-47.23	5.11	3.00	13.26	-39.08	-13.00	26.08	H
3558.6	-48.58	4.02	3.00	12.21	-40.39	-13.00	27.39	V
5337.9	-47.55	5.11	3.00	13.26	-39.4	-13.00	26.4	V

LTE FDD Band 66_Channel Bandwidth 3MHz_QPSK_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3423.0	-47.67	4.02	3.00	12.5	-39.19	-13.00	26.19	H
5134.5	-51.89	5.11	3.00	13.38	-43.62	-13.00	30.62	H
3423.0	-49.32	4.02	3.00	12.5	-40.84	-13.00	27.84	V
5134.5	-50.62	5.11	3.00	13.38	-42.35	-13.00	29.35	V

LTE FDD Band 66_Channel Bandwidth 3MHz_QPSK_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-44.28	4.02	3.00	12.45	-35.85	-13.00	22.85	H
5235	-47.23	5.11	3.00	13.38	-38.96	-13.00	25.96	H
3490	-49.42	4.02	3.00	12.45	-40.99	-13.00	27.99	V
5235	-48.07	5.11	3.00	13.38	-39.8	-13.00	26.8	V

LTE FDD Band 66_Channel Bandwidth 3MHz_QPSK_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-43.34	4.02	3.00	12.21	-35.15	-13.00	22.15	H
5335.5	-47.4	5.11	3.00	13.26	-39.25	-13.00	26.25	H
3557	-48.73	4.02	3.00	12.21	-40.54	-13.00	27.54	V
5335.5	-48.2	5.11	3.00	13.26	-40.05	-13.00	27.05	V

LTE FDD Band 66_Channel Bandwidth 5MHz_QPSK_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3425.0	-47.11	4.02	3.00	12.5	-38.63	-13.00	25.63	H
5137.5	-51.91	5.11	3.00	13.38	-43.64	-13.00	30.64	H
3425.0	-54.62	4.02	3.00	12.5	-46.14	-13.00	33.14	V
5137.5	-52.54	5.11	3.00	13.38	-44.27	-13.00	31.27	V

LTE FDD Band 66_Channel Bandwidth 5MHz_QPSK_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-44.31	4.02	3.00	12.45	-35.88	-13.00	22.88	H
5235	-47.91	5.11	3.00	13.38	-39.64	-13.00	26.64	H
3490	-50.79	4.02	3.00	12.45	-42.36	-13.00	29.36	V
5235	-47.72	5.11	3.00	13.38	-39.45	-13.00	26.45	V

LTE FDD Band 66_Channel Bandwidth 5MHz_QPSK_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-42.45	4.02	3.00	12.21	-34.26	-13.00	21.26	H
5332.5	-46.98	5.11	3.00	13.26	-38.83	-13.00	25.83	H
3555	-48.87	4.02	3.00	12.21	-40.68	-13.00	27.68	V
5332.5	-48.04	5.11	3.00	13.26	-39.89	-13.00	26.89	V

LTE FDD Band 66_Channel Bandwidth 10MHz_QPSK_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3430.0	-43.85	4.02	3.00	12.5	-35.37	-13.00	22.37	H
5145.0	-49.7	5.11	3.00	13.38	-41.43	-13.00	28.43	H
3430.0	-51.75	4.02	3.00	12.5	-43.27	-13.00	30.27	V
5145.0	-49.59	5.11	3.00	13.38	-41.32	-13.00	28.32	V

LTE FDD Band 66_Channel Bandwidth 10MHz_QPSK_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-44.35	4.02	3.00	12.45	-35.92	-13.00	22.92	H
5235	-47.46	5.11	3.00	13.38	-39.19	-13.00	26.19	H
3490	-49.28	4.02	3.00	12.45	-40.85	-13.00	27.85	V
5235	-47.03	5.11	3.00	13.38	-38.76	-13.00	25.76	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 66_Channel Bandwidth 10MHz_QPSK_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-42.47	4.02	3.00	12.21	-34.28	-13.00	21.28	H
5325	-46.49	5.11	3.00	13.26	-38.34	-13.00	25.34	H
3550	-48.44	4.02	3.00	12.21	-40.25	-13.00	27.25	V
5325	-48.21	5.11	3.00	13.26	-40.06	-13.00	27.06	V

LTE FDD Band 66_Channel Bandwidth 15MHz_QPSK_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3435.0	-47.65	4.02	3.00	12.5	-39.17	-13.00	26.17	H
5152.5	-52.47	5.11	3.00	13.38	-44.2	-13.00	31.2	H
3435.0	-51.08	4.02	3.00	12.5	-42.6	-13.00	29.6	V
5152.5	-51.23	5.11	3.00	13.38	-42.96	-13.00	29.96	V

LTE FDD Band 66_Channel Bandwidth 15MHz_QPSK_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-43.76	4.02	3.00	12.45	-35.33	-13.00	22.33	H
5235	-47.21	5.11	3.00	13.38	-38.94	-13.00	25.94	H
3490	-49.46	4.02	3.00	12.45	-41.03	-13.00	28.03	V
5235	-48.14	5.11	3.00	13.38	-39.87	-13.00	26.87	V

LTE FDD Band 66_Channel Bandwidth 15MHz_QPSK_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-42.6	4.02	3.00	12.21	-34.41	-13.00	21.41	H
5317.5	-47	5.11	3.00	13.26	-38.85	-13.00	25.85	H
3545	-48.41	4.02	3.00	12.21	-40.22	-13.00	27.22	V
5317.5	-48.07	5.11	3.00	13.26	-39.92	-13.00	26.92	V

LTE FDD Band 66_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3440.0	-44.78	4.02	3.00	12.5	-36.3	-13.00	23.3	H
5160.0	-49.69	5.11	3.00	13.38	-41.42	-13.00	28.42	H
3440.0	-52.78	4.02	3.00	12.5	-44.3	-13.00	31.3	V
5160.0	-51.07	5.11	3.00	13.38	-42.8	-13.00	29.8	V

LTE FDD Band 66_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-43.78	4.02	3.00	12.45	-35.35	-13.00	22.35	H
5235	-47.39	5.11	3.00	13.38	-39.12	-13.00	26.12	H
3490	-49.41	4.02	3.00	12.45	-40.98	-13.00	27.98	V
5235	-46.41	5.11	3.00	13.38	-38.14	-13.00	25.14	V

LTE FDD Band 66_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-42.2	4.02	3.00	12.21	-34.01	-13.00	21.01	H
5310	-47.54	5.11	3.00	13.26	-39.39	-13.00	26.39	H
3540	-47.91	4.02	3.00	12.21	-39.72	-13.00	26.72	V
5310	-47.87	5.11	3.00	13.26	-39.72	-13.00	26.72	V

LTE FDD Band 66_Channel Bandwidth 1.4MHz_16QAM_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3421.4	-45.87	4.02	3.00	12.5	-37.39	-13.00	24.39	H
5132.1	-50.17	5.11	3.00	13.38	-41.9	-13.00	28.9	H
3421.4	-52.57	4.02	3.00	12.5	-44.09	-13.00	31.09	V
5132.1	-47.98	5.11	3.00	13.38	-39.71	-13.00	26.71	V

LTE FDD Band 66_Channel Bandwidth 1.4MHz_16QAM_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-44.06	4.02	3.00	12.45	-35.63	-13.00	22.63	H
5235	-46.47	5.11	3.00	13.38	-38.2	-13.00	25.2	H
3490	-49.95	4.02	3.00	12.45	-41.52	-13.00	28.52	V
5235	-48.3	5.11	3.00	13.38	-40.03	-13.00	27.03	V

LTE FDD Band 66_Channel Bandwidth 1.4MHz_16QAM_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-42.53	4.02	3.00	12.21	-34.34	-13.00	21.34	H
5337.9	-45.96	5.11	3.00	13.26	-37.81	-13.00	24.81	H
3558.6	-48.28	4.02	3.00	12.21	-40.09	-13.00	27.09	V
5337.9	-48.45	5.11	3.00	13.26	-40.3	-13.00	27.3	V

LTE FDD Band 66_Channel Bandwidth 3MHz_16QAM_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3423.0	-45.88	4.02	3.00	12.5	-37.4	-13.00	24.4	H
5134.5	-51.49	5.11	3.00	13.38	-43.22	-13.00	30.22	H
3423.0	-51.46	4.02	3.00	12.5	-42.98	-13.00	29.98	V
5134.5	-49.55	5.11	3.00	13.38	-41.28	-13.00	28.28	V

LTE FDD Band 66_Channel Bandwidth 3MHz_16QAM_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-44.44	4.02	3.00	12.45	-36.01	-13.00	23.01	H
5235	-46.95	5.11	3.00	13.38	-38.68	-13.00	25.68	H
3490	-49.62	4.02	3.00	12.45	-41.19	-13.00	28.19	V
5235	-47.43	5.11	3.00	13.38	-39.16	-13.00	26.16	V

LTE FDD Band 66_Channel Bandwidth 3MHz_16QAM_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-42.51	4.02	3.00	12.21	-34.32	-13.00	21.32	H
5335.5	-47.2	5.11	3.00	13.26	-39.05	-13.00	26.05	H
3557	-49.09	4.02	3.00	12.21	-40.9	-13.00	27.9	V
5335.5	-48.09	5.11	3.00	13.26	-39.94	-13.00	26.94	V

LTE FDD Band 66_Channel Bandwidth 5MHz_16QAM_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3425.0	-46.82	4.02	3.00	12.5	-38.34	-13.00	25.34	H
5137.5	-49.44	5.11	3.00	13.38	-41.17	-13.00	28.17	H
3425.0	-52.08	4.02	3.00	12.5	-43.6	-13.00	30.6	V
5137.5	-51.51	5.11	3.00	13.38	-43.24	-13.00	30.24	V

LTE FDD Band 66_Channel Bandwidth 5MHz_16QAM_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-44.18	4.02	3.00	12.45	-35.75	-13.00	22.75	H
5235	-46.75	5.11	3.00	13.38	-38.48	-13.00	25.48	H
3490	-50.21	4.02	3.00	12.45	-41.78	-13.00	28.78	V
5235	-48.46	5.11	3.00	13.38	-40.19	-13.00	27.19	V

LTE FDD Band 66_Channel Bandwidth 5MHz_16QAM_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-42.47	4.02	3.00	12.21	-34.28	-13.00	21.28	H
5332.5	-46.37	5.11	3.00	13.26	-38.22	-13.00	25.22	H
3555	-48.67	4.02	3.00	12.21	-40.48	-13.00	27.48	V
5332.5	-48.77	5.11	3.00	13.26	-40.62	-13.00	27.62	V

LTE FDD Band 66_Channel Bandwidth 10MHz_16QAM_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3430.0	-47.13	4.02	3.00	12.5	-38.65	-13.00	25.65	H
5145.0	-49.53	5.11	3.00	13.38	-41.26	-13.00	28.26	H
3430.0	-53	4.02	3.00	12.5	-44.52	-13.00	31.52	V
5145.0	-50.54	5.11	3.00	13.38	-42.27	-13.00	29.27	V

LTE FDD Band 66_Channel Bandwidth 10MHz_16QAM_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-44.41	4.02	3.00	12.45	-35.98	-13.00	22.98	H
5235	-47.21	5.11	3.00	13.38	-38.94	-13.00	25.94	H
3490	-49.82	4.02	3.00	12.45	-41.39	-13.00	28.39	V
5235	-47.64	5.11	3.00	13.38	-39.37	-13.00	26.37	V

LTE FDD Band 66_Channel Bandwidth 10MHz_16QAM_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-42.46	4.02	3.00	12.21	-34.27	-13.00	21.27	H
5325	-46.64	5.11	3.00	13.26	-38.49	-13.00	25.49	H
3550	-49.32	4.02	3.00	12.21	-41.13	-13.00	28.13	V
5325	-49.23	5.11	3.00	13.26	-41.08	-13.00	28.08	V

LTE FDD Band 66_Channel Bandwidth 15MHz_16QAM_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3435.0	-45.05	4.02	3.00	12.5	-36.57	-13.00	23.57	H
5152.5	-53.98	5.11	3.00	13.38	-45.71	-13.00	32.71	H
3435.0	-50.75	4.02	3.00	12.5	-42.27	-13.00	29.27	V
5152.5	-46.41	5.11	3.00	13.38	-38.14	-13.00	25.14	V

LTE FDD Band 66_Channel Bandwidth 15MHz_16QAM_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-44.04	4.02	3.00	12.45	-35.61	-13.00	22.61	H
5235	-47.98	5.11	3.00	13.38	-39.71	-13.00	26.71	H
3490	-49.96	4.02	3.00	12.45	-41.53	-13.00	28.53	V
5235	-48.41	5.11	3.00	13.38	-40.14	-13.00	27.14	V

LTE FDD Band 66_Channel Bandwidth 15MHz_16QAM_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-43.26	4.02	3.00	12.21	-35.07	-13.00	22.07	H
5317.5	-46.42	5.11	3.00	13.26	-38.27	-13.00	25.27	H
3545	-48.9	4.02	3.00	12.21	-40.71	-13.00	27.71	V
5317.5	-47.27	5.11	3.00	13.26	-39.12	-13.00	26.12	V

LTE FDD Band 66_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3440.0	-46.48	4.02	3.00	12.5	-38	-13.00	25	H
5160.0	-51.36	5.11	3.00	13.38	-43.09	-13.00	30.09	H
3440.0	-52.63	4.02	3.00	12.5	-44.15	-13.00	31.15	V
5160.0	-50.06	5.11	3.00	13.38	-41.79	-13.00	28.79	V

LTE FDD Band 66_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-45.19	4.02	3.00	12.45	-36.76	-13.00	23.76	H
5235	-48.65	5.11	3.00	13.38	-40.38	-13.00	27.38	H
3490	-49.74	4.02	3.00	12.45	-41.31	-13.00	28.31	V
5235	-47.23	5.11	3.00	13.38	-38.96	-13.00	25.96	V

LTE FDD Band 66_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-43.37	4.02	3.00	12.21	-35.18	-13.00	22.18	H
5310	-46.68	5.11	3.00	13.26	-38.53	-13.00	25.53	H
3540	-48.24	4.02	3.00	12.21	-40.05	-13.00	27.05	V
5310	-47.99	5.11	3.00	13.26	-39.84	-13.00	26.84	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

All modes of operation were investigated and the worst-case emissions are reported.
Series Model No.: S26 Ultra

LTE FDD Band 66_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-48.29	4.02	3.00	12.21	-40.1	-13.00	27.1	H
5337.9	-47.42	5.11	3.00	13.26	-39.27	-13.00	26.27	H
3558.6	-49.96	4.02	3.00	12.21	-41.77	-13.00	28.77	V
5337.9	-48.8	5.11	3.00	13.26	-40.65	-13.00	27.65	V

LTE FDD Band 66_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-47.32	4.02	3.00	12.21	-39.13	-13.00	26.13	H
5335.5	-46.83	5.11	3.00	13.26	-38.68	-13.00	25.68	H
3557	-49.21	4.02	3.00	12.21	-41.02	-13.00	28.02	V
5335.5	-48.83	5.11	3.00	13.26	-40.68	-13.00	27.68	V

LTE FDD Band 66_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-48.01	4.02	3.00	12.21	-39.82	-13.00	26.82	H
5332.5	-46.92	5.11	3.00	13.26	-38.77	-13.00	25.77	H
3555	-49.37	4.02	3.00	12.21	-41.18	-13.00	28.18	V
5332.5	-49.07	5.11	3.00	13.26	-40.92	-13.00	27.92	V

LTE FDD Band 66_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-47.69	4.02	3.00	12.21	-39.5	-13.00	26.5	H
5325	-47.09	5.11	3.00	13.26	-38.94	-13.00	25.94	H
3550	-49.68	4.02	3.00	12.21	-41.49	-13.00	28.49	V
5325	-49.13	5.11	3.00	13.26	-40.98	-13.00	27.98	V

LTE FDD Band 66_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-47.26	4.02	3.00	12.21	-39.07	-13.00	26.07	H
5317.5	-47.15	5.11	3.00	13.26	-39	-13.00	26	H
3545	-48.72	4.02	3.00	12.21	-40.53	-13.00	27.53	V
5317.5	-48.6	5.11	3.00	13.26	-40.45	-13.00	27.45	V

LTE FDD Band 66_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-47.44	4.02	3.00	12.21	-39.25	-13.00	26.25	H
5310	-47.96	5.11	3.00	13.26	-39.81	-13.00	26.81	H
3540	-49.25	4.02	3.00	12.21	-41.06	-13.00	28.06	V
5310	-49.1	5.11	3.00	13.26	-40.95	-13.00	27.95	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 66_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-47.07	4.02	3.00	12.21	-38.88	-13.00	25.88	H
5337.9	-46.95	5.11	3.00	13.26	-38.8	-13.00	25.8	H
3558.6	-49.15	4.02	3.00	12.21	-40.96	-13.00	27.96	V
5337.9	-49.1	5.11	3.00	13.26	-40.95	-13.00	27.95	V

LTE FDD Band 66_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-47.45	4.02	3.00	12.21	-39.26	-13.00	26.26	H
5335.5	-47.17	5.11	3.00	13.26	-39.02	-13.00	26.02	H
3557	-49.64	4.02	3.00	12.21	-41.45	-13.00	28.45	V
5335.5	-48.42	5.11	3.00	13.26	-40.27	-13.00	27.27	V

LTE FDD Band 66_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-47.69	4.02	3.00	12.21	-39.5	-13.00	26.5	H
5332.5	-46.87	5.11	3.00	13.26	-38.72	-13.00	25.72	H
3555	-48.83	4.02	3.00	12.21	-40.64	-13.00	27.64	V
5332.5	-48.65	5.11	3.00	13.26	-40.5	-13.00	27.5	V

LTE FDD Band 66_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-48.36	4.02	3.00	12.21	-40.17	-13.00	27.17	H
5325	-46.32	5.11	3.00	13.26	-38.17	-13.00	25.17	H
3550	-48.27	4.02	3.00	12.21	-40.08	-13.00	27.08	V
5325	-48.11	5.11	3.00	13.26	-39.96	-13.00	26.96	V

LTE FDD Band 66_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-47.79	4.02	3.00	12.21	-39.6	-13.00	26.6	H
5317.5	-46.97	5.11	3.00	13.26	-38.82	-13.00	25.82	H
3545	-48.3	4.02	3.00	12.21	-40.11	-13.00	27.11	V
5317.5	-48.7	5.11	3.00	13.26	-40.55	-13.00	27.55	V

LTE FDD Band 66_Channel Bandwidth 20MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-47.29	4.02	3.00	12.21	-39.1	-13.00	26.1	H
5310	-47.19	5.11	3.00	13.26	-39.04	-13.00	26.04	H
3540	-49.33	4.02	3.00	12.21	-41.14	-13.00	28.14	V
5310	-49.42	5.11	3.00	13.26	-41.27	-13.00	28.27	V

Series Model No.: Pixel 9

LTE FDD Band 66 Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-47.73	4.02	3.00	12.21	-39.54	-13.00	26.54	H
5337.9	-47.28	5.11	3.00	13.26	-39.13	-13.00	26.13	H
3558.6	-48.91	4.02	3.00	12.21	-40.72	-13.00	27.72	V
5337.9	-48.82	5.11	3.00	13.26	-40.67	-13.00	27.67	V

LTE FDD Band 66 Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-48.04	4.02	3.00	12.21	-39.85	-13.00	26.85	H
5335.5	-46.7	5.11	3.00	13.26	-38.55	-13.00	25.55	H
3557	-49.16	4.02	3.00	12.21	-40.97	-13.00	27.97	V
5335.5	-48.87	5.11	3.00	13.26	-40.72	-13.00	27.72	V

LTE FDD Band 66 Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-46.87	4.02	3.00	12.21	-38.68	-13.00	25.68	H
5332.5	-47.36	5.11	3.00	13.26	-39.21	-13.00	26.21	H
3555	-48.89	4.02	3.00	12.21	-40.7	-13.00	27.7	V
5332.5	-48.99	5.11	3.00	13.26	-40.84	-13.00	27.84	V

LTE FDD Band 66 Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-46.8	4.02	3.00	12.21	-38.61	-13.00	25.61	H
5325	-47.08	5.11	3.00	13.26	-38.93	-13.00	25.93	H
3550	-49.45	4.02	3.00	12.21	-41.26	-13.00	28.26	V
5325	-49.56	5.11	3.00	13.26	-41.41	-13.00	28.41	V

LTE FDD Band 66 Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-47.97	4.02	3.00	12.21	-39.78	-13.00	26.78	H
5317.5	-46.82	5.11	3.00	13.26	-38.67	-13.00	25.67	H
3545	-49.11	4.02	3.00	12.21	-40.92	-13.00	27.92	V
5317.5	-49.15	5.11	3.00	13.26	-41	-13.00	28	V

LTE FDD Band 66 Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-47.73	4.02	3.00	12.21	-39.54	-13.00	26.54	H
5310	-47.23	5.11	3.00	13.26	-39.08	-13.00	26.08	H
3540	-49.03	4.02	3.00	12.21	-40.84	-13.00	27.84	V
5310	-48.49	5.11	3.00	13.26	-40.34	-13.00	27.34	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

LTE FDD Band 66_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-48.3	4.02	3.00	12.21	-40.11	-13.00	27.11	H
5337.9	-47.46	5.11	3.00	13.26	-39.31	-13.00	26.31	H
3558.6	-49.4	4.02	3.00	12.21	-41.21	-13.00	28.21	V
5337.9	-48.81	5.11	3.00	13.26	-40.66	-13.00	27.66	V

LTE FDD Band 66_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-46.9	4.02	3.00	12.21	-38.71	-13.00	25.71	H
5335.5	-46.68	5.11	3.00	13.26	-38.53	-13.00	25.53	H
3557	-49.11	4.02	3.00	12.21	-40.92	-13.00	27.92	V
5335.5	-49.28	5.11	3.00	13.26	-41.13	-13.00	28.13	V

LTE FDD Band 66_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-46.89	4.02	3.00	12.21	-38.7	-13.00	25.7	H
5332.5	-47.18	5.11	3.00	13.26	-39.03	-13.00	26.03	H
3555	-49.14	4.02	3.00	12.21	-40.95	-13.00	27.95	V
5332.5	-49.57	5.11	3.00	13.26	-41.42	-13.00	28.42	V

LTE FDD Band 66_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-47.05	4.02	3.00	12.21	-38.86	-13.00	25.86	H
5325	-46.97	5.11	3.00	13.26	-38.82	-13.00	25.82	H
3550	-50.01	4.02	3.00	12.21	-41.82	-13.00	28.82	V
5325	-48.97	5.11	3.00	13.26	-40.82	-13.00	27.82	V

LTE FDD Band 66_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-47.66	4.02	3.00	12.21	-39.47	-13.00	26.47	H
5317.5	-46.79	5.11	3.00	13.26	-38.64	-13.00	25.64	H
3545	-49.61	4.02	3.00	12.21	-41.42	-13.00	28.42	V
5317.5	-48.27	5.11	3.00	13.26	-40.12	-13.00	27.12	V

LTE FDD Band 66_Channel Bandwidth 20MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-47.39	4.02	3.00	12.21	-39.2	-13.00	26.2	H
5310	-47.23	5.11	3.00	13.26	-39.08	-13.00	26.08	H
3540	-49.11	4.02	3.00	12.21	-40.92	-13.00	27.92	V
5310	-48.22	5.11	3.00	13.26	-40.07	-13.00	27.07	V



Series Model No.: SP30 Pro

LTE FDD Band 66 Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-47.49	4.02	3.00	12.21	-39.3	-13.00	26.3	H
5337.9	-46.57	5.11	3.00	13.26	-38.42	-13.00	25.42	H
3558.6	-48.83	4.02	3.00	12.21	-40.64	-13.00	27.64	V
5337.9	-48.68	5.11	3.00	13.26	-40.53	-13.00	27.53	V

LTE FDD Band 66 Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-48.02	4.02	3.00	12.21	-39.83	-13.00	26.83	H
5335.5	-46.28	5.11	3.00	13.26	-38.13	-13.00	25.13	H
3557	-49.2	4.02	3.00	12.21	-41.01	-13.00	28.01	V
5335.5	-48.17	5.11	3.00	13.26	-40.02	-13.00	27.02	V

LTE FDD Band 66 Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-47	4.02	3.00	12.21	-38.81	-13.00	25.81	H
5332.5	-46.62	5.11	3.00	13.26	-38.47	-13.00	25.47	H
3555	-48.72	4.02	3.00	12.21	-40.53	-13.00	27.53	V
5332.5	-48.5	5.11	3.00	13.26	-40.35	-13.00	27.35	V

LTE FDD Band 66 Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-47.13	4.02	3.00	12.21	-38.94	-13.00	25.94	H
5325	-47.55	5.11	3.00	13.26	-39.4	-13.00	26.4	H
3550	-48.63	4.02	3.00	12.21	-40.44	-13.00	27.44	V
5325	-49.34	5.11	3.00	13.26	-41.19	-13.00	28.19	V

LTE FDD Band 66 Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-47.72	4.02	3.00	12.21	-39.53	-13.00	26.53	H
5317.5	-47.15	5.11	3.00	13.26	-39	-13.00	26	H
3545	-49.64	4.02	3.00	12.21	-41.45	-13.00	28.45	V
5317.5	-48.66	5.11	3.00	13.26	-40.51	-13.00	27.51	V

LTE FDD Band 66 Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-47.3	4.02	3.00	12.21	-39.11	-13.00	26.11	H
5310	-46.86	5.11	3.00	13.26	-38.71	-13.00	25.71	H
3540	-48.86	4.02	3.00	12.21	-40.67	-13.00	27.67	V
5310	-49.1	5.11	3.00	13.26	-40.95	-13.00	27.95	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

LTE FDD Band 66_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-47.05	4.02	3.00	12.21	-38.86	-13.00	25.86	H
5337.9	-46.33	5.11	3.00	13.26	-38.18	-13.00	25.18	H
3558.6	-48.91	4.02	3.00	12.21	-40.72	-13.00	27.72	V
5337.9	-49.4	5.11	3.00	13.26	-41.25	-13.00	28.25	V

LTE FDD Band 66_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-47.09	4.02	3.00	12.21	-38.9	-13.00	25.9	H
5335.5	-46.61	5.11	3.00	13.26	-38.46	-13.00	25.46	H
3557	-48.95	4.02	3.00	12.21	-40.76	-13.00	27.76	V
5335.5	-49.56	5.11	3.00	13.26	-41.41	-13.00	28.41	V

LTE FDD Band 66_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-47.11	4.02	3.00	12.21	-38.92	-13.00	25.92	H
5332.5	-46.51	5.11	3.00	13.26	-38.36	-13.00	25.36	H
3555	-48.73	4.02	3.00	12.21	-40.54	-13.00	27.54	V
5332.5	-49.25	5.11	3.00	13.26	-41.1	-13.00	28.1	V

LTE FDD Band 66_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-47.33	4.02	3.00	12.21	-39.14	-13.00	26.14	H
5325	-47.02	5.11	3.00	13.26	-38.87	-13.00	25.87	H
3550	-48.83	4.02	3.00	12.21	-40.64	-13.00	27.64	V
5325	-48.98	5.11	3.00	13.26	-40.83	-13.00	27.83	V

LTE FDD Band 66_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-48.08	4.02	3.00	12.21	-39.89	-13.00	26.89	H
5317.5	-46.93	5.11	3.00	13.26	-38.78	-13.00	25.78	H
3545	-48.33	4.02	3.00	12.21	-40.14	-13.00	27.14	V
5317.5	-48.61	5.11	3.00	13.26	-40.46	-13.00	27.46	V

LTE FDD Band 66_Channel Bandwidth 20MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-48.26	4.02	3.00	12.21	-40.07	-13.00	27.07	H
5310	-47.12	5.11	3.00	13.26	-38.97	-13.00	25.97	H
3540	-48.96	4.02	3.00	12.21	-40.77	-13.00	27.77	V
5310	-48.98	5.11	3.00	13.26	-40.83	-13.00	27.83	V

Series Model No.: MT Ultimate

LTE FDD Band 66_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-47.84	4.02	3.00	12.21	-39.65	-13.00	26.65	H
5337.9	-47.45	5.11	3.00	13.26	-39.3	-13.00	26.3	H
3558.6	-48.64	4.02	3.00	12.21	-40.45	-13.00	27.45	V
5337.9	-48.66	5.11	3.00	13.26	-40.51	-13.00	27.51	V

LTE FDD Band 66_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-47.41	4.02	3.00	12.21	-39.22	-13.00	26.22	H
5335.5	-47.03	5.11	3.00	13.26	-38.88	-13.00	25.88	H
3557	-48.94	4.02	3.00	12.21	-40.75	-13.00	27.75	V
5335.5	-48.73	5.11	3.00	13.26	-40.58	-13.00	27.58	V

LTE FDD Band 66_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-46.68	4.02	3.00	12.21	-38.49	-13.00	25.49	H
5332.5	-47.52	5.11	3.00	13.26	-39.37	-13.00	26.37	H
3555	-49.74	4.02	3.00	12.21	-41.55	-13.00	28.55	V
5332.5	-48.62	5.11	3.00	13.26	-40.47	-13.00	27.47	V

LTE FDD Band 66_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-47.49	4.02	3.00	12.21	-39.3	-13.00	26.3	H
5325	-46.39	5.11	3.00	13.26	-38.24	-13.00	25.24	H
3550	-49.17	4.02	3.00	12.21	-40.98	-13.00	27.98	V
5325	-49.31	5.11	3.00	13.26	-41.16	-13.00	28.16	V

LTE FDD Band 66_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-47.39	4.02	3.00	12.21	-39.2	-13.00	26.2	H
5317.5	-47.63	5.11	3.00	13.26	-39.48	-13.00	26.48	H
3545	-48.3	4.02	3.00	12.21	-40.11	-13.00	27.11	V
5317.5	-49.22	5.11	3.00	13.26	-41.07	-13.00	28.07	V

LTE FDD Band 66_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-46.66	4.02	3.00	12.21	-38.47	-13.00	25.47	H
5310	-47.3	5.11	3.00	13.26	-39.15	-13.00	26.15	H
3540	-49.21	4.02	3.00	12.21	-41.02	-13.00	28.02	V
5310	-49.06	5.11	3.00	13.26	-40.91	-13.00	27.91	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 66 Channel Bandwidth 1.4MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-48.2	4.02	3.00	12.21	-40.01	-13.00	27.01	H
5337.9	-47.39	5.11	3.00	13.26	-39.24	-13.00	26.24	H
3558.6	-49.09	4.02	3.00	12.21	-40.9	-13.00	27.9	V
5337.9	-49.12	5.11	3.00	13.26	-40.97	-13.00	27.97	V

LTE FDD Band 66 Channel Bandwidth 3MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-47.47	4.02	3.00	12.21	-39.28	-13.00	26.28	H
5335.5	-47.59	5.11	3.00	13.26	-39.44	-13.00	26.44	H
3557	-48.33	4.02	3.00	12.21	-40.14	-13.00	27.14	V
5335.5	-48.92	5.11	3.00	13.26	-40.77	-13.00	27.77	V

LTE FDD Band 66 Channel Bandwidth 5MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-47.41	4.02	3.00	12.21	-39.22	-13.00	26.22	H
5332.5	-48.03	5.11	3.00	13.26	-39.88	-13.00	26.88	H
3555	-49.04	4.02	3.00	12.21	-40.85	-13.00	27.85	V
5332.5	-48.75	5.11	3.00	13.26	-40.6	-13.00	27.6	V

LTE FDD Band 66 Channel Bandwidth 10MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-47.59	4.02	3.00	12.21	-39.4	-13.00	26.4	H
5325	-47.88	5.11	3.00	13.26	-39.73	-13.00	26.73	H
3550	-49.32	4.02	3.00	12.21	-41.13	-13.00	28.13	V
5325	-48.76	5.11	3.00	13.26	-40.61	-13.00	27.61	V

LTE FDD Band 66 Channel Bandwidth 15MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-47.01	4.02	3.00	12.21	-38.82	-13.00	25.82	H
5317.5	-47.38	5.11	3.00	13.26	-39.23	-13.00	26.23	H
3545	-48.93	4.02	3.00	12.21	-40.74	-13.00	27.74	V
5317.5	-48.77	5.11	3.00	13.26	-40.62	-13.00	27.62	V

LTE FDD Band 66 Channel Bandwidth 20MHz 16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-47.82	4.02	3.00	12.21	-39.63	-13.00	26.63	H
5310	-46.71	5.11	3.00	13.26	-38.56	-13.00	25.56	H
3540	-49.43	4.02	3.00	12.21	-41.24	-13.00	28.24	V
5310	-47.97	5.11	3.00	13.26	-39.82	-13.00	26.82	V

Series Model No.: M15 pro

LTE FDD Band 66_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-46.65	4.02	3.00	12.21	-38.46	-13.00	25.46	H
5337.9	-47.95	5.11	3.00	13.26	-39.8	-13.00	26.8	H
3558.6	-49.54	4.02	3.00	12.21	-41.35	-13.00	28.35	V
5337.9	-48.67	5.11	3.00	13.26	-40.52	-13.00	27.52	V

LTE FDD Band 66_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-47.28	4.02	3.00	12.21	-39.09	-13.00	26.09	H
5335.5	-46.92	5.11	3.00	13.26	-38.77	-13.00	25.77	H
3557	-49.7	4.02	3.00	12.21	-41.51	-13.00	28.51	V
5335.5	-48.95	5.11	3.00	13.26	-40.8	-13.00	27.8	V

LTE FDD Band 66_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-47.43	4.02	3.00	12.21	-39.24	-13.00	26.24	H
5332.5	-47.36	5.11	3.00	13.26	-39.21	-13.00	26.21	H
3555	-49.77	4.02	3.00	12.21	-41.58	-13.00	28.58	V
5332.5	-49.25	5.11	3.00	13.26	-41.1	-13.00	28.1	V

LTE FDD Band 66_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-46.98	4.02	3.00	12.21	-38.79	-13.00	25.79	H
5325	-46.57	5.11	3.00	13.26	-38.42	-13.00	25.42	H
3550	-49.63	4.02	3.00	12.21	-41.44	-13.00	28.44	V
5325	-48.04	5.11	3.00	13.26	-39.89	-13.00	26.89	V

LTE FDD Band 66_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-47.53	4.02	3.00	12.21	-39.34	-13.00	26.34	H
5317.5	-47.21	5.11	3.00	13.26	-39.06	-13.00	26.06	H
3545	-49.26	4.02	3.00	12.21	-41.07	-13.00	28.07	V
5317.5	-49.02	5.11	3.00	13.26	-40.87	-13.00	27.87	V

LTE FDD Band 66_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-47.52	4.02	3.00	12.21	-39.33	-13.00	26.33	H
5310	-47.15	5.11	3.00	13.26	-39	-13.00	26	H
3540	-48.45	4.02	3.00	12.21	-40.26	-13.00	27.26	V
5310	-48.71	5.11	3.00	13.26	-40.56	-13.00	27.56	V

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

LTE FDD Band 66_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3558.6	-47.02	4.02	3.00	12.21	-38.83	-13.00	25.83	H
5337.9	-47.21	5.11	3.00	13.26	-39.06	-13.00	26.06	H
3558.6	-48.85	4.02	3.00	12.21	-40.66	-13.00	27.66	V
5337.9	-48.68	5.11	3.00	13.26	-40.53	-13.00	27.53	V

LTE FDD Band 66_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3557	-47.27	4.02	3.00	12.21	-39.08	-13.00	26.08	H
5335.5	-47.27	5.11	3.00	13.26	-39.12	-13.00	26.12	H
3557	-49.2	4.02	3.00	12.21	-41.01	-13.00	28.01	V
5335.5	-47.96	5.11	3.00	13.26	-39.81	-13.00	26.81	V

LTE FDD Band 66_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3555	-48.01	4.02	3.00	12.21	-39.82	-13.00	26.82	H
5332.5	-46.41	5.11	3.00	13.26	-38.26	-13.00	25.26	H
3555	-49.6	4.02	3.00	12.21	-41.41	-13.00	28.41	V
5332.5	-49.42	5.11	3.00	13.26	-41.27	-13.00	28.27	V

LTE FDD Band 66_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3550	-47.99	4.02	3.00	12.21	-39.8	-13.00	26.8	H
5325	-46.7	5.11	3.00	13.26	-38.55	-13.00	25.55	H
3550	-48.72	4.02	3.00	12.21	-40.53	-13.00	27.53	V
5325	-49.14	5.11	3.00	13.26	-40.99	-13.00	27.99	V

LTE FDD Band 66_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3545	-46.9	4.02	3.00	12.21	-38.71	-13.00	25.71	H
5317.5	-47.11	5.11	3.00	13.26	-38.96	-13.00	25.96	H
3545	-48.85	4.02	3.00	12.21	-40.66	-13.00	27.66	V
5317.5	-48.51	5.11	3.00	13.26	-40.36	-13.00	27.36	V

LTE FDD Band 66_Channel Bandwidth 20MHz_16QAM


Frequency (MHz)	PMea (dBm)	Pcl (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540	-47.51	4.02	3.00	12.21	-39.32	-13.00	26.32	H
5310	-47.32	5.11	3.00	13.26	-39.17	-13.00	26.17	H
3540	-49.09	4.02	3.00	12.21	-40.9	-13.00	27.9	V
5310	-48.23	5.11	3.00	13.26	-40.08	-13.00	27.08	V

3.6 Frequency Stability under Temperature & Voltage Variations

LIMIT

According to §27.54, §2.1055 requirement, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation and should not exceed 2.5ppm.

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D.

Frequency Stability Under Temperature Variations:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 4, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1V increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS

Remark:

1. We tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 66; recorded worst case.

LTE Band 66, 1.4MHz bandwidth , QPSK (worst case of all bandwidths)



LTE FDD Band 66				
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Verdict
4.25	20	-9.33	-0.005454	PASS
5.0	20	-4.43	-0.002590	PASS
5.75	20	-7.51	-0.004390	PASS
5.0	-30	-9.71	-0.005676	PASS
5.0	-20	-9.88	-0.005775	PASS
5.0	-10	-9.63	-0.005629	PASS
5.0	0	-8.47	-0.004951	PASS
5.0	10	-11.14	-0.006512	PASS
5.0	20	-11.14	-0.006512	PASS
5.0	30	-6.25	-0.003582	PASS
5.0	40	-4.72	-0.002705	PASS
5.0	50	-7.30	-0.004183	PASS

LTE Band 66, 1.4MHz bandwidth , 16QAM (worst case of all bandwidths)


LTE FDD Band 66				
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Verdict
4.25	20	-6.67	-0.003899	PASS
5.0	20	-5.84	-0.003414	PASS
5.75	20	-8.35	-0.004881	PASS
5.0	-30	-9.10	-0.005319	PASS
5.0	-20	-7.60	-0.004443	PASS
5.0	-10	-7.88	-0.004606	PASS
5.0	0	-8.40	-0.004910	PASS
5.0	10	-4.12	-0.002408	PASS
5.0	20	-7.48	-0.004372	PASS
5.0	30	-3.99	-0.002287	PASS
5.0	40	-6.28	-0.003599	PASS
5.0	50	-5.92	-0.003393	PASS

4 Test Setup Photos of the EUT



Test Model No.: I16 Pro max
Radiated Emissions



RF Conducted Emission




Series Model No.: S26 Ultra
Radiated Emissions



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



Series Model No.: Pixel 9
Radiated Emissions



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China


Series Model No.: SP30 Pro
Radiated Emissions



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



Series Model No.: MT Ultimate
Radiated Emissions



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Series Model No.: M15 pro
Radiated Emissions



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

5 Photos of the EUT

Reference to the report: ANNEX A of external photos and ANNEX B of internal photos.

.....**End of Report**.....