

FCC ID : 2BDJ6-ME25LS03

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

$P_i = 3.1416$

R= distance between observation point and center of the radiator in cm

P_d the limit of MPE, $1\text{mW}/\text{cm}^2$, If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits. This device should be operated with a minimum separation distance of 20cm (8 inches) between the equipment and a person's body.

11.2 Measurement Result

WiFi 2.4G and Bluetooth cannot transmit at the same time

BLE

Antenna gain: 2.42dBi

LORA

Antenna gain: 2.73dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm^2)	Power density Limits (mW/cm^2)
BLE	2440	7.56	6 to 8	8	1.75	0.002	1
LORA	903.125	19.19	18 to 20	20	1.87	0.037	0.602

CONCLUSION of simultaneous transmitter

Both of the BLE and LORA can transmit simultaneously, the formula of calculated the MPE is:

$$CPD_1/LPD_1 + CPD_2/LPD_2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density



Therefore the worst-case situation is $0.002/1.00+0.037/0.602=0.0634$ which is less than “1”,

This confirmed that the device comply with FCC 1.1310 MPE limit.