FCC TEST REPORT
FCC ID:2BDK9-BS002

Report Number.....:	ZKT-231114L8833E-1
Date of Test.....	Nov.14 to Nov. 20, 2023
Date of issue.....:	Nov. 20, 2023
Total number of pages.....	35
Test Result .....:	PASS
Testing Laboratory.....:	Shenzhen ZKT Technology Co., Ltd.
Address .....:	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Applicant's name .....:	**BSC Products Limited**
Address .....:	102 Ringwood Rd, Oakville, ON, Canada, L6H1K2
Manufacturer's name .....:	**Galaxy Commutech LTD**
Address .....:	No.1 Jiaolong Road, Jiaoyi Tang Village, Tangxia Town, Dongguan City, Guangdong Province
Test specification:	
Standard.....:	FCC CFR Title 47 Part 15 Subpart C Section 15.249 ANSI C63.10:2013
Test procedure.....:	/
Non-standard test method .....:	N/A
Test Report Form No.....:	TRF-EL-111_V0
Test Report Form(s) Originator.....:	ZKT Testing
Master TRF .....:	Dated: 2023-01-05

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name.....:	Dangles
Trademark .....:	Bolt Sports Co
Model/Type reference.....:	BS002
Ratings.....:	DC 5V 1A from adapter, AC120V/60Hz for adapter or DC 3.7V from battery

Testing procedure and testing location:

Testing Laboratory.....:	Shenzhen ZKT Technology Co., Ltd.
Address.....:	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Tested by (name + signature).....:	Alen He
Reviewer (name + signature).....:	Joe Liu
Approved (name + signature).....:	Lake Xie

Table of Contents **Page**

1.VERSION **5**

2 SUMMARY OF TEST RESULTS **6**

2.1 TEST FACILITY **7**

2.2 MEASUREMENT UNCERTAINTY **7**

3. GENERAL INFORMATION **8**

3.1 GENERAL DESCRIPTION OF EUT **8**

3.2 DESCRIPTION OF TEST MODES **9**

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED **9**

3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) **10**

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS **11**

4. EMC EMISSION TEST **13**

4.1 CONDUCTED EMISSION MEASUREMENT **13**

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS **13**

4.1.2 TEST PROCEDURE **13**

4.1.3 DEVIATION FROM TEST STANDARD **13**

4.1.4 TEST SETUP **14**

4.1.5 EUT OPERATING CONDITIONS **14**

4.1.6 TEST RESULTS **15**

4.2 RADIATED EMISSION MEASUREMENT **17**

4.2.1 RADIATED EMISSION LIMITS **17**

4.2.2 TEST PROCEDURE **18**

4.2.3 DEVIATION FROM TEST STANDARD **18**

4.2.4 TEST SETUP **18**

4.2.5 EUT OPERATING CONDITIONS **19**

5. BANDWIDTH OF FREQUENCY BAND EDGE **25**

5.1 TEST REQUIREMENT: **25**

5.2 TEST PROCEDURE **25**

5.3 DEVIATION FROM TEST STANDARD **25**

5.4 TEST SETUP **25**

5.5 EUT OPERATING CONDITIONS **26**

5.6 TEST RESULT **27**

6. CHANNEL BANDWIDTH **29**

6.1 APPLIED PROCEDURES / LIMIT **29**

6.2 TEST PROCEDURE **29**

6.3 DEVIATION FROM STANDARD **29**

6.4 TEST SETUP **29**

Table of Contents **Page**

6.5 EUT OPERATION CONDITIONS 29
6.6 TEST RESULTS 30

7. CONDUCTED SPURIOUS EMISSION 32
7.1 APPLICABLE STANDARD 32
7.2 TEST PROCEDURE 32
7.3 DEVIATION FROM STANDARD 32
7.4 TEST SETUP 32
7.5 EUT OPERATION CONDITIONS 32

8.ANTENNA REQUIREMENT 34

9. TEST SETUP PHOTO 35

10. EUT CONSTRUCTIONAL DETAILS 35

1.VERSION

Report No.	Version	Description	Approved
ZKT-231114L8833E-1	Rev.01	Initial issue of report	Nov. 20, 2023

2 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
FCC part 15.203	Antennarequirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.249	Fundamental &Radiated Spurious Emission Measurement	PASS	
FCC part 15.215 (c)	20dB Channel Bandwidth	PASS	
FCC part 15.205	Band Edge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power conducted	±0.16dB
3	Spurious emissions conducted	±0.21dB
4	All emissions radiated(<1G)	±4.68dB
5	All emissions radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Dangles
Model No.:	BS002
Model Different.:	N/A
Serial No.:	N/A
Hardware Version:	HV1.0
Software Version:	SV1.0
Sample(s) Status:	Engineer sample
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel Separation:	2MHz
Modulation Type:	GFSK
Antenna Type:	PCB Antenna
Antenna gain:	0dBi
Power supply:	DC5V 1A from adapter, AC 120V/60Hz for adapter or DC 3.7V from battery
SWITCHING POWER ADAPTER:	N/A
Battery:	DC 3.7V 1000mAh

Operation Frequency each of channel

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402 MHz	11	2422 MHz	21	2442 MHz	31	2462 MHz
2	2404 MHz	12	2424 MHz	22	2444 MHz	32	2464 MHz
3	2406 MHz	13	2426 MHz	23	2446 MHz	33	2466 MHz
4	2408 MHz	14	2428 MHz	24	2448 MHz	34	2468 MHz
5	2410 MHz	15	2430 MHz	25	2450 MHz	35	2470 MHz
6	2412 MHz	16	2432 MHz	26	2452 MHz	36	2472 MHz
7	2414 MHz	17	2434 MHz	27	2454 MHz	37	2474 MHz
8	2416 MHz	18	2436 MHz	28	2456 MHz	38	2476 MHz
9	2418 MHz	19	2438 MHz	29	2458 MHz	39	2478 MHz
10	2420 MHz	20	2440 MHz	30	2460 MHz	40	2480 MHz

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	BT Test Tool
Power level setup	<0dBm

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Dangles	Bolt Sports Co	BS002	N/A	EUT
E-2	Adapter	N/A	RYF910B190342VC		Supply by Lab

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.8M	DC Line

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	Oct. 18, 2023	Oct. 17, 2024
2	Spectrum Analyzer (1GHz-40GHz)	R&S	FSQ	100363	Oct. 17, 2023	Oct. 16, 2024
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Oct. 18, 2023	Oct. 17, 2024
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	Oct. 17, 2023	Oct. 16, 2024
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	Oct. 17, 2023	Oct. 16, 2024
6	Loop Antenna	TESEQ	HLA6121	58357	Oct. 17, 2023	Oct. 16, 2024
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	060747	Oct. 18, 2023	Oct. 17, 2024
8	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	Oct. 18, 2023	Oct. 17, 2024
9	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Oct. 18, 2023	Oct. 17, 2024
10	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Oct. 18, 2023	Oct. 17, 2024
11	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Oct. 18, 2023	Oct. 17, 2024
12	ESG Signal Generator	Agilent	E4421B	N/A	Oct. 22, 2023	Oct. 21, 2024
13	Signal Generator	Agilent	N5182A	N/A	Oct. 22, 2023	Oct. 21, 2024
14	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	Oct. 17, 2022	Oct. 16, 2023
15	MWRF Power Meter Test system	MW	MW100-RPCB	N/A	Oct. 22, 2023	Oct. 21, 2024
16	D.C. Power Supply	LongWei	TPR-6405D	N/A	\	\
17	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\
18	RF Software	MW	MTS8310	V2.0.0.0	\	\
19	Turntable	MF	MF-7802BS	N/A	\	\
20	Antenna tower	MF	MF-7802BS	N/A	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Oct. 22, 2023	Oct. 21, 2024
2	LISN	CYBERTEK	EM5040A	E1850400149	Oct. 22, 2023	Oct. 21, 2024
3	Test Cable	N/A	C01	N/A	Oct. 18, 2023	Oct. 17, 2024
4	Test Cable	N/A	C02	N/A	Oct. 18, 2023	Oct. 17, 2024
5	EMI Test Receiver	R&S	ESCI3	101393	Oct. 17, 2023	Oct. 16, 2024
6	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quas-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 TEST RESULTS

Temperature :	26℃	Relative Humidity:	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.3540	30.50	10.64	41.14	58.87	-17.73	QP
2	0.3540	18.42	10.64	29.06	48.87	-19.81	AVG
3	0.6260	27.26	10.42	37.68	56.00	-18.32	QP
4	0.6260	18.06	10.42	28.48	46.00	-17.52	AVG
5	1.0620	27.10	10.30	37.40	56.00	-18.60	QP
6	1.0620	18.76	10.30	29.06	46.00	-16.94	AVG
7	1.7700	26.30	10.30	36.60	56.00	-19.40	QP
8	1.7700	18.12	10.30	28.42	46.00	-17.58	AVG
9	2.4780	24.99	10.32	35.31	56.00	-20.69	QP
10	2.4780	16.90	10.32	27.22	46.00	-18.78	AVG
11	3.5420	24.06	10.38	34.44	56.00	-21.56	QP
12	3.5420	11.10	10.38	21.48	46.00	-24.52	AVG

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

Temperature :	26℃	Relative Humidity:	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2060	26.74	10.34	37.08	63.37	-26.29	QP
2	0.2060	16.87	10.34	27.21	53.37	-26.16	AVG
3	0.6380	28.13	10.41	38.54	56.00	-17.46	QP
4	0.6380	22.81	10.41	33.22	46.00	-12.78	AVG
5	1.0380	24.95	10.30	35.25	56.00	-20.75	QP
6	1.0380	16.68	10.30	26.98	46.00	-19.02	AVG
7	1.6300	23.13	10.30	33.43	56.00	-22.57	QP
8	1.6300	15.68	10.30	25.98	46.00	-20.02	AVG
9	3.5980	22.68	10.38	33.06	56.00	-22.94	QP
10	3.5980	16.39	10.38	26.77	46.00	-19.23	AVG
11	4.8140	22.48	10.45	32.93	56.00	-23.07	QP
12	4.8140	13.03	10.45	23.48	46.00	-22.52	AVG

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
g. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
Note:
Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS (Between 9KHz – 30 MHz)

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	70.8315	42.83	-17.10	25.73	40.00	-14.27	QP
2	99.7026	45.97	-19.83	26.14	43.50	-17.36	QP
3	211.8976	51.89	-18.19	33.70	43.50	-9.80	QP
4	355.4272	45.05	-16.75	28.30	46.00	-17.70	QP
5	495.9343	35.49	-11.83	23.66	46.00	-22.34	QP
6	854.0247	33.29	-6.97	26.32	46.00	-19.68	QP

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	35.4369	47.00	-17.54	29.46	40.00	-10.54	QP
2	70.2132	50.01	-19.40	30.61	40.00	-9.39	QP
3	103.2609	52.32	-21.25	31.07	43.50	-12.43	QP
4	211.8976	50.73	-20.51	30.22	43.50	-13.28	QP
5	419.8435	37.94	-14.35	23.59	46.00	-22.41	QP
6	782.3451	35.70	-4.29	31.41	46.00	-14.59	QP

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.

Field Strength of The Fundamental Signal
Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	91.96	27.26	5.39	30.18	94.43	114.00	-19.57	Vertical
2402.00	91.24	27.26	5.39	30.18	93.71	114.00	-20.29	Horizontal
2440.00	90.20	27.33	5.43	30.06	92.90	114.00	-21.10	Vertical
2440.00	83.85	27.33	5.43	30.06	86.55	114.00	-27.45	Horizontal
2480.00	91.24	27.40	5.47	29.93	94.18	114.00	-19.82	Vertical
2480.00	88.08	27.40	5.47	29.93	91.02	114.00	-22.98	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	81.40	27.26	5.39	30.18	83.87	94.00	-10.13	Vertical
2402.00	79.69	27.26	5.39	30.18	82.16	94.00	-11.84	Horizontal
2440.00	78.57	27.33	5.43	30.06	81.27	94.00	-12.73	Vertical
2440.00	74.76	27.33	5.43	30.06	77.46	94.00	-16.54	Horizontal
2480.00	82.74	27.40	5.47	29.93	85.68	94.00	-8.32	Vertical
2480.00	79.00	27.40	5.47	29.93	81.94	94.00	-12.06	Horizontal

1GHz~25GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	51.22	30.55	5.77	31.12	57.56	74.00	-16.44	Pk
V	4804.00	31.08	30.55	5.77	31.12	37.42	54.00	-16.58	AV
V	7206.00	49.31	30.33	6.32	36.04	61.34	74.00	-12.66	Pk
V	7206.00	31.79	30.33	6.32	36.04	43.82	54.00	-10.18	AV
V	9608.00	49.81	30.85	7.45	37.58	63.99	74.00	-10.01	Pk
V	9608.00	31.69	30.85	7.45	37.58	45.87	54.00	-8.13	AV
V	12010.00	49.91	31.02	8.99	39.10	66.98	74.00	-7.02	Pk
V	12010.00	31.69	31.02	8.99	39.10	48.76	54.00	-5.24	AV
H	4804.00	51.56	30.55	5.77	31.12	57.90	74.00	-16.10	Pk
H	4804.00	31.41	30.55	5.77	31.12	37.75	54.00	-16.25	AV
H	7206.00	50.20	30.33	6.32	36.04	62.23	74.00	-11.77	Pk
H	7206.00	31.46	30.33	6.32	36.04	43.49	54.00	-10.51	AV
H	9608.00	50.20	30.85	7.45	37.58	64.38	74.00	-9.62	Pk
H	9608.00	31.46	30.85	7.45	37.58	45.64	54.00	-8.36	AV
H	12010.00	50.20	31.02	8.99	39.10	67.27	74.00	-6.73	Pk
H	12010.00	30.46	31.02	8.99	39.10	47.53	54.00	-6.47	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2440MHz									
V	4880.00	51.22	30.55	5.77	31.46	57.90	74.00	-16.10	Pk
V	4880.00	32.11	30.55	5.77	31.46	38.79	54.00	-15.21	AV
V	7320.00	49.75	30.33	6.32	36.15	61.89	74.00	-12.11	Pk
V	7320.00	31.79	30.33	6.32	36.15	43.93	54.00	-10.07	AV
V	9760.00	49.82	30.85	7.45	37.76	64.18	74.00	-9.82	Pk
V	9760.00	31.79	30.85	7.45	37.76	46.15	54.00	-7.85	AV
V	12200.00	49.72	31.02	8.99	39.10	66.79	74.00	-7.21	Pk
V	12200.00	31.79	31.02	8.99	39.10	48.86	54.00	-5.14	AV
H	4880.00	52.58	30.55	5.77	31.46	59.26	74.00	-14.74	Pk
H	4880.00	32.14	30.55	5.77	31.46	38.82	54.00	-15.18	AV
H	7320.00	53.29	30.33	6.32	36.15	65.43	74.00	-8.57	Pk
H	7320.00	31.92	30.33	6.32	36.15	44.06	54.00	-9.94	AV
H	9760.00	53.29	30.85	7.45	37.76	67.65	74.00	-6.35	Pk
H	9760.00	31.92	30.85	7.45	37.76	46.28	54.00	-7.72	AV
H	12200.00	49.79	31.02	8.99	39.10	66.86	74.00	-7.14	Pk
H	12200.00	31.92	31.02	8.99	39.10	48.99	54.00	-5.01	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	51.00	30.55	5.77	31.79	58.01	74.00	-15.99	Pk
V	4960.00	32.54	30.55	5.77	31.79	39.55	54.00	-14.45	AV
V	7440.00	53.51	30.33	6.32	36.38	65.88	74.00	-8.12	Pk
V	7440.00	32.86	30.33	6.32	36.38	45.23	54.00	-8.77	AV
V	9920.00	53.51	30.85	7.45	36.50	66.61	74.00	-7.39	Pk

V	9920.00	33.35	30.85	7.45	36.50	46.45	54.00	-7.55	AV
V	12400.00	53.51	31.02	8.99	39.11	70.59	74.00	-3.41	Pk
V	12400.00	32.75	31.02	8.99	39.11	49.83	54.00	-4.17	AV
H	4960.00	51.09	30.55	5.77	31.79	58.10	74.00	-15.90	Pk
H	4960.00	32.76	30.55	5.77	31.79	39.77	54.00	-14.23	AV
H	7440.00	52.68	30.33	6.32	36.38	65.05	74.00	-8.95	Pk
H	7440.00	33.02	30.33	6.32	36.38	45.39	54.00	-8.61	AV
H	9920.00	53.28	30.85	7.45	36.50	66.38	74.00	-7.62	Pk
H	9920.00	33.12	30.85	7.45	36.50	46.22	54.00	-7.78	AV
H	12400.00	53.18	31.02	8.99	39.11	70.26	74.00	-3.74	Pk
H	12400.00	33.12	31.02	8.99	39.11	50.20	54.00	-3.80	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. BANDWIDTH OF FREQUENCY BAND EDGE

5.1 TEST REQUIREMENT:

<table>
<tr><td>Test Requirement:</td><td>FCC Part15 C Section 15.209 and 15.205</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10: 2013</td></tr>
<tr><td>Test Frequency Range:</td><td>All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.</td></tr>
<tr><td>Test site:</td><td>Measurement Distance: 3m</td></tr>
<tr><td>Receiver setup:</td><td>
<table>
<tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Value</td></tr>
<tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak</td></tr>
<tr><td>Average</td><td>1MHz</td><td>3MHz</td><td>Average</td></tr>
</table>
</td></tr>
</table>

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
g. Test the EUT in the lowest channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	101 kPa	Test Voltage ：	AC 120V/60Hz
Test Mode ：	TX Mode		

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	38.88	27.59	5.38	30.18	41.67	74.00	-32.33	Horizontal
2400.00	42.01	27.58	5.39	30.18	44.80	74.00	-29.20	Horizontal
2390.00	36.82	27.59	5.38	30.18	39.61	74.00	-34.39	Vertical
2400.00	40.91	27.58	5.39	30.18	43.70	74.00	-30.30	Vertical

2402MHz Horizontal



2402MHz Vertical



Temperature :	26 ℃	Relative Humidity :	54%
Pressure :	101 kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode		

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	36.08	27.53	5.47	29.93	39.15	74.00	-34.85	Horizontal
2500.00	37.24	27.55	5.49	29.93	40.35	74.00	-33.65	Horizontal
2483.50	34.71	27.53	5.47	29.93	37.78	74.00	-36.22	Vertical
2500.00	36.14	27.55	5.49	29.93	39.25	74.00	-34.75	Vertical

2480MHz Horizontal



2480MHz Vertical



6. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10: 2013

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.249(c)	Bandwidth	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 1-5% or DTS BW, not to exceed 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP

6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

Temperature：	26℃	Relative Humidity：	54%
Test Mode ：	GFSK	Test Voltage ：	AC 120V/60Hz

Test channel	Channel Bandwidth (MHz)	Result
Lowest	0.6252	Pass
Middle	0.5467	
Highest	0.5326	

CH01



CH20


Agilent Spectrum Analyzer - Occupied BW
Center Freq 2.440000000 GHz
Center Freq: 2.440000000 GHz
Trig: Free Run
Avg|Hold: 100/100
#Atten: 30 dB
Radio Std: None
Radio Device: BTS
#IFGain:Low
Ref Offset 1.86 dB
10 dB/div
Ref 21.86 dBm
Mkr3 2.440281 GHz
-11.753 dBm
Center 2.44 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 2 MHz
Sweep 1.333 ms
Occupied Bandwidth
1.0666 MHz
Total Power 1.45 dBm
Transmit Freq Error 7.923 kHz
OBW Power 99.00 %
x dB Bandwidth 546.7 kHz
x dB -6.00 dB
MSG
STATUS

CH40


Agilent Spectrum Analyzer - Occupied BW
Center Freq 2.480000000 GHz
Center Freq: 2.480000000 GHz
Trig: Free Run
Avg|Hold: 100/100
#Atten: 30 dB
Radio Std: None
Radio Device: BTS
#IFGain:Low
Ref Offset 1.9 dB
10 dB/div
Ref 21.90 dBm
Mkr3 2.480274 GHz
-12.279 dBm
Center 2.48 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 2 MHz
Sweep 1.333 ms
Occupied Bandwidth
1.0699 MHz
Total Power 0.90 dBm
Transmit Freq Error 7.374 kHz
OBW Power 99.00 %
x dB Bandwidth 532.6 kHz
x dB -6.00 dB
MSG
STATUS

7. CONDUCTED SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.249
Test Method:	ANSI C63.10: 2013

7.1 APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

7.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

A) Set the RBW = 100KHz.
B) Set the VBW = 300KHz.
C) Sweep time = auto couple.
D) Detector function = peak.
E) Trace mode = max hold.
F) Allow trace to fully stabilize.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP

7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

Lowest channel



Middle channel



Highest channel



8.ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antennas are PCB antenna, the best case gain of the antennas are 0dBi, reference to the appendix II for details	

9. TEST SETUP PHOTO

Reference to the appendix I for details.

10. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

※※※※※ END OF REPORT ※※※※※