



# TEST REPORT



Report No. : KES-RF240513  
Page 1 / 31

**KES Co., Ltd.**

#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu,  
Anyang-si, Gyeonggi-do, 14057, Republic of Korea  
Tel : +82-31-425-6200, Fax : +82-31-341-3838

## ■ FCC TEST REPORT

### 1. Client

- Name : LEETEK LIFE CO.,LTD
- Address : 2F, 47, Ojeong-ro, Bucheon-si, Gyeonggi-do, South Korea

### 2. Sample Description

- Product item : Fall prevention sensor
- Model name : LFW2939-01
- Manufacturer etc. : LEETEK LIFE CO.,LTD

### 3. Date of test : 2024.08.23 ~ 2024.09.20

### 4. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing

- Address : 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea

### 5. Test method used : Part 15 Subpart C 15.247

### 6. Test result : PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
This laboratory is not accredited for the test results marked \*.  
This test report is not related to KOLAS accreditation.

|             |                                  |                                  |
|-------------|----------------------------------|----------------------------------|
| Affirmation | Tested by                        | Technical Manager                |
|             | Name : Gu-Bong, Kang (Signature) | Name : Yeong-Jun Cho (Signature) |

[강구봉]2024/09/30

[이영진]2024/09/30

2024 . 09. 30.

**KES Co., Ltd.**

**Accredited by KOLAS, Republic of KOREA**



REPORT REVISION HISTORY

| Date       | Test Report No. | Revision History |
|------------|-----------------|------------------|
| 2024.09.30 | KES-RF240513    | Initial          |
|            |                 |                  |
|            |                 |                  |

*This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.*

Use of uncertainty of measurement for decisions on conformity (decision rule):

- ☒ No decision rule is specified by the standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty(“simple acceptance” decision rule, previously known as “accuracy method”).
- ☐ Other (to be specified, for example when required by the standard or client)



## TABLE OF CONTENTS

|             |                                                |    |
|-------------|------------------------------------------------|----|
| 1.          | General information .....                      | 4  |
| 1.1.        | EUT description .....                          | 4  |
| 1.2.        | Test configuration.....                        | 4  |
| 1.3.        | Information about derivative model .....       | 5  |
| 1.4.        | Accessory information .....                    | 5  |
| 1.5.        | Device modifications.....                      | 5  |
| 1.6.        | Sample calculation .....                       | 5  |
| 1.7.        | Measurement Uncertainty .....                  | 5  |
| 1.8.        | Frequency/channel operations .....             | 6  |
| 2.          | Summary of tests .....                         | 7  |
| 3.          | Test results .....                             | 8  |
| 3.1.        | 6 dB bandwidth .....                           | 8  |
| 3.2.        | Output power .....                             | 10 |
| 3.3.        | Power spectral density .....                   | 12 |
| 3.4.        | Radiated restricted band and emissions .....   | 14 |
| 3.5.        | Conducted spurious emissions & band edge ..... | 25 |
| 3.6.        | AC conducted emissions .....                   | 28 |
| 3.7.        | Antenna Requirement.....                       | 30 |
| Appendix A. | Measurement equipment.....                     | 31 |



Report No. : KES-RF240513

## 1. General information

Applicant: LEETEK LIFE CO.,LTD  
Applicant address: 2F, 47, Ojeong-ro, Bucheon-si, Gyeonggi-do, South Korea  
Test site: KES Co., Ltd.  
Test site address: ☐ #3002, #3503, #3701, 40, Simin-daero365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea  
☒ 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea  
Test Facility FCC Accreditation Designation No.: KR0100, Registration No.: 444148  
FCC rule part(s): 15.247  
FCC ID: 2BDLQ-LFW2939-01  
Test device serial No.: ☒ Production ☐ Pre-production ☐ Engineering

### 1.1. EUT description

Equipment under test Fall prevention sensor  
Frequency range 902.2 MHz ~ 927.5 MHz (Lora)  
Model LFW2939-01  
Derivative model LF-2T  
Modulation technique GFSK  
Number of channels 902.2 MHz ~ 927.5 MHz : 3 ch  
Antenna specification PCB Antenna // Peak gain: -7.33 dBi  
Power source DC 3.7 V (Battery)  
H/W version 1.01  
S/W version 1.00

### 1.2. Test configuration

The **LEETEK LIFE CO.,LTD // Fall prevention sensor // LFW2939-01 // FCC ID: 2BDLQ-LFW2939-01** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15.247  
KDB 558074 D01 v05 r02  
ANSI C63.10-2013



Report No. : KES-RF240513

**1.3. Information about derivative model**

Added Derived model of difference in simple model name.

Basic model and electrical circuitry, structure and performance are the same.

**1.4. Accessory information**

| Equipment | Manufacturer | Model | Serial No. | Power source |
|-----------|--------------|-------|------------|--------------|
| -         | -            | -     | -          | -            |

**1.5. Device modifications**

N/A

**1.6. Sample calculation**

Where relevant, the following sample calculation is provided

For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 0.85 + 10 = 10.85 \text{ (dB)}\end{aligned}$$

For Radiation test :

$$\text{Field strength level (dB } \mu\text{V/m)} = \text{Measured level (dB } \mu\text{V)} + \text{Antenna factor (dB)} + \text{Cable loss (dB)} - \text{Amplifier gain (dB)}$$

**1.7. Measurement Uncertainty**

| Test Item                                                                                                                                     |             | Uncertainty                |
|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------|----------------------------|
| Uncertainty for Conduction emission test                                                                                                      |             | 2.22 dB ( SHIELD ROOM #6 ) |
| Uncertainty for Radiation emission test<br>(include Fundamental emission)                                                                     | Below 1 GHz | 4.04 dB ( SAC #6 )         |
|                                                                                                                                               | Above 1 GHz | 5.32 dB ( SAC #5 )         |
| Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. |             |                            |



### 1.8. Frequency/channel operations

| Ch. | Frequency (MHz) | Mode |
|-----|-----------------|------|
| 00  | 902.2           | Lora |
| 01  | 915.0           | Lora |
| 02  | 927.5           | Lora |





## 2. Summary of tests

| Section in<br>FCC Part 15 | Test description                          | Test results |
|---------------------------|-------------------------------------------|--------------|
| 15.247(a)(2)              | 6 dB bandwidth                            | Pass         |
| 15.247(b)(3)              | Output power                              | Pass         |
| 15.247(e)                 | Power spectral density                    | Pass         |
| 15.205, 15.209            | Radiated restricted band and emission     | Pass         |
| 15.247(d)                 | Conducted spurious emission and band edge | Pass         |
| 15.207(a)                 | AC Conducted emissions                    | Pass         |
| 15.203                    | Antenna Requirement                       | Pass         |

\*N/T: Not Tested






### 3. Test results

#### 3.1. 6 dB bandwidth

##### Test procedure

ANSI C63.10-2013 - Section 11.8.2

##### Test setup



##### ANSI C63.10-2013 - Section 11.8.2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW  $\geq 3 \times$  RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.


##### Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.



## Test results

| Frequency(MHz) | 6 dB bandwidth(MHz) | Limit(MHz) |
|----------------|---------------------|------------|
| 902.2          | 0.623               | ≥ 0.500    |
| 915.0          | 0.619               |            |
| 927.5          | 0.623               |            |






### 3.2. Output power

#### Test procedure

ANSI C63.10-2013 – Section 11.9.1.3 and 11.9.2.3.2

#### Test setup



#### ANSI C63.10-2013 – Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

#### ANSI C63.10-2013 – Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

#### Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 MHz, 2 400~2 483.5 MHz, and 5 725~5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.



Test results

| Mode | 902.2 MHz     |            | 915.0 MHz     |            | 927.5 MHz     |            | Power Limit (dBm) |
|------|---------------|------------|---------------|------------|---------------|------------|-------------------|
|      | Average (dBm) | Peak (dBm) | Average (dBm) | Peak (dBm) | Average (dBm) | Peak (dBm) |                   |
| Lora | 8.12          | 8.20       | 8.10          | 8.19       | 8.02          | 8.11       | 30.00             |






### 3.3. Power spectral density

#### Test procedure

ANSI C63.10-2013 - Section 11.10.2

#### Test setup



#### Section 10.2 & ANSI C63.10-2013 - Section 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- Set the VBW  $\geq [3 \times \text{RBW}]$ .
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


#### Limit

According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.



## Results

| Frequency(MHz) | PSD (dBm/3 kHz) | Limit(dBm/3 kHz) |
|----------------|-----------------|------------------|
| 902.2          | -6.07           | ≤ 8              |
| 915.0          | -5.91           |                  |
| 927.5          | -6.02           |                  |







### 3.4. Radiated restricted band and emissions

#### Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.





The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



#### Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

##### Test procedure below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that parallel was worst-case orientation; therefore, all final radiated testing was performed with the EUT in parallel.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

##### Test procedure above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground for 30 MHz-1 GHz and 1.5 meters for above 1 GHz at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
5. Spectrum analyzer settings for  $f < 1$  GHz:

- ① Span = wide enough to fully capture the emission being measured
- ② RBW = 100 kHz
- ③ VBW  $\geq$  RBW
- ④ Detector = quasi peak
- ⑤ Sweep time = auto
- ⑥ Trace = max hold



6. Spectrum analyzer settings for  $f \geq 1$  GHz: Peak

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW  $\geq 3$  MHz
- ④ Detector = peak
- ⑤ Sweep time = auto
- ⑥ Trace = max hold
- ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for  $f \geq 1$  GHz: Average

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW  $\geq 3 \times$  RBW
- ④ Detector = RMS, if  $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$ . Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- ⑤ Averaging type = power(i.e., RMS)
  - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
  - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- ⑥ Sweep = auto
- ⑦ Trace = max hold
- ⑧ Perform a trace average of at least 100 traces.
- ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
  - 1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is  $10 \log(1/x)$ , where  $x$  is the duty cycle.
  - 2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is  $20 \log(1/x)$ , where  $x$  is the duty cycle.
  - 3) If a specific emission is demonstrated to be continuous ( $\geq 98$  percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

**Note.**

1.  $f < 30$  MHz, extrapolation factor of 40 dB/decade of distance.  $F_d = 40\log(D_m/D_s)$   
 $f \geq 30$  MHz, extrapolation factor of 20 dB/decade of distance.  $F_d = 20\log(D_m/D_s)$   
 Where:  
 $F_d$  = Distance factor in dB  
 $D_m$  = Measurement distance in meters  
 $D_s$  = Specification distance in meters
2. Field strength(dB $\mu$ V/m) = Level(dB $\mu$ V) + CF (dB) + or DCF(dB)
3. Margin(dB) = Limit(dB $\mu$ V/m) – Field strength(dB $\mu$ V/m)
4. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation**.
6. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

**Limit**

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

| Frequency (MHz) | Distance (Meters) | Radiated ( $\mu$ V/m) |
|-----------------|-------------------|-----------------------|
| 0.009 ~ 0.490   | 300               | 2400/F(kHz)           |
| 0.490 ~ 1.705   | 30                | 24000/F(kHz)          |
| 1.705 ~ 30.0    | 30                | 30                    |
| 30 ~ 88         | 3                 | 100**                 |
| 88 ~ 216        | 3                 | 150**                 |
| 216 ~ 960       | 3                 | 200**                 |
| Above 960       | 3                 | 500                   |

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.



Report No. : KES-RF240513

**Duty cycle**


Regarding to KDB 558074 D01\_v05 r02, 6. Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on- and off-times of the transmitted signal.
- The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on- and off-times of the transmitted signal.

| Mode | T <sub>on</sub> time (ms) | Period (ms) | Duty cycle (Linear) | Duty cycle (%) | Duty cycle correction factor (dB) |
|------|---------------------------|-------------|---------------------|----------------|-----------------------------------|
| TX   | 13.02                     | 56.54       | 0.23                | 23.03          | 6.38                              |

Duty cycle (Linear) = T<sub>on</sub> time/Period

DCF(Duty cycle correction factor (dB)) = 10log(1/duty cycle)






### Test results (Below 30 MHz)

Distance of measurement: 3 meter

Channel: 00 (Worst case)




Note.

1. No spurious emission were detected under 30 MHz, above data is peak result.

**Test results (Below 1 000 MHz)**

Distance of measurement: 3 meter

Channel: 00 (Worst case)

**Horizontal // Vertical****Final Result**

| No. | Frequency<br>[MHz] | Pol | Reading<br>QP<br>[dB(μV)] | c.f<br>[dB(1/m)] | Result<br>QP<br>[dB(μV/m)] | Limit<br>QP<br>[dB(μV/m)] | Margin<br>QP<br>[dB] | Height<br>[cm] | Angle<br>[deg] | Remark |
|-----|--------------------|-----|---------------------------|------------------|----------------------------|---------------------------|----------------------|----------------|----------------|--------|
| 1   | 288.020            | H   | 29.6                      | -11.1            | 18.5                       | 46.0                      | 27.5                 | 100.0          | 203.3          |        |
| 2   | 416.060            | H   | 29.3                      | -8.2             | 21.1                       | 46.0                      | 24.9                 | 121.0          | 223.6          |        |
| 3   | 499.965            | V   | 26.7                      | -6.3             | 20.4                       | 46.0                      | 25.6                 | 382.0          | 0.5            |        |
| 4   | 650.315            | V   | 26.9                      | -3.7             | 23.2                       | 46.0                      | 22.8                 | 153.0          | 359.0          |        |
| 5   | 717.488            | V   | 26.9                      | -2.6             | 24.3                       | 46.0                      | 21.7                 | 100.0          | 66.3           |        |
| 6   | 745.496            | H   | 27.3                      | -1.7             | 25.6                       | 46.0                      | 20.4                 | 107.0          | 7.5            |        |
| 7   | 757.621            | V   | 27.0                      | -1.5             | 25.5                       | 46.0                      | 20.5                 | 142.0          | 229.8          |        |
| 8   | 806.243            | H   | 30.3                      | -1.2             | 29.1                       | 46.0                      | 16.9                 | 105.0          | 92.6           |        |
| 9   | 870.263            | H   | 32.1                      | 0.2              | 32.3                       | 46.0                      | 13.7                 | 104.0          | 29.6           |        |
| 10  | 875.355            | V   | 25.3                      | 0.4              | 25.7                       | 46.0                      | 20.3                 | 157.0          | 338.3          |        |
| 11  | 902.273            | H   | -----                     | 1.0              | -----                      | -----                     | -----                | 99.8           | 359.0          |        |
| 12  | 902.273            | V   | -----                     | 1.0              | -----                      | -----                     | -----                | 149.8          | 338.3          |        |
| 13  | 934.283            | H   | 35.7                      | 1.4              | 37.1                       | 46.0                      | 8.9                  | 110.0          | 180.7          |        |
| 14  | 934.283            | V   | 29.5                      | 1.4              | 30.9                       | 46.0                      | 15.1                 | 144.0          | 333.5          |        |


**Test results (Above 1 000 MHz)**

Distance of measurement: 3 meter

Channel: 00

**- Spurious**

| Frequency (MHz) | Level (dBμV) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|--------------|-------------|-----------------|---------|----------|-------------------------|----------------|-------------|
| 1 804.42        | 53.25        | Peak        | H               | -3.74   | -        | 49.51                   | 74.00          | 24.49       |
| 1 804.42        | 56.32        | Peak        | V               | -3.74   | -        | 52.58                   | 74.00          | 21.42       |



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




Distance of measurement: 3 meter

Channel: 01

**- Spurious**

| Frequency (MHz) | Level (dB $\mu$ V) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
|-----------------|--------------------|-------------|-----------------|---------|----------|-------------------------------|----------------------|-------------|
| 1 830.22        | 59.34              | Peak        | H               | -3.48   | -        | 55.86                         | 74.00                | 18.14       |
| 1 830.22        | 46.35              | Average     | H               | -3.48   | 6.38     | 49.25                         | 54.00                | 4.75        |
| 1 830.22        | 57.24              | Peak        | V               | -3.48   | -        | 53.76                         | 74.00                | 20.24       |
| 2 745.13        | 44.58              | Peak        | V               | 0.14    | -        | 44.72                         | 74.00                | 29.28       |



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




Report No. : KES-RF240513

Distance of measurement: 3 meter

Channel: 02

## - Spurious

| Frequency (MHz) | Level (dBμV) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|--------------|-------------|-----------------|---------|----------|-------------------------|----------------|-------------|
| 1 855.41        | 49.90        | Peak        | H               | -3.22   | -        | 46.68                   | 74.00          | 27.32       |
| 1 855.41        | 56.23        | Peak        | V               | -3.22   | -        | 53.01                   | 74.00          | 20.99       |




Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Test results (18 GHz to 30 GHz) – Worst case

Distance of measurement: 3 meter  
Channel: 00 (Worst case)




Note.

- 1. No spurious emission were detected above 18 GHz.



### 3.5. Conducted spurious emissions & band edge

#### Test setup



#### Test procedure

##### Band edge

ANSI C63.10-2013 - Section 11.11

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Set the RBW = 100 kHz
4. Set the VBW =  $[3 \times \text{RBW}]$ .
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow trace to fully stabilize.

##### Out of band emissions

ANSI C63.10-2013 - Section 11.11


1. Start frequency was set to 30 MHz and stop frequency was set to 25 GHz for 2.4 GHz frequencies and 40 GHz for 5 GHz frequencies
2. Set the RBW = 100 kHz
3. Set the VBW =  $[3 \times \text{RBW}]$ .
4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Allow trace to fully stabilize.


#### Limit

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))



## Test results







### 3.6. AC conducted emissions


#### Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.


| Frequency of Emission (MHz) | Conducted limit (dB $\mu$ V) |          |
|-----------------------------|------------------------------|----------|
|                             | Quasi-peak                   | Average  |
| 0.15 – 0.50                 | 66 - 56*                     | 56 - 46* |
| 0.50 – 5.00                 | 56                           | 46       |
| 5.00 – 30.0                 | 60                           | 50       |

**Test results**

Channel: 00 (Worst case)

**Hot Line****Final Result**

| Frequency (MHz) | QuasiPeak (dBμV) | CAverage (dBμV) | Limit (dBμV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|------|------------|
| 0.586000        | 35.85            | ---             | 73.00        | 37.15       | 1000.0          | 9.000           | L1   | 19.7       |
| 0.586000        | ---              | 30.70           | 60.00        | 29.30       | 1000.0          | 9.000           | L1   | 19.7       |
| 0.590000        | 36.09            | ---             | 73.00        | 36.91       | 1000.0          | 9.000           | L1   | 19.7       |
| 0.590000        | ---              | 30.97           | 60.00        | 29.03       | 1000.0          | 9.000           | L1   | 19.7       |
| 0.882000        | 29.39            | ---             | 73.00        | 43.61       | 1000.0          | 9.000           | L1   | 19.8       |
| 0.882000        | ---              | 23.13           | 60.00        | 36.87       | 1000.0          | 9.000           | L1   | 19.8       |
| 1.378000        | ---              | 22.65           | 60.00        | 37.35       | 1000.0          | 9.000           | L1   | 19.8       |
| 1.378000        | 27.61            | ---             | 73.00        | 45.39       | 1000.0          | 9.000           | L1   | 19.8       |
| 5.242000        | ---              | 20.32           | 60.00        | 39.68       | 1000.0          | 9.000           | L1   | 20.2       |
| 5.242000        | 23.87            | ---             | 73.00        | 49.13       | 1000.0          | 9.000           | L1   | 20.2       |
| 5.266000        | ---              | 20.12           | 60.00        | 39.88       | 1000.0          | 9.000           | L1   | 20.2       |
| 5.266000        | 23.81            | ---             | 73.00        | 49.19       | 1000.0          | 9.000           | L1   | 20.2       |

**Neutral Line****Final Result**

| Frequency (MHz) | QuasiPeak (dBμV) | CAverage (dBμV) | Limit (dBμV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|------|------------|
| 0.594000        | 27.64            | ---             | 73.00        | 45.36       | 1000.0          | 9.000           | N    | 19.8       |
| 0.594000        | ---              | 18.54           | 60.00        | 41.46       | 1000.0          | 9.000           | N    | 19.8       |
| 0.886000        | 18.92            | ---             | 73.00        | 54.08       | 1000.0          | 9.000           | N    | 19.8       |
| 0.886000        | ---              | 11.30           | 60.00        | 48.70       | 1000.0          | 9.000           | N    | 19.8       |
| 1.078000        | 18.54            | ---             | 73.00        | 54.46       | 1000.0          | 9.000           | N    | 19.8       |
| 1.078000        | ---              | 12.46           | 60.00        | 47.54       | 1000.0          | 9.000           | N    | 19.8       |
| 2.058000        | ---              | 10.54           | 60.00        | 49.46       | 1000.0          | 9.000           | N    | 19.9       |
| 2.038000        | 17.21            | ---             | 73.00        | 55.79       | 1000.0          | 9.000           | N    | 19.9       |
| 5.814000        | ---              | 11.56           | 60.00        | 48.44       | 1000.0          | 9.000           | N    | 20.3       |
| 5.814000        | 15.91            | ---             | 73.00        | 57.09       | 1000.0          | 9.000           | N    | 20.3       |
| 15.930000       | ---              | 13.51           | 60.00        | 46.49       | 1000.0          | 9.000           | N    | 21.0       |
| 15.930000       | 17.24            | ---             | 73.00        | 55.76       | 1000.0          | 9.000           | N    | 21.0       |



### 3.7. Antenna Requirement

According to 15.207(a), An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

**Appendix A. Measurement equipment**

| Equipment                | Manufacturer      | Model         | Serial No.   | Calibration interval | Calibration due. |
|--------------------------|-------------------|---------------|--------------|----------------------|------------------|
| Spectrum analyzer        | R&S               | FSV40         | 101725       | 1 year               | 2025.06.12       |
| Spectrum analyzer        | R&S               | FSV3044       | 101272       | 1 year               | 2025.03.12       |
| SIGNAL GENERATOR         | KEYSIGHT          | N5182B        | MY59100115   | 1 year               | 2025.04.15       |
| SIGNAL GENERATOR         | Anritsu           | 68369B        | 002118       | 1 year               | 2025.04.15       |
| Power Meter              | Anritsu           | ML2495A       | 2010001      | 1 year               | 2025.04.15       |
| Pulse Power Sensor       | Anritsu           | MA2411B       | 1911111      | 1 year               | 2025.04.15       |
| Attenuator               | Mini-Circuits     | BW-S10-2W263+ | 3            | 1 year               | 2025.01.15       |
| ACTIVE LOOP ANTENNA      | SCHWARZBECK       | FMZB 1513     | 1513-257     | 2 years              | 2025.11.16       |
| TRILOG-BROADBAND ANTENNA | Schwarzbeck       | VULB 9163     | 714          | 2 years              | 2026.04.19       |
| Attenuator               | HUBER+SHHNER      | 6806.17.A     | NONE         | 1 year               | 2025.02.13       |
| Horn Antenna             | A.H.              | SAS-571       | 414          | 1 year               | 2025.01.16       |
| Horn Antenna             | SCHWARZBECK       | BBHA9170      | BBHA 9170550 | 1 year               | 2025.01.16       |
| Amplifier                | SONOMA INSTRUMENT | 310N          | 401123       | 1 year               | 2025.02.13       |
| PREAMPLIFIER             | HP                | 8449B         | 3008A00538   | 1 year               | 2025.04.30       |
| BROADBAND AMPLIFIER      | SCHWARZBECK       | BBV9721       | PS9721-003   | 1 year               | 2025.01.15       |
| DC POWER SUPPLY          | AGILENT           | 6632B         | MY43004090   | 1 year               | 2025.06.17       |
| EMI Test Receiver        | R&S               | ESU26         | 100552       | 1 year               | 2025.02.13       |
| EMI Test Receiver        | R&S               | ESR3          | 101783       | 1 year               | 2024.11.08       |
| PULSE LIMITER            | R&S               | ESH2-Z2       | 101915       | 1 year               | 2024.11.08       |
| LISN                     | R&S               | ENV216        | 101787       | 1 year               | 2024.11.08       |

\* Statement of Traceability: KES Co., Ltd. attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Peripheral devices**

| Device            | Manufacturer         | Model No. | Serial No.    |
|-------------------|----------------------|-----------|---------------|
| Notebook computer | LG Electronics Inc., | LGS53     | 306QCZP560949 |
| Test Jig Board    | N/A                  | N/A       | N/A           |

**The end of test report.**