FCC TEST REPORT

FCC ID: 2BDLV-RSKUSU024

On Behalf of

Valor Communication, Inc.

Wireless Bluetooth Speaker

Model No.: TT-RSKUSU024, TT-RSKUSU024A, TT-RSKUSU024B, TT-RSKUSU024R, TT-RSKUSU024W, TT-RSKUSU028A, TT-RSKUSU028B, TT-RSKUSU029B, TT-RSKUSU029W, TT-RSKUSU027B, TT-RSKUSU027R, TT-RSKUSU035B, TT-RSKUSU035W, TT-RSKUSU030A, TT-RSKUSU030B, TT-RSKUSU030R, TT-RSKUSU030W, TT-RSKUSU901A, TT-RSKUSU901B, TT-RSKUSU901R, TT-RSKUSU901W, TT-RSKUSU902A, TT-RSKUSU902B, TT-RSKUSU902R, TT-RSKUSU902W, TT-RSKUSU903A, TT-RSKUSU903B, TT-RSKUSU903R, TT-RSKUSU903W, TT-RSKUSU904A, TT-RSKUSU904B, TT-RSKUSU904R, TT-RSKUSU904W

Prepared for	:	Valor Communication, Inc.
Address	:	Valor Communication 18071 Arenth Ave.,City of Industry, CA 91748

Prepared By	:	Shenzhen PSI Testing Co., Ltd.
Address	:	1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Report Number	:	psi2311008-C01-R01
Date of Receipt	:	November 03, 2023
Date of Test	:	November 03-09, 2023
Date of Report	:	November 10, 2023
Version Number	:	V0

TABLE OF CONTENTS

Description Page

1. Summary Of Standards And Results ---------- 6
1.1. Description of Standards and Results ---------- 6
2. General Information ---------- 7
2.1. Description of Device (EUT) ---------- 7
2.2. Accessories of Device (EUT) ---------- 8
2.3. Tested Supporting System Details ---------- 8
2.4. Block Diagram of Connection Between EUT and Simulators ---------- 8
2.5. Test Mode Description ---------- 9
2.6. Test Conditions ---------- 10
2.7. Test Facility ---------- 10
2.8. Measurement Uncertainty ---------- 10
2.9. Test Equipment List ---------- 11
3. Spurious Emission ---------- 12
3.1. Test Limits ---------- 12
3.2. Block Diagram of Test setup ---------- 13
3.3. Test Procedure ---------- 14
3.4. Test Results ---------- 15
4. Power Line Conducted Emission ---------- 21
4.1. Test Limits ---------- 21
4.2. Test Procedure ---------- 21
4.3. Test Setup ---------- 21
4.4. Test Results ---------- 22
5. Out-of-band Emissions ---------- 25
5.1. Test Limits ---------- 25
5.2. Test Procedure ---------- 25
5.3. Test Setup ---------- 25
5.4. Test Results ---------- 25
6. Conducted Maximum Output Power ---------- 28
6.1. Test limits ---------- 28
6.2. Test Procedure ---------- 28
6.3. Test Setup ---------- 28
6.4. Test Results ---------- 28
7. Peak Power Spectral Density ---------- 29
7.1. Test limits ---------- 29
7.2. Test Procedure ---------- 29
7.3. Test Setup ---------- 29
7.4. Test Results ---------- 30
8. Bandwidth ---------- 33
8.1. Test limits ---------- 33
8.2. Test Procedure ---------- 33
8.3. Test Setup ---------- 33
8.4. Test Results ---------- 33
9. Band Edge Test ---------- 36

9.1. Block Diagram of Test Setup ---------- 36
9.2. Test Limit ---------- 36
9.3. Test Procedure ---------- 36
9.4. Test Results ---------- 37
10. Antenna Requirement ---------- 38
10.1. Standard Requirement ---------- 38
10.2. Antenna Connected Construction ---------- 38
10.3. Results ---------- 38
11. Photos of test setup ---------- 39
12. Photos of EUT ---------- 39

TEST REPORT DECLARATION

Applicant	:	Valor Communication, Inc.
Address	:	Valor Communication 18071 Arenth Ave.,City of Industry, CA 91748
Manufacturer	:	Shen Zhen Mopoint Technology Co.,LTD
Address	:	8202, Jiangzao Digital Industrial Park, NO.1195 Liuxian Boulevard, Pingshan Community, Taoyuan St., Nanshan District Shenzhen, Guangdong
EUT Description	:	Wireless Bluetooth Speaker
		(A) Model No. : TT-RSKUSU024, more information see page 7.
		(B) Trademark : **MYBAT PRO**

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247,

ANSI C63.10-2013

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part15 requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....:	Jensen Wang Project Engineer	Jensen Wang
Approved by (name + signature)…....:	Simple Guan Project Manager	
Date of issue…… ……..:	November 10, 2023	

Revision History

Revision	Issue Date	Revisions	Revised By
V0	November 10, 2023	Initial released Issue	Jensen Wang

1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Radiated Spurious Emission	FCC Part 15: 15.209 FCC Part 15: 15.205	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d)	P
Power Line Conducted Emissions	FCC Part 15: 15.207	P
6dB Bandwidth	FCC PART 15:15.247(a)(2)	P
Output Power	FCC Part 15: 15.247(b)(3)	P
Out-of-band Emissions	FCC Part 15: 15.247(d)	P
Power Spectral Density	FCC PART 15:15.247(e)	P
Antenna Requirement	FCC Part 15: 15.203	P
Note:	1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable. 4. Conclusion determination rules of this report: Unless there are clear provisions on measurement uncertainty in the standard or customer requirements, decision by actual test data without considering measurement uncertainty.	

2. General Information

2.1. Description of Device (EUT)

Product Name	:	Wireless Bluetooth Speaker
Trademark	:	N/A
Model Number	:	TT-RSKUSU024, TT-RSKUSU024A, TT-RSKUSU024B, TT-RSKUSU024R, TT-RSKUSU024W, TT-RSKUSU028A, TT-RSKUSU028B, TT-RSKUSU029B, TT-RSKUSU029W, TT-RSKUSU027B, TT-RSKUSU027R, TT-RSKUSU035B, TT-RSKUSU035W, TT-RSKUSU030A, TT-RSKUSU030B, TT-RSKUSU030R, TT-RSKUSU030W, TT-RSKUSU901A, TT-RSKUSU901B, TT-RSKUSU901R, TT-RSKUSU901W, TT-RSKUSU902A, TT-RSKUSU902B, TT-RSKUSU902R, TT-RSKUSU902W, TT-RSKUSU903A, TT-RSKUSU903B, TT-RSKUSU903R, TT-RSKUSU903W, TT-RSKUSU904A, TT-RSKUSU904B, TT-RSKUSU904R, TT-RSKUSU904W
Diff	:	There is no difference between the except for different names of sales regions. Each model comes in four colors, So all the test were performed on the black model TT-RSKUSU024.
Trademark	:	**MYBAT PRO**
Power supply	:	DC 3.7V from battery OR DC 5V from USB port
Radio Technology	:	Bluetooth 5.0 BLE
Operation frequency	:	2402MHz-2480MHz
Modulation type	:	GFSK
Operation Frequency	:	2402MHz-2480MHz
Channel No.	:	40 Channels
Antenna Type	:	PCB Antenna, max gain 1.68dBi.
Software version	:	V1.0
Hardware version/FVIN	:	V1.0
Intend use environment	:	Residential, commercial and light industrial environment
Note	:	Antenna information is provided by applicant. Testing lab is not responsible for the accuracy of the information. The worst-case simultaneous transmission configuration was evaluated with no non-compliance found. Results in this report are only for Bluetooth 5.0 BLE function, and there is no other transmitter involved.

2.2. Accessories of Device (EUT)

Accessories1 : /

Manufacturer : /

Model : /

Ratings : /

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1	Adapter	RUIDIR	Q2W24-1U-C	N/A
2	/	/	/	/
3	/	/	/	/
4	/	/	/	/

2.4. Block Diagram of Connection Between EUT and Simulators



Signal Cable Description of the above Support Units

No.	Port Name	Cable	Length	Shielded (Yes or No)	Detachable (Yes or No)
(a)	/	/	/	/	/

2.5. Test Mode Description

The test software “RFTestTool.app” was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
GFSK Tx Mode	CH0	2402
	CH19	2440
	CH39	2480

Channel list:					
Channel	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**
CH0	2402	CH14	2430	CH28	2458
CH1	2404	CH15	2432	CH29	2460
CH2	2406	CH16	2434	CH30	2462
CH3	2408	CH17	2436	CH31	2464
CH4	2410	CH18	2438	CH32	2466
CH5	2412	CH19	2440	CH33	2468
CH6	2414	CH20	2442	CH34	2470
CH7	2416	CH21	2444	CH35	2472
CH8	2418	CH22	2446	CH36	2474
CH9	2420	CH23	2448	CH37	2476
CH10	2422	CH24	2450	CH38	2478
CH11	2424	CH25	2452	CH39	2480
CH12	2426	CH26	2454	--	--
CH13	2428	CH27	2456	--	--

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	24℃
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

September 13, 2023 File on Federal Communication Commission
Registration Number: 916281

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	**Uncertainty**
Uncertainty for Power point Conducted Emissions Test	2.17dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	2.74dB(Polarize: V)
	2.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 18GHz)	4.29dB(Polarize: V)
	4.82dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	48.24KHz
Uncertainty for conducted RF Power	0.41dB
Uncertainty for Power Spectral Density	0.39 dB

2.9. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2022.12.20	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2022.12.30	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV216	102282	/	2022.12.30	1 Year
4.	L.I.S.N.#2	RFT	NNB111	13835240	/	2023.05.04	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2023.04.03	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2022.12.26	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2022.12.30	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2022.12.26	2 Year
9.	Amplifier	SKET	LAPA_01G18G-45dB	SK2022032901	/	2022.12.29	1 Yea
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2022.12.25	2 Year
11.	Amplifier	SKET	LNPA_0118G-45	SK2020010801	/	2022.12.30	1 Yea
12	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02-1111533-Fz	/	2023.03.30	1 Yea

For Test Software Information

Item	Software Name	Manufacturer	Version
RE	EMC-I	SKET	V1.5.0.3
CE	EMC-I	SKET	V1.5.0.3
RF	RTS	TACHOY	V1.0.0

3. Spurious Emission

3.1. Test Limits

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	
Note 1: The peak limit is 20 dB higher than the average limit			

3.2. Block Diagram of Test setup

3.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



3.2.2 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



3.2.3 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



3.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
(2) Setup EUT and simulator
(3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
(a) Change work frequency or channel of device if practicable.
(b) Change modulation type of device if practicable.
(c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
(4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
(5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on Radiated Emission test.
(6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.
Test setup information:

9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHZ~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

3.4. Test Results

We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.
Detailed information please see the following page.

From 9KHz to 30MHz:					
Test Date	:	2023.11.07	Temperature	:	24℃
Test Engineer	:	Jensen Wang	Humidity	:	56%
Test Mode	:	GFSK mode			
Test Results	:	**PASS**			
Note:	The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.				

From 30MHz to 1000MHz:					
Test Date	:	2023.11.07	Temperature	:	24℃
Test Engineer	:	Jensen Wang	Humidity	:	56%
Test Mode	:	GFSK mode			
Test Results	:	**PASS**			
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of BT Link mode, BT Link mode (AC 120V/ 60Hz) was listed in this report.				

Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36.4612	13.12	13.13	26.25	40.00	-13.75	peak
2	71.9896	13.01	10.57	23.58	40.00	-16.42	peak
3	127.9446	21.76	12.02	33.78	43.50	-9.72	peak
4	168.0451	20.79	12.47	33.26	43.50	-10.24	peak
5	276.0026	19.09	13.15	32.24	46.00	-13.76	peak
6 *	512.0596	17.98	18.58	36.56	46.00	-9.44	peak

Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	127.9446	17.56	12.02	29.58	43.50	-13.92	peak
2	156.0468	14.67	13.17	27.84	43.50	-15.66	peak
3	239.9873	19.31	11.98	31.29	46.00	-14.71	peak
4	276.0026	18.71	13.15	31.86	46.00	-14.14	peak
5	587.6159	11.08	20.40	31.48	46.00	-14.52	peak
6 *	953.3465	12.62	25.18	37.80	46.00	-8.20	peak

From 1GHz to 25GHz:					
Test Date	:	2023.11.07	Temperature	:	24℃
Test Engineer	:	Jensen Wang	Humidity	:	56%
Test Mode	:	GFSK mode			
Test Results	:	**PASS**			
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.				

Test Mode : GFSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	81.64	-27.27	54.37	74.00	-19.63	Peak
2	4804	V	72.58	-27.27	45.31	54.00	-8.69	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	81.61	-27.27	54.34	74.00	-19.66	Peak
6	4804	H	68.46	-27.27	41.19	54.00	-12.81	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : GFSK TX Mid								
1	4880	V	84.31	-27.79	56.52	74.00	-17.48	Peak
2	4880	V	72.02	-27.79	44.23	54.00	-9.77	Avg
3	7320	--	--	--	--	--	--	--
4	9760	--	--	--	--	--	--	--
5	4880	H	80.53	-27.79	52.74	74.00	-21.26	Peak
6	4880	H	70.03	-27.79	42.24	54.00	-11.76	Avg
7	7320	--	--	--	--	--	--	--
8	9760	--	--	--	--	--	--	--
Test Mode : GFSK TX High								
1	4960	V	80.26	-28.30	51.96	74.00	-22.04	Peak
2	4960	V	70.59	-28.30	42.29	54.00	-11.71	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	85.61	-28.30	57.31	74.00	-16.69	Peak
6	4960	H	68.71	-28.30	40.41	54.00	-13.59	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--

Note:
1. Means other frequency and mode comply with standard requirements and at least have 20dB margin.
2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain.
Result=Reading + Correct Factor.
Margin= Result-Limit.

4. Power Line Conducted Emission

4.1. Test Limits

Frequency	Limits dB(μV)	
MHz	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.
3.The limit decreases in line with the logarithm of the frequency in the rang of 0.15 to 0.50 MHz.

4.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs.
Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement.
The bandwidth of test receiver is set at 9 kHz.

4.3. Test Setup



4.4. Test Results

Test Date	:	2023.11.07	Temperature	:	24℃
Test Engineer	:	Jensen Wang	Humidity	:	56%
Test Mode	:	GFSK mode			
Test Results	:	**PASS**			
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out. 4. All modes have been tested, and only worst data of BT Link mode, BT Link mode (AC 120V/ 60Hz) was listed in this report.				

Polarization: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1539	35.65	9.94	45.59	65.79	-20.20	peak	P
2	0.1539	23.05	9.94	32.99	55.79	-22.80	AVG	P
3	0.1860	35.42	9.95	45.37	64.21	-18.84	peak	P
4	0.1860	22.16	9.95	32.11	54.21	-22.10	AVG	P
5	0.2060	34.62	9.95	44.57	63.37	-18.80	peak	P
6	0.2060	22.46	9.95	32.41	53.37	-20.96	AVG	P
7	0.2620	33.32	9.97	43.29	61.37	-18.08	peak	P
8	0.2620	20.47	9.97	30.44	51.37	-20.93	AVG	P
9	0.3780	31.38	9.70	41.08	58.32	-17.24	peak	P
10	0.3780	18.93	9.70	28.63	48.32	-19.69	AVG	P
11 *	0.5299	30.62	9.84	40.46	56.00	-15.54	peak	P
12	0.5299	20.05	9.84	29.89	46.00	-16.11	AVG	P

Polarization: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1819	35.76	9.95	45.71	64.40	-18.69	peak	P
2	0.1819	22.37	9.95	32.32	54.40	-22.08	AVG	P
3	0.2220	34.29	9.99	44.28	62.74	-18.46	peak	P
4	0.2220	22.09	9.99	32.08	52.74	-20.66	AVG	P
5	0.2980	32.55	9.78	42.33	60.30	-17.97	peak	P
6	0.2980	20.81	9.78	30.59	50.30	-19.71	AVG	P
7	0.4260	31.82	9.61	41.43	57.33	-15.90	peak	P
8	0.4260	19.61	9.61	29.22	47.33	-18.11	AVG	P
9	0.5260	30.18	9.78	39.96	56.00	-16.04	peak	P
10	0.5260	20.35	9.78	30.13	46.00	-15.87	AVG	P
11 *	0.6460	30.62	9.78	40.40	56.00	-15.60	peak	P
12	0.6460	20.00	9.78	29.78	46.00	-16.22	AVG	P

5. Out-of-band Emissions

5.1. Test Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in FCC Part15.209(a) is not required.

5.2. Test Procedure

Connect the transmitter ouput to spectrum analvzer using a low loss RF cable, and set the spectrum analvzerto RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these setting aremade of the in-band reference level, bandedge and out-of-band emissions.

5.3. Test Setup



5.4. Test Results

PASS.

The test results are listed in next pages.

For Band Edge:



GFSK 2402MHz



GFSK 2480MHz

For Connected Spurious Emission:

GFSK 2402MHz



GFSK 2440MHz



GFSK 2480MHz

6. Conducted Maximum Output Power

6.1. Test limits

Please refer RSS-247 & FCC PART 15: 15.247.

Regulation 15.247(b) The limit of Maximum Peak Output Power Measurement is 1 W(30dBm)

6.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

5.2.1 Place the EUT on the table and set it in transmitting mode.

5.2.2 Connected the EUT's antenna port to peak power meter by 20dB attenuator.

5.2.3 Measure out each mode and each bands AVG output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

6.3. Test Setup



6.4. Test Results

Mode	Frequency (MHz)	PK Output power(dBm)	Limit (dBm)	Result
GFSK	CH0: 2402	**1.29**	30	PASS
	CH19: 2440	1.11	30	PASS
	CH39: 2480	0.63	30	PASS

7. Peak Power Spectral Density

7.1. Test limits

6.1.1 Please refer RSS-247 & FCC PART 15: 15.247.

6.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

6.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

7.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

6.2.1 Place the EUT on the table and set it in transmitting mode.

6.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

6.2.3 Set the spectrum analyzer as RBW = 100kHz(Set the RBW to: 3 kHz≤RBW≤100 kHz.), VBW = 300kHz(Set the VBW≥3×RBW), span≥1.5×DTS bandwidth., detail see the test plot.

6.2.4 Record the max reading.

6.2.5 Repeat the above procedure until the measurements for all frequencies are completed.

7.3. Test Setup



7.4. Test Results

Mode	Frequency (MHz)	Max PSD (dBm/3K)	Limit (dBm/3K)	Result
GFSK	CH0: 2402	-18.64	8	PASS
	CH19: 2440	-19.29	8	PASS
	CH39: 2480	-20.00	8	PASS



GFSK 2402MHz

GFSK 2440MHz

GFSK 2480MHz

8. Bandwidth

8.1. Test limits

Please refer RSS-247 & FCC PART 15: 15.247
For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.

8.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

a) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

b) The test receiver set RBW = 100kHz, VBW≥3*RBW =300kHz,, Peak Detector, Sweep time set auto, detail see the test plot.

8.3. Test Setup



8.4. Test Results

Mode	Frequency (MHz)	-6 dB Bandwidth (KHz)	Limit -6 dB Bandwidth (KHz)	Result
GFSK	CH0: 2402	503.02	500	PASS
	CH19: 2440	516.53	500	PASS
	CH39: 2480	528.40	500	PASS



GFSK 2402MHz



GFSK 2440MHz



GFSK 2480MHz

9. Band Edge Test

9.1. Block Diagram of Test Setup



9.2. Test Limit

Please refer section15.247 and section 15.209.
All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in FCC part 15.209 and RSS-GEN, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with FCC part 15.209 and RSS-GEN limits.
All the lower and upper band-edges emissions appearing within 2310MHz to 24100MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz and 5725MHz to 5850MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.3. Test Procedure

Refer to ANSI C 63.10, Clause 6.10.
All restriction band and non- restriction band have been tested, only worse case is reported.
Details see the KDB558074 D01 Meas Guidance v05r02

8.2.1 Put the EUT on a 1.5m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission
8.2.2 Check the spurious emissions out of band.
8.2.3 RBW 1MHz, VBW 3MHz, peak detector for peak value , RBW 1MHz ,VBW 10Hz , RMS detector for AV value.

9.4. Test Results

Test Date	:	2023.11.07			Temperature	:	24℃	
Test Engineer	:	Jensen Wang			Humidity	:	56%	
Test Results	:	**PASS**						
Frequency Range	:	**2310MHz~2410MHz**						
Test Mode	:	GFSK TX 2402MHz						
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	72.61	-21.62	50.99	74.00	-23.01	Peak
2	2390	H	--	-21.62	--	54.00	--	Avg
3	2400	H	80.81	-26.08	54.73	74.00	-19.27	Peak
4	2400	H	--	-26.08	--	54.00	--	Avg
1	2390	V	71.58	-21.62	49.96	74.00	-24.04	Peak
2	2390	V	--	-21.62	--	54.00	--	Avg
3	2400	V	79.16	-26.08	53.08	74.00	-20.92	Peak
4	2400	V	--	-26.08	--	54.00	--	Avg
Frequency Range	:	**2450MHz~2550MHz**						
Test Mode	:	GFSK TX 2480MHz						
1	2483.5	H	78.41	-25.84	52.57	74.00	-21.43	Peak
2	2483.5	H	--	-25.84	--	54.00	--	Avg
1	2483.5	V	77.50	-25.84	51.66	74.00	-22.34	Peak
2	2483.5	V	--	-25.84	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 5. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

10. Antenna Requirement

10.1.Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2.Antenna Connected Construction

The antenna connector is unique antenna and no consideration of replacement. Please see EUT photo for details.

10.3.Results

The EUT antenna is PCB Antenna. It complies with the standard requirement.

11. Photos of test setup

Reference to the **appendix I Test Setup Photo** for details.

12. Photos of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

------ END OF REPORT------

Appendix I Test Setup Photo



Spurious Radiation Emissions Test (<1G)

Spurious Radiation Emissions Test (>1G)

Conducted emission Test

------End------

Appendix II external photos





------End------

Appendix III internal photos







Antenna Location



------End------