



RF Exposure Evaluation Report

Application No.: DNT2606083515R06839-09407
Applicant: ATEK TECHNOLOGY CORP.
Address of Applicant: No. 109-1, 11th Neighborhood, Dingpu Vil., Zhunan Township, Miaoli County 35053, Taiwan
EUT Description: Portable Electronic Wine Chiller
Model No.: VENUS-G2
Additional Model(s): N/A
FCC ID: 2BDM9-VENUS-G2
Power supply DC 21.2V From Adapter Input AC 120V/60Hz;DC 18V From Battery
Trade Mark: VIVANT
47 CFR Part 2.1091
Standards: FCC KDB 447498 D01 v06
Date of Receipt: 2026/06/08
Date of Test: 2026/06/09 to 2026/06/27
Date of Issue: 2026/06/29
Test Result: **PASS**

Prepared By: Chia-Lin (Testing Engineer)
Reviewed By: Wayne Lin (Project Engineer)
Approved By: Heise Shen (Manager)



Note: If there is any objection to the results in this report, please submit a written inquiry to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp, and is issued by the company in accordance with the requirements of the "Conditions of Issuance of Test Reports" printed in the attached page. Unless otherwise stated, the results presented in this report only apply to the samples tested this time. Partial reproduction of this report is not allowed unless approved by the company in writing.

GuangDong DN Testing Co., Ltd.

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang 'an Town, Dongguan City, Guangdong P.R.China

Web: www.dn-testing.com

Tel: +86-769-88087383

E-mail: service@dn-testing.com



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	June 29, 2026	Valid	Original Report



Contents

1 GENERAL INFORMATION4

1.1 TEST LOCATION4

1.2 GENERAL DESCRIPTION OF EUT4

2 RF EXPOSURE EVALUATION5

2.1 RF EXPOSURE COMPLIANCE REQUIREMENT5

2.1.1 Limits5

2.1.2 Test Procedure6

2.1.3 EUT RF Exposure Evaluation6



1 General Information

1.1 Test Location

Company:	GuangDong DN Testing Co., Ltd
Address:	No. 1, West Fourth Street, South Xinfu Road, Wusha Liwu, Chang 'an Town, Dongguan City, Guangdong P.R.China
Test engineer:	Gali Lin

1.2 General Description of EUT

Manufacturer:	ATEK TECHNOLOGY CORP.
Address of Manufacturer:	No. 109-1, 11th Neighborhood, Dingpu Vil., Zhunan Township, Miaoli County 35053, Taiwan
EUT Description:	Portable Electronic Wine Chiller
Model No.:	VENUS-G2
Additional Model(s):	N/A
Power Supply:	DC 21.2V From Adapter Input AC 120V/60Hz;DC 18V From Battery
Trade Mark:	VIVANT
Hardware Version:	V1.0
Software Version:	V1.0
Serial number	PR2606083515R06839
Sample Type:	☐ Portable Device, ☐ Module, ☒ Mobile Device
Antenna Type:	☐ External, ☒ Integrated
Antenna Ports:	☒ Ant 1, ☐ Ant 2, ☐ Ant 3
Antenna Gain:	☒ Provided by applicant 1.01dBi
Note: *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, DNT is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.	



2 RF Exposure Evaluation

2.1 RF Exposure Compliance Requirement

2.1.1 Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30
F=frequency in MHz *=Plane-wave equivalent power density RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).				

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

**2.1.2 Test Procedure**

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

2.1.3 EUT RF Exposure Evaluation

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.0 / 2.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

This confirmed that the device comply with MPE limit.

Test Mode	Antenna	Freq(MHz)	Power[dBm]
BLE_1M	Ant1	2402	1.73
		2440	2.87
		2480	2.74

Test Mode	Antenna	Frequency[MHz]	Result [dBm]
11b	Ant1	2412	19.24
		2437	19.92
		2462	19.98
11g	Ant1	2412	23.34
		2437	23.35
		2462	23.45
11n HT 20	Ant1	2412	19.77
		2437	20.34
		2462	20.65
11n HT40	Ant1	2422	18.68
		2437	18.9
		2452	19.43

The Worst Mode	Antenna	output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result	Distance (cm)
					(dBi)	(Linear)				
BLE_1M	Ant1	2.87	2±1	3	1.01	1.262	0.0005	1	Complies	20
11g	Ant1	23.45	23±1	24	1.01	1.262	0.0631	1	Complies	20

The result less than 1, so complies

This confirmed that the device comply with MPE limit.

The End Report