



Test Report

Report No. : MTi260420016-0305E2
Date of Issue : 2026-06-05
Applicant : Dongguan Chuangjie Electronics Co., Ltd.
Product : 3 in 1 Wireless Charger
Model(s) : A07
FCC ID : 2BDOG-A07

Shenzhen Microtest Co., Ltd.

Table of contents

1	General Description	4
1.1	Description of the EUT	4
1.2	Description of test modes	5
1.3	Description of support units	7
2	Measurement uncertainty	7
2.1	Test laboratory	8
3	Test facilities and accreditations	9
4	List of test equipment	9
5	Test result	10
5.2	Test setup	11
5.3	Test Procedures	11
5.4	Information of test equipment	12
5.5	Test results	13
	Photographs of the Test Setup	14
	Photographs of the EUT	15

Test Result Certification		
Applicant	Dongguan Chuangjie Electronics Co., Ltd.	
Applicant Address	No.8, Jinxing Road, Jinfenghuang Industrial District, Fenggang Town, Dongguan City, China.	
Manufacturer	Dongguan Chuangjie Electronics Co., Ltd.	
Manufacturer Address	No.8 Jinxing Road, Fenggang Town, Dongguan City, Guangdong Province	
Factory	Dongguan Chuangjie Electronics Co., Ltd.	
Factory Address	No.8 Jinxing Road, Fenggang Town, Dongguan City, Guangdong Province	
Product description		
Product name	3 in 1 Wireless Charger	
Trademark	N/A	
Model name	A07	
Series Model(s)	N/A	
Standards	FCC CFR 47 PART 1, § 1.1310 FCC CFR 47 Part 2.1091	
Test Method	KDB 680106 D01 Wireless Power Transfer v04	
Testing Information		
Date of test	2026-05-24 to 2026-06-04	
Test result	Pass	
Prepared by:	James Qin	
Reviewed by:	David Lee	
Approved by:	Lewis Lian	

1 General Description

1.1 Description of the EUT

Product name:	3 in 1 Wireless Charger
Model name:	A07
Series Model(s):	N/A
Model difference:	N/A
Electrical rating:	Input: 9V=3A Wireless Output Phone: 5W/ 7.5W/ 10W/ 15W Wireless Output Earphone: 5W Wireless Output Watch: 2.5W
Accessories:	N/A
Hardware version:	Mainboard: CJ-A07 Watch: CJ-A08
Software version:	Mainboard: CJ-A07 V1.0 Watch: CJ-A08 V1.0
Test sample(s) number:	MTi260420016-03-R001
RF specification:	
Operating frequency range:	Coil 1&2 (Phone): 115-205kHz Coil 3 (Earphone): 115-205kHz Coil 4 (Watch): 320-330kHz
Modulation type:	ASK
Antenna type:	Coil

1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode1	Wireless Output Phone(Coil1: 5W)+Earphone(5W)+Watch(2.5W)
Mode2	Wireless Output Phone(Coil1: 7.5W)+Earphone(5W)+Watch(2.5W)
Mode3	Wireless Output Phone(Coil1: 10W)+Earphone(5W)+Watch(2.5W)
Mode4	Wireless Output Phone(Coil1: 15W)+Earphone(5W)+Watch(2.5W)
Mode5	Wireless Output Phone(Coil2: 5W)+Earphone(5W)+Watch(2.5W)
Mode6	Wireless Output Phone(Coil2: 7.5W)+Earphone(5W)+Watch(2.5W)
Mode7	Wireless Output Phone(Coil2: 10W)+Earphone(5W)+Watch(2.5W)
Mode8	Wireless Output Phone(Coil2: 15W)+Earphone(5W)+Watch(2.5W)
Mode9	Wireless Output Phone(Coil1: 5W)+Earphone(5W)
Mode10	Wireless Output Phone(Coil1: 7.5W)+Earphone(5W)
Mode11	Wireless Output Phone(Coil1: 10W)+Earphone(5W)
Mode12	Wireless Output Phone(Coil1: 15W)+Earphone(5W)
Mode13	Wireless Output Phone(Coil1: 5W)+Watch(2.5W)
Mode14	Wireless Output Phone(Coil1: 7.5W)+Watch(2.5W)
Mode15	Wireless Output Phone(Coil1: 10W)+Watch(2.5W)
Mode16	Wireless Output Phone(Coil1: 15W)+Watch(2.5W)
Mode17	Wireless Output Phone(Coil2: 5W)+Earphone(5W)
Mode18	Wireless Output Phone(Coil2: 7.5W)+Earphone(5W)
Mode19	Wireless Output Phone(Coil2: 10W)+Earphone(5W)
Mode20	Wireless Output Phone(Coil2: 15W)+Earphone(5W)
Mode21	Wireless Output Phone(Coil2: 5W) +Watch(2.5W)
Mode22	Wireless Output Phone(Coil2: 7.5W)+Watch(2.5W)
Mode23	Wireless Output Phone(Coil2: 10W)+Watch(2.5W)
Mode24	Wireless Output Phone(Coil2: 15W)+Watch(2.5W)
Mode25	Wireless Output Earphone(5W)+Watch(2.5W)
Mode26	Wireless Output Phone(Coil1: 5W)
Mode27	Wireless Output Phone(Coil1: 7.5W)
Mode28	Wireless Output Phone(Coil1: 10W)
Mode29	Wireless Output Phone(Coil1: 15W)
Mode30	Wireless Output Phone(Coil2: 5W)
Mode31	Wireless Output Phone(Coil2: 7.5W)
Mode32	Wireless Output Phone(Coil2: 10W)

TEST REPORT

Report No.: MTi260420016-0305E2

Mode33	Wireless Output Phone(Coil2: 15W)
Mode34	Wireless Output Earphone(5W)
Mode35	Wireless Output +Watch(2.5W)
Mode36	stand by

1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
Mobile phone	Find X3	bf6e6b3b	OPPO
HUAWEI QUICK CHARGE(65W)	HW-200200ZP1	JN67LSN7N03451	HUAWEI
TWS	Air Pods	MQD83CH/A	Apple
Apple Watch	Apple Watch S7	FH7PP6BAG91J6	Apple
Support cable list			
Description	Length (m)	From	To
/	/	/	/

2 Measurement uncertainty

Parameter	Expanded Uncertainty
Magnetic field measurements(3kHz~10MHz)	$\pm 0.7\text{dB}$
Electric field measurements(3kHz~10MHz)	$\pm 1.06\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

2.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

3 Test facilities and accreditations**4 List of test equipment**

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E143	Near-field Electric and Magnetic Field Sensor System	SPEAG	MAGPy-8H3 D+E3D	3101	2025/09/2 5	2026/09/2 4

No.	Equipment	Manufacturer	Model	Software version:	Cal. date	Cal. Due
MTI-E016S	MPE test software	SPEAG	MAGPY 2.6	2.6	/	/

5 Test result

5.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)


Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30

f = frequency in MHz

* = Plane-wave equivalent power density

Note 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

Note 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

5.2 Test setup

Note: tips mode of the test probe is used for 0cm measurement.

5.3 Test Procedures

- The RF exposure test was performed in anechoic chamber.
- E and H-field measurements should be made with these devices considered to meet the § 2.1091-Mobile conditions ("generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and [the nearest person]").
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

5.4 Information of test equipment

Test equipment: MAGPy-8H3D+E3D	
Diameter	60mm
8 isotropic H-field sensors	Concentric loops of 1cm ² arranged at the corner of a cube of 22mm side length
1 isotropic E-field sensor	Orthogonal dipole/monopole (arm length: 50mm)
Measurement center	18.5mm from the probe tip
Dimensions	110*635*35mm (MAGPy-8H3D+E3D V2 & MAGPy-DAS V2)
	
Test probe, without the casing	

Item	Specification
Test frequency range:	3kHz ~ 10MHz
Probe sensitivity	E-field: 0.08-2000 V/m H-field: 0.1-3200 A/m
Probe level response	E-field: ±1dB H-field: ±1dB
linearity error	E-field: ±0.3dB H-field: ±0.3dB
Isotropy	E-field: ±0.8dB H-field: ±0.6dB

5.5 Test results

Test condition 1: Mode 4 operating mode with client device (1 % battery status of client device)

Probe Position	E-field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	1.29	614	0.15%	0.06	1.63	0.49%
Bottom	0.66			0.05		
Left	0.78			0.03		
Right	0.56			0.03		
Front	0.69			0.02		
Back	0.58			0.03		

Test condition 2: Mode 4 operating mode with client device (50 % battery status of client device)

Probe Position	E-field (V/m)			H-field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Top	1.36	614	0.12%	0.07	1.63	0.39%
Bottom	0.69			0.06		
Left	0.75			0.05		
Right	0.58			0.02		
Front	0.61			0.03		
Back	0.62			0.01		

Test condition 3: Mode 4 operating mode with client device (99 % battery status of client device)

Probe Position	E-field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	1.25	614	0.10%	0.05	1.63	0.32%
Bottom	0.59			0.03		
Left	0.75			0.05		
Right	0.55			0.02		
Front	0.65			0.01		
Back	0.57			0.02		

Photographs of the Test Setup

See the Appendix - Test Setup Photos.

Photographs of the EUT

See the Appendix - EUT Photos.

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****