




FCC RADIO TEST REPORT

Applicant	: Hypertechnologie Ciara Inc. Ciara Technologies Inc
Address	: 9300 Transcanadienne St-Laurent, Quebec H4S 1K5 Canada
Equipment	: Notebook PC
Model No.	: CRIUS CO310-G1, CRIUS CO310-G1-BL, CRIUS N320-G1, CRIUS N320-G1-BL, CRIUS N310-G1, CRIUS N310-G1-BL
Trade Name	: 
FCC ID	: 2BDS2-CRIUS
Standard	: FCC part 15 Subpart C §15.247

I HEREBY CERTIFY THAT :

The sample was received on Nov. 07, 2023 and the testing was completed on Nov. 30, 2023 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:


Leevin Li /Supervisor



Contents

1.	Summary of Test Procedure and Test Results	5
1.1	Applicable Standards	5
2.	Test Configuration of Equipment under Test.....	6
2.1	Feature of Equipment under Test.....	6
2.2	Carrier Frequency of Channels	7
2.3	Test Mode & Test Software	8
2.6	General Information of Test.....	11
2.7	Measurement Uncertainty	11
3.	Test Equipment and Ancillaries Used for Tests	12
4.	Antenna Requirements.....	14
4.1	Standard Applicable	14
4.2	Antenna Construction and Directional Gain.....	14
5.	Test of Conducted Emission.....	15
5.1	Test Limit	15
5.2	Test Procedures	15
5.3	Typical Test Setup	16
5.4	Test Result and Data	17
6.	Test of Radiated Emission	19
6.1	Test Limit	19
6.2	Test Procedures.....	20
6.3	Typical Test Setup	21
6.4	Test Result and Data (9kHz ~ 30MHz)	22
6.5	Test Result and Data (30MHz ~ 1GHz)	22
6.6	Test Result and Data (1GHz ~ 25GHz)	24
6.7	Restricted Bands of Operation.....	46
7.	Test of Conducted Spurious Emission.....	63
7.1	Test Limit	63
7.2	Test Procedure	63
7.3	Test Setup Layout	63
7.4	Test Result and Data.....	63
8.	20dB Bandwidth Measurement Data.....	69
8.1	Test Limit	69
8.2	Test Procedures	69
8.3	Test Setup Layout	69
8.4	Test Result and Data.....	69
9.	Frequencies Separation	72
9.1	Test Limit	72
9.2	Test Procedures	72
9.3	Test Setup Layout	72
9.4	Test Result and Data.....	72
10.	Dwell Time on each channel	75



10.1	Test Limit	75
10.2	Test Procedures	75
10.3	Test Setup Layout	75
10.4	Test Result and Data	75
11.	Number of Hopping Channels	79
11.1	Test Limit	79
11.2	Test Procedures	79
11.3	Test Setup Layout	79
11.4	Test Result and Data	79
12.	Maximum Peak Output Power	81
12.1	Test Limit	81
12.2	Test Procedures	81
12.3	Test Setup Layout	81
12.4	Test Result and Data	81



History of this test report

Version No.	Report No	Date	Description
Rev.01	DEFB2310067	Dec. 06, 2023	Initial Issue



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.10: 2013

KDB 558074 D01 DTS Meas Guidance v05r02

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	. Description of Test	Result
§ 15.203	. Antenna Requirement	Pass
§ 15.207(a)	. Conducted Emission	Pass
§ 15.209(a)	. Radiated Emission	Pass
§ 15.247(a)(1)	. Channel Carrier Frequencies Separation	Pass
§ 15.247(a)(1)	. 20dB Bandwidth Measurement	Pass
§ 15.247(a)(1)	. Dwell Time	Pass
§ 15.247(b)	. Number of Hopping Channels	Pass
§ 15.247(b)	. Peak Output Power Measurement Data	Pass
§ 15.247(d)	. Band Edges Measurement Data	Pass
Note: Deviations Yes No ■		
*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement.		



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Equipment	Notebook PC
Model Name	CRIUS CO310-G1, CRIUS CO310-G1-BL, CRIUS N320-G1, CRIUS N320-G1-BL, CRIUS N310-G1, CRIUS N310-G1-BL
Model Discrepancy	The Motherboard and Circuit principle are identical except different antenna gain, antenna location, HVIN, appearance, keyboard, Interface Board, battery. More details please refer to Product Similarity Declaration.
Module	AX211NGW
Frequency Range	BT/BLE/ WIFI 2.4G: 2400MHz-2483.5MHz WIFI 5G: 5150MHz-5250MHz, 5250MHz-5350MHz, 5470MHz -5725MHz, 5725MHz -5850MHz WIFI 6G: 802.11ax: 5925MHz-6425MHz, 6425MHz-6525MHz 6525MHz-6875MHz 6875MHz-7125MHz
Modulation Type	BT: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE: GFSK 2.4GHz 802.11b: CCK, DQPSK, DBPSK 802.11g/n: BPSK, QPSK, 16QAM, 64QAM 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM 5GHz 802.11a/n: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM 6GHz:802.11ax: BPSK. QPSK. 16QAM. 64QAM, 256QAM. 1024QAM
Data Rate	BT: GFSK:1Mbps, $\pi/4$ -DQPSK: 2Mbps, 8DPSK:3Mbps BLE: GFSK: 1Mbps WIFI 2.4GHz: 802.11b: 1, 2, 5.5,11Mbps 802.11g: 6,9,12,18,24,36,48,54Mbps 802.11n: MCS0-MCS15, HT20/HT40 802.11ax: MCS0-MCS11, HE20/HE40 WIFI 5GHz: 802.11a: 6,9,12,18,24,36,48,54Mbps 802.11n: MCS0-MCS15, HT20/HT40 802.11ac: MCS0-MCS9, VHT20/40/80/160 802.11ax: MCS0-MCS11, HE20/HE40/HE80/HE160 WIFI 6GHz: 802.11ax: MCS0-MCS11, HE20/40/80/160
Working Temperature	0°C to 35°C
EUT Power Rating:	DC IN Input: 19V $\pm$ 3.42A from adapter type -C port Input: 20V $\pm$ 3.25A from adapter

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.2 Carrier Frequency of Channels

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470
09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	---	---



2.3 Test Mode & Test Software

- During testing, the interface cables and equipment positions were varied according to ANSI C63.10
- The complete test system included support units and EUT for RF test.
- An executive program, "DRTU.exe (Ver.: N/A)" under Windows 11 System was executed to transmit and receive data via Bluetooth.
- The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	GFSK (1Mbps) for AC120V for CRIUS N310-G1
2	$\pi/4$ -DQPSK (2Mbps) for AC120V for CRIUS N310-G1
3	8DPSK (3Mbps) for AC120V for CRIUS N310-G1
4	GFSK (1Mbps) for AC120V for CRIUS CO310-G1
5	GFSK (1Mbps) for AC120V for CRIUS N320-G1
6	GFSK (1Mbps) for AC240V for CRIUS N310-G1
7	GFSK (1Mbps) for AC240V for CRIUS CO310-G1
8	GFSK (1Mbps) for AC240V for CRIUS N320-G1
caused "Test Mode 1 and CH78:2480" generated the worst case, it was reported as the final data.	
Radiation Emissions (Below 1GHz)	
Test Mode	Operating Description
1	GFSK (1Mbps) for CRIUS N310-G1
2	$\pi/4$ -DQPSK (2Mbps) for CRIUS N310-G1
3	8DPSK (3Mbps) for CRIUS N310-G1
4	GFSK (1Mbps) for CRIUS CO310-G1
5	GFSK (1Mbps) for CRIUS N320-G1
caused "Test Mode 1 and CH78:2480" generated the worst case, it was reported as the final data.	
Radiation Emissions (1GHz ~ 25GHz)	
Test Mode	Operating Description
1	GFSK (1Mbps) for CRIUS N310-G1
2	$\pi/4$ -DQPSK (2Mbps) for CRIUS N310-G1
3	8DPSK (3Mbps) for CRIUS N310-G1
4	GFSK (1Mbps) for CRIUS CO310-G1
5	$\pi/4$ -DQPSK (2Mbps) for CRIUS CO310-G1
6	8DPSK (3Mbps) for CRIUS CO310-G1
7	GFSK (1Mbps) for CRIUS N320-G1
8	$\pi/4$ -DQPSK (2Mbps) for CRIUS N320-G1
9	8DPSK (3Mbps) for CRIUS N320-G1
caused "Test Mode 1~3,6,9" generated the worst case, they were reported as the final data. Note: Model CRIUS N310-G1 is the worst, Model CRIUS CO310-G1 and CRIUS N320-G1 only put the worst mode data	




2.4 Power Parameter Value of the test software

Mode	Frequency (MHz)	Power Setting
GFSK (1Mbps)	2402	12
	2441	12
	2480	12
$\pi/4$ -DQPSK (2Mbps)	2402	7
	2441	7
	2480	7
8DPSK (3Mbps)	2402	7
	2441	7
	2480	7



2.5 Description of Test System

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 Adapter	Aoda	A869-200325C-Uus1	5019043	N/A





2.6 General Information of Test

Test Site	CerpPASS Technology Corporation(CerpPASS Laboratory) Address: Room 102, No. 5, Xing'an Road, Chang'an Town, Dongguan City, Guangdong Province Tel: +86-769-8547-1212 Fax: +86-769-8547-1912
FCC Designation No.:	CN1288
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 9kHz to 25,000MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-DG	2023/11/20~2023/11/22	22~25℃ / 51~55%	Amos Zhang
Radiated Emissions	3M01-DG	2023/11/17	23℃ / 50%	Amos Zhang
AC Power Line Conducted Emission	CON01-DG	2023/11/30	23℃ / 54%	Amos Zhang

2.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor $k=2$).

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±2.60dB
Radiated Spurious Emission(9KHz~30MHz)	±4.10dB
Radiated Spurious Emission(30MHz~1GHz)	±4.51dB
Radiated Spurious Emission(1GHz~18GHz)	±5.36dB
Radiated Spurious Emission(18GHz~40GHz)	±5.43dB
6dB Bandwidth&20dB Bandwidth	±4.8%
Occupied Bandwidth	±4.5%
Peak Output Power(Conducted Power Meter)	±0.94dB
Power Spectral Density	±1.01dB
Dwell Time / Deactivation Time	±3.5%



3. Test Equipment and Ancillaries Used for Tests

AC Power Line Conducted Emission					
Test Site	CON01-DG				
Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100564	2023/01/06	2024/01/05
LISN	SCHWARZBECK	NSLK 8127	8127749	2023/08/03	2024/08/02
LISN	R&S	ENV216	100024	2023/01/06	2024/01/05
Cable	Aoda	RG214	Cable-06	2023/01/06	2024/01/05
Pulse Limiter with 10dB Attenuation	SCHWARZBECK	VTSD 9561-F	9561-F106	2023/01/06	2024/01/05
Temperature/ Humidity Meter	GEMLEAD	STH200A	N/A	2023/08/03	2024/08/02

Radiated Emissions					
Test Site	3M01-DG				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
EMI Test Receiver	R&S	ESCI	100565	2023/08/03	2024/08/02
Amplifier	EMCI	EMC330	980082	2023/05/06	2024/05/05
Loop Antenna	R&S	HFH2-Z2	100150	2022/05/11	2024/05/10
Bilog Antenna	Sunol Science	JB1	A072414-3	2022/06/09	2024/06/08
Preamplifier	Agilent	8449B	3008A02342	2023/08/03	2024/08/02
Preamplifier	COM-POWER	PA-840	711885	2023/05/06	2024/05/05
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120 D	9120D-619	2022/05/22	2024/05/21
Standard Gain Horn Antenna	TRC	HA-2640	18050	2022/05/09	2024/05/08
Standard Gain Horn Antenna	TRC	HA-1726	18051	2022/05/09	2024/05/08
FSQ Signal Analyzer	R&S	FSQ40	200012	2023/05/06	2024/05/05
Cable	EMCI	EM104-NM SM-8.5M	Cable-03	2023/08/03	2024/08/02
Cable	Jiuzhoubona	T-SMA	SMA48AL-7000	2023/08/03	2024/08/02
Cable	CH-CoDesign	CCXA40-2.92-2.92-1M	21071954	2023/08/03	2024/08/02
Cable	CH-CoDesign	CCX40-2.92M-2.92M-9M	21070892	2023/08/03	2024/08/02
Temperature/ Humidity Meter	GEMLEAD	STH200A	N/A	2023/08/03	2024/08/02



RF Conducted					
Test Site	RFCON01-DG				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
MXA Signal Analyzer	KEYSIGHT	N9020A	US46220290	2023/05/06	2024/05/05
EXA Signal Analyzer	KEYSIGHT	N9010A	MY53400169	2023/05/06	2024/05/05
ESG VECTOR SIGNAL GENERATOR	Agilent	E4438C	MY45092582	2023/05/06	2024/05/05
MXG VECTOR SIGNAL GENERATOR	Agilent	N5182B	MY53050127	2023/05/06	2024/05/05
USB Wideband Power Sensor	Boonton	55006	9778	2023/08/03	2024/08/02
Temperature/ Humidity Meter	mingle	ETH529	N/A	2023/01/06	2024/01/05



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Model	Antenna Type	Antenna Gain
CRIUS N320-G1 CRIUS N320-G1-BL	FPCB	2.27dbi
CRIUS CO310-G1 CRIUS N320-G1-BL	FPCB	-0.40dbi
CRIUS N310-G1 CRIUS N310-G1-BL	FPCB	4.27dbi



5. Test of Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.10-2013. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 6.2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.




5.3 Typical Test Setup






5.4 Test Result and Data



Note: Measurement Level = Reading Level + Correct Factor



Note: Measurement Level = Reading Level + Correct Factor



6. Test of Radiated Emission

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

FREQUENCIES(MHz)	FIELD STRENGTH(microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3



6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground; above 1GHz, the height was 1.5m.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- i. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.


Note: The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.

(X AXIS is the worst.)




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup







6.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz-30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)











6.6 Test Result and Data (1GHz ~ 25GHz)


Model CRIUS N310-G1























































Model CRIUS CO310-G1








Model CRIUS N320-G1







6.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz



Model CRIUS N310-G1

