



FCC TEST REPORT

FCC ID: 2BDTM-D03

On Behalf of

Shenzhen Hongshengda Optoelectronic Technology Co.,Ltd

Portable Smart Screen

Model No.: D03(For more models, please refer to the General Description of EUT.)

Prepared for : Shenzhen Hongshengda Optoelectronic Technology Co.,Ltd
Address : 3rd Floor, Building 4, No.161, Xingye Road,Fenghuang
Community,Fuyong Street,Bao 'an District, Shenzhen, China

Prepared By : Shenzhen PSI Testing Co., Ltd.
Address : 1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road,
Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number : psi2603068-C01-R02
Date of Receipt : Jan.14, 2026
Date of Test : Jan.14, 2026-Feb.24, 2026
Date of Report : Feb.24, 2026
Version Number : V0

TABLE OF CONTENTS

Description	Page
1. Summary Of Standards And Results	6
1.1. Description of Standards and Results	6
2. General Information	7
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details.....	8
2.4. Block Diagram of Connection Between EUT and Simulators	8
2.5. Test Mode Description	9
2.6. Software test version and power setting information	10
2.7. Test Conditions	10
2.8. Test Facility	11
2.9. Measurement Uncertainty	11
2.10. Test Equipment List.....	12
3. Spurious Emission	13
3.1. Test Limits.....	13
3.2. Block Diagram of Test setup	14
3.3. Test Procedure.....	15
3.4. Test Results.....	16
4. Power Line Conducted Emission	24
4.1. Test Limits.....	24
4.2. Test Procedure.....	24
4.3. Test Setup.....	24
4.4. Test Results.....	25
5. Out-of-band Emissions	28
5.1. Test Limits.....	28
5.2. Test Procedure.....	28
5.3. Test Setup.....	28
5.4. Test Results.....	28
6. Conducted Maximum Output Power	49
6.1. Test limits.....	49
6.2. Test Procedure.....	49
6.3. Test Setup.....	49
6.4. Test Results.....	49
7. Peak Power Spectral Density	50
7.1. Test limits.....	50
7.2. Test Procedure.....	50
7.3. Test Setup.....	50
7.4. Test Results.....	50
8. Occupied Bandwidth	57
8.1. Test limits.....	57
8.2. Test Procedure.....	57
8.3. Test Setup.....	57
8.4. Test Results.....	57

9. Band Edge Test	64
9.1. Test Limit	64
9.2. Block Diagram of Test Setup	64
9.3. Test Procedure	64
9.4. Test Results	65
10. Antenna Requirement	69
10.1. Standard Requirement	69
10.2. Test Results	69
11. Duty cycle	70
11.1. Test Limits	70
11.2. Test Procedure	70
11.3. Test Setup	70
12. Photos of test setup	73
13. Photos of EUT	73

TEST REPORT DECLARATION

Applicant : Shenzhen Hongshengda Optoelectronic Technology Co.,Ltd
Address : 3rd Floor, Building 4, No.161, Xingye Road,Fenghuang Community,Fuyong Street,Bao 'an District, Shenzhen, China
Manufacturer : Shenzhen Hongshengda Optoelectronic Technology Co.,Ltd
Address : 3rd Floor, Building 4, No.161, Xingye Road,Fenghuang Community,Fuyong Street,Bao 'an District, Shenzhen, China
EUT Description : Portable Smart Screen
(A) Model No. : D03(For more models, please refer to the General Description of EUT.)
(B) Trademark : N/A

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10-2020


Test Result: PASS

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part 15C requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....:

Felix Pang
Test Engineer



Approved by (name + signature).....:

Simple Guan
Project Manager



Date of issue.....:

Feb.25, 2026

Revision History

Revision	Issue Date	Revisions	Revised By
V0	Feb.25, 2026	Initial released Issue	Felix Pang

1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Conducted Emission	FCC Part 15: 15.207 ANSI C63.10-2020	P
6dB Bandwidth	FCC PART 15:15.247(a)(2), ANSI C63.10-2020	P
Output Power	FCC Part 15: 15.247(b)(3), ANSI C63.10-2020	P
Radiated Spurious Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d), ANSI C63.10-2020	P
Conducted Spurious & Band Edge Emission	FCC Part 15: 15.247(d), ANSI C63.10-2020	P
Power Spectral Density	FCC PART 15:15.247(e), ANSI C63.10-2020	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d), ANSI C63.10-2020	P
Antenna Requirement	FCC Part 15: 15.203	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable. 4. Conclusion determination rules of this report: Unless there are clear provisions on measurement uncertainty in the standard or customer requirements, decision by actual test data without considering measurement uncertainty. 5. Measurement method usage KDB 558074 D01 15.247 Meas Guidance v05r02.		

2. General Information

2.1. Description of Device (EUT)

Product Name	: Portable Smart Screen D03,P02,HSD-215,P02*****,D03*****,HSD-215*****,H*****,P***** **(" *")The digits 0-9, letters A-Z and a-z, symbols, or whitespace. The differences between models are only in color patterns and sales channels, with all other aspects being identical. These differences do not affect product safety or electromagnetic compatibility performance. The P series is desktop portable, while the others are pillar-mounted mobile types.)
Model	: All models have the same circuit and RF module, except for the model name and color
Diff	: All models have the same circuit and RF module, except for the model name and color
Test Voltage	: AC 120V 60Hz

Radio technology	: 2.4G WiFi
Operation frequency	: 2412MHz-2462MHz for IEEE 802.11 b, g, n/HT20 2422MHz-2452MHz for IEEE 802.11n/HT40
Channel No.	: 802.11b/802.11g/802.11n(HT20): 11CH 802.11n(HT40): 7CH
Modulation type	: IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)
Antenna Type	: FPC antenna, maximum gain is 1.99dBi.

PMN	: N/A
HVIN	: N/A

Software version	: N/A
Hardware version/FVIN	: N/A

Note	: Antenna information is provided by applicant. Testing lab is not responsible for the accuracy of the information.
------	--


2.2. Accessories of Device (EUT)

Accessories 1 : Adapter
Manufacturer : /
Model : FX36U-150240C
Rating : Input:100-240V 50/60Hz 0.8A
Output: DC 15V 2.4A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1	/	/	/	/
2	/	/	/	/
3	/	/	/	/

2.4. Block Diagram of Connection Between EUT and Simulators



2.5. Test Mode Description

Keeping TX			
Mode	Data rate (Mbps)	Channel	Frequency(MHz)
IEEE 802.11 b	1	Low :CH1	2412
	1	Middle: CH6	2437
	1	High: CH11	2462
IEEE 802.11 g	6	Low :CH1	2412
	6	Middle: CH6	2437
	6	High: CH11	2462
IEEE 802.11 n/HT20	6.5	Low :CH1	2412
	6.5	Middle: CH6	2437
	6.5	High: CH11	2462
IEEE 802.11 n/HT40	13.5	Low :CH3	2422
	13.5	Middle:CH6	2437
	13.5	High:CH9	2452
Note: According exploratory test, EUT will have maximum output power in those data rate. So those data rate were used for all test.			

Channel list:					
For IEEE 802.11b, g, n/HT20					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	2412	CH5	2432	CH9	2452
CH2	2417	CH6	2437	CH10	2457
CH3	2422	CH7	2442	CH11	2462
CH4	2427	CH8	2447		

For IEEE 802.11 n/HT40					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH3	2422	CH7	2442		
CH4	2427	CH8	2447		
CH5	2432	CH9	2452		
CH6	2437				

2.6. Software test version and power setting information

Software testing version	Engineering mode		
Mode	The client 's preset testing software is used to control the operation of EUT in continuous transmission mode and select the testing channel, wireless mode:		
Power level setup by client			
Mode	Channel	Frequency (MHz)	Soft Set
IEEE 802.11b/g/n20	Low :CH1	2412	TX level is set as defaults value.
	Middle: CH6	2437	TX level is set as defaults value.
	High: CH11	2462	TX level is set as defaults value.
IEEE 802.11n40	Low :CH3	2422	TX level is set as defaults value.
	Middle:CH6	2437	TX level is set as defaults value.
	High:CH9	2452	TX level is set as defaults value.

2.7. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	26℃
Humidity range:	25-75%	54%
Pressure range:	86-106kPa	101kPa

2.8. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission

Registration Number: 916281

2.9. Measurement Uncertainty

(95% confidence levels, $k=2$)

Item	Uncertainty
Power Line Conducted Emissions Test	2.13dB
Radiation Emission test in 3m chamber(Below 30MHz)	4.07dB
Radiation Emission test in 3m chamber(30MHz to 1GHz)	4.51dB
Radiation Emission test in 3m chamber(1GHz to 18GHz)	5.07dB
Radiation Emission test in 3m chamber(18GHz to 40GHz)	5.21dB
Radio Frequency	48.24KHz
Conducted RF Power	0.41dB
Power Spectral Density	0.39 dB
Occupied-Bandwidth	968Hz
Duty Cycle	1%
Conducted-Spurious Emission	1.26dB

2.10.Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2025.12.19	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2025.12.18	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV216	102282	/	2025.12.18	1 Year
4.	L.I.S.N.#2	RFT	NNB111	13835240	/	2025.12.18	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2025.01.02	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2025.01.02	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2025.12.18	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2025.01.02	2 Year
9.	Amplifier	SKET	LAPA_01G1 8G-45dB	SK20220329 01	/	2025.12.18	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2024.12.31	2 Year
11.	Amplifier	SKET	LNPA_0118 G-45	SK20200108 01	/	2025.12.18	1 Year
12.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.0 2-1111533-F z	/	2025.12.18	1 Year
13.	RF Sensor Unit	Tachoy	TR1029-2	20220428P0 08	/	2025.12.18	1 Year
14.	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2025.12.18	1 Year
15.	Temp. & Humid Chamber	Auchno	9606	/	/	2025.12.18	1 Year
16.	Regulated DC Power Supply	Xinouhua	ADC120V10 A	2022112516 38	/	2025.12.18	1 Year
17.	Cable	SKET	Cable-RE-1	#02/#03	/	2025.12.18	1 Year
18.	Cable	SKET	Cable-RE-2	#01	/	2025.12.18	1 Year
19.	Cable	SKET	Cable-RE-3	#04	/	2025.12.18	1 Year
20.	Cable	SKET	Cable-CE-1	A-E-24	/	2025.12.18	1 Year
21.	6dB Attenuator	Schwarzbeck	DGA 9552N 6dB	CK4186	/	2025.12.18	1 Year
22.	Power meter	Agilent	E4419B	GB40202121	/	2025.12.18	1 Year
23.	Comprehensive Test Instrument	Rohde&Schwarz	CMW 500	145266	/	2025.12.18	1 Year
For Test Software Information							
Item	Software Name	Manufacturer		Version			
RE	EZ EMC	Farad		PSI-3A1			
CE	EZ EMC	Farad		PSI-3A1			
RF	RTS	TACHOY		V1.0.0			

3. Spurious Emission

3.1. Test Limits

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

Note: The peak limit is 20 dB higher than the average limit


All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

3.2. Block Diagram of Test setup


a. In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



b. In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



c. In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



3.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 10 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10-2020 on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

Test setup information:


9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHZ~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

3.4. Test Results

We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.
Detailed information please see the following page.


From 9KHz to 30MHz:	
Test Date : 2026.01.21	Temperature : 23.3℃
Test Engineer : Felix Pang	Humidity : 49%
Test Mode : IEEE 802.11n20 mode	
Test Results : PASS	
Note:	The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz:	
Test Date : 2026.01.21	Temperature : 23.3℃
Test Engineer : Felix Pang	Humidity : 49%
Test Mode : IEEE 802.11n20 mode	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of IEEE 802.11n mode, Channel 2437MHz was listed in this report.

Polarization: Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	47.9938	49.14	-21.56	27.58	40.00	-12.42	QP
2	132.2204	51.27	-22.34	28.93	43.50	-14.57	QP
3	155.3642	50.06	-20.55	29.51	43.50	-13.99	QP
4	206.3975	53.42	-23.44	29.98	43.50	-13.52	QP
5	378.5842	52.56	-18.03	34.53	46.00	-11.47	QP
6	758.0407	42.06	-7.85	34.21	46.00	-11.79	QP

Level = Reading + Factor Margin = Level - Limit

Polarization: Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	47.8260	56.06	-21.54	34.52	40.00	-5.48	QP
2	59.2323	53.91	-22.49	31.42	40.00	-8.58	QP
3	157.0072	53.22	-20.55	32.67	43.50	-10.83	QP
4	220.6168	52.47	-23.54	28.93	46.00	-17.07	QP
5	378.5842	54.47	-18.03	36.44	46.00	-9.56	QP
6	758.0407	39.76	-7.85	31.91	46.00	-14.09	QP

Level = Reading + Factor Margin = Level - Limit

From 1GHz to 25GHz:	
Test Date : 2026.01.21	Temperature : 23.3℃
Test Engineer : Felix Pang	Humidity : 49%
Test Mode : WiFi mode	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

Test Mode : IEEE 802.11b TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4824	V	51.93	-13.18	38.75	74.00	-35.25	Peak
2	4824	V	45.02	-13.18	31.84	54.00	-22.16	Avg
3	7236	--	--	--	--	--	--	--
4	9648	--	--	--	--	--	--	--
5	4824	H	50.52	-13.18	37.34	74.00	-36.66	Peak
6	4824	H	42.72	-13.18	29.54	54.00	-24.46	Avg
7	7236	--	--	--	--	--	--	--
8	9648	--	--	--	--	--	--	--
Test Mode : IEEE 802.11b TX Mid								
1	4874	V	52.94	-13.00	39.94	74.00	-34.06	Peak
2	4874	V	45.24	-13.00	32.24	54.00	-21.76	Avg
3	7311	--	--	--	--	--	--	--
4	9748	--	--	--	--	--	--	--
5	4874	H	49.58	-13.00	36.58	74.00	-37.42	Peak
6	4874	H	42.00	-13.00	29.00	54.00	-25.00	Avg
7	7311	--	--	--	--	--	--	--
8	9748	--	--	--	--	--	--	--
Test Mode : IEEE 802.11b TX High								
1	4924	V	52.03	-12.83	39.20	74.00	-34.80	Peak
2	4924	V	44.05	-12.83	31.22	54.00	-22.78	Avg
3	7386	--	--	--	--	--	--	--
4	9848	--	--	--	--	--	--	--
5	4924	H	50.86	-12.83	38.03	74.00	-35.97	Peak
6	4924	H	41.57	-12.83	28.74	54.00	-25.26	Avg
7	7386	--	--	--	--	--	--	--
8	9848	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

Test Mode : IEEE 802.11g TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4824	V	51.09	-13.18	37.91	74.00	-36.09	Peak
2	4824	V	42.71	-13.18	29.53	54.00	-24.47	Avg
3	7236	--	--	--	--	--	--	--
4	9648	--	--	--	--	--	--	--
5	4824	H	50.36	-13.18	37.18	74.00	-36.82	Peak
6	4824	H	41.21	-13.18	28.03	54.00	-25.97	Avg
7	7236	--	--	--	--	--	--	--
8	9648	--	--	--	--	--	--	--
Test Mode : IEEE 802.11g TX Mid								
1	4874	V	51.52	-13.00	38.52	74.00	-35.48	Peak
2	4874	V	42.40	-13.00	29.40	54.00	-24.60	Avg
3	7311	--	--	--	--	--	--	--
4	9748	--	--	--	--	--	--	--
5	4874	H	50.51	-13.00	37.51	74.00	-36.49	Peak
6	4874	H	42.46	-13.00	29.46	54.00	-24.54	Avg
7	7311	--	--	--	--	--	--	--
8	9748	--	--	--	--	--	--	--
Test Mode : IEEE 802.11g TX High								
1	4924	V	52.10	-12.83	39.27	74.00	-34.73	Peak
2	4924	V	43.85	-12.83	31.02	54.00	-22.98	Avg
3	7386	--	--	--	--	--	--	--
4	9848	--	--	--	--	--	--	--
5	4924	H	51.60	-12.83	38.77	74.00	-35.23	Peak
6	4924	H	41.02	-12.83	28.19	54.00	-25.81	Avg
7	7386	--	--	--	--	--	--	--
8	9848	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

Test Mode : IEEE 802.11n/HT20 TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4824	V	52.25	-13.18	39.07	74.00	-34.93	Peak
2	4824	V	44.83	-13.18	31.65	54.00	-22.35	Avg
3	7236	--	--	--	--	--	--	--
4	9648	--	--	--	--	--	--	--
5	4824	H	49.56	-13.18	36.38	74.00	-37.62	Peak
6	4824	H	42.02	-13.18	28.84	54.00	-25.16	Avg
7	7236	--	--	--	--	--	--	--
8	9648	--	--	--	--	--	--	--
Test Mode : IEEE 802.11n/HT20 TX Mid								
1	4874	V	51.97	-13.00	38.97	74.00	-35.03	Peak
2	4874	V	44.45	-13.00	31.45	54.00	-22.55	Avg
3	7311	--	--	--	--	--	--	--
4	9748	--	--	--	--	--	--	--
5	4874	H	49.79	-13.00	36.79	74.00	-37.21	Peak
6	4874	H	42.45	-13.00	29.45	54.00	-24.55	Avg
7	7311	--	--	--	--	--	--	--
8	9748	--	--	--	--	--	--	--
Test Mode : IEEE 802.11n/HT20 TX High								
1	4924	V	54.39	-12.83	41.56	74.00	-32.44	Peak
2	4924	V	45.24	-12.83	32.41	54.00	-21.59	Avg
3	7386	--	--	--	--	--	--	--
4	9848	--	--	--	--	--	--	--
5	4924	H	52.12	-12.83	39.29	74.00	-34.71	Peak
6	4924	H	43.01	-12.83	30.18	54.00	-23.82	Avg
7	7386	--	--	--	--	--	--	--
8	9848	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

Test Mode : IEEE 802.11n/HT40 TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4844	V	52.42	-13.11	39.31	74.00	-34.69	Peak
2	4844	V	42.62	-13.11	29.51	54.00	-24.49	Avg
3	7266	--	--	--	--	--	--	--
4	9688	--	--	--	--	--	--	--
5	4844	H	52.86	-13.11	39.75	74.00	-34.25	Peak
6	4844	H	42.17	-13.11	29.06	54.00	-24.94	Avg
7	7266	--	--	--	--	--	--	--
8	9688	--	--	--	--	--	--	--
Test Mode : IEEE 802.11n/HT40 TX Mid								
1	4874	V	54.45	-13.00	41.45	74.00	-32.55	Peak
2	4874	V	45.09	-13.00	32.09	54.00	-21.91	Avg
3	7311	--	--	--	--	--	--	--
4	9748	--	--	--	--	--	--	--
5	4874	H	50.30	-13.00	37.30	74.00	-36.70	Peak
6	4874	H	44.59	-13.00	31.59	54.00	-22.41	Avg
7	7311	--	--	--	--	--	--	--
8	9748	--	--	--	--	--	--	--
Test Mode : IEEE 802.11n/HT40 TX High								
1	4904	V	54.00	-12.90	41.10	74.00	-32.90	Peak
2	4904	V	46.33	-12.90	33.43	54.00	-20.57	Avg
3	7356	--	--	--	--	--	--	--
4	9808	--	--	--	--	--	--	--
5	4904	H	51.27	-12.90	38.37	74.00	-35.63	Peak
6	4904	H	44.72	-12.90	31.82	54.00	-22.18	Avg
7	7356	--	--	--	--	--	--	--
8	9808	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor, Margin= Result-Limit.								

4. Power Line Conducted Emission

4.1. Test Limits

Frequency (MHz)	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2. Test Procedure

The EUT is put on the plane 0.1m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10-2020 on Conducted Emission Measurement.

The bandwidth of test receiver is set at 9 kHz.

4.3. Test Setup




4.4. Test Results

Test Date	: 2026.1.17	Temperature	: 22.1℃
Test Engineer	: Felix Pang	Humidity	: 40%
Test Mode	: WIFI mode		
Test Results	: PASS		

Note: 1. The test results are listed in next pages.

2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out.
3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.
4. All modes have been tested, and only worst data of n20 mode, Channel 2437MHz (AC 120V/ 60Hz) was listed in this report.


Polarization: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1507	41.21	9.80	51.01	65.96	-14.95	QP
2	0.1507	25.59	9.80	35.39	55.96	-20.57	AVG
3	0.2489	34.67	9.83	44.50	61.79	-17.29	QP
4	0.2489	17.51	9.83	27.34	51.79	-24.45	AVG
5	0.3975	31.98	9.90	41.88	57.91	-16.03	QP
6	0.3975	21.92	9.90	31.82	47.91	-16.09	AVG
7	4.5600	32.45	9.84	42.29	56.00	-13.71	QP
8	4.5600	23.21	9.84	33.05	46.00	-12.95	AVG
9	15.0403	29.15	9.75	38.90	60.00	-21.10	QP
10	15.0403	19.37	9.75	29.12	50.00	-20.88	AVG
11	25.6783	30.69	9.58	40.27	60.00	-19.73	QP
12	25.6783	21.87	9.58	31.45	50.00	-18.55	AVG

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1768	37.81	9.81	47.62	64.63	-17.01	QP
2	0.1768	23.33	9.81	33.14	54.63	-21.49	AVG
3	0.2535	34.51	9.83	44.34	61.64	-17.30	QP
4	0.2535	20.33	9.83	30.16	51.64	-21.48	AVG
5	0.3975	32.44	9.90	42.34	57.91	-15.57	QP
6	0.3975	23.23	9.90	33.13	47.91	-14.78	AVG
7	0.4515	29.88	9.92	39.80	56.85	-17.05	QP
8	0.4515	18.51	9.92	28.43	46.85	-18.42	AVG
9	4.5510	32.36	9.84	42.20	56.00	-13.80	QP
10	4.5510	23.13	9.84	32.97	46.00	-13.03	AVG
11	19.2748	36.62	9.68	46.30	60.00	-13.70	QP
12	19.2748	25.97	9.68	35.65	50.00	-14.35	AVG

Note: Level = Reading + Factor Margin = Level - Limit

5. Out-of-band Emissions

5.1. Test Limits


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.

5.2. Test Procedure

ANSI C63.10-2020 Section 11.11.1, Section 11.11.2, Section 11.11.3

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.

5.3. Test Setup




5.4. Test Results


PASS.

The test results are listed in next pages.


Band Edge: Pass.




1 Reference Level NVNT_ANT1_802_11b_2462




2 Bandedge NVNT_ANT1_802_11b_2462







1 Reference Level NVNT_ANT1_802_11g_2462




2 Bandedge NVNT_ANT1_802_11g_2462




1 Reference Level NVNT_ANT1_802_11n(HT20)_2412




2 Bandedge NVNT_ANT1_802_11n(HT20)_2412




1 Reference Level NVNT_ANT1_802_11n(HT20)_2462




2 Bandedge NVNT_ANT1_802_11n(HT20)_2462




1 Reference Level NVNT_ANT1_802_11n(HT40)_2422




2 Bandedge NVNT_ANT1_802_11n(HT40)_2422




1 Reference Level NVNT_ANT1_802_11n(HT40)_2452




2 Bandedge NVNT_ANT1_802_11n(HT40)_2452




Conducted spurious emission: Pass.




1 Reference Level NVNT_ANT1_802_11b_2437




2 Spurious Emission NVNT_ANT1_802_11b_2437




1 Reference Level NVNT_ANT1_802_11b_2462




2 Spurious Emission NVNT_ANT1_802_11b_2462




1 Reference Level NVNT_ANT1_802_11g_2412




2 Spurious Emission NVNT_ANT1_802_11g_2412




1 Reference Level NVNT_ANT1_802_11g_2437




2 Spurious Emission NVNT_ANT1_802_11g_2437




1 Reference Level NVNT_ANT1_802_11g_2462




2 Spurious Emission NVNT_ANT1_802_11g_2462




1 Reference Level NVNT_ANT1_802_11n(HT20)_2412




2 Spurious Emission NVNT_ANT1_802_11n(HT20)_2412




1 Reference Level NVNT_ANT1_802_11n(HT20)_2437




2 Spurious Emission NVNT_ANT1_802_11n(HT20)_2437




1 Reference Level NVNT_ANT1_802_11n(HT20)_2462




2 Spurious Emission NVNT_ANT1_802_11n(HT20)_2462




1 Reference Level NVNT_ANT1_802_11n(HT40)_2422




2 Spurious Emission NVNT_ANT1_802_11n(HT40)_2422




1 Reference Level NVNT_ANT1_802_11n(HT40)_2437




2 Spurious Emission NVNT_ANT1_802_11n(HT40)_2437



1 Reference Level NVNT_ANT1_802_11n(HT40)_2452



2 Spurious Emission NVNT_ANT1_802_11n(HT40)_2452



6. Conducted Maximum Output Power

6.1. Test limits

Please refer FCC PART 15.247.

Regulation 15.247(b) The limit of Maximum Peak Output Power Measurement is 1 W(30dBm)


6.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

1. Place the EUT on the table and set it in transmitting mode.
2. Connected the EUT's antenna port to peak power meter by 6dB attenuator.
3. Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

6.3. Test Setup



6.4. Test Results

Condition	Antenna	Modulation	Frequency (MHz)	Detector	Conducted Power(dBm)	Duty factor(dB)	Total Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	Peak	14.19	N/A	14.19	30	Pass
NVNT	ANT1	802.11b	2437.00	Peak	14.71	N/A	14.71	30	Pass
NVNT	ANT1	802.11b	2462.00	Peak	14.35	N/A	14.35	30	Pass
NVNT	ANT1	802.11g	2412.00	Peak	14.31	N/A	14.31	30	Pass
NVNT	ANT1	802.11g	2437.00	Peak	14.45	N/A	14.45	30	Pass
NVNT	ANT1	802.11g	2462.00	Peak	14.24	N/A	14.24	30	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	Peak	14.44	N/A	14.44	30	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	Peak	14.79	N/A	14.79	30	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	Peak	14.66	N/A	14.66	30	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	Peak	13.36	N/A	13.36	30	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	Peak	13.56	N/A	13.56	30	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	Peak	13.49	N/A	13.49	30	Pass

7. Peak Power Spectral Density

7.1. Test limits


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

7.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02



1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 30kHz(Set the RBW to: 3 kHz≤RBW≤100 kHz.), VBW = 300kHz(Set the VBW≥3×RBW), span≥1.5×DTS bandwidth., detail see the test plot.
4. Record the max reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.



7.3. Test Setup







7.4. Test Results



Condition	Antenna	Modulation	Frequency (MHz)	SA_PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
NVNT	ANT1	802.11b	2412.00	-7.797	8	Pass
NVNT	ANT1	802.11b	2437.00	-8.407	8	Pass
NVNT	ANT1	802.11b	2462.00	-9.624	8	Pass
NVNT	ANT1	802.11g	2412.00	-13.804	8	Pass
NVNT	ANT1	802.11g	2437.00	-14.256	8	Pass
NVNT	ANT1	802.11g	2462.00	-15.048	8	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	-13.575	8	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	-14.633	8	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	-14.568	8	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	-18.49	8	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	-17.875	8	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	-16.990	8	Pass















8. Occupied Bandwidth

8.1. Test limits


Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz

8.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02



- The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
- The test receiver set RBW = 100kHz, VBW $\geq$ 3*RBW =300kHz, Peak Detector, Sweep time set auto, detail see the test plot.
- The test receiver set RBW =1-5%BW, VBW>3*RBW, Sweep time set auto, detail see the test plot for 99%Bandwidth.


8.3. Test Setup







8.4. Test Results



Condition	Antenna	Modulation	Frequency (MHz)	-6dB BW(MHz)	limit(kHz)	Result
NVNT	ANT1	802.11b	2412.00	7.656	500	Pass
NVNT	ANT1	802.11b	2437.00	8.625	500	Pass
NVNT	ANT1	802.11b	2462.00	8.635	500	Pass
NVNT	ANT1	802.11g	2412.00	15.80	500	Pass
NVNT	ANT1	802.11g	2437.00	16.21	500	Pass
NVNT	ANT1	802.11g	2462.00	16.03	500	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	16.43	500	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	17.49	500	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	17.43	500	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	33.24	500	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	35.21	500	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	29.12	500	Pass















9. Band Edge Test


9.1. Test Limit

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241

9.2. Block Diagram of Test Setup



9.3. Test Procedure

ANSI C63.10-2020 section 6.10.5.2

All restriction band and non- restriction band have been tested, only worse case is reported.
Details see the KDB558074 D01 Meas Guidance v05r02

1. Put the EUT on a 1.5m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission
2. Check the spurious emissions out of band.
3. RBW 1MHz, VBW 3MHz, peak detector for peak value, RBW 1MHz, VBW 10Hz, RMS detector for AV value.

9.4. Test Results

Test Date : 2026.01.21					Temperature : 23.3℃			
Test Engineer : Felix Pang					Humidity : 49%			
Test Results : PASS								
Frequency Range : 2310MHz~2410MHz								
Test Mode : IEEE 802.11b TX 2412MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	68.01	-20.45	47.56	74.00	-26.44	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	72.46	-20.41	52.05	74.00	-21.95	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	63.46	-21.62	41.84	74.00	-32.16	Peak
2	2390	V	--	-21.62	--	54.00	--	Avg
3	2400	V	71.97	-26.08	45.89	74.00	-28.11	Peak
4	2400	V	--	-26.08	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : IEEE 802.11b TX 2462MHz								
1	2483.5	H	73.06	-20.15	52.91	74.00	-21.09	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	73.07	-20.15	52.92	74.00	-21.08	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Frequency Range : 2310MHz~2410MHz								
Test Mode : IEEE 802.11g TX 2412MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	68.55	-20.45	48.10	74.00	-25.90	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	73.52	-20.41	53.11	74.00	-20.89	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	70.24	-20.45	49.79	74.00	-24.21	Peak
2	2390	V	--	-20.45	--	54.00	--	Avg
3	2400	V	70.26	-20.41	49.85	74.00	-24.15	Peak
4	2400	V	--	-20.41	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : IEEE 802.11g TX 2462MHz								
1	2483.5	H	71.28	-20.15	51.13	74.00	-22.87	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	71.38	-20.15	51.23	74.00	-22.77	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

Frequency Range : 2310MHz~2410MHz								
Test Mode : IEEE 802.11n/HT20 TX 2412MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	74.34	-20.45	53.89	74.00	-20.11	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	71.43	-20.41	51.02	74.00	-22.98	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	73.37	-20.45	52.92	74.00	-21.08	Peak
2	2390	V	--	-20.45	--	54.00	--	Avg
3	2400	V	72.42	-20.41	52.01	74.00	-21.99	Peak
4	2400	V	--	-20.41	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : IEEE 802.11n/HT20 TX 2462MHz								
1	2483.5	H	72.54	-20.15	52.39	74.00	-21.61	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	73.76	-20.15	53.61	74.00	-20.39	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

Frequency Range : 2310MHz~2410MHz								
Test Mode : IEEE 802.11n/HT40 TX 2422MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	72.35	-20.45	51.90	74.00	-22.10	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	72.77	-20.41	52.36	74.00	-21.65	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	73.42	-20.45	52.97	74.00	-21.03	Peak
2	2390	V	--	-20.45	--	54.00	--	Avg
3	2400	V	73.58	-20.41	53.17	74.00	-20.83	Peak
4	2400	V	--	-20.41	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : IEEE 802.11n/HT40 TX 2452MHz								
1	2483.5	H	70.61	-20.15	50.46	74.00	-23.54	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	71.94	-20.15	51.79	74.00	-22.21	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor, Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

10. Antenna Requirement

10.1. Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2. Test Results

The EUT antenna is FPC antenna. It complies with the standard requirement.

11. DUTY CYCLE


11.1. Test Limits

N/A


11.2. Test Procedure


ANSI C63.10:2020 §11.6

11.3. Test Setup



Condition	Antenna	Modulation	Frequency (MHz)	Duty cycle(%)	Duty factor(dB)
NVNT	ANT1	802.11b	2437.00	100.00	0.00
NVNT	ANT1	802.11g	2437.00	100.00	0.00
NVNT	ANT1	802.11n(HT20)	2437.00	100.00	0.00
NVNT	ANT1	802.11n(HT40)	2437.00	100.00	0.00





12. Photos of test setup

Reference to the **appendix I Test Setup Photo** for details.

13. Photos of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

----- END OF REPORT-----