



EMC TEST REPORT

Product Name: Tablet

Model Number: ZQC-P1, M104, M105, M107, M108, M109, M20, H717, H719, H720, H821, H822, H823, H824, H825, H826, H827, ZQC-T1

FCC ID: 2BDTW-P1

Issued For : Zhongke Microelectronics Technology (Shenzhen) Co., LTD

Floor 4, Building A, Shimei Industrial Zone, Jinying New Village, Longhua District, Shenzhen, Guangdong, China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China

Report Number: LGT26A130EM01

Sample Received Date: Jan. 20, 2026

Date of Test: Jan. 20, 2026 ~ Feb. 27, 2026

Date of Issue: Feb. 27, 2026

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Zhongke Microelectronics Technology (Shenzhen) Co., LTD
Address: Floor 4, Building A, Shimei Industrial Zone, Jinying New Village,
Longhua District, Shenzhen, Guangdong, China

Manufacturer: Zhongke Microelectronics Technology (Shenzhen) Co., LTD
Address: Floor 4, Building A, Shimei Industrial Zone, Jinying New Village,
Longhua District, Shenzhen, Guangdong, China

Product Name: Tablet

Trademark: N/A

Model Number: ZQC-P1, M104, M105, M107, M108, M109, M20, H717, H719,
H720, H821, H822, H823, H824, H825, H826, H827, ZQC-T1

Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR Part 15 Subpart B ANSI C63.4-2014	PASS

Prepared by:

Terry Zhao

Terry Zhao
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





Table of Contents

1. TEST SUMMARY	5
1.1 TEST LABORATORY	6
1.2 MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF THE EUT	7
2.2 DESCRIPTION OF THE TEST MODES	8
2.3 DESCRIPTION OF THE SUPPORT UNITS	8
2.4 MEASUREMENT INSTRUMENTS LIST	9
3. EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.2 RADIATED EMISSION MEASUREMENT	14
APPENDIX I - TEST SETUP	19
APPENDIX II - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	21



Revision History

Rev.	Issue Date	Revisions
00	Feb. 27, 2026	Initial Issue



1. TEST SUMMARY

EMC Emission				
Standard	Test Item	Limit	Judgement	Remark
FCC 47 CFR Part 15 Subpart B ANSI C63.4-2014	Conducted Emissions	Class B	PASS	
	Radiated Emissions Below 1GHz	Class B	PASS	
	Radiated Emissions Above 1GHz	Class B	PASS	Note 2

Note:

- 1 "N/A" denotes test is not applicable in this Test Report
- 2 If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz. If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, measurement shall only be made up to 5 GHz. If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 40 GHz, whichever is less.



1.1 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate:	FCC Registration No.: 746540
	CAB ID: CN0136

1.2 MEASUREMENT UNCERTAINTY

Test Item	Measurement Frequency Range MHz	Uncertainty dB
Conducted Emissions at AC mains power port	0.009 ~ 30	2.80
Radiated Emissions	0.009 ~ 30	2.16
Radiated Emissions	30 ~ 1000	4.61
Radiated Emissions	1000 ~ 18000	5.49
Note: 1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. 2. The measurement uncertainty is not included in the test result.		



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	Tablet
Test Model Number:	ZQC-P1
Series Number:	M104, M105, M107, M108, M109, M20, H717, H719, H720, H821, H822, H823, H824, H825, H826, H827, ZQC-T1
Model Difference:	The only difference between product models color process. Different model names to meet market demand. Other power supply modes, internal structure, circuit, appearance and key components are the same, and do not affect safety and electromagnetic compatibility performance.
Adapter:	Input: 100-240V~50/60Hz 0.5A Output: DC5V 3A
Battery:	Rated Voltage: 3.8V Capacity:2800mAh
Test Voltage:	AC 120V/60Hz Battery: 3.8V
Hardware Version:	V3.0
Software Version:	N/A
Connecting I/O Port(s):	Please refer to the Note 1.

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operating mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test Mode	Description
Mode 1	Charging+GSM link+BT+Wi-Fi+GPS+Earphone
Mode 2	Charging+WCDMA link+BT+Wi-Fi+GPS+Earphone
Mode 3	Charging+LTE link+BT+Wi-Fi+GPS+Earphone
Mode 4	USB Data Transmission

Note: Only the data of worst-case was recorded in this report.

2.3 DESCRIPTION OF THE SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating
Adapter	Shenzhen Fangxin Technology Co., LTD	FX18U-050300U1	N/A	Input: 100-240V ~ 50/60Hz 0.5A Output: 5V, 3A
USB-A to USB-Mini-B Cable	N/A	N/A	N/A	1.8m

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Laptop	ASUS	UX3407Q	N/A	N/A
Earphone	VESAFE	39630078	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.4 MEASUREMENT INSTRUMENTS LIST

Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2025.03.06	2026.03.05
LISN	COM-POWER	LI-115	02032	2025.03.05	2026.03.04
LISN	SCHWARZBECK	NNLK 8122	00160	2025.03.05	2026.03.04
LISN	EMTRACE	PWL-50-3200	00317	2025.03.05	2026.03.04
LISN	EMTRACE	PVDC-150R-200	00353	2025.03.12	2026.03.11
ISN	FCC	T4-02	91317	2025.03.05	2026.03.04
ISN	SCHWARZBECK	NTFM 8158	00303	2025.03.05	2026.03.04
Transient Limiter	CYBERTEK	EM5010A	E2250100049	2025.03.05	2026.03.04
Temperature & Humidity	BT-3	JINGCHUAN G	N.A	2025.03.10	2026.03.09
Testing Software	SKET	EMC-I	V1.4.0.3	N/A	N/A
Radiated Emission					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2025.03.06	2026.03.05
Spectrum Analyzer	Keysight	N9020A	MY50530994	2025.03.05	2026.03.04
Spectrum Analyzer	Keysight	N9010B	MY60242508	2025.03.05	2026.03.04
Active loop Antenna	ETS	6502	00049544	2025.03.11	2028.03.10
Trilog Broadband Antenna	SCHWARZBECK	VULB 9168	01447	2024.05.17	2027.05.16
Horn Antenna	SCHWARZBECK	3115	10SL0060	2025.03.10	2028.03.09
Pre-amplifier (9kHz-1GHz)	EMtrace	RP01A	02017	2025.03.06	2026.03.05
Pre-amplifier (1-26.5G)	Agilent	8449B	3008A4722	2025.03.06	2026.03.05
Temperature & Humidity	BT-3	JINGCHUAN G	N.A	2025.03.10	2026.03.09
Testing Software	SKET	EMC-I	V1.4.0.3	N/A	N/A



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS

FREQUENCY (MHz)	Conducted Emission Limits (dBuV)			
	Class A		Class B	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.5 ~ 5	73.00	60.00	56.00	46.00
5 ~ 30	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
- (3) The test result calculated as following:
Measurement Value = Reading Level + Correct Factor
Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor
Margin Level = Measurement Value - Limit Value


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item - EUT Test Photos.


3.1.3 TEST SETUP





3.1.4 TEST RESULTS


Project: LGT26A130	Test Engineer: LiuH
EUT: Tablet	Temperature: 20.4°C
M/N: ZQC-P1	Humidity: 41%RH
Test Voltage: AC 120V/60Hz	Test Data: 2026-01-22
Test Mode: Charging+GSM link+BT+Wi-Fi+GPS+Earphone	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.154	48.66	10.78	59.44	65.78	-6.34	QP	L1
2*	0.218	40.60	10.75	51.35	62.89	-11.54	QP	L1
3*	0.442	33.35	10.89	44.24	57.02	-12.78	QP	L1
4*	1.910	28.78	11.10	39.88	56.00	-16.12	QP	L1
5*	4.678	31.13	11.30	42.43	56.00	-13.57	QP	L1
6*	10.614	31.73	11.53	43.26	60.00	-16.74	QP	L1
7*	0.154	33.62	10.78	44.40	55.78	-11.38	AV	L1
8*	0.442	22.90	10.89	33.79	47.02	-13.23	AV	L1
9*	1.262	18.23	11.04	29.27	46.00	-16.73	AV	L1
10*	2.090	17.14	11.10	28.24	46.00	-17.76	AV	L1
11*	4.442	19.12	11.27	30.39	46.00	-15.61	AV	L1
12*	10.542	19.79	11.52	31.31	50.00	-18.69	AV	L1



Project: LGT26A130	Test Engineer: LiuH
EUT: Tablet	Temperature: 20.4°C
M/N: ZQC-P1	Humidity: 41%RH
Test Voltage: AC 120V/60Hz	Test Data: 2026-01-22
Test Mode: Charging+GSM link+BT+Wi-Fi+GPS+Earphone	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.166	48.33	10.64	58.97	65.16	-6.19	QP	N
2*	0.446	33.00	10.83	43.83	56.95	-13.12	QP	N
3*	2.290	26.47	11.17	37.64	56.00	-18.36	QP	N
4*	4.750	30.64	11.30	41.94	56.00	-14.06	QP	N
5*	7.026	29.55	11.40	40.95	60.00	-19.05	QP	N
6*	10.674	32.18	11.52	43.70	60.00	-16.30	QP	N
7*	0.166	32.22	10.64	42.86	55.16	-12.30	AV	N
8*	0.434	24.32	10.82	35.14	47.18	-12.04	AV	N
9*	1.530	15.84	11.10	26.94	46.00	-19.06	AV	N
10*	4.450	17.80	11.29	29.09	46.00	-16.91	AV	N
11*	6.798	17.58	11.39	28.97	50.00	-21.03	AV	N
12*	12.090	19.23	11.56	30.79	50.00	-19.21	AV	N



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS

Below 1 GHz

Frequency (MHz)	Class A	Class B
	Field strength (dBuV/m) (at 3m)	Field strength (dBuV/m) (at 3m)
30 - 88	49.5	40
88 - 216	53.9	43.5
216 - 960	56.9	46
Above 960	60	54

Above 1 GHz

Frequency (MHz)	Class A		Class B	
	Field strength (dBuV/m) (at 3m)		Field strength (dBuV/m) (at 3m)	
	Peak	Average	Peak	Average
Above 1000	80	60	74	54

Frequency Range of Radiated Disturbance Measurement

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 - 108	1000
108 - 500	2000
500 - 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

Note:


- (1) The limit for radiated test was performed according to FCC Part 15, Subpart B;
- (2) The tighter limit applies at the band edges;
- (3) The test result calculated as following:
Measurement Value = Reading Level + Correct Factor,
Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use),
Margin Level = Measurement Value - Limit Value.

3.2.2 TEST PROCEDURE


- a. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. EUT as the center to the edge of the auxiliary device, the distance from the maximum edge to the center of the antenna is 3 meter.
- c. The height of antenna is varied from 1 meter to 4 meter above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meter and the rotatable table was turned from 0 degrees to 360 degree to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.2.3 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz







3.2.4 TEST RESULTS

BELOW 1GHZ

Project: LGT26A130	Test Engineer: zhangchengxiang
EUT: Tablet	Temperature: 24.2°C
M/N: ZQC-P1	Humidity: 50%RH
Test Voltage: AC 120V/60Hz	Test Data: 2026-01-22
Test Mode: Charging+GSM link+BT+Wi-Fi+GPS+Earphone	
Note:	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	37.518	3.08	20.05	23.13	40.00	-16.87	QP	Hor
2*	58.615	3.94	19.86	23.80	40.00	-16.20	QP	Hor
3*	157.313	2.76	22.25	25.01	43.50	-18.49	QP	Hor
4*	377.624	2.83	24.40	27.23	46.00	-18.77	QP	Hor
5*	628.248	3.97	29.95	33.92	46.00	-12.08	QP	Hor
6*	940.224	5.24	34.59	39.83	46.00	-6.17	QP	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	33.638	2.15	19.81	21.96	40.00	-18.04	QP	Ver
2*	55.341	4.26	20.22	24.48	40.00	-15.52	QP	Ver
3*	145.551	3.05	21.51	24.56	43.50	-18.94	QP	Ver
4*	312.876	3.01	22.53	25.54	46.00	-20.46	QP	Ver
5*	632.855	4.37	29.98	34.35	46.00	-11.65	QP	Ver
6*	941.800	4.64	34.69	39.33	46.00	-6.67	QP	Ver



Project: LGT26A130	Test Engineer: zhangchengxiang
EUT: Tablet	Temperature: 24.2°C
M/N: ZQC-P1	Humidity: 50%RH
Test Voltage: Battery	Test Data: 2026-01-22
Test Mode: USB Data Transmission	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	35.456	2.71	19.85	22.56	40.00	-17.44	QP	Hor
2*	45.156	2.22	20.70	22.92	40.00	-17.08	QP	Hor
3*	143.975	2.76	21.66	24.42	43.50	-19.08	QP	Hor
4*	302.691	3.33	22.09	25.42	46.00	-20.58	QP	Hor
5*	672.868	5.02	30.54	35.56	46.00	-10.44	QP	Hor
6*	963.868	4.68	34.81	39.49	54.00	-14.51	QP	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	32.789	2.48	19.67	22.15	40.00	-17.85	QP	Ver
2*	45.763	3.83	20.70	24.53	40.00	-15.47	QP	Ver
3*	139.610	4.50	21.39	25.89	43.50	-17.61	QP	Ver
4*	332.276	1.30	23.27	24.57	46.00	-21.43	QP	Ver
5*	653.104	4.33	30.43	34.76	46.00	-11.24	QP	Ver
6*	988.966	3.07	35.13	38.20	54.00	-15.80	QP	Ver




ABOVE 1GHZ

Project: LGT26A130	Test Engineer: zhangchengxiang
EUT: Tablet	Temperature: 24.2°C
M/N: ZQC-P1	Humidity: 50%RH
Test Voltage: AC 120V/60Hz	Test Data: 2026-01-22
Test Mode: Charging+GSM link+BT+Wi-Fi+GPS+Earphone	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.2699GHz	63.18	-22.44	40.74	74.00	-33.26	PK	Hor
2*	4.0260GHz	54.53	-7.58	46.95	74.00	-27.05	PK	Hor
3*	5.4200GHz	57.16	-7.59	49.57	74.00	-24.43	PK	Hor
4*	8.5629GHz	60.36	-7.43	52.93	74.00	-21.07	PK	Hor
5*	11.2212GHz	57.42	-5.06	52.36	74.00	-21.64	PK	Hor
6*	17.9766GHz	55.86	-2.93	52.93	74.00	-21.07	PK	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1144.5000	61.24	-23.75	37.49	74.00	-36.51	PK	Ver
2*	2933.7000	55.17	-8.39	46.78	74.00	-27.22	PK	Ver
3*	4980.1000	54.29	-5.99	48.30	74.00	-25.70	PK	Ver
4*	7540.7000	57.14	-7.07	50.07	74.00	-23.93	PK	Ver
5*	9604.1000	55.51	-7.20	48.31	74.00	-25.69	PK	Ver
6*	14974.0000	53.90	-3.92	49.98	74.00	-24.02	PK	Ver

APPENDIX I - TEST SETUP

Set-up for Conducted Emission on AC Mains (CE)



Set-up for Radiated Emission (RE), Below 1GHz



Set-up for Radiated Emission (RE), Above 1GHz



APPENDIX II - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

Photo 1



Photo 2



Photo 3




Photo 4




Photo 5




Photo 6




Photo 7




Photo 8




Photo 9




Photo 10



Photo 13



Photo 14



Photo 15




Photo 16



Photo 17



Photo 18




Photo 19




Photo 20




Photo 21




Photo 22




Photo 23





Photo 24



*****END OF THE REPORT*****