Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

Test Report

Report No. :	CQASZ20231202159E-01
Applicant:	DongguanBEIGEElectronics
Address of Applicant:	Qiaotou Town, Dongguan City, Qiaoxin West Road No. 10
Equipment Under Test (EUT):	
Product:	WIRELESS CONTROLLER
Model No.:	BG-04, BG04 Pro, BG-5
Test Model No.:	BG-04
Brand Name:	N/A
FCC ID:	2BDVX-BG-04
Standards:	47 CFR Part 15, Subpart C
Date of Receipt:	2023-12-1
Date of Test:	2023-12-1 to 2023-12-11
Date of Issue:	2023-12-13
Test Result :	**PASS***

***In the configuration tested, the EUT complied with the standards specified above.**

Tested By: lewis zhou

(Lewis Zhou)

Reviewed By: Timo Lei

(Timo Lei)

Approved By:

(Jack Ai)

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20231202159E-01	Rev.01	Initial report	2023-12-13

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15.203	/	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10-2013	PASS
Conducted Peak Output Power	47 CFR Part 15.247	ANSI C63.10-2013	PASS
20dB Occupied Bandwidth	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Carrier Frequencies Separation	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Hopping Channel Number	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Dwell Time	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15.247	ANSI C63.10-2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Radiated Spurious emissions	47 CFR Part 15.209	ANSI C63.10-2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15.205/15.209	ANSI C63.10-2013	PASS

Remark:
The tested sample(s) and the sample information are provided by the client.
Tx: In this whole report Tx (or tx) means Transmitter.
Rx: In this whole report Rx (or rx) means Receiver.
RF: In this whole report RF means Radiated Frequency.
CH: In this whole report CH means channel.
Volt: In this whole report Volt means Voltage.
Temp: In this whole report Temp means Temperature.
Humid: In this whole report Humid means humidity.
Press: In this whole report Press means Pressure.
N/A: In this whole report not application

3 Contents

Page

1 VERSION **2**

2 TEST SUMMARY **3**

3 CONTENTS **4**

4 GENERAL INFORMATION **5**

4.1 CLIENT INFORMATION 5
4.2 GENERAL DESCRIPTION OF EUT 5
4.3 ADDITIONAL INSTRUCTIONS 7
4.4 TEST ENVIRONMENT 8
4.5 DESCRIPTION OF SUPPORT UNITS 8
4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY 9
4.7 TEST LOCATION 10
4.8 TEST FACILITY 10
4.9 ABNORMALITIES FROM STANDARD CONDITIONS 10
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER 10
4.11 EQUIPMENT LIST 11

5 TEST RESULTS AND MEASUREMENT DATA **12**

5.1 ANTENNA REQUIREMENT 12
5.2 CONDUCTED EMISSIONS 13
5.3 CONDUCTED PEAK OUTPUT POWER 17
5.4 20DB OCCUPIED BANDWIDTH 24
5.5 CARRIER FREQUENCIES SEPARATION 30
5.6 HOPPING CHANNEL NUMBER 34
5.7 DWELL TIME 37
5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS 48
5.9 SPURIOUS RF CONDUCTED EMISSIONS 56
5.10 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM 71
5.11 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS 73
5.11.1 Radiated Emission below 1GHz *76*
5.11.2 Transmitter Emission above 1GHz *78*

6 PHOTOGRAPHS - EUT TEST SETUP **81**

6.1 RADIATED EMISSION 81
6.2 CONDUCTED EMISSION 82

7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS **83**

4 General Information

4.1 Client Information

Applicant:	DongguanBEIGEElectronics
Address of Applicant:	Qiaotou Town, Dongguan City, Qiaoxin West Road No. 10
Manufacturer:	DongguanBEIGEElectronics
Address of Manufacturer:	Qiaotou Town, Dongguan City, Qiaoxin West Road No. 10
Factory:	DongguanBEIGEElectronics
Address of Factory:	Qiaotou Town, Dongguan City, Qiaoxin West Road No. 10

4.2 General Description of EUT

Product Name:	WIRELESS CONTROLLER
Model No.:	BG-04, BG04 Pro, BG-5
Test Model No.:	BG-04
Trade Mark:	N/A
Software Version:	V1.0
Hardware Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	☐ Mobile ☒ Portable
Test Software of EUT:	FCC Assist 1.0.1.1
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	3.7V lithium battery 600mAh,Power DC 5V for adapter
Simultaneous Transmission	☐ Simultaneous TX is supported and evaluated in this report. ☒ Simultaneous TX is not supported.

Model No.:BG-04, BG04 Pro, BG-5

The circuit design, layout, components used and internal wiring are all the same, except for the color difference

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

4.3 Additional Instructions

EUT Test Software Settings:	
Mode:	☒ Special software is used. ☐ Through engineering command into the engineering mode. engineering command: *#*#3646633#*#*
EUT Power level:	(Power level is built-in set parameters and cannot be changed and selected)

Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

Mode	Channel	Frequency(MHz)
DH1/DH3/DH5	CH0	2402
	CH39	2441
	CH78	2480
2DH1/2DH3/2DH5	CH0	2402
	CH39	2441
	CH78	2480
3DH1/3DH3/3DH5	CH0	2402
	CH39	2441
	CH78	2480

Run Software:



4.4 Test Environment

Operating Environment:	
Temperature:	25 °C
Humidity:	54% RH
Atmospheric Pressure:	1009mbar
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	Supplied
Adapter	MI	/	/	CQA

4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty
1	Radiated Emission (Below 1GHz)	5.12dB
2	Radiated Emission (Above 1GHz)	4.60dB
3	Conducted Disturbance (0.15~30MHz)	3.34dB
4	Radio Frequency	3×10^{-8}
5	Duty cycle	0.6 %
6	Occupied Bandwidth	1.1%
7	RF conducted power	0.86dB
8	RF power density	0.74
9	Conducted Spurious emissions	0.86dB
10	Temperature test	0.8℃
11	Humidity test	2.0%
12	Supply voltages	0.5 %
13	Frequency Error	5.5 Hz

4.7 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

4.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:
IC Registration No.: 22984-1
The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L5785)**

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

- **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.9 Abnormalities from Standard Conditions

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2023/09/08	2024/09/07
Spectrum analyzer	R&S	FSU26	CQA-038	2023/09/08	2024/09/07
Spectrum analyzer	R&S	FSU40	CQA-075	2023/09/08	2024/09/07
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2023/09/08	2024/09/07
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2023/09/08	2024/09/07
Preamplifier	EMCI	EMC184055SE	CQA-089	2023/09/08	2024/09/07
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2021/09/16	2024/09/15
Bilog Antenna	R&S	HL562	CQA-011	2021/09/16	2024/09/15
Horn Antenna	R&S	HF906	CQA-012	2021/09/16	2024/09/15
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2021/09/16	2024/09/15
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2023/09/08	2024/09/07
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2023/09/08	2024/09/07
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2023/09/08	2024/09/07
Antenna Connector	CQA	RFC-01	CQA-080	2023/09/08	2024/09/07
Power Sensor	KEYSIGHT	U2021XA	CQA-30	2023/09/08	2024/09/07
N1918A Power Analysis Manager Power Panel	Agilent	N1918A	CQA-074	2023/09/08	2024/09/07
Power meter	R&S	NRVD	CQA-029	2023/09/08	2024/09/07
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2023/09/08	2024/09/07
EMI Test Receiver	R&S	ESR7	CQA-005	2023/09/08	2024/09/07
LISN	R&S	ENV216	CQA-003	2023/09/08	2024/09/07
Coaxial cable	CQA	N/A	CQA-C009	2023/09/08	2024/09/07
DC power	KEYSIGHT	E3631A	CQA-028	2023/09/08	2024/09/07

Note:

The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is PCB antenna. **The connection/connection type between the antenna to the EUT's antenna port is: permanently attachment.** **This is either permanently attachment or a unique coupling that satisfies the requirement.**	

5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	150kHz to 30MHz
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test Procedure:

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.

Test Setup:



Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation at the lowest channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC 120V/60Hz
Test Results:	Pass

Measurement Data

Live line:



		Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.240	21.32	10.49	31.81	52.10	-20.29	Average	Line
2		0.240	26.76	10.49	37.25	62.10	-24.85	QP	Line
3		0.340	20.16	10.50	30.66	49.20	-18.54	Average	Line
4		0.340	25.82	10.50	36.32	59.20	-22.88	QP	Line
5		0.585	20.19	10.67	30.86	46.00	-15.14	Average	Line
6		0.585	26.50	10.67	37.17	56.00	-18.83	QP	Line
7		0.760	19.10	10.80	29.90	46.00	-16.10	Average	Line
8		0.760	24.50	10.80	35.30	56.00	-20.70	QP	Line
9		1.055	19.68	10.53	30.21	46.00	-15.79	Average	Line
10		1.055	24.85	10.53	35.38	56.00	-20.62	QP	Line
11	PP	1.375	21.85	10.53	32.38	46.00	-13.62	Average	Line
12	QP	1.375	27.44	10.53	37.97	56.00	-18.03	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



		Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.260	20.99	10.53	31.52	51.43	-19.91	Average	Neutral
2		0.260	26.27	10.53	36.80	61.43	-24.63	QP	Neutral
3		0.440	19.42	10.64	30.06	47.06	-17.00	Average	Neutral
4		0.440	24.58	10.64	35.22	57.06	-21.84	QP	Neutral
5		0.535	19.32	10.73	30.05	46.00	-15.95	Average	Neutral
6		0.535	24.55	10.73	35.28	56.00	-20.72	QP	Neutral
7		0.800	18.91	10.83	29.74	46.00	-16.26	Average	Neutral
8		0.800	24.23	10.83	35.06	56.00	-20.94	QP	Neutral
9	PP	1.170	19.95	10.71	30.66	46.00	-15.34	Average	Neutral
10		1.170	24.86	10.71	35.57	56.00	-20.43	QP	Neutral
11		1.340	19.53	10.72	30.25	46.00	-15.75	Average	Neutral
12	QP	1.340	25.15	10.72	35.87	56.00	-20.13	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	***Setup for Power meter measurement method***  ***Setup for Spectrum analyser measurement method***  *Remark: Offset=Cable loss+ attenuation factor.*
Limit:	21dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

Test Mode	Antenna	Freq (MHz)	Conducted Peak Powert [dBm]	Conducted Limit [dBm]	Verdict
DH5	Ant1	2402	0.16	≤30	PASS
		2441	0.37	≤30	PASS
		2480	-1.17	≤30	PASS
2DH5	Ant1	2402	2.56	≤30	PASS
		2441	2.81	≤30	PASS
		2480	1.11	≤30	PASS
3DH5	Ant1	2402	3.07	≤30	PASS
		2441	3.43	≤30	PASS
		2480	1.73	≤30	PASS

Test plot as follows:

DH5_Ant1_2402



DH5_Ant1_2441



DH5_Ant1_2480



2DH5_Ant1_2402



2DH5_Ant1_2441



2DH5_Ant1_2480



3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



5.4 20dB Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

Test channel	20dB Occupy Bandwidth (MHz)		
	GFSK	π/4DQPSK	8DPSK
Lowest	0.90	1.29	1.31
Middle	0.90	1.31	1.31
Highest	0.90	1.31	1.31

Test plot as follows:

DH5_Ant1_2402



DH5_Ant1_2441



DH5_Ant1_2480



2DH5_Ant1_2402



2DH5_Ant1_2441



2DH5_Ant1_2480



3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



5.5 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

TestMode	Freq(MHz)	Result[MHz]	Limit[MHz]	Verdict
DH5	Hop	1.003	≥0.6	PASS
2DH5	Hop	1	≥0.873	PASS
3DH5	Hop	1	≥0.873	PASS

Mode	20dB bandwidth (MHz) (worse case)	Limit (MHz) (Carrier Frequencies Separation)
GFSK	0.9	≥0.6
π/4DQPSK	1.31	≥0.873
8DPSK	1.31	≥0.873

Test plot as follows:

DH5_Ant1_Hop

2DH5_Ant1_Hop



3DH5_Ant1_Hop

5.6 Hopping Channel Number

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 *Remark: Offset=Cable loss+ attenuation factor.*
Limit:	At least 15 channels
Exploratory Test Mode:	hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

TestMode	Freq(MHz)	Result[Num]	Limit[Num]	Verdict
DH5	Hop	79	≥15	PASS
2DH5	Hop	79	≥15	PASS
3DH5	Hop	79	≥15	PASS

Test plot as follows:

DH5_Ant1_Hop



2DH5_Ant1_Hop



3DH5_Ant1_Hop



5.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 *Remark: Offset=Cable loss+ attenuation factor.*
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass

Measurement Data

TestMode	Freq(MHz)	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Hop	0.394	330	0.13	≤0.4	PASS
DH3	Hop	1.641	170	0.279	≤0.4	PASS
DH5	Hop	2.882	130	0.375	≤0.4	PASS
2DH1	Hop	0.401	330	0.132	≤0.4	PASS
2DH3	Hop	1.645	170	0.28	≤0.4	PASS
2DH5	Hop	2.887	90	0.26	≤0.4	PASS
3DH1	Hop	0.403	320	0.129	≤0.4	PASS
3DH3	Hop	1.645	110	0.181	≤0.4	PASS
3DH5	Hop	2.889	120	0.347	≤0.4	PASS

Remark:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

Test plot as follows:

DH1_Ant1_Hop



DH3_Ant1_Hop
 Spectrum Ref Level 20.73 dBm Offset 10.73 dB RBW 1 MHz Att 20 dB SWT 10 ms VBW 3 MHz SGL Count 1/1 TRG: VID 1Pk Clrw M1[1] -23.76 dBm -13.50 µs D2[1] 23.80 dB 1.64100 ms TRG -1.670 dBm CF 2.441 GHz 8000 pts 1.0 ms/ Date: 5.DEC.2023 10:27:28
 Spectrum Ref Level 20.73 dBm Offset 10.73 dB RBW 500 kHz Att 20 dB SWT 3.2 s VBW 3 MHz SGL Count 1/1 TRG: VID 1Pk Clrw TRG -1.670 dBm CF 2.441 GHz 30000 pts 316.0 ms/ Date: 5.DEC.2023 10:27:34

DH5_Ant1_Hop
 Spectrum Ref Level 20.73 dBm Offset 10.73 dB RBW 1 MHz Att 20 dB SWT 10 ms VBW 3 MHz SGL Count 1/1 TRG: VID 1Pk Clrw M1[1] -23.42 dBm -13.50 µs D2[1] 23.40 dB 2.88200 ms TRG -1.770 dBm CF 2.441 GHz 8000 pts 1.0 ms/ Date: 5.DEC.2023 10:25:27
 Spectrum Ref Level 20.73 dBm Offset 10.73 dB RBW 500 kHz Att 20 dB SWT 3.2 s VBW 3 MHz SGL Count 1/1 TRG: VID 1Pk Clrw TRG -1.770 dBm CF 2.441 GHz 30000 pts 316.0 ms/ Date: 5.DEC.2023 10:25:33

2DH1_Ant1_Hop





2DH3_Ant1_Hop



2DH5_Ant1_Hop



3DH1_Ant1_Hop



3DH3_Ant1_Hop



3DH5_Ant1_Hop



5.8 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 *Remark: Offset=cable loss+ attenuation factor.*
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

TestMode	ChName	Freq(MHz)	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Low	2402	0.06	-54.46	≤-19.94	PASS
	High	2480	-1.28	-56.09	≤-21.28	PASS
	Low	Hop_2402	-0.72	-57.8	≤-20.72	PASS
	High	Hop_2480	-0.88	-56.71	≤-20.88	PASS
2DH5	Low	2402	-0.10	-55.45	≤-20.1	PASS
	High	2480	-1.49	-56.66	≤-21.49	PASS
	Low	Hop_2402	0.04	-56.62	≤-19.96	PASS
	High	Hop_2480	-1.00	-56.38	≤-21	PASS
3DH5	Low	2402	0.05	-50.28	≤-19.95	PASS
	High	2480	-1.32	-56.53	≤-21.32	PASS
	Low	Hop_2402	-0.84	-57.57	≤-20.84	PASS
	High	Hop_2480	-1.04	-56.27	≤-21.04	PASS

Test plot as follows:

DH5_Ant1_Low_2402



DH5_Ant1_High_2480



DH5_Ant1_Low_Hop_2402



DH5_Ant1_High_Hop_2480



2DH5_Ant1_Low_2402



2DH5_Ant1_High_2480



2DH5_Ant1_Low_Hop_2402



2DH5_Ant1_High_Hop_2480



3DH5_Ant1_Low_2402



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.402015 GHz	0.05 dBm		
M2		1	2.4 GHz	-49.94 dBm		
M3		1	2.39 GHz	-61.03 dBm		
M4		1	2.3999783 GHz	-50.28 dBm		

3DH5_Ant1_High_2480



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.48001 GHz	-1.32 dBm		
M2		1	2.4835 GHz	-60.11 dBm		
M3		1	2.5 GHz	-60.56 dBm		
M4		1	2.506406 GHz	-56.53 dBm		

3DH5_Ant1_Low_Hop_2402



3DH5_Ant1_High_Hop_2480



5.9 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 *Remark: Offset=cable loss+ attenuation factor.*
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of π/4DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Test Results:	Pass

DH5_Ant1_2402_0~Reference

DH5_Ant1_2402_30~1000



DH5_Ant1_2402_1000~26500



DH5_Ant1_2441_0~Reference



DH5_Ant1_2441_30~1000



DH5_Ant1_2441_1000~26500



DH5_Ant1_2480_0~Reference



DH5_Ant1_2480_30~1000



DH5_Ant1_2480_1000~26500



2DH5_Ant1_2402_0~Reference



2DH5_Ant1_2402_30~1000



2DH5_Ant1_2402_1000~26500



2DH5_Ant1_2441_0~Reference



2DH5_Ant1_2441_30~1000



2DH5_Ant1_2441_1000~26500



2DH5_Ant1_2480_0~Reference



2DH5_Ant1_2480_30~1000



2DH5_Ant1_2480_1000~26500



3DH5_Ant1_2402_0~Reference



3DH5_Ant1_2402_30~1000



3DH5_Ant1_2402_1000~26500



3DH5_Ant1_2441_0~Reference



3DH5_Ant1_2441_30~1000



3DH5_Ant1_2441_1000~26500



3DH5_Ant1_2480_0~Reference



3DH5_Ant1_2480_30~1000



3DH5_Ant1_2480_1000~26500



Remark:

Pre test 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.10 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage
outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 2^9 -1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)
According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels. According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

5.11 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205
Test Method:	ANSI C63.10: 2013
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Peak	120 kHz	300kHz	Peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Test Setup:	



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

Test Procedure:	a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

5.11.1 Radiated Emission below 1GHz

30MHz~1GHz		
Test mode:	Transmitting	Vertical



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	31.51	13.18	15.52	28.70	40.00	-11.30	Peak	VERTICAL
2	36.00	13.13	14.24	27.37	40.00	-12.63	Peak	VERTICAL
3	97.46	10.83	10.49	21.32	43.50	-22.18	Peak	VERTICAL
4	329.04	10.20	14.44	24.64	46.00	-21.36	Peak	VERTICAL
5	501.18	13.08	18.29	31.37	46.00	-14.63	Peak	VERTICAL
6 pp	866.09	10.82	23.98	34.80	46.00	-11.20	Peak	VERTICAL

Remark:
The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Factor= Antenna Factor + Cable Factor – Preamplifier Factor,
Level = Read Level + Factor,
Over Limit=Level-Limit Line.

Test mode:	Transmitting	Horizontal



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	33.68	9.93	14.96	24.89	40.00	-15.11	Peak	HORIZONTAL
2	82.07	10.51	9.83	20.34	40.00	-19.66	Peak	HORIZONTAL
3	102.00	10.50	10.55	21.05	43.50	-22.45	Peak	HORIZONTAL
4	151.60	10.76	8.36	19.12	43.50	-24.38	Peak	HORIZONTAL
5	511.84	10.80	18.41	29.21	46.00	-16.79	Peak	HORIZONTAL
6 pp	869.13	10.32	23.97	34.29	46.00	-11.71	Peak	HORIZONTAL

Remark:
The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Factor= Antenna Factor + Cable Factor – Preamplifier Factor,
Level = Read Level + Factor,
Over Limit=Level-Limit Line.

5.11.2 Transmitter Emission above 1GHz

Worse case mode:		GFSK(DH5)		Test channel:		Lowest	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
2390	55.70	-9.2	46.50	74	-27.50	**Peak**	**H**
2400	56.98	-9.39	47.59	74	-26.41	Peak	H
4804	53.23	-4.33	48.90	74	-25.10	Peak	H
7206	49.97	1.01	50.98	74	-23.02	Peak	H
2390	55.40	-9.2	46.20	74	-27.80	**Peak**	**V**
2400	57.11	-9.39	47.72	74	-26.28	Peak	V
4804	54.89	-4.33	50.56	74	-23.44	Peak	V
7206	50.13	1.01	51.14	74	-22.86	Peak	V

Worse case mode:		GFSK(DH5)		Test channel:		Middle	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
4882	51.82	-4.11	47.71	74	-26.29	peak	H
7323	50.21	1.51	51.72	74	-22.28	peak	H
4882	52.81	-4.11	48.70	74	-25.30	peak	V
7323	50.00	1.51	51.51	74	-22.49	peak	V

Worse case mode:		GFSK(DH5)		Test channel:		Highest	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
2483.5	55.45	-9.29	46.16	74	-27.84	**Peak**	**H**
4960	51.58	-4.04	47.54	74	-26.46	Peak	H
7440	49.32	1.57	50.89	74	-23.11	Peak	H
2483.5	55.69	-9.29	46.40	74	-27.60	**Peak**	**V**
4960	50.38	-4.04	46.34	74	-27.66	Peak	V
7440	50.17	1.57	51.74	74	-22.26	Peak	V

Worse case mode:		π /4DQPSK (2DH5)		Test channel:		Lowest	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
2390	55.46	-9.2	46.26	74	-27.74	**Peak**	**H**
2400	56.25	-9.39	46.86	74	-27.14	Peak	H
4804	54.10	-4.33	49.77	74	-24.23	Peak	H
7206	48.49	1.01	49.50	74	-24.50	Peak	H
2390	55.22	-9.2	46.02	74	-27.98	**Peak**	**V**
2400	56.67	-9.39	47.28	74	-26.72	Peak	V
4804	53.38	-4.33	49.05	74	-24.95	Peak	V
7206	51.07	1.01	52.08	74	-21.92	Peak	V

Worse case mode:		π /4DQPSK (2DH5)		Test channel:		Middle	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
4882	51.00	-4.11	46.89	74	-27.11	peak	H
7323	50.64	1.51	52.15	74	-21.85	peak	H
4882	51.28	-4.11	47.17	74	-26.83	peak	V
7323	48.58	1.51	50.09	74	-23.91	peak	V

Worse case mode:		π /4DQPSK (2DH5)		Test channel:		Highest	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
2483.5	56.16	-9.29	46.87	74	-27.13	**Peak**	**H**
4960	53.12	-4.04	49.08	74	-24.92	Peak	H
7440	49.20	1.57	50.77	74	-23.23	Peak	H
2483.5	55.49	-9.29	46.20	74	-27.80	**Peak**	**V**
4960	50.42	-4.04	46.38	74	-27.62	Peak	V
7440	50.56	1.57	52.13	74	-21.87	Peak	V

Worse case mode:		8DPSK (3DH5)		Test channel:		Lowest	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
2390	53.42	-9.2	44.22	74	-29.78	**Peak**	**H**
2400	56.72	-9.39	47.33	74	-26.67	Peak	H
4804	54.15	-4.33	49.82	74	-24.18	Peak	H
7206	49.67	1.01	50.68	74	-23.32	Peak	H
2390	54.02	-9.2	44.82	74	-29.18	**Peak**	**V**
2400	55.28	-9.39	45.89	74	-28.11	Peak	V
4804	53.73	-4.33	49.40	74	-24.60	Peak	V
7206	49.09	1.01	50.10	74	-23.90	Peak	V

Worse case mode:		8DPSK (3DH5)		Test channel:		Middle	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
4882	51.10	-4.11	46.99	74	-27.01	peak	H
7323	50.83	1.51	52.34	74	-21.66	peak	H
4882	52.36	-4.11	48.25	74	-25.75	peak	V
7323	49.24	1.51	50.75	74	-23.25	peak	V

Worse case mode:		8DPSK (3DH5)		Test channel:		Highest	
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
2483.5	54.54	-9.29	45.25	74	-28.75	**Peak**	**H**
4960	50.94	-4.04	46.90	74	-27.10	Peak	H
7440	49.12	1.57	50.69	74	-23.31	Peak	H
2483.5	54.18	-9.29	44.89	74	-29.11	**Peak**	**V**
4960	48.85	-4.04	44.81	74	-29.19	Peak	V
7440	49.62	1.57	51.19	74	-22.81	Peak	V

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

   Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6 Photographs - EUT Test Setup

6.1 Radiated Emission

9KHz~30MHz:



30MHz~1GHz:



Above 1GHz:



6.2 Conducted Emission

7 Photographs - EUT Constructional Details

Made in China
撸尺

Made in China
撸尺

OPTIONS
SHARE
CM 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
Made in China
撸尺

CM 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
Made in China
撸尺


CM
Made in China
撸尺





*** END OF REPORT ***