

FCC Radio Test Report

FCC ID: 2BDWL2417250

Report No. : BTL-FCCP-1-2407E004
Equipment : TELUS Outdoor Camera
Model Name : OCF
Brand Name : TELUS
Applicant : TELUS Communications Inc.
Address : 7th Floor, 510 West Georgia Street, Vancouver, BC, V6B0M3 Canada

Radio Function : Bluetooth Low Energy (5.0)

FCC Rule Part(s) : FCC CFR Title 47, Part 15, Subpart C (15.247)
Measurement Procedure(s) : ANSI C63.10-2013

Date of Receipt : 2024/8/12
Date of Test : 2024/8/13 ~ 2024/9/4
Issued Date : 2024/9/6

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

Prepared by :

Poken Huang

Poken Huang, Engineer

Approved by :

Peter Chen

Peter Chen, Manager



BTL Inc.

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299 Fax: +886-2-2657-3331 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** assumes no responsibility for the data provided by the Customer, any statements, inferences or generalizations drawn by the customer or others from the reports issued by **BTL**.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

CONTENTS

REVISION HISTORY	5
1 SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST ENVIRONMENT CONDITIONS	7
1.4 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	8
2 GENERAL INFORMATION	9
2.1 DESCRIPTION OF EUT	9
2.2 TEST MODES	11
2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
2.4 SUPPORT UNITS	13
3 AC POWER LINE CONDUCTED EMISSIONS TEST	14
3.1 LIMIT	14
3.2 TEST PROCEDURE	14
3.3 DEVIATION FROM TEST STANDARD	14
3.4 TEST SETUP	15
3.5 TEST RESULT	15
4 RADIATED EMISSIONS TEST	16
4.1 LIMIT	16
4.2 TEST PROCEDURE	17
4.3 DEVIATION FROM TEST STANDARD	17
4.4 TEST SETUP	18
4.5 EUT OPERATING CONDITIONS	19
4.6 TEST RESULT – BELOW 30 MHZ	19
4.7 TEST RESULT – 30 MHZ TO 1 GHZ	19
4.8 TEST RESULT – ABOVE 1 GHZ	19
5 BANDWIDTH TEST	20
5.1 APPLIED PROCEDURES / LIMIT	20
5.2 TEST PROCEDURE	20
5.3 DEVIATION FROM STANDARD	20
5.4 TEST SETUP	20
5.5 EUT OPERATION CONDITIONS	20
5.6 TEST RESULTS	20
6 MAXIMUM OUTPUT POWER TEST	21
6.1 APPLIED PROCEDURES / LIMIT	21
6.2 TEST PROCEDURE	21
6.3 DEVIATION FROM STANDARD	21
6.4 TEST SETUP	21
6.5 EUT OPERATION CONDITIONS	21
6.6 TEST RESULTS	21
7 POWER SPECTRAL DENSITY TEST	22
7.1 APPLIED PROCEDURES / LIMIT	22
7.2 TEST PROCEDURE	22
7.3 DEVIATION FROM STANDARD	22
7.4 TEST SETUP	22
7.5 EUT OPERATION CONDITIONS	22
7.6 TEST RESULTS	22

8	ANTENNA CONDUCTED SPURIOUS EMISSION	23
8.1	APPLIED PROCEDURES / LIMIT	23
8.2	TEST PROCEDURE	23
8.3	DEVIATION FROM STANDARD	23
8.4	TEST SETUP	23
8.5	EUT OPERATION CONDITIONS	23
8.6	TEST RESULTS	23
9	LIST OF MEASURING EQUIPMENTS	24
10	EUT TEST PHOTO	26
11	EUT PHOTOS	26
APPENDIX A	AC POWER LINE CONDUCTED EMISSIONS	27
APPENDIX B	RADIATED EMISSIONS - 30 MHZ TO 1 GHZ	30
APPENDIX C	RADIATED EMISSIONS - ABOVE 1 GHZ	33
APPENDIX D	BANDWIDTH	52
APPENDIX E	MAXIMUM OUTPUT POWER	55
APPENDIX F	POWER SPECTRAL DENSITY TEST	57
APPENDIX G	ANTENNA CONDUCTED SPURIOUS EMISSION	59

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-1-2407E004	R00	Original Report.	2024/9/6	Valid

1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards.

Standard(s) Section	Description	Test Result	Judgement	Remark
15.207	AC Power Line Conducted Emissions	APPENDIX A	Pass	-----
15.205 15.209 15.247(d)	Radiated Emissions	APPENDIX B APPENDIX C	Pass	-----
15.247(a)(2)	Bandwidth	APPENDIX D	Pass	-----
15.247(b)(3)	Maximum Output Power	APPENDIX E	Pass	-----
15.247(e)	Power Spectral Density	APPENDIX F	Pass	-----
15.247(d)	Antenna conducted Spurious Emission	APPENDIX G	Pass	-----
15.203	Antenna Requirement	-----	Pass	NOTE (3)

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report.
- (2) The report format version is TP.1.1.1.
- (3) The device what use replaceable antennas with non-standard interfaces are considered sufficient to comply with the provisions of 15.203.

1.1 TEST FACILITY

The test locations stated below are under the TAF Accreditation Number 0659.

The test location(s) used to collect the test data in this report are:

(FCC DN: TW0659)

No. 72, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

☒ CB21

☒ C06

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately 95 %.

The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2 U_{CISPR} requirement.

A. AC power line conducted emissions test:

Test Site	Method	Measurement Frequency Range	U (dB)
C06	CISPR	150 kHz ~ 30MHz	2.4498

B. Radiated emissions test:

Test Site	Measurement Frequency Range	U, (dB)
CB21	0.03 GHz ~ 0.2 GHz	4.17
	0.2 GHz ~ 1 GHz	4.72
	1 GHz ~ 6 GHz	5.20
	6 GHz ~ 18 GHz	5.50
	18 GHz ~ 26 GHz	3.69
	26 GHz ~ 40 GHz	4.23

C. Conducted test:

Test Item	U, (dB)
Occupied Bandwidth	0.53
Maximum Output Power	0.37
Power Spectral Density	0.66
Conducted Spurious emissions	0.53
Conducted Band edges	0.53

NOTE:

Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Environment Condition	Test Voltage	Tested by
AC Power Line Conducted Emissions	25°C, 45%	AC 120V	Ken Lu
Radiated emissions below 1 GHz	26°C, 59%	AC 120V	Ken Lu
Radiated emissions above 1 GHz	26°C, 61%	AC 120V	Ken Lu
Bandwidth	25°C, 69%	AC 120V	Cai Hu
Maximum Output Power	25°C, 69%	AC 120V	Cai Hu
Power Spectral Density	25°C, 69%	AC 120V	Cai Hu
Antenna conducted Spurious Emission	25°C, 69%	AC 120V	Cai Hu

1.4 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

Test Software	IPOP_V4.0			
Modulation Mode	2402 MHz	2440 MHz	2480 MHz	Data Rate
1 Mbps	DEF	DEF	DEF	1 Mbps
2 Mbps	DEF	DEF	DEF	2 Mbps

2 GENERAL INFORMATION

2.1 DESCRIPTION OF EUT

Equipment	TELUS Outdoor Camera
Brand Name	TELUS
Model Name	OCF
Model Difference(s)	N/A
Hardware Version	DVT
Software Version	v0.03.511
Power Source	DC voltage supplied from AC adapter. Model: DSA-20PDB FUS
Power Rating	I/P: 100-240V 50/60Hz 0.6A O/P: +5.0V  3.0A, +9.0V  2.22A, +12.0V  1.66A
Operation Band	2400 MHz ~ 2483.5 MHz
Operation Frequency	2402 MHz ~ 2480 MHz
Modulation Technology	GFSK
Transfer Rate	1Mbps, 2Mbps
Output Power Max.	2Mbps: 5.68 dBm (0.0037 W)

NOTE:

- (1) The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

(2) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

(3) Table for Filed Antenna:

Ant.	Manufacturer	P/N	Type	Connector	Gain (dBi)
Main	FIT Hon Teng Limited	ANTP2M1-CZZ27-EH	PIFA	N/A	3.35

- (4) The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.2 TEST MODES

Test Items	Test mode	Channel	Note
AC power line conducted emissions	Normal	-	-
Transmitter Radiated Emissions (below 1GHz)	2 Mbps	39	-
Transmitter Radiated Emissions (above 1GHz)	1/2 Mbps	00/39	Bandedge
	1/2 Mbps	00/19/39	Harmonic
Bandwidth	1/2 Mbps	00/19/39	-
Maximum Output Power	1/2 Mbps	00/19/39	-
Power Spectral Density	1/2 Mbps	00/19/39	-
Antenna conducted Spurious Emission	1/2 Mbps	00/19/39	-


NOTE:

- (1) For radiated emission band edge test, both Vertical and Horizontal are evaluated, but only the worst case (Horizontal) is recorded.
- (2) For radiated emission above 1 GHz test, the spurious points of 1GHz~26.5GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.
- (3) For radiated emissions below 1 GHz test, the 2 Mbps channel 39 is found to be the worst case and recorded.


2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Equipment letters and Cable numbers refer to item numbers described in the tables of clause 2.4.

AC power line conducted emissions



Radiated Emissions



2.4 SUPPORT UNITS

AC power line conducted emissions

Item	Equipment	Brand	Model No.	Series No.	Remarks
A	Adapter	N/A	DSA-20PDB-FUS	N/A	Supplied by test requester.

Item	Shielded	Ferrite Core	Length	Cable Type	Remarks
1	USB Cable	N	N	3m	Supplied by test requester.

Radiated Emissions

Item	Equipment	Brand	Model No.	Series No.	Remarks
A	Notebook	Lenovo	ThinkBook 14 G4 IAP	MP28KHAH	Furnished by test lab.

Item	Shielded	Ferrite Core	Length	Cable Type	Remarks
1	USB Cable	N	N	3m	Supplied by test requester.

3 AC POWER LINE CONDUCTED EMISSIONS TEST

3.1 LIMIT

Frequency (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56 *	56 - 46 *
0.50 - 5.0	56	46
5.0 - 30.0	60	50

NOTE:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
- (3) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor (if use)
 Margin Level = Measurement Value – Limit Value
 Calculation example:

Reading Level		Correct Factor		Measurement Value
38.22	+	3.45	=	41.67

Measurement Value		Limit Value		Margin Level
41.67	-	60	=	-18.33

The following table is the setting of the receiver.

Receiver Parameter	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

3.2 TEST PROCEDURE

- a. The EUT was placed 0.8 m above the horizontal ground plane with the EUT being connected to the power mains through a line impedance stabilization network (LISN).
 All other support equipment were powered from an additional LISN(s).
 The LISN provides 50 Ohm/50uH of impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle to keep the cable above 40 cm.
- c. Excess I/O cables that are not connected to a peripheral shall be bundled in the center.
 The end of the cable will be terminated, using the correct terminating impedance.
 The overall length shall not exceed 1 m.
- d. The LISN is spaced at least 80 cm from the nearest part of the EUT chassis.
- e. For the actual test configuration, please refer to the related Item – EUT TEST PHOTO.


NOTE:

- (1) In the results, each reading is marked as Peak, QP or AVG per the detector used.
 BW=9 kHz (6 dB Bandwidth)
- (2) All readings are Peak unless otherwise stated QP or AVG in column of Note. Both the QP and the AVG readings must be less than the limit for compliance.

3.3 DEVIATION FROM TEST STANDARD

No deviation.

3.4 TEST SETUP



3.5 TEST RESULT

Please refer to the **APPENDIX A**.

4 RADIATED EMISSIONS TEST

4.1 LIMIT

In case the emission fall within the restricted band specified on 15.205, then the 15.209 limit in the table below has to be followed.

LIMITS OF RADIATED EMISSIONS MEASUREMENT (9 kHz to 1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSIONS MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	Radiated Emissions (dBuV/m)		Measurement Distance (meters)
	Peak	Average	
Above 1000	74	54	3

NOTE:

- (1) The limit for radiated test was performed according to FCC CFR Title 47, Part 15, Subpart C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)
 Margin Level = Measurement Value - Limit Value
 Calculation example:

Reading Level		Correct Factor		Measurement Value
41.91	+	-8.36	=	33.55

Measurement Value		Limit Value		Margin Level
33.55	-	43.50	=	-9.95

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average

Spectrum Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

4.2 TEST PROCEDURE


- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5 m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item – EUT TEST PHOTO.

4.3 DEVIATION FROM TEST STANDARD


No deviation.


4.4 TEST SETUP

9 kHz to 30 MHz



30 MHz to 1 GHz





4.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.6 TEST RESULT – BELOW 30 MHZ

There were no emissions found below 30 MHz within 20 dB of the limit.

4.7 TEST RESULT – 30 MHZ TO 1 GHZ

Please refer to the APPENDIX B.

4.8 TEST RESULT – ABOVE 1 GHZ

Please refer to the APPENDIX C.

NOTE:

- (1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5 BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

Section	Test Item	Limit
15.247(a)(2)	6 dB Bandwidth	500 kHz


5.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6 TEST RESULTS

Please refer to the APPENDIX D.

6 MAXIMUM OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

Section	Test Item	Limit
15.247(b)(3)	Maximum Output Power	1 Watt or 30dBm


6.2 TEST PROCEDURE

- The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- The maximum peak conducted output power was performed in accordance with FCC KDB 558074 D01 15.247 Meas Guidance.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.6 TEST RESULTS

Please refer to the APPENDIX E.

7 POWER SPECTRAL DENSITY TEST

7.1 APPLIED PROCEDURES / LIMIT

Section	Test Item	Limit
15.247(e)	Power Spectral Density	8 dBm (in any 3 kHz)

7.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW=3KHz, VBW=10 KHz, Sweep time = auto.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.6 TEST RESULTS

Please refer to the APPENDIX F.

8 ANTENNA CONDUCTED SPURIOUS EMISSION

8.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time = 10 ms.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

8.6 TEST RESULTS

Please refer to the APPENDIX G.

9 LIST OF MEASURING EQUIPMENTS

AC Power Line Conducted Emissions						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Two-Line V-Network	R&S	ENV216	101051	2024/6/26	2025/6/25
2	Test Cable	EMCI	EMCRG58-BM-B M-9000	210501	2023/12/11	2024/12/10
3	EMC Receiver	Keysight	N9038A	MY54130009	2024/6/27	2025/6/26
4	Measurement Software	Farad	EZ_EMC (Ver. NB-03A1-01)	N/A	N/A	N/A

Radiated Emissions Below 1GHz						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Log-bicon Antenna	Schwarzbeck	VULB9168	1369	2024/6/14	2025/6/13
2	EXA Spectrum Analyzer	keysight	N9020B	MY57120120	2024/2/23	2025/2/22
3	Pre-Amplifier	EMCI	EMC330N	980850	2023/9/6	2024/9/5
4	Test Cable	EMCI	EMC104-SM-1000	180809	2024/3/8	2025/3/8
5	Test Cable	EMCI	EMC104-SM-SM-3000	220322	2024/3/8	2025/3/8
6	Test Cable	EMCI	EMC104-SM-SM-7000	220324	2024/3/8	2025/3/8
7	Measurement Software	Farad	EZ_EMC (Ver. NB-03A1-01)	N/A	N/A	N/A

Radiated Emissions Above 1 GHz						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Pre-Amplifier	EMCI	EMC118A45SE	980819	2024/3/6	2025/3/5
2	Test Cable	EMCI	EMC104-SM-1000	180809	2024/3/8	2025/3/8
3	Test Cable	EMCI	EMC104-SM-SM-3000	220322	2024/3/8	2025/3/8
4	Test Cable	EMCI	EMC104-SM-SM-7000	220324	2024/3/8	2025/3/8
5	Horn Ant	Schwarzbeck	BBHA 9170D	1136	2024/5/17	2025/5/17
6	Pre-Amplifier	EMCI	EMC184045SE	980907	2023/9/21	2024/9/20
7	Test Cable	EMCI	EMC101G-KM-K M-3000	220329	2024/3/13	2025/3/13
8	Test Cable	EMCI	EMC102-KM-KM-1000	220327	2024/3/13	2025/3/13
9	EXA Spectrum Analyzer	keysight	N9020B	MY57120120	2024/2/23	2025/2/22
10	Measurement Software	Farad	EZ_EMC (Ver. NB-03A1-01)	N/A	N/A	N/A

Bandwidth						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSP 30	100854	2024/6/27	2025/6/26
2	10dbAttenuator	INMET	AHC-10dB	1	N/A	N/A
3	BTL-Conducted Test	N/A	1247788684	N/A	N/A	N/A

Maximum Output Power						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSP 30	100854	2024/6/27	2025/6/26
2	10dbAttenuator	INMET	AHC-10dB	1	N/A	N/A
3	BTL-Conducted Test	N/A	1247788684	N/A	N/A	N/A

Power Spectral Density						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSP 30	100854	2024/6/27	2025/6/26
2	10dbAttenuator	INMET	AHC-10dB	1	N/A	N/A
3	BTL-Conducted Test	N/A	1247788684	N/A	N/A	N/A

Antenna conducted Spurious Emission						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSP 30	100854	2024/6/27	2025/6/26
2	10dbAttenuator	INMET	AHC-10dB	1	N/A	N/A
3	BTL-Conducted Test	N/A	1247788684	N/A	N/A	N/A

Remark: "N/A" denotes no model name, no serial no. or no calibration specified.
All calibration period of equipment list is one year.

10 EUT TEST PHOTO


Please refer to document Appendix No.: TP-2407E004-FCCP-1 (APPENDIX-TEST PHOTOS).

11 EUT PHOTOS

Please refer to document Appendix No.: EP-2407E004-1 (APPENDIX-EUT PHOTOS).

APPENDIX A AC POWER LINE CONDUCTED EMISSIONS

Test Mode	Normal	Tested Date	2024/8/14
Test Frequency	-	Phase	Line




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1790	27.85	9.64	37.49	64.53	-27.04	QP	
2		0.1790	23.67	9.64	33.31	54.53	-21.22	AVG	
3		0.2298	26.12	9.64	35.76	62.46	-26.70	QP	
4		0.2298	23.04	9.64	32.68	52.46	-19.78	AVG	
5		0.2602	25.62	9.64	35.26	61.43	-26.17	QP	
6		0.2602	22.76	9.64	32.40	51.43	-19.03	AVG	
7		0.4398	32.73	9.66	42.39	57.07	-14.68	QP	
8	*	0.4398	25.71	9.66	35.37	47.07	-11.70	AVG	
9		0.8285	24.85	9.69	34.54	56.00	-21.46	QP	
10		0.8285	22.33	9.69	32.02	46.00	-13.98	AVG	
11		1.1975	24.55	9.72	34.27	56.00	-21.73	QP	
12		1.1975	22.30	9.72	32.02	46.00	-13.98	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	Normal	Tested Date	2024/8/14
Test Frequency	-	Phase	Neutral




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1801	27.82	9.63	37.45	64.48	-27.03	QP	
2	0.1801	23.67	9.63	33.30	54.48	-21.18	AVG	
3	0.2574	25.60	9.63	35.23	61.51	-26.28	QP	
4	0.2574	22.77	9.63	32.40	51.51	-19.11	AVG	
5	0.4430	30.55	9.64	40.19	57.01	-16.82	QP	
6 *	0.4430	23.96	9.64	33.60	47.01	-13.41	AVG	
7	0.5495	23.77	9.64	33.41	56.00	-22.59	QP	
8	0.5495	22.09	9.64	31.73	46.00	-14.27	AVG	
9	0.9635	23.30	9.69	32.99	56.00	-23.01	QP	
10	0.9635	22.11	9.69	31.80	46.00	-14.20	AVG	
11	1.3640	22.94	9.72	32.66	56.00	-23.34	QP	
12	1.3640	21.90	9.72	31.62	46.00	-14.38	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

APPENDIX B RADIATED EMISSIONS - 30 MHZ TO 1 GHZ

Test Mode	BLE 5.0 (2Mbps)	Test Date	2024/8/27
Test Frequency	CH39: 2480 MHz	Polarization	Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		60.3286	38.78	-12.35	26.43	40.00	-13.57	peak	
2		156.6496	40.54	-11.91	28.63	43.50	-14.87	peak	
3		240.0373	45.52	-13.60	31.92	46.00	-14.08	peak	
4		335.9703	44.47	-10.71	33.76	46.00	-12.24	peak	
5	*	408.3645	52.07	-8.72	43.35	46.00	-2.65	peak	
6		480.0153	41.75	-6.96	34.79	46.00	-11.21	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (2Mbps)	Test Date	2024/8/27
Test Frequency	CH39: 2480 MHz	Polarization	Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		88.5233	45.96	-17.94	28.02	43.50	-15.48	peak	
2		158.1046	47.90	-11.91	35.99	43.50	-7.51	peak	
3		240.0050	49.98	-13.60	36.38	46.00	-9.62	peak	
4		336.0026	47.38	-10.71	36.67	46.00	-9.33	peak	
5	*	408.3970	50.62	-8.71	41.91	46.00	-4.09	peak	
6		455.9916	39.18	-7.31	31.87	46.00	-14.13	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

APPENDIX C RADIATED EMISSIONS - ABOVE 1 GHZ

Test Mode	BLE 5.0 (1 Mbps)	Test Date	2024/8/24
Test Frequency	2402MHz	Polarization	Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2339.400	46.24	-5.63	40.61	74.00	-33.39	peak	
2		2339.400	33.21	-5.63	27.58	54.00	-26.42	AVG	
3	X	2402.000	95.42	-5.51	89.91	74.00	15.91	peak	No Limit
4	*	2402.000	94.38	-5.51	88.87	54.00	34.87	AVG	No Limit
5		2488.800	46.45	-5.33	41.12	74.00	-32.88	peak	
6		2488.800	33.72	-5.33	28.39	54.00	-25.61	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (1 Mbps)	Test Date	2024/8/24
Test Frequency	2480MHz	Polarization	Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2384.200	46.09	-5.54	40.55	74.00	-33.45	peak	
2		2384.200	33.27	-5.54	27.73	54.00	-26.27	AVG	
3	X	2479.800	96.78	-5.34	91.44	74.00	17.44	peak	No Limit
4	*	2479.800	95.73	-5.34	90.39	54.00	36.39	AVG	No Limit
5		2489.200	46.42	-5.33	41.09	74.00	-32.91	peak	
6		2489.200	33.51	-5.33	28.18	54.00	-25.82	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (2 Mbps)	Test Date	2024/8/24
Test Frequency	2402MHz	Polarization	Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2312.600	46.17	-5.69	40.48	74.00	-33.52	peak	
2		2312.600	33.26	-5.69	27.57	54.00	-26.43	AVG	
3	X	2401.600	95.19	-5.51	89.68	74.00	15.68	peak	No Limit
4	*	2401.600	90.99	-5.51	85.48	54.00	31.48	AVG	No Limit
5		2487.000	45.90	-5.33	40.57	74.00	-33.43	peak	
6		2487.000	33.52	-5.33	28.19	54.00	-25.81	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (2 Mbps)	Test Date	2024/8/24
Test Frequency	2480MHz	Polarization	Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2383.600	46.00	-5.53	40.47	74.00	-33.53	peak	
2		2383.600	33.29	-5.53	27.76	54.00	-26.24	AVG	
3	X	2479.600	96.67	-5.34	91.33	74.00	17.33	peak	No Limit
4	*	2479.600	92.41	-5.34	87.07	54.00	33.07	AVG	No Limit
5		2487.600	46.79	-5.33	41.46	74.00	-32.54	peak	
6		2487.600	33.58	-5.33	28.25	54.00	-25.75	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (1 Mbps)	Test Date	2024/8/24
Test Frequency	2402MHz	Polarization	Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4804.000	45.21	0.88	46.09	74.00	-27.91	peak	
2	*	4804.000	33.09	0.88	33.97	54.00	-20.03	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (1 Mbps)	Test Date	2024/8/24
Test Frequency	2402MHz	Polarization	Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4804.000	45.11	0.88	45.99	74.00	-28.01	peak	
2	*	4804.000	33.16	0.88	34.04	54.00	-19.96	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (1 Mbps)	Test Date	2024/8/24
Test Frequency	2440MHz	Polarization	Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4880.000	45.63	1.03	46.66	74.00	-27.34	peak	
2	*	4880.000	33.31	1.03	34.34	54.00	-19.66	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (1 Mbps)	Test Date	2024/8/24
Test Frequency	2440MHz	Polarization	Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4880.000	45.34	1.03	46.37	74.00	-27.63	peak	
2	*	4880.000	33.15	1.03	34.18	54.00	-19.82	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.


Test Mode	BLE 5.0 (1 Mbps)	Test Date	2024/8/24
Test Frequency	2480MHz	Polarization	Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.000	45.43	1.21	46.64	74.00	-27.36	peak	
2	*	4960.000	32.80	1.21	34.01	54.00	-19.99	AVG	

REMARKS:
 (1) Measurement Value = Reading Level + Correct Factor.
 (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (1 Mbps)	Test Date	2024/8/24
Test Frequency	2480MHz	Polarization	Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	45.02	1.21	46.23	74.00	-27.77	peak	
2	*	4960.000	32.92	1.21	34.13	54.00	-19.87	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.


Test Mode	BLE 5.0 (2 Mbps)	Test Date	2024/8/24
Test Frequency	2402MHz	Polarization	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4804.000	44.67	0.88	45.55	74.00	-28.45	peak	
2	*	4804.000	33.94	0.88	34.82	54.00	-19.18	AVG	

REMARKS:
 (1) Measurement Value = Reading Level + Correct Factor.
 (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (2 Mbps)	Test Date	2024/8/24
Test Frequency	2402MHz	Polarization	Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	45.92	0.88	46.80	74.00	-27.20	peak	
2	*	4804.000	33.61	0.88	34.49	54.00	-19.51	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.


Test Mode	BLE 5.0 (2 Mbps)	Test Date	2024/8/24
Test Frequency	2440MHz	Polarization	Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4880.000	45.64	1.03	46.67	74.00	-27.33	peak	
2	*	4880.000	33.89	1.03	34.92	54.00	-19.08	AVG	

REMARKS:
 (1) Measurement Value = Reading Level + Correct Factor.
 (2) Margin Level = Measurement Value - Limit Value.


Test Mode	BLE 5.0 (2 Mbps)	Test Date	2024/8/24
Test Frequency	2440MHz	Polarization	Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4880.000	45.69	1.03	46.72	74.00	-27.28	peak	
2	*	4880.000	33.91	1.03	34.94	54.00	-19.06	AVG	

REMARKS:
 (1) Measurement Value = Reading Level + Correct Factor.
 (2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (2 Mbps)	Test Date	2024/8/24
Test Frequency	2480MHz	Polarization	Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	45.63	1.21	46.84	74.00	-27.16	peak	
2	*	4960.000	33.55	1.21	34.76	54.00	-19.24	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (2 Mbps)	Test Date	2024/8/24
Test Frequency	2480MHz	Polarization	Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	45.14	1.21	46.35	74.00	-27.65	peak	
2	*	4960.000	33.56	1.21	34.77	54.00	-19.23	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (2 Mbps)	Test Date	2024/8/24
Test Frequency	2480MHz	Polarization	Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		18527.00	53.66	-6.35	47.31	74.00	-26.69	peak	
2	*	18527.00	41.38	-6.35	35.03	54.00	-18.97	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	BLE 5.0 (2 Mbps)	Test Date	2024/8/24
Test Frequency	2480MHz	Polarization	Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		18221.00	54.53	-6.80	47.73	74.00	-26.27	peak	
2	*	18221.00	41.18	-6.80	34.38	54.00	-19.62	AVG	


REMARKS:
 (1) Measurement Value = Reading Level + Correct Factor.
 (2) Margin Level = Measurement Value - Limit Value.

APPENDIX D BANDWIDTH


Test Mode: 1Mbps

Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2402	0.686	1.056	500	Pass
2440	0.660	1.052	500	Pass
2480	0.668	1.052	500	Pass

CH00




Date: 16.AUG.2024 10:55:37

CH19
6 dB Bandwidth



Date: 16.AUG.2024 10:57:37

CH39




Date: 16.AUG.2024 10:59:45


99 % Occupied Bandwidth



Date: 16.AUG.2024 10:55:37



Date: 16.AUG.2024 10:57:45




Date: 16.AUG.2024 10:59:53

Test Mode:	2Mbps
------------	-------


Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2402	1.332	2.112	500	Pass
2440	1.352	2.104	500	Pass
2480	1.366	2.112	500	Pass

CH00




Date: 16.AUG.2024 11:01:47

CH19
6 dB Bandwidth




Date: 16.AUG.2024 11:04:11

CH39




Date: 16.AUG.2024 11:07:01


99 % Occupied Bandwidth



Date: 16.AUG.2024 11:01:16



Date: 16.AUG.2024 11:04:19



Date: 16.AUG.2024 11:07:09

APPENDIX E MAXIMUM OUTPUT POWER

Test Mode :	1Mbps	Tested Date	2024/8/16
-------------	-------	-------------	-----------

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	4.14	0.0026	30.00	1.0000	Pass
2440	4.25	0.0027	30.00	1.0000	Pass
2480	5.55	0.0036	30.00	1.0000	Pass


Test Mode :	2Mbps	Tested Date	2024/8/16
-------------	-------	-------------	-----------

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	4.15	0.0026	30.00	1.0000	Pass
2440	4.35	0.0027	30.00	1.0000	Pass
2480	5.68	0.0037	30.00	1.0000	Pass

APPENDIX F POWER SPECTRAL DENSITY TEST


Test Mode : 1Mbps

Frequency (MHz)	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Test Result
2402	-13.72	8.00	Pass
2440	-13.59	8.00	Pass
2480	-11.50	8.00	Pass



Test Mode : 2Mbps


Frequency (MHz)	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Test Result
2402	-17.31	8.00	Pass
2440	-16.43	8.00	Pass
2480	-14.96	8.00	Pass




APPENDIX G ANTENNA CONDUCTED SPURIOUS EMISSION

Test Mode : 1Mbps

Bandedge CH00 (Lower)






Bandedge CH39 (Upper)



Date: 16.AUG.2024 10:55:46

Date: 16.AUG.2024 11:00:02

CH00 – 10th Harmonic of the fundamental frequency






Date: 16.AUG.2024 10:56:01

Date: 16.AUG.2024 10:56:11

Date: 16.AUG.2024 10:56:20

CH19 – 10th Harmonic of the fundamental frequency






Date: 16.AUG.2024 10:58:09

Date: 16.AUG.2024 10:58:18

Date: 16.AUG.2024 10:58:27

CH39 – 10th Harmonic of the fundamental frequency




Date: 16.AUG.2024 11:00:17

Date: 16.AUG.2024 11:00:26


Date: 16.AUG.2024 11:00:35

Test Mode : 2Mbps

Bandedge CH00 (Lower)




Bandedge CH39 (Upper)




Date: 16.AUG.2024 11:01:56

Date: 16.AUG.2024 11:07:18


CH00 – 10th Harmonic of the fundamental frequency



Date: 16.AUG.2024 11:02:11




Date: 16.AUG.2024 11:02:20




Date: 16.AUG.2024 11:02:29


CH19 – 10th Harmonic of the fundamental frequency



Date: 16.AUG.2024 11:04:43




Date: 16.AUG.2024 11:04:52




Date: 16.AUG.2024 11:05:02


CH39 – 10th Harmonic of the fundamental frequency



Date: 16.AUG.2024 11:07:33



Date: 16.AUG.2024 11:07:42



Date: 16.AUG.2024 11:07:51

End of Test Report