

Prüfbericht-Nr.: Test report no.:	CN26PBO6 002	Auftrags-Nr.: Order no.:	168580336	Seite 1 von 11 Page 1 of 11	
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2025-10-22		
Auftraggeber: Client:	Shenzhen Shuye Technology Co.,Ltd. Room1301, Building T7, Qianwan 1st Road No.399, Qianhai Kerry Business				
Prüfgegenstand: Test item:	Wireless Charger				
Bezeichnung / Typ-Nr.: Identification / Type no.:	LFTB02 WC-L				
Auftrags-Inhalt: Order content:	Test Report				
Prüfgrundlage: Test specification:	CFR Title 47 FCC Part 2.1091				
Wareneingangsdatum: Date of sample receipt:	2025-11-20	Please refer to Photo Document			
Prüfmuster-Nr.: Test sample no:	A004134044-001~021 A004159959-001~002				
Prüfzeitraum: Testing period:	2025-12-12 - 2025-04-03				
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüfergebnis*: Test result*:	Pass				
geprüft von: tested by:			genehmigt von: authorized by:		
Datum: Date:	2026-04-09	Signed by: Jonathan Li		Ausstellungsdatum: Issue date:	2026-04-09
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / Other:	FCC ID: 2BE2Y-LFWCL				
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged				
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested					
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

Prüfbericht-Nr.: CN26PBO6 002
Test report no.:

Seite 2 von 11
Page 2 of 11

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Contents

1	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS.....	4
2	TEST SITES.....	5
2.1	TEST FACILITIES	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	5
2.3	TRACEABILITY	5
2.4	CALIBRATION.....	5
2.5	MEASUREMENT UNCERTAINTY	5
2.6	LOCATION OF ORIGINAL DATA	6
2.7	STATUS OF FACILITY USED FOR TESTING	6
3	GENERAL PRODUCT INFORMATION	7
3.1	PRODUCT FUNCTION AND INTENDED USE	7
3.2	RATINGS AND SYSTEM DETAILS.....	7
3.3	INDEPENDENT OPERATION MODES.....	7
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	7
3.5	SUBMITTED DOCUMENTS.....	7
3.6	TEST SETUP DIAGRAM	8
3.7	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	8
4	SAFETY HUMAN EXPOSURE.....	9
4.1	RADIO FREQUENCY EXPOSURE COMPLIANCE.....	9
4.1.1	<i>Test Procedures According to the Technical Standards</i>	<i>9</i>
4.1.2	<i>Limit of Maximum Permissible Exposure.....</i>	<i>9</i>
4.1.3	<i>Test Result</i>	<i>10</i>
5	PHOTOGRAPHS OF THE TEST SET-UP	11
6	LIST OF TABLES.....	11

Prüfbericht - Nr.: CN26PBO6 002
Test Report No.:

Seite 4 von 11
Page 4 of 11

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up.

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, China

A2LA Certificate Number: 5162.01

FCC Accreditation Designation No.: 694916

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
Electric and Magnetic Field Analyzer	Narda	EHP200A	180ZX20517	2025-09-28	2027-09-26

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Table 2: Measurement Uncertainty

Parameter	Uncertainty (k=2)
Magnetic Field Emissions (A/m)	$\pm 1.2 \mu\text{T}$
Electric Field Emissions (V/m)	$\pm 18\%$

Prüfbericht - Nr.: CN26PBO6 002
Test Report No.:

Seite 6 von 11
Page 6 of 11

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a Wireless Charger which supports wireless charging (WPT) function.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	Wireless Charger
Type Designation:	LFTB02 WC-L
FCC ID:	2BE2Y-LFWCL
Operating Voltage:	USB-C operated (Adapter input 120Vac/60Hz)
Operating Temperature Range:	0 °C ~ +40 °C
Technical Specification of WPT	
Frequency Range:	110 – 205 kHz
Type of Modulation:	FSK
Antenna Type:	Coil antenna
Antenna Gain:	0 dBi (Provided by the Client)
Wireless output power:	5W/15W

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Wireless Charging, 5W/15W
- B. On, Standby mode
- C. Off

3.4 Noise Generating and Noise Suppressing Parts


Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- User Manual
- Operation Description
- FCC/IC Label and Location Info

3.6 Test Setup Diagram

Diagram of Measurement Configuration



3.7 Special Accessories and Auxiliary Equipment

Table 4: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	Remark
AC/DC Adapter	Huawei	HW-050200C02	Output: 5 V–1 A/ 9 V–2.22 A
Electric toothbrush	Shenzhen Shuye	LFTB02	DC 3.7V by battery
Smartphone	Huawei	P30 Pro	N/A

4 Safety Human Exposure

4.1 Radio Frequency Exposure Compliance

4.1.1 Test Procedures According to the Technical Standards

Standards	Test Item	Judgment
FCC CFR 47 part1, 1.1310 KDB 680106 D01 Wireless Power Transfer v04	Electric Field Strength (E) (V/m)	PASS
	Magnetic Field Strength (H) (A/m)	PASS

4.1.2 Limit of Maximum Permissible Exposure

Limit of Maximum Permissible Exposure

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

Note 1: f = frequency in MHz ; *Plane-wave equivalent power density.

Note 2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v03.

Note 3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

Prüfbericht - Nr.: CN26PBO6 002
Test Report No.:Seite 10 von 11
Page 10 of 11

4.1.3 Test Result

RF Exposure Evaluation - Magnetic Field Emissions

Test Mode	Test Distance (cm)	Measure Value (A/m)						Limit (A/m)	Result
		Front	Rear	Left	Right	Top	Bottom		
Standby	15	0.606	0.642	0.639	0.653	0.625	0.625	1.63	PASS
Charging (5W)	15	0.623	0.636	0.632	0.613	0.633	0.616	1.63	PASS
Charging (15W)	15	0.614	0.609	0.6312	0.642	0.683	0.616	1.63	PASS

RF Exposure Evaluation - Electric Field Emissions

Test Mode	Test Distance (cm)	Measure Value (V/m)						Limit (V/m)	Result
		Front	Rear	Left	Right	Top	Bottom		
Standby	15	0.824	0.841	0.875	0.875	1.187	0.881	614	PASS
Charging (5W)	15	0.731	0.758	0.728	0.785	1.147	0.737	614	PASS
Charging (15W)	15	1.882	1.798	1.845	1.879	1.939	1.903	614	PASS

5 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

6 List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Measurement Uncertainty	5
Table 3: Technical Specification of EUT.....	7
Table 4: List of Accessories and Auxiliary Equipment.....	8

Appendix A: Photographs of the Test Set-Up

APPENDIX A: PHOTOGRAPHS OF THE TEST SET-UP	1
PHOTOGRAPH 1: SET-UP PHOTO FOR SAFETY HUMAN EXPOSURE	2

Photograph 1: Set-up photo for Safety Human Exposure



