TEST REPORT

KES Co., Ltd.
#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu,
Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

■ **FCC TEST REPORT**

1. Client

○ Name : Parks Medical Electronics Incorporated
○ Address : 19460 SW Shaw St, Beaverton, Oregon, United States

2. Sample Description

○ Product item : Parks Flo-Lab USB Receiver
○ Model name : RFR-1
○ Manufacturer etc. : Hyun Seung I&C Co., Ltd

3. Date of test : 2024.08.23 ~ 2024.10.10

4. Location of Test : ☑ Permanent Testing Lab ☐ On Site Testing

○ Adress : 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea

5. Test method used : Part 15 Subpart C 15.247

6. Test result : PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
This laboratory is not accredited for the test results marked *.
This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager
	Name : Gu-Bong, Kang (Signature) [강구봉]2024/10/11	Name : Young-Jin, Lee (Signature) [이영진]2024/10/11

2024 . 10. 11.

KES Co., Ltd.

Accredited by KOLAS, Republic of KOREA

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
2024.10.11	KES-RF240570	Initial

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

Use of uncertainty of measurement for decisions on conformity (decision rule):

■ No decision rule is specified by the standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty(“simple acceptance” decision rule, previously known as “accuracy method”).

☐ Other (to be specified, for example when required by the standard or client)

TABLE OF CONTENTS

1. General information 4
1.1. EUT description 4
1.2. Test configuration 4
1.3. Information about derivative model 5
1.4. Accessory information 5
1.5. Device modifications 5
1.6. Sample calculation 5
1.7. Measurement Uncertainty 5
1.8. Frequency/channel operations 6
2. Summary of tests 7
3. Test results 8
3.1. 6 dB bandwidth 8
3.2. Output power 10
3.3. Power spectral density 12
3.4. Radiated restricted band and emissions 14
3.5. Conducted spurious emissions & band edge 30
3.6. AC conducted emissions 33
3.7. Antenna Requirement 35
Appendix A. Measurement equipment 36

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

1. General information

Applicant:	Parks Medical Electronics Incorporated
Applicant address:	19460 SW Shaw St, Beaverton, Oregon, United States
Test site:	KES Co., Ltd.
Test site address:	☐ #3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
	☒ 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Test Facility	FCC Accreditation Designation No.: KR0100, Registration No.: 444148
FCC rule part(s):	15.247
FCC ID:	2BE53-REM22BR
Test device serial No.:	☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test	Parks Flo-Lab USB Receiver
Frequency range	2 402 ㎒ ~ 2 480 ㎒ (LE 1 Mbps)
Model	RFR-1
Modulation technique	GFSK
Number of channels	2 402 ㎒ ~ 2 480 ㎒ : 40 ch
Antenna specification	PCB Pattern Antenna // Peak gain: 7.29 ㏈i
Power source	DC 5.0 V (USB)
H/W version	Ver. 0.1A
S/W version	Ver. 0.1A

1.2. Test configuration

The **Parks Medical Electronics Incorporated // Parks Flo-Lab USB Receiver // RFR-1 // FCC ID: 2BE53-USBRFR1** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15.247
KDB 558074 D01 v05 r02
ANSI C63.10-2013

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

1.3. Information about derivative model

N/A

1.4. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
-	-	-	-	-

1.5. Device modifications

N/A

1.6. Sample calculation

Where relevant, the following sample calculation is provided
For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Offset(㎧) = RF cable loss(㎧) + attenuator factor(㎧).
= 0.65 + 10 = 10.65 (㎧)

For Radiation test :
Field strength level (㎧㎶/m) = Measured level (㎧㎶) + Antenna factor (㎧) + Cable loss (㎧) – Amplifier gain (㎧)

1.7. Measurement Uncertainty

Test Item		Uncertainty
Uncertainty for Conduction emission test		2.22 ㎧ (SHIELD ROOM #6)
Uncertainty for Radiation emission test (include Fundamental emission)	Below 1 ㎓	4.04 ㎧ (SAC #6)
	Above 1 ㎓	5.32 ㎧ (SAC #5)
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

1.8. Frequency/channel operations

Ch.	Frequency (㎒)	Mode
00	2 402	LE 1 Mbps
⋮	⋮	⋮
20	2 442	LE 1 Mbps
⋮	⋮	⋮
39	2 480	LE 1 Mbps

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

2. Summary of tests

Section in FCC Part 15	Test description	Test results
15.247(a)(2)	6 dB bandwidth	Pass
15.247(b)(3)	Output power	Pass Note.1
15.247(e)	Power spectral density	Pass Note.1
15.205, 15.209	Radiated restricted band and emission	Pass
15.247(d)	Conducted spurious emission and band edge	Pass
15.207(a)	AC Conducted emissions	Pass
15.203	Antenna Requirement	Pass

Note:

1. The antenna gain value exceeds 6 dBi, so the limit of the test was reduced by the excess.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

3. Test results

3.1. 6 dB bandwidth

Test procedure

ANSI C63.10-2013 - Section 11.8.2

Test setup



ANSI C63.10-2013 - Section 11.8.2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW ≥ 3 × RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

Test results

Frequency(㎒)	6 ㏈ bandwidth(㎒)	Limit(㎒)
2 402	0.70	≥ 0.500
2 442	0.69	
2 480	0.69	

Test plot







Blank

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

3.2. Output power

Test procedure

ANSI C63.10-2013 - Section 11.9.1.3 and 11.9.2.3.2

Test setup



ANSI C63.10-2013 - Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power m eter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandw idth and shall use a fast-responding diode detector.

ANSI C63.10-2013 - Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 ㎒, 2 400~2 483.5 ㎒, and 5 725~5 850 ㎒ bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

Test results

Mode	2 402 ㎒		2 442 ㎒		2 480 ㎒		Power Limit (dBm)
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	
LE 1 Mbps	-8.29	-6.85	-9.85	-7.96	-9.60	-7.75	28.71 Note 1.

Note
1. Reduced by 1.29 dBi due to antenna gain.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

3.3. Power spectral density

Test procedure

ANSI C63.10-2013 - Section 11.10.2

Test setup



Section 10.2 & ANSI C63.10-2013 - Section 11.10.2

a. Set analyzer center frequency to DTS channel center frequency.
b. Set the span to 1.5 times the DTS bandwidth.
c. Set the RBW to 3 ㎑ ≤ RBW ≤ 100 ㎑
d. Set the VBW ≥ [3 × RBW].
e. Detector = peak.
f. Sweep time = auto couple.
g. Trace mode = max hold.
h. Allow trace to fully stabilize.
i. Use the peak marker function to determine the maximum amplitude level within the RBW.
j. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

Limit

According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 �dBm in any 3 ㎑ band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

Results

Frequency(㎒)	PSD (㏈m/3 ㎑)	Limit(㏈m/3 ㎑)
2 402	-24.74	≤ 6.71[Note 1.]
2 442	-26.00	
2 480	-25.79	

Note

1. Reduced by 1.29 ㏈i due to antenna gain.

Test Plot







Blank

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

3.4. Radiated restricted band and emissions

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 ㎑ to 30 ㎒ Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 ㎒ to 1 ㎓ emissions.



The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

The diagram below shows the test setup that is utilized to make the measurements for emission from 1 ㎓ to the tenth harmonic of the highest fundamental frequency or to 40 ㎓ emissions, whichever is lower.



Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

Test procedure below 30 ㎒

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that **parallel** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **parallel.**
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 ㎒

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground for 30 ㎒-1 ㎓ and 1.5 meters for above 1 ㎓ at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna ,and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

5. Spectrum analyzer settings for f < 1 ㎓:

① Span = wide enough to fully capture the emission being measured
② RBW = 120 ㎑
③ VBW ≥ RBW
④ Detector = quasi peak
⑤ Sweep time = auto
⑥ Trace = max hold

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

6. Spectrum analyzer settings for *f* ≥1 ㎓: Peak
   ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
   ② RBW = 1 ㎒
   ③ VBW ≥ 3 ㎒
   ④ Detector = peak
   ⑤ Sweep time = auto
   ⑥ Trace = max hold
   ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for *f* ≥1 ㎓: Average
   ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
   ② RBW = 1 ㎒
   ③ VBW ≥ 3 × RBW
   ④ Detector = RMS, if span/(# of points in sweep) ≤ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
   ⑤ Averaging type = power(i.e., RMS)
      1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
      2) Some instruments require linear display mode in order to use linear voltage averaging. Log or ㏈ averaging shall not be used.
   ⑥ Sweep = auto
   ⑦ Trace = max hold
   ⑧ Perform a trace average of at least 100 traces.
   ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
      1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is 10 log(1/x), where x is the duty cycle.
      2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is 20 log(1/x), where x is the duty cycle.
      3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

Note.

1. *f* <30 ㎒, extrapolation factor of 40 ㏈/decade of distance. $F_d = 40\log(D_m/D_s)$
   f ≥30 ㎒, extrapolation factor of 20 ㏈/decade of distance. $F_d = 20\log(D_m/D_s)$
   Where:
   F_d = Distance factor in ㏈
   D_m = Measurement distance in meters
   D_s = Specification distance in meters
2. Field strength(㏈㎶/m) = Level(㏈㎶) + CF (㏈) + or DCF(㏈)
3. Margin(㏈) = Limit(㏈㎶/m) – Field strength(㏈㎶/m)
4. Emissions below 18 ㎓ were measured at a 3 meter test distance while emissions above 18 ㎓ were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation.**
6. The worst-case emissions are reported however emissions whose levels were not within 20 ㏈ of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 ㎑ to 30 ㎒. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values：

Frequency (㎒)	Distance (Meters)	Radiated (㎶/m)
0.009 ~ 0.490	300	2400/F(㎑)
0.490 ~ 1.705	30	24000/F(㎑)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 ㎒, 76 ~ 88 ㎒, 174 ~ 216 ㎒ or 470 ~ 806 ㎒. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

Duty cycle

Regarding to KDB 558074 D01_v05 r02, 6. Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

a) A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on- and off-times of the transmitted signal.

b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on- and off-times of the transmitted signal.

Mode	T_{on} time (㎳)	Period (㎳)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (㏈)
LE 1 Mbps	2.15	2.50	0.86	86.00	0.66

Duty cycle (Linear) = T_{on} time/Period

DCF(Duty cycle correction factor (㏈)) = 10log(1/duty cycle)

Duty cycle



Test results (Below 30 ㎒)

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	00 (Worst case)

Parallel



Note.

1. No spurious emission were detected under 30 ㎒, above data is peak result.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

Test results (Below 1 000 ㎒)

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	00 (Worst case)

Horizontal // Vertical



Final Result

No.	Frequency [MHz]	Pol	Reading QP [dB(µV)]	c.f [dB(1/m)]	Result QP [dB(µV/m)]	Limit QP [dB(µV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	63.950	V	30.6	-14.3	16.3	40.0	23.7	104.0	263.0	
2	110.753	V	32.0	-14.6	17.4	43.5	26.1	100.0	216.8	
3	127.970	H	38.9	-15.7	23.2	43.5	20.3	211.0	151.5	
4	127.970	V	39.3	-15.7	23.6	43.5	19.9	105.0	110.5	
5	147.976	H	38.6	-17.0	21.6	43.5	21.9	242.0	259.7	
6	148.098	V	41.5	-17.0	24.5	43.5	19.0	109.0	263.0	
7	185.200	V	33.7	-14.3	19.4	43.5	24.1	125.0	21.6	
8	191.990	H	31.3	-13.9	17.4	43.5	26.1	226.0	21.6	
9	260.254	H	31.6	-11.6	20.0	46.0	26.0	129.0	116.7	
10	296.629	V	30.8	-10.9	19.9	46.0	26.1	144.0	163.6	
11	370.470	H	30.3	-8.6	21.7	46.0	24.3	198.0	192.5	
12	481.414	H	29.7	-6.8	22.9	46.0	23.1	199.0	130.2	

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

Test results (Above 1 000 ㎒)

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	00

- **Spurious**

Frequency (㎒)	Level (dB㎛)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB㎛/m)	Limit (dB㎛/m)	Margin (dB)
1 020.90	45.08	Peak	V	-9.57	-	35.51	74.00	38.49
2 273.77	45.80	Peak	H	-1.19	-	44.61	74.00	29.39
2 530.35	47.52	Peak	H	-0.56	-	46.96	74.00	27.04
2 530.35	44.69	Peak	V	-0.56	-	44.13	74.00	29.87
4 805.10	40.56	Peak	H	6.14	-	46.70	74.00	27.30
7 206.30	42.18	Peak	H	11.78	-	53.96	74.00	20.04

- **Band edge (2 310 ~ 2 390 ㎒)**

Frequency (㎒)	Level (dB㎛)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB㎛/m)	Limit (dB㎛/m)	Margin (dB)
2 320.71	43.07	Peak	V	-1.08	-	41.99	74.00	32.01
2 320.79	45.41	Peak	H	-1.08	-	44.33	74.00	29.67
2 337.92	43.27	Peak	V	-1.05	-	42.22	74.00	31.78
2 338.04	45.89	Peak	H	-1.05	-	44.84	74.00	29.16

- **Band edge (2 483.5 ~ 2 500 ㎒)**

Frequency (㎒)	Level (dB㎛)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB㎛/m)	Limit (dB㎛/m)	Margin (dB)
2 483.51	43.51	Peak	V	-0.72	-	42.79	74.00	31.21
2 483.84	45.88	Peak	H	-0.72	-	45.16	74.00	28.84

(Left) Restricted band // Horizontal // Peak



(Left) Restricted band // Vertical // Peak



The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

(Right) Restricted band // Horizontal // Peak



(Right) Restricted band // Vertical // Peak



Horizontal // Peak for 1 ㎓ to 3 ㎓



Vertical // Peak for 1 ㎓ to 3 ㎓



Horizontal // Peak for 3 ㎓ to 18 ㎓



Vertical // Peak for 3 ㎓ to 18 ㎓



Note.

1. No spurious emission were detected above 3 ㎓.
2. Average test would be performed if the peak result were greater than the average limit.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).