

Certificate of Test

NCT CO., LTD. 211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, 18511, Republic of Korea (Tel: +82-31-323-6070 / Fax: +82-31-323-6071)	Report No.: NW2403-F002 Page (1) / (6)	
---	--	---

1. Client

- o Name : CUBOX Co., Ltd.
- o Address : 12, Teheran-ro 22-gil, Gangnam-gu, Seoul, Republic of Korea
- o Date of Receipt : 2024-02-22

2. Use of Report : FCC Approval

3. Test Sample

- o Description / Model : SEEUFACE / SEEUFACE-STE200
- o FCC ID : 2BE6A-STE-200

4. Place of Test : ☒ Fixed test ☐ Field test

(Address: 211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, 18511, Republic of Korea)

5. Date of Test :

6. Test method used : FCC Part 1.1310

7. Testing Environment :

- o Temperature: (25 ± 5) °C, Humidity: Less than 75 % R.H.

* Unless specified otherwise in the individual methods, the tests were conducted on ambient conditions.

8. Test Results : Refer to the test results

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
This Test Report cannot be reproduced, except in full
This test report is not related to KOLAS recognition and RRA designation.

Affirmation	Tested by Ji-won Hong 	Technical Manager Il-shin, Kim 
-------------	--	---

Mar 11, 2024

NCT CO., LTD.



Contact us at report@nct.re.kr to confirm the authenticity of this report

Table of contents

1. General Information	3
2. Information's about Test Item	3
3. Test Report	5
3.1 Test Report Version	5
3.2 RF Exposure evaluation	6

Test Repot No.: NW2403-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

1. General Information's

1.1 Test Performed

Laboratory : NCT Co., Ltd.
Address : 211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, 18511, Korea
Telephone : +82-31-323-6070
Facsimile : +82-31-323-6071
FCC Designation No. : KR0166
FCC Registration Number : 409631

2. Information's about Test Item

2.1 Applicant Information

Company name : CUBOX Co., Ltd.
Address : 12, Teheran-ro 22-gil, Gangnam-gu, Seoul, Republic of Korea
Telephone : +82-02-6277-7817
Facsimile : +82-02-6277-7880

2.2 Equipment Under Test (EUT) description

Test item particulars : SEEUFACE
Model and/or type reference : SEEUFACE-STE200
Additional model name : -
Serial number : Prototype
Antenna type : PCB Loop Antenna
Date (s) of performance of tests : 2024-02-26 ~ 2024-03-08
Date of receipt of test item : 2024-02-22
EUT condition : Pre-production, not damaged
Number of channel : 1
EUT Power Source : DC 15.0 V
Type of Modulation : ASK
Firmware version : 1.0
Hardware version : 1.0
Test software name(version) : -

Test Report No.: NW2403-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

2.3 Tested Frequency

	Low frequency	Middle frequency	High frequency
Frequency (MHz)	-	13.56	-

3. Test Report

3.1 Test Report Version

Test Report No.	Date	Description
NW2403-F002	2024-03-11	Initial issue

Test Report No.: NW2403-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

3.2 RF Exposure evaluation

According to 447498 D04 Interim General RF Exposure Guidance v01

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption

According to ANSI C63.10

where:

$$\text{EIRP(dBm)} = \text{E(dBuV/m)} - 95.3$$

$$\text{ERP} = \text{EIRP} - 2.15 \text{ dB}$$

$$\text{E} = \text{Field Strength (dBuV/m)}$$

$$\text{So ERP} = \text{E(dBuV/m)} - 95.3 - 2.15$$

Frequency(MHz)	Field Strength (dBuV/m)	ERP (mW)	Limit (mW)
13.56	61.37	0.000247	1

So a SAR test is not Required.