



No.:
FCCSZ2024-0082-RF3

TEST REPORT

FCC ID : 2BE7DM10CP


NAME OF SAMPLE : Car Multimedia Player

APPLICANT : CAD Business LLC

CLASSIFICATION OF TEST : N/A

CVC Testing Technology (Shenzhen) Co., Ltd.



Applicant		Name: CAD Business LLC Address: 11379 Harry Hines Blvd, Dallas, TX 75229 USA	
Manufacturer		Name: CAD Business LLC Address: 11379 Harry Hines Blvd, Dallas, TX 75229 USA	
Equipment Under Test		Name: Car Multimedia Player Model/Type: XA-M10CP Brand: XELON AUDIO Serial No.: N/A Sample No.: 3-1	
Date of Receipt.	2024-11-26	Date of Testing	2024-11-26 ~ 2025-01-14
Test Specification		Test Result	
FCC Part 15, Subpart E (15.407)		PASS	
Evaluation of Test Result	The equipment under test was found to comply with the requirements of the standards applied. Seal of CVC Issue Date: 2025-01-15		
Compiled by:  Zhu Yulin Name Signature	Reviewed by:  Mo Xianbiao Name Signature	Approved by:  Dong Sanbi Name Signature	
Other Aspects: NONE.			
Abbreviations: OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS	5
1.1 TEST LOCATION	5
1.2 LIST OF TEST AND MEASUREMENT INSTRUMENTS	6
1.3 MEASUREMENT UNCERTAINTY	7
2 GENERAL INFORMATION	8
2.1 GENERAL PRODUCT INFORMATION	8
2.2 CARRIER FREQUENCY AND CHANNEL	9
2.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	10
2.4 DESCRIPTION OF SUPPORT UNITS	11
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	11
3 TEST TYPES AND RESULTS	12
3.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT	12
3.2 OCCUPIED BANDWIDTH MEASUREMENT	37
3.3 26DB EMISSION BANDWIDTH	38
3.4 6DB EMISSION BANDWIDTH	39
3.5 TRANSMIT POWER MEASUREMENT	40
3.6 POWER SPECTRAL DENSITY MEASUREMENT	41
3.7 FREQUENCY STABILITY	42
3.8 ANTENNA REQUIREMENT	43
4 PHOTOGRAPHS OF TEST SETUP	44
5 PHOTOGRAPHS OF THE EUT	45



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCCSZ2024-0082-RF3	Original release	2025-01-15



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPARTE (SECTION 15.407)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
FCC 15.207	AC Power Conducted Emission	N/A	DC power supply
FCC 15.403(a)(e)	6dB&26dB Emission Bandwidth	PASS	Appendix A1&A3 of FCCSZ2024-0082-RF3-A1
---	Occupied Bandwidth Measurement	N/A	Appendix A2 of FCCSZ2024-0082-RF3-A1 (For reference)
FCC 15.407(b)	Radiated Emission and Band edge	PASS	See section 3.2
FCC 15.407(a)	Transmit Power	PASS	Appendix C of FCCSZ2024-0082-RF3-A1
FCC 15.407(a)	Power Spectral Density	PASS	Appendix D of FCCSZ2024-0082-RF3-A1
FCC 15.407(g)	Frequency Stability	PASS	Appendix E of FCCSZ2024-0082-RF3-A1
FCC 15.203 FCC 15.407(a)	Antenna Requirement	PASS	See section 3.9

1.1 TEST LOCATION

The tests and measurements refer to this report were performed by EMC testing Lab. of CVC Testing Technology (Shenzhen) Co., Ltd.

Lab Address: No. 1301, Guanguang Road, Xinlan Community, Guanlan Street, Longhua District, Shenzhen City, Guangdong Province 518110 P.R.China
Post Code: 518110 Tel: 0755-23763060-8805
Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn
FCC(Test firm designation number: CN1363)
IC(Test firm CAB identifier number: CN0137)
CNAS(Test firm designation number: L16091)



1.2 LIST OF TEST AND MEASUREMENT INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial Number	Cal. interval	Cal. Due
Antenna Port Conducted Test					
Signal&Spectrum Analyzer	Rohde&Schwarz	FSV 30	104408	1 year	2025/4/28
#3Shielding room	MORI	443	N/A	3 year	2026/5/16
Wideband radio communication tester	Rohde&Schwarz	CMW 500	168778	1 year	2025/5/24
Analog signal Generator (100kHz ~ 40GHz)	Rohde&Schwarz	SMB 100A	181934	1 year	2025/4/27
Vector signal Generator (9kHz ~ 6GHz)	Rohde&Schwarz	SGT 100A	111724	1 year	2025/4/27
RF control unit(BT/WiFi)	Tonscend	JS0806-2-8CH	20E8060261	1 year	2025/4/28
Temperature and humidity meter	/	C193561457	C193561457	1 year	2025/4/27
Radiation Spurious Test - 3M Chamber #2					
Signal&Spectrum Analyzer	Rohde&Schwarz	FSV 40	101898	1 year	2025/4/28
EMI Test Receiver	Rohde&Schwarz	ESR3	102693	1 year	2025/4/28
Antenna(30MHz~1001MHz)	SCHWARZBECK	VULB 9168	1133	1 year	2025/2/20
Horn antenna(1GHz-18GHz)	ETS	3117	227611	1 year	2025/2/4
Horn antenna(18GHz-40GHz)	QMS	QMS-00880	22051	1 year	2025/3/24
3m anechoic chamber	MORI	966	CS0300011	3 year	2026/5/18
Filter group(RSE-BT/WiFi)	Rohde&Schwarz	WiFi /BT Variant 1	100820	1 year	2025/4/28
Filter group(RSE-Cellular)	Rohde&Schwarz	Cellular Variant 1	100768	1 year	2025/4/28
Preamplifier(10kHz-1GHz)	Rohde&Schwarz	SCU-01F	100299	1 year	2025/4/28
Preamplifier(1GHz-18GHz)	Rohde&Schwarz	SCU-18F	100799	1 year	2025/4/28
Preamplifier(1GHz-18GHz)	Rohde&Schwarz	SCU-18F	100801	1 year	2025/4/28
Preamplifier(18Gz-40GHz)	Rohde&Schwarz	SCU-40A	101209	1 year	2025/4/28
Temperature and humidity meter	/	C193561517	C193561517	1 year	2025/4/27
Radiation Spurious Test - 3M Chamber #1					
EMI Test Receiver	Rohde&Schwarz	ESR 26	101718	1 year	2025/5/24
Antenna(30MHz~1000MHz)	SCHWARZBECK	VULB 9168	01132	1 year	2025/5/27
Horn antenna(1GHz-18GHz)	ETS	3117	227634	1 year	2025/3/25
Horn antenna(18GHz-40GHz)	SCHWARZBECK	BBHA 9170	01003	1 year	2025/3/25
3m anechoic chamber	MORI	966	CS0200019	3 year	2026/5/18
LISN (single-phase)	Rohde&Schwarz	ESH3-Z6	102152/102156	1 year	2025/4/27
Preamplifier(10kHz-1GHz)	Rohde&Schwarz	SCU-01F	100298	1 year	2025/4/28
Attenuator	/	SJ-5dB	607684	1 year	2025/2/4
#1 control room	MORI	433	CS0300028	3 year	2026/5/17
Temperature and humidity meter	UNI-T	A10T	C193561473	1 year	2025/4/27



1.3 MEASUREMENT UNCERTAINTY


Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

No.	Item	Measurement Uncertainty
1	Occupied Channel Bandwidth	± 1.86 %
2	RF output power, conducted	± 0.9 dB
3	Power Spectral Density, conducted	± 0.8 dB
4	Conducted emission test	± 2.7 dB
5	Radiated emission 9kHz-30MHz	± 5.6 dB
	Radiated emission 30MHz-1GHz	± 4.6 dB
	Radiated emission 1GHz-18GHz	± 4.4 dB
	Radiated emission 18GHz-40GHz	± 5.1 dB
6	Temperature	± 0.73 °C
7	Humidity	± 3.90 %
8	Supply voltages	± 0.37 %
9	Time	± 0.27 %
Remark: 95% Confidence Levels, k=2.		

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed.

The measurement uncertainty is mentioned in this test report, but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong.





2 GENERAL INFORMATION

2.1 GENERAL PRODUCT INFORMATION

PRODUCT	Car Multimedia Player		
BRAND	XELON AUDIO		
TEST MODEL	XA-M10CP		
POWER SUPPLY	DC 12V		
MODULATION TECHNOLOGY	OFDM		
MODULATION TYPE	1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM		
TRANSFER RATE	802.11a: Up to 54Mbps 802.11n: Up to MCS7 802.11ac: Up to MCS9 802.11ax: Up to MCS11		
OPERATING FREQUENCY AND MAXIMUM POWER	Frequency	MAX Output Power(dBm)	MAX.EIPR(dBm)
	5180 ~ 5240MHz	15.68	15.68
	5260 ~ 5320MHz	15.80	15.80
	5500 ~ 5700MHz	16.87	16.87
	5745 ~ 5825MHz	14.27	14.27
NUMBER OF CHANNEL	See section 2.2		
ANTENNA TYPE (REMARK 4/5)	Wire Antenna, with 0dBi gain		
HARDWARE VERSION:	cm215_v1.2		
SOFTWARE VERSION:	UP-F69L		
I/O PORTS	Refer to user’s manual		
CABLE SUPPLIED	N/A		
Remark:			
1. For a more detailed features description, please refer to the manufacturer’s specifications or the user's manual.			
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.			
3. EUT photo refer to report (Report NO.: FCCSZ2024-0082-EUT).			
4. Please refer to the antenna report.			
5. The EUT only supports full RU.			
6. Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, CVC is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.			
7. The EUT have SISO function, provides 1 completed transmitter and 1 receiver.			



2.2 CARRIER FREQUENCY AND CHANNEL

FOR 5180 ~ 5320MHz

8 channels are provided for 802.11a, 802.11n (HT20), 802.11ac(VHT20), 802.11ax(HE20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
36	5180MHz	40	5200MHz
44	5220 MHz	48	5240MHz
52	5260MHz	56	5280MHz
60	5300MHz	64	5320MHz

4 channels are provided for 802.11n (HT40), 802.11ac(VHT40), 802.11ax(HE40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
38	5190MHz	46	5230 MHz
54	5270MHz	62	5310MHz

FOR 5500 ~ 5700MHz

9 channels are provided for 802.11a, 802.11n (HT20), 802.11ac(VHT20), 802.11ax(HE20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
100	5500MHz	124	5620MHz
104	5520MHz	128	5640MHz
108	5540MHz	132	5660MHz
112	5560MHz	136	5680MHz
116	5580MHz	140	5700MHz
120	5600MHz		

4 channels are provided for 802.11n (HT40), 802.11ac(VHT40), 802.11ax(HE40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
102	5510MHz	126	5630MHz
110	5550MHz	134	5670MHz
118	5590MHz		

**FOR 5745 ~ 5825MHz**

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac(VHT20), 802.11ax(HE20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745MHz	153	5765MHz
157	5785MHz	161	5805MHz
165	5825MHz	--	--

2 channels are provided for 802.11n (HT40), 802.11ac(VHT40), 802.11ax(HE40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
151	5755MHz	159	5795MHz

The channels which were indicated in bold type of the above channel list were selected as representative test channel. Therefore only the data of the test channels were recorded in this report.

2.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	--	√	DC 5V with wifi(5G) link

Where **RE≥1G**: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

NOTE: "--" means no effect.

MODULATION	DATA RATE
802.11a	6Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Overlay HT20)	MCS0
802.11ac VHT40 (Overlay HT40)	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE<1G	24.2deg. C, 59%RH	DC 12V	Liu Yuan
RE≥1G	24.2deg. C, 59%RH	DC 12V	Liu Yuan
PLC	--	--	--
APCM	24.4deg. C, 57%RH	DC 12V	Zhu Yulin



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support Equipment							
NO	Description	Brand		Model No.	Serial Number	Supplied by	
1	DC power supply	WANPTEK		TPS605	N/A	Lab	
Support Cable							
NO	Description	Quantity (Number)	Length (cm)	Detachable (Yes/ No)	Shielded (Yes/ No)	Cores (Number)	Supplied by
1	N/A	N/A	N/A	N/A	N/A	N/A	N/A

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC Part 15, Subpart E (15.407)

KDB 789033 D02 General UNII Test Procedures New Rules v02r01

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards



3 TEST TYPES AND RESULTS

3.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

3.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 30dB under any condition of modulation.

3.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

APPLICABLE TO	LIMIT	
KDB 789033 D02 General UNII Test Procedures New Rules v02r01	FIELD STRENGTH AT 3m	
	PK:74 (dBμV/m)	AV:54 (dBμV/m)
APPLICABLE TO	EIRP LIMIT	EQUIVALENT FIELD STRENGTH AT 3m
15.407(b)(1)	PK:-27 (dBm/MHz)	PK:68.2(dBμV/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)	Note	Note

NOTE:

For transmitters operating in the 5.725-5.85 GHz band:Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the alternative limit.



15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where } P \text{ is the eirp (Watts).}$$

3.1.3 TEST PROCEDURES


- a. The EUT was placed on the top of a rotating table 1.5 meters (above 1 GHz) and 0.8 meters (below 1 GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $> 98\%$) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 TEST SETUP


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:




Note: For the actual test configuration, please refer to the related Item in this test report (Photographs of the Test Setup)




3.1.5 TEST RESULTS - BELOW 1GHz

BELOW 1GHz WORST-CASE DATA





Worst Test Mode	802.11a	Channel	CH 36
Frequency Range	9KHz ~ 1GHz	Detector Function	Quasi-Peak (QP)



NO.	Freq. [MHz]	Reading [dBuV/m]	Factor [dB/m]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]
1	101.593	11.8	16.92	28.72	43.50	14.78	100	217
2	221.206	18.59	17.58	36.17	46.00	9.83	100	50
3	399.995	13.73	21.94	35.67	46.00	10.33	100	166
4	575.971	14.14	25.27	39.41	46.00	6.59	100	132
5	720.321	10.00	27.59	37.59	46.00	8.41	100	166
6	891.058	7.07	29.52	36.59	46.00	9.41	100	324

Remark: 1. 9KHz~30MHz have been test and test data more than 20dB margin.
2. The emission levels of other frequencies were greater than 20dB margin.
3. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB/m).
4. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
5. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]




3.1.6 TEST RESULTS - Band 1 (5180-5240MHz):

ABOVE 1GHz DATA


All test modes have been conducted, and the report only presents the worst case.

Channel	802.11a CH36	Frequency	5180 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5094.06	46.89	7.59	54.48	74.00	19.52	PK
2	5107.02	34.20	7.92	42.12	54.00	11.88	AV
3	5150.00	44.94	8.03	52.97	74.00	21.03	PK
4	5150.00	34.06	8.03	42.09	54.00	11.91	AV
5	5179.06	80.45	7.80	88.25			PK
6	5183.86	72.25	7.68	79.93			AV
7	10360.00	28.10	15.59	43.69	68.20	24.51	PK
8	10360.00	18.97	15.59	34.56	54.00	19.44	AV
9	15540.00	32.17	21.44	53.61	74.00	20.39	PK
10	15540.00	24.22	21.44	45.66	54.00	8.34	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]




Channel	802.11a CH36	Frequency	5180 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5108.94	46.03	8.03	54.06	74.00	19.94	PK
2	5132.96	34.40	8.16	42.56	54.00	11.44	AV
3	5150.00	44.59	8.03	52.62	74.00	21.38	PK
4	5150.00	33.83	8.03	41.86	54.00	12.14	AV
5	5182.90	72.79	7.71	80.50			AV
6	5187.22	81.23	7.57	88.80			PK
7	10360.00	31.43	15.59	47.02	68.20	21.18	PK
8	10360.00	22.69	15.59	38.28	54.00	15.72	AV
9	15540.00	38.86	21.44	60.30	74.00	13.70	PK
10	15540.00	30.11	21.44	51.55	54.00	2.45	AV
							
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]							



Channel		802.11a CH 40		Frequency		5200MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	10400.00	28.23	15.80	44.03	68.20	24.17	AV
2	10400.00	20.60	15.80	36.40	54.00	17.60	PK
3	15600.00	31.26	21.58	52.84	74.00	21.16	AV
4	15600.00	23.10	21.58	44.68	54.00	9.32	PK
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	10400.00	33.71	15.80	49.51	68.20	18.69	PK
2	10400.00	26.38	15.80	42.18	54.00	11.82	AV
3	15600.00	35.37	21.58	56.95	74.00	17.05	PK
4	15600.00	28.15	21.58	49.73	54.00	4.27	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]							



Channel	802.11a CH48	Frequency	5240 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5243.41	73.75	8.03	81.78			AV
2	5247.73	81.60	8.05	89.65			PK
3	5350.00	33.84	9.66	43.50	54.00	10.50	AV
4	5350.00	44.22	9.66	53.88	74.00	20.12	PK
5	5397.09	46.07	9.73	55.80	74.00	18.20	PK
6	5410.06	34.26	10.01	44.27	54.00	9.73	AV
7	10480.00	28.20	15.87	44.07	68.20	24.13	PK
8	10480.00	19.31	15.87	35.18	54.00	18.82	AV
9	15720.00	32.43	22.33	54.76	74.00	19.24	PK
10	15720.00	23.14	22.33	45.47	54.00	8.53	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH48	Frequency	5240 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5243.41	73.88	8.03	81.91			AV
2	5243.89	81.92	8.03	89.95			PK
3	5350.00	34.07	9.66	43.73	54.00	10.27	AV
4	5350.00	44.62	9.66	54.28	74.00	19.72	PK
5	5407.65	34.31	9.95	44.26	54.00	9.74	AV
6	5419.66	46.58	9.52	56.10	74.00	17.90	PK
7	10480.00	34.39	15.87	50.26	68.20	17.94	PK
8	10480.00	25.35	15.87	41.22	54.00	12.78	AV
9	15720.00	34.40	22.33	56.73	74.00	17.27	PK
10	15720.00	24.90	22.33	47.23	54.00	6.77	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]							



3.1.7 TEST RESULTS - Band 2 (5260-5320MHz):


ABOVE 1GHz DATA

All test modes have been conducted, and the report only presents the worst case.

Channel	802.11a CH52	Frequency	5260 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Horizontal

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5101.74	46.29	7.64	53.93	74.00	20.07	PK
2	5130.56	33.94	8.23	42.17	54.00	11.83	AV
3	5150.00	43.96	8.03	51.99	74.00	22.01	PK
4	5150.00	33.71	8.03	41.74	54.00	12.26	AV
5	5281.83	81.94	8.31	90.25			PK
6	5285.19	73.67	8.32	81.99			AV
7	10520.00	26.33	15.70	42.03	68.20	26.17	PK
8	10520.00	17.98	15.70	33.68	54.00	20.32	AV
9	15780.00	23.35	22.35	45.70	74.00	28.30	PK
10	15780.00	12.83	22.35	35.18	54.00	18.82	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH52	Frequency	5260 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5113.75	34.21	7.96	42.17	54.00	11.83	AV
2	5120.47	46.04	7.78	53.82	74.00	20.18	PK
3	5150.00	45.18	8.03	53.21	74.00	20.79	PK
4	5150.00	33.84	8.03	41.87	54.00	12.13	AV
5	5275.59	72.65	8.34	80.99			AV
6	5276.55	80.75	8.34	89.09			PK
7	10520.00	26.46	15.70	42.16	68.20	26.04	PK
8	10520.00	17.96	15.70	33.66	54.00	20.34	AV
9	15780.00	22.63	22.35	44.98	74.00	29.02	PK
10	15780.00	12.80	22.35	35.15	54.00	18.85	AV

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).


4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]



Channel		802.11a CH56		Frequency		5280MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	10560.00	26.59	15.66	42.25	68.20	25.95	PK
2	10560.00	17.66	15.66	33.32	54.00	20.68	AV
3	15840.00	22.90	22.21	45.11	74.00	28.89	PK
4	15840.00	13.34	22.21	35.55	54.00	18.45	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	10560.00	26.91	15.66	42.57	68.20	25.63	PK
2	10560.00	17.79	15.66	33.45	54.00	20.55	AV
3	15840.00	22.21	22.21	44.42	74.00	29.58	PK
4	15840.00	13.26	22.21	35.47	54.00	18.53	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]							



Channel	802.11a CH64	Frequency	5320 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5315.45	82.68	8.78	91.46			PK
2	5326.49	73.78	9.01	82.79			AV
3	5350.00	34.87	9.66	44.53	54.00	9.47	AV
4	5350.00	45.40	9.66	55.06	74.00	18.94	PK
5	5373.08	46.04	9.68	55.72	74.00	18.28	PK
6	5402.37	34.53	9.78	44.31	54.00	9.69	AV
7	10640.00	27.64	15.47	43.11	74.00	30.89	PK
8	10640.00	17.42	15.47	32.89	54.00	21.11	AV
9	15960.00	32.31	22.57	54.88	74.00	19.12	PK
10	15960.00	24.48	22.57	47.05	54.00	6.95	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH64		Frequency	5320 MHz			
Frequency Range	Above 1G		Detector Function	PK/AV			
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5313.05	72.77	8.84	81.61			AV
2	5325.05	80.61	8.94	89.55			PK
3	5350.00	35.66	9.66	45.32	54.00	8.68	AV
4	5350.00	45.47	9.66	55.13	74.00	18.87	PK
5	5406.21	46.62	9.90	56.52	74.00	17.48	PK
6	5410.06	34.32	10.01	44.33	54.00	9.67	AV
7	10640.00	28.77	15.47	44.24	74.00	29.76	PK
8	10640.00	20.34	15.47	35.81	54.00	18.19	AV
9	15960.00	36.63	22.57	59.20	74.00	14.80	PK
10	15960.00	29.51	22.57	52.08	54.00	1.92	AV

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]



3.1.8 TEST RESULTS - Band 3 (5500-5700MHz):


ABOVE 1GHz DATA

All test modes have been conducted, and the report only presents the worst case.

Channel	802.11a CH100	Frequency	5500 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Horizontal

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5409.28	46.14	10.00	56.14	74.00	17.86	PK
2	5442.92	46.69	9.51	56.20	74.00	17.80	PK
3	5460.43	34.30	9.79	44.09	54.00	9.91	AV
4	5470.00	44.32	9.75	54.07	68.20	14.13	PK
5	5493.70	76.91	8.78	85.69			PK
6	5505.95	67.52	9.35	76.87			AV
7	11000.00	30.32	16.33	46.65	74.00	27.35	PK
8	11000.00	21.33	16.33	37.66	54.00	16.34	AV
9	16500.00	26.28	24.06	50.34	68.20	17.86	PK
10	16500.00	19.41	24.06	43.47	54.00	10.53	AV




Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH100	Frequency	5500 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Vertical

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5406.03	46.32	9.89	56.21	74.00	17.79	PK
2	5463.81	34.13	9.77	43.90	54.00	10.10	AV
3	5465.56	46.17	9.77	55.94	68.20	12.26	PK
4	5470.00	44.94	9.75	54.69	68.20	13.51	PK
5	5504.20	77.71	9.24	86.95			PK
6	5505.45	69.49	9.31	78.80			AV
7	11000.00	28.76	16.33	45.09	74.00	28.91	PK
8	11000.00	21.04	16.33	37.37	54.00	16.63	AV
9	16500.00	35.44	24.06	59.50	68.20	8.70	PK
10	16500.00	22.59	24.06	46.65	54.00	7.35	AV




Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel		802.11a CH 116		Frequency		5580MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	11160.00	34.52	16.69	51.21	74.00	22.79	PK
2	11160.00	25.10	16.69	41.79	54.00	12.21	AV
3	16740.00	20.89	25.38	46.27	68.20	21.93	PK
4	16740.00	12.81	25.38	38.19	54.00	15.81	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	11160.00	34.97	16.69	51.66	74.00	22.34	PK
2	11160.00	24.52	16.69	41.21	54.00	12.79	AV
3	16740.00	26.69	25.38	52.07	68.20	16.13	PK
4	16740.00	17.39	25.38	42.77	54.00	11.23	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]							




Channel		802.11a CH140		Frequency		5700 MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5706.18	70.47	8.74	79.21			PK
2	5725.00	45.28	8.89	54.17	68.20	14.03	PK
3	5739.29	46.82	8.92	55.74	68.20	12.46	PK
4	11400.00	30.56	16.60	47.16	74.00	26.84	PK
5	11400.00	20.87	16.60	37.47	54.00	16.53	AV
6	17100.00	21.37	27.23	48.60	68.20	19.60	PK
7	17100.00	11.24	27.23	38.47	54.00	15.53	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]



Channel	802.11a CH140	Frequency	5700 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5706.88	74.93	8.71	83.64			PK
2	5725.00	44.56	8.89	53.45	68.20	14.75	PK
3	5745.40	46.76	8.93	55.69	68.20	12.51	PK
4	11400.00	34.14	16.60	50.74	74.00	23.26	PK
5	11400.00	26.36	16.60	42.96	54.00	11.04	AV
6	17100.00	22.59	27.23	49.82	68.20	18.38	PK
7	17100.00	13.05	27.23	40.28	54.00	13.72	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]



3.1.9 TEST RESULTS - Band 4 (5745-5825MHz):


ABOVE 1GHz DATA

All test modes have been conducted, and the report only presents the worst case.

Channel	802.11a CH149	Frequency	5745 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Horizontal

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5606.19	46.84	8.97	55.81	68.20	12.39	PK
2	5739.57	70.40	8.93	79.33			PK
3	5938.98	46.87	10.78	57.65	68.20	10.55	PK
4	11490.00	28.79	16.45	45.24	74.00	28.76	PK
5	11490.00	22.66	16.45	39.11	54.00	14.89	AV
6	17235.00	21.70	27.05	48.75	68.20	19.45	PK
7	17235.00	14.59	27.05	41.64	54.00	12.36	AV




Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH157	Frequency	5785 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Vertical

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5619.51	46.92	8.99	55.91	68.20	12.29	PK
2	5742.57	76.44	8.94	85.38			PK
3	5935.61	47.07	10.67	57.74	68.20	10.46	PK
4	11490.00	34.49	16.45	50.94	74.00	23.06	PK
5	11490.00	27.02	16.45	43.47	54.00	10.53	AV
6	17235.00	21.48	27.05	48.53	68.20	19.67	PK
7	17235.00	14.46	27.05	41.51	54.00	12.49	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]




Channel		802.11a CH157		Frequency		5785 MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	11570.00	22.38	16.81	39.19	54.00	14.81	AV
2	11570.00	30.87	16.81	47.68	74.00	26.32	PK
3	17355.00	12.21	28.18	40.39	54.00	13.61	AV
4	17355.00	18.83	28.18	47.01	68.20	21.19	PK
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	11570.00	36.57	16.81	53.38	74.00	20.62	PK
2	11570.00	29.76	16.81	46.57	54.00	7.43	AV
3	17355.00	19.11	28.18	47.29	68.20	20.91	PK
4	17355.00	12.78	28.18	40.96	54.00	13.04	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]							



Channel	802.11a CH165	Frequency	5825 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Horizontal

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5633.95	47.26	8.81	56.07	68.20	12.13	PK
2	5826.05	70.42	8.78	79.20			PK
3	5939.73	46.73	10.80	57.53	68.20	10.67	PK
4	11650.00	27.32	16.70	44.02	74.00	29.98	PK
5	11650.00	21.19	16.70	37.89	54.00	16.11	AV
6	17475.00	22.34	28.12	50.46	68.20	17.74	PK
7	17475.00	12.30	28.12	40.42	54.00	13.58	AV




Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH165	Frequency	5825 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Vertical

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5646.34	47.41	8.70	56.11	68.20	12.09	PK
2	5822.86	74.85	8.83	83.68			PK
3	5939.73	48.03	10.80	58.83	68.20	9.37	PK
4	11650.00	34.81	16.70	51.51	74.00	22.49	PK
5	11650.00	28.93	16.70	45.63	54.00	8.37	AV
6	17475.00	19.06	28.12	47.18	68.20	21.02	PK
7	17475.00	11.50	28.12	39.62	54.00	14.38	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



3.2 OCCUPIED BANDWIDTH MEASUREMENT

3.2.1 Measurement procedure

The transmitter antenna output was connected to the spectrum analyzer through an attenuator. The resolution bandwidth shall be set to the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth.

below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

3.2.2 TEST SETUP





3.3 26DB EMISSION BANDWIDTH

3.3.1 LIMITS OF 26DB EMISSION BANDWIDTH

This section is for reporting purpose only, there is on restriction limit of bandwidth


3.3.2 TEST PROCEDURES

FOR 26dB BANDWIDTH

- 1) Set RBW = approximately 1% of the emission bandwidth.
- 2) Set the VBW > RBW.
- 3) Detector = Peak
- 4) Trace mode = max hold.
- 5) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

3.3.3 TEST SETUP

FOR 26dB BANDWIDTH





3.4 6DB EMISSION BANDWIDTH

3.4.1 LIMITS OF 6DB EMISSION BANDWIDTH

The minimum of 6dB Bandwidth Measurement is 0.5MHz.


3.4.2 TEST PROCEDURES

FOR 6dB BANDWIDTH

- 1) Set RBW = 100 kHz.
- 2) Set the video bandwidth (VBW) ≥ 3 RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Sweep = auto couple.
- 6) Allow the trace to stabilize.
- 7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.4.3 TEST SETUP

FOR 6dB BANDWIDTH





3.5 TRANSMIT POWER MEASUREMENT

3.5.1 LIMITS OF TRANSMIT POWER MEASUREMENT(FCC)

Operation Band	EUT Category		LIMIT
U-NII-1		Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
		Fixed point-to-point Access Point	1 Watt (30 dBm)
		Indoor Access Point	1 Watt (30 dBm)
	√	Mobile and Portable client device	250mW (24 dBm)
U-NII-2A	√		250mW(24dBm) or 11 dBm+10LogB*
U-NII-2C	√		250mW(24dBm) or 11 dBm+10LogB*
U-NII-3	√		1 Watt (30 dBm)


NOTE: 1. Where B is the 26dB emission bandwidth in MHz.

3.5.2 TEST PROCEDURES

FOR AVERAGE POWER MEASUREMENT

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is added to measured value.

3.5.3 TEST SETUP





3.6 POWER SPECTRAL DENSITY MEASUREMENT

3.6.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT(FCC)

Operation Band	EUT Category		LIMIT
U-NII-1		Outdoor Access Point	17dBm/ MHz
		Fixed point-to-point Access Point	
		Indoor Access Point	
	√	Mobile and Portable client device	11dBm/ MHz
U-NII-2A	√		11dBm/ MHz
U-NII-2C	√		11dBm/ MHz
U-NII-3	√		30dBm/ 500kHz

3.6.2 TEST PROCEDURE

For U-NII-1, U-NII-2A, U-NII-2Cband:

Using method SA-2


- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 1MHz, Set VBW =3 MHz, Detector = AV
- 3) Set Channel power measure = 1MHz
- 4) Sweep time = auto, trigger set to“free run”.
- 5) Trace average at least 100 traces in power averaging mode.
- 6) Record the max value and add 10 log (1/duty cycle)

For U-NII-3 band:

Using method SA-2

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 300 kHz, Set VBW =1 MHz, Detector = AV
- 3) Set Channel power measure = 1MHz
- 4) Sweep time = auto, trigger set to“free run”.
- 5) Trace average at least 100 traces in power averaging mode.
- 6) Record the max value and add 10 log (1/duty cycle)

3.6.3 TEST SETUP



3.7 FREQUENCY STABILITY


3.7.1 LIMITS OFFREQUENCY STABILITY

The frequency of the carrier signal shall be maintained within band of operation.

3.7.2 TEST PROCEDURES

- The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

3.7.3 TEST SETUP





3.8 ANTENNA REQUIREMENT

3.8.1 LIMITS OFFREQUENCY STABILITY

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. According to FCC 47 CFR Section 15.407(a)(1)(2) , if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 ANTENNA ANTI-REPLACEMENT CONSTRUCTION

The antenna used for this product is Wire antenna and that no antenna other than that furnished by the responsible party shall be used with the device

3.8.3 ANTENNA GAIN

The maximum peak gain of the transmit antenna is 0 dBi.



4 PHOTOGRAPHS OF TEST SETUP

Please refer to the attached file (Test Setup Photo).



5 PHOTOGRAPHS OF THE EUT

Please refer to the attached file (External Photos report and Internal Photos).

----- End of the Report -----



Important

- (1) The test report is invalid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

Address: No. 1301-14&16, Guanguang Road, Xinlan Community, Guanlan Subdistrict, Longhua District, Shenzhen, Guangdong, China

Post Code: 518110 Tel: 0755-23763060-8805

Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn

<http://www.cvc.org.cn>