

TEST REPORT

Product Name : HMI
Model Number : VT-HMI-101-TPK12-MC
Contains FCC ID : 2BEA6TPC121
Contains IC : 31870-TPC121

Prepared for : Vantron Technology, Inc.
Address : 48434 Milmont Drive Fremont, California 94538-7324,
United States

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ENS2605140206W00102R
Date(s) of Tests : May 15, 2026 to June 8, 2026
Date of issue : June 9, 2026

Table of Contents

1 TEST RESULT CERTIFICATION	3
2 EUT TECHNICAL DESCRIPTION	5
3 SUMMARY OF TEST RESULT	6
4 TEST METHODOLOGY	7
4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS	7
4.2 MEASUREMENT EQUIPMENT USED	7
4.3 DESCRIPTION OF TEST MODES	8
5 FACILITIES AND ACCREDITATIONS	9
5.1 FACILITIES	9
5.2 EQUIPMENT	9
5.3 LABORATORY ACCREDITATIONS AND LISTINGS	9
6 TEST SYSTEM UNCERTAINTY	10
7 SETUP OF EQUIPMENT UNDER TEST	11
7.1 RADIO FREQUENCY TEST SETUP 1	11
7.2 RADIO FREQUENCY TEST SETUP 2	11
7.3 CONDUCTED EMISSION TEST SETUP	14
7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	15
7.5 SUPPORT EQUIPMENT	15
8 TEST REQUIREMENTS	16
8.1 RADIATED SPURIOUS EMISSION	17

1 TEST RESULT CERTIFICATION

Applicant : Vantron Technology, Inc.
Address : 48434 Milmont Drive Fremont, California 94538-7324, United States
Manufacturer : Vantron Technology, Inc.
Address : 48434 Milmont Drive Fremont, California 94538-7324, United States
EUT : HMI
Model Name : VT-HMI-101-TPK12-MC
Trademark : Vantron

Measurement Procedure Used:


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS
IC RSS-GEN, Issue 5(04-2018)+A1(03-2019)+A2(02-2021) IC RSS-247 Issue 4(07-2025)	PASS

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2, Part 15.247, IC RSS-247 Issue 4 and IC RSS-GEN, Issue 5.

The test results of this report relate only to the tested sample identified in this report

Date of Test : May 15, 2026 to June 8, 2026

Prepared by : 
Yu Xiaolan /Editor

Reviewer : 
Xia Lili /Supervisor

Approve & Authorized Signer : 
Wang Li /Manager



Modified History

Version	Report No.	Revision Date	Summary
Ver.1.0	ENS2605140206W00102R	/	Original Report
Note: This change is to request approval for mobile category specific host product, Antenna Type is FPC antenna, According to the requirements for antenna Change in KDB178919 D01 Permissive Change Policy v06, the antenna types are different and the gain value is less than the original. Out of Band Emission, Radiated Emission tests were performed to verify RF compliance, and the results of other test items remained unchanged based on the module report.			



2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Product:	HMI
Model Number:	VT-HMI-101-TPK12-MC
Test Sample S/N:	ENS2605140206W001-01
Device Type:	Bluetooth_BT
Data Rate:	1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	79 channels
Antenna Type:	PCB Antenna
Antenna Gain:	Ant1: 3.44 dBi (Note: The antenna information is provided by the customers, which will have a certain impact on the test results.)
Power Supply:	DC12V(from adapter)
Adapter:	Model No:WTB65-1205000-T Input:100-240V~50/60Hz 1.6A Output:12.0V/5.0A 60.0W
Test Voltage:	AC 120V/60Hz
FVIN:	V0.03
Temperature Range:	0-50℃
Date of Received:	May 15, 2026
Date of Test:	May 15, 2026 to June 8, 2026

Note: for more details, please refer to the User's manual of the EUT.

3 SUMMARY OF TEST RESULT

FCC Part Clause	IC Part Clause	Test Parameter	Verdict	Remark
15.247(d) 15.209 15.205	RSS-247 clause 6.6 RSS-Gen clause 8.9 RSS-Gen clause 8.10	Radiated Spurious Emissions	PASS	
NOTE1: N/A (Not Applicable) NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.				

RELATED SUBMITTAL(S)/GRANT(S):

This submittal(s) (test report) is intended for **Contains FCC ID:2BEA6TPC121** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

This submittal(s) (test report) is intended for **Contains IC:31870-TPC121** filing to comply with Section A8 of the IC.



4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J
 FCC 47 CFR Part 15, Subpart C
 IC RSS-GEN, Issue 5(04-2018)+A1(03-2019)+A2(02-2021)
 IC RSS-247 Issue 4(07-2025)
 FCC KDB 558074 D01 15.247 Meas Guidance v05r02

4.2 MEASUREMENT EQUIPMENT USED

For Spurious Emissions Test:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESU 26	100154	2026/5/10	1Year
Pre-Amplifier	Lunar EM	LNA30M3G-25	J10100000070	2026/5/10	1Year
Bilog Antenna	Schwarzbeck	VULB9163	661	2025/5/18	2 Year
Horn antenna	Schwarzbeck	BBHA9120D	9120D-1177	2025/5/17	2 Year
Pre-Amplifier	EMC Solutions	TRLA-010180G55	26033001	2026/4/14	1Year
Loop Antenna	Schwarzbeck	FMZB1519	1519-012	2025/5/13	2 Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	100967	2026/5/8	1Year
Horn antenna	Schwarzbeck	BBHA9170	9170-399	2025/5/13	2 Year
Coaxial Cable	TIMES	NmNm-7-C15702	N/A	2026/5/8	1Year
Coaxial Cable	TIMES	HF290-NMSM-6.5M	N/A	2026/5/8	1Year
Coaxial Cable	TIMES	LMR-240 N-N	N/A	2026/5/8	1Year

For other test items:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Signal Analyzer	KEYSIGHT	N9010B	MY60240204	2025/12/16	1Year
Vector Signal Generator	Agilent	N5182B	MY53050878	2026/5/8	1Year
Analog Signal Generator	Agilent	N5171B	MY53050553	2026/5/8	1Year
RF Control Unit(Power Meter)	Tonscend	JS0806-2	\	2026/5/8	1Year
Temperature&Humidity Chamber	ESPEC	EL-02KA	12107166	2026/5/8	1Year

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation(DH5); 2Mbps for $\pi/4$ -DQPSK modulation(2DH5); 3Mbps for 8DPSK modulation(3DH5);)were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	...	...
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
...	...	...	...	78	2480

Note: $f_c = 2402\text{MHz} + (k-1) \times 1\text{MHz}$ $k=1$ to 79

Test Frequency and channel for Bluetooth

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at:

EMTEK (Shenzhen) Co., Ltd.

Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

: **Accredited by CNAS**

The Certificate Registration Number is L2291

The Laboratory has been assessed and proved to be in compliance with
CNAS-CL01 (identical to ISO/IEC 17025:2017)

Accredited by FCC

Designation Number: CN1204

Test Firm Registration Number: 882943

Accredited by A2LA

The Certificate Number is 4321.01

Accredited by Industry Canada

The Conformity Assessment Body Identifier is CN0008

Name of Firm : EMTEK (SHENZHEN) CO., LTD.


Site Location : Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Parameter	Measurement Uncertainty
Frequency error	$\pm 1.9\%$
Occupied Bandwidth	$\pm 1.9\text{KHz}$
Transmitter output power	$\pm 1.18\text{dB}$
Conducted spurious emissions	$\pm 3.3\text{dB}$
Radiated spurious emissions	$\pm 4.5\text{dB}$
Temperature	$\pm 1.2^\circ\text{C}$
Humidity	$\pm 3\%$
DC voltages	$\pm 0.25\text{V}$
Time	$\pm 1\%$


Measurement Uncertainty for a level of Confidence of 95%



7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:

The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:

(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Measurements shall be taken, using the following steps, at a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment (see RSS-Gen for applicable versions of ANSI and CISPR standards).

- (1) Line the ground plane with absorbers between the transmitter and the receive antenna to minimize reflections. The absorbers used should have a minimum-rated attenuation of 20 dB through the measurement frequency range of interest. The absorbers shall be positioned to replicate the layout used when compliance with the applicable acceptability criterion was achieved, as set forth in the aforementioned standards on site validation.
- (2) Set the height of the receive antenna to 1.5 m. The receive antenna must be one that was designed and fabricated to operate over the entire frequency range of interest, for example, an appropriate standard gain horn.
- (3) The distance between the receive antenna and the radiating source shall be sufficient in order to ensure far-field conditions.
- (4) Mount the transmitter at a height of 1.5 m.
- (5) Configure the device under test (DUT) to produce the maximum power spectral density as measured while assessing compliance with Section 6.2.2 (i.e. channel frequency, modulation type and data rate). If the DUT is equipped with a detachable antenna and the antenna is intended for remote installation (i.e. tower-mounted), the DUT may be substituted with a suitable signal generator. The level and frequency settings on the generator shall be set so as to reproduce the maximum power spectral density, measured within a 1 MHz bandwidth, obtained while assessing compliance to Section 6.2.2.
- (6) Position the transmitter or the radiating antenna so that elevation pattern measurements can be taken.
- (7) Find the 0° reference point in the horizontal plane.
- (8) Care should be taken when positioning the receive antenna to avoid cross-polarization. Antennas of known mounting polarization should be assessed with the receive antenna oriented in the same polarity. If the

polarization of the transmit antenna is unknown or the transmit antenna can be mounted in either polarization, e.i.r.p. measurements should be performed to find which mounting polarity provides the highest e.i.r.p. value. Testing shall be carried out with the receive antenna and the DUT mounted in each polarity.

(9) The emission shall be centred on the display of the spectrum analyzer with the following settings:

- i. If the power spectral density of the DUT was assessed with a peak detector and the antenna cannot be detached from the DUT, the spectrum analyzer shall be set to a peak detector with a resolution bandwidth and video bandwidth of 1 MHz.
- ii. If the power spectral density of the DUT was assessed using a sample detector with power averaging and the antenna cannot be detached from the DUT, the spectrum analyzer shall be set to a sample detector, configured to produce 100 power averages and set with a resolution bandwidth, as well as a video bandwidth of 1 MHz.
- iii. If the antenna can be detached from the DUT, a continuous wave (CW) signal equal to that of the power spectral density measurement may be used, the spectrum analyzer shall be set to peak detector with a resolution bandwidth and video bandwidth of 1 MHz.

(10) Rotate the turntable 360° recording the field strength at each step. Throughout the main beam of the antenna, the step size shall be kept to a maximum of 1°.

Once outside the main beam of the antenna, the maximum step size shall be as follows, when compared to the requirements of Section 6.2.2:

- i. Between 0° and 8°, maximum step size of 2°;
- ii. Between 8° and 40°, maximum step size of 4°;
- iii. Between 40° and 45°, maximum step size of 1°;
- iv. Between 45° and 90°, maximum step size of 5°.

Once the mask reaches 90°, the mask will be inverted and the step size will follow in the same manner as above. For the purpose of this procedure, the main beam of the antenna is defined as the 3 dB beamwidth.

(11) Convert the measured field strength values in terms of e.i.r.p. density (dBW/1 MHz) using the following equation:

$$\text{e.i.r.p. density (dBW/MHz)} = 10 \log((E \cdot r)^2 / 30)$$

E = field strength in V/m

r = measurement distance in metres

(12) Plot the results against the emission mask with reference to the horizontal plane.


(13) Using the plot, the 0° can be rotated to determine the worst-case installation tilt angle.

(14) Testing shall be performed using the highest gain antenna for every antenna type, if applicable.


(15) Antenna type(s), antenna model number(s), and worst-case tilt angle(s) necessary to remain compliant with the elevation mask requirement set forth in Section 6.2.2(3) of RSS-247 shall be clearly indicated in the user manual.

The following figure is an example of a polar elevation mask measured using the Method 1 reference to dBμV/m at 3 m.


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (Perfect Share Mini) must be connected to LISN. The LISN shall be placed 0.8m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.8m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 TEST REQUIREMENTS



8.1 RADIATED SPURIOUS EMISSION

8.1.1 Applicable Standard

According to FCC Part 15.247(d), 15.205, 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02
According to IC RSS-Gen and RSS-247

8.1.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ($\mu\text{V/m}$)	300
0.490-1.705	24000/F(KHz)	20 log ($\mu\text{V/m}$)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.1.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.1.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.1.5 Test Results

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Temperature:	25° C
Relative Humidity:	60%
ATM Pressure:	1011 mbar

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);


Limit line = Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz(1GHz to 25GHz)

All the antenna(Antenna 1) and modes(GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1,GFSK) result recorded was report as below:

no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 1GHz to 18 GHz.

Test mode: GFSK Frequency: Channel 0: 2402MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1665	47.17	-25.62	74.00	26.83	PK	Vertical
2	5135.625	44.31	-16.30	74.00	29.69	PK	Vertical
3	17966.25	57.98	-0.12	74.00	16.02	PK	Vertical

AV Final Data List


NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	1665	34.25	54.00	19.75	AV	Vertical
2	5135.625	21.60	54.00	32.40	AV	Vertical
3	17966.25	34.81	54.00	19.19	AV	Vertical



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1665	46.37	-25.62	74.00	27.63	PK	Horizontal
2	5336.25	43.84	-15.65	74.00	30.16	PK	Horizontal
3	17979.375	58.01	0.26	74.00	15.99	PK	Horizontal


AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	1665	34.24	54.00	19.76	AV	Horizontal
2	5336.25	22.49	54.00	31.51	AV	Horizontal
3	17979.375	35.12	54.00	18.88	AV	Horizontal

Test mode: GFSK Frequency: Channel 39: 2441MHz



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1665	48.14	-25.62	74.00	25.86	PK	Vertical
2	5017.5	42.98	-16.58	74.00	31.02	PK	Vertical
3	17971.875	57.43	0.04	74.00	16.57	PK	Vertical


AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	1665	34.31	54.00	19.69	AV	Vertical
2	5017.5	21.35	54.00	32.65	AV	Vertical
3	17971.875	35.48	54.00	18.52	AV	Vertical



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1665	41.46	-25.62	74.00	32.54	PK	Horizontal
2	5274.375	42.56	-15.94	74.00	31.44	PK	Horizontal
3	17971.875	56.66	0.04	74.00	17.34	PK	Horizontal


AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	1665	34.11	54.00	19.89	AV	Horizontal
2	5274.375	22.51	54.00	31.49	AV	Horizontal
3	17971.875	35.19	54.00	18.81	AV	Horizontal

Test mode: GFSK Frequency: Channel 78: 2480MHz



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1665	48.10	-25.62	74.00	25.90	PK	Vertical
2	5317.5	42.80	-15.73	74.00	31.20	PK	Vertical
3	17975.625	57.72	0.14	74.00	16.28	PK	Vertical

AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	1665	34.59	54.00	19.41	AV	Vertical
2	5317.5	22.71	54.00	31.29	AV	Vertical
3	17975.625	35.34	54.00	18.66	AV	Vertical




Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1666	41.59	-25.62	74.00	32.41	PK	Horizontal
2	5150.625	42.98	-16.31	74.00	31.02	PK	Horizontal
3	17964.375	56.68	-0.17	74.00	17.32	PK	Horizontal

AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	1666	34.86	54.00	19.14	AV	Horizontal
2	5150.625	21.51	54.00	32.49	AV	Horizontal
3	17964.375	34.51	54.00	19.49	AV	Horizontal

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	Channel 0: 2402MHz	GFSK	V



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2388.4528	49.11	30.21	74.00	24.89	PK	Vertical


AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	2388.4528	36.81	54.00	17.19	AV	Vertical

Test Model

Spurious Emission in Restricted Band 2310-2390MHz
Channel 0: 2402MHz

GFSK

H




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2387.9993	48.74	30.21	74.00	25.26	PK	Horizontal

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	2387.9993	36.45	54.00	17.55	AV	Horizontal

Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz Channel 78: 2480MHz	GFSK	V
------------	--	------	---



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.8729	46.33	30.55	74.00	27.67	PK	Vertical


AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	2483.8729	37.02	54.00	16.98	AV	Vertical

Test Model

Spurious Emission in Restricted Band 2483.5-2500MHz
Channel 78: 2480MHz

GFSK

H



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2485.3134	46.14	30.55	74.00	27.86	PK	Horizontal

AV Final Data List


NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	2485.3134	36.90	54.00	17.10	AV	Horizontal

Test Model

Spurious Emission in Restricted Band
Hopping

GFSK

V



Suspected Data List


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2384.6949	45.22	31.90	74.00	28.78	PK	Vertical
2	2457.996	85.43	32.02	-	-	PK	Vertical
3	2496.5155	46.02	32.13	74.00	27.98	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	2384.6949	38.41	54.00	15.59	AV	Vertical
2	2496.5155	38.93	54.00	15.07	AV	Vertical

Test Model

Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz
Hopping GFSK H



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2369.4898	45.11	31.81	74.00	28.89	PK	Horizontal
2	2455.0817	87.58	32.02	-	-	PK	Horizontal
3	2489.3565	45.74	32.11	74.00	28.26	PK	Horizontal


AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	2369.4898	38.65	54.00	15.35	AV	Horizontal
2	2489.3565	38.34	54.00	15.66	AV	Horizontal

■ Spurious Emission below 1GHz(30MHz to 1GHz)

All the antenna(Antenna 1) and modes(GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1,GFSK) result recorded was report as below:

Mode:	BT 2402
-------	---------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	58.1582	39.80	-11.36	28.44	PK	40.00	11.56	Vertical
2	63.013	48.01	-12.00	36.01	PK	40.00	3.99	Vertical
3	78.5485	45.10	-14.23	30.87	PK	40.00	9.13	Vertical
4	84.3744	44.88	-13.81	31.07	PK	40.00	8.93	Vertical
5	215.455	43.32	-10.99	32.33	PK	43.50	11.17	Vertical
6	479.559	43.90	-3.95	39.95	PK	46.00	6.05	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	58.1582	-11.36	26.19	40.00	13.81
2	63.013	-12.00	33.76	40.00	6.24
3	78.5485	-14.23	29.34	40.00	10.66
4	84.3744	-13.81	29.54	40.00	10.46
5	215.4555	-10.99	30.80	43.50	12.70
6	479.5596	-3.95	38.09	46.00	7.91


Mode:	BT 2402
-------	---------



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	66.8969	38.48	-12.52	25.96	PK	40.00	14.04	Horizontal
2	218.368	41.22	-10.80	30.42	PK	46.00	15.58	Horizontal
3	229.049	41.40	-10.44	30.96	PK	46.00	15.04	Horizontal
4	479.559	38.76	-3.95	34.81	PK	46.00	11.19	Horizontal
5	699.97	30.83	0.12	30.95	PK	46.00	15.05	Horizontal
6	797.067	36.60	0.43	37.03	PK	46.00	8.97	Horizontal

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	66.8969	-12.52	23.97	40.00	16.03
2	218.3684	-10.80	28.10	46.00	17.90
3	229.049	-10.44	29.36	46.00	16.64
4	479.5596	-3.95	33.21	46.00	12.79
5	699.97	0.12	29.02	46.00	16.98
6	797.0671	0.43	35.10	46.00	10.90

Mode:	BT 2441
-------	---------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	58.1582	40.14	-11.36	28.78	PK	40.00	11.22	Vertical
2	66.8969	46.47	-12.52	33.95	PK	40.00	6.05	Vertical
3	70.7808	44.19	-13.06	31.13	PK	40.00	8.87	Vertical
4	84.3744	43.57	-13.81	29.76	PK	40.00	10.24	Vertical
5	197.007	44.66	-12.21	32.45	PK	43.50	11.05	Vertical
6	479.559	43.39	-3.95	39.44	PK	46.00	6.56	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	58.1582	-11.36	26.70	40.00	13.30
2	66.8969	-12.52	32.59	40.00	7.41
3	70.7808	-13.06	29.44	40.00	10.56
4	84.3744	-13.81	28.07	40.00	11.93
5	197.007	-12.21	29.48	43.50	14.02
6	479.5596	-3.95	36.47	46.00	9.53

Mode:	BT 2441
-------	---------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	65.9259	36.62	-12.40	24.22	PK	40.00	15.78	Horizontal
2	73.6937	38.12	-13.50	24.62	PK	40.00	15.38	Horizontal
3	214.484	42.37	-11.05	31.32	PK	43.50	12.18	Horizontal
4	479.559	38.55	-3.95	34.60	PK	46.00	11.40	Horizontal
5	699.97	30.66	0.12	30.78	PK	46.00	15.22	Horizontal
6	797.067	35.89	0.43	36.32	PK	46.00	9.68	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	65.9259	-12.40	21.83	40.00	18.17
2	73.6937	-13.50	21.91	40.00	18.09
3	214.4845	-11.05	28.61	43.50	14.89
4	479.5596	-3.95	32.60	46.00	13.40
5	699.97	0.12	28.78	46.00	17.22
6	797.0671	0.43	34.32	46.00	11.68


Mode:	BT 2480
-------	---------



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	58.1582	40.12	-11.36	28.76	PK	40.00	11.24	Vertical
2	64.955	46.77	-12.26	34.51	PK	40.00	5.49	Vertical
3	70.7808	45.40	-13.06	32.34	PK	40.00	7.66	Vertical
4	83.4034	44.13	-13.95	30.18	PK	40.00	9.82	Vertical
5	479.559	43.33	-3.95	39.38	PK	46.00	6.62	Vertical
6	528.108	37.56	-3.10	34.46	PK	46.00	11.54	Vertical

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	58.1582	-11.36	25.77	40.00	14.23
2	64.955	-12.26	32.24	40.00	7.76
3	70.7808	-13.06	30.07	40.00	9.93
4	83.4034	-13.95	28.63	40.00	11.37
5	479.5596	-3.95	37.83	46.00	8.17
6	528.1081	-3.10	32.58	46.00	13.42

Mode:	BT 2480
-------	---------



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	64.955	38.27	-12.26	26.01	PK	40.00	13.99	Horizontal
2	73.6937	38.35	-13.50	24.85	PK	40.00	15.15	Horizontal
3	313.523	38.72	-7.89	30.83	PK	46.00	15.17	Horizontal
4	479.559	38.78	-3.95	34.83	PK	46.00	11.17	Horizontal
5	666.957	31.22	-0.57	30.65	PK	46.00	15.35	Horizontal
6	797.067	35.94	0.43	36.37	PK	46.00	9.63	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	64.955	-12.26	24.75	40.00	15.25
2	73.6937	-13.50	23.59	40.00	16.41
3	313.5235	-7.89	28.29	46.00	17.71
4	479.5596	-3.95	33.01	46.00	12.99
5	666.957	-0.57	28.83	46.00	17.17
6	797.0671	0.43	34.55	46.00	11.45

*** End of Report ***