

TEST REPORT

Reference No...... : WTX25X11297186W001
FCC ID..... : 2BEAP-K26
Applicant..... : Dongguan Lingdu Electronic Technology Co., Ltd.
Address..... : No.1, Longcheng Street, Qingxi Town, Dongguan City, Guangdong
Province, China
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : CAMERA
Model No...... : K26
Standards..... : FCC Part 15.407
Date of Receipt sample..... : 2025-11-12
Date of Test..... : 2025-11-12 to 2025-12-16
Date of Issue..... : 2025-12-17
Test Report Form No...... : WTX_Part 15_407W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.


Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Gala Wang/Project Engineer

Approved by:



Jason Su/Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 TEST STANDARDS	6
1.3 TEST METHODOLOGY	6
1.4 TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING	6
1.5 EUT OPERATING DURING TEST	8
1.6 TEST FACILITY	8
1.7 EUT SETUP AND TEST MODE	9
1.8 MEASUREMENT UNCERTAINTY	10
1.9 TEST EQUIPMENT LIST AND DETAILS	11
2. SUMMARY OF TEST RESULTS	15
3. ANTENNA REQUIREMENT	16
3.1 STANDARD APPLICABLE	16
3.2 EVALUATION INFORMATION	16
4. AUTOMATICALLY DISCONTINUE TRANSMISSION	17
4.1 STANDARD APPLICABLE	17
4.2 SUMMARY OF TEST RESULTS	17
5. POWER SPECTRAL DENSITY	18
5.1 STANDARD APPLICABLE	18
5.2 TEST PROCEDURE	18
5.3 SUMMARY OF TEST RESULTS/PLOTS	19
6. EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	20
6.1 STANDARD APPLICABLE	20
6.2 TEST PROCEDURE	20
6.3 SUMMARY OF TEST RESULTS/PLOTS	22
7. MAXIMUM CONDUCTED OUTPUT POWER	23
7.1 STANDARD APPLICABLE	23
7.2 TEST PROCEDURE	23
7.3 SUMMARY OF TEST RESULTS/PLOTS	24
8. RADIATED SPURIOUS EMISSIONS	25
8.1 STANDARD APPLICABLE	25
8.2 TEST PROCEDURE	25
8.3 TEST RECEIVER SETUP	27
8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION	27
8.5 SUMMARY OF TEST RESULTS/PLOTS	27
9. FREQUENCY STABILITY	147
9.1 STANDARD APPLICABLE	147
9.2 TEST PROCEDURE	147
9.3 SUMMARY OF TEST RESULTS/PLOTS	147
10. CONDUCTED EMISSIONS	148
10.1 TEST PROCEDURE	148
10.2 BASIC TEST SETUP BLOCK DIAGRAM	148
10.3 TEST RECEIVER SETUP	148
10.4 SUMMARY OF TEST RESULTS/PLOTS	148
APPENDIX SUMMARY	151
APPENDIX A1: EMISSION BANDWIDTH	152
APPENDIX A2: OCCUPIED CHANNEL BANDWIDTH	179
APPENDIX A3: MIN EMISSION BANDWIDTH	206
APPENDIX B: DUTY CYCLE	213
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	240
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	267

Reference No.: WTX25X11297186W001

APPENDIX E: FREQUENCY STABILITY 294

APPENDIX PHOTOGRAPHS 328

Report version

Version No.	Date of issue	Description
Rev.00	2025-12-17	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	CAMERA
Trade Name:	/
Model No.:	K26
Adding Model(s):	CL01, CL02, CL01N, CL02N, CL01G, CL02G, CL05, CL06, CL05G, CL06G, K26-SL
Rated Voltage:	Type-C DC 5V Battery 3.6V
Battery Capacity:	10000mAh
Power Adapter:	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model K26, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11a, 802.11n-HT20, 802.11n-HT40, 802.11ac-VHT20/40, 802.11ax-HE20/40,
Frequency Range:	5180-5240MHz, 5260-5320MHz 5500-5700MHz, 5745-5825MHz
Max. RF Output Power:	20.15dBm (Conducted)
Type of Modulation:	BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Type of Antenna:	FPC Antenna
Antenna Gain:	2.05dBi
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.407: General technical requirements.

ANSI C63.10-2020: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

KDB789033 D02 v02r01: Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-Nii) Devices Part 15, Subparte.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, KDB789033 D02 v02r01. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Table for parameters of Test Software setting

Enter instructions through the SecureCRT serial port tool, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Mode	Test Frequency (MHz)												
	NCB: 20MHz												
	5180	5200	5240	5260	5280	5320	5500	5580	5700	5720	5745	5785	5825
802.11a 6Mbps	18	18	17	17	17	17	17	17	17	17	17	17	17
802.11n-HT20 MCS0	16	15	14	15	15	15	15	15	15	15	15	15	15
802.11ac-VHT20 MCS0	16	15	14	15	15	15	15	15	15	15	15	15	15
802.11ax-HE20 MCS0	15	14	12	14	14	14	13	13	13	14	14	14	14
Mode	NCB: 40MHz												
	5190	5230	5270	5310	5510	5550	5670	5710	5755	5795			
802.11n-HT40 MCS0	15	14	15	15	15	15	15	15	15	15	15		
802.11ac-VHT40	15	14	15	15	15	15	15	15	15	15	15		

Reference No.: WTX25X11297186W001

MCS0										
802.11ax-HE40 MCS0	14	13	13	13	13	13	13	13	13	13

1.5 EUT Operating during test

EUT was programmed to be in continuously transmitting mode. During the test, EUT operation to normal function and programs under Android were executed.

1.6 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.7 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11a	5180MHz,5200MHz,5240MHz,5260MHz,5280MHz,5320MHz,5500MHz,5580MHz,5700MHz,5745MHz, 5785MHz,5825MHz
TM2	802.11n-HT20	5180MHz,5200MHz,5240MHz,5260MHz,5280MHz,5320MHz,5500MHz,5580MHz,5700MHz,5745MHz, 5785MHz,5825MHz
TM3	802.11ac-VHT20	5180MHz,5200MHz,5240MHz,5260MHz,5280MHz,5320MHz,5500MHz,5580MHz,5700MHz,5745MHz, 5785MHz,5825MHz
TM4	802.11ax-HE20	5180MHz,5200MHz,5240MHz,5260MHz,5280MHz,5320MHz,5500MHz,5580MHz,5700MHz,5745MHz, 5785MHz,5825MHz
TM5	802.11n-HT40	5190MHz,5230MHz,5270MHz,5310MHz,5510MHz,5550MHz,5670MHz,5755MHz,5795MHz
TM6	802.11ac-VHT40	5190MHz,5230MHz,5270MHz,5310MHz,5510MHz,5550MHz,5670MHz,5755MHz,5795MHz
TM7	802.11ax-HE40	5190MHz,5230MHz,5270MHz,5310MHz,5510MHz,5550MHz,5670MHz,5755MHz,5795MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC Cable	1.5	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Adapter	Iotie	CHCRIO160	/

1.8 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.57\text{dB}$
Occupied Bandwidth	Conducted	$\pm 0.015\text{MHz}$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emission 1#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Conducted Emission 2#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Transmitter Spurious Emissions chamber A	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.70\text{dB}$
		@1GHz to 6GHz: $\pm 5.88\text{dB}$
		@6GHz to 18GHz: $\pm 5.96\text{dB}$
Transmitter Spurious Emissions chamber B	Radiated	@30MHz to 1GHz: $\pm 5.36\text{dB}$
Transmitter Spurious Emissions chamber C	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.70\text{dB}$
		@1GHz to 6GHz: $\pm 5.88\text{dB}$
		@6GHz to 18GHz: $\pm 5.96\text{dB}$

1.9 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2025-02-23	2026-02-22
WTXE1005A 1005	Spectrum Analyzer	Agilent	N9020A	US471401 02	2025-02-23	2026-02-22
WTXE1084A 1001	Spectrum Analyzer	Agilent	N9020A	MY543205 48	2025-02-23	2026-02-22
WTXE1005A 1006	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2025-02-23	2026-02-22
WTXW1105A 1010	Spectrum Analyzer	KEYSIGHT	N9020A	MY512856 77	2025-02-23	2026-02-22
WTXE1105A 1008	RF Control Unit	Tonscend	JS0806-2	24F80620 870	2025-02-23	2026-02-22
WTXE1103A 1003	Attenuator	Pasternack	PE4007-4	/	2025-02-23	2026-02-22
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2025-02-23	2026-02-22
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2025-02-23	2026-02-22
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22
WTXE1007A 1002	Amplifier	HP	8447F	2805A034 75	2025-02-23	2026-02-22
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2025-02-23	2026-02-22
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☐ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2025-02-23	2026-02-22
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22

WTXE1065A 1001	Amplifier	C&D	PAP-1.0G18	14918	2025-02-23	2026-02-22
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2025-02-23	2026-02-22
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2025-02-23	2026-02-22
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2025-02-23	2026-02-22
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2025-02-23	2026-02-22
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
☒ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2025-02-23	2026-02-22
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25
WTXE1007A 1003	Amplifier	HP	8447F	2944A038 69	2025-02-23	2026-02-22
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1034-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22

WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☒ Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2025-02-23	2026-02-22
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2025-06-13	2027-06-12
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2025-02-23	2026-02-22
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2024-12-08	2025-12-07
					2025-11-25	2026-11-24
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2025-02-23	2026-02-22
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2025-02-23	2026-02-22
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2025-02-23	2026-02-22
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2025-02-23	2026-02-22
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2025-02-23	2026-02-22
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22

Software List			
Description	Manufacturer	Model	Version
EMI Test Software/EZ-EMC (Radiated Emission A)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission B)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission C)	Farad	RA-03A1-2	1.1.4.2
EMI Test Software/EZ-EMC (Conducted Emission Room 1#)	Farad	3A1*CE-RE	1.1.4.3
EMI Test Software/EZ-EMC (Conducted Emission Room 2#)	Farad	3A1*CE-RE	1.1.4.3
RF Test System	Tonscend	JS1120-3	V3.5.39

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.405	Antenna Requirement	Compliant
15.407 (c)	Automatically Discontinue Transmission	Compliant
§15.207; §15.407(b)(6)	Conducted Emission	Compliant
§15.407(a)(1),(2)	Power Spectral Density	Compliant
§15.407(e)	Emission Bandwidth and Occupied Bandwidth	Compliant
§15.407(a)(1),(2)	Maximum Conducted Output Power	Compliant
§15.407(b)(1),(2),(3),(4)	Undesirable emission	Compliant
§15.205; §15.209; §15.407(b)(1),(2),(3)	Radiated Emission	Compliant
§15.407(g)	Frequency Stability	Compliant
§15.407(h)	Dynamic Frequency Selection (DFS)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has an FCP antenna, fulfill the requirement of this section.

4. Automatically Discontinue Transmission

4.1 Standard Applicable

According to FCC Part 15.407(c), the device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

4.2 Summary of Test Results

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

5. Power Spectral Density

5.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11 \text{ dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.2 Test Procedure

According to 789033 D02 v02r01 General UNII Test Procedures New Rules v02, the following is the measurement procedure.

For devices operating in the bands 5.15-5.25GHz, 5.25-5.35GHz, and 5.47-5.725GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85GHz, the rules specify a measurement bandwidth of 500kHz. Many spectrum analyzers do not have 500kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500kHz, "provided that the measured power is integrated over the full

reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1MHz, or 500kHz). If measurements are performed using a reduced resolution bandwidth ($< 1\text{MHz}$, or $< 500\text{kHz}$) and integrated over 1 MHz, or 500kHz bandwidth, the following adjustments to the procedures apply:

- a) Set $\text{RBW} \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $\text{VBW} \geq 3 \text{ RBW}$.
- c) If measurement bandwidth of Maximum PSD is specified in 500kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 500\text{kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 1\text{MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100kHz for the sections 5.c) and 5.d) above, since $\text{RBW}=100\text{kHz}$ is available on nearly all spectrum analyzers.

5.3 Summary of Test Results/Plots

Please refer to Appendix D

6. Emission Bandwidth and Occupied Bandwidth

6.1 Standard Applicable

According to 15.407(a) and (e):

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(e) Within the 5.725-5.85GHz band, the minimum 6dB bandwidth of U-NII devices shall be at least 500kHz.

6.2 Test Procedure

According to 789033 D02 v02r0r section C&D, the following is the measurement procedure.

1. Emission Bandwidth (EBW)

a) Set RBW = approximately 1% of the emission bandwidth.

b) Set the VBW > RBW.

- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85GHz Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

D. 99 Percent Occupied Bandwidth

The 99-percent occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Measurement of the 99-percent occupied bandwidth is required only as a condition for using the optional band-edge measurement techniques described in section II.G.3.d). Measurements of 99-percent occupied bandwidth may also optionally be used in lieu of the EBW to 789033 D02 v02r01 General UNII Test Procedures New Rules v01 define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in section II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with 15.407(a).

The following procedure shall be used for measuring (99 %) power bandwidth:

- 1. Set center frequency to the nominal EUT channel center frequency.
- 2. Set span = 1.5 times to 5.0 times the OBW.
- 3. Set RBW = 1 % to 5 % of the OBW
- 4. Set VBW $\geq 3 \times$ RBW
- 5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- 6. Use the 99 % power bandwidth function of the instrument (if available).
- 7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency.

Reference No.: WTX25X11297186W001

The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6.3 Summary of Test Results/Plots

Please refer to Appendix A1&A2&A3

7. Maximum Conducted Output Power

7.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

7.2 Test Procedure

According to KDB789033 D02 v02r01 section E, the following is the measurement procedure.

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1MHz.
- (iii) Set VBW $\geq$ 3MHz.
- (iv) Number of points in sweep $\geq$ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that

narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

7.3 Summary of Test Results/Plots

Please refer to Appendix C

8. Radiated Spurious Emissions

8.1 Standard Applicable

According to §15.407(b), undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725GHz band: All emissions outside of the 5.47-5.725GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85GHz band:
 - (i) All emissions shall be limited to a level of -27dBm/MHz at 75MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6dBm/MHz at 5MHz above or below the band edge, and from 5MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

According to §15.407(b)(6), Unwanted emissions below 1GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

According to §15.407(b)(7), The provisions of §15.205 apply to intentional radiators operating under this section.

789033 D02 v02r01 General UNII Test Procedures New Rules v01

If radiated measurements are performed, field strength is then converted to EIRP as follows:

$$\text{EIRP} = ((E \cdot d)^2) / 30$$

where:


- E is the field strength in V/m;
- d is the measurement distance in meters;
- EIRP is the equivalent isotropically radiated power in watts.

8.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.205 15.407(b)(6) and FCC Part 15.209 Limit..

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



8.3 Test Receiver Setup

During the radiated emission test for above 1GHz, the test receiver was set with the following configurations:

For peak detector:

RBW = 1000kHz, VBW = 3000kHz, Sweep Time = Auto

For average detector:

RBW = 1000kHz, VBW = 10Hz, Sweep Time = Auto

8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.5 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


- Spurious Emission From 30MHz to 1GHz
- 5150-5250MHz

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.5112	31.35	-10.18	21.17	40.00	-18.83	-	-	peak
2	103.3353	39.16	-13.00	26.16	43.50	-17.34	-	-	peak
3	159.7586	39.29	-8.53	30.76	43.50	-12.74	-	-	peak
4	207.1968	40.92	-11.73	29.19	43.50	-14.31	-	-	peak
5	484.9068	33.27	-4.66	28.61	46.00	-17.39	-	-	peak
6	804.2523	31.44	1.01	32.45	46.00	-13.55	-	-	peak

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	42.43	-10.13	32.30	40.00	-7.70	-	-	peak
2	51.5365	31.03	-8.99	22.04	40.00	-17.96	-	-	peak
3	163.1623	33.72	-8.58	25.14	43.50	-18.36	-	-	peak
4	240.1442	32.65	-9.98	22.67	46.00	-23.33	-	-	peak
5	505.7891	32.60	-4.23	28.37	46.00	-17.63	-	-	peak
6	798.6205	29.98	0.99	30.97	46.00	-15.03	-	-	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	100.4712	41.17	-13.50	27.67	43.50	-15.83	-	-	peak
2	134.0194	38.41	-9.74	28.67	43.50	-14.83	-	-	peak
3	160.8852	38.90	-8.51	30.39	43.50	-13.11	-	-	peak
4	241.8377	39.64	-9.91	29.73	46.00	-16.27	-	-	peak
5	484.9068	32.37	-4.66	27.71	46.00	-18.29	-	-	peak
6	765.6482	30.32	0.45	30.77	46.00	-15.23	-	-	peak


802.11n-HT20

Test Channel

5180MHz(worst case)


Polarity:

Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	41.45	-10.13	31.32	40.00	-8.68	-	-	peak
2	67.7856	26.83	-10.70	16.13	40.00	-23.87	-	-	peak
3	158.6399	33.91	-8.56	25.35	43.50	-18.15	-	-	peak
4	343.6506	29.68	-7.09	22.59	46.00	-23.41	-	-	peak
5	516.5651	31.70	-4.01	27.69	46.00	-18.31	-	-	peak
6	938.7139	31.36	2.72	34.08	46.00	-11.92	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.5236	32.14	-10.01	22.13	40.00	-17.87	-	-	peak
2	99.7676	37.56	-13.62	23.94	43.50	-19.56	-	-	peak
3	159.7586	37.65	-8.53	29.12	43.50	-14.38	-	-	peak
4	241.8377	38.30	-9.91	28.39	46.00	-17.61	-	-	peak
5	363.5231	34.42	-6.79	27.63	46.00	-18.37	-	-	peak
6	754.9628	29.24	0.28	29.52	46.00	-16.48	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2678	42.29	-10.05	32.24	40.00	-7.76	-	-	peak
2	93.6532	32.38	-14.40	17.98	43.50	-25.52	-	-	peak
3	160.8852	33.98	-8.51	25.47	43.50	-18.03	-	-	peak
4	401.1050	32.37	-6.08	26.29	46.00	-19.71	-	-	peak
5	516.5651	32.70	-4.01	28.69	46.00	-17.31	-	-	peak
6	945.3336	31.93	2.85	34.78	46.00	-11.22	-	-	peak

802.11ax-HE20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	29.94	-10.13	19.81	40.00	-20.19	-	-	peak
2	100.4712	37.68	-13.50	24.18	43.50	-19.32	-	-	peak
3	159.7586	37.83	-8.53	29.30	43.50	-14.20	-	-	peak
4	216.1197	40.83	-11.66	29.17	46.00	-16.83	-	-	peak
5	448.8361	32.71	-5.00	27.71	46.00	-18.29	-	-	peak
6	793.0281	30.87	0.89	31.76	46.00	-14.24	-	-	peak

802.11ax-HE20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2678	43.18	-10.05	33.13	40.00	-6.87	-	-	peak
2	59.7315	27.32	-9.53	17.79	40.00	-22.21	-	-	peak
3	163.1623	35.38	-8.58	26.80	43.50	-16.70	-	-	peak
4	353.4471	30.25	-6.97	23.28	46.00	-22.72	-	-	peak
5	660.6025	29.82	-1.26	28.56	46.00	-17.44	-	-	peak
6	958.7135	30.77	2.97	33.74	46.00	-12.26	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.5112	29.71	-10.18	19.53	40.00	-20.47	-	-	peak
2	100.4712	41.55	-13.50	28.05	43.50	-15.45	-	-	peak
3	166.6385	38.77	-8.75	30.02	43.50	-13.48	-	-	peak
4	246.9901	38.06	-9.71	28.35	46.00	-17.65	-	-	peak
5	478.1394	33.16	-4.79	28.37	46.00	-17.63	-	-	peak
6	952.0001	30.61	2.95	33.56	46.00	-12.44	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.5112	39.91	-10.18	29.73	40.00	-10.27	-	-	peak
2	65.9067	27.60	-10.34	17.26	40.00	-22.74	-	-	peak
3	151.0252	33.90	-8.90	25.00	43.50	-18.50	-	-	peak
4	433.3397	30.93	-5.51	25.42	46.00	-20.58	-	-	peak
5	527.5707	31.38	-3.81	27.57	46.00	-18.43	-	-	peak
6	965.4742	30.62	2.98	33.60	54.00	-20.40	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	80.2383	31.42	-13.08	18.34	40.00	-21.66	-	-	peak
2	100.4712	38.00	-13.50	24.50	43.50	-19.00	-	-	peak
3	140.7767	38.33	-9.32	29.01	43.50	-14.49	-	-	peak
4	227.0164	39.03	-11.13	27.90	46.00	-18.10	-	-	peak
5	241.8377	37.79	-9.91	27.88	46.00	-18.12	-	-	peak
6	684.2259	28.79	-1.07	27.72	46.00	-18.28	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2678	42.83	-10.05	32.78	40.00	-7.22	-	-	peak
2	58.0759	29.07	-9.39	19.68	40.00	-20.32	-	-	peak
3	159.7586	34.68	-8.53	26.15	43.50	-17.35	-	-	peak
4	452.0013	29.67	-4.96	24.71	46.00	-21.29	-	-	peak
5	505.7891	32.06	-4.23	27.83	46.00	-18.17	-	-	peak
6	965.4742	31.75	2.98	34.73	54.00	-19.27	-	-	peak

802.11ax-HE40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.5112	29.89	-10.18	19.71	40.00	-20.29	-	-	peak
2	99.7676	40.52	-13.62	26.90	43.50	-16.60	-	-	peak
3	159.7586	38.21	-8.53	29.68	43.50	-13.82	-	-	peak
4	246.9901	38.97	-9.71	29.26	46.00	-16.74	-	-	peak
5	488.3263	32.00	-4.59	27.41	46.00	-18.59	-	-	peak
6	965.4742	31.79	2.98	34.77	54.00	-19.23	-	-	peak


802.11ax-HE40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	42.23	-10.13	32.10	40.00	-7.90	-	-	peak
2	94.9788	32.93	-14.28	18.65	43.50	-24.85	-	-	peak
3	157.5290	34.45	-8.57	25.88	43.50	-17.62	-	-	peak
4	336.4817	28.99	-7.10	21.89	46.00	-24.11	-	-	peak
5	495.2379	32.56	-4.45	28.11	46.00	-17.89	-	-	peak
6	838.8870	30.28	0.97	31.25	46.00	-14.75	-	-	peak


➤ 5250-5350MHz

802.11a			
Test Channel	5260MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.7811	30.72	-9.97	20.75	40.00	-19.25	-	-	peak
2	99.7676	38.88	-13.62	25.26	43.50	-18.24	-	-	peak
3	139.7909	37.32	-9.40	27.92	43.50	-15.58	-	-	peak
4	162.0197	38.91	-8.53	30.38	43.50	-13.12	-	-	peak
5	240.1442	38.30	-9.98	28.32	46.00	-17.68	-	-	peak
6	938.7139	31.02	2.72	33.74	46.00	-12.26	-	-	peak

802.11a			
Test Channel	5260MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2678	42.73	-10.05	32.68	40.00	-7.32	-	-	peak
2	100.4712	31.56	-13.50	18.06	43.50	-25.44	-	-	peak
3	147.8747	33.21	-8.97	24.24	43.50	-19.26	-	-	peak
4	346.0740	31.18	-7.05	24.13	46.00	-21.87	-	-	peak
5	491.7700	31.99	-4.52	27.47	46.00	-18.53	-	-	peak
6	952.0001	30.50	2.95	33.45	46.00	-12.55	-	-	peak

802.11n-HT20			
Test Channel	5260MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.5236	30.30	-10.01	20.29	40.00	-19.71	-	-	peak
2	91.0574	39.39	-14.44	24.95	43.50	-18.55	-	-	peak
3	103.3353	40.57	-13.00	27.57	43.50	-15.93	-	-	peak
4	159.7586	38.77	-8.53	30.24	43.50	-13.26	-	-	peak
5	241.8377	38.67	-9.91	28.76	46.00	-17.24	-	-	peak
6	893.6557	29.32	1.84	31.16	46.00	-14.84	-	-	peak

802.11n-HT20			
Test Channel	5260MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.5236	43.02	-10.01	33.01	40.00	-6.99	-	-	peak
2	49.7571	30.76	-8.98	21.78	40.00	-18.22	-	-	peak
3	158.6399	34.14	-8.56	25.58	43.50	-17.92	-	-	peak
4	170.1888	33.97	-8.87	25.10	43.50	-18.40	-	-	peak
5	315.8601	29.28	-7.37	21.91	46.00	-24.09	-	-	peak
6	516.5651	31.91	-4.01	27.90	46.00	-18.10	-	-	peak

802.11ac-VHT20			
Test Channel	5260MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.0139	30.86	-10.10	20.76	40.00	-19.24	-	-	peak
2	104.0640	39.87	-12.88	26.99	43.50	-16.51	-	-	peak
3	165.4716	37.40	-8.71	28.69	43.50	-14.81	-	-	peak
4	241.8377	39.07	-9.91	29.16	46.00	-16.84	-	-	peak
5	360.9775	35.51	-6.84	28.67	46.00	-17.33	-	-	peak
6	965.4742	31.78	2.98	34.76	54.00	-19.24	-	-	peak

802.11ac-VHT20			
Test Channel	5260MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.7811	42.86	-9.97	32.89	40.00	-7.11	-	-	peak
2	49.7571	31.86	-8.98	22.88	40.00	-17.12	-	-	peak
3	155.3305	33.91	-8.62	25.29	43.50	-18.21	-	-	peak
4	381.8520	30.63	-6.44	24.19	46.00	-21.81	-	-	peak
5	516.5651	31.51	-4.01	27.50	46.00	-18.50	-	-	peak
6	868.8860	30.37	1.33	31.70	46.00	-14.30	-	-	peak

802.11ax-HE20			
Test Channel	5260MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	31.02	-10.13	20.89	40.00	-19.11	-	-	peak
2	100.4712	40.53	-13.50	27.03	43.50	-16.47	-	-	peak
3	162.0197	37.68	-8.53	29.15	43.50	-14.35	-	-	peak
4	222.2807	40.53	-11.50	29.03	46.00	-16.97	-	-	peak
5	651.3831	28.24	-1.33	26.91	46.00	-19.09	-	-	peak
6	938.7139	31.84	2.72	34.56	46.00	-11.44	-	-	peak

802.11ax-HE20			
Test Channel	5260MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2678	43.35	-10.05	33.30	40.00	-6.70	-	-	peak
2	56.0708	31.33	-9.26	22.07	40.00	-17.93	-	-	peak
3	170.1888	34.19	-8.87	25.32	43.50	-18.18	-	-	peak
4	366.0866	30.41	-6.75	23.66	46.00	-22.34	-	-	peak
5	516.5651	31.81	-4.01	27.80	46.00	-18.20	-	-	peak
6	938.7139	31.09	2.72	33.81	46.00	-12.19	-	-	peak

802.11n-HT40			
Test Channel	5270MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	104.0640	39.69	-12.88	26.81	43.50	-16.69	-	-	peak
2	145.8109	36.62	-9.10	27.52	43.50	-15.98	-	-	peak
3	159.7586	38.96	-8.53	30.43	43.50	-13.07	-	-	peak
4	246.9901	38.12	-9.71	28.41	46.00	-17.59	-	-	peak
5	495.2379	31.57	-4.45	27.12	46.00	-18.88	-	-	peak
6	938.7139	31.62	2.72	34.34	46.00	-11.66	-	-	peak

802.11n-HT40			
Test Channel	5270MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.5236	41.80	-10.01	31.79	40.00	-8.21	-	-	peak
2	44.4657	30.54	-9.10	21.44	40.00	-18.56	-	-	peak
3	156.4259	34.41	-8.58	25.83	43.50	-17.67	-	-	peak
4	254.0312	32.04	-9.43	22.61	46.00	-23.39	-	-	peak
5	343.6506	30.23	-7.09	23.14	46.00	-22.86	-	-	peak
6	642.2923	30.25	-1.59	28.66	46.00	-17.34	-	-	peak

802.11ac-VHT40			
Test Channel	5270MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	31.22	-10.13	21.09	40.00	-18.91	-	-	peak
2	100.4712	38.29	-13.50	24.79	43.50	-18.71	-	-	peak
3	162.0197	38.10	-8.53	29.57	43.50	-13.93	-	-	peak
4	252.2523	37.84	-9.50	28.34	46.00	-17.66	-	-	peak
5	358.4497	34.26	-6.88	27.38	46.00	-18.62	-	-	peak
6	718.7246	27.88	-0.53	27.35	46.00	-18.65	-	-	peak

802.11ac-VHT40			
Test Channel	5270MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2678	42.60	-10.05	32.55	40.00	-7.45	-	-	peak
2	62.3038	27.71	-9.86	17.85	40.00	-22.15	-	-	peak
3	165.4716	33.51	-8.71	24.80	43.50	-18.70	-	-	peak
4	348.5145	30.35	-7.04	23.31	46.00	-22.69	-	-	peak
5	516.5651	32.13	-4.01	28.12	46.00	-17.88	-	-	peak
6	781.9606	29.79	0.71	30.50	46.00	-15.50	-	-	peak

802.11ax-HE40			
Test Channel	5270MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2678	29.45	-10.05	19.40	40.00	-20.60	-	-	peak
2	87.9136	34.52	-14.28	20.24	40.00	-19.76	-	-	peak
3	100.4712	38.69	-13.50	25.19	43.50	-18.31	-	-	peak
4	162.0197	36.91	-8.53	28.38	43.50	-15.12	-	-	peak
5	252.2523	38.42	-9.50	28.92	46.00	-17.08	-	-	peak
6	938.7139	31.09	2.72	33.81	46.00	-12.19	-	-	peak


802.11ax-HE40			
Test Channel	5270MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.0139	43.20	-10.10	33.10	40.00	-6.90	-	-	peak
2	56.0708	31.51	-9.26	22.25	40.00	-17.75	-	-	peak
3	166.6385	34.28	-8.75	25.53	43.50	-17.97	-	-	peak
4	254.0312	31.72	-9.43	22.29	46.00	-23.71	-	-	peak
5	505.7891	32.25	-4.23	28.02	46.00	-17.98	-	-	peak
6	938.7139	29.78	2.72	32.50	46.00	-13.50	-	-	peak


➤ 5470-5725MHz

802.11a			
Test Channel	5500MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2678	33.01	-10.05	22.96	40.00	-17.04	-	-	peak
2	97.6864	37.83	-13.92	23.91	43.50	-19.59	-	-	peak
3	166.6385	38.74	-8.75	29.99	43.50	-13.51	-	-	peak
4	246.9901	38.80	-9.71	29.09	46.00	-16.91	-	-	peak
5	484.9068	32.02	-4.66	27.36	46.00	-18.64	-	-	peak
6	804.2523	30.78	1.01	31.79	46.00	-14.21	-	-	peak

802.11a			
Test Channel	5500MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2678	42.63	-10.05	32.58	40.00	-7.42	-	-	peak
2	100.4712	31.66	-13.50	18.16	43.50	-25.34	-	-	peak
3	162.0197	33.55	-8.53	25.02	43.50	-18.48	-	-	peak
4	246.9901	32.28	-9.71	22.57	46.00	-23.43	-	-	peak
5	464.8867	30.52	-4.90	25.62	46.00	-20.38	-	-	peak
6	938.7139	31.41	2.72	34.13	46.00	-11.87	-	-	peak

802.11n-HT20			
Test Channel	5500MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	29.20	-10.13	19.07	40.00	-20.93	-	-	peak
2	100.4712	42.03	-13.50	28.53	43.50	-14.97	-	-	peak
3	166.6385	41.45	-8.75	32.70	43.50	-10.80	-	-	peak
4	241.8377	39.19	-9.91	29.28	46.00	-16.72	-	-	peak
5	488.3263	32.21	-4.59	27.62	46.00	-18.38	-	-	peak
6	952.0001	31.59	2.95	34.54	46.00	-11.46	-	-	peak

802.11n-HT20			
Test Channel	5500MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.0139	40.98	-10.10	30.88	40.00	-9.12	-	-	peak
2	51.5365	30.62	-8.99	21.63	40.00	-18.37	-	-	peak
3	160.8852	34.53	-8.51	26.02	43.50	-17.48	-	-	peak
4	395.5071	29.54	-6.18	23.36	46.00	-22.64	-	-	peak
5	646.8217	29.89	-1.45	28.44	46.00	-17.56	-	-	peak
6	925.6132	29.94	2.46	32.40	46.00	-13.60	-	-	peak

802.11ac-VHT20			
Test Channel	5500MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	30.66	-10.13	20.53	40.00	-19.47	-	-	peak
2	100.4712	40.56	-13.50	27.06	43.50	-16.44	-	-	peak
3	145.8109	37.35	-9.10	28.25	43.50	-15.25	-	-	peak
4	159.7586	38.38	-8.53	29.85	43.50	-13.65	-	-	peak
5	478.1394	32.08	-4.79	27.29	46.00	-18.71	-	-	peak
6	952.0001	32.67	2.95	35.62	46.00	-10.38	-	-	peak

802.11ac-VHT20			
Test Channel	5500MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.5236	42.19	-10.01	32.18	40.00	-7.82	-	-	peak
2	100.4712	31.60	-13.50	18.10	43.50	-25.40	-	-	peak
3	168.9970	34.68	-8.80	25.88	43.50	-17.62	-	-	peak
4	360.9775	30.02	-6.84	23.18	46.00	-22.82	-	-	peak
5	505.7891	31.71	-4.23	27.48	46.00	-18.52	-	-	peak
6	906.3041	29.98	2.08	32.06	46.00	-13.94	-	-	peak

802.11ax-HE20			
Test Channel	5500MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	30.37	-10.13	20.24	40.00	-19.76	-	-	peak
2	100.4712	38.95	-13.50	25.45	43.50	-18.05	-	-	peak
3	137.8400	35.59	-9.52	26.07	43.50	-17.43	-	-	peak
4	162.0197	39.35	-8.53	30.82	43.50	-12.68	-	-	peak
5	474.7913	32.96	-4.86	28.10	46.00	-17.90	-	-	peak
6	965.4742	32.14	2.98	35.12	54.00	-18.88	-	-	peak

802.11ax-HE20			
Test Channel	5500MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.5236	42.39	-10.01	32.38	40.00	-7.62	-	-	peak
2	38.6357	40.72	-9.73	30.99	40.00	-9.01	-	-	peak
3	159.7586	33.87	-8.53	25.34	43.50	-18.16	-	-	peak
4	350.9722	30.93	-7.01	23.92	46.00	-22.08	-	-	peak
5	527.5707	31.84	-3.81	28.03	46.00	-17.97	-	-	peak
6	972.2827	29.92	2.98	32.90	54.00	-21.10	-	-	peak

802.11n-HT40			
Test Channel	5510MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	30.03	-10.13	19.90	40.00	-20.10	-	-	peak
2	100.4712	40.62	-13.50	27.12	43.50	-16.38	-	-	peak
3	162.0197	37.52	-8.53	28.99	43.50	-14.51	-	-	peak
4	236.7928	38.29	-10.18	28.11	46.00	-17.89	-	-	peak
5	478.1394	32.48	-4.79	27.69	46.00	-18.31	-	-	peak
6	938.7139	32.41	2.72	35.13	46.00	-10.87	-	-	peak

802.11n-HT40			
Test Channel	5510MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.7811	43.64	-9.97	33.67	40.00	-6.33	-	-	peak
2	54.9011	30.41	-9.20	21.21	40.00	-18.79	-	-	peak
3	162.0197	34.89	-8.53	26.36	43.50	-17.14	-	-	peak
4	170.1888	32.82	-8.87	23.95	43.50	-19.55	-	-	peak
5	445.6932	29.59	-5.11	24.48	46.00	-21.52	-	-	peak
6	655.9766	29.47	-1.30	28.17	46.00	-17.83	-	-	peak

802.11ac-VHT40			
Test Channel	5510MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	80.2383	33.94	-13.08	20.86	40.00	-19.14	-	-	peak
2	99.0690	38.18	-13.73	24.45	43.50	-19.05	-	-	peak
3	159.7586	38.30	-8.53	29.77	43.50	-13.73	-	-	peak
4	246.9901	39.72	-9.71	30.01	46.00	-15.99	-	-	peak
5	484.9068	32.69	-4.66	28.03	46.00	-17.97	-	-	peak
6	938.7139	31.33	2.72	34.05	46.00	-11.95	-	-	peak

802.11ac-VHT40			
Test Channel	5510MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.0139	42.42	-10.10	32.32	40.00	-7.68	-	-	peak
2	56.0708	29.43	-9.26	20.17	40.00	-19.83	-	-	peak
3	159.7586	33.22	-8.53	24.69	43.50	-18.81	-	-	peak
4	401.1050	32.73	-6.08	26.65	46.00	-19.35	-	-	peak
5	505.7891	31.03	-4.23	26.80	46.00	-19.20	-	-	peak
6	850.7603	29.98	0.97	30.95	46.00	-15.05	-	-	peak

802.11ax-HE40			
Test Channel	5510MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	30.36	-10.13	20.23	40.00	-19.77	-	-	peak
2	100.4712	37.54	-13.50	24.04	43.50	-19.46	-	-	peak
3	158.6399	38.20	-8.56	29.64	43.50	-13.86	-	-	peak
4	246.9901	38.22	-9.71	28.51	46.00	-17.49	-	-	peak
5	488.3263	32.08	-4.59	27.49	46.00	-18.51	-	-	peak
6	798.6205	30.46	0.99	31.45	46.00	-14.55	-	-	peak


802.11ax-HE40			
Test Channel	5510MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.5112	42.07	-10.18	31.89	40.00	-8.11	-	-	peak
2	57.2654	27.78	-9.33	18.45	40.00	-21.55	-	-	peak
3	163.1623	33.52	-8.58	24.94	43.50	-18.56	-	-	peak
4	358.4497	32.99	-6.88	26.11	46.00	-19.89	-	-	peak
5	505.7891	32.38	-4.23	28.15	46.00	-17.85	-	-	peak
6	952.0001	32.69	2.95	35.64	46.00	-10.36	-	-	peak


➤ 5725-5850MHz

802.11a			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.5112	30.78	-10.18	20.60	40.00	-19.40	-	-	peak
2	100.4712	38.44	-13.50	24.94	43.50	-18.56	-	-	peak
3	159.7586	38.24	-8.53	29.71	43.50	-13.79	-	-	peak
4	240.1442	39.24	-9.98	29.26	46.00	-16.74	-	-	peak
5	401.1050	37.15	-6.08	31.07	46.00	-14.93	-	-	peak
6	965.4742	31.70	2.98	34.68	54.00	-19.32	-	-	peak

802.11a			
Test Channel	5745MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	37.0405	41.87	-9.93	31.94	40.00	-8.06	-	-	peak
2	62.7432	27.40	-9.92	17.48	40.00	-22.52	-	-	peak
3	162.0197	34.71	-8.53	26.18	43.50	-17.32	-	-	peak
4	360.9775	30.68	-6.84	23.84	46.00	-22.16	-	-	peak
5	642.2923	29.41	-1.59	27.82	46.00	-18.18	-	-	peak
6	945.3336	30.82	2.85	33.67	46.00	-12.33	-	-	peak


802.11n-HT20

Test Channel

5745MHz(worst case)


Polarity:

Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.0157	30.89	-10.25	20.64	40.00	-19.36	-	-	peak
2	99.7676	41.27	-13.62	27.65	43.50	-15.85	-	-	peak
3	140.7767	39.58	-9.32	30.26	43.50	-13.24	-	-	peak
4	254.0312	36.00	-9.43	26.57	46.00	-19.43	-	-	peak
5	718.7246	28.72	-0.53	28.19	46.00	-17.81	-	-	peak
6	965.4742	31.11	2.98	34.09	54.00	-19.91	-	-	peak

802.11n-HT20			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.5236	42.59	-10.01	32.58	40.00	-7.42	-	-	peak
2	105.5369	30.76	-12.66	18.10	43.50	-25.40	-	-	peak
3	158.6399	34.38	-8.56	25.82	43.50	-17.68	-	-	peak
4	371.2679	29.88	-6.66	23.22	46.00	-22.78	-	-	peak
5	491.7700	30.44	-4.52	25.92	46.00	-20.08	-	-	peak
6	899.9577	29.50	1.96	31.46	46.00	-14.54	-	-	peak

802.11ac-VHT20			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.5112	31.79	-10.18	21.61	40.00	-18.39	-	-	peak
2	100.4712	39.43	-13.50	25.93	43.50	-17.57	-	-	peak
3	159.7586	38.50	-8.53	29.97	43.50	-13.53	-	-	peak
4	246.9901	38.55	-9.71	28.84	46.00	-17.16	-	-	peak
5	401.1050	37.25	-6.08	31.17	46.00	-14.83	-	-	peak
6	938.7139	31.49	2.72	34.21	46.00	-11.79	-	-	peak

802.11ac-VHT20			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.0139	43.73	-10.10	33.63	40.00	-6.37	-	-	peak
2	56.0708	28.92	-9.26	19.66	40.00	-20.34	-	-	peak
3	124.9249	30.90	-10.50	20.40	43.50	-23.10	-	-	peak
4	157.5290	34.32	-8.57	25.75	43.50	-17.75	-	-	peak
5	371.2679	30.96	-6.66	24.30	46.00	-21.70	-	-	peak
6	516.5651	33.47	-4.01	29.46	46.00	-16.54	-	-	peak

802.11ax-HE20			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	37.0405	30.18	-9.93	20.25	40.00	-19.75	-	-	peak
2	100.4712	39.46	-13.50	25.96	43.50	-17.54	-	-	peak
3	146.8392	38.50	-9.04	29.46	43.50	-14.04	-	-	peak
4	162.0197	38.99	-8.53	30.46	43.50	-13.04	-	-	peak
5	241.8377	38.84	-9.91	28.93	46.00	-17.07	-	-	peak
6	815.6352	31.13	0.99	32.12	46.00	-13.88	-	-	peak

802.11ax-HE20			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2678	40.80	-10.05	30.75	40.00	-9.25	-	-	peak
2	99.7676	31.70	-13.62	18.08	43.50	-25.42	-	-	peak
3	156.4259	34.66	-8.58	26.08	43.50	-17.42	-	-	peak
4	254.0312	31.84	-9.43	22.41	46.00	-23.59	-	-	peak
5	491.7700	30.53	-4.52	26.01	46.00	-19.99	-	-	peak
6	887.3978	30.19	1.70	31.89	46.00	-14.11	-	-	peak

802.11n-HT40			
Test Channel	5755MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	48.0392	26.71	-9.02	17.69	40.00	-22.31	-	-	peak
2	101.1797	39.85	-13.38	26.47	43.50	-17.03	-	-	peak
3	162.0197	39.02	-8.53	30.49	43.50	-13.01	-	-	peak
4	240.1442	38.84	-9.98	28.86	46.00	-17.14	-	-	peak
5	488.3263	32.71	-4.59	28.12	46.00	-17.88	-	-	peak
6	798.6205	30.57	0.99	31.56	46.00	-14.44	-	-	peak

802.11n-HT40			
Test Channel	5755MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.7617	42.11	-10.13	31.98	40.00	-8.02	-	-	peak
2	56.4662	29.96	-9.28	20.68	40.00	-19.32	-	-	peak
3	158.6399	34.11	-8.56	25.55	43.50	-17.95	-	-	peak
4	252.2523	31.76	-9.50	22.26	46.00	-23.74	-	-	peak
5	505.7891	31.92	-4.23	27.69	46.00	-18.31	-	-	peak
6	919.1315	30.47	2.33	32.80	46.00	-13.20	-	-	peak

802.11ac-VHT40			
Test Channel	5755MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.0139	29.38	-10.10	19.28	40.00	-20.72	-	-	peak
2	94.9788	36.29	-14.28	22.01	43.50	-21.49	-	-	peak
3	146.8392	37.13	-9.04	28.09	43.50	-15.41	-	-	peak
4	241.8377	39.26	-9.91	29.35	46.00	-16.65	-	-	peak
5	355.9397	34.68	-6.92	27.76	46.00	-18.24	-	-	peak
6	952.0001	31.57	2.95	34.52	46.00	-11.48	-	-	peak

802.11ac-VHT40			
Test Channel	5755MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2678	42.45	-10.05	32.40	40.00	-7.60	-	-	peak
2	56.0708	29.96	-9.26	20.70	40.00	-19.30	-	-	peak
3	158.6399	34.35	-8.56	25.79	43.50	-17.71	-	-	peak
4	243.5431	31.46	-9.83	21.63	46.00	-24.37	-	-	peak
5	516.5651	33.19	-4.01	29.18	46.00	-16.82	-	-	peak
6	887.3978	30.65	1.70	32.35	46.00	-13.65	-	-	peak

802.11ax-HE40			
Test Channel	5755MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.2626	29.37	-10.21	19.16	40.00	-20.84	-	-	peak
2	97.6864	36.48	-13.92	22.56	43.50	-20.94	-	-	peak
3	141.7694	38.52	-9.23	29.29	43.50	-14.21	-	-	peak
4	241.8377	38.50	-9.91	28.59	46.00	-17.41	-	-	peak
5	590.3511	29.56	-2.36	27.20	46.00	-18.80	-	-	peak
6	938.7139	31.10	2.72	33.82	46.00	-12.18	-	-	peak

802.11ax-HE40			
Test Channel	5755MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.0139	43.32	-10.10	33.22	40.00	-6.78	-	-	peak
2	155.3305	34.21	-8.62	25.59	43.50	-17.91	-	-	peak
3	236.7928	33.19	-10.18	23.01	46.00	-22.99	-	-	peak
4	355.9397	29.98	-6.92	23.06	46.00	-22.94	-	-	peak
5	516.5651	30.82	-4.01	26.81	46.00	-19.19	-	-	peak
6	862.8015	30.09	1.21	31.30	46.00	-14.70	-	-	peak

Remark: '-'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.


➤ Spurious Emission above 1GHz

802.11a- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	55.71	-13.11	42.60	74.00	-31.40	-	-	peak
2	5145.824	70.95	-11.64	59.31	74.00	-14.69	-	-	peak
3	5150.000	62.19	-11.61	50.58	74.00	-23.42	-	-	peak

802.11a- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	43.09	-13.11	29.98	54.00	-24.02	-	-	AVG
2	5150.000	48.18	-11.61	36.57	54.00	-17.43	-	-	AVG

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	56.32	-13.11	43.21	74.00	-30.79	-	-	peak
2	5150.000	77.47	-11.61	65.86	74.00	-8.14	-	-	peak

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	42.99	-13.11	29.88	54.00	-24.12	-	-	AVG
2	5150.000	51.96	-11.61	40.35	54.00	-13.65	-	-	AVG

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	54.86	-13.11	41.75	74.00	-32.25	-	-	peak
2	5150.000	79.91	-11.61	68.30	74.00	-5.70	-	-	peak

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	42.83	-13.11	29.72	54.00	-24.28	-	-	AVG
2	5150.000	50.19	-11.61	38.58	54.00	-15.42	-	-	AVG

802.11ax-HE20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	55.54	-13.11	42.43	74.00	-31.57	-	-	peak
2	5150.000	56.69	-11.61	45.08	74.00	-28.92	-	-	peak

802.11ax-HE20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	42.82	-13.11	29.71	54.00	-24.29	-	-	AVG
2	5150.000	45.03	-11.61	33.42	54.00	-20.58	-	-	AVG

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	55.99	-13.11	42.88	74.00	-31.12	-	-	peak
2	5150.000	76.13	-11.61	64.52	74.00	-9.48	-	-	peak

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	42.97	-13.11	29.86	54.00	-24.14	-	-	AVG
2	5150.000	55.00	-11.61	43.39	54.00	-10.61	-	-	AVG

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	55.08	-13.11	41.97	74.00	-32.03	-	-	peak
2	5150.000	76.59	-11.61	64.98	74.00	-9.02	-	-	peak

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	42.89	-13.11	29.78	54.00	-24.22	-	-	AVG
2	5150.000	51.66	-11.61	40.05	54.00	-13.95	-	-	AVG

802.11ax-HE40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	54.88	-13.11	41.77	74.00	-32.23	-	-	peak
2	5150.000	62.11	-11.61	50.50	74.00	-23.50	-	-	peak

802.11ax-HE40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4500.000	42.73	-13.11	29.62	54.00	-24.38	-	-	AVG
2	5150.000	45.23	-11.61	33.62	54.00	-20.38	-	-	AVG

802.11a- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	70.00	-9.77	60.23	74.00	-13.77	-	-	peak
2	5460.000	56.24	-9.55	46.69	74.00	-27.31	-	-	peak

802.11a- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	44.80	-9.77	35.03	54.00	-18.97	-	-	AVG
2	5460.000	43.14	-9.55	33.59	54.00	-20.41	-	-	AVG

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	69.80	-9.77	60.03	74.00	-13.97	-	-	peak
2	5460.000	55.52	-9.55	45.97	74.00	-28.03	-	-	peak

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	49.41	-9.77	39.64	54.00	-14.36	-	-	AVG
2	5460.000	43.34	-9.55	33.79	54.00	-20.21	-	-	AVG

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	69.78	-9.77	60.01	74.00	-13.99	-	-	peak
2	5460.000	55.63	-9.55	46.08	74.00	-27.92	-	-	peak

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	49.89	-9.77	40.12	54.00	-13.88	-	-	AVG
2	5460.000	43.42	-9.55	33.87	54.00	-20.13	-	-	AVG

802.11ax-HE20- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	72.01	-9.77	62.24	74.00	-11.76	-	-	peak
2	5460.000	56.08	-9.55	46.53	74.00	-27.47	-	-	peak

802.11ax-HE20- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	49.98	-9.77	40.21	54.00	-13.79	-	-	AVG
2	5460.000	43.33	-9.55	33.78	54.00	-20.22	-	-	AVG

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	75.19	-9.77	65.42	74.00	-8.58	-	-	peak
2	5460.000	55.60	-9.55	46.05	74.00	-27.95	-	-	peak

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	56.58	-9.77	46.81	54.00	-7.19	-	-	AVG
2	5460.000	43.34	-9.55	33.79	54.00	-20.21	-	-	AVG

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	76.41	-9.77	66.64	74.00	-7.36	-	-	peak
2	5460.000	56.22	-9.55	46.67	74.00	-27.33	-	-	peak

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	56.71	-9.77	46.94	54.00	-7.06	-	-	AVG
2	5460.000	43.49	-9.55	33.94	54.00	-20.06	-	-	AVG

802.11ax-HE40- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	76.23	-9.77	66.46	74.00	-7.54	-	-	peak
2	5460.000	56.17	-9.55	46.62	74.00	-27.38	-	-	peak

802.11ax-HE40- Restricted Bandedge			
Test Channel	band 5.25-5.35GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	56.49	-9.77	46.72	54.00	-7.28	-	-	AVG
2	5460.000	43.32	-9.55	33.77	54.00	-20.23	-	-	AVG

802.11a- Restricted Bandedge			
Test Channel	band 5.47-5.72GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	55.55	-9.77	45.78	74.00	-28.22	-	-	peak
2	5460.000	60.26	-9.55	50.71	74.00	-23.29	-	-	peak

802.11a- Restricted Bandedge			
Test Channel	band 5.47-5.72GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	43.44	-9.77	33.67	54.00	-20.33	-	-	AVG
2	5460.000	46.46	-9.55	36.91	54.00	-17.09	-	-	AVG

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.47-5.72GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	56.34	-9.77	46.57	74.00	-27.43	-	-	peak
2	5460.000	58.15	-9.55	48.60	74.00	-25.40	-	-	peak

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.47-5.72GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5350.000	43.24	-9.77	33.47	54.00	-20.53	-	-	AVG
2	5460.000	46.00	-9.55	36.45	54.00	-17.55	-	-	AVG