



Electromagnetic Compatibility Test Report

Tests Performed on a Consumer Safety Technology, LLC

Keepr Drive Relay Control, Model KEEPRDRIVE1

Radiometrics Document RP-10157



Product Detail:

FCC ID: 2BEEUKEEPRDRIVE1

Equipment type: 2.4 GHz Bluetooth Radio Transceiver

Test Standards:

US CFR Title 47, Chapter I, FCC Part 15 Subpart C

FCC Part 15 CFR Title 47: 2025

Canada ISSED; RSS-210, Issue 11: 2024 as required for Category I Equipment

IC RSS-GEN Issue 5: 2018

This report concerns: Original Grant for Certification

FCC Part 15.249

Tests Performed For:

Consumer Safety Technology, LLC

12421 Meredith Drive, Suite 100

Urbandale, IA 50323

Test Facility:

Radiometrics Midwest Corporation

12 Devonwood Avenue

Romeoville, IL 60446-1349

(815) 293-0772

Test Date(s):

May 29 to June 25, 2025

Document RP-10157 Revisions:

Rev.	Issue Date	Revised By
0	January 30, 2026	




Table of Contents

1.0 ADMINISTRATIVE DATA.....	3
2.0 TEST SUMMARY AND RESULTS	3
2.1 RF Exposure Compliance Requirements	4
3.0 EQUIPMENT UNDER TEST (EUT) DETAILS	4
3.1 EUT Description.....	4
3.1.1 FCC Section 15.203 & RSS-GEN Antenna Requirements.....	4
4.0 TESTED SYSTEM DETAILS.....	4
4.1 Tested System Configuration.....	4
4.2 EUT Operating Mode	5
4.3 Special Accessories.....	5
4.4 Equipment Modifications	5
5.0 TEST SPECIFICATIONS	5
6.0 TEST PROCEDURE DOCUMENTS.....	6
7.0 RADIOMETRICS' TEST FACILITIES	6
8.0 DEVIATIONS AND EXCLUSIONS FROM THE TEST SPECIFICATIONS.....	6
9.0 CERTIFICATION.....	6
10.0 TEST EQUIPMENT TABLE.....	7
11.0 TEST SECTIONS.....	7
11.1 Radiated RF Emissions.....	7
11.1.1 Field Strength Calculation.....	8
11.1.2 Duty Cycle	8
11.1.3 Radiated Emissions Test Results	10
11.2 Occupied Bandwidth Data.....	15
11.3 Unintentional Emissions (Receive Mode).....	17
11.3.1 Measurement Instrumentation Uncertainty	20
12.0 REVISION HISTORY	20

Notice: This report must not be reproduced (except in full) without the written approval of
Radiometrics Midwest Corporation.



1.0 ADMINISTRATIVE DATA

<i>Equipment Under Test:</i> A Consumer Safety Technology, Keepr Drive Relay Control Model: KEEPRDRIVE1 Serial Number: 1BB0AC0 This will be referred to as the EUT in this Report	
<i>Date EUT Received at Radiometrics:</i> May 29, 2025	<i>Test Date(s):</i> May 29 to June 25 2025
<i>Test Report Written and Authorized By:</i> Joseph Strzelecki Senior EMC Engineer	<i>Test Witnessed By:</i> The tests were not witnessed by personnel from Consumer Safety Technology.
<i>Radiometrics' Personnel Responsible for Test:</i>  01/30/2025 Date Joseph Strzelecki Senior EMC Engineer NARTE EMC-000877-NE Chris D'Alessio EMC Technician	<i>EUT Checked By:</i> Joseph Strzelecki Radiometrics

2.0 TEST SUMMARY AND RESULTS

The EUT (Equipment Under Test) is a Keepr Drive Relay Control, Model KEEPRDRIVE1, manufactured by Consumer Safety Technology. The detailed test results are presented in a separate section. The following is a summary of the test results.

Emissions Tests Results

Environmental Phenomena	Frequency Range	Basic Standard	Test Result
RF Radiated Emissions	30-25,000 MHz	RSS-210 & FCC Part 15	Pass
Occupied Bandwidth Test	Fundamental Freq.	RSS-210 & FCC Part 15	Pass

IEC 17025 Decision Rule:

The declaration of pass or fail is based on the specifications listed above. The declaration of pass or fail did not consider measurement uncertainty.



2.1 RF Exposure Compliance Requirements

Since the power output is less than 10 mW, the EUT meets the FCC requirement for RF exposure, and it is exempt from RSS-102 SAR and RF exposure evaluations. There are no power level adjustments available to the end user. The antenna is permanently attached. The detailed calculations for RF Exposure are presented in a separate document.

3.0 EQUIPMENT UNDER TEST (EUT) DETAILS

3.1 EUT Description

The EUT is a Keepr Drive Relay Control, Model KEEPRDRIVE1, manufactured by Consumer Safety Technology. The EUT was in good working condition during the tests, with no known defects.

3.1.1 FCC Section 15.203 & RSS-GEN Antenna Requirements

The antenna is permanently attached to the printed circuit board. The antenna is internal to the EUT, and it is not readily available to be modified by the end user. Therefore, it meets the 15.203 Requirements.

4.0 TESTED SYSTEM DETAILS

4.1 Tested System Configuration

The system was configured for testing in a typical fashion. The EUT was placed on an 80-cm or 150 cm high, nonconductive test stand. The testing was performed in conditions as close as possible to installed conditions. Wiring was consistent with manufacturer's recommendations. Power was supplied with a 12 V battery.

The identification for all equipment, plus descriptions of all cables used in the tested system, are:

Tested System Configuration List

Item	Description	Type*	Manufacturer	Model Number	Serial Number
1	Keepr Drive Relay Control	E	Consumer Safety Technology, LLC	KEEPRDRIVE1	1BB0AC0
2	Computer	S	Dell	P117F	CQBQPL3
3	Computer Charger	S	Dell	130W	CN-DV363H-CH2DD-275-D2CZ-AD5
4	Remote Display	P	IntoxaLock	1BD7CFA4	2186301

* Type: E = EUT, P = Peripheral, S = Support Equipment; H = Host Computer

**List of System Cables**

QTY	Length (m)	Cable Description	Shielded?
1	2.4 m	Kronos debug harness	Yes
1	2.9 m	USB A to USB A	Yes
1	1.47 m	Filter Assembly	No
1	1.49 m	Griffin Camera assembly	Yes
1	3.23 m	LTE Antenna Assembly	Yes
1	3.12 m	CST Intoxalock legacy handheld	Yes

Type of modulation including the bit rate and symbol rate	1 Mbps transmission rate; BLE uses Gaussian Frequency Shift Keying (GFSK) with a frequency deviation of +/- 185 kHz
Name and version of the test software used to exercise the device	STM32CubeMonitor-RF; Version 2.17.0
Power settings used for the purpose of exercising the device	31 (6 dBm)
Firmware number of the transmitter	V0.6.1

4.2 EUT Operating Mode

The EUT was in its normal GFSK modulation during the tests. It was tested as a stand-alone battery powered device, since that is the configuration in the final installation.

4.3 Special Accessories

No special accessories were used during the tests in order to achieve compliance.

4.4 Equipment Modifications

No modifications were made to the EUT at Radiometrics' test facility in order to comply with the standards listed in this report.

5.0 TEST SPECIFICATIONS

Document	Date	Title
FCC CFR Title 47	2025	Code of Federal Regulations Title 47, Chapter 1, Federal Communications Commission, Part 15 - Radio Frequency Devices
IC RSS-210 Issue 11	2024	Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands) Category I Equipment
IC RSS-Gen Issue 5	2019	General Requirements and Information for the Certification of Radiocommunication Equipment (RSS-Gen)



6.0 TEST PROCEDURE DOCUMENTS

The tests were performed using the procedures from the following specifications:

Document	Date	Title
ANSI C63.4-2014	2014	Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10-2013	2013	American National Standard for Testing Unlicensed Wireless Devices

7.0 RADIOMETRICS' TEST FACILITIES

The results of these tests were obtained at Radiometrics Midwest Corp. in Romeoville, Illinois, USA. Radiometrics is accredited by A2LA (American Association for Laboratory Accreditation) to conform to ISO/IEC 17025: 2017 "General Requirements for the Competence of Calibration and Testing Laboratories". Radiometrics' Lab Code is 121191 and Certification Number is 1495.01. Radiometrics' scope of accreditation includes all of the test methods listed herein. A copy of the accreditation can be accessed on our web site (www.radiomet.com). Radiometrics accreditation status can be verified at A2LA's web site (www.a2la2.org).

The following is a list of shielded enclosures located in Romeoville, Illinois used during the tests:

Chamber E: Is a custom-made anechoic chamber that measures 52' L X 30' W X 18' H. The walls and ceiling are fully lined with RF absorbers. Pro-shield of Collinsville, Oklahoma manufactured the chamber. The floor has a 9' x 9' section of microwave absorber for testing above 1 GHz.

A separate ten-foot long, brass plated, steel ground rod attached via a 6-inch copper braid grounds each of the above chambers. Each enclosure is also equipped with low-pass power line filters.

The FCC has accepted these sites as test site number US1065. The FCC test site Registration Number is 732175. Details of the site characteristics are on file with the Industry Canada as site number IC 3124A with a CAB ID of US0224.

A complete list of the test equipment is provided herein. The calibration due dates are indicated on the equipment list. The equipment is calibrated in accordance with ANSI/NCSL Z540-1 with traceability to the National Institute of Standards and Technology (NIST).

8.0 DEVIATIONS AND EXCLUSIONS FROM THE TEST SPECIFICATIONS

There were no deviations or exclusions from the test specifications.

9.0 CERTIFICATION

Radiometrics Midwest Corporation certifies that the data contained herein was taken under conditions that meet or exceed the requirements of the test specification and the data contained herein was taken with calibrated test equipment. The results relate only to the EUT listed herein.



10.0 TEST EQUIPMENT TABLE

RMC ID	Manufacturer	Description	Model No.	Serial No.	Frequency Range	Cal Period	Cal Date
AMP-05	RMC/Celeritek	Pre-amplifier	MW110G	1001	1.0-12GHz	12 Mo.	02/05/25
AMP-20	Avantek	Pre-amplifier	SF8-0652	15221	8-18GHz	12 Mo.	02/05/25
AMP-59	Amplitech	Pre-amplifier	APTMP44	AMP-59	18-26 GHz	12 Mo.	02/05/25
ANT-48	RMC	Std Gain Horn	HW2020	1001	18-26 GHz	36 Mo.	11/23/22
ANT-66	ETS-Lindgren	Horn Antenna	3115	62580	1.0-18GHz	24 Mo.	03/31/25
ANT-68	EMCO	Log-Periodic Ant.	93146	9604-4456	200-1000MHz	24 Mo.	01/30/24
ANT-80	AH Systems	Bicon Antenna	SAS-540	294	20-330MHz	24 Mo.	01/31/25
CAB-1090	Teledyne	Coaxial Cable	N/A	1090	DC-26 GHz	24 Mo.	12/20/24
CAB-207A	Teledyne	Coaxial Cable	N/A	207A	DC-26 GHz	24 Mo.	12/18/24
CAB-114G	Teledyne	Coaxial Cable	N/A	114G	DC-26 GHz	24 Mo.	12/17/24
CAB-295A	Teledyne	Coaxial Cable	N/A	295A	DC-26 GHz	24 Mo.	12/17/24
REC-21	Agilent	Spectrum Analyzer	E7405A	MY45118341	9Hz-26.5 GHz	24 Mo.	04/24/24
REC-44	Agilent	Spectrum Analyzer	E4440A	US40420673	3Hz-26.5GHz	24 Mo.	07/18/24

Note: All calibrated equipment is subject to periodic checks.

Software Company	Test Software Name	Version	Applicable Tests
Radiometrics	RREC11D	07.21.22	RF Radiated Emissions (FCC Part 15 & EN 55032)
Agilent	PSA/ESA-E/L/EMC	2.4.0.42	Bandwidth and screen shots

11.0 TEST SECTIONS

11.1 Radiated RF Emissions

Radiated emission measurements were performed with linearly polarized broadband antennas. The results obtained with these antennas can be correlated with results obtained with a tuned dipole antenna. The radiated emission measurements were performed with a spectrum analyzer. The bandwidth used from 150 kHz to 30 MHz is 9 kHz and the bandwidth from 30 MHz to 1000 MHz is 120 kHz. Above 1 GHz, a 1 MHz bandwidth is used. A 10 dB linearity check is performed prior to start of testing in order to determine if an overload condition exists. Figure 1 herein lists the details of the test equipment used during radiated emissions tests. The EUT was rotated through three orthogonal axis as per 5.10.1 of ANSI C63.10 during the radiated tests.

Final radiated emissions measurements were performed inside of an anechoic chamber at a test distance of 3 meters. The anechoic chamber is designated as Chamber E. This Chamber meets the Site Attenuation requirements of ANSI C63.4 and CISPR 16-1. Chamber E is located at 12 East Devonwood Ave. Romeoville, Illinois EMI test lab.

The entire frequency range from 30 to 25,000 MHz was slowly scanned. Measurements were performed using two antenna polarizations, (vertical and horizontal). The worst case emissions were recorded. All measurements may be performed using either the peak, average or quasi-peak detector functions. If the peak detector data exceeds or is marginally close to the limits, the measurements are repeated using a quasi-peak detector or average function as required by the specification for final determination of compliance. The QP and average detectors have a linear response.

The detected emission levels were maximized by rotating the EUT, adjusting the positions of all cables, and by scanning the measurement antenna from 1 to 4 meters above the ground.



11.1.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and by subtracting the Amplifier Gain from the measured reading. The basic equation is as follows:

$$FS = RA + AF + CF - AG + HPF + PKA$$

Where: FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

PKA = Peak to Average Factor (This is only used for Harmonic average measurements above 1 GHz)

The Peak to average factor is used when average measurements are required. It is calculated by the highest duty cycle in percent over any 100mS transmission. The factor in dB is $20 \cdot \log(1.351 \text{ mS}/100 \text{ mS})$.

Radiated Emissions Field Strength Limits

Frequency Range (MHz)	Test Distance (meters)	Class B Limits	
		uV/m	dB(uV/m)
30 - 88	3	100	40.0
88 - 216	3	150	43.5
216 - 960	3	200	46.0
Above 960	3	500	54.0

The emission limits shown in the above table are based on measurements using a CISPR quasi-peak detector except above 1000 MHz.

11.1.2 Duty Cycle

The Peak to average factor is calculated by the highest duty cycle in percent over any 100mS transmission. The factor in dB is $20 \cdot \log(\text{Duty cycle}/100)$. The transmitter operates for a maximum duration of 1.351 ms in any 100 ms interval for a 10% maximum duty cycle. $20 \log(1.351 \text{ mSec}/100 \text{ mSec}) = -37.4 \text{ dB}$ Peak to average Correction factor.

Since the difference between the peak and the average limits are 20 dB, there is no need to use a correction factor more than 20 dB. Therefore, a 20 dB factor was used.



Agilent 09:18:34 Jun 25, 2025

R T

Duty Cycle

Mkr1 Δ 462.5 μ s

Ref 0 dBm

Atten 10 dB

0.247 dB

Peak

Log

10

dB/

V1 S2

S3 VC

Center 2.48 GHz

Span 0 Hz

Res BW 1 MHz

VBW 3 MHz

Sweep 5 ms (401 pts)

Undefined header

Agilent 09:25:40 Jun 25, 2025

R T

Second Pulse Width

Mkr1 Δ 213 μ s

Ref 0 dBm

Atten 10 dB

1.566 dB

Peak

Log

10

dB/

V1 S2

S3 VC

Center 2.48 GHz

Span 0 Hz

Res BW 1 MHz

VBW 3 MHz

Sweep 5 ms (400 pts)



Agilent

09:06:33 Jun 25, 2025

R T

Duty Cycle

Ref 0 dBm

Atten 10 dB

Peak

Log

10

dB/

V1 S2

S3 VC

Center 2.48 GHz

Res BW 1 MHz

VBW 3 MHz

Span 0 Hz

Sweep 100 ms (401 pts)

Undefined header

There is at most 2 sets of pulses within a 100 mSecond window. The Widest pulses are 0.4625 and 0.213 mS. $(0.4625 + 0.213) \times 2 = 1.351$ mS.

11.1.3 Radiated Emissions Test Results

Test Date	05-29-2025
Test Distance	3 Meters
Specification	FCC Part 15 Subpart C & RSS-210 Section B.10
Abbreviations	Pol = Antenna Polarization; V = Vertical; H = Horizontal; P = peak; Q = QP
Configuration	The EUT is in the transmit mode with the receiver on

This table includes all emissions except Fundamental, Band edge and harmonics emissions.

Freq. MHz	Meter Reading dBuV	Dect.	Ant. Pol.	Ant Factor dB/m	Cbl/amp Factors	Dist Fact dB	EUT dBuV/m	Limit dBuV/m	Margin Under Limit dB	Note
34.9	12.2	P	H	12.4	0.5	0.0	25.1	40.0	14.9	
40.0	8.6	P	H	11.2	0.5	0.0	20.3	40.0	19.7	
49.5	5.5	P	H	9.8	0.6	0.0	15.9	40.0	24.1	
68.7	11.4	P	H	9.4	0.7	0.0	21.5	40.0	18.5	
77.8	5.5	P	H	9.5	0.7	0.0	15.7	40.0	24.3	
92.8	15.2	P	H	10.0	0.8	0.0	26.0	43.5	17.5	
103.2	13.1	P	H	10.6	0.8	0.0	24.5	43.5	19.0	
113.4	11.8	P	H	11.1	0.9	0.0	23.8	43.5	19.7	
120.0	15.6	P	H	11.6	0.9	0.0	28.1	43.5	15.4	
132.6	13.4	P	H	12.2	1.0	0.0	26.6	43.5	16.9	
143.9	14.1	P	H	12.9	1.0	0.0	28.0	43.5	15.5	
155.2	14.1	P	H	13.0	1.0	0.0	28.1	43.5	15.4	
168.0	14.3	P	H	13.3	1.1	0.0	28.7	43.5	14.8	
181.5	20.0	P	H	13.4	1.1	0.0	34.5	43.5	9.0	



Freq. MHz	Meter Reading dBuV	Dect.	Ant. Pol.	Ant Factor dB/m	Cbl/amp Factors	Dist Fact dB	EUT dBuV/m	Limit dBuV/m	Margin Under Limit dB	Note
195.5	18.1	P	H	14.4	1.2	0.0	33.7	43.5	9.8	
216.1	17.7	P	H	14.9	1.3	0.0	33.9	46.0	12.1	
239.9	23.5	P	H	15.0	1.3	0.0	39.8	46.0	6.2	
264.1	20.4	P	H	12.4	1.4	0.0	34.2	46.0	11.8	
288.1	16.1	P	H	13.9	1.4	0.0	31.4	46.0	14.6	
299.5	13.2	P	H	14.8	1.5	0.0	29.5	46.0	16.5	
312.1	18.3	P	H	14.5	1.5	0.0	34.3	46.0	11.7	
336.0	17.2	P	H	14.2	1.6	0.0	33.0	46.0	13.0	
350.9	18.3	P	H	14.4	1.6	0.0	34.3	46.0	11.7	
360.0	21.6	P	H	14.5	1.6	0.0	37.7	46.0	8.3	
373.9	18.2	P	H	14.8	1.7	0.0	34.7	46.0	11.3	
388.7	15.9	P	H	15.1	1.7	0.0	32.7	46.0	13.3	
407.9	16.7	P	H	15.4	1.7	0.0	33.8	46.0	12.2	
430.4	19.8	P	H	16.0	1.8	0.0	37.6	46.0	8.4	
463.9	22.7	P	H	16.7	1.9	0.0	41.3	46.0	4.7	
463.9	17.8	Q	H	16.7	1.9	0.0	36.4	46.0	9.6	
500.2	15.3	P	H	17.7	1.9	0.0	34.9	46.0	11.1	
520.0	14.9	P	H	17.8	2.0	0.0	34.7	46.0	11.3	
575.1	16.6	P	H	18.3	2.1	0.0	37.0	46.0	9.0	
623.6	14.4	P	H	19.3	2.2	0.0	35.9	46.0	10.1	
655.2	9.5	P	H	19.8	2.3	0.0	31.6	46.0	14.4	
688.2	8.1	P	H	21.3	2.3	0.0	31.7	46.0	14.3	
725.7	6.4	P	H	21.1	2.4	0.0	29.9	46.0	16.1	
796.8	5.9	P	H	21.3	2.5	0.0	29.7	46.0	16.3	
838.3	8.3	P	H	22.0	2.6	0.0	32.9	46.0	13.1	
960.0	4.5	P	H	23.5	2.7	0.0	30.7	46.0	15.3	
1081.1	39.2	P	H	24.4	-32.8	0.0	30.8	74.0	43.2	1
1536.5	38.4	P	H	25.3	-32.4	0.0	31.3	74.0	42.7	1
1692.7	38.0	P	H	26.2	-32.2	0.0	32.0	74.0	42.0	1
1748.7	39.4	P	H	26.6	-32.1	0.0	33.9	74.0	40.1	1
1978.0	38.3	P	H	27.3	-31.7	0.0	33.9	74.0	40.1	1
2594.6	37.0	P	H	28.7	-30.9	0.0	34.8	74.0	39.2	1
2752.8	39.0	P	H	29.1	-30.7	0.0	37.4	74.0	36.6	1
2860.9	37.5	P	H	29.4	-30.4	0.0	36.5	74.0	37.5	1
3145.1	35.0	P	H	30.7	-29.7	0.0	36.0	74.0	38.0	1
3318.3	35.6	P	H	31.2	-29.6	0.0	37.2	74.0	36.8	1
3703.7	34.3	P	H	32.1	-29.1	0.0	37.3	74.0	36.7	1
3912.9	34.9	P	H	32.8	-28.6	0.0	39.1	74.0	34.9	1
4348.3	34.2	P	H	32.5	-27.9	0.0	38.8	74.0	35.2	1
4586.6	34.3	P	H	33.1	-27.5	0.0	39.9	74.0	34.1	1
4960.0	37.4	P	H	33.5	-26.5	0.0	44.4	74.0	29.6	1
36.2	18.4	P	V	12.1	0.5	0.0	31.0	40.0	9.0	
41.5	18.5	P	V	10.9	0.5	0.0	29.9	40.0	10.1	
51.2	14.5	P	V	9.6	0.6	0.0	24.7	40.0	15.3	
61.2	8.8	P	V	9.4	0.7	0.0	18.9	40.0	21.1	
72.0	17.1	P	V	9.4	0.7	0.0	27.2	40.0	12.8	
89.7	24.0	P	V	9.8	0.8	0.0	34.6	43.5	8.9	
96.4	15.0	P	V	10.1	0.8	0.0	25.9	43.5	17.6	
105.0	19.4	P	V	10.7	0.9	0.0	31.0	43.5	12.5	
120.0	18.3	P	V	11.6	0.9	0.0	30.8	43.5	12.7	
133.1	18.5	P	V	12.2	1.0	0.0	31.7	43.5	11.8	
154.3	15.8	P	V	13.0	1.0	0.0	29.8	43.5	13.7	
168.0	15.0	P	V	13.3	1.1	0.0	29.4	43.5	14.1	
183.5	17.0	P	V	13.4	1.1	0.0	31.5	43.5	12.0	



Freq. MHz	Meter Reading dBuV	Dect.	Ant. Pol.	Ant Factor dB/m	Cbl/amp Factors	Dist Fact dB	EUT dBuV/m	Limit dBuV/m	Margin Under Limit dB	Note
203.7	19.0	P	V	14.7	1.2	0.0	34.9	43.5	8.6	
216.1	24.4	P	V	14.9	1.3	0.0	40.6	46.0	5.4	
216.1	21.5	Q	V	14.9	1.3	0.0	37.7	46.0	8.3	
240.2	27.3	P	V	15.0	1.3	0.0	43.6	46.0	2.4	
240.2	19.8	Q	V	15.0	1.3	0.0	36.1	46.0	9.9	
264.1	16.3	P	V	12.4	1.4	0.0	30.1	46.0	15.9	
294.4	13.9	P	V	14.3	1.4	0.0	29.6	46.0	16.4	
312.1	13.0	P	V	14.5	1.5	0.0	29.0	46.0	17.0	
360.0	18.9	P	V	14.5	1.6	0.0	35.0	46.0	11.0	
367.3	12.1	P	V	14.6	1.7	0.0	28.4	46.0	17.6	
384.0	12.7	P	V	15.0	1.7	0.0	29.4	46.0	16.6	
407.9	12.4	P	V	15.4	1.7	0.0	29.5	46.0	16.5	
434.9	12.3	P	V	16.1	1.8	0.0	30.2	46.0	15.8	
452.6	16.1	P	V	16.4	1.8	0.0	34.3	46.0	11.7	
466.7	14.9	P	V	16.8	1.9	0.0	33.6	46.0	12.4	
473.8	17.8	P	V	17.1	1.9	0.0	36.8	46.0	9.2	
527.0	15.0	P	V	17.5	2.0	0.0	34.5	46.0	11.5	
557.1	8.0	P	V	18.3	2.0	0.0	28.3	46.0	17.7	
590.1	13.8	P	V	18.6	2.1	0.0	34.5	46.0	11.5	
615.1	11.7	P	V	19.1	2.1	0.0	32.9	46.0	13.1	
639.1	11.9	P	V	19.7	2.2	0.0	33.8	46.0	12.2	
666.7	11.8	P	V	20.5	2.3	0.0	34.6	46.0	11.4	
718.2	4.5	P	V	21.1	2.3	0.0	27.9	46.0	18.1	
797.3	5.3	P	V	21.3	2.5	0.0	29.1	46.0	16.9	
839.8	8.5	P	V	22.1	2.6	0.0	33.2	46.0	12.8	
871.9	2.4	P	V	22.7	2.6	0.0	27.7	46.0	18.3	
954.0	1.7	P	V	23.3	2.7	0.0	27.7	46.0	18.3	
1103.1	38.5	P	V	24.6	-32.7	0.0	30.4	74.0	43.6	1
1389.4	40.6	P	V	25.0	-32.6	0.0	33.0	74.0	41.0	1
1587.6	39.3	P	V	25.4	-32.5	0.0	32.2	74.0	41.8	1
1745.7	37.9	P	V	26.6	-32.1	0.0	32.4	74.0	41.6	1
1816.8	38.7	P	V	27.0	-32.1	0.0	33.6	74.0	40.4	1
1905.9	40.5	P	V	27.1	-31.9	0.0	35.7	74.0	38.3	1
2090.1	36.2	P	V	27.5	-31.6	0.0	32.1	74.0	41.9	1
2302.3	37.4	P	V	28.0	-31.4	0.0	34.0	74.0	40.0	1
2500.5	37.3	P	V	28.4	-31.0	0.0	34.7	74.0	39.3	1
2639.6	37.5	P	V	28.8	-30.8	0.0	35.5	74.0	38.5	1
2917.9	36.6	P	V	29.6	-30.3	0.0	35.9	74.0	38.1	1
3206.2	34.3	P	V	30.9	-29.7	0.0	35.5	74.0	38.5	1
3403.4	34.7	P	V	31.2	-29.6	0.0	36.3	74.0	37.7	1
3530.5	35.2	P	V	31.3	-29.4	0.0	37.1	74.0	36.9	1
3892.9	34.9	P	V	32.8	-28.7	0.0	39.0	74.0	35.0	1
4192.2	33.5	P	V	32.4	-28.3	0.0	37.6	74.0	36.4	1
4680.7	33.8	P	V	33.3	-27.4	0.0	39.7	74.0	34.3	1
4895.9	34.3	P	V	33.5	-26.6	0.0	41.2	74.0	32.8	1

Note 1: The Peak data is under the Average limit, therefore Average measurement not performed.

Judgment: Passed by 6.2 dB; Where there is both peak and QP data, the QP data is the final determination of compliance



Fundamental and Harmonic Emissions FCC 15.249; Three axis

	Tx	Spectrum Analyzer Readings dBuV									EUT	Peak	Ave	Peak	Ave	Margin
hrm	Freq	Peak				Ave				Corr.	Emission	Tot. FS		Limit		Under
#	MHz	Vertical Polarization				Horizontal Polarization				Fact dB/m	Freq MHz	dBuV/m		dBuV/m		Limit dB
		X	Y	Z	Max	X	Y	Z	Max							
1	2402	98.8	100.0	94.9	80.0	96.1	96.5	101.9	81.9	-3.0	2402.0	98.9	78.9	114	94	15.1
BE	2402	48.8	50.0	44.9	30.0	46.1	46.5	51.9	31.9	-3.0	2390.0	48.9	28.9	74	54	25.1
2	2402	50.2	52.1	50.9	32.1	47.3	49.2	51.6	31.6	6.4	4804.0	58.5	38.5	74	54	15.5
3	2402	35.1	36.5	37.4	17.4	35.3	36.6	38.8	18.8	12.0	7206.0	50.8	30.8	74	54	23.2
4	2402	32.7	33.1	33.6	13.6	32.7	32.6	33.9	13.9	17.3	9608.0	51.2	31.2	74	54	22.8
1	2440	95.8	98.9	92.8	78.9	95.8	95.1	99.9	79.9	-2.9	2440.0	97.0	77.0	114	94	17.0
2	2440	51.6	52.7	53.8	33.8	49.6	53.4	55.4	35.4	6.4	4880.0	61.8	41.8	74	54	12.2
3	2440	34.5	35.8	37.4	17.4	35.7	35.8	37.6	17.6	12.0	7320.0	49.6	29.6	74	54	24.4
4	2440	32.7	32.5	33.5	13.5	31.9	33.0	33.6	13.6	17.3	9760.0	50.9	30.9	74	54	23.1
1	2480	93.4	96.0	92.1	76.0	93.0	92.8	100.8	80.8	-2.6	2480.0	98.2	78.2	114	94	15.8
BE	2480	45.3	47.9	44.0	27.9	44.9	44.7	52.7	32.7	-2.6	2483.5	50.1	30.1	74	54	23.9
2	2480	52.0	55.1	54.0	35.1	50.9	52.2	58.6	38.6	7.0	4960.0	65.6	45.6	74	54	8.4
3	2480	35.0	35.8	37.8	17.8	35.4	36.0	39.7	19.7	13.0	7440.0	52.7	32.7	74	54	21.3
4	2480	32.5	31.7	32.3	12.5	31.8	32.2	33.3	13.3	17.8	9920.0	51.1	31.1	74	54	22.9
Column numbers (see below for explanations)																
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17

Column #1. hrm = Harmonic; BE = Band Edge emissions

Column #2. Frequency of Transmitter.

Column #3. Uncorrected readings from the spectrum analyzer with First Axis Rotation.

Column #4. Uncorrected readings from the spectrum analyzer with Second Axis Rotation.

Column #5. Uncorrected readings from the spectrum analyzer with Third Axis Rotation.

Column #6. Average Reading based on peak reading reduced by the Duty cycle correction

Column #7. Uncorrected readings from the spectrum analyzer with First Axis Rotation.

Column #8. Uncorrected readings from the spectrum analyzer with Second Axis Rotation.

Column #9. Uncorrected readings from the spectrum analyzer with Third Axis Rotation.

Column #10. Average Reading based on peak reading reduced by the Duty cycle correction

Column #11. Corr. Factors = Cable Loss – Preamp Gain + Antenna Factor

Column #12. Frequency of Tested Emission

Column #13. Highest peak field strength at listed frequency.

Column #14. Highest Average field strength at listed frequency.

Column #15. Peak Limit.

Column #16. Average Limit.

Column #17. The margin (last column) is the worst-case margin under the peak or average limits for that row.


Overall Judgment: Passed by at least 9.9 dB

No other Emissions were detected from 30 to 25,000 MHz within 10 dB of the limits.



Figure 1. Drawings of Radiated Emissions Setup

Chamber E, anechoic





Notes:

- Not to Scale
- Antenna height varied 1-4 meters
- Distance from antenna to tested system is 3 meters
- AC cords not shown. They are connected to AC outlet with low-pass filter on turntable

Frequency Range	Receive Antenna	Pre-Amplifier	Spectrum Analyzer	High Pass Filter
0.01 to 30 MHz	ANT-53	None	REC-21	None
30 to 200 MHz	ANT-80	AMP-22	REC-21	None*
200 to 1000 MHz	ANT-68	AMP-22	REC-21	None*
1 to 10 GHz	ANT-66	AMP-05	REC-21	HPF-06/07
10 to 18 GHz	ANT-66	AMP-20	REC-21	None*
18 to 25 GHz	ANT-48	AMP-59	REC-21	None*

* A high pass filter was not needed since the fundamental frequency was outside of the amplifiers pass band.

**Radiated Emissions Test Setup for Frequencies from 30MHz to 1000MHz (Side View)****Radiated Emissions Test Setup for Frequencies over 1000MHz (Side View)****11.2 Occupied Bandwidth Data**



The occupied bandwidth of the RF output was measured using a spectrum analyzer. The bandwidth was measured using the peak detector function. The spectrum analyzer was set to the MAX HOLD mode to record the worst case of the modulation. The marker-to-peak function was set to the peak of the emission. Then the marker-delta function was used to measure 20 dB down one side of the emission. The marker-delta function was reset and then moved to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the bandwidth of the emission. The plots of the occupied bandwidth for the EUT are supplied on the following pages.


The 20 dB OBW is within the allowed 2400 to 2483.5 MHz authorized band.

Channel	20 dB OBW MHz	99% EBW MHz
2402	1.090	1.0213
2440	1.090	1.0356
2480	1.164	1.0343



Figure 2. Occupied Bandwidth Plot





11.3 Unintentional Emissions (Receive Mode)

Manufacturer	Consumer Safety Technology	Specification	FCC Part 15.209 & RSS-GEN
Model	KEEPRDRIVE1	Test Date	5-29 & 5-30-25
Serial Number	1BB0AC0	Test Distance	3 Meters
Abbreviations	Pol = Antenna Polarization; V = Vertical; H = Horizontal; P = peak; Q = QP		
Notes	Corr. Factors = Cable Loss – Preamp Gain		
Configuration	Receive mode		

Freq. MHz	Meter Reading dBuV	Decd.	Ant. Pol.	Ant Factor dB/m	Cbl/amp Factors dB	Dist Fact dB	EUT dBuV/m	Limit dBuV/m	Margin Under Limit dB	Note
36.4	12.2	P	H	12.0	0.5	0.0	24.7	40.0	15.3	
41.5	10.8	P	H	10.9	0.5	0.0	22.2	40.0	17.8	
57.7	10.6	P	H	9.4	0.6	0.0	20.6	40.0	19.4	
65.8	18.3	P	H	9.4	0.7	0.0	28.4	40.0	11.6	
81.8	16.5	P	H	9.6	0.8	0.0	26.9	40.0	13.1	
97.3	17.1	P	H	10.1	0.8	0.0	28.0	43.5	15.5	
113.0	14.4	P	H	11.1	0.9	0.0	26.4	43.5	17.1	
120.0	10.7	P	H	11.6	0.9	0.0	23.2	43.5	20.3	
143.9	16.5	P	H	12.9	1.0	0.0	30.4	43.5	13.1	
155.6	16.3	P	H	13.0	1.0	0.0	30.3	43.5	13.2	
168.0	13.3	P	H	13.3	1.1	0.0	27.7	43.5	15.8	
191.9	15.4	P	H	14.2	1.2	0.0	30.8	43.5	12.7	
201.2	18.4	P	H	14.6	1.2	0.0	34.2	43.5	9.3	
216.1	19.1	P	H	14.9	1.3	0.0	35.3	46.0	10.7	
228.0	8.7	P	H	14.9	1.3	0.0	24.9	46.0	21.1	



Freq. MHz	Meter Reading dBuV	Dect.	Ant. Pol.	Ant Factor dB/m	Cbl/amp Factors dB	Dist Fact dB	EUT dBuV/m	Limit dBuV/m	Margin Under Limit dB	Note
239.9	14.0	P	H	15.0	1.3	0.0	30.3	46.0	15.7	
246.8	8.9	P	H	15.2	1.3	0.0	25.4	46.0	20.6	
264.1	22.8	P	H	12.4	1.4	0.0	36.6	46.0	9.4	
288.1	16.6	P	H	13.9	1.4	0.0	31.9	46.0	14.1	
312.1	19.8	P	H	14.5	1.5	0.0	35.8	46.0	10.2	
336.0	19.0	P	H	14.2	1.6	0.0	34.8	46.0	11.2	
360.0	22.8	P	H	14.5	1.6	0.0	38.9	46.0	7.1	
384.0	17.2	P	H	15.0	1.7	0.0	33.9	46.0	12.1	
407.9	14.4	P	H	15.4	1.7	0.0	31.5	46.0	14.5	
431.9	15.8	P	H	16.0	1.8	0.0	33.6	46.0	12.4	
456.1	10.1	P	H	16.5	1.8	0.0	28.4	46.0	17.6	
480.1	11.8	P	H	17.2	1.9	0.0	30.9	46.0	15.1	
504.0	7.8	P	H	17.8	1.9	0.0	27.5	46.0	18.5	
552.1	4.7	P	H	18.1	2.0	0.0	24.8	46.0	21.2	
576.1	13.4	P	H	18.4	2.1	0.0	33.9	46.0	12.1	
672.2	5.4	P	H	20.9	2.3	0.0	28.6	46.0	17.4	
720.2	6.2	P	H	21.1	2.3	0.0	29.6	46.0	16.4	
791.8	3.8	P	H	21.3	2.5	0.0	27.6	46.0	18.4	
960.0	1.7	P	H	23.5	2.7	0.0	27.9	46.0	18.1	
1096.1	41.0	P	H	24.5	-32.7	0.0	32.8	74.0	41.2	1
1194.2	41.5	P	H	24.9	-32.7	0.0	33.7	74.0	40.3	1
1250.3	42.6	P	H	24.9	-32.7	0.0	34.8	74.0	39.2	1
1614.6	39.9	P	H	25.6	-32.4	0.0	33.1	74.0	40.9	1
1772.8	38.3	P	H	26.8	-32.1	0.0	33.0	74.0	41.0	1
2060.1	39.0	P	H	27.5	-31.7	0.0	34.8	74.0	39.2	1
2380.4	37.7	P	H	28.2	-31.2	0.0	34.7	74.0	39.3	1
2632.6	37.1	P	H	28.8	-30.8	0.0	35.1	74.0	38.9	1
3209.2	35.5	P	H	30.9	-29.7	0.0	36.7	74.0	37.3	1
3678.7	34.9	P	H	31.9	-29.2	0.0	37.6	74.0	36.4	1
3895.9	34.6	P	H	32.8	-28.7	0.0	38.7	74.0	35.3	1
4282.3	34.3	P	H	32.4	-28.1	0.0	38.6	74.0	35.4	1
4544.5	33.6	P	H	33.0	-27.6	0.0	39.0	74.0	35.0	1
4897.9	33.7	P	H	33.5	-26.6	0.0	40.6	74.0	33.4	1
36.4	14.9	P	V	12.0	0.5	0.0	27.4	40.0	12.6	
44.2	16.1	P	V	10.3	0.5	0.0	26.9	40.0	13.1	
53.5	9.9	P	V	9.4	0.6	0.0	19.9	40.0	20.1	
57.0	16.3	P	V	9.4	0.6	0.0	26.3	40.0	13.7	
61.4	24.8	P	V	9.4	0.7	0.0	34.9	40.0	5.1	
61.4	11.5	Q	V	9.4	0.7	0.0	21.6	40.0	18.4	
66.5	21.3	P	V	9.4	0.7	0.0	31.4	40.0	8.6	
72.0	16.2	P	V	9.4	0.7	0.0	26.3	40.0	13.7	
81.1	23.3	P	V	9.5	0.7	0.0	33.5	40.0	6.5	
88.8	20.5	P	V	9.8	0.8	0.0	31.1	43.5	12.4	
97.7	19.7	P	V	10.2	0.8	0.0	30.7	43.5	12.8	
112.5	20.2	P	V	11.1	0.9	0.0	32.2	43.5	11.3	
117.2	21.4	P	V	11.4	0.9	0.0	33.7	43.5	9.8	
122.0	9.9	P	V	11.7	0.9	0.0	22.5	43.5	21.0	
132.0	11.1	P	V	12.2	1.0	0.0	24.3	43.5	19.2	
143.9	10.7	P	V	12.9	1.0	0.0	24.6	43.5	18.9	
154.6	16.9	P	V	13.0	1.0	0.0	30.9	43.5	12.6	
168.0	16.5	P	V	13.3	1.1	0.0	30.9	43.5	12.6	
180.2	11.8	P	V	13.4	1.1	0.0	26.3	43.5	17.2	
191.9	15.0	P	V	14.2	1.2	0.0	30.4	43.5	13.1	
200.3	14.7	P	V	14.6	1.2	0.0	30.5	43.5	13.0	




Freq. MHz	Meter Reading dBuV	Dect.	Ant. Pol.	Ant Factor dB/m	Cbl/amp Factors dB	Dist Fact dB	EUT dBuV/m	Limit dBuV/m	Margin Under Limit dB	Note
216.1	22.2	P	V	14.9	1.3	0.0	38.4	46.0	7.6	
228.0	8.7	P	V	14.9	1.3	0.0	24.9	46.0	21.1	
239.9	14.7	P	V	15.0	1.3	0.0	31.0	46.0	15.0	
263.9	17.7	P	V	12.4	1.4	0.0	31.5	46.0	14.5	
288.1	8.3	P	V	13.9	1.4	0.0	23.6	46.0	22.4	
312.1	12.2	P	V	14.5	1.5	0.0	28.2	46.0	17.8	
336.0	13.5	P	V	14.2	1.6	0.0	29.3	46.0	16.7	
360.0	16.9	P	V	14.5	1.6	0.0	33.0	46.0	13.0	
384.0	12.8	P	V	15.0	1.7	0.0	29.5	46.0	16.5	
407.9	9.1	P	V	15.4	1.7	0.0	26.2	46.0	19.8	
422.5	11.9	P	V	15.8	1.8	0.0	29.5	46.0	16.5	
431.9	10.7	P	V	16.0	1.8	0.0	28.5	46.0	17.5	
456.1	9.0	P	V	16.5	1.8	0.0	27.3	46.0	18.7	
461.9	14.8	P	V	16.6	1.9	0.0	33.3	46.0	12.7	
480.1	12.2	P	V	17.2	1.9	0.0	31.3	46.0	14.7	
600.1	7.7	P	V	18.8	2.9	0.0	29.4	47.0	17.6	
679.2	7.3	P	V	21.3	3.0	0.0	31.6	47.0	15.4	
770.3	8.6	P	V	21.0	3.3	0.0	32.9	47.0	14.1	
845.8	8.0	P	V	22.3	3.5	0.0	33.8	47.0	13.2	
871.9	8.1	P	V	22.7	3.5	0.0	34.3	47.0	12.7	
951.0	8.5	P	V	23.3	3.7	0.0	35.5	47.0	11.5	
1104.1	38.8	P	V	24.6	-32.7	0.0	30.7	74.0	43.3	1
1317.3	39.0	P	V	25.0	-32.6	0.0	31.4	74.0	42.6	1
1445.4	40.8	P	V	25.1	-32.5	0.0	33.4	74.0	40.6	1
1489.5	43.2	P	V	25.2	-32.6	0.0	35.8	74.0	38.2	1
1659.7	40.8	P	V	25.9	-32.2	0.0	34.5	74.0	39.5	1
1896.9	39.1	P	V	27.1	-31.9	0.0	34.3	74.0	39.7	1
1989.0	39.8	P	V	27.3	-31.6	0.0	35.5	74.0	38.5	1
2174.2	41.2	P	V	27.7	-31.5	0.0	37.4	74.0	36.6	1
2340.3	41.9	P	V	28.1	-31.5	0.0	38.5	74.0	35.5	1
2588.6	37.8	P	V	28.7	-30.9	0.0	35.6	74.0	38.4	1
2677.7	37.4	P	V	28.9	-30.8	0.0	35.5	74.0	38.5	1
3150.2	35.2	P	V	30.7	-29.7	0.0	36.2	74.0	37.8	1
3363.4	35.8	P	V	31.2	-29.6	0.0	37.4	74.0	36.6	1
3515.5	35.1	P	V	31.3	-29.4	0.0	37.0	74.0	37.0	1
3743.7	34.9	P	V	32.3	-28.9	0.0	38.3	74.0	35.7	1
3915.9	34.3	P	V	32.8	-28.6	0.0	38.5	74.0	35.5	1
4137.1	34.9	P	V	32.4	-28.4	0.0	38.9	74.0	35.1	1
4393.4	34.5	P	V	32.6	-27.8	0.0	39.3	74.0	34.7	1
4479.5	34.3	P	V	32.9	-27.6	0.0	39.6	74.0	34.4	1
4800.8	35.0	P	V	33.4	-27.0	0.0	41.4	74.0	32.6	1
4931.9	33.6	P	V	33.5	-26.5	0.0	40.6	74.0	33.4	1

Note 1: The Peak data is under the Average limit, therefore Average measurement not performed.

Judgment: Passed by 7.1 dB; Where there is both peak and QP data, the QP data is the final determination of compliance



Radiated emissions in a graphical format. The following chart is the same data as the previous table. The peak limit is not shown, since the peak readings meet the lower average limit.



11.3.1 Measurement Instrumentation Uncertainty

Measurement	Uncertainty
Radiated Emissions, E-field, 3 meters, 30 to 200 MHz	4.8 dB
Radiated Emissions, E-field, 3 meters, 200 to 1000 MHz	4.6 dB
Radiated Emissions, E-field, 3 meters, 1 to 6 GHz	5.0 dB
Radiated Emissions, E-field, 3 meters, 6 to 18 GHz	5.5 dB
Radiated Emissions, E-field, 3 meters, 18 to 26 GHz	5.9 dB
99% Occupied Bandwidth using REC-44	1% of frequency span
Temperature THM-02	0.6 Deg C

The uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of $k=2$ in accordance with CISPR 16-4-2.

12.0 REVISION HISTORY

Document RP-10157 Revisions:			
Rev.	Affected Sections	Description	Rationale