

FCC ID: 2BEFM-WTP6000

Maximum Permissible Exposure (MPE)

According to KDB 447498 D01 General RF Exposure Guidance v06 & FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

According to 2.1091

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

Operation Frequency: 916MHz

Antenna Type: Spring Antenna

Antenna gain: -1dBi,

R=20cm

$mW=10^{(dBm/10)}$

Transmit power

Frequency (MHz)	ERP power (dBuV/m)	ERP power (dBm)	ERP power (mW)
916	82.75	-12.51	0.056

$EIRP=E-104.8+20\log(D)$

Maximum Permissible Exposure:

Channel Freq. (MHz)	modulation	ERP power (dBm)	ERP power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
916	FSK	-12.51	0.056	-12±1	-11	0.000013	0.61

Conclusion:

For the max result : $0.000013 \leq 0.61$ for Max Power Density, compliance RF exposure.

Signature:

Date: 2026-06-22



NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China