

FCC ID: 2BEFM-WTP6000

Portable device

According to §2.1091 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

916MHz

Transmit power:

Frequency (MHz)	ERP power (dBuV/m)	ERP power (dBm)
916	82.75	-12.51

$$\text{EIRP} = \text{E} - 104.8 + 20 \log(D)$$

Channel Freq. (GHz)	ERP (dBm)	ERP (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
0.916	-12.51	0.0561	-12±1	-11	0.079	<5	0.01520	3.00	YES

Conclusion:

For the max result : $0.0152 \leq 3.0$ for 1g SAR, SAR is not required.



Signature:

Date: 2026-07-08

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China